



RF Exposure Report

Report No.: SA140901E08B

FCC ID: PY314200280

Test Model: EX7000

Received Date: Sep. 01, 2014

Test Date: May 15, 2015

Issued Date: June 05, 2015

Applicant: NETGEAR, Inc.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	6
4 Calculation Result of Maximum Conducted Power	7



A D T

Release Control Record

Issue No.	Description	Date Issued
SA140901E08B	Original release.	June 05, 2015



1 Certificate of Conformity

Product: AC1900 WiFi Range Extender

Brand: NETGEAR

Test Model: EX7000

Sample Status: ENGINEERING SAMPLE

Applicant: NETGEAR, Inc.

Test Date: May 15, 2015


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** June 05, 2015
Elsie Hsu / Specialist

Approved by : , **Date:** June 05, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 27cm away from the body of the user.

So, this device is classified as **Mobile Device**.

3 Antenna Gain

1. The antennas provided to the EUT, please refer to the following table:

Antenna No.	Brand	Model	Antenna Gain(dBi)	Frequency range (MHz ~ MHz)	Antenna Type	Connector Type	Cable Length(External only)
Antenna L	Netgear	NA	2	2412~2477 5150~5250 5250~5350 5470~5725 5725~5850	Dipole	Re-SMA	85+5/-0 mm
Antenna M	Netgear	NA	2	2412~2477 5150~5250 5250~5350 5470~5725 5725~5850	Dipole	Re-SMA	85+5/-0 mm
Antenna R	Netgear	NA	2	2412~2477 5150~5250 5250~5350 5470~5725 5725~5850	Dipole	Re-SMA	85+5/-0 mm

4 Calculation Result of Maximum Conducted Power

For 15.247 and 15.407 (U-NII-1 band & U-NII 3 band) data was copied from the original test report (Report No.: SA140901E08)

For 15.247(2.4GHz):

CDD Mode:

802.11b:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	970.44	6.77	27	0.50354	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11g:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	836.767	6.77	27	0.43418	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

VHT20:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	911.213	6.77	27	0.47280	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

VHT40:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2422 ~ 2452	151.299	6.77	27	0.07851	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

Beamforming Mode:

VHT20:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	827.261	6.77	27	0.42924	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

VHT40:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2422 ~ 2452	151.299	6.77	27	0.07851	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

For 15.247(5GHz):

CDD Mode:

802.11a:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5745 ~ 5825	748.103	6.77	27	0.38817	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT20)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5745 ~ 5825	771.017	6.77	27	0.40006	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5755 ~ 5795	858.132	6.77	27	0.44526	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT80)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5755	377.16	6.77	27	0.19570	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

Beamforming Mode:

802.11ac (VHT20)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5745 ~ 5825	771.017	6.77	27	0.40006	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5755 ~ 5795	819.794	6.77	27	0.42537	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT80)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5755	377.16	6.77	27	0.19570	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

For 15.407(5GHz):

CDD Mode:

802.11a:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 ~ 5240	432.426	6.77	27	0.22437	1
5260 ~ 5320	207.32	6.77	27	0.10757	1
5500 ~ 5700	209.369	6.77	27	0.10864	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT20)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 ~ 5240	432.772	6.77	27	0.22455	1
5260 ~ 5320	204.639	6.77	27	0.10618	1
5500 ~ 5700	209.113	6.77	27	0.10850	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5190 ~ 5230	208.518	6.77	27	0.10819	1
5270 ~ 5310	244.829	6.77	27	0.12704	1
5510 ~ 5670	243.878	6.77	27	0.12654	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT80)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5210	90.311	6.77	27	0.04686	1
5290	153.597	6.77	27	0.07970	1
5530 ~ 5610	244.004	6.77	27	0.12661	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

Beamforming Mode:

802.11ac (VHT20)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 ~ 5240	432.772	6.77	27	0.22455	1
5260 ~ 5320	204.639	6.77	27	0.10618	1
5500 ~ 5700	209.113	6.77	27	0.10850	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5190 ~ 5230	208.518	6.77	27	0.10819	1
5270 ~ 5310	205.19	6.77	27	0.10647	1
5510 ~ 5670	206.429	6.77	27	0.10711	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

802.11ac (VHT80)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5210	90.311	6.77	27	0.04686	1
5290	153.597	6.77	27	0.07970	1
5530 ~ 5610	206.913	6.77	27	0.10736	1

Directional gain = 2dBi + 10log(3) = 6.77dBi

CONCLUSION:

Both of the 2.4GHz and 5GHz WLAN can transmit simultaneously, the formula of calculated the MPE is:

CPD₁ / LPD₁ + CPD₂ / LPD₂ +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is 0.50354 / 1 + 0.44526 / 1 = 0.949, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---