			1			
R-NZ	. ( E 🕱 🐵	REV	DESCRIPTION OF REVISION	ENG APPD	DATE	
R-NZ	EXTENDER LOGIN	01	INITIAL ARTWORK	MHUMPHREY	23FEB16	
http://www.mywifiext.net INDOOR USE ONLY		02	CHANGE CE MARK	M HUMPHREY	31MAR16	
	Made in China	03	ADD BARS	M HUMPHREY	01APR16	
	7	04	PASSWORD TO SECURITY PIN	M HUMPHREY	05APR16	
		05	LABEL LOCATIONS MARKED	M HUMPHREY	07APR16	
		06	FD CORRECTION TITLE CHANGE	M HUMPHREY	12APR16	
SECURITY PIN		07	LIGATURE ADJUSTMENT TO EXTENDER LOGIN	M HUMPHREY	18APR16	
SERIAL						
	AR					
	2.4GHz Link Rate LED					
111 2.45% 111 2004	2.4GHz Link Rate LED					
	Device to Extender LED					
∠ •€	LAN LEDS USB LED		NOTE:			
	200 WiFi Range Extender		1. REFER TO NETGEAR SPEC. DOC-00093 FOR COLOR TOLERANCES.			
AC 1.	Model: EX6200v2		2. INK COLOR IS SHOWN TO THE RIGHT. 3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT.			
			4. MAC & SERIAL NUMBERS TO BE PRINTED B			
			5. See NTGR DOC-00112 for SN standard.			
		_	6. NTGR SN and MAC address barcode to be e and include printed characters below barco			
MAC1		9	7. INSURE COUNTRY OF ORIGIN IS CORRECT.			
			A. IF COUNTRY OF ORIGIN IS PRE-PRINTED APPROPRIATE COUNTRY OF ORIGIN LA COUNTRY OF ORIGIN ON LABEL.			
MAC2			B. IF COUNTRY OF ORIGIN IS POST-PRINTE PRINTER (OR EQUIVALENT), OMIT TEX			
	FCC IC: PY316100335 IC: 4054A-16100335					
subject to the following two conditions: (1	FCC Rules and Canada ICES-003. Operation is ) this device may not cause harmful interference, rferencerceived, including interference that CAN ICES-3 (A)/NMB-3(A)		8. THE BACK OF PRODUCT LABEL SHOULD BE BLACK WITHOUT THE OF THE TRACE OF FRONT ARTWORK.			
			9. ALIGN THE PRINTED LABELS AT THE CORN PLACE THE LABELS.	ER OF THE MARKS WHEN		
			Black			
NETGE	AR, INC. 272-12644-01		Pantone 877C			
	AUTHOR: TIT	LE:				
	M HUMPHREY		AW, PLBL, EX6200, V2		NETGEAR	

THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.

SHEET:

1 of 1

REV: 07

P/N:

AW-13475-01