## NOTF:

- 1. REFER TO NETGEAR SPEC. DOC-00093 FOR COLOR TOLERANCES.
- 2. INK COLOR IS SHOWN TO THE RIGHT.
- 3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT.
- 4. MAC & SERIAL NUMBERS TO BE PRINTED BY THE ODM.
- 5. See NTGR DOC-00112 for SN standard.
- 6. NTGR SERIAL, MAC(3), AND WPS PIN TO BE ENCODED QR (2D) BARCODE IN THE FOLLOWING FORMAT. TEXT OUTSIDE BRACKETS ARE STATIC.

ELEMENT: SERIAL:[SERIAL NUMBER];MAC:[MAC ADDRESS];;

EXAMPLE: SERIAL:NETGEAR13;WPA2:fgjkllopqweerti345;;

- 7. SSID AND PASSWORD FONT: ARIAL 8PT
- 8. INSURE COUNTRY OF ORIGIN IS CORRECT.
  - A. IF COUNTRY OF ORIGIN IS PRE-PRINTED, UNHIDE THE APPROPRIATE COUNTRY OF ORIGIN LAYER AND INCLUDE COUNTRY OF ORIGIN ON LABEL.
  - B. IF COUNTRY OF ORIGIN IS POST-PRINTED USING A THERMAL PRINTER (OR EQUIVALENT), OMIT TEXT FROM ARTWORK (USE LAYERS).

REV	DESCRIPTION OF REVISION	ENG APPD	DATE
01	INITIAL DOCUMENT CREATION	M HUMPHREY 19JAN17	
02	NEW FD,TITLE CHANGE,QR CODE	M HUMPHREY	24JAN17
03	272- NOTE ADDED	M HUMPHREY	06FEB17
04	FCC ID ADDED	M HUMPHREY	08MAR17



White
Black

Reference 272-12852-01

AUTHOR: M HUMPHREY	AW,PLBL,EX8000,NAS,V1	NETGEAR	
SHEET:	THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.	P/N: AW-13756-01	REV: 04

