

## FCC Test Report

**Report No.:** RF190430E07-1 R1

**FCC ID:** PY319200443

**Test Model:** MC327

**Series Model:** MC327BL, MC327WL, MC327HW, MC327LW

**Received Date:** Apr. 30, 2019

**Test Date:** May 10 to Jun. 18, 2019

**Issued Date:** Jul. 17, 2019

**Applicant:** NETGEAR, Inc.

**Address:** 350 East Plumeria Drive, San Jose, CA 95134, USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location (1):** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**FCC Registration /  
Designation Number:** 198487 / TW2021

**Test Location (2):** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

**FCC Registration /  
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|   |           |
|---|-----------|
| <b>Release Control Record</b> .....                             | <b>4</b>  |
| <b>1 Certificate of Conformity</b> .....                        | <b>5</b>  |
| <b>2 Summary of Test Results</b> .....                          | <b>6</b>  |
| 2.1 Measurement Uncertainty.....                                | 6         |
| 2.2 Modification Record.....                                    | 6         |
| <b>3 General Information</b> .....                              | <b>7</b>  |
| 3.1 General Description of EUT.....                             | 7         |
| 3.2 Description of Test Modes.....                              | 9         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....    | 10        |
| 3.3 Duty Cycle of Test Signal.....                              | 12        |
| 3.4 Description of Support Units.....                           | 13        |
| 3.4.1 Configuration of System under Test.....                   | 13        |
| 3.5 General Description of Applied Standard.....                | 14        |
| <b>4 Test Types and Results</b> .....                           | <b>15</b> |
| 4.1 Radiated Emission and Bandedge Measurement.....             | 15        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement..... | 15        |
| 4.1.2 Test Instruments.....                                     | 16        |
| 4.1.3 Test Procedure.....                                       | 17        |
| 4.1.4 Deviation from Test Standard.....                         | 17        |
| 4.1.5 Test Setup.....   | 18        |
| 4.1.6 EUT Operating Condition.....                              | 19        |
| 4.1.7 Test Results.....   | 20        |
| 4.2 Conducted Emission Measurement.....                         | 40        |
| 4.2.1 Limits of Conducted Emission Measurement.....             | 40        |
| 4.2.2 Test Instruments.....                                     | 40        |
| 4.2.3 Test Procedure.....                                       | 41        |
| 4.2.4 Deviation from Test Standard.....                         | 41        |
| 4.2.5 Test Setup.....   | 41        |
| 4.2.6 EUT Operating Condition.....                              | 41        |
| 4.2.7 Test Results.....   | 42        |
| 4.3 Transmit Power Measurement.....                             | 44        |
| 4.3.1 Limits of Transmit Power Measurement.....                 | 44        |
| 4.3.2 Test Setup.....   | 44        |
| 4.3.3 Test Instruments.....                                     | 44        |
| 4.3.4 Test Procedure.....                                       | 45        |
| 4.3.5 Deviation from Test Standard.....                         | 45        |
| 4.3.6 EUT Operating Condition.....                              | 45        |
| 4.3.7 Test Result.....  | 46        |
| 4.4 Occupied Bandwidth Measurement.....                         | 47        |
| 4.4.1 Test Setup.....   | 47        |
| 4.4.2 Test Instruments.....                                     | 47        |
| 4.4.3 Test Procedure.....                                       | 47        |
| 4.4.4 Test Results.....   | 48        |
| 4.5 Peak Power Spectral Density Measurement.....                | 50        |
| 4.5.1 Limits of Peak Power Spectral Density Measurement.....    | 50        |
| 4.5.2 Test Setup.....   | 50        |
| 4.5.3 Test Instruments.....                                     | 50        |
| 4.5.4 Test Procedure.....                                       | 50        |
| 4.5.5 Deviation from Test Standard.....                         | 50        |
| 4.5.6 EUT Operating Condition.....                              | 50        |
| 4.5.7 Test Results.....   | 51        |
| 4.6 Frequency Stability Measurement.....                        | 55        |

|          |  |           |
|----------|--|-----------|
| 4.6.1    | Limits of Frequency Stability Measurement .....  | 55        |
| 4.6.2    | Test Setup.....  | 55        |
| 4.6.3    | Test Instruments .....   | 55        |
| 4.6.4    | Test Procedure .....   | 55        |
| 4.6.5    | Deviation from Test Standard .....   | 55        |
| 4.6.6    | EUT Operating Condition .....  | 55        |
| 4.6.7    | Test Results .....   | 56        |
| 4.7      | 6dB Bandwidth Measurement.....   | 57        |
| 4.7.1    | Limits of 6dB Bandwidth Measurement.....   | 57        |
| 4.7.2    | Test Setup.....  | 57        |
| 4.7.3    | Test Instruments .....   | 57        |
| 4.7.4    | Test Procedure .....   | 57        |
| 4.7.5    | Deviation from Test Standard .....   | 57        |
| 4.7.6    | EUT Operating Condition .....  | 57        |
| 4.7.7    | Test Results .....   | 58        |
| <b>5</b> | <b>Pictures of Test Arrangements.....</b>  | <b>60</b> |
|          | <b>Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band).....</b> | <b>61</b> |
|          | <b>Appendix – Information of the Testing Laboratories .....</b>                          | <b>64</b> |

### Release Control Record

| Issue No.        | Description                  | Date Issued   |
|------------------|------------------------------|---------------|
| RF190430E07-1    | Original release.            | Jun. 20, 2019 |
| RF190430E07-1 R1 | Addition of Model No. MC327. | Jul. 17, 2019 |

## 1 Certificate of Conformity

**Product:** Meural Canvas

**Brand:** NETGEAR

**Test Model:** MC327

**Series Model:** MC327BL, MC327WL, MC327HW, MC327LW

**Sample Status:** Engineering sample

**Applicant:** NETGEAR, Inc.

**Test Date:** May 10 to Jun. 18, 2019

**Standard:** 47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Annie Chang, **Date:** Jul. 17, 2019  
Annie Chang / Senior Specialist

**Approved by :** Rex Lai, **Date:** Jul. 17, 2019  
Rex Lai / Associate Technical Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart E (Section 15.407) |   |        |  |
|--|---|--------|--|
| FCC Clause                                     | Test Item                                   | Result | Remarks  |
| 15.407(b)(6)                                   | AC Power Conducted Emissions                | Pass   | Meet the requirement of limit. Minimum passing margin is -11.12dB at 0.16172MHz. |
| 15.407(b)(1/2/3/4(i/ii)/6)                     | Radiated Emissions & Band Edge Measurement* | Pass   | Meet the requirement of limit. Minimum passing margin is -0.45dB at 5150.00MHz.  |
| 15.407(a)(1/2/3)                               | Max Average Transmit Power                  | Pass   | Meet the requirement of limit.   |
| ---  | Occupied Bandwidth Measurement              | -      | Reference only.  |
| 15.407(a)(1/2/3)                               | Peak Power Spectral Density                 | Pass   | Meet the requirement of limit.   |
| 15.407(e)                                      | 6dB bandwidth                               | Pass   | Meet the requirement of limit. (U-NII-3 Band only)                               |
| 15.407(g)                                      | Frequency Stability                         | Pass   | Meet the requirement of limit.   |
| 15.203   | Antenna Requirement                         | Pass   | Antenna connector is I-PEX not a standard connector.                             |

\*For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency      | Expanded Uncertainty (k=2) ( $\pm$ ) |
|------------------------------------|----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 1.8 dB                               |
| Radiated Emissions up to 1 GHz     | 9kHz ~ 30MHz   | 2.38 dB                              |
|                                    | 30MHz ~ 1GHz   | 5.43 dB                              |
| Radiated Emissions above 1 GHz     | Above 1GHz     | 5.42 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |  |
|-----------------------|--|
| Product               | Meural Canvas  |
| Brand                 | NETGEAR  |
| Test Model            | MC327  |
| Series Model          | MC327BL, MC327WL, MC327HW, MC327LW   |
| Model Difference      | Refer to note as below   |
| Status of EUT         | Engineering sample   |
| Power Supply Rating   | 12Vdc from Adapter   |
| Modulation Type       | 64QAM, 16QAM, QPSK, BPSK for OFDM<br>256QAM for OFDM in 11ac mode only.  |
| Modulation Technology | OFDM   |
| Transfer Rate         | 802.11a: up to 54Mbps<br>802.11n: up to 150Mbps<br>802.11ac: up to 433.3Mbps   |
| Operating Frequency   | 5180 ~ 5240MHz, 5745 ~ 5825MHz   |
| Number of Channel     | <b>5180 ~ 5240MHz</b><br>4 for 802.11a, 802.11n (20MHz), 802.11ac (20MHz)<br>2 for 802.11n (40MHz), 802.11ac (40MHz)<br>1 for 802.11ac (80MHz)<br><b>5745 ~ 5825MHz</b><br>5 for 802.11a, 802.11n (20MHz) 802.11ac (20MHz)<br>2 for 802.11n (40MHz) 802.11ac (40MHz)<br>1 for 802.11ac (80MHz) |
| Output Power          | <b>5180 ~ 5240MHz:</b> 240.991mW<br><b>5745 ~ 5825MHz:</b> 230.144mW   |
| Antenna Type          | <b>5180 ~ 5240MHz:</b> Dipole antenna with 3.77dBi gain<br><b>5745 ~ 5825MHz:</b> Dipole antenna with 3.81dBi gain   |
| Antenna Connector     | I-PEX  |
| Accessory Device      | Adapter  |
| Data Cable Supplied   | N/A  |

Note:

1. All models are listed as below. Model: MC327 is the representative for final test.

| Brand   | Test Model | Series Model | Exterior color differences       |
|---------|------------|--------------|----------------------------------|
| NETGEAR | MC327      | MC327BL      | BL for black                     |
|         |            | MC327WL      | WL for white                     |
|         |            | MC327HW      | HW for hardwood color or walnut  |
|         |            | MC327LW      | LW for light wood color or birch |

2. The EUT provides 1 completed transmitter and 1 receiver.

| Modulation Mode  | TX FUNCTION |
|------------------|-------------|
| 802.11a          | 1TX         |
| 802.11n (20MHz)  | 1TX         |
| 802.11n (40MHz)  | 1TX         |
| 802.11ac (20MHz) | 1TX         |
| 802.11ac (40MHz) | 1TX         |
| 802.11ac (80MHz) | 1TX         |

\* The modulation and bandwidth are similar for 802.11n mode for 20MHz / 40MHz and 802.11ac mode for 20MHz / 40MHz, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

3. The EUT uses following adapter. And the **Adapter 1** was the worst case for final test.

| Adapter      | 1                            | 2                            |
|--------------|------------------------------|------------------------------|
| Brand        | NETGEAR                      | NETGEAR                      |
| Model        | AD2067M20                    | AD2067F10                    |
| Input Power  | 100-240Vac, 1.0A, 50/60Hz    | 100-120Vac, 1.0A, 50/60Hz    |
| Output Power | 12Vdc, 2.5A                  | 12Vdc, 2.5A                  |
| Power Line   | Non-shielded DC cable (2.4m) | Non-shielded DC cable (2.4m) |

4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.



### 3.2 Description of Test Modes

#### FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n (20MHz), 802.11ac (20MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 36      | 5180 MHz  | 44      | 5220 MHz  |
| 40      | 5200 MHz  | 48      | 5240 MHz  |

2 channels are provided for 802.11n (40MHz), 802.11ac (40MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 38      | 5190 MHz  | 46      | 5230 MHz  |

1 channel is provided for 802.11ac (80MHz):

| Channel | Frequency |
|---------|-----------|
| 42      | 5210MHz   |

#### FOR 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (20MHz), 802.11ac (20MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 149     | 5745MHz   | 161     | 5805MHz   |
| 153     | 5765MHz   | 165     | 5825MHz   |
| 157     | 5785MHz   |         |           |

2 channels are provided for 802.11n (40MHz), 802.11ac (40MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 151     | 5755MHz   | 159     | 5795MHz   |

1 channel is provided for 802.11ac (80MHz):

| Channel | Frequency |
|---------|-----------|
| 155     | 5775MHz   |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable To |       |     |      | Description |
|--------------------|---------------|-------|-----|------|-------------|
|                    | RE≥1G         | RE<1G | PLC | APCM |             |
| -                  | √             | √     | √   | √    | -           |

Where **RE≥1G**: Radiated Emission above 1GHz      **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

#### **Radiated Emission Test (Above 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode             | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|--------------------|------------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11a          | 5180-5240        | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6                |
| -                  | 802.11ac (20MHz) |                  | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6.5              |
| -                  | 802.11ac (40MHz) |                  | 38 to 46          | 38, 46         | OFDM                  | BPSK            | 13.5             |
| -                  | 802.11ac (80MHz) |                  | 42                | 42             | OFDM                  | BPSK            | 29.3             |
| -                  | 802.11a          | 5745-5825        | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6                |
| -                  | 802.11ac (20MHz) |                  | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6.5              |
| -                  | 802.11ac (40MHz) |                  | 151 to 159        | 151, 159       | OFDM                  | BPSK            | 13.5             |
| -                  | 802.11ac (80MHz) |                  | 155               | 155            | OFDM                  | BPSK            | 29.3             |

#### **Radiated Emission Test (Below 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode    | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|--------------------|---------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11a | 5180-5240        | 36 to 48          | 149            | OFDM                  | BPSK            | 6                |
| -                  | 802.11a | 5745-5825        | 149 to 165        |                | OFDM                  | BPSK            | 6                |

**Power Line Conducted Emission Test:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode    | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|--------------------|---------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11a | 5180-5240        | 36 to 48          | 149            | OFDM                  | BPSK            | 6                |
| -                  | 802.11a | 5745-5825        | 149 to 165        |                | OFDM                  | BPSK            | 6                |

**Antenna Port Conducted Measurement:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode             | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate (Mbps) |
|--------------------|------------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11a          | 5180-5240        | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6                |
| -                  | 802.11ac (20MHz) |                  | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6.5              |
| -                  | 802.11ac (40MHz) |                  | 38 to 46          | 38, 46         | OFDM                  | BPSK            | 13.5             |
| -                  | 802.11ac (80MHz) |                  | 42                | 42             | OFDM                  | BPSK            | 29.3             |
| -                  | 802.11a          | 5745-5825        | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6                |
| -                  | 802.11ac (20MHz) |                  | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6.5              |
| -                  | 802.11ac (40MHz) |                  | 151 to 159        | 151, 159       | OFDM                  | BPSK            | 13.5             |
| -                  | 802.11ac (80MHz) |                  | 155               | 155            | OFDM                  | BPSK            | 29.3             |

**Test Condition:**

| Applicable To | Environmental Conditions | Input Power  | Tested By |
|---------------|--------------------------|--------------|-----------|
| RE≥1G         | 23deg. C, 72%RH          | 120Vac, 60Hz | Dalen Dai |
| RE<1G         | 23deg. C, 72%RH          | 120Vac, 60Hz | Dalen Dai |
| PLC           | 23deg. C, 75%RH          | 120Vac, 60Hz | Andy Ho   |
| APCM          | 25deg. C, 76%RH          | 120Vac, 60Hz | Saxon Lee |

### 3.3 Duty Cycle of Test Signal


Duty cycle of test signal is < 98 %, duty factor is required

**802.11a:** Duty cycle = 2.079/2.170 = 0.958, Duty factor =  $10 * \log(1/0.958) = 0.19$

**802.11ac (20MHz):** Duty cycle = 1.951/2.049 = 0.952, Duty factor =  $10 * \log(1/0.952) = 0.21$

**802.11ac (40MHz):** Duty cycle = 0.965/1.070 = 0.902, Duty factor =  $10 * \log(1/0.902) = 0.45$

**802.11ac (80MHz):** Duty cycle = 0.472/0.562 = 0.840, Duty factor =  $10 * \log(1/0.840) = 0.76$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product     | Brand | Model No. | Serial No. | FCC ID | Remarks         |
|----|-------------|-------|-----------|------------|--------|-----------------|
| A. | Notebook PC | DELL  | E5410     | BW33YM1    | N/A    | Provided by Lab |


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as communication partners to transfer data.

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks            |
|----|--------------|------|------------|--------------------|--------------|--------------------|
| 1. | DC cable     | 1    | 2.4        | N                  | 0            | Supplied by client |
| 2. | LAN cable    | 1    | 10         | N                  | 0            | Provided by Lab    |

Note: The core(s) is(are) originally attached to the cable(s).

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standard

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)**

**KDB 789033 D02 General UNII Test Procedure New Rules v02r01**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To   |   | Limit   |   |
|---|---|---|---|
| 789033 D02 General UNII Test Procedure<br>New Rules v02r01                            |   | Field Strength at 3m  |   |
|   |   | PK:74 (dBµV/m)  | AV:54 (dBµV/m)  |
| Frequency Band  | Applicable To                                       | EIRP Limit  | Equivalent Field Strength at 3m   |
| 5150~5250 MHz   | 15.407(b)(1)  | PK:-27 (dBm/MHz)  | PK:68.2(dBµV/m)   |
| 5250~5350 MHz   | 15.407(b)(2)  |   |   |
| 5470~5725 MHz   | 15.407(b)(3)  |   |   |
| 5725~5850 MHz   | <input checked="" type="checkbox"/> 15.407(b)(4)(i) | PK:-27 (dBm/MHz) <sup>*1</sup><br>PK:10 (dBm/MHz) <sup>*2</sup><br>PK:15.6 (dBm/MHz) <sup>*3</sup><br>PK:27 (dBm/MHz) <sup>*4</sup> | PK: 68.2(dBµV/m) <sup>*1</sup><br>PK:105.2 (dBµV/m) <sup>*2</sup><br>PK: 110.8(dBµV/m) <sup>*3</sup><br>PK:122.2 (dBµV/m) <sup>*4</sup> |
|   | <input type="checkbox"/> 15.407(b)(4)(ii)           | Emission limits in section 15.247(d)  |   |
| *1 beyond 75 MHz or more above of the band edge.                                      |   | *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.   |   |
| *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. |   | *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.                           |   |

#### Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

| DESCRIPTION & MANUFACTURER                | MODEL NO.            | SERIAL NO.     | DATE OF CALIBRATION          | DUE DATE OF CALIBRATION      |
|---|----------------------|----------------|------------------------------|------------------------------|
| HP Preamplifier                           | 8447D                | 2432A03504     | Feb. 20, 2019                | Feb. 19, 2020                |
| HP Preamplifier                           | 8449B                | 3008A01201     | Feb. 21, 2019                | Feb. 20, 2020                |
| MITEQ Preamplifier                        | AMF-6F-260400-33-8P  | 892164         | Feb. 20, 2019                | Feb. 19, 2020                |
| Agilent<br>TEST RECEIVER                  | N9038A               | MY51210129     | Mar. 05, 2019                | Mar. 04, 2020                |
| Schwarzbeck Antenna                       | VULB 9168            | 139            | Nov. 26, 2018                | Nov. 25, 2019                |
| Schwarzbeck Horn<br>Antenna               | BBHA-9170            | 212            | Nov. 25, 2018                | Nov. 24, 2019                |
| Schwarzbeck Horn<br>Antenna               | BBHA 9120-D1         | D130           | Nov. 25, 2018                | Nov. 24, 2019                |
| ADT. Turn Table                           | TT100                | 0306           | NA                           | NA                           |
| ADT. Tower                                | AT100                | 0306           | NA                           | NA                           |
| Software                                  | Radiated_V7.6.15.9.5 | NA             | NA                           | NA                           |
| SUHNER RF cable<br>With 4dB PAD           | SF102                | Cable-CH6-01   | Aug. 13, 2018                | Aug. 12, 2019                |
| SUHNER RF cable<br>With 3/4dB PAD         | SF102                | Cable-CH8-3.6m | Aug. 13, 2018                | Aug. 12, 2019                |
| KEYSIGHT<br>Spectrum Analyzer             | N9030A               | MY54490260     | Aug. 3, 2018                 | Aug. 2, 2019                 |
| Loop Antenna EMCI                         | LPA600               | 270            | Aug. 11, 2017                | Aug. 10, 2019                |
| EMCO Horn Antenna                         | 3115                 | 00028257       | Nov. 25, 2018                | Nov. 24, 2019                |
| Highpass filter<br>Wainwright Instruments | WHK 3.1/18G-10SS     | SN 8           | NA                           | NA                           |
| ROHDE & SCHWARZ<br>Spectrum Analyzer      | FSV40                | 101042         | Sep. 27, 2018                | Sep. 26, 2019                |
| Anritsu<br>Power Sensor                   | MA2411B              | 0738404        | Apr. 16, 2019                | Apr. 15, 2020                |
| Anritsu<br>Power Meter                    | ML2495A              | 0842014        | Apr. 16, 2019                | Apr. 15, 2020                |
| Temperature & Humidity<br>Chamber         | MHU-225AU            | 920409         | May 24, 2018<br>May 24, 2019 | May 23, 2019<br>May 23, 2020 |
| DIGITAL POWER METER<br>IDRC               | CP-240               | 240515         | Sep. 13, 2018                | Sep. 12, 2019                |
| AC Power Source<br>ExTech                 | CFW-105              | E000603        | NA                           | NA                           |

- NOTE:**
1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  3. The test was performed in Chamber No. 6.



#### 4.1.3 Test Procedure

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



**For Radiated emission above 1GHz**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**4.1.6 EUT Operating Condition**

- a. Connected the EUT with AC adapter placed on testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1GHz Data:

802.11a

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 36 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 5150.00        | 70.05 PK                      | 74.00             | -3.95          | 2.90 H                   | 188                        | 62.84                  | 7.21                           |
| 2   | 5150.00        | 53.47 AV                      | 54.00             | -0.53          | 2.90 H                   | 188                        | 46.26                  | 7.21                           |
| 3   | *5180.00       | 112.05 PK                     |                   |                | 2.90 H                   | 187                        | 104.80                 | 7.25                           |
| 4   | *5180.00       | 101.81 AV                     |                   |                | 2.90 H                   | 187                        | 94.56                  | 7.25                           |
| 5   | #10360.00      | 56.60 PK                      | 68.20             | -11.60         | 1.63 H                   | 231                        | 39.46                  | 17.14                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 5150.00        | 62.87 PK                      | 74.00             | -11.13         | 1.53 V                   | 99                         | 55.66                  | 7.21                           |
| 2   | 5150.00        | 47.00 AV                      | 54.00             | -7.00          | 1.53 V                   | 99                         | 39.79                  | 7.21                           |
| 3   | *5180.00       | 104.50 PK                     |                   |                | 1.53 V                   | 99                         | 97.25                  | 7.25                           |
| 4   | *5180.00       | 94.87 AV                      |                   |                | 1.53 V                   | 99                         | 87.62                  | 7.25                           |
| 5   | #10360.00      | 54.26 PK                      | 68.20             | -13.94         | 2.15 V                   | 105                        | 37.12                  | 17.14                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 40 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 5150.00     | 64.30 PK                | 74.00          | -9.70       | 2.87 H             | 187                  | 57.09            | 7.21                     |
| 2   | 5150.00     | 49.10 AV                | 54.00          | -4.90       | 2.87 H             | 187                  | 41.89            | 7.21                     |
| 3   | *5200.00    | 113.71 PK               |                |             | 2.87 H             | 187                  | 106.45           | 7.26                     |
| 4   | *5200.00    | 103.41 AV               |                |             | 2.87 H             | 187                  | 96.15            | 7.26                     |
| 5   | #10400.00   | 57.49 PK                | 68.20          | -10.71      | 1.94 H             | 221                  | 40.15            | 17.34                    |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 5150.00     | 57.43 PK                | 74.00          | -16.57      | 1.54 V             | 96                   | 50.22            | 7.21                     |
| 2   | 5150.00     | 41.99 AV                | 54.00          | -12.01      | 1.54 V             | 96                   | 34.78            | 7.21                     |
| 3   | *5200.00    | 106.82 PK               |                |             | 1.54 V             | 96                   | 99.56            | 7.26                     |
| 4   | *5200.00    | 97.01 AV                |                |             | 1.54 V             | 96                   | 89.75            | 7.26                     |
| 5   | #10400.00   | 56.08 PK                | 68.20          | -12.12      | 2.36 V             | 110                  | 38.74            | 17.34                    |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 48 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *5240.00       | 114.25 PK                     |                   |                | 2.72 H                   | 186                        | 107.29                 | 6.96                           |
| 2   | *5240.00       | 103.22 AV                     |                   |                | 2.72 H                   | 186                        | 96.26                  | 6.96                           |
| 3   | 5350.00        | 60.29 PK                      | 74.00             | -13.71         | 2.72 H                   | 186                        | 52.92                  | 7.37                           |
| 4   | 5350.00        | 46.21 AV                      | 54.00             | -7.79          | 2.72 H                   | 186                        | 38.84                  | 7.37                           |
| 5   | #10480.00      | 58.26 PK                      | 68.20             | -9.94          | 1.94 H                   | 220                        | 40.56                  | 17.70                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *5240.00       | 107.32 PK                     |                   |                | 1.53 V                   | 100                        | 100.36                 | 6.96                           |
| 2   | *5240.00       | 96.48 AV                      |                   |                | 1.53 V                   | 100                        | 89.52                  | 6.96                           |
| 3   | 5350.00        | 53.16 PK                      | 74.00             | -20.84         | 1.53 V                   | 100                        | 45.79                  | 7.37                           |
| 4   | 5350.00        | 38.95 AV                      | 54.00             | -15.05         | 1.53 V                   | 100                        | 31.58                  | 7.37                           |
| 5   | #10480.00      | 56.44 PK                      | 68.20             | -11.76         | 2.35 V                   | 112                        | 38.74                  | 17.70                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 149 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5602.97       | 59.05 PK                      | 68.20             | -9.15          | 2.35 H                   | 181                        | 51.40                  | 7.65                           |
| 2   | *5745.00       | 115.48 PK                     |                   |                | 2.35 H                   | 181                        | 107.89                 | 7.59                           |
| 3   | *5745.00       | 104.25 AV                     |                   |                | 2.35 H                   | 181                        | 96.66                  | 7.59                           |
| 4   | #5935.34       | 59.41 PK                      | 68.20             | -8.79          | 2.35 H                   | 181                        | 51.26                  | 8.15                           |
| 5   | 11490.00       | 61.95 PK                      | 74.00             | -12.05         | 1.65 H                   | 238                        | 43.88                  | 18.07                          |
| 6   | 11490.00       | 47.76 AV                      | 54.00             | -6.24          | 1.65 H                   | 238                        | 29.69                  | 18.07                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5616.49       | 58.26 PK                      | 68.20             | -9.94          | 1.48 V                   | 89                         | 50.66                  | 7.60                           |
| 2   | *5745.00       | 108.55 PK                     |                   |                | 1.48 V                   | 39                         | 100.96                 | 7.59                           |
| 3   | *5745.00       | 99.44 AV                      |                   |                | 1.48 V                   | 39                         | 91.85                  | 7.59                           |
| 4   | #5940.82       | 58.98 PK                      | 68.20             | -9.22          | 1.48 V                   | 89                         | 50.85                  | 8.13                           |
| 5   | 11490.00       | 59.72 PK                      | 74.00             | -14.28         | 2.13 V                   | 104                        | 41.65                  | 18.07                          |
| 6   | 11490.00       | 45.55 AV                      | 54.00             | -8.45          | 2.13 V                   | 104                        | 27.48                  | 18.07                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 157 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5628.74       | 58.62 PK                      | 68.20             | -9.58          | 2.45 H                   | 186                        | 51.09                  | 7.53                           |
| 2   | *5785.00       | 115.22 PK                     |                   |                | 2.45 H                   | 186                        | 107.48                 | 7.74                           |
| 3   | *5785.00       | 103.88 AV                     |                   |                | 2.45 H                   | 186                        | 96.14                  | 7.74                           |
| 4   | #5939.10       | 60.25 PK                      | 68.20             | -7.95          | 2.45 H                   | 186                        | 52.12                  | 8.13                           |
| 5   | 11570.00       | 61.27 PK                      | 74.00             | -12.73         | 1.62 H                   | 248                        | 43.29                  | 17.98                          |
| 6   | 11570.00       | 47.03 AV                      | 54.00             | -6.97          | 1.62 H                   | 248                        | 29.05                  | 17.98                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5641.70       | 57.49 PK                      | 68.20             | -10.71         | 1.55 V                   | 99                         | 50.01                  | 7.48                           |
| 2   | *5785.00       | 107.83 PK                     |                   |                | 1.55 V                   | 99                         | 100.09                 | 7.74                           |
| 3   | *5785.00       | 96.97 AV                      |                   |                | 1.55 V                   | 99                         | 89.23                  | 7.74                           |
| 4   | #5932.90       | 58.97 PK                      | 68.20             | -9.23          | 1.55 V                   | 99                         | 50.81                  | 8.16                           |
| 5   | 11570.00       | 59.64 PK                      | 74.00             | -14.36         | 2.14 V                   | 105                        | 41.66                  | 17.98                          |
| 6   | 11570.00       | 46.72 AV                      | 54.00             | -7.28          | 2.14 V                   | 105                        | 28.74                  | 17.98                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



|                        |                |                          |              |
|------------------------|----------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 165 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | #5623.66    | 57.45 PK                | 68.20          | -10.75      | 2.48 H             | 188                  | 49.89            | 7.56                     |
| 2   | *5825.00    | 115.44 PK               |                |             | 2.48 H             | 188                  | 107.52           | 7.92                     |
| 3   | *5825.00    | 104.51 AV               |                |             | 2.48 H             | 188                  | 96.59            | 7.92                     |
| 4   | #5926.26    | 60.06 PK                | 68.20          | -8.14       | 2.48 H             | 188                  | 51.88            | 8.18                     |
| 5   | 11650.00    | 62.68 PK                | 74.00          | -11.32      | 1.64 H             | 250                  | 44.96            | 17.72                    |
| 6   | 11650.00    | 48.31 AV                | 54.00          | -5.69       | 1.64 H             | 250                  | 30.59            | 17.72                    |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | #5594.12    | 58.93 PK                | 68.20          | -9.27       | 1.53 V             | 102                  | 51.26            | 7.67                     |
| 2   | *5825.00    | 107.50 PK               |                |             | 1.53 V             | 102                  | 99.58            | 7.92                     |
| 3   | *5825.00    | 96.59 AV                |                |             | 1.53 V             | 102                  | 88.67            | 7.92                     |
| 4   | #5947.11    | 59.84 PK                | 68.20          | -8.36       | 1.53 V             | 102                  | 51.72            | 8.12                     |
| 5   | 11650.00    | 58.41 PK                | 74.00          | -15.59      | 2.20 V             | 110                  | 40.69            | 17.72                    |
| 6   | 11650.00    | 44.90 AV                | 54.00          | -9.10       | 2.20 V             | 110                  | 27.18            | 17.72                    |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ac (20MHz)

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 36 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 5150.00     | 68.09 PK                | 74.00          | -5.91       | 2.86 H             | 189                  | 60.88            | 7.21                     |
| 2   | 5150.00     | 53.33 AV                | 54.00          | -0.67       | 2.86 H             | 189                  | 46.12            | 7.21                     |
| 3   | *5180.00    | 111.76 PK               |                |             | 2.86 H             | 189                  | 104.51           | 7.25                     |
| 4   | *5180.00    | 101.40 AV               |                |             | 2.86 H             | 189                  | 94.15            | 7.25                     |
| 5   | #10360.00   | 56.81 PK                | 68.20          | -11.39      | 1.88 H             | 200                  | 39.67            | 17.14                    |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 5150.00     | 60.96 PK                | 74.00          | -13.04      | 1.50 V             | 103                  | 53.75            | 7.21                     |
| 2   | 5150.00     | 47.06 AV                | 54.00          | -6.94       | 1.50 V             | 103                  | 39.85            | 7.21                     |
| 3   | *5180.00    | 104.40 PK               |                |             | 1.50 V             | 103                  | 97.15            | 7.25                     |
| 4   | *5180.00    | 94.87 AV                |                |             | 1.50 V             | 103                  | 87.62            | 7.25                     |
| 5   | #10360.00   | 54.28 PK                | 68.20          | -13.92      | 2.41 V             | 158                  | 37.14            | 17.14                    |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 40 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 5150.00        | 62.95 PK                      | 74.00             | -11.05         | 2.84 H                   | 188                        | 55.74                  | 7.21                           |
| 2   | 5150.00        | 48.80 AV                      | 54.00             | -5.20          | 2.84 H                   | 188                        | 41.59                  | 7.21                           |
| 3   | *5200.00       | 113.51 PK                     |                   |                | 2.84 H                   | 188                        | 106.25                 | 7.26                           |
| 4   | *5200.00       | 103.28 AV                     |                   |                | 2.84 H                   | 188                        | 96.02                  | 7.26                           |
| 5   | #10400.00      | 57.55 PK                      | 68.20             | -10.65         | 1.96 H                   | 256                        | 40.21                  | 17.34                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 5150.00        | 56.00 PK                      | 74.00             | -18.00         | 1.49 V                   | 108                        | 48.79                  | 7.21                           |
| 2   | 5150.00        | 42.17 AV                      | 54.00             | -11.83         | 1.49 V                   | 108                        | 34.96                  | 7.21                           |
| 3   | *5200.00       | 106.58 PK                     |                   |                | 1.49 V                   | 108                        | 99.32                  | 7.26                           |
| 4   | *5200.00       | 97.24 AV                      |                   |                | 1.49 V                   | 108                        | 89.98                  | 7.26                           |
| 5   | #10400.00      | 55.59 PK                      | 68.20             | -12.61         | 2.43 V                   | 162                        | 38.25                  | 17.34                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 48 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *5240.00       | 114.07 PK                     |                   |                | 2.77 H                   | 189                        | 107.11                 | 6.96                           |
| 2   | *5240.00       | 102.77 AV                     |                   |                | 2.77 H                   | 189                        | 95.81                  | 6.96                           |
| 3   | 5350.00        | 59.50 PK                      | 74.00             | -14.50         | 2.77 H                   | 189                        | 52.13                  | 7.37                           |
| 4   | 5350.00        | 45.46 AV                      | 54.00             | -8.54          | 2.77 H                   | 189                        | 38.09                  | 7.37                           |
| 5   | #10480.00      | 58.22 PK                      | 68.20             | -9.98          | 1.89 H                   | 156                        | 40.52                  | 17.70                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *5240.00       | 106.99 PK                     |                   |                | 1.52 V                   | 111                        | 100.03                 | 6.96                           |
| 2   | *5240.00       | 95.42 AV                      |                   |                | 1.52 V                   | 111                        | 88.46                  | 6.96                           |
| 3   | 5350.00        | 52.69 PK                      | 74.00             | -21.31         | 1.52 V                   | 111                        | 45.32                  | 7.37                           |
| 4   | 5350.00        | 39.22 AV                      | 54.00             | -14.78         | 1.52 V                   | 111                        | 31.85                  | 7.37                           |
| 5   | #10480.00      | 55.87 PK                      | 68.20             | -12.33         | 2.42 V                   | 163                        | 38.17                  | 17.70                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 149 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5616.74       | 58.42 PK                      | 68.20             | -9.78          | 2.39 H                   | 185                        | 50.82                  | 7.60                           |
| 2   | *5745.00       | 114.71 PK                     |                   |                | 2.39 H                   | 185                        | 107.12                 | 7.59                           |
| 3   | *5745.00       | 103.77 AV                     |                   |                | 2.39 H                   | 185                        | 96.18                  | 7.59                           |
| 4   | #5958.95       | 59.33 PK                      | 68.20             | -8.87          | 2.39 H                   | 185                        | 51.22                  | 8.11                           |
| 5   | 11490.00       | 61.51 PK                      | 74.00             | -12.49         | 1.63 H                   | 252                        | 43.44                  | 18.07                          |
| 6   | 11490.00       | 47.33 AV                      | 54.00             | -6.67          | 1.63 H                   | 252                        | 29.26                  | 18.07                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5625.32       | 58.81 PK                      | 68.20             | -9.39          | 1.56 V                   | 104                        | 51.26                  | 7.55                           |
| 2   | *5745.00       | 107.84 PK                     |                   |                | 1.56 V                   | 104                        | 100.25                 | 7.59                           |
| 3   | *5745.00       | 96.35 AV                      |                   |                | 1.56 V                   | 104                        | 88.76                  | 7.59                           |
| 4   | #5941.95       | 59.81 PK                      | 68.20             | -8.39          | 1.56 V                   | 104                        | 51.69                  | 8.12                           |
| 5   | 11490.00       | 59.32 PK                      | 74.00             | -14.68         | 2.18 V                   | 107                        | 41.25                  | 18.07                          |
| 6   | 11490.00       | 45.21 AV                      | 54.00             | -8.79          | 2.18 V                   | 107                        | 27.14                  | 18.07                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 157 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5614.20       | 58.24 PK                      | 68.20             | -9.96          | 2.40 H                   | 188                        | 50.63                  | 7.61                           |
| 2   | *5785.00       | 115.43 PK                     |                   |                | 2.40 H                   | 188                        | 107.69                 | 7.74                           |
| 3   | *5785.00       | 104.62 AV                     |                   |                | 2.40 H                   | 188                        | 96.88                  | 7.74                           |
| 4   | #5950.00       | 59.86 PK                      | 68.20             | -8.34          | 2.40 H                   | 188                        | 51.75                  | 8.11                           |
| 5   | 11570.00       | 61.69 PK                      | 74.00             | -12.31         | 1.66 H                   | 248                        | 43.71                  | 17.98                          |
| 6   | 11570.00       | 47.83 AV                      | 54.00             | -6.17          | 1.66 H                   | 248                        | 29.85                  | 17.98                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5615.34       | 58.08 PK                      | 68.20             | -10.12         | 1.47 V                   | 85                         | 50.48                  | 7.60                           |
| 2   | *5785.00       | 107.88 PK                     |                   |                | 1.47 V                   | 85                         | 100.14                 | 7.74                           |
| 3   | *5785.00       | 97.10 AV                      |                   |                | 1.47 V                   | 85                         | 89.36                  | 7.74                           |
| 4   | #5930.56       | 59.77 PK                      | 68.20             | -8.43          | 1.47 V                   | 85                         | 51.62                  | 8.15                           |
| 5   | 11570.00       | 59.53 PK                      | 74.00             | -14.47         | 2.15 V                   | 112                        | 41.55                  | 17.98                          |
| 6   | 11570.00       | 45.42 AV                      | 54.00             | -8.58          | 2.15 V                   | 112                        | 27.44                  | 17.98                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                          |              |
|------------------------|----------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 165 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | #5644.80    | 58.05 PK                | 68.20          | -10.15      | 2.39 H             | 189                  | 50.59            | 7.46                     |
| 2   | *5825.00    | 115.80 PK               |                |             | 2.39 H             | 189                  | 107.88           | 7.92                     |
| 3   | *5825.00    | 104.70 AV               |                |             | 2.39 H             | 189                  | 96.78            | 7.92                     |
| 4   | #5944.19    | 59.38 PK                | 68.20          | -8.82       | 2.39 H             | 189                  | 51.25            | 8.13                     |
| 5   | 11650.00    | 60.98 PK                | 74.00          | -13.02      | 1.65 H             | 243                  | 43.26            | 17.72                    |
| 6   | 11650.00    | 46.89 AV                | 54.00          | -7.11       | 1.65 H             | 243                  | 29.17            | 17.72                    |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | #5634.37    | 57.96 PK                | 68.20          | -10.24      | 1.44 V             | 97                   | 50.46            | 7.50                     |
| 2   | *5825.00    | 108.15 PK               |                |             | 1.44 V             | 97                   | 100.23           | 7.92                     |
| 3   | *5825.00    | 97.03 AV                |                |             | 1.44 V             | 97                   | 89.11            | 7.92                     |
| 4   | #5957.18    | 59.84 PK                | 68.20          | -8.36       | 1.44 V             | 97                   | 51.73            | 8.11                     |
| 5   | 11650.00    | 59.57 PK                | 74.00          | -14.43      | 2.23 V             | 107                  | 41.85            | 17.72                    |
| 6   | 11650.00    | 45.06 AV                | 54.00          | -8.94       | 2.23 V             | 107                  | 27.34            | 17.72                    |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ac (40MHz)

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 38 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | 5150.00        | 68.71 PK                      | 74.00             | -5.29          | 2.87 H                   | 187                        | 61.50                  | 7.21                           |
| 2   | 5150.00        | 53.44 AV                      | 54.00             | -0.56          | 2.87 H                   | 187                        | 46.23                  | 7.21                           |
| 3   | *5190.00       | 106.42 PK                     |                   |                | 2.87 H                   | 187                        | 99.17                  | 7.25                           |
| 4   | *5190.00       | 96.73 AV                      |                   |                | 2.87 H                   | 187                        | 89.48                  | 7.25                           |
| 5   | #10380.00      | 56.88 PK                      | 68.20             | -11.32         | 1.79 H                   | 251                        | 39.64                  | 17.24                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.   | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1   | 5150.00        | 61.92 PK                      | 74.00             | -12.08         | 1.54 V                   | 96                         | 54.71                  | 7.21                           |
| 2   | 5150.00        | 46.77 AV                      | 54.00             | -7.23          | 1.54 V                   | 96                         | 39.56                  | 7.21                           |
| 3   | *5190.00       | 99.69 PK                      |                   |                | 1.54 V                   | 96                         | 92.44                  | 7.25                           |
| 4   | *5190.00       | 89.58 AV                      |                   |                | 1.54 V                   | 96                         | 82.33                  | 7.25                           |
| 5   | #10380.00      | 54.69 PK                      | 68.20             | -13.51         | 2.35 V                   | 158                        | 37.45                  | 17.24                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 46 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ. (MHz)    | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB)  | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 5150.00        | 66.82 PK                | 74.00          | -7.18        | 2.83 H             | 188                  | 59.61            | 7.21                     |
| 2   | <b>5150.00</b> | <b>53.55 AV</b>         | <b>54.00</b>   | <b>-0.45</b> | <b>2.83 H</b>      | <b>188</b>           | <b>46.34</b>     | <b>7.21</b>              |
| 3   | *5230.00       | 109.97 PK               |                |              | 2.83 H             | 188                  | 102.93           | 7.04                     |
| 4   | *5230.00       | 100.05 AV               |                |              | 2.83 H             | 188                  | 93.01            | 7.04                     |
| 5   | 5350.00        | 61.36 PK                | 74.00          | -12.64       | 2.83 H             | 188                  | 53.99            | 7.37                     |
| 6   | 5350.00        | 44.97 AV                | 54.00          | -9.03        | 2.83 H             | 188                  | 37.60            | 7.37                     |
| 7   | #10460.00      | 57.46 PK                | 68.20          | -10.74       | 1.52 H             | 263                  | 39.85            | 17.61                    |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 5150.00     | 59.35 PK                | 74.00          | -14.65      | 1.53 V             | 101                  | 52.14            | 7.21                     |
| 2   | 5150.00     | 47.17 AV                | 54.00          | -6.83       | 1.53 V             | 101                  | 39.96            | 7.21                     |
| 3   | *5230.00    | 102.59 PK               |                |             | 1.53 V             | 101                  | 95.55            | 7.04                     |
| 4   | *5230.00    | 93.51 AV                |                |             | 1.53 V             | 101                  | 86.47            | 7.04                     |
| 5   | 5350.00     | 53.98 PK                | 74.00          | -20.02      | 1.53 V             | 101                  | 46.61            | 7.37                     |
| 6   | 5350.00     | 39.22 AV                | 54.00          | -14.78      | 1.53 V             | 101                  | 31.85            | 7.37                     |
| 7   | #10460.00   | 55.09 PK                | 68.20          | -13.11      | 2.38 V             | 155                  | 37.48            | 17.61                    |

**REMARKS:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 151 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5649.69       | 66.74 PK                      | 68.20             | -1.46          | 2.49 H                   | 182                        | 59.30                  | 7.44                           |
| 2   | *5755.00       | 111.08 PK                     |                   |                | 2.49 H                   | 182                        | 103.47                 | 7.61                           |
| 3   | *5755.00       | 101.23 AV                     |                   |                | 2.49 H                   | 182                        | 93.62                  | 7.61                           |
| 4   | #5942.94       | 60.55 PK                      | 68.20             | -7.65          | 2.49 H                   | 182                        | 52.43                  | 8.12                           |
| 5   | 11510.00       | 59.38 PK                      | 74.00             | -14.62         | 1.69 H                   | 252                        | 41.29                  | 18.09                          |
| 6   | 11510.00       | 45.45 AV                      | 54.00             | -8.55          | 1.69 H                   | 252                        | 27.36                  | 18.09                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5647.29       | 60.77 PK                      | 68.20             | -7.43          | 1.53 V                   | 85                         | 53.32                  | 7.45                           |
| 2   | *5755.00       | 104.46 PK                     |                   |                | 1.53 V                   | 85                         | 96.85                  | 7.61                           |
| 3   | *5755.00       | 94.35 AV                      |                   |                | 1.53 V                   | 85                         | 86.74                  | 7.61                           |
| 4   | #5942.97       | 59.49 PK                      | 68.20             | -8.71          | 1.53 V                   | 85                         | 51.37                  | 8.12                           |
| 5   | 11510.00       | 57.65 PK                      | 74.00             | -16.35         | 2.18 V                   | 110                        | 39.56                  | 18.09                          |
| 6   | 11510.00       | 43.97 AV                      | 54.00             | -10.03         | 2.18 V                   | 110                        | 25.88                  | 18.09                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 159 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5633.22       | 59.98 PK                      | 68.20             | -8.22          | 2.40 H                   | 189                        | 52.47                  | 7.51                           |
| 2   | *5795.00       | 111.05 PK                     |                   |                | 2.40 H                   | 189                        | 103.26                 | 7.79                           |
| 3   | *5795.00       | 100.94 AV                     |                   |                | 2.40 H                   | 189                        | 93.15                  | 7.79                           |
| 4   | #5927.97       | 65.35 PK                      | 68.20             | -2.85          | 2.40 H                   | 189                        | 57.19                  | 8.16                           |
| 5   | 11590.00       | 59.32 PK                      | 74.00             | -14.68         | 1.68 H                   | 251                        | 41.38                  | 17.94                          |
| 6   | 11590.00       | 45.59 AV                      | 54.00             | -8.41          | 1.68 H                   | 251                        | 27.65                  | 17.94                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5622.57       | 59.09 PK                      | 68.20             | -9.11          | 1.55 V                   | 99                         | 51.53                  | 7.56                           |
| 2   | *5795.00       | 104.26 PK                     |                   |                | 1.55 V                   | 99                         | 96.47                  | 7.79                           |
| 3   | *5795.00       | 94.31 AV                      |                   |                | 1.55 V                   | 99                         | 86.52                  | 7.79                           |
| 4   | #5925.46       | 60.35 PK                      | 68.20             | -7.85          | 1.55 V                   | 99                         | 52.17                  | 8.18                           |
| 5   | 11590.00       | 57.39 PK                      | 74.00             | -16.61         | 2.24 V                   | 114                        | 39.45                  | 17.94                          |
| 6   | 11590.00       | 43.07 AV                      | 54.00             | -10.93         | 2.24 V                   | 114                        | 25.13                  | 17.94                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ac (80MHz)

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 42 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 5150.00     | 65.30 PK                | 74.00          | -8.70       | 2.66 H             | 188                  | 58.09            | 7.21                     |
| 2   | 5150.00     | 53.29 AV                | 54.00          | -0.71       | 2.66 H             | 188                  | 46.08            | 7.21                     |
| 3   | *5210.00    | 102.68 PK               |                |             | 2.66 H             | 188                  | 95.50            | 7.18                     |
| 4   | *5210.00    | 92.54 AV                |                |             | 2.66 H             | 188                  | 85.36            | 7.18                     |
| 5   | 5350.00     | 57.96 PK                | 74.00          | -16.04      | 2.66 H             | 188                  | 50.59            | 7.37                     |
| 6   | 5350.00     | 45.29 AV                | 54.00          | -8.71       | 2.66 H             | 188                  | 37.92            | 7.37                     |
| 7   | #10420.00   | 57.30 PK                | 68.20          | -10.90      | 1.85 H             | 164                  | 39.87            | 17.43                    |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 5150.00     | 58.66 PK                | 74.00          | -15.34      | 1.53 V             | 104                  | 51.45            | 7.21                     |
| 2   | 5150.00     | 47.07 AV                | 54.00          | -6.93       | 1.53 V             | 104                  | 39.86            | 7.21                     |
| 3   | *5210.00    | 95.93 PK                |                |             | 1.53 V             | 104                  | 88.75            | 7.18                     |
| 4   | *5210.00    | 85.44 AV                |                |             | 1.53 V             | 104                  | 78.26            | 7.18                     |
| 5   | 5350.00     | 50.58 PK                | 74.00          | -23.42      | 1.53 V             | 104                  | 43.21            | 7.37                     |
| 6   | 5350.00     | 39.33 AV                | 54.00          | -14.67      | 1.53 V             | 104                  | 31.96            | 7.37                     |
| 7   | #10420.00   | 54.85 PK                | 68.20          | -13.35      | 2.40 V             | 156                  | 37.42            | 17.43                    |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 155 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5625.96       | 66.22 PK                      | 68.20             | -1.98          | 2.91 H                   | 226                        | 58.67                  | 7.55                           |
| 2   | *5775.00       | 109.66 PK                     |                   |                | 2.91 H                   | 226                        | 101.96                 | 7.70                           |
| 3   | *5775.00       | 98.57 AV                      |                   |                | 2.91 H                   | 226                        | 90.87                  | 7.70                           |
| 4   | #5925.83       | 67.70 PK                      | 68.20             | -0.50          | 2.91 H                   | 226                        | 59.52                  | 8.18                           |
| 5   | 11550.00       | 58.77 PK                      | 74.00             | -15.23         | 1.60 H                   | 243                        | 40.75                  | 18.02                          |
| 6   | 11550.00       | 44.49 AV                      | 54.00             | -9.51          | 1.60 H                   | 243                        | 26.47                  | 18.02                          |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | #5651.01       | 65.19 PK                      | 68.20             | -3.01          | 1.68 V                   | 121                        | 57.76                  | 7.43                           |
| 2   | *5775.00       | 102.33 PK                     |                   |                | 1.68 V                   | 121                        | 94.63                  | 7.70                           |
| 3   | *5775.00       | 90.87 AV                      |                   |                | 1.68 V                   | 121                        | 83.17                  | 7.70                           |
| 4   | #5926.27       | 64.08 PK                      | 68.20             | -4.12          | 1.68 V                   | 121                        | 55.90                  | 8.18                           |
| 5   | 11550.00       | 57.16 PK                      | 74.00             | -16.84         | 2.30 V                   | 116                        | 39.14                  | 18.02                          |
| 6   | 11550.00       | 43.90 AV                      | 54.00             | -10.10         | 2.30 V                   | 116                        | 25.88                  | 18.02                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

**Below 1GHz Data:**


**802.11a**

|                        |                |                          |                 |
|------------------------|----------------|--------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 149 | <b>DETECTOR FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 9kHz ~ 1GHz    |                          |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.   | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1   | 125.01      | 39.87 QP                | 43.50          | -3.63       | 1.85 H             | 110                  | 48.43            | -8.56                    |
| 2   | 250.00      | 36.43 QP                | 46.00          | -9.57       | 1.00 H             | 219                  | 43.38            | -6.95                    |
| 3   | 375.03      | 35.63 QP                | 46.00          | -10.37      | 2.68 H             | 332                  | 39.33            | -3.70                    |
| 4   | 519.12      | 26.86 QP                | 46.00          | -19.14      | 3.08 H             | 329                  | 27.85            | -0.99                    |
| 5   | 625.00      | 35.60 QP                | 46.00          | -10.40      | 3.33 H             | 144                  | 34.04            | 1.56                     |
| 6   | 875.02      | 38.67 QP                | 46.00          | -7.33       | 1.00 H             | 360                  | 32.97            | 5.70                     |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




|                        |                |                          |                 |
|------------------------|----------------|--------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 149 | <b>DETECTOR FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 9kHz ~ 1GHz    |                          |                 |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 40.86       | 32.66 QP                | 40.00          | -7.34       | 1.00 V             | 280                  | 40.23            | -7.57                    |
| 2   | 125.01      | 39.00 QP                | 43.50          | -4.50       | 1.96 V             | 70                   | 47.56            | -8.56                    |
| 3   | 250.00      | 34.70 QP                | 46.00          | -11.30      | 2.58 V             | 72                   | 41.65            | -6.95                    |
| 4   | 374.98      | 31.30 QP                | 46.00          | -14.70      | 3.69 V             | 216                  | 35.00            | -3.70                    |
| 5   | 500.06      | 26.60 QP                | 46.00          | -19.40      | 1.59 V             | 287                  | 27.87            | -1.27                    |
| 6   | 625.00      | 41.23 QP                | 46.00          | -4.77       | 3.57 V             | 99                   | 39.67            | 1.56                     |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer   | Model No.               | Serial No. | Cal. Date     | Cal. Due      |
|--|-------------------------|------------|---------------|---------------|
| Test Receiver<br>R&S   | ESCS 30                 | 847124/029 | Oct. 24, 2018 | Oct. 23, 2019 |
| Line-Impedance Stabilization<br>Network (for EUT)<br>R&S           | ESH3-Z5                 | 848773/004 | Oct. 22, 2018 | Oct. 21, 2019 |
| Line-Impedance Stabilization<br>Network<br>(for Peripheral)<br>R&S | ESH3-Z5                 | 835239/001 | Mar. 17, 2019 | Mar. 16, 2020 |
| 50 ohms Terminator   | N/A                     | 3          | Oct. 22, 2018 | Oct. 21, 2019 |
| RF Cable   | 5D-FB                   | COCCAB-001 | Sep. 28, 2018 | Sep. 27, 2019 |
| Fixed attenuator<br>EMCI   | STI02-2200-10           | 003        | Mar. 14, 2019 | Mar. 13, 2020 |
| Software<br>BVADT  | BVADT_Cond_<br>V7.3.7.4 | NA         | NA            | NA            |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in Conduction 1. (TAF no.: 2022)



#### 4.2.3 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note: 1.Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Condition

Same as 4.1.6.


#### 4.2.7 Test Results

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|----------|-------------------|--------------------------------|
|-------|----------|-------------------|--------------------------------|

| No       | Freq.<br>[MHz] | Corr.        | Reading Value |              | Emission Level |              | Limit        |              | Margin        |               |
|----------|----------------|--------------|---------------|--------------|----------------|--------------|--------------|--------------|---------------|---------------|
|          |                | Factor       | [dB (uV)]     |              | [dB (uV)]      |              | [dB (uV)]    |              | (dB)          |               |
|          | (dB)           | Q.P.         | AV.           | Q.P.         | AV.            | Q.P.         | AV.          | Q.P.         | AV.           |               |
| 1        | 0.15000        | 10.03        | 40.74         | 22.96        | 50.77          | 32.99        | 66.00        | 56.00        | -15.23        | -23.01        |
| <b>2</b> | <b>0.16172</b> | <b>10.03</b> | <b>44.23</b>  | <b>29.37</b> | <b>54.26</b>   | <b>39.40</b> | <b>65.38</b> | <b>55.38</b> | <b>-11.12</b> | <b>-15.98</b> |
| 3        | 0.18516        | 10.04        | 40.64         | 25.59        | 50.68          | 35.63        | 64.25        | 54.25        | -13.57        | -18.62        |
| 4        | 0.48203        | 10.09        | 28.10         | 22.50        | 38.19          | 32.59        | 56.30        | 46.30        | -18.11        | -13.71        |
| 5        | 7.41797        | 10.54        | 22.72         | 17.52        | 33.26          | 28.06        | 60.00        | 50.00        | -26.74        | -21.94        |
| 6        | 20.41406       | 11.37        | 16.49         | 11.03        | 27.86          | 22.40        | 60.00        | 50.00        | -32.14        | -27.60        |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No | Freq.    | Corr.  | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|----------|--------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    | [MHz]    | Factor | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    |          | (dB)   | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.16172  | 9.94   | 43.71         | 26.58 | 53.65          | 36.52 | 65.38     | 55.38 | -11.73 | -18.86 |
| 2  | 0.18516  | 9.95   | 40.31         | 22.46 | 50.26          | 32.41 | 64.25     | 54.25 | -13.99 | -21.84 |
| 3  | 0.23594  | 9.96   | 33.23         | 18.05 | 43.19          | 28.01 | 62.24     | 52.24 | -19.05 | -24.23 |
| 4  | 0.48203  | 9.98   | 29.75         | 24.67 | 39.73          | 34.65 | 56.30     | 46.30 | -16.57 | -11.65 |
| 5  | 7.24219  | 10.36  | 20.01         | 13.12 | 30.37          | 23.48 | 60.00     | 50.00 | -29.63 | -26.52 |
| 6  | 21.07422 | 11.16  | 16.92         | 11.42 | 28.08          | 22.58 | 60.00     | 50.00 | -31.92 | -27.42 |

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Note: The test, calibration and test results are compliance with the TAF (Certificate # 2022)


### 4.3 Transmit Power Measurement

#### 4.3.1 Limits of Transmit Power Measurement

| Operation Band | EUT Category |                                   | Limit   |
|----------------|--------------|-----------------------------------|---|
| U-NII-1        |              | Outdoor Access Point              | 1 Watt (30 dBm)<br>(Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon) |
|                |              | Fixed point-to-point Access Point | 1 Watt (30 dBm)   |
|                |              | Indoor Access Point               | 1 Watt (30 dBm)   |
|                | √            | Client device                     | 250mW (24 dBm)  |
| U-NII-2A       | ---          |                                   | 250mW (24 dBm) or 11 dBm+10 log B*  |
| U-NII-2C       | ---          |                                   | 250mW (24 dBm) or 11 dBm+10 log B*  |
| U-NII-3        | √            |                                   | 1 Watt (30 dBm)   |

\*B is the 26 dB emission bandwidth in megahertz

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

##### For Average Power Measurement

##### For 802.11a, 802.11ac (20MHz), 802.11ac (40MHz)

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to AVERAGE. Duty factor is not added to measured value.

##### For 802.11ac (80MHz)

- 1) Set span to encompass the entire 26 dB EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- 2) Set sweep trigger to "free run".
- 3) Set RBW = 1 MHz.
- 4) Set VBW  $\geq$  3 MHz
- 5) Number of points in sweep  $\geq$  2 Span / RBW.
- 6) Sweep time  $\leq$  (number of points in sweep) \* T
- 7) Using emission bandwidth to determine the frequency span for integration the channel bandwidth.
- 8) Detector = RMS.
- 9) Trace mode = max hold.
- 10) Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

#### Power Output:

##### 802.11a

| Chan. | Freq. (MHz) | Conducted Power (mW) | Conducted Power (dBm) | Power Limit (dBm) | Pass / Fail |
|-------|-------------|----------------------|-----------------------|-------------------|-------------|
| 36    | 5180        | 147.231              | 21.68                 | 24.00             | Pass        |
| 40    | 5200        | 232.809              | 23.67                 | 24.00             | Pass        |
| 48    | 5240        | <b>240.991</b>       | 23.82                 | 24.00             | Pass        |
| 149   | 5745        | <b>230.144</b>       | 23.62                 | 30.00             | Pass        |
| 157   | 5785        | 216.272              | 23.35                 | 30.00             | Pass        |
| 165   | 5825        | 209.894              | 23.22                 | 30.00             | Pass        |

##### 802.11ac (20MHz)

| Chan. | Freq. (MHz) | Conducted Power (mW) | Conducted Power (dBm) | Power Limit (dBm) | Pass / Fail |
|-------|-------------|----------------------|-----------------------|-------------------|-------------|
| 36    | 5180        | 110.408              | 20.43                 | 24.00             | Pass        |
| 40    | 5200        | 229.615              | 23.61                 | 24.00             | Pass        |
| 48    | 5240        | 228.034              | 23.58                 | 24.00             | Pass        |
| 149   | 5745        | 221.820              | 23.46                 | 30.00             | Pass        |
| 157   | 5785        | 217.771              | 23.38                 | 30.00             | Pass        |
| 165   | 5825        | 210.378              | 23.23                 | 30.00             | Pass        |

##### 802.11ac (40MHz)


| Chan. | Freq. (MHz) | Conducted Power (mW) | Conducted Power (dBm) | Power Limit (dBm) | Pass / Fail |
|-------|-------------|----------------------|-----------------------|-------------------|-------------|
| 38    | 5190        | 78.705               | 18.96                 | 24.00             | Pass        |
| 46    | 5230        | 171.396              | 22.34                 | 24.00             | Pass        |
| 151   | 5755        | 224.905              | 23.52                 | 30.00             | Pass        |
| 159   | 5795        | 216.770              | 23.36                 | 30.00             | Pass        |

##### 802.11ac (80MHz)

| Chan. | Freq. (MHz) | Conducted Power (mW) | Conducted Power (dBm) | Power Limit (dBm) | Pass / Fail |
|-------|-------------|----------------------|-----------------------|-------------------|-------------|
| 42    | 5210        | 85.310               | 19.31                 | 24.00             | Pass        |
| 155   | 5775        | 210.378              | 23.23                 | 30.00             | Pass        |

## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Setup



### 4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to SAMPLE. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 4.4.4 Test Results

##### 802.11a

| Channel | Channel Frequency (MHz) | Occupied Bandwidth (MHz) |
|---------|-------------------------|--------------------------|
| 36      | 5180                    | 16.32                    |
| 40      | 5200                    | 20.40                    |
| 48      | 5240                    | 18.24                    |
| 149     | 5745                    | 25.57                    |
| 157     | 5785                    | 23.10                    |
| 165     | 5825                    | 27.80                    |

##### 802.11ac (20MHz)

| Channel | Channel Frequency (MHz) | Occupied Bandwidth (MHz) |
|---------|-------------------------|--------------------------|
| 36      | 5180                    | 17.64                    |
| 40      | 5200                    | 19.80                    |
| 48      | 5240                    | 18.24                    |
| 149     | 5745                    | 23.57                    |
| 157     | 5785                    | 21.40                    |
| 165     | 5825                    | 27.60                    |

##### 802.11ac (40MHz)

| Channel | Channel Frequency (MHz) | Occupied Bandwidth (MHz) |
|---------|-------------------------|--------------------------|
| 38      | 5190                    | 35.80                    |
| 46      | 5230                    | 37.80                    |
| 151     | 5755                    | 46.23                    |
| 159     | 5795                    | 43.50                    |


##### 802.11ac (80MHz)

| Channel | Channel Frequency (MHz) | Occupied Bandwidth (MHz) |
|---------|-------------------------|--------------------------|
| 42      | 5210                    | 75.12                    |
| 155     | 5775                    | 76.69                    |




### Spectrum Plot of Worst Value


#### 802.11a / CH165




#### 802.11ac (20MHz) / CH165



#### 802.11ac (40MHz) / CH151



#### 802.11ac (80MHz) / CH155




## 4.5 Peak Power Spectral Density Measurement

### 4.5.1 Limits of Peak Power Spectral Density Measurement

| Operation Band | EUT Category |                                   | Limit         |
|----------------|--------------|-----------------------------------|---------------|
| U-NII-1        |              | Outdoor Access Point              | 17dBm/ MHz    |
|                |              | Fixed point-to-point Access Point |               |
|                |              | Indoor Access Point               |               |
|                | √            | Client device                     | 11dBm/ MHz    |
| U-NII-2A       | ---          |                                   | 11dBm/ MHz    |
| U-NII-2C       | ---          |                                   | 11dBm/ MHz    |
| U-NII-3        | √            |                                   | 30dBm/ 500kHz |

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

#### For U-NII-1 band:

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS
- 3) Sweep time = auto, trigger set to “free run”.
- 4) Trace average at least 100 traces in power averaging mode.
- 5) Record the max value and add 10 log (1/duty cycle)

#### For U-NII-3 band:

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 500 kHz, Set VBW ≥ 1 MHz, Detector = RMS
- 3) Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
- 4) Sweep time = auto, trigger set to “free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

Same as Item 4.3.6.

#### 4.5.7 Test Results

##### 802.11a

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/MHz) | Duty Factor (dB) | PSD With Duty Factor (dBm/MHz) | MAX. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------------|-------------------------------|------------------|--------------------------------|----------------------|-------------|
| 36    | 5180              | 9.02                          | 0.19             | 9.21                           | 11                   | Pass        |
| 40    | 5200              | 10.77                         | 0.19             | 10.96                          | 11                   | Pass        |
| 48    | 5240              | 10.75                         | 0.19             | 10.94                          | 11                   | Pass        |

**Note:** Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11ac (20MHz)

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/MHz) | Duty Factor (dB) | PSD With Duty Factor (dBm/MHz) | MAX. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------------|-------------------------------|------------------|--------------------------------|----------------------|-------------|
| 36    | 5180              | 8.53                          | 0.21             | 8.74                           | 11                   | Pass        |
| 40    | 5200              | 10.65                         | 0.21             | 10.86                          | 11                   | Pass        |
| 48    | 5240              | 10.68                         | 0.21             | 10.89                          | 11                   | Pass        |

**Note:** Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11ac (40MHz)

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/MHz) | Duty Factor (dB) | PSD With Duty Factor (dBm/MHz) | MAX. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------------|-------------------------------|------------------|--------------------------------|----------------------|-------------|
| 38    | 5190              | 4.12                          | 0.45             | 4.57                           | 11                   | Pass        |
| 46    | 5230              | 7.23                          | 0.45             | 7.68                           | 11                   | Pass        |

**Note:** Refer to section 3.3 for duty cycle spectrum plot.


##### 802.11ac (80MHz)

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/MHz) | Duty Factor (dB) | PSD With Duty Factor (dBm/MHz) | MAX. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------------|-------------------------------|------------------|--------------------------------|----------------------|-------------|
| 42    | 5210              | -0.16                         | 0.76             | 0.60                           | 11                   | Pass        |


**Note:** Refer to section 3.3 for duty cycle spectrum plot.

### Spectrum Plot of Worst Value


#### 802.11a / CH40




#### 802.11ac (20MHz) / CH48



#### 802.11ac (40MHz) / CH46



#### 802.11ac (80MHz) / CH42



**For U-NII-3:**

**802.11a**

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/500kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass /Fail |
|-------|-------------------|----------------------------------|------------------|---|--------------------|------------|
| 149   | 5745              | 2.43                             | 0.19             | 2.62                                    | 30                 | Pass       |
| 157   | 5785              | 2.27                             | 0.19             | 2.46                                    | 30                 | Pass       |
| 165   | 5825              | 3.04                             | 0.19             | 3.23                                    | 30                 | Pass       |

**Note:** Refer to section 3.3 for duty cycle spectrum plot.

**802.11ac (20MHz)**

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/500kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass /Fail |
|-------|-------------------|----------------------------------|------------------|---|--------------------|------------|
| 149   | 5745              | 2.42                             | 0.21             | 2.63                                    | 30                 | Pass       |
| 157   | 5785              | 2.18                             | 0.21             | 2.39                                    | 30                 | Pass       |
| 165   | 5825              | 2.89                             | 0.21             | 3.10                                    | 30                 | Pass       |

**Note:** Refer to section 3.3 for duty cycle spectrum plot.

**802.11ac (40MHz)**

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/500kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass /Fail |
|-------|-------------------|----------------------------------|------------------|---|--------------------|------------|
| 151   | 5755              | -1.55                            | 0.45             | -1.10                                   | 30                 | Pass       |
| 159   | 5795              | -1.59                            | 0.45             | -1.14                                   | 30                 | Pass       |

**Note:** Refer to section 3.3 for duty cycle spectrum plot.


**802.11ac (80MHz)**

| Chan. | Chan. Freq. (MHz) | PSD W/O Duty Factor (dBm/500kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass /Fail |
|-------|-------------------|----------------------------------|------------------|---|--------------------|------------|
| 155   | 5775              | -5.72                            | 0.76             | -4.96                                   | 30                 | Pass       |


**Note:** Refer to section 3.3 for duty cycle spectrum plot.

### Spectrum Plot of Worst Value


**802.11a / CH165**




**802.11ac (20MHz) / CH165**



**802.11ac (40MHz) / CH151**



**802.11ac (80MHz) / CH155**




## 4.6 Frequency Stability Measurement

### 4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed..
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

4.6.7 Test Results

| Frequency Stability Versus Temp. |                          |                                |           |                                |           |                                |           |                                |           |
|----------------------------------|--------------------------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|
| Operating Frequency: 5180 MHz    |                          |                                |           |                                |           |                                |           |                                |           |
| TEMP.<br>(°C)                    | Power<br>Supply<br>(Vac) | 0 Minute                       |           | 2 Minute                       |           | 5 Minute                       |           | 10 Minute                      |           |
|                                  |                          | Measured<br>Frequency<br>(MHz) | Pass/Fail | Measured<br>Frequency<br>(MHz) | Pass/Fail | Measured<br>Frequency<br>(MHz) | Pass/Fail | Measured<br>Frequency<br>(MHz) | Pass/Fail |
| 50                               | 120                      | 5180.0054                      | Pass      | 5180.0048                      | Pass      | 5180.0048                      | Pass      | 5180.0063                      | Pass      |
| 40                               | 120                      | 5179.9723                      | Pass      | 5179.9723                      | Pass      | 5179.9724                      | Pass      | 5179.974                       | Pass      |
| 30                               | 120                      | 5179.9779                      | Pass      | 5179.9759                      | Pass      | 5179.9759                      | Pass      | 5179.9771                      | Pass      |
| 20                               | 120                      | 5180.0207                      | Pass      | 5180.022                       | Pass      | 5180.0238                      | Pass      | 5180.022                       | Pass      |
| 10                               | 120                      | 5179.9935                      | Pass      | 5179.9917                      | Pass      | 5179.9953                      | Pass      | 5179.9957                      | Pass      |
| 0                                | 120                      | 5180.001                       | Pass      | 5179.9992                      | Pass      | 5179.9986                      | Pass      | 5180.0004                      | Pass      |
| -10                              | 120                      | 5179.9816                      | Pass      | 5179.9773                      | Pass      | 5179.9767                      | Pass      | 5179.9807                      | Pass      |
| -20                              | 120                      | 5179.9765                      | Pass      | 5179.9738                      | Pass      | 5179.9774                      | Pass      | 5179.9753                      | Pass      |
| -30                              | 120                      | 5180.018                       | Pass      | 5180.0222                      | Pass      | 5180.0201                      | Pass      | 5180.022                       | Pass      |

| Frequency Stability Versus Voltage |                          |                                |           |                                |           |                                |           |                                |           |
|------------------------------------|--------------------------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|
| Operating Frequency: 5180 MHz      |                          |                                |           |                                |           |                                |           |                                |           |
| TEMP.<br>(°C)                      | Power<br>Supply<br>(Vac) | 0 Minute                       |           | 2 Minute                       |           | 5 Minute                       |           | 10 Minute                      |           |
|                                    |                          | Measured<br>Frequency<br>(MHz) | Pass/Fail | Measured<br>Frequency<br>(MHz) | Pass/Fail | Measured<br>Frequency<br>(MHz) | Pass/Fail | Measured<br>Frequency<br>(MHz) | Pass/Fail |
| 20                                 | 138                      | 5180.0211                      | Pass      | 5180.0213                      | Pass      | 5180.0247                      | Pass      | 5180.0228                      | Pass      |
|                                    | 120                      | 5180.0207                      | Pass      | 5180.022                       | Pass      | 5180.0238                      | Pass      | 5180.022                       | Pass      |
|                                    | 102                      | 5180.0198                      | Pass      | 5180.0215                      | Pass      | 5180.0239                      | Pass      | 5180.0223                      | Pass      |




## 4.7 6dB Bandwidth Measurement

### 4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

### 4.7.2 Test Setup



### 4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.7.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.7.5 Deviation from Test Standard

No deviation.

### 4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.7.7 Test Results

##### 802.11a

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 149     | 5745            | 15.19               | 0.5                 | PASS        |
| 157     | 5785            | 15.22               | 0.5                 | PASS        |
| 165     | 5825            | 15.20               | 0.5                 | PASS        |

##### 802.11ac (20MHz)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 149     | 5745            | 16.56               | 0.5                 | PASS        |
| 157     | 5785            | 16.18               | 0.5                 | PASS        |
| 165     | 5825            | 16.60               | 0.5                 | PASS        |

##### 802.11ac (40MHz)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 151     | 5755            | 35.11               | 0.5                 | PASS        |
| 159     | 5795            | 35.18               | 0.5                 | PASS        |

##### 802.11ac (80MHz)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 155     | 5775            | 72.72               | 0.5                 | PASS        |

### Spectrum Plot of Worst Value


#### 802.11a / CH149




#### 802.11ac (20MHz) / CH157



#### 802.11ac (40MHz) / CH151



#### 802.11ac (80MHz) / CH155




## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)


### 802.11a




### 802.11ac (20MHz)

**CH 149 5745 MHz**

**Horizontal**




**Vertical**




**CH 157 5785 MHz**

**Horizontal**




**Vertical**




**CH 165 5825 MHz**

**Horizontal**




**Vertical**




### 802.11ac (40MHz)

**CH 151 5755 MHz**

**Horizontal**




**Vertical**




**CH 159 5795 MHz**

**Horizontal**




**Vertical**




### 802.11ac (80MHz)

**CH 155 5775 MHz**

**Horizontal**



**Vertical**



## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---