

## FCC Test Report

**Report No.:** RF190725E05C

**FCC ID:** PY319300460

**Test Model:** EAX20

**Received Date:** Oct. 25, 2019

**Test Date:** Nov. 27 to 28, 2019

**Issued Date:** Dec. 10, 2019

**Applicant:** NETGEAR, Inc.

**Address:** 350 East Plumeria Drive San Jose, CA 95134

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**FCC Registration /  
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate of Conformity</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty.....	6
2.2 Modification Record.....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT.....	7
3.2 Description of Test Modes.....	10
3.2.1 Test Mode Applicability and Tested Channel Detail.....	11
3.3 Duty Cycle of Test Signal.....	13
3.4 Description of Support Units.....	14
3.4.1 Configuration of System under Test.....	14
3.5 General Description of Applied Standards and references.....	15
<b>4 Test Types and Results</b> .....	<b>16</b>
4.1 Radiated Emission and Bandedge Measurement.....	16
4.1.1 Limits of Radiated Emission and Bandedge Measurement.....	16
4.1.2 Test Instruments.....	17
4.1.3 Test Procedures.....	18
4.1.4 Deviation from Test Standard.....	18
4.1.5 Test Setup.....	19
4.1.6 EUT Operating Conditions.....	20
4.1.7 Test Results.....	21
4.2 Conducted Emission Measurement.....	35
4.2.1 Limits of Conducted Emission Measurement.....	35
4.2.2 Test Instruments.....	35
4.2.3 Test Procedures.....	36
4.2.4 Deviation from Test Standard.....	36
4.2.5 Test Setup.....	36
4.2.6 EUT Operating Conditions.....	36
4.2.7 Test Results.....	37
4.3 6dB Bandwidth Measurement.....	39
4.3.1 Limits of 6dB Bandwidth Measurement.....	39
4.3.2 Test Setup.....	39
4.3.3 Test Instruments.....	39
4.3.4 Test Procedure.....	39
4.3.5 Deviation from Test Standard.....	39
4.3.6 EUT Operating Conditions.....	39
4.3.7 Test Result.....	40
4.4 Conducted Output Power Measurement.....	42
4.4.1 Limits of Conducted Output Power Measurement.....	42
4.4.2 Test Setup.....	42
4.4.3 Test Instruments.....	42
4.4.4 Test Procedures.....	42
4.4.5 Deviation from Test Standard.....	42
4.4.6 EUT Operating Conditions.....	42
4.4.7 Test Results.....	43
4.5 Power Spectral Density Measurement.....	45
4.5.1 Limits of Power Spectral Density Measurement.....	45
4.5.2 Test Setup.....	45
4.5.3 Test Instruments.....	45
4.5.4 Test Procedure.....	45
4.5.5 Deviation from Test Standard.....	46
4.5.6 EUT Operating Condition.....	46

4.5.7 Test Results .....	47
4.6 Conducted Out of Band Emission Measurement.....	49
4.6.1 Limits of Conducted Out of Band Emission Measurement .....	49
4.6.2 Test Setup.....	49
4.6.3 Test Instruments .....	49
4.6.4 Test Procedure .....	49
4.6.5 Deviation from Test Standard .....	49
4.6.6 EUT Operating Condition .....	49
4.6.7 Test Results .....	49
<b>5 Pictures of Test Arrangements.....</b>	<b>58</b>
<b>Appendix – Information of the Testing Laboratories .....</b>	<b>59</b>

### Release Control Record

Issue No.	Description	Date Issued
RF190725E05C	Original release.	Dec. 10, 2019

## 1 Certificate of Conformity

**Product:** AX1800 Mesh Extender

**Brand:** NETGEAR

**Test Model:** EAX20

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** NETGEAR, Inc.

**Test Date:** Nov. 27 to 28, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Phoenix Huang , **Date:** Dec. 10, 2019  
Phoenix Huang / Specialist

**Approved by :** Clark Lin , **Date:** Dec. 10, 2019  
Clark Lin / Technical Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.66dB at 0.31406MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.2dB at 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

**Note:**

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.8 dB
Conducted emissions	-	3.1 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.0 dB
	30MHz ~ 1GHz	4.9 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.1 dB
	6GHz ~ 18GHz	4.9 dB
	18GHz ~ 40GHz	5.2 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	AX1800 Mesh Extender
Brand	NETGEAR
Test Model	EAX20
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	12Vdc from power adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in VHT20/40 mode 1024QAM for OFDM in 11ac mode 1024QAM for OFDMA in 11ax HE mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11 Mbps 802.11a/g: up to 54 Mbps 802.11n: up to 300 Mbps 802.11ac: up to 866.7 Mbps 802.11ax: up to 1201 Mbps
Operating Frequency	<b>2.4GHz:</b> 2.412 ~ 2.462 GHz <b>5GHz:</b> 5.18 ~ 5.24 GHz, 5.745 ~ 5.825 GHz
Number of Channel	<b>2.4GHz:</b> 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 <b>5GHz:</b> 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 9 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 4 802.11ac (VHT80), 802.11ax (HE80): 2
Output Power	<b>Non-Beamforming Mode:</b> <b>2.412 ~ 2.462 GHz:</b> 995.663 mW <b>5.18 ~ 5.24 GHz:</b> 880.125 mW <b>5.745 ~ 5.825 GHz:</b> 986.32 mW <b>Beamforming Mode:</b> <b>2.412 ~ 2.462 GHz:</b> 883.556 mW <b>5.18 ~ 5.24 GHz:</b> 876.053 mW <b>5.745 ~ 5.825 GHz:</b> 986.32 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x 1
Data Cable Supplied	NA

Note:

1. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	WLAN 5GHz

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

2. The EUT must be supplied one power adapter and following different models could be chosen as following table:

No.	Brand	Model No.	P/N	Spec.
1	NETGEAR	2ABL030F 1 NA	332-10758-01	Input: 100-120Vac, 1.0A, 50/60Hz Output: 12V, 2.5A DC Output cable: Unshielded, 1.8m
2	NETGEAR	AD2067F10	332-10797-01	Input: 100-120Vac, 1.0A, 50/60Hz Output: 12V, 2.5A DC Output cable: Unshielded, 1.8m

Note: From the above adapters, the AC Power Conducted Emissions and Radiated Emissions worse case was found in **Adapter 1**. Therefore only the test data of the mode was recorded in this report.

3. The antennas provided to the EUT, please refer to the following table:

Antenna No.	Transmitter Circuit	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
1	Chain 0	3.48	2.4~2.4835	PIFA	i-pex(MHF)
		2.56	5.15~5.25		
		2.56	5.25~5.35		
		2.58	5.47~5.725		
		3.03	5.725~5.85		
2	Chain 1	3.48	2.4~2.4835	PIFA	i-pex(MHF)
		2.56	5.15~5.25		
		2.56	5.25~5.35		
		2.58	5.47~5.725		
		3.03	5.725~5.85		

4. The EUT incorporates a MIMO function:

2.4GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11b	2TX	2RX
802.11g	2TX	2RX
802.11n (HT20)	2TX	2RX
802.11n (HT40)	2TX	2RX
VHT20	2TX	2RX
VHT40	2TX	2RX
802.11ax (HE20)	2TX	2RX
802.11ax (HE40)	2TX	2RX
5GHz Band		
MODULATION MODE	TX & RX CONFIGURATION	
802.11a	2TX	2RX
802.11n (HT20)	2TX	2RX
802.11n (HT40)	2TX	2RX
802.11ac (VHT20)	2TX	2RX
802.11ac (VHT40)	2TX	2RX
802.11ac (VHT80)	2TX	2RX
802.11ax (HE20)	2TX	2RX
802.11ax (HE40)	2TX	2RX
802.11ax (HE80)	2TX	2RX



Note:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
  2. The EUT support Beamforming and Non-Beamforming mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
  3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz), 802.11ac mode for 20MHz (40MHz) and 802.11ax mode for 20MHz (40MHz), therefore the manufacturer will control the power for 802.11n mode is the same as the 802.11ac or more lower than it and investigated worst case to representative mode in test report. (Final test mode refer to section 3.2.1)
5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	PLC	APCM	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE $<$ 1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

#### **Radiated Emission Test (Above 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

#### **Radiated Emission Test (Below 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11g	1 to 11	6	OFDM	BPSK	6Mb/s

#### **Power Line Conducted Emission Test:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11g	1 to 11	6	OFDM	BPSK	6Mb/s

**Antenna Port Conducted Measurement:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
VHT20 (Output power only)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40 (Output power only)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0
Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
VHT20 (Output power only)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40 (Output power only)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

**Test Condition:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	23deg. C, 64%RH	120Vac, 60Hz	Kevin Ko
RE $<$ 1G	25deg. C, 70%RH	120Vac, 60Hz	Kevin Ko
PLC	25deg. C, 75%RH	120Vac, 60Hz	Kevin Ko
APCM	25deg. C, 60%RH	120Vac, 60Hz	Jyunchun Lin

### 3.3 Duty Cycle of Test Signal

If duty cycle of test signal is  $\geq 98\%$ , duty factor is not required.

If duty cycle of test signal is  $< 98\%$ , duty factor shall be considered.


**802.11b:** Duty cycle = 12.45 ms/12.525 ms = 0.994

**802.11g:** Duty cycle = 2.063 ms/2.096 ms = 0.984


**802.11ax (HE20):** Duty cycle = 1.487 ms/1.522 ms = 0.977, Duty factor =  $10 * \log(1/\text{Duty cycle}) = 0.1$

**802.11ax (HE40):** Duty cycle = 0.769 ms/0.803 ms = 0.958, Duty factor =  $10 * \log(1/\text{Duty cycle}) = 0.19$


**802.11b**




**802.11g**



**802.11ax (HE20)**



**802.11ax (HE40)**



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ-45 Cable	1	10	No	0	Provided by Lab
2.	DC Cable	1	1.8	No	0	Supplied by client

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

**Test standard:**

**FCC Part 15, Subpart C (15.247)**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**References Test Guidance:**

**KDB 558074 D01 15.247 Meas Guidance v05r02**

**KDB 662911 D01 Multiple Transmitter Output v02r01**

All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**Note:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 03, 2019	July 02, 2020
Pre-Amplifier EMCI	EMC001340	980142	May 30, 2019	May 29, 2020
Loop Antenna Electro-Metrics	EM-6879	264	Jan. 22, 2019	Jan. 21, 2020
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 23, 2019	Oct. 22, 2020
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 11, 2019	Nov. 10, 2020
RF Cable	8D	966-4-1	Mar. 19, 2019	Mar. 18, 2020
RF Cable	8D	966-4-2	Mar. 19, 2019	Mar. 18, 2020
RF Cable	8D	966-4-3	Mar. 19, 2019	Mar. 18, 2020
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 26, 2019	Sep. 25, 2020
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Nov. 24, 2019	Nov. 23, 2020
Pre-Amplifier EMCI	EMC12630SE	980385	Aug. 15, 2019	Aug. 14, 2020
RF Cable	EMC104-SM-SM-1200	160923	Jan. 28, 2019	Jan. 27, 2020
RF Cable	104 RF cable	131215	Jan. 10, 2019	Jan. 09, 2020
RF Cable	EMC104-SM-SM-6000	180418	May 03, 2019	May 02, 2020
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 28, 2019	Jan. 27, 2020
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 24, 2019	Nov. 23, 2020
RF Cable	EMC102-KM-KM-1200	160924	Jan. 28, 2019	Jan. 27, 2020
RF Cable	EMC102-KM-KM-1200	160925	Jan. 28, 2019	Jan. 27, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 04, 2019	June 03, 2020
Power meter Anritsu	ML2495A	1014008	May 13, 2019	May 12, 2020
Power sensor Anritsu	MA2411B	0917122	May 13, 2019	May 12, 2020
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Nov. 27 to 28, 2019

#### 4.1.3 Test Procedures

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



**For Radiated emission above 1GHz**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

**4.1.6 EUT Operating Conditions**

- a. Connected the EUT with the Laptop which is placed on remote site.
- b. Controlling software (Mtool 3.1.0.1) has been activated to set the EUT under transmission condition continuously.

## 4.1.7 Test Results

## Above 1GHz Data:

## 802.11b

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	1.49 H	215	59.5	-1.6
2	2390.00	45.0 AV	54.0	-9.0	1.49 H	215	46.6	-1.6
3	*2412.00	114.7 PK			1.49 H	215	116.4	-1.7
4	*2412.00	112.2 AV			1.49 H	215	113.9	-1.7
5	4824.00	42.8 PK	74.0	-31.2	2.47 H	331	40.5	2.3
6	4824.00	35.8 AV	54.0	-18.2	2.47 H	331	33.5	2.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2312.90	56.5 PK	74.0	-17.5	1.48 V	268	58.0	-1.5
2	2312.90	48.4 AV	54.0	-5.6	1.48 V	268	49.9	-1.5
3	2390.00	61.5 PK	74.0	-12.5	1.48 V	268	63.1	-1.6
4	2390.00	50.5 AV	54.0	-3.5	1.48 V	268	52.1	-1.6
5	*2412.00	121.8 PK			1.48 V	268	123.5	-1.7
6	*2412.00	119.6 AV			1.48 V	268	121.3	-1.7
7	4824.00	42.8 PK	74.0	-31.2	2.53 V	157	40.5	2.3
8	4824.00	39.5 AV	54.0	-14.5	2.53 V	157	37.2	2.3

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	1.42 H	166	58.8	-1.6
2	2390.00	44.1 AV	54.0	-9.9	1.42 H	166	45.7	-1.6
3	*2437.00	114.2 PK			1.42 H	166	116.0	-1.8
4	*2437.00	112.5 AV			1.42 H	166	114.3	-1.8
5	2483.50	58.1 PK	74.0	-15.9	1.42 H	166	59.8	-1.7
6	2483.50	45.2 AV	54.0	-8.8	1.42 H	166	46.9	-1.7
7	4874.00	41.6 PK	74.0	-32.4	1.33 H	346	39.2	2.4
8	4874.00	35.4 AV	54.0	-18.6	1.33 H	346	33.0	2.4
9	7311.00	43.3 PK	74.0	-30.7	1.02 H	108	34.1	9.2
10	7311.00	32.3 AV	54.0	-21.7	1.02 H	108	23.1	9.2

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2337.80	60.4 PK	74.0	-13.6	1.50 V	165	62.0	-1.6
2	2337.80	49.0 AV	54.0	-5.0	1.50 V	165	50.6	-1.6
3	2390.00	60.8 PK	74.0	-13.2	1.50 V	165	62.4	-1.6
4	2390.00	49.2 AV	54.0	-4.8	1.50 V	165	50.8	-1.6
5	*2437.00	121.6 PK			1.50 V	165	123.4	-1.8
6	*2437.00	119.4 AV			1.50 V	165	121.2	-1.8
7	2483.50	61.2 PK	74.0	-12.8	1.50 V	165	62.9	-1.7
8	2483.50	48.8 AV	54.0	-5.2	1.50 V	165	50.5	-1.7
9	4874.00	43.2 PK	74.0	-30.8	1.58 V	9	40.8	2.4
10	4874.00	39.4 AV	54.0	-14.6	1.58 V	9	37.0	2.4
11	7311.00	43.6 PK	74.0	-30.4	1.61 V	14	34.4	9.2
12	7311.00	31.7 AV	54.0	-22.3	1.61 V	14	22.5	9.2

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.9 PK			2.62 H	165	116.7	-1.8
2	*2462.00	113.1 AV			2.62 H	165	114.9	-1.8
3	2483.50	58.7 PK	74.0	-15.3	2.62 H	165	60.4	-1.7
4	2483.50	45.2 AV	54.0	-8.8	2.62 H	165	46.9	-1.7
5	4924.00	42.1 PK	74.0	-31.9	1.77 H	150	39.6	2.5
6	4924.00	36.3 AV	54.0	-17.7	1.77 H	150	33.8	2.5
7	7386.00	44.4 PK	74.0	-29.6	1.55 H	106	35.0	9.4
8	7386.00	32.1 AV	54.0	-21.9	1.55 H	106	22.7	9.4

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2361.30	62.3 PK	74.0	-11.7	1.35 V	116	63.9	-1.6
2	2361.30	53.5 AV	54.0	-0.5	1.35 V	116	55.1	-1.6
3	2390.00	61.8 PK	74.0	-12.2	1.35 V	116	63.4	-1.6
4	<b>2390.00</b>	<b>53.8 AV</b>	<b>54.0</b>	<b>-0.2</b>	<b>1.35 V</b>	<b>116</b>	<b>55.4</b>	<b>-1.6</b>
5	*2462.00	122.4 PK			1.35 V	116	124.2	-1.8
6	*2462.00	120.1 AV			1.35 V	116	121.9	-1.8
7	2483.50	63.9 PK	74.0	-10.1	1.35 V	116	65.6	-1.7
8	2483.50	50.9 AV	54.0	-3.1	1.35 V	116	52.6	-1.7
9	4924.00	43.9 PK	74.0	-30.1	1.45 V	30	41.4	2.5
10	4924.00	40.3 AV	54.0	-13.7	1.45 V	30	37.8	2.5
11	7386.00	43.6 PK	74.0	-30.4	1.53 V	68	34.2	9.4
12	7386.00	32.4 AV	54.0	-21.6	1.53 V	68	23.0	9.4

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

**802.11g**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.1 PK	74.0	-5.9	2.22 H	171	69.7	-1.6
2	2390.00	46.7 AV	54.0	-7.3	2.22 H	171	48.3	-1.6
3	*2412.00	111.5 PK			2.22 H	171	113.2	-1.7
4	*2412.00	101.4 AV			2.22 H	171	103.1	-1.7
5	4824.00	41.6 PK	74.0	-32.4	1.53 H	14	39.3	2.3
6	4824.00	35.9 AV	54.0	-18.1	1.53 H	14	33.6	2.3

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.3 PK	74.0	-0.7	1.26 V	118	74.9	-1.6
2	2390.00	51.9 AV	54.0	-2.1	1.26 V	118	53.5	-1.6
3	*2412.00	118.2 PK			1.26 V	118	119.9	-1.7
4	*2412.00	108.3 AV			1.26 V	118	110.0	-1.7
5	4824.00	43.2 PK	74.0	-30.8	1.22 V	61	40.9	2.3
6	4824.00	39.5 AV	54.0	-14.5	1.22 V	61	37.2	2.3

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.



<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.1 PK	74.0	-7.9	2.66 H	251	67.7	-1.6
2	2390.00	46.7 AV	54.0	-7.3	2.66 H	251	48.3	-1.6
3	*2437.00	115.3 PK			2.66 H	251	117.1	-1.8
4	*2437.00	105.2 AV			2.66 H	251	107.0	-1.8
5	2483.50	68.4 PK	74.0	-5.6	2.66 H	251	70.1	-1.7
6	2483.50	47.8 AV	54.0	-6.2	2.66 H	251	49.5	-1.7
7	4874.00	42.0 PK	74.0	-32.0	1.27 H	152	39.6	2.4
8	4874.00	35.9 AV	54.0	-18.1	1.27 H	152	33.5	2.4
9	7311.00	44.9 PK	74.0	-29.1	1.93 H	151	35.7	9.2
10	7311.00	32.5 AV	54.0	-21.5	1.93 H	151	23.3	9.2

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.4 PK	74.0	-2.6	1.52 V	251	73.0	-1.6
2	2390.00	51.4 AV	54.0	-2.6	1.52 V	251	53.0	-1.6
3	*2437.00	122.6 PK			1.52 V	251	124.4	-1.8
4	*2437.00	112.5 AV			1.52 V	251	114.3	-1.8
5	2483.50	73.6 PK	74.0	-0.4	1.52 V	251	75.3	-1.7
6	2483.50	52.6 AV	54.0	-1.4	1.52 V	251	54.3	-1.7
7	4874.00	43.4 PK	74.0	-30.6	2.42 V	234	41.0	2.4
8	4874.00	40.4 AV	54.0	-13.6	2.42 V	234	38.0	2.4
9	7311.00	42.9 PK	74.0	-31.1	1.56 V	12	33.7	9.2
10	7311.00	32.3 AV	54.0	-21.7	1.56 V	12	23.1	9.2

**REMARKS:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- Margin value = Emission Level – Limit value
- The other emission levels were very low against the limit.
- " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.5 PK			2.42 H	344	112.3	-1.8
2	*2462.00	100.4 AV			2.42 H	344	102.2	-1.8
3	2483.50	68.7 PK	74.0	-5.3	2.42 H	344	70.4	-1.7
4	2483.50	45.9 AV	54.0	-8.1	2.42 H	344	47.6	-1.7
5	4924.00	41.5 PK	74.0	-32.5	2.65 H	158	39.0	2.5
6	4924.00	36.1 AV	54.0	-17.9	2.65 H	158	33.6	2.5
7	7386.00	44.0 PK	74.0	-30.0	1.31 H	150	34.6	9.4
8	7386.00	32.2 AV	54.0	-21.8	1.31 H	150	22.8	9.4

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	117.9 PK			1.33 V	115	119.7	-1.8
2	*2462.00	107.8 AV			1.33 V	115	109.6	-1.8
3	2483.50	73.2 PK	74.0	-0.8	1.33 V	115	74.9	-1.7
4	2483.50	50.3 AV	54.0	-3.7	1.33 V	115	52.0	-1.7
5	4924.00	43.4 PK	74.0	-30.6	2.37 V	298	40.9	2.5
6	4924.00	39.9 AV	54.0	-14.1	2.37 V	298	37.4	2.5
7	7386.00	42.7 PK	74.0	-31.3	2.38 V	153	33.3	9.4
8	7386.00	32.5 AV	54.0	-21.5	2.38 V	153	23.1	9.4

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

**802.11ax (HE20)**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.2 PK	74.0	-5.8	1.92 H	262	69.8	-1.6
2	2390.00	46.4 AV	54.0	-7.6	1.92 H	262	48.0	-1.6
3	*2412.00	111.8 PK			1.92 H	262	113.5	-1.7
4	*2412.00	99.5 AV			1.92 H	262	101.2	-1.7
5	4824.00	42.1 PK	74.0	-31.9	2.68 H	173	39.8	2.3
6	4824.00	35.5 AV	54.0	-18.5	2.68 H	173	33.2	2.3

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.5 PK	74.0	-0.5	1.20 V	111	75.1	-1.6
2	2390.00	51.4 AV	54.0	-2.6	1.20 V	111	53.0	-1.6
3	*2412.00	118.9 PK			1.20 V	111	120.6	-1.7
4	*2412.00	106.4 AV			1.20 V	111	108.1	-1.7
5	4824.00	43.1 PK	74.0	-30.9	2.50 V	339	40.8	2.3
6	4824.00	40.6 AV	54.0	-13.4	2.50 V	339	38.3	2.3

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.9 PK	74.0	-7.1	1.15 H	291	68.5	-1.6
2	2390.00	48.1 AV	54.0	-5.9	1.15 H	291	49.7	-1.6
3	*2437.00	117.6 PK			1.15 H	291	119.4	-1.8
4	*2437.00	104.2 AV			1.15 H	291	106.0	-1.8
5	2483.50	69.5 PK	74.0	-4.5	1.15 H	291	71.2	-1.7
6	2483.50	49.2 AV	54.0	-4.8	1.15 H	291	50.9	-1.7
7	4874.00	42.3 PK	74.0	-31.7	1.54 H	58	39.9	2.4
8	4874.00	35.4 AV	54.0	-18.6	1.54 H	58	33.0	2.4
9	7311.00	44.0 PK	74.0	-30.0	1.90 H	147	34.8	9.2
10	7311.00	32.5 AV	54.0	-21.5	1.90 H	147	23.3	9.2

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.2 PK	74.0	-2.8	1.62 V	238	72.8	-1.6
2	2390.00	53.6 AV	54.0	-0.4	1.62 V	238	55.2	-1.6
3	*2437.00	124.1 PK			1.62 V	238	125.9	-1.8
4	*2437.00	111.5 AV			1.62 V	238	113.3	-1.8
5	2483.50	73.0 PK	74.0	-1.0	1.62 V	238	74.7	-1.7
6	2483.50	53.5 AV	54.0	-0.5	1.62 V	238	55.2	-1.7
7	4874.00	43.6 PK	74.0	-30.4	2.13 V	351	41.2	2.4
8	4874.00	39.3 AV	54.0	-14.7	2.13 V	351	36.9	2.4
9	7311.00	43.5 PK	74.0	-30.5	2.51 V	263	34.3	9.2
10	7311.00	32.6 AV	54.0	-21.4	2.51 V	263	23.4	9.2

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.6 PK			2.02 H	278	112.4	-1.8
2	*2462.00	97.5 AV			2.02 H	278	99.3	-1.8
3	2483.50	68.1 PK	74.0	-5.9	2.02 H	278	69.8	-1.7
4	2483.50	44.2 AV	54.0	-9.8	2.02 H	278	45.9	-1.7
5	4924.00	41.8 PK	74.0	-32.2	1.06 H	185	39.3	2.5
6	4924.00	35.9 AV	54.0	-18.1	1.06 H	185	33.4	2.5
7	7386.00	44.1 PK	74.0	-29.9	1.99 H	197	34.7	9.4
8	7386.00	31.7 AV	54.0	-22.3	1.99 H	197	22.3	9.4

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	117.9 PK			1.35 V	115	119.7	-1.8
2	*2462.00	105.1 AV			1.35 V	115	106.9	-1.8
3	2483.50	73.3 PK	74.0	-0.7	1.35 V	115	75.0	-1.7
4	2483.50	49.3 AV	54.0	-4.7	1.35 V	115	51.0	-1.7
5	4924.00	43.4 PK	74.0	-30.6	1.82 V	52	40.9	2.5
6	4924.00	39.7 AV	54.0	-14.3	1.82 V	52	37.2	2.5
7	7386.00	42.3 PK	74.0	-31.7	2.21 V	243	32.9	9.4
8	7386.00	31.6 AV	54.0	-22.4	2.21 V	243	22.2	9.4

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

**802.11ax (HE40)**

<b>CHANNEL</b>	TX Channel 3	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.2 PK	74.0	-13.8	1.17 H	335	61.8	-1.6
2	2390.00	49.3 AV	54.0	-4.7	1.17 H	335	50.9	-1.6
3	*2422.00	105.9 PK			1.17 H	335	107.6	-1.7
4	*2422.00	66.1 AV			1.17 H	335	67.8	-1.7
5	4844.00	41.5 PK	74.0	-32.5	1.33 H	282	39.3	2.2
6	4844.00	36.7 AV	54.0	-17.3	1.33 H	282	34.5	2.2
7	7266.00	44.3 PK	74.0	-29.7	1.25 H	37	35.3	9.0
8	7266.00	32.1 AV	54.0	-21.9	1.25 H	37	23.1	9.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.4 PK	74.0	-8.6	1.00 V	116	67.0	-1.6
2	2390.00	53.5 AV	54.0	-0.5	1.00 V	116	55.1	-1.6
3	*2422.00	113.2 PK			1.00 V	116	114.9	-1.7
4	*2422.00	102.3 AV			1.00 V	116	104.0	-1.7
5	4844.00	42.9 PK	74.0	-31.1	1.30 V	30	40.7	2.2
6	4844.00	39.6 AV	54.0	-14.4	1.30 V	30	37.4	2.2
7	7266.00	42.2 PK	74.0	-31.8	2.49 V	314	33.2	9.0
8	7266.00	32.6 AV	54.0	-21.4	2.49 V	314	23.6	9.0

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.2 PK	74.0	-5.8	1.38 H	28	69.8	-1.6
2	2390.00	49.3 AV	54.0	-4.7	1.38 H	28	50.9	-1.6
3	*2437.00	110.4 PK			1.38 H	28	112.2	-1.8
4	*2437.00	99.2 AV			1.38 H	28	101.0	-1.8
5	2483.50	69.1 PK	74.0	-4.9	1.38 H	28	70.8	-1.7
6	2483.50	48.7 AV	54.0	-5.3	1.38 H	28	50.4	-1.7
7	4874.00	41.4 PK	74.0	-32.6	1.24 H	25	39.0	2.4
8	4874.00	35.9 AV	54.0	-18.1	1.24 H	25	33.5	2.4
9	7311.00	44.0 PK	74.0	-30.0	2.19 H	165	34.8	9.2
10	7311.00	32.0 AV	54.0	-22.0	2.19 H	165	22.8	9.2

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.0 PK	74.0	-3.0	1.07 V	118	72.6	-1.6
2	2390.00	53.8 AV	54.0	-0.2	1.07 V	118	55.4	-1.6
3	*2437.00	117.7 PK			1.07 V	118	119.5	-1.8
4	*2437.00	106.4 AV			1.07 V	118	108.2	-1.8
5	2483.50	72.4 PK	74.0	-1.6	1.07 V	118	74.1	-1.7
6	2483.50	52.7 AV	54.0	-1.3	1.07 V	118	54.4	-1.7
7	4874.00	42.9 PK	74.0	-31.1	2.39 V	322	40.5	2.4
8	4874.00	39.3 AV	54.0	-14.7	2.39 V	322	36.9	2.4
9	7311.00	43.4 PK	74.0	-30.6	1.48 V	8	34.2	9.2
10	7311.00	31.8 AV	54.0	-22.2	1.48 V	8	22.6	9.2

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 9	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	108.5 PK			1.56 H	131	110.3	-1.8
2	*2452.00	98.7 AV			1.56 H	131	100.5	-1.8
3	2483.50	65.7 PK	74.0	-8.3	1.56 H	131	67.4	-1.7
4	2483.50	52.9 AV	54.0	-1.1	1.56 H	131	54.6	-1.7
5	4904.00	42.4 PK	74.0	-31.6	2.58 H	331	39.9	2.5
6	4904.00	35.9 AV	54.0	-18.1	2.58 H	331	33.4	2.5
7	7356.00	44.7 PK	74.0	-29.3	1.61 H	232	35.5	9.2
8	7356.00	31.6 AV	54.0	-22.4	1.61 H	232	22.4	9.2

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	115.6 PK			1.39 V	115	117.4	-1.8
2	*2452.00	104.2 AV			1.39 V	115	106.0	-1.8
3	2483.50	70.6 PK	74.0	-3.4	1.39 V	115	72.3	-1.7
4	2483.50	53.6 AV	54.0	-0.4	1.39 V	115	55.3	-1.7
5	4904.00	42.5 PK	74.0	-31.5	1.20 V	50	40.0	2.5
6	4904.00	40.0 AV	54.0	-14.0	1.20 V	50	37.5	2.5
7	7356.00	43.3 PK	74.0	-30.7	1.90 V	236	34.1	9.2
8	7356.00	31.7 AV	54.0	-22.3	1.90 V	236	22.5	9.2

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.



Below 1GHz Data:

802.11g


<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9kHz ~ 1GHz		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	32.84	30.8 QP	40.0	-9.2	4.00 H	54	39.9	-9.1
2	80.27	28.6 QP	40.0	-11.4	2.00 H	272	41.4	-12.8
3	138.13	29.7 QP	43.5	-13.8	2.00 H	60	38.1	-8.4
4	155.83	32.5 QP	43.5	-11.0	2.00 H	254	40.3	-7.8
5	179.82	32.3 QP	43.5	-11.2	2.00 H	263	41.6	-9.3
6	750.01	37.0 QP	46.0	-9.0	1.00 H	228	33.3	3.7

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.23	30.2 QP	40.0	-9.8	1.00 V	0	39.3	-9.1
2	44.36	29.7 QP	40.0	-10.3	1.00 V	175	37.8	-8.1
3	51.19	33.2 QP	40.0	-6.8	1.00 V	139	41.2	-8.0
4	79.13	35.9 QP	40.0	-4.1	3.00 V	360	48.4	-12.5
5	94.50	34.5 QP	43.5	-9.0	1.00 V	244	47.6	-13.1
6	875.02	36.4 QP	46.0	-9.6	2.00 V	0	31.1	5.3

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 23, 2019	Oct. 22, 2020
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 17, 2019	Mar. 16, 2020
50 ohms Terminator	50	3	Oct. 23, 2019	Oct. 22, 2020
RF Cable	5D-FB	COCCAB-001	Sep. 27, 2019	Sep. 26, 2020
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 14, 2019	Mar. 13, 2020
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: Nov. 28, 2019

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.


#### 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.99	34.91	21.39	44.90	31.38	65.79	55.79	-20.89	-24.41
2	0.18906	9.99	31.53	22.57	41.52	32.56	64.08	54.08	-22.56	-21.52
3	0.23594	9.99	30.03	21.61	40.02	31.60	62.24	52.24	-22.22	-20.64
4	0.28672	9.99	34.99	28.46	44.98	38.45	60.62	50.62	-15.64	-12.17
5	0.30625	10.00	36.29	28.43	46.29	38.43	60.07	50.07	-13.78	-11.64
6	0.36875	10.00	21.22	10.74	31.22	20.74	58.53	48.53	-27.31	-27.79

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	9.99	35.38	24.24	45.37	34.23	65.58	55.58	-20.21	-21.35
2	0.18906	9.99	31.07	22.43	41.06	32.42	64.08	54.08	-23.02	-21.66
3	0.20859	9.99	29.75	20.62	39.74	30.61	63.26	53.26	-23.52	-22.65
4	0.24375	9.99	30.88	21.61	40.87	31.60	61.97	51.97	-21.10	-20.37
<b>5</b>	<b>0.31406</b>	<b>10.00</b>	<b>37.77</b>	<b>32.20</b>	<b>47.77</b>	<b>42.20</b>	<b>59.86</b>	<b>49.86</b>	<b>-12.09</b>	<b>-7.66</b>
6	10.52734	10.61	7.97	1.94	18.58	12.55	60.00	50.00	-41.42	-37.45

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

##### 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	7.11	7.10	0.5	Pass
6	2437	7.06	7.10	0.5	Pass
11	2462	7.13	7.11	0.5	Pass

##### 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.45	16.46	0.5	Pass
6	2437	16.42	16.43	0.5	Pass
11	2462	16.41	16.44	0.5	Pass

##### 802.11ax (HE20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	19.07	19.05	0.5	Pass
6	2437	19.02	19.05	0.5	Pass
11	2462	19.10	19.07	0.5	Pass


##### 802.11ax (HE40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	37.75	37.21	0.5	Pass
6	2437	37.87	37.30	0.5	Pass
9	2452	37.79	37.52	0.5	Pass




Spectrum Plot of Worst Value


802.11b\_Chain 0 / CH6




802.11g\_Chain 0 / CH11



802.11ax (HE20)\_Chain 0 / CH6



802.11ac (HE40)\_Chain 1 / CH3



## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;

Array Gain =  $5 \log(N_{ANT}/N_{SS})$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(N_{ANT}/N_{SS})$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

#### 4.4.7 Test Results

#### Non-Beamforming Mode

##### 802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	26.81	26.92	971.773	29.88	30	Pass
6	2437	26.88	26.95	982.978	29.93	30	Pass
11	2462	26.74	26.89	960.715	29.83	30	Pass

##### 802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	21.66	20.51	259.015	24.13	30	Pass
6	2437	27.19	26.74	995.663	29.98	30	Pass
11	2462	21.61	21.42	283.553	24.53	30	Pass

##### VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	20.15	19.25	187.654	22.73	30	Pass
6	2437	26.94	26.17	908.311	29.58	30	Pass
11	2462	20.44	20.15	214.176	23.31	30	Pass

##### VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.76	17.19	112.064	20.49	30	Pass
6	2437	21.90	21.42	293.558	24.68	30	Pass
9	2452	19.89	19.68	190.396	22.80	30	Pass

##### 802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	20.36	19.44	196.545	22.93	30	Pass
6	2437	27.13	26.38	950.926	29.78	30	Pass
11	2462	20.61	20.09	217.174	23.37	30	Pass

##### 802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.97	17.38	117.363	20.70	30	Pass
6	2437	22.08	21.63	306.982	24.87	30	Pass
9	2452	20.08	19.89	199.358	23.00	30	Pass

## Beamforming Mode

### VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	20.15	19.25	187.654	22.73	29.51	Pass
6	2437	26.68	25.86	851.064	29.30	29.51	Pass
11	2462	20.44	20.15	214.176	23.31	29.51	Pass

Note: The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$  , so the power limit shall be reduced to  $30 - (6.49 - 6) = 29.51 \text{ dBm}$ .

### VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.76	17.19	112.064	20.49	29.51	Pass
6	2437	21.90	21.42	293.558	24.68	29.51	Pass
9	2452	19.89	19.68	190.396	22.80	29.51	Pass

Note: The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$  , so the power limit shall be reduced to  $30 - (6.49 - 6) = 29.51 \text{ dBm}$ .

### 802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	20.36	19.44	196.545	22.93	29.51	Pass
6	2437	26.82	26.05	883.556	29.46	29.51	Pass
11	2462	20.61	20.09	217.174	23.37	29.51	Pass

Note: The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$  , so the power limit shall be reduced to  $30 - (6.49 - 6) = 29.51 \text{ dBm}$ .

### 802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.97	17.38	117.363	20.70	29.51	Pass
6	2437	22.08	21.63	306.982	24.87	29.51	Pass
9	2452	20.08	19.89	199.358	23.00	29.51	Pass


Note: The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$  , so the power limit shall be reduced to  $30 - (6.49 - 6) = 29.51 \text{ dBm}$ .

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

#### For 802.11b, 802.11g

- a. Set instrument center frequency to DTS channel center frequency.
- b. Set span to at least 1.5 times the OBW.
- c. Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = power averaging (RMS) or sample detector (when RMS not available).
- f. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g. Sweep time = auto couple.
- h. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i. Use the peak marker function to determine the maximum amplitude level.

#### For 802.11ax (HE20), 802.11ax (HE40)

- a. Measure the duty cycle (x).
- b. Set instrument center frequency to DTS channel center frequency.
- c. Set span to at least 1.5 times the OBW.
- d. Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- e. Set VBW  $\geq 3 \times \text{RBW}$ .
- f. Detector = power averaging (RMS) or sample detector (when RMS not available).
- g. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- h. Sweep time = auto couple.
- i. Do not use sweep triggering. Allow sweep to "free run".
- j. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k. Use the peak marker function to determine the maximum amplitude level.
- l. Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

#### 4.5.5 Deviation from Test Standard

No deviation.

#### 4.5.6 EUT Operating Condition

Same as Item 4.3.6

#### 4.5.7 Test Results

##### 802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-2.93	3.01	0.08	7.51	Pass
	6	2437	-3.43	3.01	-0.42	7.51	Pass
	11	2462	-3.14	3.01	-0.13	7.51	Pass
1	1	2412	-4.07	3.01	-1.06	7.51	Pass
	6	2437	-2.61	3.01	0.40	7.51	Pass
	11	2462	-3.72	3.01	-0.71	7.51	Pass

Note: The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$ , so the power density limit shall be reduced to  $8 - (6.49 - 6) = 7.51 \text{ dBm}$ .

##### 802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-9.84	3.01	-6.83	7.51	Pass
	6	2437	-4.23	3.01	-1.22	7.51	Pass
	11	2462	-8.35	3.01	-5.34	7.51	Pass
1	1	2412	-10.86	3.01	-7.85	7.51	Pass
	6	2437	-3.59	3.01	-0.58	7.51	Pass
	11	2462	-9.01	3.01	-6.00	7.51	Pass

Note: The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$ , so the power density limit shall be reduced to  $8 - (6.49 - 6) = 7.51 \text{ dBm}$ .

##### 802.11ax (HE20)


TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-12.62	3.01	0.10	-9.51	7.51	Pass
	6	2437	-5.25	3.01	0.10	-2.14	7.51	Pass
	11	2462	-12.08	3.01	0.10	-8.97	7.51	Pass
1	1	2412	-12.94	3.01	0.10	-9.83	7.51	Pass
	6	2437	-5.78	3.01	0.10	-2.67	7.51	Pass
	11	2462	-12.75	3.01	0.10	-9.64	7.51	Pass

- Note:
1. The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$ , so the power density limit shall be reduced to  $8 - (6.49 - 6) = 7.51 \text{ dBm}$ .
  2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11ax (HE40)

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-16.77	3.01	0.19	-13.57	7.51	Pass
	6	2437	-12.80	3.01	0.19	-9.60	7.51	Pass
	9	2452	-14.32	3.01	0.19	-11.12	7.51	Pass
1	3	2422	-18.48	3.01	0.19	-15.28	7.51	Pass
	6	2437	-13.81	3.01	0.19	-10.61	7.51	Pass
	9	2452	-15.21	3.01	0.19	-12.01	7.51	Pass

- Note:
- The directional gain =  $3.48 \text{ dBi} + 10\log(2) = 6.49 \text{ dBi} > 6 \text{ dBi}$ , so the power density limit shall be reduced to  $8 - (6.49 - 6) = 7.51 \text{ dBm}$ .
  - Refer to section 3.3 for duty cycle spectrum plot.






## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.6.5 Deviation from Test Standard

No deviation.


### 4.6.6 EUT Operating Condition

Same as Item 4.3.6


### 4.6.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b




Chain 0




### Chain 1


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




802.11g

**Maximum REF**




Chain 0


**CH 1**




**CH 6**




**CH 11**



**CH 1 Band edge**




**CH 11 Band edge**




### Chain 1



#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




# 802.11ax (HE20)

## Maximum REF




## Chain 0


### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




### Chain 1


#### CH 1




#### CH 6




#### CH 11




#### CH 1 Band edge



#### CH 11 Band edge




# 802.11ax (HE40)




## Chain 0


### CH 3



### CH 6




### CH 9




### CH 9 Band edge



### CH 3 Band edge




### CH 9 Band edge






### Chain 1



#### CH 3




#### CH 6




#### CH 9



#### CH 3 Band edge



#### CH 9 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---