REV	DESCRIPTION OF	REVISION		ENG APPD	DATE
01	INITIAL DOCUMENT CI	REATION		R HU	230CT19
	Model: RAX	45 http://www.routeflogin.net	ERIAL		
	This device complies to the following two- interference, and (2)	conductors: (1) this device must accept any interference received, ReadyShare Access on Windows: PASSWORD N	IAC		
	Input:12V === 2 NETGEAR' &	.5A U G 1 2 3 4 USB (m) (m) (m) (m)			
NOTE:		DC-00093 FOR COLOR TOLERANCES.			
	COLOR IS SHOWN TO THE		Pantone	e Cool Gray 1C	
3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT. Black					
4. MAC & SERIAL NUMBERS TO BE PRINTED BY THE ODM.					
5. See NTGR DOC-00112 for SN standard.					
NTGR SN and MAC address barcode to be encoded AIM USS Code39 and include printed characters below barcodes.					
	RE COUNTRY OF ORIGIN	IS CORRECT			
A. IF COUNTRY OF ORIGIN IS PRE-PRINTED, UNHIDE THE APPROPRIATE COUNTRY OF ORIGIN LAYER AND INCLUDE COUNTRY OF ORIGIN ON LABEL.					
	COUNTRY OF ORIGIN IS	POST-PRINTED USING A THERMAL PRINTER (OR EQUIVALENT), RK (USE LAYERS).			
AUTHOR:		TITLE:			
SHEET:	AHAN	AW, PLBL, RAX45NA, V1	P/N:	NETGE	A R
=	1 of 1	THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.		AW-14468-01	01