

## RF Exposure Report

**Report No.:** SA191030C05

**FCC ID:** PY319400468

**Contains FCC ID:** XMR202002EG18NA

**Test Model:** LBR20

**Received Date:** Oct. 30, 2019

**Test Date:** Feb. 12 ~ Mar. 13, 2020

**Issued Date:** Apr. 17, 2020

**Applicant:** NETGEAR, INC.

**Address:** 350 East Plumeria Drive San Jose, CA 95134

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, TAIWAN

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
<b>3 Calculation Result of Maximum Conducted Power</b> .....	<b>6</b>

### Release Control Record

Issue No.	Description	Date Issued
SA191030C05	Original release.	Apr. 17, 2020

## 1 Certificate of Conformity

**Product:** ORBI LTE Router LBR20

**Brand:** NETGEAR

**Test Model:** LBR20

**Sample Status:** Engineering Sample

**Applicant:** NETGEAR, INC.

**Date of Evaluation:** Feb. 12 ~ Mar. 13, 2020

**Standards:** FCC Part 2 (Section 2.1091)

**References Test** KDB 447498 D01 General RF Exposure Guidance v06

**Guidance:**  
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :**  , **Date:** Apr. 17, 2020  
Polly Chien / Specialist

**Approved by :**  , **Date:** Apr. 17, 2020  
Bruce Chen / Senior Project Engineer

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Output Power EIRP (dBm)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WCDMA Band 2	24.3	20	0.054	1
WCDMA Band 4	24.9	20	0.061	1
LTE Band 2	24.5	20	0.056	1
LTE Band 4	25.2	20	0.066	1
LTE Band 7	24.7	20	0.059	1
LTE Band 25	24.6	20	0.057	1
LTE Band 30	22.9	20	0.039	1
LTE Band 41	24.5	20	0.056	1
LTE Band 66	24.7	20	0.059	1
LTE Band 7C	25.5	20	0.071	1
LTE Band 41C	25.4	20	0.069	1

Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WCDMA Band 5	20.4	22.55	20	0.036	0.55
LTE Band 5	20.4	22.55	20	0.036	0.55
LTE Band 26 (Part 22)	20.8	22.95	20	0.039	0.55
LTE Band 12	21.0	23.15	20	0.041	0.47
LTE Band 13	20.6	22.75	20	0.037	0.52
LTE Band 14	20.6	22.75	20	0.037	0.53
LTE Band 25	24.6	26.75	20	0.094	1
LTE Band 26 (Part 90)	21.3	23.45	20	0.044	0.54

EIRP = ERP + 2.15dB

Frequency Band (MHz)	Max. AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
<b>CDD mode:</b>					
2412-2462	24.96	4.33	20	0.169	1
5180-5240	23.40	6.38	20	0.189	1
5745-5825	27.72	5.82	20	0.449	1
<b>Beamforming Mode</b>					
2412-2462	24.29	4.33	20	0.145	1
5180-5240	23.32	6.38	20	0.186	1
5745-5825	27.72	5.82	20	0.449	1

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. 2.4GHz & 5GHz & WWAN technology can transmit at same time.

For antenna gain:

WLAN:

Ant. Type	Dipole		
Connector	i-pex(MHF)		
Band	2.4GHz	5GHz Band 1	5GHz Band 4
Directional Gain (dBi)	4.33	6.38	5.82

WWAN:

Ant. Type	Ant 1 & Ant 2: Monopole Ant 5 & Ant 6: PCB				
Connector	Ant 1 & Ant 2: I-Pex Ant 5 & Ant 6: I-Pex				
Function	Frequency (MHz)	Antenna Gain (dBi)			
		Ant 1 (TX/RX)	Ant 2 (RX)	Ant 5 (RX)	Ant 6 (RX)
WCDMA Band 2	1850~1910	1.8	2.7	N/A	N/A
WCDMA Band 4	1710~1755	1.6	1.6	N/A	N/A
WCDMA Band 5	824~849	5.8	6.2	N/A	N/A
LTE Band 2	1850~1910	1.8	2.7	1.6	2.4
LTE Band 4	1710~1755	1.6	1.6	2.5	0.5
LTE Band 5	824~849	5.8	6.2	N/A	N/A
LTE Band 7	2500~2570	3.3	2.4	2.5	2
LTE Band 12	698~716	4.5	4.5	N/A	N/A
LTE Band 13	777~787	6.5	6.8	N/A	N/A
LTE Band 14	788~798	6.8	7.1	N/A	N/A
LTE Band 25	1850 ~1915	1.6	2.3	2.2	2.8
LTE Band 26	814 ~849	6	6.4	N/A	N/A
LTE Band 30	2305 ~2315	3.4	1.4	N/A	N/A
LTE Band 41	2496~2690	3.8	1.8	N/A	N/A
LTE Band 66	1710 ~1780	1.3	2	2.6	0.8

**Conclusion:**

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WWAN + WLAN 2.4GHz+WLAN 5GHz = 0.094/1 + 0.169/1 + 0.449/1 =0.712$$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---