

FCC Test Report

Report No.: RF191129E09D

FCC ID: PY319400470

Test Model: RBR750

Series Model: RBS750

Received Date: May 08, 2020

Test Date: May 11, 2020

Issued Date: June 01, 2020

Applicant: NETGEAR, Inc.

Address: 350 East Plumeria Drive, San Jose, CA 95134, USA

- **Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
- Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan
- **Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan.

FCC Registration / 723255 / TW2022 Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specification, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty2.2 Modification Record	5 5
3 General Information	6
 3.1 General Description of EUT	6 9 10 11 12 13
4 Test Types and Results 1	14
4.1 Radiated Emission and Bandedge Measurement	14 15 16 17 17
5 Pictures of Test Arrangements	20
Appendix – Information of the Testing Laboratories	21



	Re	lease Control Re	cord	
Issue No.	Description			Date Issued
RF191129E09D	Original release.			June 01, 2020
	200	Daga Na 2/04		



Certificate of Conformity 1

Product:	Orbi Router, Orbi Satellite
Brand:	NETGEAR
Test Model:	RBR750
Series Moel:	RBS750
Sample Status:	ENGINEERING SAMPLE
Applicant:	NETGEAR, Inc.
Test Date:	May 11, 2020
Standards:	47 CFR FCC Part 15, Subpart C (Section 15.247) ANSI C63.10: 2013

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :

' VP

Joyce Kuo / Specialist

Date:

June 01, 2020

June 01, 2020

Approved by :

Clark Lin / Technical Manager

Date:



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)				
FCC Clause	Test Item Result Remarks			
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -3.6dB at 84.75MHz.	

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2. This report is prepared for supplementary report.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Dedicted Emissions up to 1 CHz	9kHz ~ 30MHz	3.1 dB
Radiated Emissions up to T GHZ	30MHz ~ 1GHz	5.5 dB

2.2 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	Orbi Router, Orbi Satellite
Brand	NETGEAR
Test Model	RBR750
Series Model	RBS750
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	12Vdc from power adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT20/40 in 2.4GHz 1024QAM for OFDMA in 11ax HE mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 600Mbps 802.11ac: up to 1733.3Mbps 802.11ax: up to 2401.9Mbps
Operating Frequency	2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.18~ 5.24GHz, 5.745 ~ 5.825GHz
Number of Channel	2.4GHz: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 5GHz (U-NII-1): 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 5GHz (U-NII-3): 802.11a, 802.11n (HT20), 802.11ac (VHT20): 5 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1
Output Power	CDD Mode: 2.412 ~ 2.462 GHz: 958.897 mW 5.18 ~ 5.24GHz: 666.121mW 5.745 ~ 5.825GHz: 948.986mW Beamforming Mode: 2.412 ~ 2.462 GHz: 646.447 mW 5.18 ~ 5.24GHz: 665.956mW 5.745 ~ 5.825GHz: 798.119mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x 1
Data Cable Supplied	RJ45 cable x 1 (Unshielded, 1.8m)



Note:

- 1. This report is prepared for FCC class II change. The difference compared with the Report No.: RF191129E09 as the following:
 - Change RF FEM from Skyworks to Qorvo: Pin to Pin, draws 50mA more current
 - The new chip component is pin-for-pin compatible.
 - The new chip has the same basic function as the old chip, from an external perspective (internal circuitry may differ).
 - No change in radio parameters has occurred.
 - The same conditions apply when a small area (approximately the same area as the chip) of the PCB is replaced with an equivalent chip
- 2. According to above conditions, only radiated emission (Below 1GHz) test items need to be performed. And all data was verified to meet the requirements.

	Brand	Product Name	Model		Difference
		Orthi Davidan		Function:	Master
		Orbi Router	RBR750	WAN port	*1; LAN port*3
	NETGEAR	Orbi Satellite	RBS750	Function: Master + Client LAN port*2	
From the above models, model: RBR750 was the worst case and it was selected as representative model for the test and its data was recorded in this report.					
4. Sim	nultaneously trar	nsmission condition.			
Condit	Condition Technology				
1			WLAN 5GHz		WLAN 5GHz
	VVL		(low band)	band) (high band)	
Note:	Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.			no non-compliance was found.	
5. The EUT must be supplied power adapter and following different models could be chosen as following table:				could be chosen as following	
No.	Brand	Model No.	P/N	Spec.	
1	NETGEAR	2ABL030F1 NJ	332-10948-01	Input: 100-120Vac, 1.0A, 50/60Hz Output: 12.0V, 2.5A	
2	NETGEAR	AD2067F10	332-11509-01	Input: 100-120Vac, 1.0A, 50/60Hz Output: 12.0V, 2.5A	

3. All models are listed as below.

For conducted and radiated emissions test, the EUT was pre-tested worst case was found in **adapter 3**. Therefore the test and its data was recorded in this report.

332-11074-01

6. The EUT uses following antennas.

AD2067M20

NETGEAR

3

	9		
Antenna Type	Dipole		
Antenna Connector	i-pex(MH	F)	
	Directional Gain (dBi)		
2.4GHz Band		5GHz U-NII-1	5GHz U-NII-3
5.46		5.67	6.94

DC Output cable: Unshielded, 1.8m Input: 100-240Vac, 1.0A, 50/60Hz

DC Output cable: Unshielded, 1.8m

Output: 12.0V, 2.5A



7. The EUT incorporates a MIMO function:					
	2.4GHz Band				
MODULATION MODE		TX & RX CONFIGURATION			
802.11b	21	TX	2RX		
802.11g	21	-X	2F	RX	
802.11n (HT20)	21	-X	2F	RX	
802.11n (HT40)	21	TX	2F	RX	
VHT20	21	X	2F	RX	
VHT40	21	X	2F	RX	
802.11ax (HE20)	21	TX	2F	RX	
802.11ax (HE40)	21	-X	2F	RX	
	5GHz Band				
MODULATION	TX & RX CON	FIGURATION	TX & RX CON	IFIGURATION	
MODE	5180 ~ 5	240MHz	5745 ~ 5	825MHz	
802.11a	2TX	2RX	4TX	4RX	
802.11n (HT20)	2TX	2RX	4TX	4RX	
802.11n (HT40)	2TX	2RX	4TX	4RX	
802.11ac (VHT20)	2TX	2RX	4TX	4RX	
802.11ac (VHT40)	2TX	2RX	4TX	4RX	
802.11ac (VHT80)	2TX	2RX	4TX	4RX	
802.11ax (HE20)	2TX	2RX	4TX	4RX	
802.11ax (HE40)	2TX	2RX	4TX	4RX	
802.11ax (HE80)	2TX	2RX	4TX	4RX	

N ote:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.

2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.

3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz), 802.11ac mode for 20MHz (40MHz) and 802.11ax mode for 20MHz (40MHz), therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

8. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



3.2 Description of Test Modes

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), VHT20 and 802.11ax (HE20):

7 channels are provided for 802.11n (HT40), VHT40 and 802.11ax (HE40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		



3.2.1 Test Mode Applicability and Tested Channel Detail

EUT	APPLICABLE TO	DESCRIPTION
MODE RE<1G	RE<1G	DESCRIPTION
-	1	-

Where **RE<1G:** Radiated Emission below 1GHz

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

CDD Mode							
Mode Available Channel		Tested Channel Modulation Technology		Modulation Type	Data Rate Parameter		
802.11b	1 to 11	6	DSSS	DBPSK	1Mb/s		

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY	
RE<1G	22deg. C, 67%RH	120Vac, 60Hz	Ryan Du	



3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
Α.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
В.	Laptop	DELL	E5430	GM1SKV1	FCC DoC	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC cable	1	1.8	N	0	Supplied by client
2.	RJ45 cable	1	10	N	0	Provided by Lab
3.	RJ45 cable	1	10	N	0	Provided by Lab



3.3.1 Configuration of System under Test





3.4 General Description of Applied Standards and reference

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and reference:

Test standard: FCC Part 15, Subpart C (15.247) ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02 KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.

- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 Test Instruments

For Radiated emission (Below 1GHz)

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 13, 2019	Dec. 12, 2020
Pre-Amplifier EMCI	EMC001340	980142	May 30, 2019	May 29, 2020
Loop Antenna Electro-Metrics	EM-6879	264	Feb. 18, 2020	Feb. 17, 2021
RF Cable	NA	LOOPCAB-001	Jan. 08, 2020	Jan. 07, 2021
RF Cable	NA	LOOPCAB-002	Jan. 08, 2020	Jan. 07, 2021
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Oct. 23, 2019	Oct. 22, 2020
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Nov. 11, 2019	Nov. 10, 2020
RF Cable	8D	966-4-1	Mar. 18, 2020	Mar. 17, 2021
RF Cable	8D	966-4-2	Mar. 18, 2020	Mar. 17, 2021
RF Cable	8D	966-4-3	Mar. 18, 2020	Mar. 17, 2021
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Sep. 26, 2019	Sep. 25, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in 966 Chamber No. 4.

3. Tested Date: May 11, 2020



4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.



4.1.5 Test Setup



b. Controlling software (QSPR (5.0-00140)) has been activated to set the EUT under transmission condition continuously at specific channel frequency.



4.1.7 Test Results

Below 1GHz Data:

802.11b

CHANNEL	TX Channel 6	DETECTOR	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	84.75	36.4 QP	40.0	-3.6	2.50 H	142	49.9	-13.5	
2	150.28	34.8 QP	43.5	-8.7	2.00 H	173	42.2	-7.4	
3	230.61	25.3 QP	46.0	-20.7	1.00 H	79	35.2	-9.9	
4	311.72	30.6 QP	46.0	-15.4	1.50 H	39	36.7	-6.1	
5	350.89	30.6 QP	46.0	-15.4	1.00 H	341	35.9	-5.3	
6	500.02	31.5 QP	46.0	-14.5	2.00 H	278	32.8	-1.3	

REMARKS:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. Margin value = Emission Level Limit value
- 4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
- 5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



CHANNEL	TX Channel 6	DETECTOR		
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)	

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	46.63	35.7 QP	40.0	-4.3	1.00 V	56	43.6	-7.9	
2	83.70	34.1 QP	40.0	-5.9	1.00 V	181	47.4	-13.3	
3	96.57	35.8 QP	43.5	-7.7	1.50 V	114	48.4	-12.6	
4	151.03	33.3 QP	43.5	-10.2	1.00 V	261	40.8	-7.5	
5	185.55	31.5 QP	43.5	-12.0	1.00 V	246	41.3	-9.8	
6	305.02	29.3 QP	46.0	-16.7	2.00 V	337	35.6	-6.3	

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.

5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.





5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab Tel: 886-2-26052180 Fax: 886-2-26051924 Hsin Chu EMC/RF/Telecom Lab Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <u>service.adt@tw.bureauveritas.com</u> Web Site: <u>www.bureauveritas-adt.com</u>

The address and road map of all our labs can be found in our web site also.

--- END ----