

RF Mode	TX 802.11ax (HE20)	Channel	CH 113 : 6515 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	113.1 PK			1.98 H	265	107.1	6.0
2	*6515.00	102.8 AV			1.98 H	265	96.8	6.0
3	#13030.00	48.1 PK	88.2	-40.1	1.66 H	352	34.8	13.3
4	#13030.00	39.9 AV	68.2	-28.3	1.66 H	352	26.6	13.3
5	19545.00	48.4 PK	74.0	-25.6	1.15 H	321	54.6	-6.2
6	19545.00	36.3 AV	54.0	-17.7	1.15 H	321	42.5	-6.2
7	#26060.00	47.2 PK	88.2	-41.0	1.40 H	329	48.6	-1.4
8	#26060.00	36.6 AV	68.2	-31.6	1.40 H	329	38.0	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6515.00	120.8 PK			1.58 V	355	114.8	6.0
2	*6515.00	109.9 AV			1.58 V	355	103.9	6.0
3	#13030.00	48.7 PK	88.2	-39.5	1.66 V	313	35.4	13.3
4	#13030.00	40.4 AV	68.2	-27.8	1.66 V	313	27.1	13.3
5	19545.00	50.4 PK	74.0	-23.6	1.25 V	323	56.6	-6.2
6	19545.00	42.2 AV	54.0	-11.8	1.25 V	323	48.4	-6.2
7	#26060.00	48.3 PK	88.2	-39.9	1.35 V	297	49.7	-1.4
8	#26060.00	37.8 AV	68.2	-30.4	1.35 V	297	39.2	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 117 : 6535 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	113.1 PK			1.93 H	269	107.1	6.0
2	*6535.00	103.1 AV			1.93 H	269	97.1	6.0
3	#13070.00	48.7 PK	88.2	-39.5	1.67 H	332	35.3	13.4
4	#13070.00	40.2 AV	68.2	-28.0	1.67 H	332	26.8	13.4
5	19605.00	47.7 PK	74.0	-26.3	1.12 H	318	53.8	-6.1
6	19605.00	36.0 AV	54.0	-18.0	1.12 H	318	42.1	-6.1
7	#26140.00	47.0 PK	88.2	-41.2	1.30 H	321	48.3	-1.3
8	#26140.00	36.5 AV	68.2	-31.7	1.30 H	321	37.8	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6535.00	120.7 PK			1.58 V	345	114.7	6.0
2	*6535.00	109.7 AV			1.58 V	345	103.7	6.0
3	#13070.00	48.5 PK	88.2	-39.7	1.67 V	315	35.1	13.4
4	#13070.00	40.4 AV	68.2	-27.8	1.67 V	315	27.0	13.4
5	19605.00	50.6 PK	74.0	-23.4	1.18 V	330	56.7	-6.1
6	19605.00	42.5 AV	54.0	-11.5	1.18 V	330	48.6	-6.1
7	#26140.00	48.4 PK	88.2	-39.8	1.26 V	315	49.7	-1.3
8	#26140.00	38.1 AV	68.2	-30.1	1.26 V	315	39.4	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 153 : 6715 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	113.7 PK			1.93 H	241	107.6	6.1
2	*6715.00	103.4 AV			1.93 H	241	97.3	6.1
3	#13430.00	48.3 PK	88.2	-39.9	1.61 H	338	33.4	14.9
4	#13430.00	40.0 AV	68.2	-28.2	1.61 H	338	25.1	14.9
5	20145.00	48.7 PK	74.0	-25.3	1.15 H	309	54.1	-5.4
6	20145.00	36.6 AV	54.0	-17.4	1.15 H	309	42.0	-5.4
7	#26860.00	46.5 PK	88.2	-41.7	1.37 H	332	47.6	-1.1
8	#26860.00	36.2 AV	68.2	-32.0	1.37 H	332	37.3	-1.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6715.00	121.3 PK			1.64 V	358	115.2	6.1
2	*6715.00	110.1 AV			1.64 V	358	104.0	6.1
3	#13430.00	48.2 PK	88.2	-40.0	1.59 V	321	33.3	14.9
4	#13430.00	40.1 AV	68.2	-28.1	1.59 V	321	25.2	14.9
5	20145.00	50.9 PK	74.0	-23.1	1.19 V	319	56.3	-5.4
6	20145.00	42.5 AV	54.0	-11.5	1.19 V	319	47.9	-5.4
7	#26860.00	48.5 PK	88.2	-39.7	1.35 V	324	49.6	-1.1
8	#26860.00	38.3 AV	68.2	-29.9	1.35 V	324	39.4	-1.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 181 : 6855 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	113.7 PK			1.95 H	256	106.9	6.8
2	*6855.00	103.3 AV			1.95 H	256	96.5	6.8
3	#13710.00	48.3 PK	88.2	-39.9	1.63 H	345	32.6	15.7
4	#13710.00	40.3 AV	68.2	-27.9	1.63 H	345	24.6	15.7
5	20565.00	48.6 PK	74.0	-25.4	1.15 H	323	53.5	-4.9
6	20565.00	36.7 AV	54.0	-17.3	1.15 H	323	41.6	-4.9
7	#27420.00	46.5 PK	88.2	-41.7	1.35 H	332	48.1	-1.6
8	#27420.00	36.0 AV	68.2	-32.2	1.35 H	332	37.6	-1.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6855.00	121.1 PK			1.63 V	352	114.3	6.8
2	*6855.00	110.2 AV			1.63 V	352	103.4	6.8
3	#13710.00	48.7 PK	88.2	-39.5	1.58 V	322	33.0	15.7
4	#13710.00	40.5 AV	68.2	-27.7	1.58 V	322	24.8	15.7
5	20565.00	50.0 PK	74.0	-24.0	1.19 V	330	54.9	-4.9
6	20565.00	41.7 AV	54.0	-12.3	1.19 V	330	46.6	-4.9
7	#27420.00	48.0 PK	88.2	-40.2	1.31 V	315	49.6	-1.6
8	#27420.00	37.6 AV	68.2	-30.6	1.31 V	315	39.2	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 185 : 6875 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	113.9 PK			1.96 H	246	106.9	7.0
2	*6875.00	103.5 AV			1.96 H	246	96.5	7.0
3	#13750.00	48.6 PK	88.2	-39.6	1.66 H	330	32.8	15.8
4	#13750.00	40.2 AV	68.2	-28.0	1.66 H	330	24.4	15.8
5	20625.00	48.7 PK	74.0	-25.3	1.10 H	315	53.5	-4.8
6	20625.00	36.4 AV	54.0	-17.6	1.10 H	315	41.2	-4.8
7	#27500.00	46.0 PK	88.2	-42.2	1.37 H	308	47.2	-1.2
8	#27500.00	35.9 AV	68.2	-32.3	1.37 H	308	37.1	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	120.7 PK			1.56 V	353	113.7	7.0
2	*6875.00	109.7 AV			1.56 V	353	102.7	7.0
3	#13750.00	48.0 PK	88.2	-40.2	1.64 V	316	32.2	15.8
4	#13750.00	40.0 AV	68.2	-28.2	1.64 V	316	24.2	15.8
5	20625.00	49.8 PK	74.0	-24.2	1.22 V	316	54.6	-4.8
6	20625.00	41.7 AV	54.0	-12.3	1.22 V	316	46.5	-4.8
7	#27500.00	48.2 PK	88.2	-40.0	1.32 V	326	49.4	-1.2
8	#27500.00	37.7 AV	68.2	-30.5	1.32 V	326	38.9	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 213 : 7015 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	113.4 PK			1.98 H	266	105.5	7.9
2	*7015.00	103.2 AV			1.98 H	266	95.3	7.9
3	#14030.00	48.1 PK	88.2	-40.1	1.64 H	327	32.2	15.9
4	#14030.00	39.8 AV	68.2	-28.4	1.64 H	327	23.9	15.9
5	21045.00	48.0 PK	74.0	-26.0	1.18 H	332	52.4	-4.4
6	21045.00	36.2 AV	54.0	-17.8	1.18 H	332	40.6	-4.4
7	#28060.00	47.3 PK	88.2	-40.9	1.38 H	332	48.7	-1.4
8	#28060.00	36.7 AV	68.2	-31.5	1.38 H	332	38.1	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	121.2 PK			1.67 V	350	113.3	7.9
2	*7015.00	110.2 AV			1.67 V	350	102.3	7.9
3	#14030.00	48.6 PK	88.2	-39.6	1.66 V	307	32.7	15.9
4	#14030.00	40.4 AV	68.2	-27.8	1.66 V	307	24.5	15.9
5	21045.00	50.6 PK	74.0	-23.4	1.22 V	314	55.0	-4.4
6	21045.00	42.5 AV	54.0	-11.5	1.22 V	314	46.9	-4.4
7	#28060.00	47.9 PK	88.2	-40.3	1.32 V	311	49.3	-1.4
8	#28060.00	37.8 AV	68.2	-30.4	1.32 V	311	39.2	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 229 : 7095 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7095.00	112.5 PK			1.57 H	15	104.2	8.3
2	*7095.00	100.5 AV			1.57 H	15	92.2	8.3
3	#7125.00	63.4 PK	88.2	-24.8	1.57 H	15	54.9	8.5
4	#7125.00	50.7 AV	68.2	-17.5	1.57 H	15	42.2	8.5
5	#14190.00	49.1 PK	88.2	-39.1	1.56 H	331	32.1	17.0
6	#14190.00	40.7 AV	68.2	-27.5	1.56 H	331	23.7	17.0
7	21285.00	49.0 PK	74.0	-25.0	1.13 H	334	53.4	-4.4
8	21285.00	36.3 AV	54.0	-17.7	1.13 H	334	40.7	-4.4
9	#28380.00	46.2 PK	88.2	-42.0	1.34 H	350	48.1	-1.9
10	#28380.00	36.1 AV	68.2	-32.1	1.34 H	350	38.0	-1.9

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7095.00	119.0 PK			1.50 V	356	110.7	8.3
2	*7095.00	107.2 AV			1.50 V	356	98.9	8.3
3	#7125.00	72.5 PK	88.2	-15.7	1.50 V	356	64.0	8.5
4	#7125.00	58.7 AV	68.2	-9.5	1.50 V	356	50.2	8.5
5	#14190.00	48.2 PK	88.2	-40.0	1.57 V	314	31.2	17.0
6	#14190.00	40.0 AV	68.2	-28.2	1.57 V	314	23.0	17.0
7	21285.00	50.4 PK	74.0	-23.6	1.20 V	321	54.8	-4.4
8	21285.00	42.0 AV	54.0	-12.0	1.20 V	321	46.4	-4.4
9	#28380.00	48.9 PK	88.2	-39.3	1.36 V	324	50.8	-1.9
10	#28380.00	38.3 AV	68.2	-29.9	1.36 V	324	40.2	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 233 : 7115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	90.7 PK			1.87 H	226	82.6	8.1
2	*7115.00	80.6 AV			1.87 H	226	72.5	8.1
3	#7125.00	70.1 PK	88.2	-18.1	1.87 H	226	61.9	8.2
4	#7125.00	58.7 AV	68.2	-9.5	1.87 H	226	50.5	8.2
5	#14230.00	48.9 PK	88.2	-39.3	1.67 H	334	31.8	17.1
6	#14230.00	40.5 AV	68.2	-27.7	1.67 H	334	23.4	17.1
7	21345.00	48.7 PK	74.0	-25.3	1.11 H	315	52.9	-4.2
8	21345.00	36.7 AV	54.0	-17.3	1.11 H	315	40.9	-4.2
9	#28460.00	47.1 PK	88.2	-41.1	1.35 H	324	48.5	-1.4
10	#28460.00	36.6 AV	68.2	-31.6	1.35 H	324	38.0	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	98.2 PK			1.69 V	359	90.1	8.1
2	*7115.00	86.8 AV			1.69 V	359	78.7	8.1
3	#7125.00	79.9 PK	88.2	-8.3	1.69 V	359	71.7	8.2
4	#7125.00	67.7 AV	68.2	-0.5	1.69 V	359	59.5	8.2
5	#14230.00	47.7 PK	88.2	-40.5	1.59 V	328	30.6	17.1
6	#14230.00	39.7 AV	68.2	-28.5	1.59 V	328	22.6	17.1
7	21345.00	50.4 PK	74.0	-23.6	1.26 V	324	54.6	-4.2
8	21345.00	41.8 AV	54.0	-12.2	1.26 V	324	46.0	-4.2
9	#28460.00	48.6 PK	88.2	-39.6	1.36 V	321	50.0	-1.4
10	#28460.00	38.1 AV	68.2	-30.1	1.36 V	321	39.5	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 35 : 6125 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5876.14	51.5 PK	88.2	-36.7	1.68 H	219	47.8	3.7
2	#5876.14	41.6 AV	68.2	-26.6	1.68 H	219	37.9	3.7
3	*6125.00	110.5 PK			1.68 H	219	106.2	4.3
4	*6125.00	100.6 AV			1.68 H	219	96.3	4.3
5	12250.00	48.3 PK	74.0	-25.7	1.61 H	337	35.1	13.2
6	12250.00	39.5 AV	54.0	-14.5	1.61 H	337	26.3	13.2
7	18375.00	48.2 PK	74.0	-25.8	1.15 H	308	55.4	-7.2
8	18375.00	37.2 AV	54.0	-16.8	1.15 H	308	44.4	-7.2
9	#24500.00	46.2 PK	88.2	-42.0	1.37 H	340	48.3	-2.1
10	#24500.00	36.0 AV	68.2	-32.2	1.37 H	340	38.1	-2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5906.00	51.9 PK	88.2	-36.3	2.39 V	357	48.2	3.7
2	#5906.00	40.5 AV	68.2	-27.7	2.39 V	357	36.8	3.7
3	*6125.00	117.9 PK			2.39 V	357	113.6	4.3
4	*6125.00	107.8 AV			2.39 V	357	103.5	4.3
5	12250.00	47.4 PK	74.0	-26.6	1.65 V	320	34.2	13.2
6	12250.00	39.3 AV	54.0	-14.7	1.65 V	320	26.1	13.2
7	18375.00	48.7 PK	74.0	-25.3	1.22 V	304	55.9	-7.2
8	18375.00	40.7 AV	54.0	-13.3	1.22 V	304	47.9	-7.2
9	#24500.00	47.6 PK	88.2	-40.6	1.27 V	297	49.7	-2.1
10	#24500.00	37.2 AV	68.2	-31.0	1.27 V	297	39.3	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 59 : 6245 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6245.00	110.3 PK			1.69 H	214	105.6	4.7
2	*6245.00	100.5 AV			1.69 H	214	95.8	4.7
3	12490.00	47.4 PK	74.0	-26.6	1.58 H	332	34.9	12.5
4	12490.00	39.1 AV	54.0	-14.9	1.58 H	332	26.6	12.5
5	18735.00	48.1 PK	74.0	-25.9	1.12 H	320	54.9	-6.8
6	18735.00	37.5 AV	54.0	-16.5	1.12 H	320	44.3	-6.8
7	#24980.00	45.6 PK	88.2	-42.6	1.31 H	320	47.4	-1.8
8	#24980.00	35.5 AV	68.2	-32.7	1.31 H	320	37.3	-1.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6245.00	118.1 PK			2.45 V	354	113.4	4.7
2	*6245.00	107.9 AV			2.45 V	354	103.2	4.7
3	12490.00	47.2 PK	74.0	-26.8	1.65 V	330	34.7	12.5
4	12490.00	39.1 AV	54.0	-14.9	1.65 V	330	26.6	12.5
5	18735.00	48.2 PK	74.0	-25.8	1.18 V	301	55.0	-6.8
6	18735.00	40.5 AV	54.0	-13.5	1.18 V	301	47.3	-6.8
7	#24980.00	47.4 PK	88.2	-40.8	1.22 V	289	49.2	-1.8
8	#24980.00	36.9 AV	68.2	-31.3	1.22 V	289	38.7	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 91 : 6405 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	110.7 PK			1.72 H	225	105.4	5.3
2	*6405.00	100.8 AV			1.72 H	225	95.5	5.3
3	#12810.00	48.1 PK	88.2	-40.1	1.56 H	333	34.6	13.5
4	#12810.00	39.2 AV	68.2	-29.0	1.56 H	333	25.7	13.5
5	19215.00	47.2 PK	74.0	-26.8	1.10 H	311	53.9	-6.7
6	19215.00	36.6 AV	54.0	-17.4	1.10 H	311	43.3	-6.7
7	#25620.00	45.9 PK	88.2	-42.3	1.30 H	334	47.6	-1.7
8	#25620.00	35.8 AV	68.2	-32.4	1.30 H	334	37.5	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	118.5 PK			2.34 V	9	113.2	5.3
2	*6405.00	108.2 AV			2.34 V	9	102.9	5.3
3	#12810.00	47.5 PK	88.2	-40.7	1.65 V	323	34.0	13.5
4	#12810.00	39.5 AV	68.2	-28.7	1.65 V	323	26.0	13.5
5	19215.00	48.5 PK	74.0	-25.5	1.26 V	318	55.2	-6.7
6	19215.00	40.4 AV	54.0	-13.6	1.26 V	318	47.1	-6.7
7	#25620.00	46.8 PK	88.2	-41.4	1.28 V	307	48.5	-1.7
8	#25620.00	36.7 AV	68.2	-31.5	1.28 V	307	38.4	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 99 : 6445 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	110.5 PK			1.67 H	210	105.0	5.5
2	*6445.00	100.4 AV			1.67 H	210	94.9	5.5
3	#12890.00	46.9 PK	88.2	-41.3	1.56 H	335	33.6	13.3
4	#12890.00	38.6 AV	68.2	-29.6	1.56 H	335	25.3	13.3
5	19335.00	47.5 PK	74.0	-26.5	1.15 H	325	54.3	-6.8
6	19335.00	37.0 AV	54.0	-17.0	1.15 H	325	43.8	-6.8
7	#25780.00	46.0 PK	88.2	-42.2	1.33 H	330	47.4	-1.4
8	#25780.00	35.5 AV	68.2	-32.7	1.33 H	330	36.9	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	118.2 PK			2.34 V	355	112.7	5.5
2	*6445.00	107.9 AV			2.34 V	355	102.4	5.5
3	#12890.00	47.2 PK	88.2	-41.0	1.68 V	324	33.9	13.3
4	#12890.00	39.0 AV	68.2	-29.2	1.68 V	324	25.7	13.3
5	19335.00	48.5 PK	74.0	-25.5	1.21 V	304	55.3	-6.8
6	19335.00	40.5 AV	54.0	-13.5	1.21 V	304	47.3	-6.8
7	#25780.00	47.2 PK	88.2	-41.0	1.24 V	308	48.6	-1.4
8	#25780.00	37.0 AV	68.2	-31.2	1.24 V	308	38.4	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 107 : 6485 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	110.9 PK			1.63 H	221	105.1	5.8
2	*6485.00	101.0 AV			1.63 H	221	95.2	5.8
3	#12970.00	47.9 PK	88.2	-40.3	1.64 H	338	34.6	13.3
4	#12970.00	39.5 AV	68.2	-28.7	1.64 H	338	26.2	13.3
5	19455.00	47.4 PK	74.0	-26.6	1.10 H	330	54.0	-6.6
6	19455.00	36.6 AV	54.0	-17.4	1.10 H	330	43.2	-6.6
7	#25940.00	45.9 PK	88.2	-42.3	1.32 H	329	47.7	-1.8
8	#25940.00	35.5 AV	68.2	-32.7	1.32 H	329	37.3	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	117.8 PK			2.37 V	6	112.0	5.8
2	*6485.00	107.8 AV			2.37 V	6	102.0	5.8
3	#12970.00	46.8 PK	88.2	-41.4	1.68 V	322	33.5	13.3
4	#12970.00	38.8 AV	68.2	-29.4	1.68 V	322	25.5	13.3
5	19455.00	49.2 PK	74.0	-24.8	1.25 V	307	55.8	-6.6
6	19455.00	41.0 AV	54.0	-13.0	1.25 V	307	47.6	-6.6
7	#25940.00	47.8 PK	88.2	-40.4	1.28 V	292	49.6	-1.8
8	#25940.00	37.6 AV	68.2	-30.6	1.28 V	292	39.4	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 115 : 6525 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	110.6 PK			1.69 H	230	104.6	6.0
2	*6525.00	100.7 AV			1.69 H	230	94.7	6.0
3	#13050.00	47.6 PK	88.2	-40.6	1.65 H	342	34.3	13.3
4	#13050.00	39.2 AV	68.2	-29.0	1.65 H	342	25.9	13.3
5	19575.00	47.7 PK	74.0	-26.3	1.11 H	330	53.9	-6.2
6	19575.00	36.7 AV	54.0	-17.3	1.11 H	330	42.9	-6.2
7	#26100.00	46.4 PK	88.2	-41.8	1.37 H	316	47.8	-1.4
8	#26100.00	35.9 AV	68.2	-32.3	1.37 H	316	37.3	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	117.6 PK			2.38 V	6	111.6	6.0
2	*6525.00	107.4 AV			2.38 V	6	101.4	6.0
3	#13050.00	47.5 PK	88.2	-40.7	1.62 V	318	34.2	13.3
4	#13050.00	39.5 AV	68.2	-28.7	1.62 V	318	26.2	13.3
5	19575.00	48.9 PK	74.0	-25.1	1.25 V	297	55.1	-6.2
6	19575.00	41.1 AV	54.0	-12.9	1.25 V	297	47.3	-6.2
7	#26100.00	47.2 PK	88.2	-41.0	1.25 V	312	48.6	-1.4
8	#26100.00	37.1 AV	68.2	-31.1	1.25 V	312	38.5	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 123 : 6565 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	110.6 PK			1.63 H	226	104.5	6.1
2	*6565.00	100.9 AV			1.63 H	226	94.8	6.1
3	#13130.00	47.1 PK	88.2	-41.1	1.67 H	340	33.6	13.5
4	#13130.00	38.7 AV	68.2	-29.5	1.67 H	340	25.2	13.5
5	19695.00	48.4 PK	74.0	-25.6	1.18 H	325	54.4	-6.0
6	19695.00	37.3 AV	54.0	-16.7	1.18 H	325	43.3	-6.0
7	#26260.00	45.5 PK	88.2	-42.7	1.34 H	344	46.9	-1.4
8	#26260.00	35.4 AV	68.2	-32.8	1.34 H	344	36.8	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	118.3 PK			2.43 V	8	112.2	6.1
2	*6565.00	107.9 AV			2.43 V	8	101.8	6.1
3	#13130.00	47.3 PK	88.2	-40.9	1.61 V	318	33.8	13.5
4	#13130.00	39.2 AV	68.2	-29.0	1.61 V	318	25.7	13.5
5	19695.00	49.3 PK	74.0	-24.7	1.22 V	306	55.3	-6.0
6	19695.00	41.1 AV	54.0	-12.9	1.22 V	306	47.1	-6.0
7	#26260.00	47.4 PK	88.2	-40.8	1.21 V	309	48.8	-1.4
8	#26260.00	37.1 AV	68.2	-31.1	1.21 V	309	38.5	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 155 : 6725 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	110.1 PK			1.64 H	235	103.9	6.2
2	*6725.00	100.4 AV			1.64 H	235	94.2	6.2
3	#13450.00	47.6 PK	88.2	-40.6	1.58 H	337	32.8	14.8
4	#13450.00	39.2 AV	68.2	-29.0	1.58 H	337	24.4	14.8
5	20175.00	48.5 PK	74.0	-25.5	1.14 H	321	53.9	-5.4
6	20175.00	37.5 AV	54.0	-16.5	1.14 H	321	42.9	-5.4
7	#26900.00	47.0 PK	88.2	-41.2	1.30 H	324	48.3	-1.3
8	#26900.00	36.3 AV	68.2	-31.9	1.30 H	324	37.6	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	117.4 PK			2.40 V	11	111.2	6.2
2	*6725.00	107.3 AV			2.40 V	11	101.1	6.2
3	#13450.00	47.4 PK	88.2	-40.8	1.68 V	308	32.6	14.8
4	#13450.00	39.3 AV	68.2	-28.9	1.68 V	308	24.5	14.8
5	20175.00	48.6 PK	74.0	-25.4	1.18 V	288	54.0	-5.4
6	20175.00	40.7 AV	54.0	-13.3	1.18 V	288	46.1	-5.4
7	#26900.00	47.6 PK	88.2	-40.6	1.24 V	303	48.9	-1.3
8	#26900.00	37.2 AV	68.2	-31.0	1.24 V	303	38.5	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 179 : 6845 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	110.8 PK			1.67 H	213	104.1	6.7
2	*6845.00	101.0 AV			1.67 H	213	94.3	6.7
3	#13690.00	47.5 PK	88.2	-40.7	1.63 H	356	32.0	15.5
4	#13690.00	39.1 AV	68.2	-29.1	1.63 H	356	23.6	15.5
5	20535.00	47.5 PK	74.0	-26.5	1.12 H	309	52.4	-4.9
6	20535.00	36.6 AV	54.0	-17.4	1.12 H	309	41.5	-4.9
7	#27380.00	46.6 PK	88.2	-41.6	1.32 H	323	48.3	-1.7
8	#27380.00	36.2 AV	68.2	-32.0	1.32 H	323	37.9	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	117.3 PK			2.36 V	344	110.6	6.7
2	*6845.00	107.3 AV			2.36 V	344	100.6	6.7
3	#13690.00	47.1 PK	88.2	-41.1	1.64 V	321	31.6	15.5
4	#13690.00	39.0 AV	68.2	-29.2	1.64 V	321	23.5	15.5
5	20535.00	48.7 PK	74.0	-25.3	1.21 V	300	53.6	-4.9
6	20535.00	41.0 AV	54.0	-13.0	1.21 V	300	45.9	-4.9
7	#27380.00	47.1 PK	88.2	-41.1	1.29 V	299	48.8	-1.7
8	#27380.00	36.7 AV	68.2	-31.5	1.29 V	299	38.4	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 187 : 6885 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	110.5 PK			1.63 H	212	103.4	7.1
2	*6885.00	100.8 AV			1.63 H	212	93.7	7.1
3	#13770.00	47.3 PK	88.2	-40.9	1.64 H	352	31.5	15.8
4	#13770.00	38.6 AV	68.2	-29.6	1.64 H	352	22.8	15.8
5	20655.00	47.9 PK	74.0	-26.1	1.10 H	310	52.8	-4.9
6	20655.00	37.1 AV	54.0	-16.9	1.10 H	310	42.0	-4.9
7	#27540.00	46.3 PK	88.2	-41.9	1.35 H	333	47.6	-1.3
8	#27540.00	35.7 AV	68.2	-32.5	1.35 H	333	37.0	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	117.9 PK			2.33 V	8	110.8	7.1
2	*6885.00	107.8 AV			2.33 V	8	100.7	7.1
3	#13770.00	47.2 PK	88.2	-41.0	1.64 V	319	31.4	15.8
4	#13770.00	39.3 AV	68.2	-28.9	1.64 V	319	23.5	15.8
5	20655.00	48.5 PK	74.0	-25.5	1.18 V	296	53.4	-4.9
6	20655.00	40.8 AV	54.0	-13.2	1.18 V	296	45.7	-4.9
7	#27540.00	47.6 PK	88.2	-40.6	1.26 V	292	48.9	-1.3
8	#27540.00	37.3 AV	68.2	-30.9	1.26 V	292	38.6	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 211 : 7005 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	110.6 PK			1.72 H	218	102.7	7.9
2	*7005.00	100.5 AV			1.72 H	218	92.6	7.9
3	#14010.00	47.7 PK	88.2	-40.5	1.61 H	347	32.0	15.7
4	#14010.00	39.1 AV	68.2	-29.1	1.61 H	347	23.4	15.7
5	21015.00	47.8 PK	74.0	-26.2	1.15 H	315	52.2	-4.4
6	21015.00	37.0 AV	54.0	-17.0	1.15 H	315	41.4	-4.4
7	#28020.00	46.3 PK	88.2	-41.9	1.34 H	329	47.6	-1.3
8	#28020.00	35.9 AV	68.2	-32.3	1.34 H	329	37.2	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	117.5 PK			2.36 V	12	109.6	7.9
2	*7005.00	107.6 AV			2.36 V	12	99.7	7.9
3	#14010.00	47.7 PK	88.2	-40.5	1.68 V	307	32.0	15.7
4	#14010.00	39.7 AV	68.2	-28.5	1.68 V	307	24.0	15.7
5	21015.00	48.8 PK	74.0	-25.2	1.18 V	295	53.2	-4.4
6	21015.00	40.8 AV	54.0	-13.2	1.18 V	295	45.2	-4.4
7	#28020.00	47.6 PK	88.2	-40.6	1.29 V	292	48.9	-1.3
8	#28020.00	37.3 AV	68.2	-30.9	1.29 V	292	38.6	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 227 : 7085 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	111.1 PK			1.53 H	219	103.0	8.1
2	*7085.00	100.3 AV			1.53 H	219	92.2	8.1
3	#7125.00	72.6 PK	88.2	-15.6	1.53 H	219	64.4	8.2
4	#7125.00	59.1 AV	68.2	-9.1	1.53 H	219	50.9	8.2
5	#14170.00	48.1 PK	88.2	-40.1	1.67 H	355	31.3	16.8
6	#14170.00	39.8 AV	68.2	-28.4	1.67 H	355	23.0	16.8
7	21255.00	48.1 PK	74.0	-25.9	1.20 H	317	52.3	-4.2
8	21255.00	36.4 AV	54.0	-17.6	1.20 H	317	40.6	-4.2
9	#28340.00	46.6 PK	88.2	-41.6	1.37 H	311	47.9	-1.3
10	#28340.00	36.5 AV	68.2	-31.7	1.37 H	311	37.8	-1.3

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	118.8 PK			1.70 V	358	110.7	8.1
2	*7085.00	107.8 AV			1.70 V	358	99.7	8.1
3	#7125.00	83.7 PK	88.2	-4.5	1.70 V	358	75.5	8.2
4	#7125.00	67.8 AV	68.2	-0.4	1.70 V	358	59.6	8.2
5	#14170.00	48.0 PK	88.2	-40.2	1.68 V	318	31.2	16.8
6	#14170.00	40.2 AV	68.2	-28.0	1.68 V	318	23.4	16.8
7	21255.00	48.7 PK	74.0	-25.3	1.21 V	280	52.9	-4.2
8	21255.00	40.6 AV	54.0	-13.4	1.21 V	280	44.8	-4.2
9	#28340.00	47.3 PK	88.2	-40.9	1.29 V	280	48.6	-1.3
10	#28340.00	37.2 AV	68.2	-31.0	1.29 V	280	38.5	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 39 : 6145 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5868.44	52.0 PK	88.2	-36.2	2.03 H	220	48.1	3.9
2	#5868.44	42.0 AV	68.2	-26.2	2.03 H	220	38.1	3.9
3	*6145.00	108.9 PK			2.03 H	220	104.6	4.3
4	*6145.00	99.3 AV			2.03 H	220	95.0	4.3
5	12290.00	47.8 PK	74.0	-26.2	1.67 H	354	34.5	13.3
6	12290.00	39.8 AV	54.0	-14.2	1.67 H	354	26.5	13.3
7	18435.00	48.1 PK	74.0	-25.9	1.16 H	321	55.3	-7.2
8	18435.00	36.1 AV	54.0	-17.9	1.16 H	321	43.3	-7.2
9	#24580.00	47.1 PK	88.2	-41.1	1.37 H	316	49.0	-1.9
10	#24580.00	36.8 AV	68.2	-31.4	1.37 H	316	38.7	-1.9

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5856.00	52.8 PK	88.2	-35.4	2.65 V	358	48.9	3.9
2	#5856.00	40.4 AV	68.2	-27.8	2.65 V	358	36.5	3.9
3	*6145.00	115.2 PK			2.65 V	358	110.9	4.3
4	*6145.00	104.4 AV			2.65 V	358	100.1	4.3
5	12290.00	47.5 PK	74.0	-26.5	1.66 V	318	34.2	13.3
6	12290.00	39.1 AV	54.0	-14.9	1.66 V	318	25.8	13.3
7	18435.00	49.3 PK	74.0	-24.7	1.25 V	302	56.5	-7.2
8	18435.00	41.0 AV	54.0	-13.0	1.25 V	302	48.2	-7.2
9	#24580.00	48.1 PK	88.2	-40.1	1.32 V	305	50.0	-1.9
10	#24580.00	37.5 AV	68.2	-30.7	1.32 V	305	39.4	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 55 : 6225 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6225.00	108.8 PK			1.56 H	7	104.2	4.6
2	*6225.00	99.2 AV			1.56 H	7	94.6	4.6
3	12450.00	47.8 PK	74.0	-26.2	1.59 H	360	35.1	12.7
4	12450.00	39.1 AV	54.0	-14.9	1.59 H	360	26.4	12.7
5	18675.00	48.4 PK	74.0	-25.6	1.16 H	324	55.3	-6.9
6	18675.00	37.3 AV	54.0	-16.7	1.16 H	324	44.2	-6.9
7	#24900.00	46.0 PK	88.2	-42.2	1.31 H	344	47.8	-1.8
8	#24900.00	35.4 AV	68.2	-32.8	1.31 H	344	37.2	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6225.00	115.8 PK			2.62 V	351	111.2	4.6
2	*6225.00	104.8 AV			2.62 V	351	100.2	4.6
3	12450.00	47.0 PK	74.0	-27.0	1.66 V	318	34.3	12.7
4	12450.00	39.1 AV	54.0	-14.9	1.66 V	318	26.4	12.7
5	18675.00	48.6 PK	74.0	-25.4	1.24 V	291	55.5	-6.9
6	18675.00	40.5 AV	54.0	-13.5	1.24 V	291	47.4	-6.9
7	#24900.00	47.9 PK	88.2	-40.3	1.31 V	297	49.7	-1.8
8	#24900.00	37.6 AV	68.2	-30.6	1.31 V	297	39.4	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 87 : 6385 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	109.0 PK			1.52 H	12	103.8	5.2
2	*6385.00	99.5 AV			1.52 H	12	94.3	5.2
3	#12770.00	47.8 PK	88.2	-40.4	1.58 H	342	34.5	13.3
4	#12770.00	39.3 AV	68.2	-28.9	1.58 H	342	26.0	13.3
5	19155.00	47.3 PK	74.0	-26.7	1.20 H	312	54.0	-6.7
6	19155.00	36.7 AV	54.0	-17.3	1.20 H	312	43.4	-6.7
7	#25540.00	46.3 PK	88.2	-41.9	1.28 H	323	48.0	-1.7
8	#25540.00	35.8 AV	68.2	-32.4	1.28 H	323	37.5	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	115.5 PK			2.69 V	342	110.3	5.2
2	*6385.00	104.9 AV			2.69 V	342	99.7	5.2
3	#12770.00	47.9 PK	88.2	-40.3	1.70 V	319	34.6	13.3
4	#12770.00	39.7 AV	68.2	-28.5	1.70 V	319	26.4	13.3
5	19155.00	48.3 PK	74.0	-25.7	1.19 V	306	55.0	-6.7
6	19155.00	40.4 AV	54.0	-13.6	1.19 V	306	47.1	-6.7
7	#25540.00	47.0 PK	88.2	-41.2	1.24 V	302	48.7	-1.7
8	#25540.00	36.7 AV	68.2	-31.5	1.24 V	302	38.4	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 103 : 6465 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	108.7 PK			1.59 H	7	103.1	5.6
2	*6465.00	99.1 AV			1.59 H	7	93.5	5.6
3	#12930.00	47.7 PK	88.2	-40.5	1.63 H	336	34.4	13.3
4	#12930.00	38.9 AV	68.2	-29.3	1.63 H	336	25.6	13.3
5	19395.00	47.9 PK	74.0	-26.1	1.12 H	321	54.7	-6.8
6	19395.00	37.2 AV	54.0	-16.8	1.12 H	321	44.0	-6.8
7	#25860.00	46.6 PK	88.2	-41.6	1.40 H	342	48.3	-1.7
8	#25860.00	36.1 AV	68.2	-32.1	1.40 H	342	37.8	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	114.9 PK			2.60 V	356	109.3	5.6
2	*6465.00	103.9 AV			2.60 V	356	98.3	5.6
3	#12930.00	47.5 PK	88.2	-40.7	1.60 V	307	34.2	13.3
4	#12930.00	39.1 AV	68.2	-29.1	1.60 V	307	25.8	13.3
5	19395.00	49.4 PK	74.0	-24.6	1.20 V	317	56.2	-6.8
6	19395.00	41.2 AV	54.0	-12.8	1.20 V	317	48.0	-6.8
7	#25860.00	47.1 PK	88.2	-41.1	1.26 V	285	48.8	-1.7
8	#25860.00	36.9 AV	68.2	-31.3	1.26 V	285	38.6	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 119 : 6545 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6545.00	109.2 PK			1.56 H	11	103.2	6.0
2	*6545.00	99.5 AV			1.56 H	11	93.5	6.0
3	#13090.00	47.9 PK	88.2	-40.3	1.64 H	339	34.4	13.5
4	#13090.00	39.5 AV	68.2	-28.7	1.64 H	339	26.0	13.5
5	19635.00	47.8 PK	74.0	-26.2	1.10 H	312	53.9	-6.1
6	19635.00	37.1 AV	54.0	-16.9	1.10 H	312	43.2	-6.1
7	#26180.00	46.3 PK	88.2	-41.9	1.34 H	313	47.5	-1.2
8	#26180.00	36.2 AV	68.2	-32.0	1.34 H	313	37.4	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6545.00	114.4 PK			2.67 V	360	108.4	6.0
2	*6545.00	103.9 AV			2.67 V	360	97.9	6.0
3	#13090.00	47.7 PK	88.2	-40.5	1.64 V	336	34.2	13.5
4	#13090.00	39.7 AV	68.2	-28.5	1.64 V	336	26.2	13.5
5	19635.00	48.3 PK	74.0	-25.7	1.26 V	314	54.4	-6.1
6	19635.00	40.6 AV	54.0	-13.4	1.26 V	314	46.7	-6.1
7	#26180.00	47.8 PK	88.2	-40.4	1.27 V	311	49.0	-1.2
8	#26180.00	37.6 AV	68.2	-30.6	1.27 V	311	38.8	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 135 : 6625 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6625.00	108.9 PK			1.55 H	27	102.7	6.2
2	*6625.00	99.3 AV			1.55 H	27	93.1	6.2
3	13250.00	47.7 PK	74.0	-26.3	1.68 H	344	33.4	14.3
4	13250.00	39.4 AV	54.0	-14.6	1.68 H	344	25.1	14.3
5	19875.00	47.9 PK	74.0	-26.1	1.12 H	322	54.0	-6.1
6	19875.00	37.4 AV	54.0	-16.6	1.12 H	322	43.5	-6.1
7	#26500.00	46.0 PK	88.2	-42.2	1.39 H	309	46.8	-0.8
8	#26500.00	35.7 AV	68.2	-32.5	1.39 H	309	36.5	-0.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6625.00	115.0 PK			2.62 V	357	108.8	6.2
2	*6625.00	104.4 AV			2.62 V	357	98.2	6.2
3	13250.00	47.8 PK	74.0	-26.2	1.69 V	310	33.5	14.3
4	13250.00	39.5 AV	54.0	-14.5	1.69 V	310	25.2	14.3
5	19875.00	48.4 PK	74.0	-25.6	1.22 V	293	54.5	-6.1
6	19875.00	40.6 AV	54.0	-13.4	1.22 V	293	46.7	-6.1
7	#26500.00	47.6 PK	88.2	-40.6	1.24 V	285	48.4	-0.8
8	#26500.00	37.3 AV	68.2	-30.9	1.24 V	285	38.1	-0.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 151 : 6705 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6705.00	108.3 PK			1.58 H	1	102.2	6.1
2	*6705.00	99.1 AV			1.58 H	1	93.0	6.1
3	#13410.00	47.1 PK	88.2	-41.1	1.59 H	348	32.3	14.8
4	#13410.00	38.7 AV	68.2	-29.5	1.59 H	348	23.9	14.8
5	20115.00	47.8 PK	74.0	-26.2	1.15 H	326	53.3	-5.5
6	20115.00	37.2 AV	54.0	-16.8	1.15 H	326	42.7	-5.5
7	#26820.00	45.8 PK	88.2	-42.4	1.31 H	329	46.8	-1.0
8	#26820.00	35.7 AV	68.2	-32.5	1.31 H	329	36.7	-1.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6705.00	115.4 PK			2.67 V	351	109.3	6.1
2	*6705.00	104.5 AV			2.67 V	351	98.4	6.1
3	#13410.00	47.9 PK	88.2	-40.3	1.60 V	305	33.1	14.8
4	#13410.00	39.7 AV	68.2	-28.5	1.60 V	305	24.9	14.8
5	20115.00	49.1 PK	74.0	-24.9	1.22 V	302	54.6	-5.5
6	20115.00	40.8 AV	54.0	-13.2	1.22 V	302	46.3	-5.5
7	#26820.00	47.3 PK	88.2	-40.9	1.26 V	291	48.3	-1.0
8	#26820.00	37.1 AV	68.2	-31.1	1.26 V	291	38.1	-1.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 167 : 6785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6785.00	108.7 PK			1.60 H	14	102.4	6.3
2	*6785.00	99.1 AV			1.60 H	14	92.8	6.3
3	#13570.00	47.9 PK	88.2	-40.3	1.58 H	348	33.0	14.9
4	#13570.00	39.2 AV	68.2	-29.0	1.58 H	348	24.3	14.9
5	20355.00	47.9 PK	74.0	-26.1	1.12 H	305	53.5	-5.6
6	20355.00	37.3 AV	54.0	-16.7	1.12 H	305	42.9	-5.6
7	#27140.00	46.5 PK	88.2	-41.7	1.29 H	338	47.8	-1.3
8	#27140.00	35.9 AV	68.2	-32.3	1.29 H	338	37.2	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6785.00	115.0 PK			2.66 V	360	108.7	6.3
2	*6785.00	104.5 AV			2.66 V	360	98.2	6.3
3	#13570.00	47.5 PK	88.2	-40.7	1.69 V	329	32.6	14.9
4	#13570.00	39.1 AV	68.2	-29.1	1.69 V	329	24.2	14.9
5	20355.00	49.2 PK	74.0	-24.8	1.27 V	298	54.8	-5.6
6	20355.00	40.9 AV	54.0	-13.1	1.27 V	298	46.5	-5.6
7	#27140.00	47.8 PK	88.2	-40.4	1.31 V	308	49.1	-1.3
8	#27140.00	37.2 AV	68.2	-31.0	1.31 V	308	38.5	-1.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 183 : 6865 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6865.00	107.8 PK			1.53 H	5	100.9	6.9
2	*6865.00	98.6 AV			1.53 H	5	91.7	6.9
3	#13730.00	47.8 PK	88.2	-40.4	1.67 H	360	32.1	15.7
4	#13730.00	39.2 AV	68.2	-29.0	1.67 H	360	23.5	15.7
5	20595.00	48.4 PK	74.0	-25.6	1.17 H	322	53.1	-4.7
6	20595.00	37.4 AV	54.0	-16.6	1.17 H	322	42.1	-4.7
7	#27460.00	46.5 PK	88.2	-41.7	1.37 H	328	47.9	-1.4
8	#27460.00	35.8 AV	68.2	-32.4	1.37 H	328	37.2	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6865.00	115.2 PK			2.66 V	360	108.3	6.9
2	*6865.00	104.5 AV			2.66 V	360	97.6	6.9
3	#13730.00	47.5 PK	88.2	-40.7	1.59 V	329	31.8	15.7
4	#13730.00	39.6 AV	68.2	-28.6	1.59 V	329	23.9	15.7
5	20595.00	48.4 PK	74.0	-25.6	1.19 V	296	53.1	-4.7
6	20595.00	40.3 AV	54.0	-13.7	1.19 V	296	45.0	-4.7
7	#27460.00	47.6 PK	88.2	-40.6	1.21 V	311	49.0	-1.4
8	#27460.00	37.2 AV	68.2	-31.0	1.21 V	311	38.6	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 199 : 6945 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6945.00	108.8 PK			1.54 H	19	101.5	7.3
2	*6945.00	99.0 AV			1.54 H	19	91.7	7.3
3	#13890.00	47.2 PK	88.2	-41.0	1.63 H	336	31.4	15.8
4	#13890.00	38.6 AV	68.2	-29.6	1.63 H	336	22.8	15.8
5	20835.00	47.7 PK	74.0	-26.3	1.17 H	325	52.5	-4.8
6	20835.00	37.2 AV	54.0	-16.8	1.17 H	325	42.0	-4.8
7	#27780.00	46.5 PK	88.2	-41.7	1.31 H	315	48.4	-1.9
8	#27780.00	36.1 AV	68.2	-32.1	1.31 H	315	38.0	-1.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6945.00	114.8 PK			2.60 V	349	107.5	7.3
2	*6945.00	104.0 AV			2.60 V	349	96.7	7.3
3	#13890.00	47.2 PK	88.2	-41.0	1.67 V	307	31.4	15.8
4	#13890.00	39.4 AV	68.2	-28.8	1.67 V	307	23.6	15.8
5	20835.00	49.1 PK	74.0	-24.9	1.18 V	288	53.9	-4.8
6	20835.00	41.0 AV	54.0	-13.0	1.18 V	288	45.8	-4.8
7	#27780.00	48.0 PK	88.2	-40.2	1.28 V	282	49.9	-1.9
8	#27780.00	37.4 AV	68.2	-30.8	1.28 V	282	39.3	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 215 : 7025 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7025.00	108.6 PK			1.56 H	12	100.6	8.0
2	*7025.00	99.1 AV			1.56 H	12	91.1	8.0
3	#7125.80	61.2 PK	88.2	-27.0	1.56 H	12	53.0	8.2
4	#7125.80	51.8 AV	68.2	-16.4	1.56 H	12	43.6	8.2
5	#14050.00	47.7 PK	88.2	-40.5	1.59 H	360	31.6	16.1
6	#14050.00	39.4 AV	68.2	-28.8	1.59 H	360	23.3	16.1
7	21075.00	47.5 PK	74.0	-26.5	1.11 H	309	51.8	-4.3
8	21075.00	36.9 AV	54.0	-17.1	1.11 H	309	41.2	-4.3
9	#28100.00	46.4 PK	88.2	-41.8	1.32 H	316	47.8	-1.4
10	#28100.00	36.1 AV	68.2	-32.1	1.32 H	316	37.5	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7025.00	115.7 PK			1.71 V	358	107.7	8.0
2	*7025.00	105.0 AV			1.71 V	358	97.0	8.0
3	#7125.00	70.8 PK	88.2	-17.4	1.71 V	358	62.6	8.2
4	#7125.00	58.5 AV	68.2	-9.7	1.71 V	358	50.3	8.2
5	#14050.00	47.8 PK	88.2	-40.4	1.70 V	323	31.7	16.1
6	#14050.00	39.7 AV	68.2	-28.5	1.70 V	323	23.6	16.1
7	21075.00	47.9 PK	74.0	-26.1	1.24 V	288	52.2	-4.3
8	21075.00	40.2 AV	54.0	-13.8	1.24 V	288	44.5	-4.3
9	#28100.00	47.3 PK	88.2	-40.9	1.21 V	294	48.7	-1.4
10	#28100.00	37.1 AV	68.2	-31.1	1.21 V	294	38.5	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 47 : 6185 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5858.32	51.2 PK	88.2	-37.0	2.08 H	220	47.3	3.9
2	#5858.32	41.6 AV	68.2	-26.6	2.08 H	220	37.7	3.9
3	*6185.00	105.9 PK			2.08 H	220	101.4	4.5
4	*6185.00	96.0 AV			2.08 H	220	91.5	4.5
5	12370.00	47.3 PK	74.0	-26.7	1.58 H	358	34.3	13.0
6	12370.00	38.9 AV	54.0	-15.1	1.58 H	358	25.9	13.0
7	18555.00	48.3 PK	74.0	-25.7	1.11 H	302	55.5	-7.2
8	18555.00	37.4 AV	54.0	-16.6	1.11 H	302	44.6	-7.2
9	#24740.00	46.3 PK	88.2	-41.9	1.29 H	321	48.0	-1.7
10	#24740.00	35.9 AV	68.2	-32.3	1.29 H	321	37.6	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5845.00	52.0 PK	88.2	-36.2	2.42 V	349	48.1	3.9
2	#5845.00	40.4 AV	68.2	-27.8	2.42 V	349	36.5	3.9
3	*6185.00	113.3 PK			2.42 V	349	108.8	4.5
4	*6185.00	102.2 AV			2.42 V	349	97.7	4.5
5	12370.00	46.7 PK	74.0	-27.3	1.62 V	329	33.7	13.0
6	12370.00	38.9 AV	54.0	-15.1	1.62 V	329	25.9	13.0
7	18555.00	48.9 PK	74.0	-25.1	1.16 V	303	56.1	-7.2
8	18555.00	40.8 AV	54.0	-13.2	1.16 V	303	48.0	-7.2
9	#24740.00	47.4 PK	88.2	-40.8	1.32 V	291	49.1	-1.7
10	#24740.00	36.8 AV	68.2	-31.4	1.32 V	291	38.5	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 79 : 6345 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6345.00	105.1 PK			1.47 H	12	99.9	5.2
2	*6345.00	95.2 AV			1.47 H	12	90.0	5.2
3	12690.00	47.5 PK	74.0	-26.5	1.55 H	359	34.8	12.7
4	12690.00	38.8 AV	54.0	-15.2	1.55 H	359	26.1	12.7
5	19035.00	47.3 PK	74.0	-26.7	1.12 H	301	54.2	-6.9
6	19035.00	36.6 AV	54.0	-17.4	1.12 H	301	43.5	-6.9
7	#25380.00	46.8 PK	88.2	-41.4	1.37 H	335	48.6	-1.8
8	#25380.00	36.1 AV	68.2	-32.1	1.37 H	335	37.9	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6345.00	112.2 PK			1.67 V	360	107.0	5.2
2	*6345.00	101.7 AV			1.67 V	360	96.5	5.2
3	12690.00	47.0 PK	74.0	-27.0	1.62 V	327	34.3	12.7
4	12690.00	39.1 AV	54.0	-14.9	1.62 V	327	26.4	12.7
5	19035.00	48.8 PK	74.0	-25.2	1.19 V	292	55.7	-6.9
6	19035.00	41.0 AV	54.0	-13.0	1.19 V	292	47.9	-6.9
7	#25380.00	47.7 PK	88.2	-40.5	1.29 V	302	49.5	-1.8
8	#25380.00	37.4 AV	68.2	-30.8	1.29 V	302	39.2	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 111 : 6505 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6505.00	105.2 PK			1.52 H	20	99.2	6.0
2	*6505.00	95.4 AV			1.52 H	20	89.4	6.0
3	#13010.00	47.3 PK	88.2	-40.9	1.58 H	360	34.0	13.3
4	#13010.00	38.8 AV	68.2	-29.4	1.58 H	360	25.5	13.3
5	19515.00	47.8 PK	74.0	-26.2	1.12 H	326	54.1	-6.3
6	19515.00	37.0 AV	54.0	-17.0	1.12 H	326	43.3	-6.3
7	#26020.00	45.9 PK	88.2	-42.3	1.39 H	332	47.3	-1.4
8	#26020.00	35.7 AV	68.2	-32.5	1.39 H	332	37.1	-1.4

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6505.00	112.1 PK			1.77 V	356	106.1	6.0
2	*6505.00	101.5 AV			1.77 V	356	95.5	6.0
3	#13010.00	47.1 PK	88.2	-41.1	1.67 V	317	33.8	13.3
4	#13010.00	39.2 AV	68.2	-29.0	1.67 V	317	25.9	13.3
5	19515.00	48.7 PK	74.0	-25.3	1.20 V	314	55.0	-6.3
6	19515.00	41.0 AV	54.0	-13.0	1.20 V	314	47.3	-6.3
7	#26020.00	47.9 PK	88.2	-40.3	1.25 V	297	49.3	-1.4
8	#26020.00	37.6 AV	68.2	-30.6	1.25 V	297	39.0	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 143 : 6665 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6665.00	105.3 PK			1.53 H	17	99.2	6.1
2	*6665.00	95.3 AV			1.53 H	17	89.2	6.1
3	13330.00	47.9 PK	74.0	-26.1	1.56 H	334	33.1	14.8
4	13330.00	39.5 AV	54.0	-14.5	1.56 H	334	24.7	14.8
5	19995.00	47.4 PK	74.0	-26.6	1.12 H	325	53.1	-5.7
6	19995.00	36.7 AV	54.0	-17.3	1.12 H	325	42.4	-5.7
7	#26660.00	46.3 PK	88.2	-41.9	1.34 H	344	46.9	-0.6
8	#26660.00	36.2 AV	68.2	-32.0	1.34 H	344	36.8	-0.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6665.00	112.8 PK			1.75 V	360	106.7	6.1
2	*6665.00	101.9 AV			1.75 V	360	95.8	6.1
3	13330.00	47.1 PK	74.0	-26.9	1.64 V	332	32.3	14.8
4	13330.00	38.8 AV	54.0	-15.2	1.64 V	332	24.0	14.8
5	19995.00	48.5 PK	74.0	-25.5	1.20 V	290	54.2	-5.7
6	19995.00	40.2 AV	54.0	-13.8	1.20 V	290	45.9	-5.7
7	#26660.00	47.6 PK	88.2	-40.6	1.22 V	309	48.2	-0.6
8	#26660.00	37.2 AV	68.2	-31.0	1.22 V	309	37.8	-0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 175 : 6825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6825.00	104.9 PK			1.42 H	7	98.4	6.5
2	*6825.00	95.0 AV			1.42 H	7	88.5	6.5
3	#13650.00	47.5 PK	88.2	-40.7	1.14 H	305	32.2	15.3
4	#13650.00	36.7 AV	68.2	-31.5	1.14 H	305	21.4	15.3
5	20475.00	46.3 PK	74.0	-27.7	1.37 H	336	51.4	-5.1
6	20475.00	36.0 AV	54.0	-18.0	1.37 H	336	41.1	-5.1
7	#27300.00	46.8 PK	88.2	-41.4	1.44 H	345	48.6	-1.8
8	#27300.00	36.1 AV	68.2	-32.1	1.44 H	345	37.9	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6825.00	112.3 PK			1.70 V	360	105.8	6.5
2	*6825.00	101.4 AV			1.70 V	360	94.9	6.5
3	#13650.00	47.4 PK	88.2	-40.8	1.62 V	308	32.1	15.3
4	#13650.00	39.3 AV	68.2	-28.9	1.62 V	308	24.0	15.3
5	20475.00	49.0 PK	74.0	-25.0	1.27 V	292	54.1	-5.1
6	20475.00	41.1 AV	54.0	-12.9	1.27 V	292	46.2	-5.1
7	#27300.00	47.7 PK	88.2	-40.5	1.31 V	312	49.5	-1.8
8	#27300.00	37.6 AV	68.2	-30.6	1.31 V	312	39.4	-1.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE160)	Channel	CH 207 : 6985 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6985.00	105.1 PK			1.48 H	14	97.4	7.7
2	*6985.00	95.3 AV			1.48 H	14	87.6	7.7
3	#7125.00	63.4 PK	88.2	-24.8	1.48 H	14	55.2	8.2
4	#7125.00	55.5 AV	68.2	-12.7	1.48 H	14	47.3	8.2
5	#13970.00	47.7 PK	88.2	-40.5	1.66 H	345	31.9	15.8
6	#13970.00	39.2 AV	68.2	-29.0	1.66 H	345	23.4	15.8
7	20955.00	48.4 PK	74.0	-25.6	1.20 H	323	52.9	-4.5
8	20955.00	37.5 AV	54.0	-16.5	1.20 H	323	42.0	-4.5
9	#27940.00	46.9 PK	88.2	-41.3	1.39 H	341	48.1	-1.2
10	#27940.00	36.3 AV	68.2	-31.9	1.39 H	341	37.5	-1.2

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6985.00	112.4 PK			1.72 V	359	104.7	7.7
2	*6985.00	101.7 AV			1.72 V	359	94.0	7.7
3	#7125.00	79.1 PK	88.2	-9.1	1.72 V	359	70.9	8.2
4	#7125.00	62.2 AV	68.2	-6.0	1.72 V	359	54.0	8.2
5	#13970.00	47.5 PK	88.2	-40.7	1.60 V	313	31.7	15.8
6	#13970.00	39.3 AV	68.2	-28.9	1.60 V	313	23.5	15.8
7	20955.00	48.7 PK	74.0	-25.3	1.27 V	308	53.2	-4.5
8	20955.00	40.8 AV	54.0	-13.2	1.27 V	308	45.3	-4.5
9	#27940.00	47.7 PK	88.2	-40.5	1.21 V	297	48.9	-1.2
10	#27940.00	37.1 AV	68.2	-31.1	1.21 V	297	38.3	-1.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

4.1.7 Test Results (Mode 2)

Above 1GHz Data:

RF Mode	TX 802.11ax (HE20)	Channel	CH 33 : 6115 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5916.24	52.9 PK	88.2	-35.3	3.88 H	124	49.2	3.7
2	#5916.24	41.5 AV	68.2	-26.7	3.88 H	124	37.8	3.7
3	*6115.00	111.4 PK			3.88 H	124	107.1	4.3
4	*6115.00	101.3 AV			3.88 H	124	97.0	4.3
5	12230.00	48.8 PK	74.0	-25.2	1.57 H	336	35.7	13.1
6	12230.00	40.7 AV	54.0	-13.3	1.57 H	336	27.6	13.1
7	18345.00	48.8 PK	74.0	-25.2	1.14 H	320	56.0	-7.2
8	18345.00	36.3 AV	54.0	-17.7	1.14 H	320	43.5	-7.2
9	#24460.00	45.9 PK	88.2	-42.3	1.36 H	335	48.0	-2.1
10	#24460.00	35.9 AV	68.2	-32.3	1.36 H	335	38.0	-2.1

Antenna Polarity & Test Distance : Vertical at 3 m

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5863.00	52.3 PK	88.2	-35.9	1.68 V	358	48.4	3.9
2	#5863.00	40.4 AV	68.2	-27.8	1.68 V	358	36.5	3.9
3	*6115.00	117.8 PK			1.68 V	358	113.5	4.3
4	*6115.00	106.6 AV			1.68 V	358	102.3	4.3
5	12230.00	48.1 PK	74.0	-25.9	1.59 V	316	35.0	13.1
6	12230.00	39.8 AV	54.0	-14.2	1.59 V	316	26.7	13.1
7	18345.00	50.2 PK	74.0	-23.8	1.25 V	331	57.4	-7.2
8	18345.00	41.7 AV	54.0	-12.3	1.25 V	331	48.9	-7.2
9	#24460.00	49.0 PK	88.2	-39.2	1.38 V	317	51.1	-2.1
10	#24460.00	38.4 AV	68.2	-29.8	1.38 V	317	40.5	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.