

FCC Test Report (WLAN)

Report No.: RFBBQZ-WTW-P21060012-1

FCC ID: PY321100531

Test Model: MR70

Series Model: MS70

Received Date: 2021/6/7

Test Date: 2021/10/9 ~ 2021/10/20

Issued Date: 2021/10/29

**Applicant and
Manufacturer:** NETGEAR, Inc.

Address: 350 East Plumeria Drive San Jose, CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

| | |
|--|-----------|
| Release Control Record | 4 |
| 1 Certificate of Conformity | 5 |
| 2 Summary of Test Results | 6 |
| 2.1 Measurement Uncertainty | 6 |
| 2.2 Modification Record | 6 |
| 3 General Information | 7 |
| 3.1 General Description of EUT | 7 |
| 3.2 Description of Test Modes | 10 |
| 3.2.1 Test Mode Applicability and Tested Channel Detail | 12 |
| 3.3 Duty Cycle of Test Signal | 15 |
| 3.4 Description of Support Units | 16 |
| 3.4.1 Configuration of System under Test | 16 |
| 3.5 General Description of Applied Standard and References | 17 |
| 4 Test Types and Results | 18 |
| 4.1 Radiated Emission and Bandedge Measurement | 18 |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 18 |
| 4.1.2 Test Instruments | 19 |
| 4.1.3 Test Procedure | 21 |
| 4.1.4 Deviation from Test Standard | 22 |
| 4.1.5 Test Setup | 22 |
| 4.1.6 EUT Operating Condition | 23 |
| 4.1.7 Test Results | 24 |
| 4.2 Conducted Emission Measurement | 70 |
| 4.2.1 Limits of Conducted Emission Measurement | 70 |
| 4.2.2 Test Instruments | 70 |
| 4.2.3 Test Procedure | 71 |
| 4.2.4 Deviation from Test Standard | 71 |
| 4.2.5 Test Setup | 71 |
| 4.2.6 EUT Operating Condition | 71 |
| 4.2.7 Test Results | 72 |
| 4.3 Transmit Power Measurement | 74 |
| 4.3.1 Limits of Transmit Power Measurement | 74 |
| 4.3.2 Test Setup | 74 |
| 4.3.3 Test Instruments | 75 |
| 4.3.4 Test Procedure | 75 |
| 4.3.5 Deviation from Test Standard | 75 |
| 4.3.6 EUT Operating Condition | 75 |
| 4.3.7 Test Results | 76 |
| 4.4 Occupied Bandwidth Measurement | 106 |
| 4.4.1 Test Setup | 106 |
| 4.4.2 Test Instruments | 106 |
| 4.4.3 Test Procedure | 106 |
| 4.4.4 Test Results | 107 |
| 4.5 Peak Power Spectral Density Measurement | 114 |
| 4.5.1 Limits of Peak Power Spectral Density Measurement | 114 |
| 4.5.2 Test Setup | 114 |
| 4.5.3 Test Instruments | 114 |
| 4.5.4 Test Procedure | 114 |
| 4.5.5 Deviation from Test Standard | 115 |
| 4.5.6 EUT Operating Condition | 115 |
| 4.5.7 Test Results | 116 |

| | | |
|----------|--|------------|
| 4.6 | Frequency Stability Measurement..... | 122 |
| 4.6.1 | Limits of Frequency Stability Measurement | 122 |
| 4.6.2 | Test Setup..... | 122 |
| 4.6.3 | Test Instruments | 122 |
| 4.6.4 | Test Procedure | 122 |
| 4.6.5 | Deviation from Test Standard | 122 |
| 4.6.6 | EUT Operating Condition | 122 |
| 4.6.7 | Test Results | 123 |
| 4.7 | 6dB Bandwidth Measurement..... | 124 |
| 4.7.1 | Limits of 6dB Bandwidth Measurement..... | 124 |
| 4.7.2 | Test Setup..... | 124 |
| 4.7.3 | Test Instruments | 124 |
| 4.7.4 | Test Procedure | 124 |
| 4.7.5 | Deviation from Test Standard | 124 |
| 4.7.6 | EUT Operating Condition | 124 |
| 4.7.7 | Test Results | 125 |
| 5 | Pictures of Test Arrangements..... | 127 |
| | Annex A - Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band) | 128 |
| | Annex B - Band-Edge Measurement (For U-NII-1, U-NII-2A, U-NII-2C band) | 131 |
| | Appendix – Information of the Testing Laboratories | 139 |

Release Control Record

| Issue No. | Description | Date Issued |
|------------------------|-------------------|-------------|
| RFBBQZ-WTW-P21060012-1 | Original release. | 2021/10/29 |

1 Certificate of Conformity

Product: Mesh WiFi 6 Router, Mesh WiFi 6 Satellite

Brand: NETGEAR

Test Model: MR70

Series Model: MS70

Sample Status: Engineering sample

**Applicant and
Manufacturer:** NETGEAR, Inc.

Test Date: 2021/10/9 ~ 2021/10/20

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** 2021/10/29
Vivian Huang / Specialist

Approved by : Clark Lin , **Date:** 2021/10/29
Clark Lin / Technical Manager

2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart E (Section 15.407) | | | |
|--|---|--------|--|
| FCC Clause | Test Item | Result | Remarks |
| 15.407(b)(6) | AC Power Conducted Emissions | Pass | Meet the requirement of limit. Minimum passing margin is -10.80dB at 0.26719 MHz. |
| 15.407(b) (1/2/3/4(i/ii)/6) | Radiated Emissions & Band Edge Measurement* | Pass | Meet the requirement of limit. Minimum passing margin is -0.1 dB at 5470.00 MHz, 5919.07 MHz, 5149.30 MHz and 5466.00 MHz. |
| 15.407(a)(1/2/3) | Max Average Transmit Power | Pass | Meet the requirement of limit. |
| --- | Occupied Bandwidth Measurement | - | Reference only. |
| 15.407(a)(1/2/3) | Peak Power Spectral Density | Pass | Meet the requirement of limit. |
| 15.407(e) | 6dB bandwidth | Pass | Meet the requirement of limit. (U-NII-3 Band only) |
| 15.407(g) | Frequency Stability | Pass | Meet the requirement of limit. |
| 15.203 | Antenna Requirement | Pass | Antenna connector is ipex(MHF) not a standard connector. |

Note:

- For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.
- For U-NII-1, U-NII-2A, U-NII-2C band compliance with rule 15.407(b) of the band-edge items, the test plots were recorded in Annex B. Test Procedures refer to report 4.1.3.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement | Frequency | Expanded Uncertainty (k=2) (\pm) |
|------------------------------------|----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 1.9 dB |
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz | 3.1 dB |
| | 30MHz ~ 1GHz | 5.5 dB |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz | 5.1 dB |
| | 18GHz ~ 40GHz | 5.3 dB |

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

| | |
|-----------------------|--|
| Product | Mesh WiFi 6 Router, Mesh WiFi 6 Satellite |
| Brand | NETGEAR |
| Test Model | MR70 |
| Series Model | MS70 |
| Status of EUT | Engineering sample |
| Power Supply Rating | 12 Vdc from power adapter |
| Modulation Type | 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode 1024QAM for OFDMA in 11ax HE mode |
| Modulation Technology | OFDM, OFDMA |
| Transfer Rate | 802.11a: up to 54 Mbps 802.11n: up to 300 Mbps 802.11ac: up to 1733.3 Mbps 802.11ax: up to 2401.9 Mbps |
| Operating Frequency | 5.18~5.32GHz, 5.50~5.72GHz, 5.745 ~ 5.825GHz |
| Number of Channel | 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 25 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 12 802.11ac (VHT80), 802.11ax (HE80): 6 802.11ac (VHT160), 802.11ax (HE160): 2 |
| Output Power | CDD Mode 5.18 ~ 5.25 GHz: 667.974 mW 5.25 ~ 5.32GHz: 247.558 mW 5.5 ~ 5.72GHz: 246.715 mW 5.745 ~ 5.825 GHz: 868.573 mW Beamforming Mode 5.18 ~ 5.25 GHz: 544.575 mW 5.25 ~ 5.32GHz: 247.558 mW 5.5 ~ 5.72GHz: 246.715 mW 5.745 ~ 5.825 GHz: 867.187 mW |
| Antenna Type | Refer to Note |
| Antenna Connector | Refer to Note |
| Accessory Device | Adapter x1 |
| Data Cable Supplied | NA |

Note:

- The EUT has two model names, which are identical to each other in all aspects except for the following information:

| Product Name | Model Name | Description |
|-----------------------|------------|--|
| Mesh WiFi 6 Router | MR70 | Function: Master, WAN port and single GPHY |
| Mesh WiFi 6 Satellite | MS70 | Function: Master+Client |

Note: From the above models, the worst model was found in **MR70**. Therefore only the test data of the modes were recorded in this report.

- The EUT has below radios as following table:

| Radio 1 | Radio 2 |
|-------------|-----------|
| WLAN 2.4GHz | WLAN 5GHz |

3. Simultaneously transmission condition.

| Condition | Technology | |
|-----------|--------------------|------------------|
| 1 | WLAN (2.4GHz)_Ant0 | WLAN (5GHz)_Ant1 |
| 2 | WLAN (2.4GHz)_Ant1 | WLAN (5GHz)_Ant0 |

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The EUT must be supplied one power adapter and following different models could be chosen as following table:

| No. | Brand | Model name | Part Number | Spec | plug | Difference |
|-----|---------|------------|-----------------------------------|---|------|---|
| 1 | NETGEAR | 2ABB018F 1 | 332-10927-01 & 332-10927-02 | Input: 100-120Vac, 50/60Hz, 0.6A Output: 12Vdc, 1.5A Output Cable: Unshielded, 1.8m, Without core | US | Design are identical, the only difference is manufacture location. |
| 2 | NETGEAR | AD2076F10 | 332-10993-01 & 332-10993-03 | Input: 100-120Vac, 50/60Hz, 0.56A Output: 12Vdc, 1.5A Output Cable: Unshielded, 1.8m, Without core | US | Design are identical , the differences are: 1)manufacture location 2)-01 has BSMI logo, and -03 does not have BSMI logo. |

Note:

- From the above adapters, the worst Radiated Emissions was found in Adapter 2 and the worst Conducted Emissions test was found in Adapter 1. Therefore only the test data of the modes were recorded in this report.

5. The antennas provided to the EUT, please refer to the following table:

| Antenna NO. | RF Chain NO. | Antenna Net Gain(dBi) | Frequency range | Antenna Type | Connector Type |
|-------------|--------------|-----------------------|-----------------|--------------|----------------|
| 2.4G_0 | 0 | 2.85 | 2.4~2.4835GHz | PIFA | ipex(MHF) |
| 2.4G_1 | 1 | 2.8 | 2.4~2.4835GHz | PIFA | ipex(MHF) |
| 5G_0 | 0 | 2.11 | 5.15~5.25GHz | PIFA | ipex(MHF) |
| | | 2.11 | 5.25~5.35GHz | | |
| | | 2.45 | 5.47~5.725GHz | | |
| | | 2.31 | 5.725~5.85GHz | | |
| 5G_1 | 1 | 2.82 | 5.15~5.25GHz | PIFA | ipex(MHF) |
| | | 2.82 | 5.25~5.35GHz | | |
| | | 2.65 | 5.47~5.725GHz | | |
| | | 2.74 | 5.725~5.85GHz | | |

6. The EUT incorporates a MIMO function:

| 5GHz Band | | |
|-------------------|-----------------------|-----|
| MODULATION MODE | TX & RX CONFIGURATION | |
| 802.11a | 2TX | 2RX |
| 802.11n (HT20) | 2TX | 2RX |
| 802.11n (HT40) | 2TX | 2RX |
| 802.11ac (VHT20) | 2TX | 2RX |
| 802.11ac (VHT40) | 2TX | 2RX |
| 802.11ac (VHT80) | 2TX | 2RX |
| 802.11ac (VHT160) | 2TX | 2RX |
| 802.11ax (HE20) | 2TX | 2RX |
| 802.11ax (HE40) | 2TX | 2RX |
| 802.11ax (HE80) | 2TX | 2RX |
| 802.11ax (HE160) | 2TX | 2RX |

Note:

1. All of modulation mode support beamforming function except 802.11a modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz), 802.11ac mode for 20MHz (40MHz, 80MHz, 160MHz) and 802.11ax mode for 20MHz (40MHz, 80MHz, 160MHz), therefore the manufacturer will control the power for 802.11n/ac mode is the same as the 802.11ax mode or more lower than it and investigated worst case to representative mode in test report. (Final test mode refer to section 3.2.1)

7. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

8. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

FOR 5180 ~ 5320MHz

8 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20) and 802.11ax (HE20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 36 | 5180 MHz | 52 | 5260 MHz |
| 40 | 5200 MHz | 56 | 5280 MHz |
| 44 | 5220 MHz | 60 | 5300 MHz |
| 48 | 5240 MHz | 64 | 5320 MHz |

4 channels are provided for 802.11n (HT40), 802.11ac (VHT40) and 802.11ax (HE40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 38 | 5190 MHz | 54 | 5270 MHz |
| 46 | 5230 MHz | 62 | 5310 MHz |

2 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 42 | 5210 MHz | 58 | 5290 MHz |

1 straddle channel is provided for 802.11ac (VHT160), 802.11ax (HE160):

| Channel | Frequency |
|---------|-----------|
| 50 | 5250 MHz |

FOR 5500 ~ 5720MHz

12 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20) and 802.11ax (HE20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 100 | 5500 MHz | 124 | 5620 MHz |
| 104 | 5520 MHz | 128 | 5640 MHz |
| 108 | 5540 MHz | 132 | 5660 MHz |
| 112 | 5560 MHz | 136 | 5680 MHz |
| 116 | 5580 MHz | 140 | 5700 MHz |
| 120 | 5600 MHz | 144 | 5720 MHz |

6 channels are provided for 802.11n (HT40), 802.11ac (VHT40) and 802.11ax (HE40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 102 | 5510 MHz | 126 | 5630 MHz |
| 110 | 5550 MHz | 134 | 5670 MHz |
| 118 | 5590 MHz | 142 | 5710 MHz |

3 channels are provided for 802.11ac (VHT80), 802.11ax (HE80):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 106 | 5530 MHz | 138 | 5690 MHz |
| 122 | 5610 MHz | | |

1 straddle channel is provided for 802.11ac (VHT160), 802.11ax (HE160):

| Channel | Frequency |
|---------|-----------|
| 114 | 5570 MHz |

FOR 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20) and 802.11ax (HE20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 149 | 5745 MHz | 161 | 5805 MHz |
| 153 | 5765 MHz | 165 | 5825 MHz |
| 157 | 5785 MHz | | |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40) and 802.11ax (HE40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 151 | 5755 MHz | 159 | 5795 MHz |

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

| Channel | Frequency |
|---------|-----------|
| 155 | 5775 MHz |

3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable To | | | | Description |
|--------------------|---------------|-------|-----|------|-------------|
| | RE \geq 1G | RE<1G | PLC | APCM | |
| - | √ | √ | √ | √ | - |

Where **RE \geq 1G**: Radiated Emission above 1GHz
RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission
APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| CDD Mode | | | | | | |
|------------------|------------------|-------------------|------------------------|-----------------------|-----------------|---------------------|
| Mode | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate Parameter |
| 802.11a | 5180-5320 | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDM | BPSK | 6Mb/s |
| 802.11ax (HE20) | | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 38 to 62 | 38, 46, 54, 62 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 42, 58 | 42, 58 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE160) | | 50 | 50 | OFDMA | BPSK | MCS0 |
| 802.11a | 5500-5720 | 100 to 144 | 100, 116, 140, 144 | OFDM | BPSK | 6Mb/s |
| 802.11ax (HE20) | | 100 to 144 | 100, 116, 140, 144 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 102 to 142 | 102, 110, 134, 142 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 106 to 138 | 106, 122, 138 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE160) | | 114 | 114 | OFDMA | BPSK | MCS0 |
| 802.11a | 5745-5825 | 149 to 165 | 149, 157, 165 | OFDM | BPSK | 6Mb/s |
| 802.11ax (HE20) | | 149 to 165 | 149, 157, 165 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 151 to 159 | 151, 159 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 155 | 155 | OFDMA | BPSK | MCS0 |

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| CDD Mode | | | | | | |
|-----------------|-------------------------------------|--------------------------------------|----------------|-----------------------|-----------------|---------------------|
| Mode | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate Parameter |
| 802.11ax (HE20) | 5180-5320 5500-5720 5745-5825 | 36 to 64 100 to 144 149 to 165 | 157 | OFDMA | BPSK | MCS0 |

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| CDD Mode | | | | | | |
|-----------------|------------------|-------------------|----------------|-----------------------|-----------------|---------------------|
| Mode | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate Parameter |
| 802.11ax (HE20) | 5180-5320 | 36 to 64 | 157 | OFDMA | BPSK | MCS0 |
| | 5500-5720 | 100 to 144 | | | | |
| | 5745-5825 | 149 to 165 | | | | |

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| CDD Mode | | | | | | |
|--|------------------|-------------------|------------------------|-----------------------|-----------------|---------------------|
| Mode | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate Parameter |
| 802.11a | 5180-5320 | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDM | BPSK | 6Mb/s |
| 802.11ac (VHT20) (Output power only) | | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT40) (Output power only) | | 38 to 62 | 38, 46, 54, 62 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT80) (Output power only) | | 42, 58 | 42, 58 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT160) (Output power only) | | 50 | 50 | OFDM | BPSK | MCS0 |
| 802.11ax (HE20) | | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 38 to 62 | 38, 46, 54, 62 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 42, 58 | 42, 58 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE160) | | 50 | 50 | OFDMA | BPSK | MCS0 |
| 802.11a | | 5500-5720 | 100 to 144 | 100, 116, 140, 144 | OFDM | BPSK |
| 802.11ac (VHT20) (Output power only) | 100 to 144 | | 100, 116, 140, 144 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT40) (Output power only) | 102 to 142 | | 102, 110, 134, 142 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT80) (Output power only) | 106 to 138 | | 106, 122, 138 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT160) (Output power only) | 114 | | 114 | OFDM | BPSK | MCS0 |
| 802.11ax (HE20) | 100 to 144 | | 100, 116, 140, 144 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | 102 to 142 | | 102, 110, 134, 142 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | 106 to 138 | | 106, 122, 138 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE160) | 114 | | 114 | OFDMA | BPSK | MCS0 |

| 802.11a | 5745-5825 | 149 to 165 | 149, 157, 165 | OFDM | BPSK | 6Mb/s |
|---|------------------|-------------------|------------------------|-----------------------|-----------------|---------------------|
| 802.11ac (VHT20) (Output power only) | | 149 to 165 | 149, 157, 165 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT40) (Output power only) | | 151 to 159 | 151, 159 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT80) (Output power only) | | 155 | 155 | OFDM | BPSK | MCS0 |
| 802.11ax (HE20) | | 149 to 165 | 149, 157, 165 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 151 to 159 | 151, 159 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 155 | 155 | OFDMA | BPSK | MCS0 |
| Beamforming Mode (output power only) | | | | | | |
| Mode | FREQ. Band (MHz) | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Data Rate Parameter |
| 802.11ac (VHT20) | 5180-5320 | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT40) | | 38 to 62 | 38, 46, 54, 62 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT80) | | 42, 58 | 42, 58 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT160) | | 50 | 50 | OFDM | BPSK | MCS0 |
| 802.11ax (HE20) | | 36 to 64 | 36, 40, 48, 52, 60, 64 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 38 to 62 | 38, 46, 54, 62 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 42, 58 | 42, 58 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE160) | | 50 | 50 | OFDMA | BPSK | MCS0 |
| 802.11ac (VHT20) | 5500-5720 | 100 to 144 | 100, 116, 140, 144 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT40) | | 102 to 142 | 102, 110, 134, 142 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT80) | | 106 to 138 | 106, 122, 138 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT160) | | 114 | 114 | OFDM | BPSK | MCS0 |
| 802.11ax (HE20) | | 100 to 144 | 100, 116, 140, 144 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 102 to 142 | 102, 110, 134, 142 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 106 to 138 | 106, 122, 138 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE160) | | 114 | 114 | OFDMA | BPSK | MCS0 |
| 802.11ac (VHT20) | 5745-5825 | 149 to 165 | 149, 157, 165 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT40) | | 151 to 159 | 151, 159 | OFDM | BPSK | MCS0 |
| 802.11ac (VHT80) | | 155 | 155 | OFDM | BPSK | MCS0 |
| 802.11ax (HE20) | | 149 to 165 | 149, 157, 165 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE40) | | 151 to 159 | 151, 159 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 155 | 155 | OFDMA | BPSK | MCS0 |
| 802.11ax (HE80) | | 155 | 155 | OFDMA | BPSK | MCS0 |

Test Condition:

| Applicable To | Environmental Conditions | Input Power | Tested By |
|-----------------------|--------------------------|--------------|--------------|
| RE _≥ 1G | 25deg. C, 75%RH | 120Vac, 60Hz | Carter Lin |
| RE _{<} 1G | 25deg. C, 68%RH | 120Vac, 60Hz | Tom Yang |
| PLC | 25deg. C, 68%RH | 120Vac, 60Hz | Sampson Chen |
| APCM | 25deg. C, 60%RH | 120Vac, 60Hz | Leon Dai |

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is $\geq 98\%$, duty factor is not required.

802.11a: Duty cycle = 2.963 ms / 3.003 ms = 0.987

802.11ax (HE20): Duty cycle = 2.961 ms / 3.011 ms = 0.983

802.11ax (HE40): Duty cycle = 2.969 ms / 3.007 ms = 0.987

802.11ax (HE80): Duty cycle = 2.957 ms / 2.997 ms = 0.987

802.11ax (HE160): Duty cycle = 1.483 ms / 1.508 ms = 0.983



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|---------|-------|-----------|------------|---------|-----------------|
| A. | Laptop | DELL | E5430 | 4YV4VY1 | FCC DoC | Provided by Lab |
| B. | Laptop | DELL | E5430 | HYV4VY1 | FCC DoC | Provided by Lab |

Note:

- All power cords of the above support units are non-shielded (1.8m).

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------|------|------------|--------------------|--------------|--------------------|
| 1. | DC Cable | 1 | 1.8 | No | 0 | Supplied by client |
| 2. | RJ-45 Cable | 1 | 10 | No | 0 | Provided by Lab |
| 3. | RJ-45 Cable | 1 | 10 | No | 0 | Provided by Lab |
| 4. | RJ-45 Cable | 1 | 2 | No | 0 | Supplied by client |

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standard and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart E (15.407)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To | | Limit | |
|---|-----------------|---|---|
| 789033 D02 General UNII Test Procedure New Rules v02r01 | | Field Strength at 3m | |
| | | PK:74 (dBuV/m) | AV:54 (dBuV/m) |
| Frequency Band | Applicable To | EIRP Limit | Equivalent Field Strength at 3m |
| 5150~5250 MHz | 15.407(b)(1) | PK:-27 (dBm/MHz) | PK:68.2(dBuV/m) |
| 5250~5350 MHz | 15.407(b)(2) | | |
| 5470~5725 MHz | 15.407(b)(3) | | |
| 5725~5850 MHz | 15.407(b)(4)(i) | PK:-27 (dBm/MHz) ^{*1} PK:10 (dBm/MHz) ^{*2} PK:15.6 (dBm/MHz) ^{*3} PK:27 (dBm/MHz) ^{*4} | PK: 68.2(dBuV/m) ^{*1} PK:105.2 (dBuV/m) ^{*2} PK: 110.8(dBuV/m) ^{*3} PK:122.2 (dBuV/m) ^{*4} |
| *1 beyond 75 MHz or more above of the band edge. | | *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. | |
| *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. | | *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. | |

Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.2 Test Instruments

For Radiated emission & Bandedge & OBE test:

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|---|----------------------|-------------|-----------------|------------------|
| Test Receiver Agilent | N9038A | MY51210202 | 2020/12/1 | 2021/11/30 |
| Software | ADT_Radiated_V8.7.08 | NA | NA | NA |
| Boresight Antenna Tower & Turn Table Max-Full | MF-7802BS | MF780208530 | NA | NA |
| Pre_Amplifier EMCI | EMC001340 | 980142 | 2021/5/24 | 2022/5/23 |
| LOOP ANTENNA Electro-Metrics | EM-6879 | 264 | 2021/3/5 | 2022/3/4 |
| RF Coaxial Cable JYEBO | 5D-FB | LOOPCAB-001 | 2021/1/7 | 2022/1/6 |
| RF Coaxial Cable JYEBO | 5D-FB | LOOPCAB-002 | 2021/1/7 | 2022/1/6 |
| Pre_Amplifier EMCI | EMC330N | 980701 | 2021/3/10 | 2022/3/9 |
| Trilog Broadband Antenna Schwarzbeck | VULB 9168 | 9168-406 | 2020/11/6 | 2021/11/5 |
| RF Coaxial Cable COMMATE/PEWC | 8D | 966-4-1 | 2021/3/17 | 2022/3/16 |
| RF Coaxial Cable COMMATE/PEWC | 8D | 966-4-2 | 2021/3/17 | 2022/3/16 |
| RF Coaxial Cable COMMATE/PEWC | 8D | 966-4-3 | 2021/3/17 | 2022/3/16 |
| Fixed attenuator Mini-Circuits | UNAT-5+ | PAD-ATT5-03 | 2021/1/11 | 2022/1/10 |
| Horn Antenna SCHWARZBECK | BBHA 9120D | 9120D-783 | 2020/11/22 | 2021/11/21 |
| Pre_Amplifier EMCI | EMC 12630 SE | 980638 | 2021/4/7 | 2022/4/6 |
| RF Cable-Frequency Range : 1-26.5GHz EMCI | EMC104-SM-SM-1200 | 160922 | 2020/12/25 | 2021/12/24 |
| RF Coaxial Cable EMCI | EMC104-SM-SM-2000 | 180502 | 2021/4/26 | 2022/4/25 |
| RF Coaxial Cable EMCI | EMC104-SM-SM-6000 | 180418 | 2021/4/26 | 2022/4/25 |
| Pre_Amplifier EMCI | EMC184045SE | 980387 | 2021/1/11 | 2022/1/10 |
| Horn Antenna Schwarzbeck | BBHA 9170 | BBHA9170519 | 2020/11/22 | 2021/11/21 |
| RF Cable-Frequency range: 1-40GHz EMCI | EMC102-KM-KM-1200 | 160924 | 2021/1/11 | 2022/1/10 |
| RF cable (40GHz) EMCI | EMC-KM-KM-4000 | 200214 | 2021/3/10 | 2022/3/9 |

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 4.
3. Tested Date: 2021/10/9 ~ 2021/10/13

For other test items:

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|--|----------------------------------|---------------|-----------------|------------------|
| Spectrum Analyzer R&S | FSV40 | 101516 | 2021/3/8 | 2022/3/7 |
| Power Meter Anritsu | ML2495A | 1529002 | 2021/6/21 | 2022/6/20 |
| Pulse Power Sensor Anritsu | MA2411B | 1339443 | 2021/5/31 | 2022/5/30 |
| Attenuator WOKEN | MDCS18N-10 | MDCS18N-10-01 | 2021/4/13 | 2022/4/12 |
| Software | ADT_RF Test Software V6.6.5.4 | NA | NA | NA |
| AC Power Source GOOD WILL | 6905S | 1991551 | NA | NA |
| Temperature & Humidity Chamber Giant Force | GTH-150-40-SP-AR | MAA0812-008 | 2021/1/14 | 2022/1/13 |
| True RMS Clamp Meter Fluke | 325 | 31130711WS | 2021/6/2 | 2022/6/1 |

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: 2021/10/20

4.1.3 Test Procedure

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Condition

- Connected the EUT with the Laptop which is placed on the testing table.
- Controlling software (TOOL:Mtool 3.1.0.1) has been activated to set the EUT under transmission condition continuously.

4.1.7 Test Results

Above 1GHz Data:

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 36 : 5180 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5147.38 | 65.8 PK | 74.0 | -8.2 | 1.42 H | 167 | 64.3 | 1.5 |
| 2 | 5147.38 | 48.3 AV | 54.0 | -5.7 | 1.42 H | 167 | 46.8 | 1.5 |
| 3 | *5180.00 | 111.1 PK | | | 1.42 H | 167 | 109.7 | 1.4 |
| 4 | *5180.00 | 101.3 AV | | | 1.42 H | 167 | 99.9 | 1.4 |
| 5 | #10360.00 | 62.2 PK | 68.2 | -6.0 | 3.97 H | 354 | 51.5 | 10.7 |
| 6 | 15540.00 | 51.3 PK | 74.0 | -22.7 | 1.21 H | 228 | 39.3 | 12.0 |
| 7 | 15540.00 | 40.4 AV | 54.0 | -13.6 | 1.21 H | 228 | 28.4 | 12.0 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5147.00 | 67.6 PK | 74.0 | -6.4 | 2.46 V | 183 | 66.1 | 1.5 |
| 2 | 5147.00 | 53.4 AV | 54.0 | -0.6 | 2.46 V | 183 | 51.9 | 1.5 |
| 3 | *5180.00 | 116.5 PK | | | 2.46 V | 183 | 115.1 | 1.4 |
| 4 | *5180.00 | 108.4 AV | | | 2.46 V | 183 | 107.0 | 1.4 |
| 5 | #10360.00 | 61.9 PK | 68.2 | -6.3 | 1.99 V | 76 | 51.2 | 10.7 |
| 6 | 15540.00 | 57.2 PK | 74.0 | -16.8 | 1.21 V | 291 | 45.2 | 12.0 |
| 7 | 15540.00 | 48.2 AV | 54.0 | -5.8 | 1.21 V | 291 | 36.2 | 12.0 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 40 : 5200 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 65.3 PK | 74.0 | -8.7 | 1.37 H | 177 | 63.8 | 1.5 |
| 2 | 5150.00 | 48.2 AV | 54.0 | -5.8 | 1.37 H | 177 | 46.7 | 1.5 |
| 3 | *5200.00 | 114.3 PK | | | 1.37 H | 177 | 112.7 | 1.6 |
| 4 | *5200.00 | 104.5 AV | | | 1.37 H | 177 | 102.9 | 1.6 |
| 5 | #10400.00 | 61.7 PK | 68.2 | -6.5 | 3.91 H | 337 | 50.8 | 10.9 |
| 6 | 15600.00 | 52.0 PK | 74.0 | -22.0 | 1.32 H | 215 | 40.0 | 12.0 |
| 7 | 15600.00 | 40.8 AV | 54.0 | -13.2 | 1.32 H | 215 | 28.8 | 12.0 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 68.1 PK | 74.0 | -5.9 | 2.46 V | 183 | 66.6 | 1.5 |
| 2 | 5150.00 | 53.6 AV | 54.0 | -0.4 | 2.46 V | 183 | 52.1 | 1.5 |
| 3 | *5200.00 | 121.0 PK | | | 2.46 V | 183 | 119.4 | 1.6 |
| 4 | *5200.00 | 112.2 AV | | | 2.46 V | 183 | 110.6 | 1.6 |
| 5 | #10400.00 | 61.9 PK | 68.2 | -6.3 | 1.91 V | 88 | 51.0 | 10.9 |
| 6 | 15600.00 | 57.2 PK | 74.0 | -16.8 | 1.24 V | 307 | 45.2 | 12.0 |
| 7 | 15600.00 | 48.6 AV | 54.0 | -5.4 | 1.24 V | 307 | 36.6 | 12.0 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 48 : 5240 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5240.00 | 112.4 PK | | | 1.44 H | 161 | 111.2 | 1.2 |
| 2 | *5240.00 | 102.4 AV | | | 1.44 H | 161 | 101.2 | 1.2 |
| 3 | 5350.00 | 54.3 PK | 74.0 | -19.7 | 1.44 H | 161 | 53.0 | 1.3 |
| 4 | 5350.00 | 42.8 AV | 54.0 | -11.2 | 1.44 H | 161 | 41.5 | 1.3 |
| 5 | #10480.00 | 61.9 PK | 68.2 | -6.3 | 4.00 H | 348 | 51.0 | 10.9 |
| 6 | 15720.00 | 52.2 PK | 74.0 | -21.8 | 1.30 H | 226 | 40.3 | 11.9 |
| 7 | 15720.00 | 40.9 AV | 54.0 | -13.1 | 1.30 H | 226 | 29.0 | 11.9 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5240.00 | 118.8 PK | | | 2.46 V | 184 | 117.6 | 1.2 |
| 2 | *5240.00 | 110.4 AV | | | 2.46 V | 184 | 109.2 | 1.2 |
| 3 | 5350.00 | 55.0 PK | 74.0 | -19.0 | 2.46 V | 184 | 53.7 | 1.3 |
| 4 | 5350.00 | 43.6 AV | 54.0 | -10.4 | 2.46 V | 184 | 42.3 | 1.3 |
| 5 | #10480.00 | 61.2 PK | 68.2 | -7.0 | 1.97 V | 68 | 50.3 | 10.9 |
| 6 | 15720.00 | 57.4 PK | 74.0 | -16.6 | 1.26 V | 282 | 45.5 | 11.9 |
| 7 | 15720.00 | 48.5 AV | 54.0 | -5.5 | 1.26 V | 282 | 36.6 | 11.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 52 : 5260 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 55.4 PK | 74.0 | -18.6 | 1.41 H | 151 | 53.9 | 1.5 |
| 2 | 5150.00 | 44.0 AV | 54.0 | -10.0 | 1.41 H | 151 | 42.5 | 1.5 |
| 3 | *5260.00 | 111.0 PK | | | 1.41 H | 151 | 109.9 | 1.1 |
| 4 | *5260.00 | 100.9 AV | | | 1.41 H | 151 | 99.8 | 1.1 |
| 5 | #10520.00 | 61.7 PK | 68.2 | -6.5 | 4.00 H | 360 | 50.8 | 10.9 |
| 6 | 15780.00 | 51.2 PK | 74.0 | -22.8 | 1.29 H | 226 | 39.4 | 11.8 |
| 7 | 15780.00 | 40.3 AV | 54.0 | -13.7 | 1.29 H | 226 | 28.5 | 11.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 55.8 PK | 74.0 | -18.2 | 2.47 V | 184 | 54.3 | 1.5 |
| 2 | 5150.00 | 44.3 AV | 54.0 | -9.7 | 2.47 V | 184 | 42.8 | 1.5 |
| 3 | *5260.00 | 118.2 PK | | | 2.47 V | 184 | 117.1 | 1.1 |
| 4 | *5260.00 | 109.6 AV | | | 2.47 V | 184 | 108.5 | 1.1 |
| 5 | #10520.00 | 61.0 PK | 68.2 | -7.2 | 1.95 V | 96 | 50.1 | 10.9 |
| 6 | 15780.00 | 57.8 PK | 74.0 | -16.2 | 1.29 V | 302 | 46.0 | 11.8 |
| 7 | 15780.00 | 48.6 AV | 54.0 | -5.4 | 1.29 V | 302 | 36.8 | 11.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 60 : 5300 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5300.00 | 111.3 PK | | | 1.48 H | 157 | 110.1 | 1.2 |
| 2 | *5300.00 | 101.2 AV | | | 1.48 H | 157 | 100.0 | 1.2 |
| 3 | 10600.00 | 61.8 PK | 74.0 | -12.2 | 3.97 H | 345 | 50.8 | 11.0 |
| 4 | 10600.00 | 50.1 AV | 54.0 | -3.9 | 3.97 H | 345 | 39.1 | 11.0 |
| 5 | 15900.00 | 51.6 PK | 74.0 | -22.4 | 1.27 H | 221 | 39.4 | 12.2 |
| 6 | 15900.00 | 40.6 AV | 54.0 | -13.4 | 1.27 H | 221 | 28.4 | 12.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5300.00 | 118.1 PK | | | 2.50 V | 198 | 116.9 | 1.2 |
| 2 | *5300.00 | 109.5 AV | | | 2.50 V | 198 | 108.3 | 1.2 |
| 3 | 10600.00 | 61.4 PK | 74.0 | -12.6 | 1.94 V | 80 | 50.4 | 11.0 |
| 4 | 10600.00 | 49.5 AV | 54.0 | -4.5 | 1.94 V | 80 | 38.5 | 11.0 |
| 5 | 15900.00 | 57.5 PK | 74.0 | -16.5 | 1.25 V | 295 | 45.3 | 12.2 |
| 6 | 15900.00 | 48.6 AV | 54.0 | -5.4 | 1.25 V | 295 | 36.4 | 12.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 64 : 5320 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 67.5 PK | 74.0 | -6.5 | 1.08 H | 159 | 66.0 | 1.5 |
| 2 | 5150.00 | 49.4 AV | 54.0 | -4.6 | 1.08 H | 159 | 47.9 | 1.5 |
| 3 | *5320.00 | 111.7 PK | | | 1.08 H | 159 | 110.5 | 1.2 |
| 4 | *5320.00 | 101.7 AV | | | 1.08 H | 159 | 100.5 | 1.2 |
| 5 | 10640.00 | 61.8 PK | 74.0 | -12.2 | 4.00 H | 331 | 50.7 | 11.1 |
| 6 | 10640.00 | 50.3 AV | 54.0 | -3.7 | 4.00 H | 331 | 39.2 | 11.1 |
| 7 | 15960.00 | 51.2 PK | 74.0 | -22.8 | 1.27 H | 221 | 39.0 | 12.2 |
| 8 | 15960.00 | 40.1 AV | 54.0 | -13.9 | 1.27 H | 221 | 27.9 | 12.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5320.00 | 117.0 PK | | | 2.49 V | 183 | 115.8 | 1.2 |
| 2 | *5320.00 | 108.1 AV | | | 2.49 V | 183 | 106.9 | 1.2 |
| 3 | 5351.83 | 71.3 PK | 74.0 | -2.7 | 2.49 V | 183 | 70.0 | 1.3 |
| 4 | 5351.83 | 53.5 AV | 54.0 | -0.5 | 2.49 V | 183 | 52.2 | 1.3 |
| 5 | 10640.00 | 61.1 PK | 74.0 | -12.9 | 1.92 V | 66 | 50.0 | 11.1 |
| 6 | 10640.00 | 49.4 AV | 54.0 | -4.6 | 1.92 V | 66 | 38.3 | 11.1 |
| 7 | 15960.00 | 57.0 PK | 74.0 | -17.0 | 1.30 V | 303 | 44.8 | 12.2 |
| 8 | 15960.00 | 48.2 AV | 54.0 | -5.8 | 1.30 V | 303 | 36.0 | 12.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 100 : 5500 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 51.5 PK | 74.0 | -22.5 | 1.01 H | 155 | 50.0 | 1.5 |
| 2 | 5460.00 | 39.4 AV | 54.0 | -14.6 | 1.01 H | 155 | 37.9 | 1.5 |
| 3 | #5470.00 | 55.4 PK | 68.2 | -12.8 | 1.01 H | 155 | 53.9 | 1.5 |
| 4 | *5500.00 | 105.2 PK | | | 1.01 H | 155 | 103.7 | 1.5 |
| 5 | *5500.00 | 95.5 AV | | | 1.01 H | 155 | 94.0 | 1.5 |
| 6 | 11000.00 | 62.5 PK | 74.0 | -11.5 | 3.92 H | 340 | 50.7 | 11.8 |
| 7 | 11000.00 | 50.6 AV | 54.0 | -3.4 | 3.92 H | 340 | 38.8 | 11.8 |
| 8 | #16500.00 | 51.4 PK | 68.2 | -16.8 | 1.21 H | 223 | 37.3 | 14.1 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5457.00 | 61.4 PK | 74.0 | -12.6 | 1.08 V | 291 | 59.9 | 1.5 |
| 2 | 5457.00 | 45.7 AV | 54.0 | -8.3 | 1.08 V | 291 | 44.2 | 1.5 |
| 3 | 5460.00 | 58.9 PK | 74.0 | -15.1 | 1.08 V | 291 | 57.4 | 1.5 |
| 4 | 5460.00 | 47.2 AV | 54.0 | -6.8 | 1.08 V | 291 | 45.7 | 1.5 |
| 5 | #5470.00 | 68.0 PK | 68.2 | -0.2 | 1.08 V | 291 | 66.5 | 1.5 |
| 6 | *5500.00 | 115.1 PK | | | 1.08 V | 291 | 113.6 | 1.5 |
| 7 | *5500.00 | 104.6 AV | | | 1.08 V | 291 | 103.1 | 1.5 |
| 8 | 11000.00 | 61.7 PK | 74.0 | -12.3 | 1.94 V | 81 | 49.9 | 11.8 |
| 9 | 11000.00 | 49.8 AV | 54.0 | -4.2 | 1.94 V | 81 | 38.0 | 11.8 |
| 10 | #16500.00 | 56.9 PK | 68.2 | -11.3 | 1.30 V | 295 | 42.8 | 14.1 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 116 : 5580 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5580.00 | 111.5 PK | | | 1.40 H | 158 | 109.8 | 1.7 |
| 2 | *5580.00 | 101.3 AV | | | 1.40 H | 158 | 99.6 | 1.7 |
| 3 | 11160.00 | 60.0 PK | 74.0 | -14.0 | 3.60 H | 0 | 48.1 | 11.9 |
| 4 | 11160.00 | 49.6 AV | 54.0 | -4.4 | 3.60 H | 0 | 37.7 | 11.9 |
| 5 | #16740.00 | 58.6 PK | 68.2 | -9.6 | 1.38 H | 139 | 42.8 | 15.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5580.00 | 117.6 PK | | | 1.21 V | 278 | 115.9 | 1.7 |
| 2 | *5580.00 | 109.2 AV | | | 1.21 V | 278 | 107.5 | 1.7 |
| 3 | 11160.00 | 61.6 PK | 74.0 | -12.4 | 1.88 V | 66 | 49.7 | 11.9 |
| 4 | 11160.00 | 49.6 AV | 54.0 | -4.4 | 1.88 V | 66 | 37.7 | 11.9 |
| 5 | #16740.00 | 56.8 PK | 68.2 | -11.4 | 1.30 V | 301 | 41.0 | 15.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 140 : 5700 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5700.00 | 110.8 PK | | | 1.45 H | 172 | 108.9 | 1.9 |
| 2 | *5700.00 | 100.1 AV | | | 1.45 H | 172 | 98.2 | 1.9 |
| 3 | #5725.00 | 55.9 PK | 68.2 | -12.3 | 1.45 H | 172 | 53.9 | 2.0 |
| 4 | 11400.00 | 59.5 PK | 74.0 | -14.5 | 3.65 H | 14 | 46.9 | 12.6 |
| 5 | 11400.00 | 49.0 AV | 54.0 | -5.0 | 3.65 H | 14 | 36.4 | 12.6 |
| 6 | #17100.00 | 59.1 PK | 68.2 | -9.1 | 1.41 H | 141 | 42.7 | 16.4 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5700.00 | 117.0 PK | | | 1.07 V | 310 | 115.1 | 1.9 |
| 2 | *5700.00 | 108.5 AV | | | 1.07 V | 310 | 106.6 | 1.9 |
| 3 | #5725.00 | 67.8 PK | 68.2 | -0.4 | 1.07 V | 310 | 65.8 | 2.0 |
| 4 | 11400.00 | 61.7 PK | 74.0 | -12.3 | 2.00 V | 81 | 49.1 | 12.6 |
| 5 | 11400.00 | 49.8 AV | 54.0 | -4.2 | 2.00 V | 81 | 37.2 | 12.6 |
| 6 | #17100.00 | 56.8 PK | 68.2 | -11.4 | 1.28 V | 307 | 40.4 | 16.4 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 144 : 5720 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 55.0 PK | 74.0 | -19.0 | 1.38 H | 166 | 53.5 | 1.5 |
| 2 | 5460.00 | 43.0 AV | 54.0 | -11.0 | 1.38 H | 166 | 41.5 | 1.5 |
| 3 | #5470.00 | 55.8 PK | 68.2 | -12.4 | 1.38 H | 166 | 54.3 | 1.5 |
| 4 | *5720.00 | 111.2 PK | | | 1.38 H | 166 | 109.2 | 2.0 |
| 5 | *5720.00 | 101.1 AV | | | 1.38 H | 166 | 99.1 | 2.0 |
| 6 | #5850.00 | 53.6 PK | 68.2 | -14.6 | 1.38 H | 166 | 51.3 | 2.3 |
| 7 | 11440.00 | 59.7 PK | 74.0 | -14.3 | 3.68 H | 2 | 47.1 | 12.6 |
| 8 | 11440.00 | 48.9 AV | 54.0 | -5.1 | 3.68 H | 2 | 36.3 | 12.6 |
| 9 | #17160.00 | 58.8 PK | 68.2 | -9.4 | 1.39 H | 148 | 42.2 | 16.6 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 55.2 PK | 74.0 | -18.8 | 1.11 V | 311 | 53.7 | 1.5 |
| 2 | 5460.00 | 43.2 AV | 54.0 | -10.8 | 1.11 V | 311 | 41.7 | 1.5 |
| 3 | #5470.00 | 56.2 PK | 68.2 | -12.0 | 1.11 V | 311 | 54.7 | 1.5 |
| 4 | *5720.00 | 118.8 PK | | | 1.11 V | 311 | 116.8 | 2.0 |
| 5 | *5720.00 | 110.0 AV | | | 1.11 V | 311 | 108.0 | 2.0 |
| 6 | #5850.00 | 53.8 PK | 68.2 | -14.4 | 1.11 V | 311 | 51.5 | 2.3 |
| 7 | 11440.00 | 61.3 PK | 74.0 | -12.7 | 1.90 V | 79 | 48.7 | 12.6 |
| 8 | 11440.00 | 49.6 AV | 54.0 | -4.4 | 1.90 V | 79 | 37.0 | 12.6 |
| 9 | #17160.00 | 57.2 PK | 68.2 | -11.0 | 1.26 V | 295 | 40.6 | 16.6 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 149 : 5745 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5648.56 | 59.1 PK | 68.2 | -9.1 | 3.97 H | 286 | 57.3 | 1.8 |
| 2 | *5745.00 | 117.7 PK | | | 3.97 H | 286 | 115.6 | 2.1 |
| 3 | *5745.00 | 106.8 AV | | | 3.97 H | 286 | 104.7 | 2.1 |
| 4 | #5943.10 | 52.1 PK | 68.2 | -16.1 | 3.97 H | 286 | 49.8 | 2.3 |
| 5 | 11490.00 | 60.1 PK | 74.0 | -13.9 | 3.63 H | 10 | 47.5 | 12.6 |
| 6 | 11490.00 | 49.6 AV | 54.0 | -4.4 | 3.63 H | 10 | 37.0 | 12.6 |
| 7 | #17235.00 | 58.7 PK | 68.2 | -9.5 | 1.43 H | 149 | 41.9 | 16.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5643.34 | 66.6 PK | 68.2 | -1.6 | 1.04 V | 293 | 64.8 | 1.8 |
| 2 | *5745.00 | 123.7 PK | | | 1.04 V | 293 | 121.6 | 2.1 |
| 3 | *5745.00 | 113.4 AV | | | 1.04 V | 293 | 111.3 | 2.1 |
| 4 | #5940.55 | 54.9 PK | 68.2 | -13.3 | 1.04 V | 293 | 52.6 | 2.3 |
| 5 | 11490.00 | 61.2 PK | 74.0 | -12.8 | 1.96 V | 67 | 48.6 | 12.6 |
| 6 | 11490.00 | 49.3 AV | 54.0 | -4.7 | 1.96 V | 67 | 36.7 | 12.6 |
| 7 | #17235.00 | 57.1 PK | 68.2 | -11.1 | 1.30 V | 299 | 40.3 | 16.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 157 : 5785 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5642.70 | 52.6 PK | 68.2 | -15.6 | 3.81 H | 297 | 50.8 | 1.8 |
| 2 | *5785.00 | 117.0 PK | | | 3.81 H | 297 | 114.8 | 2.2 |
| 3 | *5785.00 | 105.9 AV | | | 3.81 H | 297 | 103.7 | 2.2 |
| 4 | #5938.23 | 52.3 PK | 68.2 | -15.9 | 3.81 H | 297 | 50.0 | 2.3 |
| 5 | 11570.00 | 59.8 PK | 74.0 | -14.2 | 3.66 H | 6 | 47.4 | 12.4 |
| 6 | 11570.00 | 49.3 AV | 54.0 | -4.7 | 3.66 H | 6 | 36.9 | 12.4 |
| 7 | #17355.00 | 58.8 PK | 68.2 | -9.4 | 1.40 H | 137 | 41.3 | 17.5 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5644.42 | 61.6 PK | 68.2 | -6.6 | 1.05 V | 292 | 59.8 | 1.8 |
| 2 | *5785.00 | 123.6 PK | | | 1.05 V | 292 | 121.4 | 2.2 |
| 3 | *5785.00 | 113.2 AV | | | 1.05 V | 292 | 111.0 | 2.2 |
| 4 | #5928.53 | 58.0 PK | 68.2 | -10.2 | 1.05 V | 292 | 55.8 | 2.2 |
| 5 | 11570.00 | 62.3 PK | 74.0 | -11.7 | 2.02 V | 253 | 49.9 | 12.4 |
| 6 | 11570.00 | 48.9 AV | 54.0 | -5.1 | 2.02 V | 253 | 36.5 | 12.4 |
| 7 | #17355.00 | 65.7 PK | 68.2 | -2.5 | 1.09 V | 206 | 48.2 | 17.5 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11a | Channel | CH 165 : 5825 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5573.16 | 52.2 PK | 68.2 | -16.0 | 3.88 H | 301 | 50.5 | 1.7 |
| 2 | *5825.00 | 117.7 PK | | | 3.88 H | 301 | 115.5 | 2.2 |
| 3 | *5825.00 | 107.1 AV | | | 3.88 H | 301 | 104.9 | 2.2 |
| 4 | #5925.12 | 58.2 PK | 68.2 | -10.0 | 3.88 H | 301 | 56.0 | 2.2 |
| 5 | 11650.00 | 59.4 PK | 74.0 | -14.6 | 3.61 H | 6 | 47.1 | 12.3 |
| 6 | 11650.00 | 49.0 AV | 54.0 | -5.0 | 3.61 H | 6 | 36.7 | 12.3 |
| 7 | #17475.00 | 59.2 PK | 68.2 | -9.0 | 1.42 H | 144 | 40.8 | 18.4 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5638.75 | 56.6 PK | 68.2 | -11.6 | 1.01 V | 291 | 54.8 | 1.8 |
| 2 | *5825.00 | 122.9 PK | | | 1.01 V | 291 | 120.7 | 2.2 |
| 3 | *5825.00 | 113.0 AV | | | 1.01 V | 291 | 110.8 | 2.2 |
| 4 | #5927.19 | 66.3 PK | 68.2 | -1.9 | 1.01 V | 291 | 64.1 | 2.2 |
| 5 | 11650.00 | 62.1 PK | 74.0 | -11.9 | 2.07 V | 262 | 49.8 | 12.3 |
| 6 | 11650.00 | 48.5 AV | 54.0 | -5.5 | 2.07 V | 262 | 36.2 | 12.3 |
| 7 | #17475.00 | 65.8 PK | 68.2 | -2.4 | 1.13 V | 212 | 47.4 | 18.4 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 36 : 5180 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 60.0 PK | 74.0 | -14.0 | 1.16 H | 173 | 58.5 | 1.5 |
| 2 | 5150.00 | 49.0 AV | 54.0 | -5.0 | 1.16 H | 173 | 47.5 | 1.5 |
| 3 | *5180.00 | 111.7 PK | | | 1.16 H | 173 | 110.3 | 1.4 |
| 4 | *5180.00 | 101.3 AV | | | 1.16 H | 173 | 99.9 | 1.4 |
| 5 | #10360.00 | 57.8 PK | 68.2 | -10.4 | 3.75 H | 359 | 47.1 | 10.7 |
| 6 | 15540.00 | 51.8 PK | 74.0 | -22.2 | 1.25 H | 230 | 39.8 | 12.0 |
| 7 | 15540.00 | 40.9 AV | 54.0 | -13.1 | 1.25 H | 230 | 28.9 | 12.0 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 66.8 PK | 74.0 | -7.2 | 1.11 V | 304 | 65.3 | 1.5 |
| 2 | 5150.00 | 53.6 AV | 54.0 | -0.4 | 1.11 V | 304 | 52.1 | 1.5 |
| 3 | *5180.00 | 118.9 PK | | | 1.11 V | 304 | 117.5 | 1.4 |
| 4 | *5180.00 | 107.0 AV | | | 1.11 V | 304 | 105.6 | 1.4 |
| 5 | #10360.00 | 57.5 PK | 68.2 | -10.7 | 1.94 V | 80 | 46.8 | 10.7 |
| 6 | 15540.00 | 53.5 PK | 74.0 | -20.5 | 1.25 V | 297 | 41.5 | 12.0 |
| 7 | 15540.00 | 45.2 AV | 54.0 | -8.8 | 1.25 V | 297 | 33.2 | 12.0 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 40 : 5200 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 64.8 PK | 74.0 | -9.2 | 1.36 H | 159 | 63.3 | 1.5 |
| 2 | 5150.00 | 48.5 AV | 54.0 | -5.5 | 1.36 H | 159 | 47.0 | 1.5 |
| 3 | *5200.00 | 113.8 PK | | | 1.36 H | 159 | 112.2 | 1.6 |
| 4 | *5200.00 | 101.7 AV | | | 1.36 H | 159 | 100.1 | 1.6 |
| 5 | #10400.00 | 57.6 PK | 68.2 | -10.6 | 3.70 H | 360 | 46.7 | 10.9 |
| 6 | 15600.00 | 52.4 PK | 74.0 | -21.6 | 1.22 H | 241 | 40.4 | 12.0 |
| 7 | 15600.00 | 41.4 AV | 54.0 | -12.6 | 1.22 H | 241 | 29.4 | 12.0 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 67.3 PK | 74.0 | -6.7 | 1.11 V | 304 | 65.8 | 1.5 |
| 2 | 5150.00 | 53.5 AV | 54.0 | -0.5 | 1.11 V | 304 | 52.0 | 1.5 |
| 3 | *5200.00 | 121.5 PK | | | 1.11 V | 304 | 119.9 | 1.6 |
| 4 | *5200.00 | 109.8 AV | | | 1.11 V | 304 | 108.2 | 1.6 |
| 5 | #10400.00 | 57.6 PK | 68.2 | -10.6 | 1.99 V | 73 | 46.7 | 10.9 |
| 6 | 15600.00 | 53.6 PK | 74.0 | -20.4 | 1.26 V | 308 | 41.6 | 12.0 |
| 7 | 15600.00 | 45.1 AV | 54.0 | -8.9 | 1.26 V | 308 | 33.1 | 12.0 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 48 : 5240 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5240.00 | 113.7 PK | | | 1.40 H | 151 | 112.5 | 1.2 |
| 2 | *5240.00 | 101.5 AV | | | 1.40 H | 151 | 100.3 | 1.2 |
| 3 | 5350.00 | 54.1 PK | 74.0 | -19.9 | 1.40 H | 151 | 52.8 | 1.3 |
| 4 | 5350.00 | 42.7 AV | 54.0 | -11.3 | 1.40 H | 151 | 41.4 | 1.3 |
| 5 | #10480.00 | 58.3 PK | 68.2 | -9.9 | 3.72 H | 360 | 47.4 | 10.9 |
| 6 | 15720.00 | 51.9 PK | 74.0 | -22.1 | 1.28 H | 234 | 40.0 | 11.9 |
| 7 | 15720.00 | 41.2 AV | 54.0 | -12.8 | 1.28 H | 234 | 29.3 | 11.9 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5240.00 | 121.2 PK | | | 1.05 V | 310 | 120.0 | 1.2 |
| 2 | *5240.00 | 109.4 AV | | | 1.05 V | 310 | 108.2 | 1.2 |
| 3 | 5350.00 | 54.4 PK | 74.0 | -19.6 | 1.05 V | 310 | 53.1 | 1.3 |
| 4 | 5350.00 | 43.1 AV | 54.0 | -10.9 | 1.05 V | 310 | 41.8 | 1.3 |
| 5 | #10480.00 | 57.0 PK | 68.2 | -11.2 | 1.97 V | 92 | 46.1 | 10.9 |
| 6 | 15720.00 | 53.6 PK | 74.0 | -20.4 | 1.25 V | 305 | 41.7 | 11.9 |
| 7 | 15720.00 | 45.1 AV | 54.0 | -8.9 | 1.25 V | 305 | 33.2 | 11.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 52 : 5260 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 54.8 PK | 74.0 | -19.2 | 1.42 H | 182 | 53.3 | 1.5 |
| 2 | 5150.00 | 44.7 AV | 54.0 | -9.3 | 1.42 H | 182 | 43.2 | 1.5 |
| 3 | *5260.00 | 114.0 PK | | | 1.42 H | 182 | 112.9 | 1.1 |
| 4 | *5260.00 | 101.8 AV | | | 1.42 H | 182 | 100.7 | 1.1 |
| 5 | #10520.00 | 58.1 PK | 68.2 | -10.1 | 3.75 H | 354 | 47.2 | 10.9 |
| 6 | 15780.00 | 52.1 PK | 74.0 | -21.9 | 1.27 H | 234 | 40.3 | 11.8 |
| 7 | 15780.00 | 41.2 AV | 54.0 | -12.8 | 1.27 H | 234 | 29.4 | 11.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 55.3 PK | 74.0 | -18.7 | 1.13 V | 294 | 53.8 | 1.5 |
| 2 | 5150.00 | 45.5 AV | 54.0 | -8.5 | 1.13 V | 294 | 44.0 | 1.5 |
| 3 | *5260.00 | 120.8 PK | | | 1.13 V | 294 | 119.7 | 1.1 |
| 4 | *5260.00 | 109.2 AV | | | 1.13 V | 294 | 108.1 | 1.1 |
| 5 | #10520.00 | 57.1 PK | 68.2 | -11.1 | 1.91 V | 74 | 46.2 | 10.9 |
| 6 | 15780.00 | 53.2 PK | 74.0 | -20.8 | 1.30 V | 296 | 41.4 | 11.8 |
| 7 | 15780.00 | 45.1 AV | 54.0 | -8.9 | 1.30 V | 296 | 33.3 | 11.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 60 : 5300 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5300.00 | 113.5 PK | | | 1.36 H | 182 | 112.3 | 1.2 |
| 2 | *5300.00 | 101.4 AV | | | 1.36 H | 182 | 100.2 | 1.2 |
| 3 | 10600.00 | 58.4 PK | 74.0 | -15.6 | 3.78 H | 345 | 47.4 | 11.0 |
| 4 | 10600.00 | 47.2 AV | 54.0 | -6.8 | 3.78 H | 345 | 36.2 | 11.0 |
| 5 | 15900.00 | 51.9 PK | 74.0 | -22.1 | 1.25 H | 241 | 39.7 | 12.2 |
| 6 | 15900.00 | 41.3 AV | 54.0 | -12.7 | 1.25 H | 241 | 29.1 | 12.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5300.00 | 120.8 PK | | | 1.18 V | 308 | 119.6 | 1.2 |
| 2 | *5300.00 | 109.2 AV | | | 1.18 V | 308 | 108.0 | 1.2 |
| 3 | 10600.00 | 57.3 PK | 74.0 | -16.7 | 1.96 V | 80 | 46.3 | 11.0 |
| 4 | 10600.00 | 46.2 AV | 54.0 | -7.8 | 1.96 V | 80 | 35.2 | 11.0 |
| 5 | 15900.00 | 53.5 PK | 74.0 | -20.5 | 1.30 V | 283 | 41.3 | 12.2 |
| 6 | 15900.00 | 45.2 AV | 54.0 | -8.8 | 1.30 V | 283 | 33.0 | 12.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 64 : 5320 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5320.00 | 112.4 PK | | | 1.16 H | 163 | 111.2 | 1.2 |
| 2 | *5320.00 | 102.5 AV | | | 1.16 H | 163 | 101.3 | 1.2 |
| 3 | 5350.00 | 63.8 PK | 74.0 | -10.2 | 1.16 H | 163 | 62.5 | 1.3 |
| 4 | 5350.00 | 50.7 AV | 54.0 | -3.3 | 1.16 H | 163 | 49.4 | 1.3 |
| 5 | 10640.00 | 58.4 PK | 74.0 | -15.6 | 3.81 H | 360 | 47.3 | 11.1 |
| 6 | 10640.00 | 47.2 AV | 54.0 | -6.8 | 3.81 H | 360 | 36.1 | 11.1 |
| 7 | 15960.00 | 52.4 PK | 74.0 | -21.6 | 1.27 H | 241 | 40.2 | 12.2 |
| 8 | 15960.00 | 41.3 AV | 54.0 | -12.7 | 1.27 H | 241 | 29.1 | 12.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5320.00 | 119.3 PK | | | 1.11 V | 304 | 118.1 | 1.2 |
| 2 | *5320.00 | 108.2 AV | | | 1.11 V | 304 | 107.0 | 1.2 |
| 3 | 5351.27 | 67.6 PK | 74.0 | -6.4 | 1.11 V | 304 | 66.3 | 1.3 |
| 4 | 5351.27 | 53.7 AV | 54.0 | -0.3 | 1.11 V | 304 | 52.4 | 1.3 |
| 5 | 10640.00 | 57.1 PK | 74.0 | -16.9 | 1.94 V | 68 | 46.0 | 11.1 |
| 6 | 10640.00 | 45.8 AV | 54.0 | -8.2 | 1.94 V | 68 | 34.7 | 11.1 |
| 7 | 15960.00 | 53.6 PK | 74.0 | -20.4 | 1.21 V | 313 | 41.4 | 12.2 |
| 8 | 15960.00 | 45.5 AV | 54.0 | -8.5 | 1.21 V | 313 | 33.3 | 12.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 100 : 5500 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 53.0 PK | 74.0 | -21.0 | 1.17 H | 162 | 51.5 | 1.5 |
| 2 | 5460.00 | 42.3 AV | 54.0 | -11.7 | 1.17 H | 162 | 40.8 | 1.5 |
| 3 | #5467.90 | 56.7 PK | 68.2 | -11.5 | 1.17 H | 162 | 55.2 | 1.5 |
| 4 | *5500.00 | 109.6 PK | | | 1.17 H | 162 | 108.1 | 1.5 |
| 5 | *5500.00 | 99.0 AV | | | 1.17 H | 162 | 97.5 | 1.5 |
| 6 | 11000.00 | 57.3 PK | 74.0 | -16.7 | 3.81 H | 360 | 45.5 | 11.8 |
| 7 | 11000.00 | 46.5 AV | 54.0 | -7.5 | 3.81 H | 360 | 34.7 | 11.8 |
| 8 | #16500.00 | 51.4 PK | 68.2 | -16.8 | 1.27 H | 224 | 37.3 | 14.1 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5459.20 | 62.1 PK | 74.0 | -11.9 | 1.01 V | 290 | 60.6 | 1.5 |
| 2 | 5459.20 | 47.0 AV | 54.0 | -7.0 | 1.01 V | 290 | 45.5 | 1.5 |
| 3 | #5470.00 | 68.1 PK | 68.2 | -0.1 | 1.01 V | 290 | 66.6 | 1.5 |
| 4 | *5500.00 | 117.9 PK | | | 1.01 V | 290 | 116.4 | 1.5 |
| 5 | *5500.00 | 105.5 AV | | | 1.01 V | 290 | 104.0 | 1.5 |
| 6 | 11000.00 | 58.1 PK | 74.0 | -15.9 | 1.94 V | 84 | 46.3 | 11.8 |
| 7 | 11000.00 | 46.5 AV | 54.0 | -7.5 | 1.94 V | 84 | 34.7 | 11.8 |
| 8 | #16500.00 | 53.3 PK | 68.2 | -14.9 | 1.20 V | 281 | 39.2 | 14.1 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 116 : 5580 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5580.00 | 113.6 PK | | | 1.41 H | 175 | 111.9 | 1.7 |
| 2 | *5580.00 | 101.2 AV | | | 1.41 H | 175 | 99.5 | 1.7 |
| 3 | 11160.00 | 58.1 PK | 74.0 | -15.9 | 3.81 H | 360 | 46.2 | 11.9 |
| 4 | 11160.00 | 47.0 AV | 54.0 | -7.0 | 3.81 H | 360 | 35.1 | 11.9 |
| 5 | #16740.00 | 51.4 PK | 68.2 | -16.8 | 1.28 H | 216 | 35.6 | 15.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5580.00 | 120.7 PK | | | 1.08 V | 279 | 119.0 | 1.7 |
| 2 | *5580.00 | 109.0 AV | | | 1.08 V | 279 | 107.3 | 1.7 |
| 3 | 11160.00 | 57.5 PK | 74.0 | -16.5 | 1.94 V | 83 | 45.6 | 11.9 |
| 4 | 11160.00 | 46.0 AV | 54.0 | -8.0 | 1.94 V | 83 | 34.1 | 11.9 |
| 5 | #16740.00 | 53.5 PK | 68.2 | -14.7 | 1.21 V | 293 | 37.7 | 15.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 140 : 5700 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5700.00 | 108.4 PK | | | 1.37 H | 155 | 106.5 | 1.9 |
| 2 | *5700.00 | 97.3 AV | | | 1.37 H | 155 | 95.4 | 1.9 |
| 3 | #5725.00 | 63.3 PK | 68.2 | -4.9 | 1.37 H | 155 | 61.3 | 2.0 |
| 4 | 11400.00 | 57.4 PK | 74.0 | -16.6 | 3.70 H | 345 | 44.8 | 12.6 |
| 5 | 11400.00 | 46.4 AV | 54.0 | -7.6 | 3.70 H | 345 | 33.8 | 12.6 |
| 6 | #17100.00 | 51.9 PK | 68.2 | -16.3 | 1.21 H | 216 | 35.5 | 16.4 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5700.00 | 116.3 PK | | | 1.04 V | 292 | 114.4 | 1.9 |
| 2 | *5700.00 | 105.1 AV | | | 1.04 V | 292 | 103.2 | 1.9 |
| 3 | #5725.00 | 67.9 PK | 68.2 | -0.3 | 1.04 V | 292 | 65.9 | 2.0 |
| 4 | 11400.00 | 57.3 PK | 74.0 | -16.7 | 1.95 V | 90 | 44.7 | 12.6 |
| 5 | 11400.00 | 45.9 AV | 54.0 | -8.1 | 1.95 V | 90 | 33.3 | 12.6 |
| 6 | #17100.00 | 52.8 PK | 68.2 | -15.4 | 1.29 V | 289 | 36.4 | 16.4 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 144 : 5720 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 56.5 PK | 74.0 | -17.5 | 1.46 H | 152 | 55.0 | 1.5 |
| 2 | 5460.00 | 44.2 AV | 54.0 | -9.8 | 1.46 H | 152 | 42.7 | 1.5 |
| 3 | #5470.00 | 56.7 PK | 68.2 | -11.5 | 1.46 H | 152 | 55.2 | 1.5 |
| 4 | *5720.00 | 113.6 PK | | | 1.46 H | 152 | 111.6 | 2.0 |
| 5 | *5720.00 | 101.4 AV | | | 1.46 H | 152 | 99.4 | 2.0 |
| 6 | #5850.00 | 55.2 PK | 68.2 | -13.0 | 1.46 H | 152 | 52.9 | 2.3 |
| 7 | 11440.00 | 57.7 PK | 74.0 | -16.3 | 3.75 H | 360 | 45.1 | 12.6 |
| 8 | 11440.00 | 47.0 AV | 54.0 | -7.0 | 3.75 H | 360 | 34.4 | 12.6 |
| 9 | #17160.00 | 52.1 PK | 68.2 | -16.1 | 1.26 H | 222 | 35.5 | 16.6 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 57.2 PK | 74.0 | -16.8 | 1.06 V | 292 | 55.7 | 1.5 |
| 2 | 5460.00 | 44.6 AV | 54.0 | -9.4 | 1.06 V | 292 | 43.1 | 1.5 |
| 3 | #5470.00 | 57.5 PK | 68.2 | -10.7 | 1.06 V | 292 | 56.0 | 1.5 |
| 4 | *5720.00 | 121.7 PK | | | 1.06 V | 292 | 119.7 | 2.0 |
| 5 | *5720.00 | 109.7 AV | | | 1.06 V | 292 | 107.7 | 2.0 |
| 6 | #5850.00 | 55.8 PK | 68.2 | -12.4 | 1.06 V | 292 | 53.5 | 2.3 |
| 7 | 11440.00 | 57.4 PK | 74.0 | -16.6 | 1.96 V | 73 | 44.8 | 12.6 |
| 8 | 11440.00 | 46.1 AV | 54.0 | -7.9 | 1.96 V | 73 | 33.5 | 12.6 |
| 9 | #17160.00 | 53.5 PK | 68.2 | -14.7 | 1.19 V | 283 | 36.9 | 16.6 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 149 : 5745 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5649.37 | 62.1 PK | 68.2 | -6.1 | 3.93 H | 311 | 60.3 | 1.8 |
| 2 | *5745.00 | 118.6 PK | | | 3.93 H | 311 | 116.5 | 2.1 |
| 3 | *5745.00 | 105.6 AV | | | 3.93 H | 311 | 103.5 | 2.1 |
| 4 | #5949.56 | 52.8 PK | 68.2 | -15.4 | 3.93 H | 311 | 50.5 | 2.3 |
| 5 | 11490.00 | 57.7 PK | 74.0 | -16.3 | 3.72 H | 358 | 45.1 | 12.6 |
| 6 | 11490.00 | 46.9 AV | 54.0 | -7.1 | 3.72 H | 358 | 34.3 | 12.6 |
| 7 | #17235.00 | 51.9 PK | 68.2 | -16.3 | 1.19 H | 238 | 35.1 | 16.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5646.48 | 64.2 PK | 68.2 | -4.0 | 1.00 V | 291 | 62.4 | 1.8 |
| 2 | *5745.00 | 123.3 PK | | | 1.00 V | 291 | 121.2 | 2.1 |
| 3 | *5745.00 | 111.6 AV | | | 1.00 V | 291 | 109.5 | 2.1 |
| 4 | #5993.57 | 55.9 PK | 68.2 | -12.3 | 1.00 V | 291 | 53.6 | 2.3 |
| 5 | 11490.00 | 56.8 PK | 74.0 | -17.2 | 1.93 V | 70 | 44.2 | 12.6 |
| 6 | 11490.00 | 45.7 AV | 54.0 | -8.3 | 1.93 V | 70 | 33.1 | 12.6 |
| 7 | #17235.00 | 53.0 PK | 68.2 | -15.2 | 1.30 V | 297 | 36.2 | 16.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 157 : 5785 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5649.43 | 52.6 PK | 68.2 | -15.6 | 3.98 H | 299 | 50.8 | 1.8 |
| 2 | *5785.00 | 119.0 PK | | | 3.98 H | 299 | 116.8 | 2.2 |
| 3 | *5785.00 | 105.8 AV | | | 3.98 H | 299 | 103.6 | 2.2 |
| 4 | #5926.82 | 53.6 PK | 68.2 | -14.6 | 3.98 H | 299 | 51.4 | 2.2 |
| 5 | 11570.00 | 57.4 PK | 74.0 | -16.6 | 3.75 H | 350 | 45.0 | 12.4 |
| 6 | 11570.00 | 46.4 AV | 54.0 | -7.6 | 3.75 H | 350 | 34.0 | 12.4 |
| 7 | #17355.00 | 52.2 PK | 68.2 | -16.0 | 1.31 H | 224 | 34.7 | 17.5 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5649.24 | 64.2 PK | 68.2 | -4.0 | 1.02 V | 295 | 62.4 | 1.8 |
| 2 | *5785.00 | 124.3 PK | | | 1.02 V | 295 | 122.1 | 2.2 |
| 3 | *5785.00 | 112.2 AV | | | 1.02 V | 295 | 110.0 | 2.2 |
| 4 | #5925.32 | 65.1 PK | 68.2 | -3.1 | 1.02 V | 295 | 62.9 | 2.2 |
| 5 | 11570.00 | 57.8 PK | 74.0 | -16.2 | 1.94 V | 95 | 45.4 | 12.4 |
| 6 | 11570.00 | 46.2 AV | 54.0 | -7.8 | 1.94 V | 95 | 33.8 | 12.4 |
| 7 | #17355.00 | 53.6 PK | 68.2 | -14.6 | 1.28 V | 291 | 36.1 | 17.5 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 165 : 5825 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5598.75 | 52.9 PK | 68.2 | -15.3 | 3.94 H | 296 | 51.2 | 1.7 |
| 2 | *5825.00 | 118.3 PK | | | 3.94 H | 296 | 116.1 | 2.2 |
| 3 | *5825.00 | 105.0 AV | | | 3.94 H | 296 | 102.8 | 2.2 |
| 4 | #5926.54 | 59.7 PK | 68.2 | -8.5 | 3.94 H | 296 | 57.5 | 2.2 |
| 5 | 11650.00 | 58.3 PK | 74.0 | -15.7 | 3.71 H | 360 | 46.0 | 12.3 |
| 6 | 11650.00 | 47.2 AV | 54.0 | -6.8 | 3.71 H | 360 | 34.9 | 12.3 |
| 7 | #17475.00 | 52.0 PK | 68.2 | -16.2 | 1.29 H | 219 | 33.6 | 18.4 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5580.92 | 58.0 PK | 68.2 | -10.2 | 1.04 V | 292 | 56.3 | 1.7 |
| 2 | *5825.00 | 124.4 PK | | | 1.04 V | 292 | 122.2 | 2.2 |
| 3 | *5825.00 | 111.7 AV | | | 1.04 V | 292 | 109.5 | 2.2 |
| 4 | #5919.07 | 72.5 PK | 72.6 | -0.1 | 1.04 V | 292 | 70.3 | 2.2 |
| 5 | #5929.17 | 67.0 PK | 68.2 | -1.2 | 1.04 V | 292 | 64.8 | 2.2 |
| 6 | 11650.00 | 57.2 PK | 74.0 | -16.8 | 1.97 V | 91 | 44.9 | 12.3 |
| 7 | 11650.00 | 46.0 AV | 54.0 | -8.0 | 1.97 V | 91 | 33.7 | 12.3 |
| 8 | #17475.00 | 53.5 PK | 68.2 | -14.7 | 1.30 V | 287 | 35.1 | 18.4 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 38 : 5190 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 58.4 PK | 74.0 | -15.6 | 1.23 H | 167 | 56.9 | 1.5 |
| 2 | 5150.00 | 46.0 AV | 54.0 | -8.0 | 1.23 H | 167 | 44.5 | 1.5 |
| 3 | *5190.00 | 104.5 PK | | | 1.23 H | 167 | 103.1 | 1.4 |
| 4 | *5190.00 | 95.0 AV | | | 1.23 H | 167 | 93.6 | 1.4 |
| 5 | #10380.00 | 55.6 PK | 68.2 | -12.6 | 3.72 H | 360 | 44.8 | 10.8 |
| 6 | 15570.00 | 52.5 PK | 74.0 | -21.5 | 1.25 H | 233 | 40.4 | 12.1 |
| 7 | 15570.00 | 41.2 AV | 54.0 | -12.8 | 1.25 H | 233 | 29.1 | 12.1 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5148.80 | 64.8 PK | 74.0 | -9.2 | 1.02 V | 305 | 63.3 | 1.5 |
| 2 | 5148.80 | 53.8 AV | 54.0 | -0.2 | 1.02 V | 305 | 52.3 | 1.5 |
| 3 | *5190.00 | 112.5 PK | | | 1.02 V | 305 | 111.1 | 1.4 |
| 4 | *5190.00 | 100.2 AV | | | 1.02 V | 305 | 98.8 | 1.4 |
| 5 | #10380.00 | 55.3 PK | 68.2 | -12.9 | 1.95 V | 69 | 44.5 | 10.8 |
| 6 | 15570.00 | 51.4 PK | 74.0 | -22.6 | 1.26 V | 303 | 39.3 | 12.1 |
| 7 | 15570.00 | 43.2 AV | 54.0 | -10.8 | 1.26 V | 303 | 31.1 | 12.1 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 46 : 5230 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 62.1 PK | 74.0 | -11.9 | 1.44 H | 155 | 60.6 | 1.5 |
| 2 | 5150.00 | 47.6 AV | 54.0 | -6.4 | 1.44 H | 155 | 46.1 | 1.5 |
| 3 | *5230.00 | 111.3 PK | | | 1.44 H | 155 | 110.0 | 1.3 |
| 4 | *5230.00 | 98.2 AV | | | 1.44 H | 155 | 96.9 | 1.3 |
| 5 | #10460.00 | 55.2 PK | 68.2 | -13.0 | 3.71 H | 360 | 44.3 | 10.9 |
| 6 | 15690.00 | 52.4 PK | 74.0 | -21.6 | 1.24 H | 220 | 40.5 | 11.9 |
| 7 | 15690.00 | 41.0 AV | 54.0 | -13.0 | 1.24 H | 220 | 29.1 | 11.9 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5150.00 | 68.0 PK | 74.0 | -6.0 | 1.02 V | 305 | 66.5 | 1.5 |
| 2 | 5150.00 | 53.6 AV | 54.0 | -0.4 | 1.02 V | 305 | 52.1 | 1.5 |
| 3 | *5230.00 | 119.1 PK | | | 1.02 V | 305 | 117.8 | 1.3 |
| 4 | *5230.00 | 106.8 AV | | | 1.02 V | 305 | 105.5 | 1.3 |
| 5 | #10460.00 | 55.8 PK | 68.2 | -12.4 | 1.99 V | 67 | 44.9 | 10.9 |
| 6 | 15690.00 | 51.5 PK | 74.0 | -22.5 | 1.30 V | 291 | 39.6 | 11.9 |
| 7 | 15690.00 | 43.4 AV | 54.0 | -10.6 | 1.30 V | 291 | 31.5 | 11.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 54 : 5270 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5270.00 | 113.9 PK | | | 1.47 H | 162 | 112.8 | 1.1 |
| 2 | *5270.00 | 98.7 AV | | | 1.47 H | 162 | 97.6 | 1.1 |
| 3 | 5350.97 | 61.8 PK | 74.0 | -12.2 | 1.47 H | 162 | 60.5 | 1.3 |
| 4 | 5350.97 | 47.4 AV | 54.0 | -6.6 | 1.47 H | 162 | 46.1 | 1.3 |
| 5 | #10540.00 | 55.8 PK | 68.2 | -12.4 | 3.71 H | 360 | 44.8 | 11.0 |
| 6 | 15810.00 | 52.3 PK | 74.0 | -21.7 | 1.20 H | 242 | 40.5 | 11.8 |
| 7 | 15810.00 | 41.2 AV | 54.0 | -12.8 | 1.20 H | 242 | 29.4 | 11.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5270.00 | 118.7 PK | | | 1.02 V | 305 | 117.6 | 1.1 |
| 2 | *5270.00 | 106.7 AV | | | 1.02 V | 305 | 105.6 | 1.1 |
| 3 | 5350.97 | 66.5 PK | 74.0 | -7.5 | 1.02 V | 305 | 65.2 | 1.3 |
| 4 | 5350.97 | 53.8 AV | 54.0 | -0.2 | 1.02 V | 305 | 52.5 | 1.3 |
| 5 | #10540.00 | 55.5 PK | 68.2 | -12.7 | 2.00 V | 74 | 44.5 | 11.0 |
| 6 | 15810.00 | 51.6 PK | 74.0 | -22.4 | 1.22 V | 288 | 39.8 | 11.8 |
| 7 | 15810.00 | 43.6 AV | 54.0 | -10.4 | 1.22 V | 288 | 31.8 | 11.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 62 : 5310 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5310.00 | 106.9 PK | | | 1.09 H | 165 | 105.7 | 1.2 |
| 2 | *5310.00 | 96.8 AV | | | 1.09 H | 165 | 95.6 | 1.2 |
| 3 | 5350.00 | 63.5 PK | 74.0 | -10.5 | 1.09 H | 165 | 62.2 | 1.3 |
| 4 | 5350.00 | 49.8 AV | 54.0 | -4.2 | 1.09 H | 165 | 48.5 | 1.3 |
| 5 | 10620.00 | 56.1 PK | 74.0 | -17.9 | 3.76 H | 360 | 45.0 | 11.1 |
| 6 | 10620.00 | 44.5 AV | 54.0 | -9.5 | 3.76 H | 360 | 33.4 | 11.1 |
| 7 | 15930.00 | 52.9 PK | 74.0 | -21.1 | 1.29 H | 242 | 40.8 | 12.1 |
| 8 | 15930.00 | 41.5 AV | 54.0 | -12.5 | 1.29 H | 242 | 29.4 | 12.1 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5310.00 | 112.3 PK | | | 1.02 V | 305 | 111.1 | 1.2 |
| 2 | *5310.00 | 100.3 AV | | | 1.02 V | 305 | 99.1 | 1.2 |
| 3 | 5350.00 | 65.5 PK | 74.0 | -8.5 | 1.02 V | 305 | 64.2 | 1.3 |
| 4 | 5350.00 | 53.7 AV | 54.0 | -0.3 | 1.02 V | 305 | 52.4 | 1.3 |
| 5 | 10620.00 | 55.2 PK | 74.0 | -18.8 | 1.93 V | 60 | 44.1 | 11.1 |
| 6 | 10620.00 | 44.3 AV | 54.0 | -9.7 | 1.93 V | 60 | 33.2 | 11.1 |
| 7 | 15930.00 | 51.6 PK | 74.0 | -22.4 | 1.26 V | 312 | 39.5 | 12.1 |
| 8 | 15930.00 | 43.2 AV | 54.0 | -10.8 | 1.26 V | 312 | 31.1 | 12.1 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 102 : 5510 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 54.1 PK | 74.0 | -19.9 | 1.21 H | 159 | 52.6 | 1.5 |
| 2 | 5460.00 | 44.9 AV | 54.0 | -9.1 | 1.21 H | 159 | 43.4 | 1.5 |
| 3 | #5467.70 | 61.7 PK | 68.2 | -6.5 | 1.21 H | 159 | 60.2 | 1.5 |
| 4 | *5510.00 | 105.2 PK | | | 1.21 H | 159 | 103.7 | 1.5 |
| 5 | *5510.00 | 95.1 AV | | | 1.21 H | 159 | 93.6 | 1.5 |
| 6 | 11020.00 | 56.2 PK | 74.0 | -17.8 | 3.72 H | 360 | 44.4 | 11.8 |
| 7 | 11020.00 | 44.7 AV | 54.0 | -9.3 | 3.72 H | 360 | 32.9 | 11.8 |
| 8 | #16530.00 | 52.5 PK | 68.2 | -15.7 | 1.20 H | 243 | 38.2 | 14.3 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5458.30 | 63.6 PK | 74.0 | -10.4 | 1.10 V | 292 | 62.1 | 1.5 |
| 2 | 5458.30 | 49.5 AV | 54.0 | -4.5 | 1.10 V | 292 | 48.0 | 1.5 |
| 3 | #5470.00 | 68.1 PK | 68.2 | -0.1 | 1.10 V | 292 | 66.6 | 1.5 |
| 4 | *5510.00 | 113.6 PK | | | 1.10 V | 292 | 112.1 | 1.5 |
| 5 | *5510.00 | 101.1 AV | | | 1.10 V | 292 | 99.6 | 1.5 |
| 6 | 11020.00 | 55.5 PK | 74.0 | -18.5 | 1.94 V | 85 | 43.7 | 11.8 |
| 7 | 11020.00 | 44.1 AV | 54.0 | -9.9 | 1.94 V | 85 | 32.3 | 11.8 |
| 8 | #16530.00 | 51.2 PK | 68.2 | -17.0 | 1.25 V | 317 | 36.9 | 14.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 110 : 5550 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5550.00 | 113.6 PK | | | 1.37 H | 164 | 112.1 | 1.5 |
| 2 | *5550.00 | 98.5 AV | | | 1.37 H | 164 | 97.0 | 1.5 |
| 3 | 11100.00 | 55.3 PK | 74.0 | -18.7 | 3.70 H | 360 | 43.4 | 11.9 |
| 4 | 11100.00 | 44.0 AV | 54.0 | -10.0 | 3.70 H | 360 | 32.1 | 11.9 |
| 5 | #16650.00 | 52.4 PK | 68.2 | -15.8 | 1.30 H | 234 | 37.1 | 15.3 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5550.00 | 118.3 PK | | | 1.15 V | 305 | 116.8 | 1.5 |
| 2 | *5550.00 | 106.4 AV | | | 1.15 V | 305 | 104.9 | 1.5 |
| 3 | 11100.00 | 55.4 PK | 74.0 | -18.6 | 1.96 V | 74 | 43.5 | 11.9 |
| 4 | 11100.00 | 44.1 AV | 54.0 | -9.9 | 1.96 V | 74 | 32.2 | 11.9 |
| 5 | #16650.00 | 51.6 PK | 68.2 | -16.6 | 1.32 V | 306 | 36.3 | 15.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 134 : 5670 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5670.00 | 112.8 PK | | | 1.37 H | 177 | 110.9 | 1.9 |
| 2 | *5670.00 | 97.2 AV | | | 1.37 H | 177 | 95.3 | 1.9 |
| 3 | #5725.00 | 64.7 PK | 68.2 | -3.5 | 1.37 H | 177 | 62.7 | 2.0 |
| 4 | 11340.00 | 55.5 PK | 74.0 | -18.5 | 3.77 H | 360 | 43.1 | 12.4 |
| 5 | 11340.00 | 44.5 AV | 54.0 | -9.5 | 3.77 H | 360 | 32.1 | 12.4 |
| 6 | #17010.00 | 51.8 PK | 68.2 | -16.4 | 1.20 H | 221 | 35.2 | 16.6 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5670.00 | 116.9 PK | | | 1.00 V | 309 | 115.0 | 1.9 |
| 2 | *5670.00 | 105.7 AV | | | 1.00 V | 309 | 103.8 | 1.9 |
| 3 | #5725.00 | 67.8 PK | 68.2 | -0.4 | 1.00 V | 309 | 65.8 | 2.0 |
| 4 | 11340.00 | 54.9 PK | 74.0 | -19.1 | 1.90 V | 80 | 42.5 | 12.4 |
| 5 | 11340.00 | 43.8 AV | 54.0 | -10.2 | 1.90 V | 80 | 31.4 | 12.4 |
| 6 | #17010.00 | 51.2 PK | 68.2 | -17.0 | 1.25 V | 308 | 34.6 | 16.6 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 142 : 5710 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 55.8 PK | 74.0 | -18.2 | 1.40 H | 170 | 54.3 | 1.5 |
| 2 | 5460.00 | 43.6 AV | 54.0 | -10.4 | 1.40 H | 170 | 42.1 | 1.5 |
| 3 | #5470.00 | 56.6 PK | 68.2 | -11.6 | 1.40 H | 170 | 55.1 | 1.5 |
| 4 | *5710.00 | 113.8 PK | | | 1.40 H | 170 | 111.8 | 2.0 |
| 5 | *5710.00 | 98.6 AV | | | 1.40 H | 170 | 96.6 | 2.0 |
| 6 | #5850.00 | 57.3 PK | 68.2 | -10.9 | 1.40 H | 170 | 55.0 | 2.3 |
| 7 | 11420.00 | 55.2 PK | 74.0 | -18.8 | 3.76 H | 360 | 42.6 | 12.6 |
| 8 | 11420.00 | 44.0 AV | 54.0 | -10.0 | 3.76 H | 360 | 31.4 | 12.6 |
| 9 | #17130.00 | 52.7 PK | 68.2 | -15.5 | 1.20 H | 226 | 36.2 | 16.5 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 56.6 PK | 74.0 | -17.4 | 1.06 V | 302 | 55.1 | 1.5 |
| 2 | 5460.00 | 44.2 AV | 54.0 | -9.8 | 1.06 V | 302 | 42.7 | 1.5 |
| 3 | #5470.00 | 57.3 PK | 68.2 | -10.9 | 1.06 V | 302 | 55.8 | 1.5 |
| 4 | *5710.00 | 118.4 PK | | | 1.06 V | 302 | 116.4 | 2.0 |
| 5 | *5710.00 | 106.7 AV | | | 1.06 V | 302 | 104.7 | 2.0 |
| 6 | #5850.00 | 59.7 PK | 68.2 | -8.5 | 1.06 V | 302 | 57.4 | 2.3 |
| 7 | 11420.00 | 54.6 PK | 74.0 | -19.4 | 2.00 V | 54 | 42.0 | 12.6 |
| 8 | 11420.00 | 43.6 AV | 54.0 | -10.4 | 2.00 V | 54 | 31.0 | 12.6 |
| 9 | #17130.00 | 51.2 PK | 68.2 | -17.0 | 1.26 V | 309 | 34.7 | 16.5 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 151 : 5755 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5641.40 | 60.9 PK | 68.2 | -7.3 | 3.94 H | 306 | 59.1 | 1.8 |
| 2 | *5755.00 | 114.5 PK | | | 3.94 H | 306 | 112.4 | 2.1 |
| 3 | *5755.00 | 101.3 AV | | | 3.94 H | 306 | 99.2 | 2.1 |
| 4 | #5928.47 | 53.8 PK | 68.2 | -14.4 | 3.94 H | 306 | 51.6 | 2.2 |
| 5 | 11510.00 | 55.2 PK | 74.0 | -18.8 | 3.76 H | 360 | 42.6 | 12.6 |
| 6 | 11510.00 | 44.2 AV | 54.0 | -9.8 | 3.76 H | 360 | 31.6 | 12.6 |
| 7 | #17265.00 | 52.9 PK | 68.2 | -15.3 | 1.30 H | 232 | 36.1 | 16.8 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5634.40 | 67.9 PK | 68.2 | -0.3 | 1.05 V | 310 | 66.1 | 1.8 |
| 2 | *5755.00 | 119.7 PK | | | 1.05 V | 310 | 117.6 | 2.1 |
| 3 | *5755.00 | 107.3 AV | | | 1.05 V | 310 | 105.2 | 2.1 |
| 4 | #5928.44 | 58.4 PK | 68.2 | -9.8 | 1.05 V | 310 | 56.2 | 2.2 |
| 5 | 11510.00 | 55.2 PK | 74.0 | -18.8 | 1.95 V | 66 | 42.6 | 12.6 |
| 6 | 11510.00 | 44.1 AV | 54.0 | -9.9 | 1.95 V | 66 | 31.5 | 12.6 |
| 7 | #17265.00 | 51.6 PK | 68.2 | -16.6 | 1.26 V | 301 | 34.8 | 16.8 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE40) | Channel | CH 159 : 5795 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5645.91 | 54.9 PK | 68.2 | -13.3 | 4.00 H | 301 | 53.1 | 1.8 |
| 2 | *5795.00 | 115.3 PK | | | 4.00 H | 301 | 113.1 | 2.2 |
| 3 | *5795.00 | 101.6 AV | | | 4.00 H | 301 | 99.4 | 2.2 |
| 4 | #5929.07 | 61.4 PK | 68.2 | -6.8 | 4.00 H | 301 | 59.2 | 2.2 |
| 5 | 11590.00 | 55.6 PK | 74.0 | -18.4 | 3.67 H | 360 | 43.2 | 12.4 |
| 6 | 11590.00 | 44.0 AV | 54.0 | -10.0 | 3.67 H | 360 | 31.6 | 12.4 |
| 7 | #17385.00 | 52.3 PK | 68.2 | -15.9 | 1.28 H | 227 | 34.4 | 17.9 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5649.74 | 66.0 PK | 68.2 | -2.2 | 1.03 V | 295 | 64.2 | 1.8 |
| 2 | *5795.00 | 121.6 PK | | | 1.03 V | 295 | 119.4 | 2.2 |
| 3 | *5795.00 | 107.8 AV | | | 1.03 V | 295 | 105.6 | 2.2 |
| 4 | #5928.88 | 67.7 PK | 68.2 | -0.5 | 1.03 V | 295 | 65.5 | 2.2 |
| 5 | 11590.00 | 54.7 PK | 74.0 | -19.3 | 1.92 V | 62 | 42.3 | 12.4 |
| 6 | 11590.00 | 43.8 AV | 54.0 | -10.2 | 1.92 V | 62 | 31.4 | 12.4 |
| 7 | #17385.00 | 51.6 PK | 68.2 | -16.6 | 1.21 V | 319 | 33.7 | 17.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE80) | Channel | CH 42 : 5210 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5144.40 | 60.7 PK | 74.0 | -13.3 | 1.06 H | 167 | 59.2 | 1.5 |
| 2 | 5144.40 | 48.9 AV | 54.0 | -5.1 | 1.06 H | 167 | 47.4 | 1.5 |
| 3 | *5210.00 | 104.2 PK | | | 1.06 H | 167 | 102.8 | 1.4 |
| 4 | *5210.00 | 93.0 AV | | | 1.06 H | 167 | 91.6 | 1.4 |
| 5 | 5354.20 | 53.3 PK | 74.0 | -20.7 | 1.06 H | 167 | 52.0 | 1.3 |
| 6 | 5354.20 | 43.8 AV | 54.0 | -10.2 | 1.06 H | 167 | 42.5 | 1.3 |
| 7 | #10420.00 | 55.7 PK | 68.2 | -12.5 | 3.69 H | 360 | 44.8 | 10.9 |
| 8 | 15630.00 | 52.7 PK | 74.0 | -21.3 | 1.24 H | 228 | 40.7 | 12.0 |
| 9 | 15630.00 | 41.4 AV | 54.0 | -12.6 | 1.24 H | 228 | 29.4 | 12.0 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5149.30 | 64.3 PK | 74.0 | -9.7 | 1.00 V | 308 | 62.8 | 1.5 |
| 2 | 5149.30 | 53.9 AV | 54.0 | -0.1 | 1.00 V | 308 | 52.4 | 1.5 |
| 3 | *5210.00 | 109.8 PK | | | 1.00 V | 308 | 108.4 | 1.4 |
| 4 | *5210.00 | 97.2 AV | | | 1.00 V | 308 | 95.8 | 1.4 |
| 5 | 5350.00 | 54.6 PK | 74.0 | -19.4 | 1.00 V | 308 | 53.3 | 1.3 |
| 6 | 5350.00 | 43.5 AV | 54.0 | -10.5 | 1.00 V | 308 | 42.2 | 1.3 |
| 7 | #10420.00 | 54.9 PK | 68.2 | -13.3 | 1.98 V | 83 | 44.0 | 10.9 |
| 8 | 15630.00 | 51.4 PK | 74.0 | -22.6 | 1.30 V | 298 | 39.4 | 12.0 |
| 9 | 15630.00 | 43.3 AV | 54.0 | -10.7 | 1.30 V | 298 | 31.3 | 12.0 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE80) | Channel | CH 58 : 5290 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5144.20 | 55.0 PK | 74.0 | -19.0 | 1.02 H | 169 | 53.5 | 1.5 |
| 2 | 5144.20 | 43.9 AV | 54.0 | -10.1 | 1.02 H | 169 | 42.4 | 1.5 |
| 3 | *5290.00 | 106.5 PK | | | 1.02 H | 169 | 105.4 | 1.1 |
| 4 | *5290.00 | 94.8 AV | | | 1.02 H | 169 | 93.7 | 1.1 |
| 5 | 5350.00 | 64.0 PK | 74.0 | -10.0 | 1.02 H | 169 | 62.7 | 1.3 |
| 6 | 5350.00 | 52.1 AV | 54.0 | -1.9 | 1.02 H | 169 | 50.8 | 1.3 |
| 7 | #10580.00 | 55.3 PK | 68.2 | -12.9 | 3.73 H | 360 | 44.3 | 11.0 |
| 8 | 15870.00 | 52.9 PK | 74.0 | -21.1 | 1.30 H | 233 | 40.7 | 12.2 |
| 9 | 15870.00 | 41.3 AV | 54.0 | -12.7 | 1.30 H | 233 | 29.1 | 12.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5149.00 | 55.2 PK | 74.0 | -18.8 | 1.11 V | 304 | 53.7 | 1.5 |
| 2 | 5149.00 | 44.3 AV | 54.0 | -9.7 | 1.11 V | 304 | 42.8 | 1.5 |
| 3 | *5290.00 | 109.3 PK | | | 1.11 V | 304 | 108.2 | 1.1 |
| 4 | *5290.00 | 96.9 AV | | | 1.11 V | 304 | 95.8 | 1.1 |
| 5 | 5350.00 | 68.8 PK | 74.0 | -5.2 | 1.11 V | 304 | 67.5 | 1.3 |
| 6 | 5350.00 | 53.7 AV | 54.0 | -0.3 | 1.11 V | 304 | 52.4 | 1.3 |
| 7 | #10580.00 | 54.8 PK | 68.2 | -13.4 | 1.91 V | 74 | 43.8 | 11.0 |
| 8 | 15870.00 | 52.0 PK | 74.0 | -22.0 | 1.29 V | 310 | 39.8 | 12.2 |
| 9 | 15870.00 | 43.6 AV | 54.0 | -10.4 | 1.29 V | 310 | 31.4 | 12.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE80) | Channel | CH 106 : 5530 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 54.8 PK | 74.0 | -19.2 | 1.34 H | 165 | 53.3 | 1.5 |
| 2 | 5460.00 | 45.0 AV | 54.0 | -9.0 | 1.34 H | 165 | 43.5 | 1.5 |
| 3 | #5469.20 | 57.8 PK | 68.2 | -10.4 | 1.34 H | 165 | 56.3 | 1.5 |
| 4 | *5530.00 | 103.2 PK | | | 1.34 H | 165 | 101.7 | 1.5 |
| 5 | *5530.00 | 92.3 AV | | | 1.34 H | 165 | 90.8 | 1.5 |
| 6 | #5771.80 | 50.6 PK | 68.2 | -17.6 | 1.34 H | 165 | 48.4 | 2.2 |
| 7 | 11060.00 | 55.2 PK | 74.0 | -18.8 | 3.66 H | 360 | 43.3 | 11.9 |
| 8 | 11060.00 | 43.9 AV | 54.0 | -10.1 | 3.66 H | 360 | 32.0 | 11.9 |
| 9 | #16590.00 | 52.0 PK | 68.2 | -16.2 | 1.26 H | 242 | 37.1 | 14.9 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5458.10 | 67.4 PK | 74.0 | -6.6 | 1.02 V | 290 | 65.9 | 1.5 |
| 2 | 5458.10 | 52.7 AV | 54.0 | -1.3 | 1.02 V | 290 | 51.2 | 1.5 |
| 3 | #5465.90 | 67.9 PK | 68.2 | -0.3 | 1.02 V | 290 | 66.4 | 1.5 |
| 4 | *5530.00 | 109.9 PK | | | 1.02 V | 290 | 108.4 | 1.5 |
| 5 | *5530.00 | 97.8 AV | | | 1.02 V | 290 | 96.3 | 1.5 |
| 6 | #5729.00 | 53.6 PK | 68.2 | -14.6 | 1.02 V | 290 | 51.6 | 2.0 |
| 7 | 11060.00 | 55.3 PK | 74.0 | -18.7 | 1.97 V | 78 | 43.4 | 11.9 |
| 8 | 11060.00 | 43.9 AV | 54.0 | -10.1 | 1.97 V | 78 | 32.0 | 11.9 |
| 9 | #16590.00 | 51.5 PK | 68.2 | -16.7 | 1.26 V | 315 | 36.6 | 14.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE80) | Channel | CH 122 : 5610 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5610.00 | 103.4 PK | | | 2.56 H | 179 | 101.7 | 1.7 |
| 2 | *5610.00 | 96.3 AV | | | 2.56 H | 179 | 94.6 | 1.7 |
| 3 | #5725.00 | 64.5 PK | 68.2 | -3.7 | 2.56 H | 179 | 62.5 | 2.0 |
| 4 | 11220.00 | 55.8 PK | 74.0 | -18.2 | 3.70 H | 360 | 43.8 | 12.0 |
| 5 | 11220.00 | 44.7 AV | 54.0 | -9.3 | 3.70 H | 360 | 32.7 | 12.0 |
| 6 | #16830.00 | 53.0 PK | 68.2 | -15.2 | 1.23 H | 227 | 36.8 | 16.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | *5610.00 | 115.2 PK | | | 1.08 V | 312 | 113.5 | 1.7 |
| 2 | *5610.00 | 104.1 AV | | | 1.08 V | 312 | 102.4 | 1.7 |
| 3 | #5725.00 | 67.9 PK | 68.2 | -0.3 | 1.08 V | 312 | 65.9 | 2.0 |
| 4 | 11220.00 | 55.2 PK | 74.0 | -18.8 | 1.92 V | 62 | 43.2 | 12.0 |
| 5 | 11220.00 | 44.2 AV | 54.0 | -9.8 | 1.92 V | 62 | 32.2 | 12.0 |
| 6 | #16830.00 | 52.0 PK | 68.2 | -16.2 | 1.24 V | 294 | 35.8 | 16.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE80) | Channel | CH 138 : 5690 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 56.7 PK | 74.0 | -17.3 | 2.58 H | 158 | 55.2 | 1.5 |
| 2 | 5460.00 | 44.3 AV | 54.0 | -9.7 | 2.58 H | 158 | 42.8 | 1.5 |
| 3 | #5470.00 | 59.2 PK | 68.2 | -9.0 | 2.58 H | 158 | 57.7 | 1.5 |
| 4 | *5690.00 | 103.0 PK | | | 2.58 H | 158 | 101.1 | 1.9 |
| 5 | *5690.00 | 95.9 AV | | | 2.58 H | 158 | 94.0 | 1.9 |
| 6 | #5850.00 | 59.6 PK | 68.2 | -8.6 | 2.58 H | 158 | 57.3 | 2.3 |
| 7 | 11380.00 | 56.0 PK | 74.0 | -18.0 | 3.76 H | 360 | 43.5 | 12.5 |
| 8 | 11380.00 | 44.5 AV | 54.0 | -9.5 | 3.76 H | 360 | 32.0 | 12.5 |
| 9 | #17070.00 | 52.7 PK | 68.2 | -15.5 | 1.28 H | 238 | 36.3 | 16.4 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5460.00 | 59.2 PK | 74.0 | -14.8 | 1.05 V | 310 | 57.7 | 1.5 |
| 2 | 5460.00 | 46.7 AV | 54.0 | -7.3 | 1.05 V | 310 | 45.2 | 1.5 |
| 3 | #5470.00 | 62.1 PK | 68.2 | -6.1 | 1.05 V | 310 | 60.6 | 1.5 |
| 4 | *5690.00 | 116.7 PK | | | 1.05 V | 310 | 114.8 | 1.9 |
| 5 | *5690.00 | 103.6 AV | | | 1.05 V | 310 | 101.7 | 1.9 |
| 6 | #5850.00 | 63.7 PK | 68.2 | -4.5 | 1.05 V | 310 | 61.4 | 2.3 |
| 7 | 11380.00 | 55.5 PK | 74.0 | -18.5 | 1.93 V | 56 | 43.0 | 12.5 |
| 8 | 11380.00 | 44.0 AV | 54.0 | -10.0 | 1.93 V | 56 | 31.5 | 12.5 |
| 9 | #17070.00 | 51.2 PK | 68.2 | -17.0 | 1.25 V | 295 | 34.8 | 16.4 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|--------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE80) | Channel | CH 155 : 5775 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5622.60 | 60.7 PK | 68.2 | -7.5 | 3.95 H | 299 | 58.9 | 1.8 |
| 2 | *5775.00 | 109.7 PK | | | 3.95 H | 299 | 107.5 | 2.2 |
| 3 | *5775.00 | 96.3 AV | | | 3.95 H | 299 | 94.1 | 2.2 |
| 4 | #5937.68 | 57.7 PK | 68.2 | -10.5 | 3.95 H | 299 | 55.4 | 2.3 |
| 5 | 11550.00 | 56.0 PK | 74.0 | -18.0 | 3.78 H | 360 | 43.6 | 12.4 |
| 6 | 11550.00 | 44.5 AV | 54.0 | -9.5 | 3.78 H | 360 | 32.1 | 12.4 |
| 7 | #17325.00 | 53.0 PK | 68.2 | -15.2 | 1.23 H | 223 | 35.8 | 17.2 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | #5638.50 | 67.5 PK | 68.2 | -0.7 | 1.00 V | 298 | 65.7 | 1.8 |
| 2 | *5775.00 | 116.3 PK | | | 1.00 V | 298 | 114.1 | 2.2 |
| 3 | *5775.00 | 105.2 AV | | | 1.00 V | 298 | 103.0 | 2.2 |
| 4 | #5927.60 | 62.8 PK | 68.2 | -5.4 | 1.00 V | 298 | 60.6 | 2.2 |
| 5 | 11550.00 | 55.1 PK | 74.0 | -18.9 | 1.90 V | 59 | 42.7 | 12.4 |
| 6 | 11550.00 | 43.7 AV | 54.0 | -10.3 | 1.90 V | 59 | 31.3 | 12.4 |
| 7 | #17325.00 | 51.6 PK | 68.2 | -16.6 | 1.27 V | 288 | 34.4 | 17.2 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|---------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE160) | Channel | CH 50 : 5250 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5138.90 | 58.9 PK | 74.0 | -15.1 | 1.01 H | 166 | 57.4 | 1.5 |
| 2 | 5138.90 | 47.4 AV | 54.0 | -6.6 | 1.01 H | 166 | 45.9 | 1.5 |
| 3 | *5250.00 | 97.3 PK | | | 1.01 H | 166 | 96.2 | 1.1 |
| 4 | *5250.00 | 87.2 AV | | | 1.01 H | 166 | 86.1 | 1.1 |
| 5 | 5407.50 | 55.8 PK | 74.0 | -18.2 | 1.01 H | 166 | 54.5 | 1.3 |
| 6 | 5407.50 | 45.4 AV | 54.0 | -8.6 | 1.01 H | 166 | 44.1 | 1.3 |
| 7 | #10500.00 | 55.1 PK | 68.2 | -13.1 | 3.66 H | 360 | 44.2 | 10.9 |
| 8 | 15750.00 | 53.1 PK | 74.0 | -20.9 | 1.23 H | 221 | 41.2 | 11.9 |
| 9 | 15750.00 | 41.6 AV | 54.0 | -12.4 | 1.23 H | 221 | 29.7 | 11.9 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5094.80 | 65.4 PK | 74.0 | -8.6 | 1.04 V | 303 | 64.0 | 1.4 |
| 2 | 5094.80 | 53.8 AV | 54.0 | -0.2 | 1.04 V | 303 | 52.4 | 1.4 |
| 3 | *5250.00 | 106.6 PK | | | 1.04 V | 303 | 105.5 | 1.1 |
| 4 | *5250.00 | 94.0 AV | | | 1.04 V | 303 | 92.9 | 1.1 |
| 5 | 5351.85 | 65.8 PK | 74.0 | -8.2 | 1.04 V | 303 | 64.5 | 1.3 |
| 6 | 5351.85 | 52.6 AV | 54.0 | -1.4 | 1.04 V | 303 | 51.3 | 1.3 |
| 7 | #10500.00 | 55.2 PK | 68.2 | -13.0 | 1.89 V | 77 | 44.3 | 10.9 |
| 8 | 15750.00 | 51.6 PK | 74.0 | -22.4 | 1.21 V | 293 | 39.7 | 11.9 |
| 9 | 15750.00 | 43.5 AV | 54.0 | -10.5 | 1.21 V | 293 | 31.6 | 11.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

| | | | |
|------------------------|---------------------|---------------------------------|---------------------------|
| RF Mode | TX 802.11ax (HE160) | Channel | CH 114 : 5570 MHz |
| Frequency Range | 1GHz ~ 40GHz | Detector Function | Peak (PK) Average (AV) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 75% RH |
| Tested By | Carter Lin | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5393.60 | 60.9 PK | 74.0 | -13.1 | 1.15 H | 159 | 59.6 | 1.3 |
| 2 | 5393.60 | 49.5 AV | 54.0 | -4.5 | 1.15 H | 159 | 48.2 | 1.3 |
| 3 | #5466.40 | 56.9 PK | 68.2 | -11.3 | 1.15 H | 159 | 55.4 | 1.5 |
| 4 | *5570.00 | 98.6 PK | | | 1.15 H | 159 | 96.9 | 1.7 |
| 5 | *5570.00 | 89.0 AV | | | 1.15 H | 159 | 87.3 | 1.7 |
| 6 | #5727.20 | 60.5 PK | 68.2 | -7.7 | 1.15 H | 159 | 58.5 | 2.0 |
| 7 | 11140.00 | 56.1 PK | 74.0 | -17.9 | 3.72 H | 360 | 44.1 | 12.0 |
| 8 | 11140.00 | 44.8 AV | 54.0 | -9.2 | 3.72 H | 360 | 32.8 | 12.0 |
| 9 | #16710.00 | 53.1 PK | 68.2 | -15.1 | 1.27 H | 220 | 37.4 | 15.7 |

Antenna Polarity & Test Distance : Vertical at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 5442.20 | 65.6 PK | 74.0 | -8.4 | 1.00 V | 312 | 64.2 | 1.4 |
| 2 | 5442.20 | 52.9 AV | 54.0 | -1.1 | 1.00 V | 312 | 51.5 | 1.4 |
| 3 | 5460.00 | 63.4 PK | 74.0 | -10.6 | 1.00 V | 312 | 61.9 | 1.5 |
| 4 | 5460.00 | 53.6 AV | 54.0 | -0.4 | 1.00 V | 312 | 52.1 | 1.5 |
| 5 | #5466.00 | 68.1 PK | 68.2 | -0.1 | 1.00 V | 312 | 66.6 | 1.5 |
| 6 | *5570.00 | 105.7 PK | | | 1.00 V | 312 | 104.0 | 1.7 |
| 7 | *5570.00 | 93.4 AV | | | 1.00 V | 312 | 91.7 | 1.7 |
| 8 | #5739.10 | 64.8 PK | 68.2 | -3.4 | 1.00 V | 312 | 62.7 | 2.1 |
| 9 | 11140.00 | 55.5 PK | 74.0 | -18.5 | 1.91 V | 71 | 43.5 | 12.0 |
| 10 | 11140.00 | 44.6 AV | 54.0 | -9.4 | 1.91 V | 71 | 32.6 | 12.0 |
| 11 | #16710.00 | 52.1 PK | 68.2 | -16.1 | 1.31 V | 308 | 36.4 | 15.7 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Below 1GHz Data:


| | | | |
|------------------------|--------------------|---------------------------------|-------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 157 : 5785 MHz |
| Frequency Range | 9kHz ~ 1GHz | Detector Function | Quasi-Peak (QP) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 66% RH |
| Tested By | Tom Yang | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 30.82 | 27.3 QP | 40.0 | -12.7 | 1.00 H | 271 | 41.1 | -13.8 |
| 2 | 113.18 | 37.3 QP | 43.5 | -6.2 | 3.00 H | 280 | 52.0 | -14.7 |
| 3 | 182.53 | 32.2 QP | 43.5 | -11.3 | 1.50 H | 79 | 46.0 | -13.8 |
| 4 | 250.02 | 29.9 QP | 46.0 | -16.1 | 1.00 H | 254 | 42.6 | -12.7 |
| 5 | 435.44 | 31.4 QP | 46.0 | -14.6 | 2.00 H | 202 | 37.8 | -6.4 |
| 6 | 533.79 | 35.8 QP | 46.0 | -10.2 | 1.50 H | 318 | 40.1 | -4.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




| | | | |
|------------------------|--------------------|---------------------------------|-------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 157 : 5785 MHz |
| Frequency Range | 9kHz ~ 1GHz | Detector Function | Quasi-Peak (QP) |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 66% RH |
| Tested By | Tom Yang | | |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 56.87 | 30.0 QP | 40.0 | -10.0 | 1.50 V | 248 | 43.0 | -13.0 |
| 2 | 112.45 | 30.0 QP | 43.5 | -13.5 | 1.50 V | 245 | 44.9 | -14.9 |
| 3 | 182.65 | 24.8 QP | 43.5 | -18.7 | 1.50 V | 175 | 38.7 | -13.9 |
| 4 | 250.02 | 27.5 QP | 46.0 | -18.5 | 1.50 V | 179 | 40.2 | -12.7 |
| 5 | 375.17 | 25.7 QP | 46.0 | -20.3 | 1.50 V | 14 | 34.1 | -8.4 |
| 6 | 541.72 | 30.7 QP | 46.0 | -15.3 | 2.00 V | 360 | 34.8 | -4.1 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) | |
|-----------------|------------------------|---------|
| | Quasi-peak | Average |
| 0.15 - 0.5 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 56 | 46 |
| 5.0 - 30.0 | 60 | 50 |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

| DESCRIPTION & MANUFACTURER | MODEL NO. | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|----------------------------|-------------------------|------------|-----------------|------------------|
| Test Receiver R&S | ESCS 30 | 847124/029 | 2021/10/13 | 2022/10/12 |
| LISN R&S | ESH3-Z5 | 848773/004 | 2020/10/27 | 2021/10/26 |
| LISN R & S | ESH3-Z5 | 835239/001 | 2021/3/26 | 2022/3/25 |
| 50 ohms Terminator | 50 | 3 | 2020/10/26 | 2021/10/25 |
| RF Coaxial Cable JYEBO | 5D-FB | COCCAB-001 | 2021/9/25 | 2022/9/24 |
| Fixed attenuator STI | STI02-2200-10 | 005 | 2021/8/27 | 2022/8/26 |
| Software BVADT | BVADT_Cond_ V7.3.7.4 | NA | NA | NA |

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
- 3 Tested Date: 2021/10/14

4.2.3 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.


4.2.7 Test Results

| | | | |
|------------------------|--------------------|---|--------------------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 157 : 5785 MHz |
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 68% RH |
| Tested By | Sampson Chen | | |

| Phase Of Power : Line (L) | | | | | | | | | | |
|---------------------------|-----------------|------------------------|----------------------|--------------|-----------------------|--------------|--------------|--------------|---------------|---------------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | | Emission Level (dBuV) | | Limit (dBuV) | | Margin (dB) | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.15391 | 10.05 | 30.97 | 18.75 | 41.02 | 28.80 | 65.79 | 55.79 | -24.77 | -26.99 |
| 2 | 0.19297 | 10.07 | 34.63 | 27.59 | 44.70 | 37.66 | 63.91 | 53.91 | -19.21 | -16.25 |
| 3 | 0.26719 | 10.08 | 38.33 | 30.32 | 48.41 | 40.40 | 61.20 | 51.20 | -12.79 | -10.80 |
| 4 | 0.38047 | 10.09 | 25.58 | 17.33 | 35.67 | 27.42 | 58.27 | 48.27 | -22.60 | -20.85 |
| 5 | 3.50000 | 10.30 | 21.93 | 15.12 | 32.23 | 25.42 | 56.00 | 46.00 | -23.77 | -20.58 |
| 6 | 4.51172 | 10.38 | 19.34 | 13.88 | 29.72 | 24.26 | 56.00 | 46.00 | -26.28 | -21.74 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




| | | | |
|------------------------|--------------------|---|--------------------------------------|
| RF Mode | TX 802.11ax (HE20) | Channel | CH 157 : 5785 MHz |
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 25 °C, 68% RH |
| Tested By | Sampson Chen | | |

| Phase Of Power : Neutral (N) | | | | | | | | | | |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | | Emission Level (dBuV) | | Limit (dBuV) | | Margin (dB) | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.15391 | 10.07 | 30.48 | 18.17 | 40.55 | 28.24 | 65.79 | 55.79 | -25.24 | -27.55 |
| 2 | 0.18516 | 10.08 | 31.53 | 22.83 | 41.61 | 32.91 | 64.25 | 54.25 | -22.64 | -21.34 |
| 3 | 0.27109 | 10.10 | 36.57 | 28.74 | 46.67 | 38.84 | 61.08 | 51.08 | -14.41 | -12.24 |
| 4 | 0.37266 | 10.12 | 23.44 | 16.26 | 33.56 | 26.38 | 58.44 | 48.44 | -24.88 | -22.06 |
| 5 | 3.58984 | 10.33 | 24.33 | 18.04 | 34.66 | 28.37 | 56.00 | 46.00 | -21.34 | -17.63 |
| 6 | 4.97266 | 10.42 | 20.25 | 15.05 | 30.67 | 25.47 | 56.00 | 46.00 | -25.33 | -20.53 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 Transmit Power Measurement

4.3.1 Limits of Transmit Power Measurement

| Operation Band | EUT Category | | Limit |
|----------------|--------------|-----------------------------------|---|
| U-NII-1 | | Outdoor Access Point | 1 Watt (30 dBm) (Max. e.i.r.p \leq 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon) |
| | | Fixed point-to-point Access Point | 1 Watt (30 dBm) |
| | √ | Indoor Access Point | 1 Watt (30 dBm) |
| | | Client device | 250mW (23.97 dBm) |
| U-NII-2A | √ | | 250mW (23.97 dBm) or 11 dBm+10 log B* |
| U-NII-2C | √ | | 250mW (23.97dBm) or 11 dBm+10 log B* |
| U-NII-3 | √ | | 1 Watt (30 dBm) |

*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;


Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.


4.3.2 Test Setup

FOR POWER OUTPUT MEASUREMENT


For channel straddling 5250MHz & channel straddling 5725MHz:



For other channels:



FOR 26dB OCCUPIED BANDWIDTH



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

FOR POWER OUTPUT MEASUREMENT

For channel straddling 5250MHz & channel straddling 5725MHz:

Follow FCC KDB 789033 UNII test procedure:

Method SA-1

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$.
5. Sweep time = auto.
6. Set trigger to free run (duty cycle ≥ 98 percent)
7. Detector = RMS.
8. Trace average at least 100 traces in power averaging mode
9. Compute power by integrating the spectrum across the 26 dB EBW of the signal.

For other channels:

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

FOR 26dB OCCUPIED BANDWIDTH

1. Set RBW = approximately 1% of the emission bandwidth.
2. Set the VBW $>$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Results

POWER OUTPUT
CDD Mode
802.11a

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|----------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 36 | 5180 | 21.73 | 22.80 | 339.482 | 25.31 | 30 | Pass |
| 40 | 5200 | 24.63 | 25.77 | 667.974 | 28.25 | 30 | Pass |
| 48 | 5240 | 23.94 | 23.88 | 492.085 | 26.92 | 30 | Pass |
| 52 | 5260 | 20.08 | 20.21 | 206.813 | 23.16 | 23.97 | Pass |
| 60 | 5300 | 20.16 | 20.18 | 207.985 | 23.18 | 23.97 | Pass |
| 64 | 5320 | 20.11 | 20.13 | 205.604 | 23.13 | 23.97 | Pass |
| 100 | 5500 | 19.94 | 20.46 | 209.801 | 23.22 | 23.97 | Pass |
| 116 | 5580 | 20.04 | 20.23 | 206.364 | 23.15 | 23.97 | Pass |
| 140 | 5700 | 19.97 | 20.38 | 208.456 | 23.19 | 23.97 | Pass |
| *144 (U-NII-2C Band) | 5720 | 19.43 | 19.35 | 173.799 | 22.40 | 23.01 | Pass |
| *144 (U-NII-3 Band) | 5720 | 13.15 | 13.24 | 41.74 | 16.21 | 30 | Pass |
| 149 | 5745 | 26.21 | 26.33 | 847.367 | 29.28 | 30 | Pass |
| 157 | 5785 | 26.22 | 26.53 | 868.573 | 29.39 | 30 | Pass |
| 165 | 5825 | 26.12 | 26.41 | 846.783 | 29.28 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 52 | 5260 | 21.76 | 24.37 > 24 |
| 60 | 5300 | 21.78 | 24.38 > 24 |
| 64 | 5320 | 21.72 | 24.36 > 24 |
| 100 | 5500 | 21.69 | 24.36 > 24 |
| 116 | 5580 | 21.79 | 24.38 > 24 |
| 140 | 5700 | 21.8 | 24.38 > 24 |
| 144 (U-NII-2C Band) | 5720 | 15.9 | 23.01 < 24 |

802.11ac (VHT20)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 36 | 5180 | 20.33 | 20.59 | 222.446 | 23.47 | 30 | Pass |
| 40 | 5200 | 23.29 | 24.34 | 484.948 | 26.86 | 30 | Pass |
| 48 | 5240 | 24.42 | 24.06 | 531.377 | 27.25 | 30 | Pass |
| 52 | 5260 | 20.04 | 20.40 | 210.573 | 23.23 | 23.97 | Pass |
| 60 | 5300 | 19.82 | 20.40 | 205.588 | 23.13 | 23.97 | Pass |
| 64 | 5320 | 19.94 | 20.42 | 208.782 | 23.20 | 23.97 | Pass |
| 100 | 5500 | 19.76 | 18.43 | 164.286 | 22.16 | 23.97 | Pass |
| 116 | 5580 | 20.14 | 20.31 | 210.675 | 23.24 | 23.97 | Pass |
| 140 | 5700 | 19.35 | 18.59 | 158.376 | 22.00 | 23.97 | Pass |
| *144 (U-NII-2C Band) | 5720 | 19.06 | 18.24 | 147.219 | 21.68 | 23.04 | Pass |
| *144 (U-NII-3 Band) | 5720 | 13.46 | 12.64 | 40.547 | 16.08 | 30 | Pass |
| 149 | 5745 | 25.82 | 26.17 | 795.944 | 29.01 | 30 | Pass |
| 157 | 5785 | 25.77 | 26.26 | 800.241 | 29.03 | 30 | Pass |
| 165 | 5825 | 26.19 | 25.97 | 811.277 | 29.09 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 52 | 5260 | 22.11 | 24.44 > 23.97 |
| 60 | 5300 | 22.04 | 24.43 > 23.97 |
| 64 | 5320 | 21.92 | 24.4 > 23.97 |
| 100 | 5500 | 21.88 | 24.4 > 23.97 |
| 116 | 5580 | 21.87 | 24.39 > 23.97 |
| 140 | 5700 | 21.85 | 24.39 > 23.97 |
| 144 (U-NII-2C Band) | 5720 | 16.01 | 23.04 < 23.97 |

802.11ac (VHT40)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 38 | 5190 | 18.36 | 17.23 | 121.393 | 20.84 | 30 | Pass |
| 46 | 5230 | 23.18 | 23.60 | 437.056 | 26.41 | 30 | Pass |
| 54 | 5270 | 20.22 | 21.17 | 236.114 | 23.73 | 23.97 | Pass |
| 62 | 5310 | 18.22 | 18.15 | 131.687 | 21.20 | 23.97 | Pass |
| 102 | 5510 | 18.40 | 17.71 | 128.203 | 21.08 | 23.97 | Pass |
| 110 | 5550 | 19.87 | 20.34 | 205.194 | 23.12 | 23.97 | Pass |
| 134 | 5670 | 20.10 | 19.78 | 197.39 | 22.95 | 23.97 | Pass |
| *142 (U-NII-2C Band) | 5710 | 18.75 | 18.68 | 148.78 | 21.73 | 23.97 | Pass |
| *142 (U-NII-3 Band) | 5710 | 8.79 | 8.41 | 14.503 | 11.61 | 30 | Pass |
| 151 | 5755 | 25.46 | 25.88 | 738.818 | 28.69 | 30 | Pass |
| 159 | 5795 | 25.97 | 26.11 | 803.686 | 29.05 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 54 | 5270 | 41.4 | 27.17 > 23.97 |
| 62 | 5310 | 41.19 | 27.14 > 23.97 |
| 102 | 5510 | 41.16 | 27.14 > 23.97 |
| 110 | 5550 | 41.35 | 27.16 > 23.97 |
| 134 | 5670 | 41.38 | 27.16 > 23.97 |
| 142 (U-NII-2C Band) | 5710 | 35.74 | 26.53 > 23.97 |

802.11ac (VHT80)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 42 | 5210 | 19.03 | 17.99 | 142.934 | 21.55 | 30 | Pass |
| 58 | 5290 | 19.95 | 19.14 | 180.89 | 22.57 | 23.97 | Pass |
| 106 | 5530 | 17.69 | 17.05 | 109.448 | 20.39 | 23.97 | Pass |
| 122 | 5610 | 20.21 | 20.68 | 221.904 | 23.46 | 23.97 | Pass |
| *138 (U-NII-2C Band) | 5690 | 18.85 | 19.71 | 170.277 | 22.31 | 23.97 | Pass |
| *138 (U-NII-3 Band) | 5690 | 5.17 | 5.92 | 7.197 | 8.57 | 30 | Pass |
| 155 | 5775 | 23.60 | 23.24 | 439.95 | 26.43 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 58 | 5290 | 82.92 | 30.18 > 23.97 |
| 106 | 5530 | 82.78 | 30.17 > 23.97 |
| 122 | 5610 | 82.83 | 30.18 > 23.97 |
| 138 (U-NII-2C Band) | 5690 | 76.32 | 29.82 > 23.97 |

802.11ac (VHT160)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| *50 (U-NII-1 Band) | 5250 | 12.70 | 12.67 | 37.114 | 15.70 | 30 | Pass |
| *50 (U-NII-2A Band) | 5250 | 12.77 | 12.92 | 38.512 | 15.86 | 23.97 | Pass |
| 114 | 5570 | 18.20 | 17.12 | 117.592 | 20.70 | 23.97 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 50 (U-NII-2A Band) | 5250 | 83.26 | 30.2 > 23.97 |
| 114 | 5570 | 167.52 | 33.24 > 23.97 |

802.11ax (HE20)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 36 | 5180 | 20.29 | 20.56 | 220.668 | 23.44 | 30 | Pass |
| 40 | 5200 | 23.91 | 24.75 | 544.575 | 27.36 | 30 | Pass |
| 48 | 5240 | 24.51 | 24.14 | 541.906 | 27.34 | 30 | Pass |
| 52 | 5260 | 20.12 | 20.36 | 211.444 | 23.25 | 23.97 | Pass |
| 60 | 5300 | 20.02 | 20.39 | 209.857 | 23.22 | 23.97 | Pass |
| 64 | 5320 | 20.21 | 20.31 | 212.353 | 23.27 | 23.97 | Pass |
| 100 | 5500 | 19.75 | 18.50 | 165.201 | 22.18 | 23.97 | Pass |
| 116 | 5580 | 20.22 | 20.32 | 212.843 | 23.28 | 23.97 | Pass |
| 140 | 5700 | 19.39 | 18.57 | 158.841 | 22.01 | 23.97 | Pass |
| *144 (U-NII-2C Band) | 5720 | 19.29 | 19.26 | 169.252 | 22.29 | 23.04 | Pass |
| *144 (U-NII-3 Band) | 5720 | 13.61 | 13.70 | 46.404 | 16.67 | 30 | Pass |
| 149 | 5745 | 26.20 | 26.12 | 826.13 | 29.17 | 30 | Pass |
| 157 | 5785 | 26.14 | 26.59 | 867.187 | 29.38 | 30 | Pass |
| 165 | 5825 | 26.20 | 26.32 | 845.418 | 29.27 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 52 | 5260 | 22.11 | 24.44 > 23.97 |
| 60 | 5300 | 22.04 | 24.43 > 23.97 |
| 64 | 5320 | 21.92 | 24.4 > 23.97 |
| 100 | 5500 | 21.88 | 24.4 > 23.97 |
| 116 | 5580 | 21.87 | 24.39 > 23.97 |
| 140 | 5700 | 21.85 | 24.39 > 23.97 |
| 144 (U-NII-2C Band) | 5720 | 16.01 | 23.04 < 23.97 |

802.11ax (HE40)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 38 | 5190 | 18.39 | 17.22 | 121.747 | 20.85 | 30 | Pass |
| 46 | 5230 | 23.85 | 23.33 | 457.939 | 26.61 | 30 | Pass |
| 54 | 5270 | 20.42 | 21.38 | 247.558 | 23.94 | 23.97 | Pass |
| 62 | 5310 | 18.37 | 18.24 | 135.388 | 21.32 | 23.97 | Pass |
| 102 | 5510 | 18.47 | 17.76 | 130.011 | 21.14 | 23.97 | Pass |
| 110 | 5550 | 20.56 | 20.57 | 227.788 | 23.58 | 23.97 | Pass |
| 134 | 5670 | 20.70 | 20.45 | 228.407 | 23.59 | 23.97 | Pass |
| *142 (U-NII-2C Band) | 5710 | 19.71 | 19.69 | 186.651 | 22.71 | 23.97 | Pass |
| *142 (U-NII-3 Band) | 5710 | 9.26 | 9.37 | 17.083 | 12.33 | 30 | Pass |
| 151 | 5755 | 25.56 | 25.92 | 750.59 | 28.75 | 30 | Pass |
| 159 | 5795 | 26.17 | 26.33 | 843.536 | 29.26 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 54 | 5270 | 41.4 | 27.17 > 23.97 |
| 62 | 5310 | 41.19 | 27.14 > 23.97 |
| 102 | 5510 | 41.16 | 27.14 > 23.97 |
| 110 | 5550 | 41.35 | 27.16 > 23.97 |
| 134 | 5670 | 41.38 | 27.16 > 23.97 |
| 142 (U-NII-2C Band) | 5710 | 35.74 | 26.53 > 23.97 |

802.11ax (HE80)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 42 | 5210 | 19.05 | 18.02 | 143.74 | 21.58 | 30 | Pass |
| 58 | 5290 | 20.00 | 19.16 | 182.414 | 22.61 | 23.97 | Pass |
| 106 | 5530 | 17.76 | 17.07 | 110.637 | 20.44 | 23.97 | Pass |
| 122 | 5610 | 20.79 | 21.03 | 246.715 | 23.92 | 23.97 | Pass |
| *138 (U-NII-2C Band) | 5690 | 19.75 | 20.01 | 194.637 | 22.89 | 23.97 | Pass |
| *138 (U-NII-3 Band) | 5690 | 6.12 | 5.98 | 8.055 | 9.06 | 30 | Pass |
| 155 | 5775 | 23.64 | 23.25 | 442.555 | 26.46 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The maximum gain is 2.74 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 58 | 5290 | 82.92 | 30.18 > 23.97 |
| 106 | 5530 | 82.78 | 30.17 > 23.97 |
| 122 | 5610 | 82.83 | 30.18 > 23.97 |
| 138 (U-NII-2C Band) | 5690 | 76.32 | 29.82 > 23.97 |

802.11ax (HE160)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| *50 (U-NII-1 Band) | 5250 | 13.06 | 12.81 | 39.329 | 15.95 | 30 | Pass |
| *50 (U-NII-2A Band) | 5250 | 13.13 | 12.80 | 39.614 | 15.98 | 23.97 | Pass |
| 114 | 5570 | 18.25 | 17.19 | 119.194 | 20.76 | 23.97 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The maximum gain is 2.82 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The maximum gain is 2.65 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 50 (U-NII-2A Band) | 5250 | 83.26 | 30.2 > 23.97 |
| 114 | 5570 | 167.52 | 33.24 > 23.97 |

Beamforming Mode

802.11ac (VHT20)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 36 | 5180 | 20.33 | 20.59 | 222.446 | 23.47 | 30 | Pass |
| 40 | 5200 | 23.29 | 24.34 | 484.948 | 26.86 | 30 | Pass |
| 48 | 5240 | 24.42 | 24.06 | 531.377 | 27.25 | 30 | Pass |
| 52 | 5260 | 20.04 | 20.40 | 210.573 | 23.23 | 23.97 | Pass |
| 60 | 5300 | 19.82 | 20.40 | 205.588 | 23.13 | 23.97 | Pass |
| 64 | 5320 | 19.94 | 20.42 | 208.782 | 23.20 | 23.97 | Pass |
| 100 | 5500 | 19.76 | 18.43 | 164.286 | 22.16 | 23.97 | Pass |
| 116 | 5580 | 20.14 | 20.31 | 210.675 | 23.24 | 23.97 | Pass |
| 140 | 5700 | 19.35 | 18.59 | 158.376 | 22.00 | 23.97 | Pass |
| *144 (U-NII-2C Band) | 5720 | 19.06 | 18.24 | 147.219 | 21.68 | 23.04 | Pass |
| *144 (U-NII-3 Band) | 5720 | 13.46 | 12.64 | 40.547 | 16.08 | 30 | Pass |
| 149 | 5745 | 25.82 | 26.17 | 795.944 | 29.01 | 30 | Pass |
| 157 | 5785 | 25.77 | 26.26 | 800.241 | 29.03 | 30 | Pass |
| 165 | 5825 | 26.19 | 25.97 | 811.277 | 29.09 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6 \text{ dBi}$, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6 \text{ dBi}$, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56 \text{ dBi} < 6 \text{ dBi}$, so the output power limit shall not be reduced.
4. For U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54 \text{ dBi} < 6 \text{ dBi}$, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 52 | 5260 | 22.11 | 24.44 > 23.97 |
| 60 | 5300 | 22.04 | 24.43 > 23.97 |
| 64 | 5320 | 21.92 | 24.4 > 23.97 |
| 100 | 5500 | 21.88 | 24.4 > 23.97 |
| 116 | 5580 | 21.87 | 24.39 > 23.97 |
| 140 | 5700 | 21.85 | 24.39 > 23.97 |
| 144 (U-NII-2C Band) | 5720 | 16.01 | 23.04 < 23.97 |

802.11ac (VHT40)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|----------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 38 | 5190 | 18.36 | 17.23 | 121.393 | 20.84 | 30 | Pass |
| 46 | 5230 | 23.18 | 23.60 | 437.056 | 26.41 | 30 | Pass |
| 54 | 5270 | 20.22 | 21.17 | 236.114 | 23.73 | 23.97 | Pass |
| 62 | 5310 | 18.22 | 18.15 | 131.687 | 21.20 | 23.97 | Pass |
| 102 | 5510 | 18.40 | 17.71 | 128.203 | 21.08 | 23.97 | Pass |
| 110 | 5550 | 19.87 | 20.34 | 205.194 | 23.12 | 23.97 | Pass |
| 134 | 5670 | 20.10 | 19.78 | 197.39 | 22.95 | 23.97 | Pass |
| *142 (U-NII-2C Band) | 5710 | 18.75 | 18.68 | 148.78 | 21.73 | 23.97 | Pass |
| *142 (U-NII-3 Band) | 5710 | 8.79 | 8.41 | 14.503 | 11.61 | 30 | Pass |
| 151 | 5755 | 25.46 | 25.88 | 738.818 | 28.69 | 30 | Pass |
| 159 | 5795 | 25.97 | 26.11 | 803.686 | 29.05 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
4. For U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 54 | 5270 | 41.4 | 27.17 > 23.97 |
| 62 | 5310 | 41.19 | 27.14 > 23.97 |
| 102 | 5510 | 41.16 | 27.14 > 23.97 |
| 110 | 5550 | 41.35 | 27.16 > 23.97 |
| 134 | 5670 | 41.38 | 27.16 > 23.97 |
| 142 (U-NII-2C Band) | 5710 | 35.74 | 26.53 > 23.97 |

802.11ac (VHT80)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 42 | 5210 | 19.03 | 17.99 | 142.934 | 21.55 | 30 | Pass |
| 58 | 5290 | 19.95 | 19.14 | 180.89 | 22.57 | 23.97 | Pass |
| 106 | 5530 | 17.69 | 17.05 | 109.448 | 20.39 | 23.97 | Pass |
| 122 | 5610 | 20.21 | 20.68 | 221.904 | 23.46 | 23.97 | Pass |
| *138 (U-NII-2C Band) | 5690 | 18.85 | 19.71 | 170.277 | 22.31 | 23.97 | Pass |
| *138 (U-NII-3 Band) | 5690 | 5.17 | 5.92 | 7.197 | 8.57 | 30 | Pass |
| 155 | 5775 | 23.60 | 23.24 | 439.95 | 26.43 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
4. For U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 58 | 5290 | 82.92 | 30.18 > 23.97 |
| 106 | 5530 | 82.78 | 30.17 > 23.97 |
| 122 | 5610 | 82.83 | 30.18 > 23.97 |
| 138 (U-NII-2C Band) | 5690 | 76.32 | 29.82 > 23.97 |

802.11ac (VHT160)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| *50 (U-NII-1 Band) | 5250 | 12.70 | 12.67 | 37.114 | 15.70 | 30 | Pass |
| *50 (U-NII-2A Band) | 5250 | 12.77 | 12.92 | 38.512 | 15.86 | 23.97 | Pass |
| 114 | 5570 | 18.20 | 17.12 | 117.592 | 20.70 | 23.97 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 50 (U-NII-2A Band) | 5250 | 83.26 | 30.2 > 23.97 |
| 114 | 5570 | 167.52 | 33.24 > 23.97 |

802.11ax (HE20)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 36 | 5180 | 20.29 | 20.56 | 220.668 | 23.44 | 30 | Pass |
| 40 | 5200 | 23.91 | 24.75 | 544.575 | 27.36 | 30 | Pass |
| 48 | 5240 | 24.51 | 24.14 | 541.906 | 27.34 | 30 | Pass |
| 52 | 5260 | 20.12 | 20.36 | 211.444 | 23.25 | 23.97 | Pass |
| 60 | 5300 | 20.02 | 20.39 | 209.857 | 23.22 | 23.97 | Pass |
| 64 | 5320 | 20.21 | 20.31 | 212.353 | 23.27 | 23.97 | Pass |
| 100 | 5500 | 19.75 | 18.50 | 165.201 | 22.18 | 23.97 | Pass |
| 116 | 5580 | 20.22 | 20.32 | 212.843 | 23.28 | 23.97 | Pass |
| 140 | 5700 | 19.39 | 18.57 | 158.841 | 22.01 | 23.97 | Pass |
| *144 (U-NII-2C Band) | 5720 | 19.29 | 19.26 | 169.252 | 22.29 | 23.04 | Pass |
| *144 (U-NII-3 Band) | 5720 | 13.61 | 13.70 | 46.404 | 16.67 | 30 | Pass |
| 149 | 5745 | 26.20 | 26.12 | 826.13 | 29.17 | 30 | Pass |
| 157 | 5785 | 26.14 | 26.59 | 867.187 | 29.38 | 30 | Pass |
| 165 | 5825 | 26.20 | 26.32 | 845.418 | 29.27 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.48 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.48 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.56 dBi < 6dBi, so the output power limit shall not be reduced.
4. For U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.54 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 52 | 5260 | 22.11 | 24.44 > 23.97 |
| 60 | 5300 | 22.04 | 24.43 > 23.97 |
| 64 | 5320 | 21.92 | 24.4 > 23.97 |
| 100 | 5500 | 21.88 | 24.4 > 23.97 |
| 116 | 5580 | 21.87 | 24.39 > 23.97 |
| 140 | 5700 | 21.85 | 24.39 > 23.97 |
| 144 (U-NII-2C Band) | 5720 | 16.01 | 23.04 < 23.97 |

802.11ax (HE40)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 38 | 5190 | 18.39 | 17.22 | 121.747 | 20.85 | 30 | Pass |
| 46 | 5230 | 23.85 | 23.33 | 457.939 | 26.61 | 30 | Pass |
| 54 | 5270 | 20.42 | 21.38 | 247.558 | 23.94 | 23.97 | Pass |
| 62 | 5310 | 18.37 | 18.24 | 135.388 | 21.32 | 23.97 | Pass |
| 102 | 5510 | 18.47 | 17.76 | 130.011 | 21.14 | 23.97 | Pass |
| 110 | 5550 | 20.56 | 20.57 | 227.788 | 23.58 | 23.97 | Pass |
| 134 | 5670 | 20.70 | 20.45 | 228.407 | 23.59 | 23.97 | Pass |
| *142 (U-NII-2C Band) | 5710 | 19.71 | 19.69 | 186.651 | 22.71 | 23.97 | Pass |
| *142 (U-NII-3 Band) | 5710 | 9.26 | 9.37 | 17.083 | 12.33 | 30 | Pass |
| 151 | 5755 | 25.56 | 25.92 | 750.59 | 28.75 | 30 | Pass |
| 159 | 5795 | 26.17 | 26.33 | 843.536 | 29.26 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
4. For U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 54 | 5270 | 41.4 | 27.17 > 23.97 |
| 62 | 5310 | 41.19 | 27.14 > 23.97 |
| 102 | 5510 | 41.16 | 27.14 > 23.97 |
| 110 | 5550 | 41.35 | 27.16 > 23.97 |
| 134 | 5670 | 41.38 | 27.16 > 23.97 |
| 142 (U-NII-2C Band) | 5710 | 35.74 | 26.53 > 23.97 |

802.11ax (HE80)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 42 | 5210 | 19.05 | 18.02 | 143.74 | 21.58 | 30 | Pass |
| 58 | 5290 | 20.00 | 19.16 | 182.414 | 22.61 | 23.97 | Pass |
| 106 | 5530 | 17.76 | 17.07 | 110.637 | 20.44 | 23.97 | Pass |
| 122 | 5610 | 20.79 | 21.03 | 246.715 | 23.92 | 23.97 | Pass |
| *138 (U-NII-2C Band) | 5690 | 19.75 | 20.01 | 194.637 | 22.89 | 23.97 | Pass |
| *138 (U-NII-3 Band) | 5690 | 6.12 | 5.98 | 8.055 | 9.06 | 30 | Pass |
| 155 | 5775 | 23.64 | 23.25 | 442.555 | 26.46 | 30 | Pass |

Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.
4. For U-NII-3: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54 \text{ dBi} < 6\text{dBi}$, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth

| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 58 | 5290 | 82.92 | 30.18 > 23.97 |
| 106 | 5530 | 82.78 | 30.17 > 23.97 |
| 122 | 5610 | 82.83 | 30.18 > 23.97 |
| 138 (U-NII-2C Band) | 5690 | 76.32 | 29.82 > 23.97 |

802.11ax (HE160)

| Chan. | Chan. Freq. (MHz) | Average Power (dBm) | | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------------------|-------------------|---------------------|---------|------------------|-------------------|-------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| *50 (U-NII-1 Band) | 5250 | 13.06 | 12.81 | 39.329 | 15.95 | 30 | Pass |
| *50 (U-NII-2A Band) | 5250 | 13.13 | 12.80 | 39.614 | 15.98 | 23.97 | Pass |
| 114 | 5570 | 18.25 | 17.19 | 119.194 | 20.76 | 23.97 | Pass |


Note: * Test was performed in accordance with Measurement follow FCC KDB 789033 UNII test procedure Method SA-1 and use spectrum analyzer test.

1. For U-NII-1: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.48 dBi < 6dBi, so the output power limit shall not be reduced.
2. For U-NII-2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.48 dBi < 6dBi, so the output power limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.56 dBi < 6dBi, so the output power limit shall not be reduced.

Note: For U-NII-2A, U-NII-2C Band output power limitation is determined based on 26dBc bandwidth


| Power Limit = 11dBm + 10logB < U-NII-2A, U-NII-2C > | | | |
|---|------------|-------------|----------------------------------|
| Channel Number | Freq.(MHz) | Min. B(MHz) | Determined Conducted Limit (dBm) |
| 50 (U-NII-2A Band) | 5250 | 83.26 | 30.2 > 23.97 |
| 114 | 5570 | 167.52 | 33.24 > 23.97 |

**For channel straddling 5725MHz of Power
CDD / Beamforming Mode**




Spectrum Plot Value of Power


802.11ac (VHT40)_Chain 0 / CH142 (U-NII-2C Band)




802.11ac (VHT40)_Chain 0 / CH142 (U-NII-3 Band)




802.11ac (VHT40)_Chain 1 / CH142 (U-NII-2C Band)




802.11ac (VHT40)_Chain 1 / CH142 (U-NII-3 Band)




802.11ac (VHT80)_Chain 0 / CH138 (U-NII-2C Band)




802.11ac (VHT80)_Chain 0 / CH138 (U-NII-3 Band)



802.11ac (VHT80)_Chain 1 / CH138 (U-NII-2C Band)




802.11ac (VHT80)_Chain 1 / CH138 (U-NII-3 Band)




Spectrum Plot Value of Power


802.11ax (HE20)_Chain 0 / CH144 (U-NII-2C Band)




802.11ax (HE20)_Chain 0 / CH144 (U-NII-3 Band)




802.11ax (HE20)_Chain 1 / CH144 (U-NII-2C Band)




802.11ax (HE20)_Chain 1 / CH144 (U-NII-3 Band)




802.11ax (HE40)_Chain 0 / CH142 (U-NII-2C Band)




802.11ax (HE40)_Chain 0 / CH142 (U-NII-3 Band)



802.11ax (HE40)_Chain 1 / CH142 (U-NII-2C Band)




802.11ax (HE40)_Chain 1 / CH142 (U-NII-3 Band)




Spectrum Plot Value of Power


802.11ax (HE80)_Chain 0 / CH138 (U-NII-2C Band)




802.11ax (HE80)_Chain 0 / CH138 (U-NII-3 Band)



802.11ax (HE80)_Chain 1 / CH138 (U-NII-2C Band)



802.11ax (HE80)_Chain 1 / CH138 (U-NII-3 Band)



For channel straddling 5250MHz of Power



26dB OCCUPIED BANDWIDTH

802.11a

| Channel | Frequency (MHz) | 26dB Bandwidth (MHz) | |
|---------------------|-----------------|----------------------|--------|
| | | Chain0 | Chain1 |
| 52 | 5260 | 21.79 | 21.76 |
| 60 | 5300 | 21.78 | 21.82 |
| 64 | 5320 | 21.72 | 21.76 |
| 100 | 5500 | 21.75 | 21.69 |
| 116 | 5580 | 21.79 | 21.79 |
| 140 | 5700 | 21.83 | 21.8 |
| 144 (U-NII-2C Band) | 5720 | 15.93 | 15.9 |

802.11ax (HE20)

| Channel | Frequency (MHz) | 26dB Bandwidth (MHz) | |
|---------------------|-----------------|----------------------|--------|
| | | Chain0 | Chain1 |
| 52 | 5260 | 22.13 | 22.11 |
| 60 | 5300 | 22.16 | 22.04 |
| 64 | 5320 | 22.11 | 21.92 |
| 100 | 5500 | 22.03 | 21.88 |
| 116 | 5580 | 22.19 | 21.87 |
| 140 | 5700 | 22.16 | 21.85 |
| 144 (U-NII-2C Band) | 5720 | 16.08 | 16.01 |

802.11ax (HE40)

| Channel | Frequency (MHz) | 26dB Bandwidth (MHz) | |
|---------------------|-----------------|----------------------|--------|
| | | Chain0 | Chain1 |
| 54 | 5270 | 41.4 | 42.66 |
| 62 | 5310 | 41.24 | 41.19 |
| 102 | 5510 | 41.37 | 41.16 |
| 110 | 5550 | 41.35 | 41.47 |
| 134 | 5670 | 41.38 | 41.49 |
| 142 (U-NII-2C Band) | 5710 | 35.74 | 36.02 |

802.11ax (HE80)


| Channel | Frequency (MHz) | 26dB Bandwidth (MHz) | |
|---------------------|-----------------|----------------------|--------|
| | | Chain0 | Chain1 |
| 58 | 5290 | 82.96 | 82.92 |
| 106 | 5530 | 83.09 | 82.78 |
| 122 | 5610 | 82.88 | 82.83 |
| 138 (U-NII-2C Band) | 5690 | 76.32 | 76.39 |

802.11ax (HE160)


| Channel | Frequency (MHz) | 26dB Bandwidth (MHz) | |
|--------------------|-----------------|----------------------|--------|
| | | Chain0 | Chain1 |
| 50 (U-NII-2A Band) | 5250 | 83.69 | 83.26 |
| 114 | 5570 | 168.95 | 167.52 |

Spectrum Plot of Min. Value


802.11a_Chain 1 / CH144 (U-NII-2C Band)




802.11ax (HE20)_Chain 1 / CH144 (U-NII-2C Band)




802.11ax (HE40)_Chain 0 / CH142 (U-NII-2C Band)



802.11ax (HE80)_Chain 0 / CH138 (U-NII-2C Band)



802.11ax (HE160)_Chain 1 / CH50 (U-NII-2A Band)




Note:

- For CH144 (U-NII-2C) = Delta 2 - (5725MHz - Marker 1)
- For CH142 (U-NII-2C) = Delta 2 - (5725MHz - Marker 1)
- For CH138 (U-NII-2C) = Delta 2 - (5725MHz - Marker 1)
- For CH50 (U-NII-2A) = 5250MHz - Marker 1

4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to SAMPLE. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

4.4.4 Test Results

802.11a

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | |
|---------------------|-----------------|--------------------------|---------|
| | | Chain 0 | Chain 1 |
| 36 | 5180 | 17.64 | 17.28 |
| 40 | 5200 | 25.32 | 23.76 |
| 48 | 5240 | 18.6 | 17.88 |
| 52 | 5260 | 17.04 | 17.04 |
| 60 | 5300 | 17.04 | 17.04 |
| 64 | 5320 | 17.04 | 17.04 |
| 100 | 5500 | 17.04 | 17.04 |
| 116 | 5580 | 17.16 | 17.16 |
| 140 | 5700 | 17.04 | 17.04 |
| 144 (U-NII-2C Band) | 5720 | 13.52 | 13.52 |
| 144 (U-NII-3 Band) | 5720 | 3.52 | 3.52 |
| 149 | 5745 | 20.04 | 24.84 |
| 157 | 5785 | 21 | 27.12 |
| 165 | 5825 | 21.84 | 27.96 |

802.11ax (HE20)

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | |
|---------------------|-----------------|--------------------------|---------|
| | | Chain 0 | Chain 1 |
| 36 | 5180 | 18.24 | 18 |
| 40 | 5200 | 19.8 | 19.56 |
| 48 | 5240 | 19.68 | 18.84 |
| 52 | 5260 | 18.12 | 18.12 |
| 60 | 5300 | 18.24 | 18.12 |
| 64 | 5320 | 18.12 | 17.88 |
| 100 | 5500 | 18.12 | 17.88 |
| 116 | 5580 | 18.24 | 18 |
| 140 | 5700 | 18.12 | 18 |
| 144 (U-NII-2C Band) | 5720 | 14.12 | 14.12 |
| 144 (U-NII-3 Band) | 5720 | 4.12 | 4 |
| 149 | 5745 | 20.16 | 30.48 |
| 157 | 5785 | 22.2 | 31.92 |
| 165 | 5825 | 23.64 | 32.16 |

802.11ax (HE40)

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | |
|---------------------|-----------------|--------------------------|---------|
| | | Chain 0 | Chain 1 |
| 38 | 5190 | 36.72 | 36.48 |
| 46 | 5230 | 37.92 | 37.2 |
| 54 | 5270 | 36.96 | 36.96 |
| 62 | 5310 | 36.72 | 36.48 |
| 102 | 5510 | 36.72 | 36.48 |
| 110 | 5550 | 36.72 | 36.96 |
| 134 | 5670 | 36.72 | 36.96 |
| 142 (U-NII-2C Band) | 5710 | 33.48 | 33.48 |
| 142 (U-NII-3 Band) | 5710 | 3.48 | 3.48 |
| 151 | 5755 | 47.76 | 50.88 |
| 159 | 5795 | 60.24 | 61.2 |

802.11ax (HE80)


| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | |
|---------------------|-----------------|--------------------------|---------|
| | | Chain 0 | Chain 1 |
| 42 | 5210 | 75.84 | 75.84 |
| 58 | 5290 | 76.8 | 75.84 |
| 106 | 5530 | 77.28 | 76.32 |
| 122 | 5610 | 77.28 | 75.84 |
| 138 (U-NII-2C Band) | 5690 | 73.88 | 72.92 |
| 138 (U-NII-3 Band) | 5690 | 3.4 | 2.92 |
| 155 | 5775 | 77.57 | 75.84 |

802.11ax (HE160)


| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | |
|---------------|-----------------|--------------------------|---------|
| | | Chain 0 | Chain 1 |
| 50 (U-NII-1) | 5250 | 77.76 | 77.76 |
| 50 (U-NII-2A) | 5250 | 76.8 | 77.76 |
| 114 | 5570 | 154.56 | 155.52 |

Spectrum Plot of Max. Value


802.11a_Chain 1 / CH165




802.11ax (HE20)_Chain 1 / CH165




802.11ax (HE40)_Chain 1 / CH159




802.11ax (HE80)_Chain 0 / CH155




802.11ax (HE160)_Chain 1 / CH 114



For channel straddling 5725MHz of OCP99% BW




For channel straddling 5250MHz of OCP99% BW



Note:


- For CH144 (U-NII-2C) = 5725MHz - Temp 1
- For CH142 (U-NII-2C) = 5725MHz - Temp 1
- For CH138 (U-NII-2C) = 5725MHz - Temp 1
- For CH144 (U-NII-3) = Temp 2 - 5725MHz
- For CH142 (U-NII-3) = Temp 2 - 5725MHz
- For CH138 (U-NII-3) = Temp 2 - 5725MHz
- For CH50 (U-NII-2A) = Temp 2 – 5250MHz
- For CH50 (U-NII-1) = 5250MHz – Temp 1

**Spectrum Plot for near by DFS band
(DFS is required, if 99% OCP straddle into U-NII-2A band)**




**Spectrum Plot for near by DFS band
(DFS is required, if 99% OCP straddle into U-NII-2C band)**


802.11a_Chain 0 / CH149




802.11a_Chain 1 / CH149




802.11ax (HE20)_Chain 0 / CH149




802.11ax (HE20)_Chain 1 / CH149




802.11ax (HE40)_Chain 0 / CH151




802.11ax (HE40)_Chain 1 / CH151



802.11ax (HE80)_Chain 0 / CH155



802.11ax (HE80)_Chain 1 / CH155




4.5 Peak Power Spectral Density Measurement

4.5.1 Limits of Peak Power Spectral Density Measurement

| Operation Band | EUT Category | | Limit |
|----------------|--------------|-----------------------------------|---------------|
| U-NII-1 | | Outdoor Access Point | 17dBm/ MHz |
| | | Fixed point-to-point Access Point | |
| | √ | Indoor Access Point | |
| | | Client device | |
| U-NII-2A | | √ | 11dBm/ MHz |
| U-NII-2C | | √ | 11dBm/ MHz |
| U-NII-3 | | √ | 30dBm/ 500kHz |

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-1

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW \geq 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value

For U-NII-3 band:

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 300 kHz, Set VBW \geq 1 MHz, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent value in 500 kHz by adjusting (increasing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500\text{kHz}/300\text{kHz})$
5. Sweep time = auto, trigger set to "free run".
6. Trace average at least 100 traces in power averaging mode.
7. Record the max value

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6.

4.5.7 Test Results

For U-NII-1, U-NII-2A, U-NII-2C band:

802.11a

| Chan. | Chan. Freq. (MHz) | PSD (dBm/MHz) | | Total PSD (dBm/MHz) | Max. PSD Limit (dBm/MHz) | Pass / Fail |
|---------------------|-------------------|---------------|---------|---------------------|--------------------------|-------------|
| | | Chain 0 | Chain 1 | | | |
| 36 | 5180 | 9.80 | 9.35 | 12.59 | 17.00 | Pass |
| 40 | 5200 | 12.36 | 12.41 | 15.40 | 17.00 | Pass |
| 48 | 5240 | 11.12 | 10.51 | 13.84 | 17.00 | Pass |
| 52 | 5260 | 6.97 | 7.43 | 10.22 | 11.00 | Pass |
| 60 | 5300 | 7.16 | 7.07 | 10.13 | 11.00 | Pass |
| 64 | 5320 | 7.16 | 7.15 | 10.17 | 11.00 | Pass |
| 100 | 5500 | 5.67 | 6.92 | 9.35 | 11.00 | Pass |
| 116 | 5580 | 8.35 | 7.36 | 10.89 | 11.00 | Pass |
| 140 | 5700 | 7.83 | 7.10 | 10.49 | 11.00 | Pass |
| 144 (U-NII-2C Band) | 5720 | 7.91 | 7.22 | 10.59 | 11.00 | Pass |

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. For U-NII-1&2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11ax (HE20)

| Chan. | Chan. Freq. (MHz) | PSD (dBm/MHz) | | Total PSD (dBm/MHz) | Max. PSD Limit (dBm/MHz) | Pass / Fail |
|---------------------|-------------------|---------------|---------|---------------------|--------------------------|-------------|
| | | Chain 0 | Chain 1 | | | |
| 36 | 5180 | 7.47 | 6.74 | 10.13 | 17.00 | Pass |
| 40 | 5200 | 10.63 | 11.04 | 13.85 | 17.00 | Pass |
| 48 | 5240 | 10.78 | 10.29 | 13.55 | 17.00 | Pass |
| 52 | 5260 | 6.97 | 7.11 | 10.05 | 11.00 | Pass |
| 60 | 5300 | 7.08 | 7.03 | 10.07 | 11.00 | Pass |
| 64 | 5320 | 6.98 | 7.02 | 10.01 | 11.00 | Pass |
| 100 | 5500 | 5.99 | 5.14 | 8.60 | 11.00 | Pass |
| 116 | 5580 | 6.90 | 6.69 | 9.81 | 11.00 | Pass |
| 140 | 5700 | 5.34 | 4.91 | 8.14 | 11.00 | Pass |
| 144 (U-NII-2C Band) | 5720 | 6.93 | 6.77 | 9.86 | 11.00 | Pass |

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. For U-NII-1&2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11ax (HE40)

| Chan. | Chan. Freq. (MHz) | PSD (dBm/MHz) | | Total PSD (dBm/MHz) | Max. PSD Limit (dBm/MHz) | Pass / Fail |
|---------------------|-------------------|---------------|---------|---------------------|--------------------------|-------------|
| | | Chain 0 | Chain 1 | | | |
| 38 | 5190 | 1.32 | 0.63 | 4.00 | 17.00 | Pass |
| 46 | 5230 | 7.13 | 6.53 | 9.85 | 17.00 | Pass |
| 54 | 5270 | 4.43 | 4.86 | 7.66 | 11.00 | Pass |
| 62 | 5310 | 2.84 | 0.58 | 4.87 | 11.00 | Pass |
| 102 | 5510 | 2.05 | 1.56 | 4.82 | 11.00 | Pass |
| 110 | 5550 | 4.13 | 3.90 | 7.03 | 11.00 | Pass |
| 134 | 5670 | 3.56 | 3.80 | 6.69 | 11.00 | Pass |
| 142 (U-NII-2C Band) | 5710 | 3.89 | 4.12 | 7.02 | 11.00 | Pass |

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. For U-NII-1&2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11ax (HE80)

| Chan. | Chan. Freq. (MHz) | PSD (dBm/MHz) | | Total PSD (dBm/MHz) | Max. PSD Limit (dBm/MHz) | Pass / Fail |
|---------------------|-------------------|---------------|---------|---------------------|--------------------------|-------------|
| | | Chain 0 | Chain 1 | | | |
| 42 | 5210 | -0.54 | -1.63 | 1.96 | 17.00 | Pass |
| 58 | 5290 | 0.71 | -0.33 | 3.23 | 11.00 | Pass |
| 106 | 5530 | -1.49 | -2.36 | 1.11 | 11.00 | Pass |
| 122 | 5610 | 1.35 | 1.54 | 4.46 | 11.00 | Pass |
| 138 (U-NII-2C Band) | 5690 | 1.43 | 1.43 | 4.44 | 11.00 | Pass |

- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. For U-NII-1&2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.48\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.56\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.


802.11ax (HE160)

| Chan. | Chan. Freq. (MHz) | PSD (dBm/MHz) | | Total PSD (dBm/MHz) | Max. PSD Limit (dBm/MHz) | Pass / Fail |
|---------------|-------------------|---------------|---------|---------------------|--------------------------|-------------|
| | | Chain 0 | Chain 1 | | | |
| 50 (U-NII-1) | 5250 | -6.45 | -6.75 | -3.59 | 17.00 | Pass |
| 50 (U-NII-2A) | 5250 | -6.28 | -6.57 | -3.41 | 11.00 | Pass |
| 114 | 5570 | -4.10 | -6.39 | -2.09 | 11.00 | Pass |


- Note: 1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. For U-NII-1&2A: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.48dBi < 6dBi, so the power density limit shall not be reduced.
3. For U-NII-2C: The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2]$ = 5.56dBi < 6dBi, so the power density limit shall not be reduced.

Spectrum Plot of Worst Value


802.11a_Chain 1 / CH40




802.11ax (HE20)_Chain 1 / CH40




802.11ax (HE40)_Chain 0 / CH46



802.11ax (HE80)_Chain 1 / CH122



802.11ax (HE160)_Chain 0 / CH114



For U-NII-3 band:

802.11a

| Chan. | Chan. Freq. (MHz) | PSD (dBm/300kHz) | | Total PSD (dBm/300kHz) | Total PSD (dBm/500kHz) | PSD Limit (dBm/500kHz) | Pass / Fail |
|--------------------|-------------------|------------------|---------|------------------------|------------------------|------------------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 144 (U-NII-3 Band) | 5720 | -0.92 | -1.50 | 1.81 | 4.03 | 30.00 | Pass |
| 149 | 5745 | 3.31 | 4.48 | 6.94 | 9.16 | 30.00 | Pass |
| 157 | 5785 | 3.47 | 4.23 | 6.88 | 9.10 | 30.00 | Pass |
| 165 | 5825 | 3.77 | 4.63 | 7.23 | 9.45 | 30.00 | Pass |

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11ax (HE20)

| Chan. | Chan. Freq. (MHz) | PSD (dBm/300kHz) | | Total PSD (dBm/300kHz) | Total PSD (dBm/500kHz) | PSD Limit (dBm/500kHz) | Pass / Fail |
|--------------------|-------------------|------------------|---------|------------------------|------------------------|------------------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 144 (U-NII-3 Band) | 5720 | -1.49 | -2.20 | 1.18 | 3.40 | 30.00 | Pass |
| 149 | 5745 | 3.13 | 4.39 | 6.82 | 9.04 | 30.00 | Pass |
| 157 | 5785 | 3.25 | 4.59 | 6.98 | 9.20 | 30.00 | Pass |
| 165 | 5825 | 3.47 | 4.54 | 7.05 | 9.27 | 30.00 | Pass |

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11ax (HE40)


| Chan. | Chan. Freq. (MHz) | PSD (dBm/300kHz) | | Total PSD (dBm/300kHz) | Total PSD (dBm/500kHz) | PSD Limit (dBm/500kHz) | Pass / Fail |
|--------------------|-------------------|------------------|---------|------------------------|------------------------|------------------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 142 (U-NII-3 Band) | 5710 | -5.81 | -5.33 | -2.55 | -0.33 | 30.00 | Pass |
| 151 | 5755 | -0.13 | 0.09 | 2.99 | 5.21 | 30.00 | Pass |
| 159 | 5795 | 0.66 | 0.62 | 3.65 | 5.87 | 30.00 | Pass |

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11ax (HE80)

| Chan. | Chan. Freq. (MHz) | PSD (dBm/300kHz) | | Total PSD (dBm/300kHz) | Total PSD (dBm/500kHz) | PSD Limit (dBm/500kHz) | Pass / Fail |
|--------------------|-------------------|------------------|---------|------------------------|------------------------|------------------------|-------------|
| | | Chain 0 | Chain 1 | | | | |
| 138 (U-NII-3 Band) | 5710 | -9.12 | -8.72 | -5.91 | -3.69 | 30.00 | Pass |
| 155 | 5755 | -5.66 | -5.48 | -2.56 | -0.34 | 30.00 | Pass |

- Note: 1. Method b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
 2. The directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 5.54\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.




4.6 Frequency Stability Measurement

4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

4.6.7 Test Results

| Frequency Stability Versus Temp. | | | | | | | | | |
|----------------------------------|--------------------------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|
| Operating Frequency: 5180 MHz | | | | | | | | | |
| TEMP. (°C) | Power Supply (Vac) | 0 Minute | | 2 Minutes | | 5 Minutes | | 10 Minutes | |
| | | Measured Frequency (MHz) | Pass/Fail | Measured Frequency (MHz) | Pass/Fail | Measured Frequency (MHz) | Pass/Fail | Measured Frequency (MHz) | Pass/Fail |
| 35 | 120 | 5179.9801 | Pass | 5179.9795 | Pass | 5179.9789 | Pass | 5179.9811 | Pass |
| 30 | 120 | 5179.9932 | Pass | 5179.9966 | Pass | 5179.9928 | Pass | 5179.9949 | Pass |
| 20 | 120 | 5180.0139 | Pass | 5180.016 | Pass | 5180.0172 | Pass | 5180.0176 | Pass |
| 10 | 120 | 5180.0112 | Pass | 5180.0075 | Pass | 5180.0077 | Pass | 5180.0111 | Pass |
| 0 | 120 | 5179.9868 | Pass | 5179.9862 | Pass | 5179.9885 | Pass | 5179.9889 | Pass |


| Frequency Stability Versus Voltage | | | | | | | | | |
|------------------------------------|--------------------------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|--------------------------------|-----------|
| Operating Frequency: 5180 MHz | | | | | | | | | |
| TEMP. (°C) | Power Supply (Vac) | 0 Minute | | 2 Minutes | | 5 Minutes | | 10 Minutes | |
| | | Measured Frequency (MHz) | Pass/Fail | Measured Frequency (MHz) | Pass/Fail | Measured Frequency (MHz) | Pass/Fail | Measured Frequency (MHz) | Pass/Fail |
| 20 | 138 | 5180.0259 | Pass | 5180.0258 | Pass | 5180.0243 | Pass | 5180.0237 | Pass |
| | 120 | 5180.0139 | Pass | 5180.016 | Pass | 5180.0172 | Pass | 5180.0176 | Pass |
| | 102 | 5180.024 | Pass | 5180.0213 | Pass | 5180.0237 | Pass | 5180.0192 | Pass |

4.7 6dB Bandwidth Measurement

4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

802.11a

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | | Limit (MHz) | Pass / Fail |
|--------------------|-----------------|---------------------|---------|-------------|-------------|
| | | Chain 0 | Chain 1 | | |
| 144 (U-NII-3 Band) | 5720 | 3.19 | 3.19 | 0.5 | Pass |
| 149 | 5745 | 16.42 | 16.4 | 0.5 | Pass |
| 157 | 5785 | 16.43 | 16.41 | 0.5 | Pass |
| 165 | 5825 | 16.41 | 16.41 | 0.5 | Pass |

802.11ax (HE20)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | | Limit (MHz) | Pass / Fail |
|--------------------|-----------------|---------------------|---------|-------------|-------------|
| | | Chain 0 | Chain 1 | | |
| 144 (U-NII-3 Band) | 5720 | 3.82 | 3.82 | 0.5 | Pass |
| 149 | 5745 | 17.66 | 17.62 | 0.5 | Pass |
| 157 | 5785 | 17.65 | 17.63 | 0.5 | Pass |
| 165 | 5825 | 17.65 | 17.62 | 0.5 | Pass |

802.11ax (HE40)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | | Limit (MHz) | Pass / Fail |
|--------------------|-----------------|---------------------|---------|-------------|-------------|
| | | Chain 0 | Chain 1 | | |
| 142 (U-NII-3 Band) | 5710 | 3.25 | 3.23 | 0.5 | Pass |
| 151 | 5755 | 36.47 | 36.49 | 0.5 | Pass |
| 159 | 5795 | 36.45 | 36.51 | 0.5 | Pass |

802.11ax (HE80)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | | Limit (MHz) | Pass / Fail |
|--------------------|-----------------|---------------------|---------|-------------|-------------|
| | | Chain 0 | Chain 1 | | |
| 138 (U-NII-3 Band) | 5690 | 3.88 | 3.24 | 0.5 | Pass |
| 155 | 5775 | 77.86 | 76.44 | 0.5 | Pass |

Spectrum Plot of Worst Value


802.11a_Chain 0 / CH144 (U-NII-3 Band)




802.11ax (HE20)_Chain 0 / CH144 (U-NII-3 Band)



802.11ax (HE40)_Chain 1 / CH142 (U-NII-3 Band)



802.11ax (HE80)_Chain 1 / CH138 (U-NII-3 Band)



Note: The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz


5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).


Annex A - Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)

802.11a CH 149 : 5745 MHz

Horizontal




Vertical




802.11a CH 157 : 5785 MHz

Horizontal




Vertical




802.11a CH 165 : 5825 MHz

Horizontal




Vertical




802.11ax (HE20) CH 149 : 5745 MHz

Horizontal




Vertical




802.11ax (HE20) CH 157 : 5785 MHz

Horizontal




Vertical




802.11ax (HE20) CH 165 : 5825 MHz

Horizontal




Vertical




802.11ax (HE40) CH 151 : 5755 MHz

Horizontal




Vertical




802.11ax (HE40) CH 159 : 5795 MHz

Horizontal




Vertical




802.11ax (HE80) CH 155 : 5775 MHz


Horizontal



Vertical





Annex B - Band-Edge Measurement (For U-NII-1, U-NII-2A, U-NII-2C band)





802.11ax (HE20) Channel 36

| Horizontal (Peak) | Horizontal (Average) |
|-------------------|----------------------|
|-------------------|----------------------|





| Vertical (Peak) | Vertical (Average) |
|-----------------|--------------------|
|-----------------|--------------------|





802.11ax (HE20) Channel 64

| Horizontal (Peak) | Horizontal (Average) |
|-------------------|----------------------|
|-------------------|----------------------|




| Vertical (Peak) | Vertical (Average) |
|-----------------|--------------------|
|-----------------|--------------------|




802.11ax (HE20) Channel 100


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE40) Channel 38

| Horizontal (Peak) | Horizontal (Average) |
|-------------------|----------------------|
|-------------------|----------------------|




| Vertical (Peak) | Vertical (Average) |
|-----------------|--------------------|
|-----------------|--------------------|




802.11ax (HE40) Channel 62

| Horizontal (Peak) | Horizontal (Average) |
|-------------------|----------------------|
|-------------------|----------------------|




| Vertical (Peak) | Vertical (Average) |
|-----------------|--------------------|
|-----------------|--------------------|




802.11ax (HE40) Channel 102


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE80) Channel 42

| Horizontal (Peak) | Horizontal (Average) |
|-------------------|----------------------|
|-------------------|----------------------|




| Vertical (Peak) | Vertical (Average) |
|-----------------|--------------------|
|-----------------|--------------------|




802.11ax (HE80) Channel 58

| Horizontal (Peak) | Horizontal (Average) |
|-------------------|----------------------|
|-------------------|----------------------|




| Vertical (Peak) | Vertical (Average) |
|-----------------|--------------------|
|-----------------|--------------------|




802.11ax (HE80) Channel 106


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE160) Channel 50


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)




Vertical (Average)




802.11ax (HE160) Channel 114


Horizontal (Peak)




Horizontal (Average)



Vertical (Peak)



Vertical (Average)



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---