

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 185 : 6875 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	115.9 PK			1.40 H	114	108.9	7.0
2	*6875.00	105.9 AV			1.40 H	114	98.9	7.0
3	#13750.00	42.8 PK	88.2	-45.4	1.61 H	15	27.0	15.8
4	#13750.00	38.1 AV	68.2	-30.1	1.61 H	15	22.3	15.8
5	20625.00	41.1 PK	74.0	-32.9	1.42 H	335	45.9	-4.8
6	20625.00	29.6 AV	54.0	-24.4	1.42 H	335	34.4	-4.8
7	#27500.00	40.7 PK	88.2	-47.5	1.54 H	305	41.9	-1.2
8	#27500.00	39.0 AV	68.2	-29.2	1.54 H	305	40.2	-1.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6875.00	120.4 PK			1.57 V	125	113.4	7.0
2	*6875.00	109.1 AV			1.57 V	125	102.1	7.0
3	#13750.00	41.2 PK	88.2	-47.0	2.56 V	29	25.4	15.8
4	#13750.00	35.7 AV	68.2	-32.5	2.56 V	29	19.9	15.8
5	20625.00	37.3 PK	74.0	-36.7	1.62 V	236	42.1	-4.8
6	20625.00	26.9 AV	54.0	-27.1	1.62 V	236	31.7	-4.8
7	#27500.00	40.9 PK	88.2	-47.3	1.57 V	6	42.1	-1.2
8	#27500.00	35.2 AV	68.2	-33.0	1.57 V	6	36.4	-1.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 213 : 7015 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	115.5 PK			1.46 H	112	107.6	7.9
2	*7015.00	105.4 AV			1.46 H	112	97.5	7.9
3	#14030.00	43.1 PK	88.2	-45.1	1.54 H	22	27.2	15.9
4	#14030.00	38.4 AV	68.2	-29.8	1.54 H	22	22.5	15.9
5	21045.00	41.3 PK	74.0	-32.7	1.50 H	316	45.7	-4.4
6	21045.00	29.7 AV	54.0	-24.3	1.50 H	316	34.1	-4.4
7	#28060.00	40.0 PK	88.2	-48.2	1.51 H	326	41.4	-1.4
8	#28060.00	38.1 AV	68.2	-30.1	1.51 H	326	39.5	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7015.00	120.1 PK			1.54 V	116	112.2	7.9
2	*7015.00	109.2 AV			1.54 V	116	101.3	7.9
3	#14030.00	40.2 PK	88.2	-48.0	2.48 V	7	24.3	15.9
4	#14030.00	34.7 AV	68.2	-33.5	2.48 V	7	18.8	15.9
5	21045.00	38.1 PK	74.0	-35.9	1.73 V	239	42.5	-4.4
6	21045.00	27.5 AV	54.0	-26.5	1.73 V	239	31.9	-4.4
7	#28060.00	40.5 PK	88.2	-47.7	1.52 V	21	41.9	-1.4
8	#28060.00	34.7 AV	68.2	-33.5	1.52 V	21	36.1	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 229 : 7095 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7095.00	115.1 PK			1.64 H	312	109.1	6.0
2	*7095.00	105.2 AV			1.64 H	312	99.2	6.0
3	#7125.00	65.0 PK	88.2	-23.2	1.64 H	312	58.7	6.3
4	#7125.00	53.4 AV	68.2	-14.8	1.64 H	312	47.1	6.3
5	#14190.00	42.6 PK	88.2	-45.6	1.56 H	13	28.2	14.4
6	#14190.00	38.1 AV	68.2	-30.1	1.56 H	13	23.7	14.4
7	21285.00	41.0 PK	74.0	-33.0	1.47 H	308	45.2	-4.2
8	21285.00	29.6 AV	54.0	-24.4	1.47 H	308	33.8	-4.2
9	#28380.00	40.1 PK	88.2	-48.1	1.53 H	319	41.8	-1.7
10	#28380.00	38.0 AV	68.2	-30.2	1.53 H	319	39.7	-1.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7095.00	119.8 PK			1.85 V	115	113.8	6.0
2	*7095.00	108.9 AV			1.85 V	115	102.9	6.0
3	#7125.00	72.1 PK	88.2	-16.1	1.85 V	115	65.8	6.3
4	#7125.00	57.3 AV	68.2	-10.9	1.85 V	115	51.0	6.3
5	#14190.00	40.6 PK	88.2	-47.6	2.42 V	10	26.2	14.4
6	#14190.00	34.8 AV	68.2	-33.4	2.42 V	10	20.4	14.4
7	21285.00	38.3 PK	74.0	-35.7	1.75 V	229	42.5	-4.2
8	21285.00	27.6 AV	54.0	-26.4	1.75 V	229	31.8	-4.2
9	#28380.00	40.5 PK	88.2	-47.7	1.53 V	14	42.2	-1.7
10	#28380.00	34.8 AV	68.2	-33.4	1.53 V	14	36.5	-1.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 233 : 7115 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	91.2 PK			1.54 H	82	83.1	8.1
2	*7115.00	82.0 AV			1.54 H	82	73.9	8.1
3	#7125.00	74.6 PK	88.2	-13.6	1.54 H	82	66.4	8.2
4	#7125.00	66.5 AV	68.2	-1.7	1.54 H	82	58.3	8.2
5	#14230.00	42.5 PK	88.2	-45.7	1.54 H	17	25.4	17.1
6	#14230.00	37.4 AV	68.2	-30.8	1.54 H	17	20.3	17.1
7	21345.00	40.8 PK	74.0	-33.2	1.41 H	326	45.0	-4.2
8	21345.00	29.4 AV	54.0	-24.6	1.41 H	326	33.6	-4.2
9	#28460.00	40.2 PK	88.2	-48.0	1.47 H	312	41.6	-1.4
10	#28460.00	38.4 AV	68.2	-29.8	1.47 H	312	39.8	-1.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7115.00	98.6 PK			2.03 V	222	90.5	8.1
2	*7115.00	86.1 AV			2.03 V	222	78.0	8.1
3	#7125.00	75.6 PK	88.2	-12.6	2.03 V	222	67.4	8.2
4	#7125.00	68.0 AV	68.2	-0.2	2.03 V	222	59.8	8.2
5	#14230.00	41.2 PK	88.2	-47.0	2.50 V	23	24.1	17.1
6	#14230.00	35.6 AV	68.2	-32.6	2.50 V	23	18.5	17.1
7	21345.00	37.5 PK	74.0	-36.5	1.64 V	235	41.7	-4.2
8	21345.00	26.7 AV	54.0	-27.3	1.64 V	235	30.9	-4.2
9	#28460.00	40.7 PK	88.2	-47.5	1.52 V	25	42.1	-1.4
10	#28460.00	35.0 AV	68.2	-33.2	1.52 V	25	36.4	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 35 : 6125 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.6 PK	88.2	-37.6	1.63 H	82	46.9	3.7
2	#5925.00	39.4 AV	68.2	-28.8	1.63 H	82	35.7	3.7
3	*6125.00	114.2 PK			1.63 H	82	109.9	4.3
4	*6125.00	103.0 AV			1.63 H	82	98.7	4.3
5	12250.00	42.2 PK	74.0	-31.8	1.56 H	15	29.0	13.2
6	12250.00	37.2 AV	54.0	-16.8	1.56 H	15	24.0	13.2
7	18375.00	41.0 PK	74.0	-33.0	1.43 H	320	48.2	-7.2
8	18375.00	29.8 AV	54.0	-24.2	1.43 H	320	37.0	-7.2
9	#24500.00	39.9 PK	88.2	-48.3	1.50 H	312	42.0	-2.1
10	#24500.00	37.9 AV	68.2	-30.3	1.50 H	312	40.0	-2.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.9 PK	88.2	-37.3	1.56 V	121	47.2	3.7
2	#5925.00	39.5 AV	68.2	-28.7	1.56 V	121	35.8	3.7
3	*6125.00	117.3 PK			1.56 V	121	113.0	4.3
4	*6125.00	106.4 AV			1.56 V	121	102.1	4.3
5	12250.00	40.7 PK	74.0	-33.3	2.59 V	34	27.5	13.2
6	12250.00	35.0 AV	54.0	-19.0	2.59 V	34	21.8	13.2
7	18375.00	37.7 PK	74.0	-36.3	1.64 V	214	44.9	-7.2
8	18375.00	27.3 AV	54.0	-26.7	1.64 V	214	34.5	-7.2
9	#24500.00	40.5 PK	88.2	-47.7	1.56 V	23	42.6	-2.1
10	#24500.00	35.0 AV	68.2	-33.2	1.56 V	23	37.1	-2.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 59 : 6245 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6245.00	111.3 PK			1.73 H	86	106.6	4.7
2	*6245.00	102.3 AV			1.73 H	86	97.6	4.7
3	12490.00	42.5 PK	74.0	-31.5	1.50 H	34	30.0	12.5
4	12490.00	37.6 AV	54.0	-16.4	1.50 H	34	25.1	12.5
5	18735.00	41.4 PK	74.0	-32.6	1.42 H	311	48.2	-6.8
6	18735.00	29.7 AV	54.0	-24.3	1.42 H	311	36.5	-6.8
7	#24980.00	40.2 PK	88.2	-48.0	1.49 H	307	42.0	-1.8
8	#24980.00	38.1 AV	68.2	-30.1	1.49 H	307	39.9	-1.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6245.00	117.0 PK			1.48 V	135	112.3	4.7
2	*6245.00	106.0 AV			1.48 V	135	101.3	4.7
3	12490.00	41.2 PK	74.0	-32.8	2.53 V	30	28.7	12.5
4	12490.00	35.5 AV	54.0	-18.5	2.53 V	30	23.0	12.5
5	18735.00	37.8 PK	74.0	-36.2	1.63 V	240	44.6	-6.8
6	18735.00	27.2 AV	54.0	-26.8	1.63 V	240	34.0	-6.8
7	#24980.00	40.9 PK	88.2	-47.3	1.46 V	28	42.7	-1.8
8	#24980.00	35.4 AV	68.2	-32.8	1.46 V	28	37.2	-1.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 91 : 6405 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	111.9 PK			1.68 H	89	106.6	5.3
2	*6405.00	103.0 AV			1.68 H	89	97.7	5.3
3	#12810.00	42.6 PK	88.2	-45.6	1.58 H	15	29.1	13.5
4	#12810.00	37.6 AV	68.2	-30.6	1.58 H	15	24.1	13.5
5	19215.00	40.8 PK	74.0	-33.2	1.40 H	336	47.5	-6.7
6	19215.00	29.3 AV	54.0	-24.7	1.40 H	336	36.0	-6.7
7	#25620.00	39.6 PK	88.2	-48.6	1.43 H	308	41.3	-1.7
8	#25620.00	38.0 AV	68.2	-30.2	1.43 H	308	39.7	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6405.00	116.8 PK			1.51 V	146	111.5	5.3
2	*6405.00	106.0 AV			1.51 V	146	100.7	5.3
3	#12810.00	40.5 PK	88.2	-47.7	2.55 V	7	27.0	13.5
4	#12810.00	35.0 AV	68.2	-33.2	2.55 V	7	21.5	13.5
5	19215.00	37.8 PK	74.0	-36.2	1.64 V	240	44.5	-6.7
6	19215.00	27.1 AV	54.0	-26.9	1.64 V	240	33.8	-6.7
7	#25620.00	40.8 PK	88.2	-47.4	1.47 V	18	42.5	-1.7
8	#25620.00	35.0 AV	68.2	-33.2	1.47 V	18	36.7	-1.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 99 : 6445 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	114.2 PK			1.64 H	70	108.7	5.5
2	*6445.00	103.2 AV			1.64 H	70	97.7	5.5
3	#12890.00	42.8 PK	88.2	-45.4	1.56 H	22	29.5	13.3
4	#12890.00	37.8 AV	68.2	-30.4	1.56 H	22	24.5	13.3
5	19335.00	41.0 PK	74.0	-33.0	1.45 H	333	47.8	-6.8
6	19335.00	29.4 AV	54.0	-24.6	1.45 H	333	36.2	-6.8
7	#25780.00	40.2 PK	88.2	-48.0	1.52 H	321	41.6	-1.4
8	#25780.00	38.6 AV	68.2	-29.6	1.52 H	321	40.0	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6445.00	117.0 PK			1.45 V	151	111.5	5.5
2	*6445.00	106.1 AV			1.45 V	151	100.6	5.5
3	#12890.00	41.1 PK	88.2	-47.1	2.60 V	7	27.8	13.3
4	#12890.00	35.7 AV	68.2	-32.5	2.60 V	7	22.4	13.3
5	19335.00	37.7 PK	74.0	-36.3	1.65 V	216	44.5	-6.8
6	19335.00	27.0 AV	54.0	-27.0	1.65 V	216	33.8	-6.8
7	#25780.00	41.4 PK	88.2	-46.8	1.50 V	6	42.8	-1.4
8	#25780.00	35.6 AV	68.2	-32.6	1.50 V	6	37.0	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 107 : 6485 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	111.7 PK			1.64 H	96	105.9	5.8
2	*6485.00	103.0 AV			1.64 H	96	97.2	5.8
3	#12970.00	43.1 PK	88.2	-45.1	1.52 H	15	29.8	13.3
4	#12970.00	37.9 AV	68.2	-30.3	1.52 H	15	24.6	13.3
5	19455.00	41.3 PK	74.0	-32.7	1.40 H	319	47.9	-6.6
6	19455.00	29.7 AV	54.0	-24.3	1.40 H	319	36.3	-6.6
7	#25940.00	40.2 PK	88.2	-48.0	1.48 H	298	42.0	-1.8
8	#25940.00	38.3 AV	68.2	-29.9	1.48 H	298	40.1	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6485.00	117.0 PK			1.43 V	133	111.2	5.8
2	*6485.00	106.1 AV			1.43 V	133	100.3	5.8
3	#12970.00	40.7 PK	88.2	-47.5	2.59 V	23	27.4	13.3
4	#12970.00	35.5 AV	68.2	-32.7	2.59 V	23	22.2	13.3
5	19455.00	37.1 PK	74.0	-36.9	1.64 V	239	43.7	-6.6
6	19455.00	26.7 AV	54.0	-27.3	1.64 V	239	33.3	-6.6
7	#25940.00	40.3 PK	88.2	-47.9	1.49 V	31	42.1	-1.8
8	#25940.00	34.7 AV	68.2	-33.5	1.49 V	31	36.5	-1.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 115 : 6525 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	112.1 PK			1.60 H	109	106.1	6.0
2	*6525.00	103.1 AV			1.60 H	109	97.1	6.0
3	#13050.00	42.4 PK	88.2	-45.8	1.60 H	6	29.1	13.3
4	#13050.00	37.2 AV	68.2	-31.0	1.60 H	6	23.9	13.3
5	19575.00	40.7 PK	74.0	-33.3	1.46 H	332	46.9	-6.2
6	19575.00	29.4 AV	54.0	-24.6	1.46 H	332	35.6	-6.2
7	#26100.00	40.1 PK	88.2	-48.1	1.45 H	315	41.5	-1.4
8	#26100.00	38.1 AV	68.2	-30.1	1.45 H	315	39.5	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6525.00	117.2 PK			1.50 V	150	111.2	6.0
2	*6525.00	106.3 AV			1.50 V	150	100.3	6.0
3	#13050.00	40.5 PK	88.2	-47.7	2.48 V	21	27.2	13.3
4	#13050.00	35.3 AV	68.2	-32.9	2.48 V	21	22.0	13.3
5	19575.00	37.6 PK	74.0	-36.4	1.65 V	231	43.8	-6.2
6	19575.00	27.3 AV	54.0	-26.7	1.65 V	231	33.5	-6.2
7	#26100.00	41.1 PK	88.2	-47.1	1.55 V	21	42.5	-1.4
8	#26100.00	35.5 AV	68.2	-32.7	1.55 V	21	36.9	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 123 : 6565 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	112.1 PK			1.74 H	95	106.0	6.1
2	*6565.00	103.0 AV			1.74 H	95	96.9	6.1
3	#13130.00	42.1 PK	88.2	-46.1	1.56 H	24	28.6	13.5
4	#13130.00	37.3 AV	68.2	-30.9	1.56 H	24	23.8	13.5
5	19695.00	40.3 PK	74.0	-33.7	1.43 H	322	46.3	-6.0
6	19695.00	29.0 AV	54.0	-25.0	1.43 H	322	35.0	-6.0
7	#26260.00	40.2 PK	88.2	-48.0	1.50 H	302	41.6	-1.4
8	#26260.00	38.4 AV	68.2	-29.8	1.50 H	302	39.8	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6565.00	117.0 PK			1.41 V	150	110.9	6.1
2	*6565.00	106.1 AV			1.41 V	150	100.0	6.1
3	#13130.00	40.4 PK	88.2	-47.8	2.52 V	10	26.9	13.5
4	#13130.00	34.8 AV	68.2	-33.4	2.52 V	10	21.3	13.5
5	19695.00	37.4 PK	74.0	-36.6	1.62 V	213	43.4	-6.0
6	19695.00	27.0 AV	54.0	-27.0	1.62 V	213	33.0	-6.0
7	#26260.00	40.3 PK	88.2	-47.9	1.48 V	12	41.7	-1.4
8	#26260.00	34.9 AV	68.2	-33.3	1.48 V	12	36.3	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 155 : 6725 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	111.0 PK			1.71 H	76	104.8	6.2
2	*6725.00	102.3 AV			1.71 H	76	96.1	6.2
3	#13450.00	42.7 PK	88.2	-45.5	1.60 H	11	27.9	14.8
4	#13450.00	37.3 AV	68.2	-30.9	1.60 H	11	22.5	14.8
5	20175.00	41.3 PK	74.0	-32.7	1.37 H	312	46.7	-5.4
6	20175.00	29.7 AV	54.0	-24.3	1.37 H	312	35.1	-5.4
7	#26900.00	40.4 PK	88.2	-47.8	1.45 H	307	41.7	-1.3
8	#26900.00	38.8 AV	68.2	-29.4	1.45 H	307	40.1	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6725.00	116.7 PK			1.37 V	160	110.5	6.2
2	*6725.00	105.9 AV			1.37 V	160	99.7	6.2
3	#13450.00	40.4 PK	88.2	-47.8	2.53 V	21	25.6	14.8
4	#13450.00	34.9 AV	68.2	-33.3	2.53 V	21	20.1	14.8
5	20175.00	37.7 PK	74.0	-36.3	1.70 V	227	43.1	-5.4
6	20175.00	27.3 AV	54.0	-26.7	1.70 V	227	32.7	-5.4
7	#26900.00	40.5 PK	88.2	-47.7	1.56 V	0	41.8	-1.3
8	#26900.00	34.9 AV	68.2	-33.3	1.56 V	0	36.2	-1.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 179 : 6845 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	111.9 PK			1.67 H	97	105.2	6.7
2	*6845.00	102.9 AV			1.67 H	97	96.2	6.7
3	#13690.00	42.9 PK	88.2	-45.3	1.51 H	35	27.4	15.5
4	#13690.00	37.7 AV	68.2	-30.5	1.51 H	35	22.2	15.5
5	20535.00	40.7 PK	74.0	-33.3	1.38 H	313	45.6	-4.9
6	20535.00	29.0 AV	54.0	-25.0	1.38 H	313	33.9	-4.9
7	#27380.00	40.2 PK	88.2	-48.0	1.48 H	309	41.9	-1.7
8	#27380.00	38.6 AV	68.2	-29.6	1.48 H	309	40.3	-1.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6845.00	117.4 PK			1.41 V	140	110.7	6.7
2	*6845.00	106.4 AV			1.41 V	140	99.7	6.7
3	#13690.00	40.8 PK	88.2	-47.4	2.49 V	24	25.3	15.5
4	#13690.00	35.5 AV	68.2	-32.7	2.49 V	24	20.0	15.5
5	20535.00	38.0 PK	74.0	-36.0	1.63 V	227	42.9	-4.9
6	20535.00	27.4 AV	54.0	-26.6	1.63 V	227	32.3	-4.9
7	#27380.00	40.3 PK	88.2	-47.9	1.48 V	21	42.0	-1.7
8	#27380.00	35.0 AV	68.2	-33.2	1.48 V	21	36.7	-1.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 187 : 6885 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	111.9 PK			1.70 H	97	104.8	7.1
2	*6885.00	103.1 AV			1.70 H	97	96.0	7.1
3	#13770.00	41.9 PK	88.2	-46.3	1.50 H	15	26.1	15.8
4	#13770.00	36.9 AV	68.2	-31.3	1.50 H	15	21.1	15.8
5	20655.00	41.1 PK	74.0	-32.9	1.41 H	332	46.0	-4.9
6	20655.00	29.9 AV	54.0	-24.1	1.41 H	332	34.8	-4.9
7	#27540.00	40.0 PK	88.2	-48.2	1.49 H	297	41.3	-1.3
8	#27540.00	38.5 AV	68.2	-29.7	1.49 H	297	39.8	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6885.00	116.4 PK			1.44 V	143	109.3	7.1
2	*6885.00	105.5 AV			1.44 V	143	98.4	7.1
3	#13770.00	40.6 PK	88.2	-47.6	2.52 V	28	24.8	15.8
4	#13770.00	35.2 AV	68.2	-33.0	2.52 V	28	19.4	15.8
5	20655.00	37.1 PK	74.0	-36.9	1.71 V	229	42.0	-4.9
6	20655.00	26.7 AV	54.0	-27.3	1.71 V	229	31.6	-4.9
7	#27540.00	40.6 PK	88.2	-47.6	1.45 V	2	41.9	-1.3
8	#27540.00	34.9 AV	68.2	-33.3	1.45 V	2	36.2	-1.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 211 : 7005 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	111.3 PK			1.69 H	97	103.4	7.9
2	*7005.00	102.6 AV			1.69 H	97	94.7	7.9
3	#14010.00	42.6 PK	88.2	-45.6	1.57 H	14	26.9	15.7
4	#14010.00	37.4 AV	68.2	-30.8	1.57 H	14	21.7	15.7
5	21015.00	40.7 PK	74.0	-33.3	1.39 H	340	45.1	-4.4
6	21015.00	29.3 AV	54.0	-24.7	1.39 H	340	33.7	-4.4
7	#28020.00	39.8 PK	88.2	-48.4	1.47 H	324	41.1	-1.3
8	#28020.00	38.2 AV	68.2	-30.0	1.47 H	324	39.5	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7005.00	117.4 PK			1.40 V	128	109.5	7.9
2	*7005.00	106.4 AV			1.40 V	128	98.5	7.9
3	#14010.00	40.2 PK	88.2	-48.0	2.57 V	11	24.5	15.7
4	#14010.00	34.9 AV	68.2	-33.3	2.57 V	11	19.2	15.7
5	21015.00	38.5 PK	74.0	-35.5	1.70 V	223	42.9	-4.4
6	21015.00	27.6 AV	54.0	-26.4	1.70 V	223	32.0	-4.4
7	#28020.00	40.7 PK	88.2	-47.5	1.53 V	19	42.0	-1.3
8	#28020.00	35.2 AV	68.2	-33.0	1.53 V	19	36.5	-1.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE40)	<b>Channel</b>	CH 227 : 7085 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	111.6 PK			1.69 H	87	103.5	8.1
2	*7085.00	102.7 AV			1.69 H	87	94.6	8.1
3	#7125.00	76.6 PK	88.2	-11.6	1.69 H	87	68.4	8.2
4	#7125.00	66.6 AV	68.2	-1.6	1.69 H	87	58.4	8.2
5	#14170.00	42.2 PK	88.2	-46.0	1.59 H	34	25.4	16.8
6	#14170.00	36.9 AV	68.2	-31.3	1.59 H	34	20.1	16.8
7	21255.00	41.1 PK	74.0	-32.9	1.41 H	341	45.3	-4.2
8	21255.00	29.8 AV	54.0	-24.2	1.41 H	341	34.0	-4.2
9	#28340.00	39.9 PK	88.2	-48.3	1.42 H	311	41.2	-1.3
10	#28340.00	38.3 AV	68.2	-29.9	1.42 H	311	39.6	-1.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7085.00	116.8 PK			1.46 V	137	108.7	8.1
2	*7085.00	106.0 AV			1.46 V	137	97.9	8.1
3	#7140.00	77.8 PK	88.2	-10.4	1.46 V	137	69.4	8.4
4	#7140.00	65.8 AV	68.2	-2.4	1.46 V	137	57.4	8.4
5	#14170.00	40.3 PK	88.2	-47.9	2.57 V	6	23.5	16.8
6	#14170.00	35.1 AV	68.2	-33.1	2.57 V	6	18.3	16.8
7	21255.00	37.9 PK	74.0	-36.1	1.71 V	217	42.1	-4.2
8	21255.00	27.4 AV	54.0	-26.6	1.71 V	217	31.6	-4.2
9	#28340.00	41.0 PK	88.2	-47.2	1.55 V	8	42.3	-1.3
10	#28340.00	35.6 AV	68.2	-32.6	1.55 V	8	36.9	-1.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 39 : 6145 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.6 PK	88.2	-37.6	1.42 H	84	46.9	3.7
2	#5925.00	39.3 AV	68.2	-28.9	1.42 H	84	35.6	3.7
3	*6145.00	112.7 PK			1.42 H	84	108.4	4.3
4	*6145.00	100.5 AV			1.42 H	84	96.2	4.3
5	12290.00	42.8 PK	74.0	-31.2	1.57 H	22	29.5	13.3
6	12290.00	37.7 AV	54.0	-16.3	1.57 H	22	24.4	13.3
7	18435.00	40.3 PK	74.0	-33.7	1.46 H	335	47.5	-7.2
8	18435.00	29.1 AV	54.0	-24.9	1.46 H	335	36.3	-7.2
9	#24580.00	40.2 PK	88.2	-48.0	1.42 H	310	42.1	-1.9
10	#24580.00	38.2 AV	68.2	-30.0	1.42 H	310	40.1	-1.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	51.0 PK	88.2	-37.2	1.49 V	122	47.3	3.7
2	#5925.00	39.5 AV	68.2	-28.7	1.49 V	122	35.8	3.7
3	*6145.00	114.8 PK			1.49 V	122	110.5	4.3
4	*6145.00	103.7 AV			1.49 V	122	99.4	4.3
5	12290.00	39.8 PK	74.0	-34.2	2.57 V	20	26.5	13.3
6	12290.00	34.7 AV	54.0	-19.3	2.57 V	20	21.4	13.3
7	18435.00	38.3 PK	74.0	-35.7	1.62 V	225	45.5	-7.2
8	18435.00	27.5 AV	54.0	-26.5	1.62 V	225	34.7	-7.2
9	#24580.00	41.2 PK	88.2	-47.0	1.51 V	16	43.1	-1.9
10	#24580.00	35.5 AV	68.2	-32.7	1.51 V	16	37.4	-1.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 55 : 6225 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6225.00	110.6 PK			1.46 H	89	106.0	4.6
2	*6225.00	100.2 AV			1.46 H	89	95.6	4.6
3	12450.00	42.4 PK	74.0	-31.6	1.56 H	17	29.7	12.7
4	12450.00	37.1 AV	54.0	-16.9	1.56 H	17	24.4	12.7
5	18675.00	40.7 PK	74.0	-33.3	1.39 H	313	47.6	-6.9
6	18675.00	29.2 AV	54.0	-24.8	1.39 H	313	36.1	-6.9
7	#24900.00	40.1 PK	88.2	-48.1	1.53 H	313	41.9	-1.8
8	#24900.00	38.6 AV	68.2	-29.6	1.53 H	313	40.4	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6225.00	114.9 PK			1.44 V	120	110.3	4.6
2	*6225.00	103.5 AV			1.44 V	120	98.9	4.6
3	12450.00	40.8 PK	74.0	-33.2	2.53 V	5	28.1	12.7
4	12450.00	35.5 AV	54.0	-18.5	2.53 V	5	22.8	12.7
5	18675.00	37.3 PK	74.0	-36.7	1.70 V	213	44.2	-6.9
6	18675.00	26.7 AV	54.0	-27.3	1.70 V	213	33.6	-6.9
7	#24900.00	40.1 PK	88.2	-48.1	1.49 V	17	41.9	-1.8
8	#24900.00	34.8 AV	68.2	-33.4	1.49 V	17	36.6	-1.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 87 : 6385 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	111.1 PK			1.47 H	74	105.9	5.2
2	*6385.00	100.9 AV			1.47 H	74	95.7	5.2
3	#12770.00	42.1 PK	88.2	-46.1	1.51 H	26	28.8	13.3
4	#12770.00	37.2 AV	68.2	-31.0	1.51 H	26	23.9	13.3
5	19155.00	40.6 PK	74.0	-33.4	1.41 H	331	47.3	-6.7
6	19155.00	29.1 AV	54.0	-24.9	1.41 H	331	35.8	-6.7
7	#25540.00	40.1 PK	88.2	-48.1	1.51 H	298	41.8	-1.7
8	#25540.00	38.0 AV	68.2	-30.2	1.51 H	298	39.7	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6385.00	115.1 PK			1.54 V	130	109.9	5.2
2	*6385.00	103.8 AV			1.54 V	130	98.6	5.2
3	#12770.00	40.3 PK	88.2	-47.9	2.57 V	31	27.0	13.3
4	#12770.00	34.8 AV	68.2	-33.4	2.57 V	31	21.5	13.3
5	19155.00	38.2 PK	74.0	-35.8	1.69 V	223	44.9	-6.7
6	19155.00	27.5 AV	54.0	-26.5	1.69 V	223	34.2	-6.7
7	#25540.00	40.6 PK	88.2	-47.6	1.52 V	5	42.3	-1.7
8	#25540.00	35.0 AV	68.2	-33.2	1.52 V	5	36.7	-1.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 103 : 6465 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	110.9 PK			1.47 H	73	105.3	5.6
2	*6465.00	100.7 AV			1.47 H	73	95.1	5.6
3	#12930.00	42.3 PK	88.2	-45.9	1.49 H	34	29.0	13.3
4	#12930.00	37.3 AV	68.2	-30.9	1.49 H	34	24.0	13.3
5	19395.00	41.1 PK	74.0	-32.9	1.38 H	319	47.9	-6.8
6	19395.00	29.5 AV	54.0	-24.5	1.38 H	319	36.3	-6.8
7	#25860.00	39.8 PK	88.2	-48.4	1.48 H	312	41.5	-1.7
8	#25860.00	38.0 AV	68.2	-30.2	1.48 H	312	39.7	-1.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6465.00	115.3 PK			1.46 V	131	109.7	5.6
2	*6465.00	104.0 AV			1.46 V	131	98.4	5.6
3	#12930.00	40.9 PK	88.2	-47.3	2.55 V	26	27.6	13.3
4	#12930.00	35.4 AV	68.2	-32.8	2.55 V	26	22.1	13.3
5	19395.00	37.6 PK	74.0	-36.4	1.65 V	228	44.4	-6.8
6	19395.00	26.8 AV	54.0	-27.2	1.65 V	228	33.6	-6.8
7	#25860.00	40.5 PK	88.2	-47.7	1.55 V	8	42.2	-1.7
8	#25860.00	35.1 AV	68.2	-33.1	1.55 V	8	36.8	-1.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 119 : 6545 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6545.00	110.5 PK			1.52 H	73	104.5	6.0
2	*6545.00	100.2 AV			1.52 H	73	94.2	6.0
3	#13090.00	41.9 PK	88.2	-46.3	1.52 H	25	28.4	13.5
4	#13090.00	37.1 AV	68.2	-31.1	1.52 H	25	23.6	13.5
5	19635.00	41.0 PK	74.0	-33.0	1.43 H	334	47.1	-6.1
6	19635.00	29.5 AV	54.0	-24.5	1.43 H	334	35.6	-6.1
7	#26180.00	39.4 PK	88.2	-48.8	1.54 H	314	40.6	-1.2
8	#26180.00	37.5 AV	68.2	-30.7	1.54 H	314	38.7	-1.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6545.00	114.8 PK			1.48 V	108	108.8	6.0
2	*6545.00	103.4 AV			1.48 V	108	97.4	6.0
3	#13090.00	40.7 PK	88.2	-47.5	2.51 V	4	27.2	13.5
4	#13090.00	35.3 AV	68.2	-32.9	2.51 V	4	21.8	13.5
5	19635.00	37.9 PK	74.0	-36.1	1.68 V	232	44.0	-6.1
6	19635.00	27.3 AV	54.0	-26.7	1.68 V	232	33.4	-6.1
7	#26180.00	40.5 PK	88.2	-47.7	1.50 V	9	41.7	-1.2
8	#26180.00	34.7 AV	68.2	-33.5	1.50 V	9	35.9	-1.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 135 : 6625 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6625.00	110.5 PK			1.49 H	85	104.3	6.2
2	*6625.00	100.3 AV			1.49 H	85	94.1	6.2
3	13250.00	42.4 PK	74.0	-31.6	1.53 H	49	28.1	14.3
4	13250.00	37.2 AV	54.0	-16.8	1.53 H	49	22.9	14.3
5	19875.00	41.7 PK	74.0	-32.3	1.43 H	310	47.8	-6.1
6	19875.00	29.9 AV	54.0	-24.1	1.43 H	310	36.0	-6.1
7	#26500.00	39.0 PK	88.2	-49.2	1.43 H	308	39.8	-0.8
8	#26500.00	37.5 AV	68.2	-30.7	1.43 H	308	38.3	-0.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6625.00	114.6 PK			1.50 V	130	108.4	6.2
2	*6625.00	103.6 AV			1.50 V	130	97.4	6.2
3	13250.00	40.3 PK	74.0	-33.7	2.53 V	17	26.0	14.3
4	13250.00	35.1 AV	54.0	-18.9	2.53 V	17	20.8	14.3
5	19875.00	37.8 PK	74.0	-36.2	1.74 V	238	43.9	-6.1
6	19875.00	27.1 AV	54.0	-26.9	1.74 V	238	33.2	-6.1
7	#26500.00	40.6 PK	88.2	-47.6	1.48 V	10	41.4	-0.8
8	#26500.00	35.0 AV	68.2	-33.2	1.48 V	10	35.8	-0.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 151 : 6705 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6705.00	110.9 PK			1.47 H	88	104.8	6.1
2	*6705.00	100.9 AV			1.47 H	88	94.8	6.1
3	#13410.00	43.1 PK	88.2	-45.1	1.53 H	23	28.3	14.8
4	#13410.00	37.8 AV	68.2	-30.4	1.53 H	23	23.0	14.8
5	20115.00	40.4 PK	74.0	-33.6	1.38 H	326	45.9	-5.5
6	20115.00	29.1 AV	54.0	-24.9	1.38 H	326	34.6	-5.5
7	#26820.00	40.3 PK	88.2	-47.9	1.50 H	297	41.3	-1.0
8	#26820.00	38.3 AV	68.2	-29.9	1.50 H	297	39.3	-1.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6705.00	115.0 PK			1.54 V	135	108.9	6.1
2	*6705.00	103.8 AV			1.54 V	135	97.7	6.1
3	#13410.00	40.5 PK	88.2	-47.7	2.59 V	33	25.7	14.8
4	#13410.00	35.3 AV	68.2	-32.9	2.59 V	33	20.5	14.8
5	20115.00	37.8 PK	74.0	-36.2	1.66 V	240	43.3	-5.5
6	20115.00	27.5 AV	54.0	-26.5	1.66 V	240	33.0	-5.5
7	#26820.00	40.7 PK	88.2	-47.5	1.53 V	30	41.7	-1.0
8	#26820.00	35.3 AV	68.2	-32.9	1.53 V	30	36.3	-1.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 167 : 6785 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6785.00	110.9 PK			1.44 H	82	104.6	6.3
2	*6785.00	100.8 AV			1.44 H	82	94.5	6.3
3	#13570.00	41.8 PK	88.2	-46.4	1.53 H	38	26.9	14.9
4	#13570.00	36.9 AV	68.2	-31.3	1.53 H	38	22.0	14.9
5	20355.00	40.8 PK	74.0	-33.2	1.36 H	323	46.4	-5.6
6	20355.00	29.2 AV	54.0	-24.8	1.36 H	323	34.8	-5.6
7	#27140.00	39.9 PK	88.2	-48.3	1.52 H	297	41.2	-1.3
8	#27140.00	38.2 AV	68.2	-30.0	1.52 H	297	39.5	-1.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6785.00	115.2 PK			1.46 V	136	108.9	6.3
2	*6785.00	104.1 AV			1.46 V	136	97.8	6.3
3	#13570.00	41.2 PK	88.2	-47.0	2.49 V	2	26.3	14.9
4	#13570.00	35.5 AV	68.2	-32.7	2.49 V	2	20.6	14.9
5	20355.00	37.6 PK	74.0	-36.4	1.71 V	240	43.2	-5.6
6	20355.00	26.9 AV	54.0	-27.1	1.71 V	240	32.5	-5.6
7	#27140.00	41.0 PK	88.2	-47.2	1.48 V	8	42.3	-1.3
8	#27140.00	35.6 AV	68.2	-32.6	1.48 V	8	36.9	-1.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 183 : 6865 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6865.00	111.3 PK			1.46 H	97	104.4	6.9
2	*6865.00	101.3 AV			1.46 H	97	94.4	6.9
3	#13730.00	42.8 PK	88.2	-45.4	1.48 H	20	27.1	15.7
4	#13730.00	37.7 AV	68.2	-30.5	1.48 H	20	22.0	15.7
5	20595.00	40.7 PK	74.0	-33.3	1.34 H	306	45.4	-4.7
6	20595.00	29.3 AV	54.0	-24.7	1.34 H	306	34.0	-4.7
7	#27460.00	39.5 PK	88.2	-48.7	1.50 H	319	40.9	-1.4
8	#27460.00	37.7 AV	68.2	-30.5	1.50 H	319	39.1	-1.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6865.00	114.3 PK			1.51 V	113	107.4	6.9
2	*6865.00	103.5 AV			1.51 V	113	96.6	6.9
3	#13730.00	40.8 PK	88.2	-47.4	2.56 V	17	25.1	15.7
4	#13730.00	35.4 AV	68.2	-32.8	2.56 V	17	19.7	15.7
5	20595.00	37.8 PK	74.0	-36.2	1.68 V	239	42.5	-4.7
6	20595.00	27.1 AV	54.0	-26.9	1.68 V	239	31.8	-4.7
7	#27460.00	40.4 PK	88.2	-47.8	1.55 V	11	41.8	-1.4
8	#27460.00	34.9 AV	68.2	-33.3	1.55 V	11	36.3	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 199 : 6945 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6945.00	110.5 PK			1.56 H	91	103.2	7.3
2	*6945.00	100.6 AV			1.56 H	91	93.3	7.3
3	#13890.00	42.4 PK	88.2	-45.8	1.55 H	27	26.6	15.8
4	#13890.00	37.2 AV	68.2	-31.0	1.55 H	27	21.4	15.8
5	20835.00	40.6 PK	74.0	-33.4	1.36 H	334	45.4	-4.8
6	20835.00	29.2 AV	54.0	-24.8	1.36 H	334	34.0	-4.8
7	#27780.00	39.3 PK	88.2	-48.9	1.46 H	314	41.2	-1.9
8	#27780.00	37.7 AV	68.2	-30.5	1.46 H	314	39.6	-1.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6945.00	114.8 PK			1.46 V	109	107.5	7.3
2	*6945.00	103.8 AV			1.46 V	109	96.5	7.3
3	#13890.00	39.9 PK	88.2	-48.3	2.58 V	24	24.1	15.8
4	#13890.00	34.8 AV	68.2	-33.4	2.58 V	24	19.0	15.8
5	20835.00	38.2 PK	74.0	-35.8	1.62 V	233	43.0	-4.8
6	20835.00	27.5 AV	54.0	-26.5	1.62 V	233	32.3	-4.8
7	#27780.00	40.7 PK	88.2	-47.5	1.53 V	10	42.6	-1.9
8	#27780.00	35.0 AV	68.2	-33.2	1.53 V	10	36.9	-1.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE80)	<b>Channel</b>	CH 215 : 7025 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7025.00	110.6 PK			1.50 H	81	102.6	8.0
2	*7025.00	100.4 AV			1.50 H	81	92.4	8.0
3	#7125.00	75.2 PK	88.2	-13.0	1.50 H	81	67.0	8.2
4	#7125.00	62.9 AV	68.2	-5.3	1.50 H	81	54.7	8.2
5	#14050.00	41.7 PK	88.2	-46.5	1.49 H	32	25.6	16.1
6	#14050.00	36.9 AV	68.2	-31.3	1.49 H	32	20.8	16.1
7	21075.00	41.3 PK	74.0	-32.7	1.35 H	319	45.6	-4.3
8	21075.00	29.4 AV	54.0	-24.6	1.35 H	319	33.7	-4.3
9	#28100.00	39.7 PK	88.2	-48.5	1.43 H	312	41.1	-1.4
10	#28100.00	37.9 AV	68.2	-30.3	1.43 H	312	39.3	-1.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*7025.00	114.4 PK			2.12 V	213	106.4	8.0
2	*7025.00	103.8 AV			2.12 V	213	95.8	8.0
3	#7129.50	73.0 PK	88.2	-15.2	2.12 V	213	64.7	8.3
4	#7129.50	63.8 AV	68.2	-4.4	2.12 V	213	55.5	8.3
5	#14050.00	40.0 PK	88.2	-48.2	2.53 V	14	23.9	16.1
6	#14050.00	34.8 AV	68.2	-33.4	2.53 V	14	18.7	16.1
7	21075.00	38.2 PK	74.0	-35.8	1.71 V	235	42.5	-4.3
8	21075.00	27.4 AV	54.0	-26.6	1.71 V	235	31.7	-4.3
9	#28100.00	40.2 PK	88.2	-48.0	1.56 V	28	41.6	-1.4
10	#28100.00	34.7 AV	68.2	-33.5	1.56 V	28	36.1	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE160)	<b>Channel</b>	CH 47 : 6185 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	49.9 PK	88.2	-38.3	1.60 H	88	46.2	3.7
2	#5925.00	39.4 AV	68.2	-28.8	1.60 H	88	35.7	3.7
3	*6185.00	106.9 PK			1.60 H	88	102.4	4.5
4	*6185.00	96.9 AV			1.60 H	88	92.4	4.5
5	12370.00	42.6 PK	74.0	-31.4	1.47 H	23	29.6	13.0
6	12370.00	37.6 AV	54.0	-16.4	1.47 H	23	24.6	13.0
7	18555.00	40.6 PK	74.0	-33.4	1.39 H	329	47.8	-7.2
8	18555.00	29.2 AV	54.0	-24.8	1.39 H	329	36.4	-7.2
9	#24740.00	40.0 PK	88.2	-48.2	1.50 H	318	41.7	-1.7
10	#24740.00	38.5 AV	68.2	-29.7	1.50 H	318	40.2	-1.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	50.7 PK	88.2	-37.5	1.53 V	119	47.0	3.7
2	#5925.00	39.5 AV	68.2	-28.7	1.53 V	119	35.8	3.7
3	*6185.00	109.1 PK			1.53 V	119	104.6	4.5
4	*6185.00	100.0 AV			1.53 V	119	95.5	4.5
5	12370.00	41.0 PK	74.0	-33.0	2.49 V	15	28.0	13.0
6	12370.00	35.4 AV	54.0	-18.6	2.49 V	15	22.4	13.0
7	18555.00	37.8 PK	74.0	-36.2	1.64 V	242	45.0	-7.2
8	18555.00	27.0 AV	54.0	-27.0	1.64 V	242	34.2	-7.2
9	#24740.00	41.1 PK	88.2	-47.1	1.49 V	13	42.8	-1.7
10	#24740.00	35.2 AV	68.2	-33.0	1.49 V	13	36.9	-1.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE160)	<b>Channel</b>	CH 79 : 6345 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6345.00	108.3 PK			1.23 H	69	103.1	5.2
2	*6345.00	96.4 AV			1.23 H	69	91.2	5.2
3	12690.00	42.8 PK	74.0	-31.2	1.46 H	22	30.1	12.7
4	12690.00	37.7 AV	54.0	-16.3	1.46 H	22	25.0	12.7
5	19035.00	40.5 PK	74.0	-33.5	1.42 H	315	47.4	-6.9
6	19035.00	29.2 AV	54.0	-24.8	1.42 H	315	36.1	-6.9
7	#25380.00	39.7 PK	88.2	-48.5	1.54 H	300	41.5	-1.8
8	#25380.00	37.7 AV	68.2	-30.5	1.54 H	300	39.5	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6345.00	109.0 PK			1.54 V	124	103.8	5.2
2	*6345.00	99.9 AV			1.54 V	124	94.7	5.2
3	12690.00	40.5 PK	74.0	-33.5	2.58 V	30	27.8	12.7
4	12690.00	35.2 AV	54.0	-18.8	2.58 V	30	22.5	12.7
5	19035.00	38.1 PK	74.0	-35.9	1.64 V	238	45.0	-6.9
6	19035.00	27.2 AV	54.0	-26.8	1.64 V	238	34.1	-6.9
7	#25380.00	40.7 PK	88.2	-47.5	1.48 V	26	42.5	-1.8
8	#25380.00	35.2 AV	68.2	-33.0	1.48 V	26	37.0	-1.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE160)	<b>Channel</b>	CH 111 : 6505 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6505.00	108.2 PK			1.28 H	70	102.2	6.0
2	*6505.00	96.4 AV			1.28 H	70	90.4	6.0
3	#13010.00	42.7 PK	88.2	-45.5	1.51 H	50	29.4	13.3
4	#13010.00	37.7 AV	68.2	-30.5	1.51 H	50	24.4	13.3
5	19515.00	40.7 PK	74.0	-33.3	1.43 H	322	47.0	-6.3
6	19515.00	29.2 AV	54.0	-24.8	1.43 H	322	35.5	-6.3
7	#26020.00	39.1 PK	88.2	-49.1	1.52 H	322	40.5	-1.4
8	#26020.00	37.6 AV	68.2	-30.6	1.52 H	322	39.0	-1.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6505.00	109.1 PK			1.52 V	118	103.1	6.0
2	*6505.00	100.2 AV			1.52 V	118	94.2	6.0
3	#13010.00	40.1 PK	88.2	-48.1	2.50 V	3	26.8	13.3
4	#13010.00	34.9 AV	68.2	-33.3	2.50 V	3	21.6	13.3
5	19515.00	37.5 PK	74.0	-36.5	1.67 V	223	43.8	-6.3
6	19515.00	26.7 AV	54.0	-27.3	1.67 V	223	33.0	-6.3
7	#26020.00	40.6 PK	88.2	-47.6	1.54 V	31	42.0	-1.4
8	#26020.00	35.2 AV	68.2	-33.0	1.54 V	31	36.6	-1.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE160)	<b>Channel</b>	CH 143 : 6665 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6665.00	108.2 PK			1.31 H	81	102.1	6.1
2	*6665.00	96.6 AV			1.31 H	81	90.5	6.1
3	13330.00	42.0 PK	74.0	-32.0	1.50 H	39	27.2	14.8
4	13330.00	36.9 AV	54.0	-17.1	1.50 H	39	22.1	14.8
5	19995.00	41.3 PK	74.0	-32.7	1.38 H	306	47.0	-5.7
6	19995.00	29.9 AV	54.0	-24.1	1.38 H	306	35.6	-5.7
7	#26660.00	40.0 PK	88.2	-48.2	1.48 H	306	40.6	-0.6
8	#26660.00	38.1 AV	68.2	-30.1	1.48 H	306	38.7	-0.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6665.00	109.9 PK			1.51 V	131	103.8	6.1
2	*6665.00	100.5 AV			1.51 V	131	94.4	6.1
3	13330.00	40.9 PK	74.0	-33.1	2.58 V	12	26.1	14.8
4	13330.00	35.3 AV	54.0	-18.7	2.58 V	12	20.5	14.8
5	19995.00	37.6 PK	74.0	-36.4	1.67 V	241	43.3	-5.7
6	19995.00	27.0 AV	54.0	-27.0	1.67 V	241	32.7	-5.7
7	#26660.00	40.4 PK	88.2	-47.8	1.55 V	20	41.0	-0.6
8	#26660.00	34.7 AV	68.2	-33.5	1.55 V	20	35.3	-0.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE160)	<b>Channel</b>	CH 175 : 6825 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6825.00	108.7 PK			1.23 H	72	102.2	6.5
2	*6825.00	96.9 AV			1.23 H	72	90.4	6.5
3	#13650.00	42.7 PK	88.2	-45.5	1.44 H	22	27.4	15.3
4	#13650.00	37.4 AV	68.2	-30.8	1.44 H	22	22.1	15.3
5	20475.00	41.4 PK	74.0	-32.6	1.44 H	314	46.5	-5.1
6	20475.00	30.0 AV	54.0	-24.0	1.44 H	314	35.1	-5.1
7	#27300.00	39.4 PK	88.2	-48.8	1.49 H	298	41.2	-1.8
8	#27300.00	37.6 AV	68.2	-30.6	1.49 H	298	39.4	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6825.00	108.9 PK			1.48 V	126	102.4	6.5
2	*6825.00	99.5 AV			1.48 V	126	93.0	6.5
3	#13650.00	40.4 PK	88.2	-47.8	2.55 V	4	25.1	15.3
4	#13650.00	35.1 AV	68.2	-33.1	2.55 V	4	19.8	15.3
5	20475.00	38.1 PK	74.0	-35.9	1.68 V	220	43.2	-5.1
6	20475.00	27.5 AV	54.0	-26.5	1.68 V	220	32.6	-5.1
7	#27300.00	41.1 PK	88.2	-47.1	1.53 V	1	42.9	-1.8
8	#27300.00	35.5 AV	68.2	-32.7	1.53 V	1	37.3	-1.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	TX 802.11ax (HE160)	<b>Channel</b>	CH 207 : 6985 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6985.00	108.6 PK			1.29 H	79	100.9	7.7
2	*6985.00	96.7 AV			1.29 H	79	89.0	7.7
3	#7125.00	75.6 PK	88.2	-12.6	1.29 H	79	67.4	8.2
4	#7125.00	63.8 AV	68.2	-4.4	1.29 H	79	55.6	8.2
5	#13970.00	42.4 PK	88.2	-45.8	1.47 H	21	26.6	15.8
6	#13970.00	37.6 AV	68.2	-30.6	1.47 H	21	21.8	15.8
7	20955.00	41.3 PK	74.0	-32.7	1.37 H	333	45.8	-4.5
8	20955.00	29.7 AV	54.0	-24.3	1.37 H	333	34.2	-4.5
9	#27940.00	40.0 PK	88.2	-48.2	1.42 H	301	41.2	-1.2
10	#27940.00	38.0 AV	68.2	-30.2	1.42 H	301	39.2	-1.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6985.00	111.5 PK			2.22 V	213	103.8	7.7
2	*6985.00	100.6 AV			2.22 V	213	92.9	7.7
3	#7129.20	77.4 PK	88.2	-10.8	2.22 V	213	69.1	8.3
4	<b>#7129.20</b>	<b>68.1 AV</b>	<b>68.2</b>	<b>-0.1</b>	<b>2.22 V</b>	<b>213</b>	<b>59.8</b>	<b>8.3</b>
5	#13970.00	40.6 PK	88.2	-47.6	2.55 V	16	24.8	15.8
6	#13970.00	34.9 AV	68.2	-33.3	2.55 V	16	19.1	15.8
7	20955.00	37.6 PK	74.0	-36.4	1.73 V	215	42.1	-4.5
8	20955.00	27.2 AV	54.0	-26.8	1.73 V	215	31.7	-4.5
9	#27940.00	40.9 PK	88.2	-47.3	1.48 V	24	42.1	-1.2
10	#27940.00	35.1 AV	68.2	-33.1	1.48 V	24	36.3	-1.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

## 4.1.7 Test Results (Mode 2)

## Above 1GHz Data:

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 33 : 6115 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	51.3 PK	88.2	-36.9	1.53 H	117	47.6	3.7
2	#5925.00	38.7 AV	68.2	-29.5	1.53 H	117	35.0	3.7
3	*6115.00	113.5 PK			1.53 H	117	109.2	4.3
4	*6115.00	101.8 AV			1.53 H	117	97.5	4.3
5	12230.00	42.5 PK	74.0	-31.5	1.53 H	21	29.4	13.1
6	12230.00	37.4 AV	54.0	-16.6	1.53 H	21	24.3	13.1
7	18345.00	40.5 PK	74.0	-33.5	1.46 H	324	47.7	-7.2
8	18345.00	29.2 AV	54.0	-24.8	1.46 H	324	36.4	-7.2
9	#24460.00	40.0 PK	88.2	-48.2	1.43 H	303	42.1	-2.1
10	#24460.00	37.9 AV	68.2	-30.3	1.43 H	303	40.0	-2.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5925.00	51.7 PK	88.2	-36.5	1.51 V	121	48.0	3.7
2	#5925.00	38.8 AV	68.2	-29.4	1.51 V	121	35.1	3.7
3	*6115.00	116.2 PK			1.51 V	121	111.9	4.3
4	*6115.00	104.5 AV			1.51 V	121	100.2	4.3
5	12230.00	46.1 PK	74.0	-27.9	2.58 V	0	33.0	13.1
6	12230.00	40.5 AV	54.0	-13.5	2.58 V	0	27.4	13.1
7	18345.00	37.1 PK	74.0	-36.9	1.71 V	227	44.3	-7.2
8	18345.00	26.8 AV	54.0	-27.2	1.71 V	227	34.0	-7.2
9	#24460.00	40.8 PK	88.2	-47.4	1.53 V	28	42.9	-2.1
10	#24460.00	35.1 AV	68.2	-33.1	1.53 V	28	37.2	-2.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 61 : 6255 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6255.00	113.9 PK			1.49 H	126	109.2	4.7
2	*6255.00	102.3 AV			1.49 H	126	97.6	4.7
3	12510.00	42.6 PK	74.0	-31.4	1.59 H	6	30.2	12.4
4	12510.00	37.7 AV	54.0	-16.3	1.59 H	6	25.3	12.4
5	18765.00	40.9 PK	74.0	-33.1	1.42 H	321	47.7	-6.8
6	18765.00	29.6 AV	54.0	-24.4	1.42 H	321	36.4	-6.8
7	#25020.00	39.6 PK	88.2	-48.6	1.51 H	303	41.4	-1.8
8	#25020.00	38.0 AV	68.2	-30.2	1.51 H	303	39.8	-1.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6255.00	116.0 PK			1.56 V	108	111.3	4.7
2	*6255.00	104.2 AV			1.56 V	108	99.5	4.7
3	12510.00	45.7 PK	74.0	-28.3	2.63 V	1	33.3	12.4
4	12510.00	40.0 AV	54.0	-14.0	2.63 V	1	27.6	12.4
5	18765.00	36.9 PK	74.0	-37.1	1.76 V	228	43.7	-6.8
6	18765.00	26.8 AV	54.0	-27.2	1.76 V	228	33.6	-6.8
7	#25020.00	39.9 PK	88.2	-48.3	1.56 V	10	41.7	-1.8
8	#25020.00	34.4 AV	68.2	-33.8	1.56 V	10	36.2	-1.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	TX 802.11ax (HE20)	<b>Channel</b>	CH 93 : 6415 MHz
<b>Frequency Range</b>	1GHz ~ 40GHz	<b>Detector Function</b>	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6415.00	112.9 PK			1.58 H	121	107.6	5.3
2	*6415.00	101.3 AV			1.58 H	121	96.0	5.3
3	#12830.00	42.6 PK	88.2	-45.6	1.51 H	26	29.2	13.4
4	#12830.00	37.5 AV	68.2	-30.7	1.51 H	26	24.1	13.4
5	19245.00	40.7 PK	74.0	-33.3	1.45 H	317	47.4	-6.7
6	19245.00	29.6 AV	54.0	-24.4	1.45 H	317	36.3	-6.7
7	#25660.00	40.3 PK	88.2	-47.9	1.43 H	306	41.9	-1.6
8	#25660.00	38.4 AV	68.2	-29.8	1.43 H	306	40.0	-1.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*6415.00	116.0 PK			1.51 V	122	110.7	5.3
2	*6415.00	104.6 AV			1.51 V	122	99.3	5.3
3	#12830.00	45.9 PK	88.2	-42.3	2.53 V	0	32.5	13.4
4	#12830.00	39.9 AV	68.2	-28.3	2.53 V	0	26.5	13.4
5	19245.00	37.1 PK	74.0	-36.9	1.76 V	233	43.8	-6.7
6	19245.00	26.6 AV	54.0	-27.4	1.76 V	233	33.3	-6.7
7	#25660.00	40.2 PK	88.2	-48.0	1.52 V	15	41.8	-1.6
8	#25660.00	34.5 AV	68.2	-33.7	1.52 V	15	36.1	-1.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.