

RF EXPOSURE EVALUATION REPORT

FCC ID : PY321100542
Equipment : Netgear 5G MHS Travel Router
Brand Name : Netgear
Model Name : MR6110
Applicant : Netgear Inc.
350 E. Plumeria Drive, San
Jose, CA 95134, United States
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 1.1310, 1.1307 and Part 2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full



Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	5
3. RF EXPOSURE LIMIT INTRODUCTION	6
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	7
4.1. External Antenna Gain.....	7
4.2. Sim-Tx analysis	8



History of this test report

Report No.	Version	Description	Issued Date
FA190614-01E	Rev. 01	Initial issue of report	Mar. 24, 2022



1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Netgear 5G MHS Travel Router
Brand Name	Netgear
Model Name	MR6110
FCC ID	PY321100542
Wireless Technology and Frequency Range	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 30: 2305 MHz ~ 2315 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 1710 MHz ~ 1780 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n12 : 699 MHz ~ 716 MHz 5G NR n14 : 788 MHz ~ 798 MHz 5G NR n30 : 2305 MHz ~ 2315 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n77: 3700 MHz ~ 3980 MHz, 3450MHz ~ 3550MHz WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz
Mode	LTE: QPSK, 16QAM, 64QAM, 256QAM 5G FR1: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160
EUT Stage	Identical Prototype

Reviewed by: Jason Wang

Report Producer: Carlie Tsai



2. Maximum RF average output power among production units

Radio Tech	Band Number	Antenna name	Maximum Transmit Power Level (dBm)
LTE	B2	ANT1	23.5
LTE	B4	ANT2	24
LTE	B5	ANT1	24
LTE	B12	ANT1	24
LTE	B14	ANT1	24
LTE	B66	ANT1	24
LTE	B2	ANT2	24
LTE	B7	ANT2	23.5
LTE	B30	ANT2	23
LTE	B66	ANT2	24
LTE	B48	ANT1	23
5G FR1	N2	ANT1	23.5
5G FR1	N5	ANT1	24
5G FR1	N12	ANT1	24
5G FR1	N14	ANT1	24
5G FR1	N66	ANT1	24
5G FR1	N77	ANT1	22.3
5G FR1	N2	ANT2	24
5G FR1	N5	ANT2	24
5G FR1	N30	ANT2	23
5G FR1	N66	ANT2	24
5G FR1	N77	ANT2	22.2
5G FR1	N77	ANT5	21.5
5G FR1	N77	ANT6	20.5

Mode		Maximum Average Power (dBm)	
		Ant 3	Ant 4
WLAN	2.4GHz WLAN	10	10
	5GHz WLAN	10	10



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



4. Radio Frequency Radiation Exposure Evaluation

4.1. External Antenna Gain

Band	Transmit Antenna	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
LTE Band 2	1	4.00	23.50	27.50	0.56	562.34	0.112	1.000	0.112
LTE Band 5	1	4.00	24.00	28.00	0.63	630.96	0.126	0.549	0.229
LTE Band 12	1	4.00	24.00	28.00	0.63	630.96	0.126	0.466	0.270
LTE Band 14	1	4.00	24.00	28.00	0.63	630.96	0.126	0.525	0.239
LTE Band 48	1	0.17	23.00	23.17	0.21	207.49	0.041	1.000	0.041
LTE Band 66	1	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
LTE Band 2	2	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
LTE Band 4	2	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
LTE Band 7	2	4.00	23.50	27.50	0.56	562.34	0.112	1.000	0.112
LTE Band 30	2	1.05	23.00	24.05	0.25	254.10	0.051	1.000	0.051
LTE Band 66	2	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
n2	1	4.00	23.50	27.50	0.56	562.34	0.112	1.000	0.112
n5	1	4.00	24.00	28.00	0.63	630.96	0.126	0.549	0.229
n12	1	4.00	24.00	28.00	0.63	630.96	0.126	0.466	0.270
n14	1	4.00	24.00	28.00	0.63	630.96	0.126	0.525	0.239
n66	1	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
n77	1	6.00	22.30	28.30	0.68	676.08	0.135	1.000	0.135
n2	2	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
n5	2	4.00	24.00	28.00	0.63	630.96	0.126	0.549	0.229
n30	2	1.05	23.00	24.05	0.25	254.10	0.051	1.000	0.051
n66	2	4.00	24.00	28.00	0.63	630.96	0.126	1.000	0.126
n77	2	6.00	22.20	28.20	0.66	660.69	0.132	1.000	0.132
n77(SRS)	5	6.00	21.50	27.50	0.56	562.34	0.112	1.000	0.112
n77(SRS)	6	6.00	20.50	26.50	0.45	446.68	0.089	1.000	0.089
2.4GHz WLAN	3	2.63	10.00	12.63	0.02	18.32	0.004	1.000	0.004
2.4GHz WLAN	4	2.15	10.00	12.15	0.02	16.41	0.003	1.000	0.003
5GHz WLAN	3	3.40	10.00	13.40	0.02	21.88	0.004	1.000	0.004
5GHz WLAN	4	2.59	10.00	12.59	0.02	18.16	0.004	1.000	0.004



4.2. Sim-Tx analysis

Exposure condition	NO.	Simultaneous Transmission Configurations	Support
Body condition	1	WWAN + 2.4GHz Ant3 + 2.4GHz Ant4	V
	2	WWAN + 5GHz Ant3 + 5GHz Ant4	V
	3	WWAN + 2.4GHz Ant3 + 5GHz Ant4	V
	4	WWAN + 2.4GHz Ant4 + 5GHz Ant3	V
	5	LTE + FR1 + 2.4GHz Ant3 + 2.4GHz Ant4	V
	6	LTE + FR1+ 5GHz Ant3 + 5GHz Ant4	V
	7	LTE + FR1+ 2.4GHz Ant3 + 5GHz Ant4	V
	8	LTE + FR1+ 2.4GHz Ant4 + 5GHz Ant3	V
	9	2.4GHz Ant3 (client) + 5GHz Ant4(AP)	V
	10	5GHz Ant3 (Client) + 2.4GHz Ant4 (AP)	V

Maximum WWAN Power Density / Limit	Maximum WLAN Ant3 Power Density / Limit	Maximum WLAN Ant4 Power Density / Limit	Σ (Power Density / Limit) of LTE + WLAN Ant3 + WLAN Ant4
0.270	0.004	0.004	0.278

Note:

1. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)].
2. In simultaneous transmission for this device, 5G NR and LTE transmission are managed and controlled by Qualcomm® Smart Transmit, while the RF exposure from WLAN radios is managed using legacy approach, therefore simultaneous transmission compliance can be assessed on LTE + WLAN Ant 3 + WLAN Ant 4 or NR + WLAN Ant 3 + WLAN Ant 4.
3. Considering all of the EIRP performance listed in the table above was consider wrost antenna combination for WWAN + WLAN Ant 3 + WLAN Ant 4, the aggregated (power density /limit) is smaller than 1.

Conclusion:

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.