

System Check_Head_2600MHz

DUT: D2600V2-1008

Communication System: CW; Frequency: 2600.0 MHz; Duty Cycle: 1:1

Medium: HSL_2600_230119 Medium parameters used: $f = 2600.0$ MHz; $\sigma = 1.98$ S/m; $\epsilon_r = 38.1$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

DASY6 Configuration:

- Probe: EX3DV4 - SN7306; ConvF(7.44, 7.44, 7.44); Calibrated: 2022-07-28
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1311; Calibrated: 2022-08-25
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2055; Section: Flat
- Measurement Software: 16.2.2.1588
- UID: CW, 0--

Pin=17.0dBm/Area Scan (40.0 mm x 96.0 mm): Measurement Grid: 10.0 mm x 12.0 mm

SAR (1g) = 2.64 W/kg; SAR (10g) = 1.19 W/kg;

Pin=17.0dBm/Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm

Power Drift = 0.04 dB

SAR (1g) = 2.69 W/kg; SAR (8g) = 1.35 W/kg; SAR (10g) = 1.21 W/kg

