

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBBQZ-WTW-P23120041

FCC ID: PY323300611

Product: NIGHTHAWK BE9300 WiFi 7 Router, NIGHTHAWK BE9200 WiFi 7 Router,
NIGHTHAWK BE9100 WiFi 7 Router

Brand: NETGEAR

Model No.: RS300

Series Model: RS280, RS270

Received Date: 2023/12/4

Test Date: 2024/2/2

Issued Date: 2024/2/16

Applicant: NETGEAR, INC.

Address: 350 East Plumeria Drive San Jose CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration /

Designation Number: 788550 / TW0003

Approved by: _____

Jeremy Lin

, Date: _____

2024/2/16

Jeremy Lin / Project Engineer

This test report consists of 13 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Pettie Chen / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

| | | |
|---|---|----|
| 1 | Release Control Record | 3 |
| 2 | Certificate..... | 4 |
| 3 | Measurement Uncertainty | 5 |
| 4 | Test Instruments | 5 |
| 5 | Applicable RF Exposure Limit | 6 |
| 6 | Test Results | 10 |
| 7 | Conclusion..... | 12 |
| 8 | Information of the Testing Laboratories | 13 |

1 Release Control Record

| Issue No. | Description | Date Issued |
|----------------------|-------------------|-------------|
| MFBBQZ-WTW-P23120041 | Original release. | 2024/2/16 |

2 Certificate

Product: NIGHTHAWK BE9300 WiFi 7 Router, NIGHTHAWK BE9200 WiFi 7 Router,
NIGHTHAWK BE9100 WiFi 7 Router (refer to item 3.1 for more details)

Brand: NETGEAR

Test Model: RS300

Series Model: RS280, RS270

Sample Status: Engineering sample

Applicant: NETGEAR, INC.

Test Date: 2024/2/2

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

3 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

| Measurement | Specification | Expanded Uncertainty (k=2) (±) |
|-------------|-----------------|-----------------------------------|
| RF Exposure | 2.5 GHz ~ 8 GHz | 1.3 dB |

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

Routine Evaluation

Routine Evaluation Procedure - Single and/or Multiple RF Sources

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|-------------------------------|-----------|------------|--------------------|---------------------|
| EM Field Meter Wavecontrol | SMP2 Dual | 22SN1913 | 2023/7/6 | 2024/7/5 |
| Probe Wavecontrol | WPF60 | 22SN1914 | 2023/5/15 | 2024/5/14 |

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/2/2

5 Applicable RF Exposure Limit

§ 1.1310 Radiofrequency radiation exposure limits.

(a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).

(b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

(c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

(e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

➤ Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | (100)* | <30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | <30 |
| 30-300 | 27.5 | 0.073 | 0.2 | <30 |
| 300-1,500 | ... | ... | f/1500 | <30 |
| 1,500-100,000 | ... | ... | 1.0 | <30 |

f = frequency in MHz. * = Plane-wave equivalent power density.

➤ Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| Limits For General Population / Uncontrolled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | ≤6 |
| 3.0-30 | 1842/f | 4.89/f | *(900/f ²) | <6 |
| 30-300 | 61.4 | 0.163 | 1.0 | <6 |
| 300-1,500 | | | f/300 | <6 |
| 1,500-100,000 | | | 5 | <6 |

f = frequency in MHz. * = Plane-wave equivalent power density.

MPE-based Exemption – §1.1307(b)(3)(i)(C)

- The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.
- Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

| RF Source frequency (MHz) | Minimum Distance | | Threshold ERP (watts) |
|---------------------------|--------------------|--------------------|-----------------------|
| | $\lambda_L / 2\pi$ | $\lambda_H / 2\pi$ | |
| 0.3-1.34 | 159 m–35.6 m | | $1,920 R^2$. |
| 1.34-30 | 35.6 m–1.6 m | | $3,450 R^2/f^2$. |
| 30-300 | 1.6 m–159 mm | | $3.83 R^2$. |
| 300-1,500 | 159 mm–31.8 mm | | $0.0128 R^{2f}$. |
| 1,500-100,000 | 31.8 mm–0.5 mm | | $19.2 R^2$. |

R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.

MPE-based Exemption – §1.1307(b)(3)(i)(B)

- For mobile devices that are not exempt per Table 1 of §1.1307(b)(1)(i)(C) and device at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

Routine Evaluation


Routine Evaluation Procedure - Single and/or Multiple RF Sources

- MPE compliance are measurement in all directions surrounding the antenna and radiating structures of the device.

For non-directional antennas, MPE evaluation points shall be along radials extending from the antenna (axis) that are no more than 30° apart. The direction of maximum exposure shall be aligned with one of the radials.

For each specific exposure condition, the evaluation points along the longest dimension (e.g., vertical) shall use a spatial resolution of 10 cm or less, and shall extend at least 10 cm beyond the exposed portions of a person's body or until the evaluated results are less than 10% of the MPE limit. For exposures occurring next to the ground or next to a ground plane, the evaluation points shall be no closer than 10 cm from the ground.

Test Setup



Note: The measurement antenna are moving and surrounding the EUT when performed the test, the test results recorded the highest values for each sides of the EUT (left/right/top/bottom/z-axis)

Fixed RF sources operating in the same time-averaging period – §1.1307(b)(3)(ii)(B)

- Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for P_{th} , including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_{th,i}$ = the exemption threshold power (P_{th}) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source i .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Exposure Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from [§ 1.1310 of this chapter](#).

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

6 Test Results

| | | | |
|---------------------------|--------------|------------|--------------|
| Environmental Conditions: | 25°C, 60% RH | Tested By: | Jisyong Wang |
|---------------------------|--------------|------------|--------------|

For Single RF Source

| MPE-based Exemption §1.1307(b)(3)(i)(C) | | | | | |
|---|----------------------|------------------|---------------|----------------------|-------------|
| Operation Mode | Frequency Band (MHz) | Maximum ERP (mW) | Distance (cm) | Limit Threshold (mW) | Test Result |
| WLAN 6 GHz_CDD | 6115-7115 | 567.545 | 20 | 768 | Pass |

Notes:

- Calculate the ERP of WLAN 6 GHz_CDD from the radiated field strength:
 $ERP \text{ (dBm)} = \text{Radiated field strength (dBuV/m)} + 20 \times \text{Log}(d) - 104.77 - 2.15$
 d is the measurement distance, in 3 m.
 $ERP = 124.92 + 20 \times \text{Log}(3) - 104.77 - 2.15 = 27.54 \text{ dBm (567.545 mW)}$

| MPE-based Exemption §1.1307(b)(3)(i)(B) | | | | | | | |
|---|----------------------|--------------------|--------------------|------------------|---------------|----------------------|-------------|
| Operation Mode | Frequency Band (MHz) | Average Power (mW) | Antenna Gain (dBi) | Maximum ERP (mW) | Distance (cm) | Limit Threshold (mW) | Test Result |
| WLAN 2.4 GHz_CDD | 2412-2462 | 848.465 | 1.98 | 815.894 | 20 | 3060 | Pass |
| WLAN 2.4 GHz_BF | 2412-2462 | 845.481 | 4.68 | 1513.923 | 20 | 3060 | Pass |
| WLAN 5 GHz_CDD | 5180-5825 | 845.346 | 2.98 | 1023.374 | 20 | 3060 | Pass |
| WLAN 5.9 GHz_CDD | 5815-5885 | - | - | 909.913 | 20 | 3060 | Pass |
| WLAN 5.9 GHz_BF | 5815-5885 | - | - | 1584.893 | 20 | 3060 | Pass |

Notes:

- Calculate the ERP of WLAN 5.9 GHz_CDD from the radiated field strength:
 $ERP \text{ (dBm)} = \text{Radiated field strength (dBuV/m)} + 20 \times \text{Log}(d) - 104.77 - 2.15$
 d is the measurement distance, in 3 m.
 $ERP = 126.97 + 20 \times \text{Log}(3) - 104.77 - 2.15 = 29.59 \text{ dBm (909.913 mW)}$
- Calculate the ERP of WLAN 5.9 GHz_BF from the radiated field strength:
 $ERP \text{ (dBm)} = \text{Radiated field strength (dBuV/m)} + 20 \times \text{Log}(d) - 104.77 - 2.15$
 d is the measurement distance, in 3 m.
 $ERP = 129.38 + 20 \times \text{Log}(3) - 104.77 - 2.15 = 32 \text{ dBm (1584.893 mW)}$

| Routine Evaluation (General Population) | | | | | |
|---|----------------------|-------------------------------------|--------------------|-----------------------------|-------------|
| Operation Mode | Frequency Band (MHz) | Power Density (mW/cm ²) | Test Distance (cm) | Limit (mW/cm ²) | Test Result |
| WLAN 5 GHz_BF | 5180-5825 | 0.035 | 20 | 1 | Pass |
| WLAN 6 GHz_BF | 6115-7115 | 0.035 | 20 | 1 | Pass |

For Multiple RF Sources (Simultaneous Operations)

| Multiple RF Sources (Simultaneous Operations) | | | | | | | |
|---|----------------------|-------------------------------------|-----------------------------|-------|---------------|-----------------|-------------|
| Exemption Evaluation | | | | | Sum of Ratios | Limit of Ratios | Test Result |
| Operation Mode | Frequency Band (MHz) | Maximum ERP (mW) | Limit Threshold (mW) | Ratio | | | |
| WLAN 2.4 GHz_BF | 2412-2462 | 1513.923 | 3060 | 0.495 | 0.565 | 1 | Pass |
| Routine Evaluation (General Population) | | | | | | | |
| Operation Mode | Operation Mode | Power Density (mW/cm ²) | Limit (mW/cm ²) | Ratio | | | |
| WLAN 5 GHz_BF | 5180-5825 | 0.035 | 1 | 0.035 | | | |
| WLAN 6 GHz_BF | 6115-7115 | 0.035 | 1 | 0.035 | | | |

7 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

8 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---