

## RF Exposure Report

**Report No.:** SA141008E07D

**FCC ID:** PY3DC112A

**Test Model:** DC112A

**Received Date:** Oct. 19, 2016

**Test Date:** Nov. 24, 2016

**Issued Date:** Dec. 02, 2016

**Applicant:** NETGEAR, Inc.

**Address:** 350 East Plumeria Drive San Jose, CA 95134

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits For Maximum Permissible Exposure (MPE) .....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
2.4 Antenna Gain .....	5
2.5 Calculation Result .....	6

### Release Control Record

Issue No.	Description	Date Issued
SA141008E07D	Original release.	Dec. 02, 2016



## 2 RF Exposure

### 2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

This product could be applied with 2G USB cellular device, and the safe distance is 48cm for collocated radio.

### 2.4 Antenna Gain

Antenna NO.	PCB Chain NO.	Brand	Model No.	Ant. Gain(dBi) <Excluding cable loss>	Frequency range (MHz to MHz)	Ant. Type	Connector Type	Cable Loss(dB)		
1	Chain 0	Master Wave	98619PRSX006	2.48	2400~2500	Dipole	R-SMA	1		
				2.96	5150~5850			1.9		
2	Chain 1	Master Wave	98619PRSX006	2.48	2400~2500			PCB	i-pex	0.7
				2.96	5150~5850					1.5
3	WWAN_chain_0	Master Wav	9 8P2RZIPF000	2.5	703~960	PCB	i-pex	NA		
				4.4	1700~ 2170					
				4.5	2300~ 2700					
4	WWAN_chain_1	Master Wav	9 8P2RZIPF000	2.5	703~960	PCB	i-pex	NA		
				4.4	1700~ 2170					
				4.5	2300~ 2700					

## 2.5 Calculation Result

### For WLAN:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	996.75	4.64	20	0.57719	1
5180-5240	498.389	4.27	20	0.26503	1
5745-5825	791.595	4.27	20	0.42095	1

### NOTE:

2.4GHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.64\text{dBi}$

5.0GHz: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.27\text{dBi}$

### For WLAN / 2G device coexistence mode:

Condition	Coexistence		
1	WLAN (2.4GHz)	WLAN (5GHz)	-
2	WLAN (2.4GHz)	WLAN (5GHz)	2G (USB cellular device)

#### Condition 1

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	996.75	4.64	20	0.57719	1
5745-5825	791.595	4.27	20	0.42095	1

#### Condition 2

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	996.75	4.64	48	0.10021	1
5745-5825	791.595	4.27	48	0.07308	1
824-849	11480*	-	48	0.39650	0.5495

\* This product can operate with plug-in USB cellular device which has maximum of 7W(ERP) output power.

ERP is then converted to EIRP as follows:

Formula :  $EIRP(W) = 1.64 \times ERP(W)$

$$EIRP = 1.64 \times 7 \text{ W} = 11.48 \text{ W} = 11480\text{mW}$$

**Conclusion:**

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

**Condition 1:**

Therefore, the worst-case situation is  $0.57719 / 1 + 0.42095 / 1 = 0.99814$ ,  
which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

**Condition 2:**

Therefore, the worst-case situation is  $0.10021 / 1 + 0.07308 / 1 + 0.39650 / 0.5495 = 0.89491$ ,  
which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---