# **FCC RF Test Report**

APPLICANT : Sony Mobile Communications Inc.

EQUIPMENT : GSM/WCDMA/LTE Phone+Bluetooth,

DTS/UNII a/b/g/n and NFC

BRAND NAME : Sony

FCC ID : PY7-02885J

STANDARD : 47 CFR Part 2, 22(H), 24(E), 27

**CLASSIFICATION**: PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Apr. 28, 2017 and completely tested on May 25, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

#### SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 1 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report No.: FG742206-01B

Report Template No.: BU5-FGLTE Version 1.6

## **TABLE OF CONTENTS**

RE'	VISIOI	N HISTORY	3
SU	MMAR	Y OF TEST RESULT	4
1	GENE	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Product Feature of Equipment Under Test	5
	1.4	Modification of EUT	5
	1.5	Emission Designator	6
	1.6	Testing Location	
	1.7	Applicable Standards	
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	
	2.2	Connection Diagram of Test System	
	2.3	Support Unit used in test configuration and system	
	2.4	Measurement Results Explanation Example	
	2.5	Frequency List of Low/Middle/High Channels	
3	CONI	DUCTED TEST ITEMS	
	3.1	Measuring Instruments	
	3.2	Test Setup	
	3.3	Test Result of Conducted Test	
	3.4	Conducted Output Power and ERP/EIRP	
	3.5	Peak-to-Average Ratio	
	3.6	Occupied Bandwidth	
	3.7	Conducted Band Edge	
	3.8	Conducted Spurious Emission	
	3.9	Frequency Stability	
4		ATED TEST ITEMS	_
	4.1	Measuring Instruments	
	4.2	Test Setup	
	4.3	Test Result of Radiated Test	
	4.4	Radiated Spurious Emission	
		OF MEASURING EQUIPMENT	
6		ERTAINTY OF EVALUATION	24
AP	PEND	IX A. TEST RESULTS OF CONDUCTED TEST	
AP	PEND	IX B. TEST RESULTS OF ERP/EIRP AND RADIATED TEST	

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 2 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## **REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG742206-01B	Rev. 01	Initial issue of report	Jul. 03, 2017

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 3 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## **SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result	Remark	
	§2.1046	Conducted Output Power	Reporting Only			
3.4	§22.913(a)(2)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	-	
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 2) (Band 7)	EIRP < 2Watt			
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-	
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-	
3.7	§2.1051 §22.917(a) §24.238(a)	Conducted Band Edge Measurement (Band 2) (Band 5)	< 43+10log10(P[Watts])	PASS		
3.1	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7)	§27.53(m)(4)	FAGG	-	
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission (Band 2) (Band 5)	< 43+10log10(P[Watts])	PASS	_	
3.0	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7)	< 55+10log <sub>10</sub> (P[Watts])	1700	-	
	§2.1055 §22.355		< 2.5 ppm for Part 22			
3.9	§2.1055 §24.235 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-	
4.4	§2.1053 §22.917(a) §24.238(a)	Radiated Spurious Emission (Band 2) (Band 5)	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 6.23 dB at	
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7)	< 55+10log <sub>10</sub> (P[Watts])		15192.000 MHz	

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 4 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 1 General Description

## 1.1 Applicant

#### Sony Mobile Communications Inc.

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

#### 1.2 Manufacturer

#### Sony Mobile Communications Inc.

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

## 1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII, a/b/g/n, NFC, and GPS

	Standards-related Product Specification
Antenna Type / Gain	C-feed Antenna

Report No.: FG742206-01B

EUT Information List												
HW Version	SW Version	S/N	Performed Test Item									
А	0.32	RQ3004R80Y	Conducted Measurement ERP/EIRP Test									
		RQ3004R80Y	Radiated Spurious Emission									

	Accessory List				
AC Adomton 4	Model No. : UCH20				
AC Adapter 1	S/N: 1215W48600059				
Familian 4	Model No.: MH410c				
Earphone 1	S/N: 1632A86900000FC				
110D 0 -1 1-	Model No. : UCB20				
USB Cable	S/N: 1625A91900007E2				

#### Note:

- 1. Above EUT list and accessory list used are electrically identical per declared by manufacturer.
- 2. Above the accessories list are used to exercise the EUT during test.
- 3. For other wireless features of this EUT, test report will be issued separately.
- **4.** For conducted test items except conducted output power is carrying out, FG742206-01B report reuses test data from the FG692208-01B report.

#### 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 5 of 24

 TEL: 886-3-327-3456
 Report Issued Date
 : Jul. 03, 2017

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

FCC ID : PY7-02885J Report Template No.: BU5-FGLTE Version 1.6

# 1.5 Emission Designator

L	TE Band 2		QPSK			16QAM			
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)		
1.4	1850.7 ~ 1909.3	1M09G7D	-	0.2070	1M09W7D	-	0.1734		
3	1851.5 ~ 1908.5	2M73G7D	-	0.2094	2M74W7D	-	0.1770		
5	1852.5 ~ 1907.5	4M53G7D	-	0.2094	4M55W7D	-	0.1762		
10	1855.0 ~ 1905.0	9M15G7D	0.0125	0.2109	9M07W7D	-	0.1782		
15	1857.5 ~ 1902.5	13M5G7D	-	0.2168	13M5W7D	-	0.1824		
20	1860.0 ~ 1900.0	18M4G7D	-	0.2239	18M5W7D	-	0.1875		
L	TE Band 5		QPSK		16QAM				
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)		
1.4	824.7 ~ 848.3	1M09G7D	-	0.0733	1M10W7D	-	0.0586		
3	825.5 ~ 847.5	2M75G7D	-	0.0736	2M75W7D	-	0.0605		
5	826.5 ~ 846.5	4M52G7D	-	0.0731	4M51W7D	-	0.0608		
10	829.0 ~ 844.0	9M11G7D	0.0103	0.0746	9M07W7D	-	0.0630		
L	TE Band 7		QPSK			16QAM			
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)		
5	2502.5 ~ 2567.5	4M51G7D	-	0.1524	4M52W7D	-	0.1285		
10	2505.0 ~ 2565.0	9M13G7D	0.0095	0.1563	9M05W7D	-	0.1285		
15	2507.5 ~ 2562.5	13M5G7D	-	0.1581	13M5W7D	-	0.1288		
20	2510.0 ~ 2560.0	18M5G7D	-	0.1585	18M5W7D	-	0.1288		

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 6 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Report No.: FG742206-01B

Test Site	SPORTON INTERNATIONAL INC.						
	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park,						
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.						
Test Site Location	TEL: +886-3-327-3456						
	FAX: +886-3-328-4978						
Test Site No.	Sporton Site No.						
Test Site NO.	TH05-HY						

Test Site	SPORTON INTERNATIONAL INC.							
	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist,							
Test Site Location	Taoyuan City, Taiwan (R.O.C.)							
rest Site Location	TEL: +886-3-327-0868							
	FAX: +886-3-327-0855							
Took Site No	Sporton Site No.							
Test Site No.	03CH10HY							

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

#### Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

SPORTON INTERNATIONAL INC.

Page Number : 7 of 24 TEL: 886-3-327-3456 Report Issued Date: Jul. 03, 2017 FAX: 886-3-328-4978 Report Version : Rev. 01

FCC ID: PY7-02885J Report Template No.: BU5-FGLTE Version 1.6

## 2 Test Configuration of Equipment Under Test

## 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Tool Home	Don't		В	andwi	dth (MF	lz)		Modi	ulation		RB#		Tes	st Char	nel
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	М	Н
Max. Output	2	V	V	V	٧	V	V	V	v	V	V	V	V	٧	v
Power	5	V	V	V	V	•	•	v	y	V	v	V	V	V	v
1 Owel	7	-	-	v	V	V	V	v	y	v	v	V	v	V	v
Peak-to-Average	2						V	V	V	V		V	V	٧	v
Ratio	5				V	•	•	v	y	V		V	V	V	v
Ratio	7	•	•				V	v	V	V		V	V	V	v
26dB and 99%	2	V	V	V	٧	V	V	V	V			V	V	٧	v
Bandwidth	5	V	V	V	V	•	-	V	V			V	V	V	v
Bandwidth	7	•	•	V	٧	V	V	V	V			V	V	٧	v
Conducted	2	v	V	v	٧	V	v	v	v	V		V	V		v
Band Edge	5	V	V	V	V	•	-	v	v	V		V	V		v
Ballu Luge	7	-	•	V	V	V	V	v	y	V		V	V		v
Conducted	2	V	V	V	V	V	V	v	y	V			V	V	v
Spurious	5	v	v	v	V	-	-	v	v	v			v	V	v
Emission	7	•	•	y	y	V	V	v	V	V			V	٧	v
F	2				V			V				V		V	
Frequency	5				y	-	-	v				V		γ	
Stability	7	-	-		V			v				V		v	

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 8 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6


			Bandwidth (MHz)					Modulation		RB#			Test Channel		
Test Items	Band	1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	Н
	2	v	V	V	V	V	V	v	v	V			y	V	V
E.R.P./ E.I.R.P.	5	V	V	V	V	-	-	v	V	V			V	V	v
	7	-	-	v	v	V	V	v	v	v			v	V	V
Radiated	2	y	V	v	V	V	V	V		V				V	
Spurious	5	V	V	v	v	-	-	v		v				V	
Emission	7	•	•	v	V	V	V	v		v				V	
Note	2. Th 3. Th	e mai e dev urious	rk "-" r ice is s emis	means invest sion te	that that the thick the thick the thick the thick the thick that the thick t	his ba I from der dif	ndwid 30MF ferent	th is not Iz to 10 : RB size	chosen to support times of e/offset a are repo	ed. funda ind mo	menta	•			

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 9 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

#### Example:

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB)

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 10 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

# 2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List							
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest			
20	Channel	18700	18900	19100			
20	Frequency	1860	1880	1900			
15	Channel	18675	18900	19125			
15	Frequency	1857.5	1880	1902.5			
10	Channel	18650	18900	19150			
10	Frequency	1855	1880	1905			
5	Channel	18625	18900	19175			
5	Frequency	1852.5	1880	1907.5			
3	Channel	18615	18900	19185			
3	Frequency	1851.5	1880	1908.5			
1.4	Channel	18607	18900	19193			
1.4	Frequency	1850.7	1880	1909.3			

LTE Band 5 Channel and Frequency List							
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest			
10	Channel	20450	20525	20600			
10	Frequency	829	836.5	844			
5	Channel	20425	20525	20625			
5	Frequency	826.5	836.5	846.5			
2	Channel	20415	20525	20635			
3	Frequency	825.5	836.5	847.5			
4.4	Channel	20407	20525	20643			
1.4	Frequency	824.7	836.5	848.3			

LTE Band 7 Channel and Frequency List							
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest			
20	Channel	20850	21100	21350			
20	Frequency	2510	2535	2560			
45	Channel	20825	21100	21375			
15	Frequency	2507.5	2535	2562.5			
10	Channel	20800	21100	21400			
10	Frequency	2505	2535	2565			
E	Channel	20775	21100	21425			
5	Frequency	2502.5	2535	2567.5			

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 11 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6


## 3 Conducted Test Items

## 3.1 Measuring Instruments


See list of measuring instruments of this test report.

## 3.2 Test Setup


#### 3.2.1 Conducted Output Power



# 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 12 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report No.: FG742206-01B

Report Template No.: BU5-FGLTE Version 1.6

## 3.4 Conducted Output Power and ERP/EIRP

# 3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2 and Band 7

According to KDB 412172 D01 Power Approach,

 $EIRP = P_T + G_T - L_C$ , ERP = EIRP - 2.15, where

 $P_T$  = transmitter output power in dBm

 $G_T$  = gain of the transmitting antenna in dBi

 $L_{\text{C}}$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through the system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure and record the power level from the system simulator.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 13 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 3.5 Peak-to-Average Ratio

#### 3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

#### 3.5.2 Test Procedures

- 1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
- 2. The EUT was connected to spectrum and system simulator via a power divider.
- 3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- 4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
- 5. Record the deviation as Peak to Average Ratio.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 14 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 3.6 Occupied Bandwidth

#### 3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

- 1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
   The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- 4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- 5. Set the detection mode to peak, and the trace mode to max hold.
- 6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
- 7. Determine the "-26 dB down amplitude" as equal to (Reference Value X).
- 8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- 9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

## 3.7 Conducted Band Edge

#### 3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is 43 + 10log<sub>10</sub>(P[Watts]) dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is  $43 + 10\log_{10}(P[Watts])$  dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 16 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

#### 3.7.2 Test Procedures

- 1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 3. The band edges of low and high channels for the highest RF powers were measured.
- 4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
- 5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
- 6. Set spectrum analyzer with RMS detector.
- 7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- Checked that all the results comply with the emission limit line.
   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
- 9. For LTE Band 7, the other 40 dB, and 55 dB have additionally applied same calculation above.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 17 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 3.8 Conducted Spurious Emission

## 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 7:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

#### 3.8.2 Test Procedures

- 1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
   The path loss was compensated to the results for each measurement.
- 4. The middle channel for the highest RF power within the transmitting frequency was measured.
- 5. The conducted spurious emission for the whole frequency range was taken.
- 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
- 7. Set spectrum analyzer with RMS detector.
- 8. Taking the record of maximum spurious emission.
- The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 10. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
- 11. For Band 7

The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 18 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

#### 3.9.2 Test Procedures for Temperature Variation

- 1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
- 2. The EUT was set up in the thermal chamber and connected with the system simulator.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.9.3 Test Procedures for Voltage Variation

- 1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
- 2. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
- The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- 4. The variation in frequency was measured for the worst case.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 19 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6


## 4 Radiated Test Items

## 4.1 Measuring Instruments


See list of measuring instruments of this test report.

## 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



#### 4.3 Test Result of Radiated Test

Please refer to Appendix B.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 20 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

## 4.4 Radiated Spurious Emission

#### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 7

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 4.4.2 Test Procedures

- The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
- 2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 9. Taking the record of output power at antenna port.
- 10. Repeat step 7 to step 8 for another polarization.
- 11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

12. For Band 7,

The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)

EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain

ERP (dBm) = EIRP - 2.15

Page Number : 21 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

# 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	GSM/GPRS /WCDMA/LTE	Oct. 11, 2016	May 11, 2017	Oct. 10, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 04, 2016	May 11, 2017	Nov. 03, 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30℃ ~70℃	Sep. 01, 2016	May 11, 2017	Aug. 31, 2017	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890089	1V~20V 0.5A~5A	Jan. 12, 2017	May 11, 2017	Jan. 11, 2018	Conducted (TH05-HY)
Hygrometer	Testo	608-H2	41410069	N/A	Aug. 28, 2016	May 11, 2017	Aug. 27, 2017	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY84209521	1GHz~26GHz	Dec. 02, 2016	May 11, 2017	Dec. 01, 2017	Conducted (TH05-HY)
Bilog Antenna	TESEQ	CBL 6111D&008	35413&02	30MHz~1GHz	Jan. 07, 2017	May 23, 2017~ May 25, 2017	Jan. 06, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 30, 2016	May 23, 2017~ May 25, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Mar. 17, 2017	May 23, 2017~ May 25, 2017	Mar. 16, 2018	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 27, 2017	May 23, 2017~ May 25, 2017	Apr. 26, 2018	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 08, 2016	May 23, 2017~ May 25, 2017	Nov. 07, 2017	Radiation (03CH10-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 26, 2016	May 23, 2017~ May 25, 2017	Oct. 25, 2017	Radiation (03CH10-HY)
Preamplifier	MITEQ	JS44-18004 000-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	May 23, 2017~ May 25, 2017	Jun. 13, 2017	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Oct. 26, 2016	May 23, 2017~ May 25, 2017	Oct. 25, 2017	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 17, 2016	May 23, 2017~ May 25, 2017	Oct. 16, 2017	Radiation (03CH10-HY)

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 22 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	May 23, 2017~ May 25, 2017	N/A	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-450 0-B	N/A	1~4m	N/A	May 23, 2017~ May 25, 2017	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	May 23, 2017~ May 25, 2017	N/A	Radiation (03CH10-HY)
Hygrometer	TECPEL	DTM-303B	TP140320	N/A	Nov. 14, 2016	May 23, 2017~ May 25, 2017	Nov. 13, 2017	Radiation (03CH10-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 22, 2017	May 23, 2017~ May 25, 2017	May 21, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524	25GHz~40GHz	Sep. 30, 2016	May 23, 2017~ May 25, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524	30MHz~1GHz	Sep. 30, 2016	May 23, 2017~ May 25, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524	1GHz~25GHz	Sep. 30, 2016	May 23, 2017~ May 25, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
Filter	Wainwright	WHKX12-27 00-3000-180	SN2	3 GHz High Pass	Jul. 07, 2016	May 23, 2017~ May 25, 2017	Jul. 06, 2017	Radiation (03CH10-HY)
Filter	Wainwright	WHKX12-10 80-1200-150	SN1	1.2 GHz High Pass	Sep. 19, 2016	May 23, 2017~ May 25, 2017	Sep. 18, 2017	Radiation (03CH10-HY)
Filter	Wainwright	WLKS1200- 12SS	SN2	1.2G Low Pass	Sep. 19, 2016	May 23, 2017~ May 25, 2017	Sep. 18, 2017	Radiation (03CH10-HY)
Notch Filter	Wainwright	WRCT/800/ 960-0.2/40-8	SN11	GSM850	Aug. 25, 2016	May 23, 2017~ May 25, 2017	Aug. 24, 2017	Radiation (03CH10-HY)
Notch Filter	Wainwright	WRCT1850/ 1910-40/8S	SN21	1900	Nov. 22, 2016	May 23, 2017~ May 25, 2017	Nov. 21, 2017	Radiation (03CH10-HY)
Notch Filter	Wainwright	WRCT2500/ 2570-10/40-	SN1 R	LTE Band7	Aug. 25, 2016	May 23, 2017~ May 25, 2017	Aug. 24, 2017	Radiation (03CH10-HY)
Test Software	N/A	E3	6.2009-8-24	N/A	N/A	May 23, 2017~ May 25, 2017	N/A	Radiation (03CH10-HY)

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 23 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6



# 6 Uncertainty of Evaluation

#### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	3.07
Confidence of 95% (U = 2Uc(y))	3.07

#### <u>Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)</u>

Measuring Uncertainty for a Level of	3.48
Confidence of 95% (U = 2Uc(y))	3.40

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of	3.92
Confidence of 95% (U = 2Uc(y))	3.92

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: PY7-02885J Page Number : 24 of 24
Report Issued Date : Jul. 03, 2017
Report Version : Rev. 01

Report Template No.: BU5-FGLTE Version 1.6



# **Appendix A. Test Results of Conducted Test**

## Conducted Output Power(Average power)

	LTE Band 2 Maximum Average Power [dBm]							
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest		
20	1	0		23.66	23.70	23.69		
20	1	49		23.43	23.42	23.24		
20	1	99		23.54	23.59	23.46		
20	50	0	QPSK	22.50	22.48	22.42		
20	50	24		22.47	22.45	22.30		
20	50	50		22.46	22.51	22.25		
20	100	0		22.50	22.52	22.33		
20	1	0		22.81	22.92	22.93		
20	1	49		22.63	22.68	22.44		
20	1	99		22.78	22.84	22.65		
20	50	0	16-QAM	21.47	21.50	21.42		
20	50	24		21.44	21.46	21.28		
20	50	50		21.46	21.53	21.23		
20	100	0		21.48	21.54	21.35		
15	1	0		23.50	23.56	23.39		
15	1	37		23.37	23.39	23.18		
15	1	74		23.47	23.46	23.30		
15	36	0	QPSK	22.41	22.42	22.28		
15	36	20		22.39	22.39	22.21		
15	36	39		22.42	22.41	22.19		
15	75	0		22.40	22.42	22.22		
15	1	0		22.67	22.81	22.64		
15	1	37		22.56	22.66	22.42		
15	1	74		22.68	22.71	22.52		
15	36	0	16-QAM	21.38	21.45	21.27		
15	36	20		21.36	21.42	21.21		
15	36	39		21.40	21.43	21.18		
15	75	0		21.39	21.44	21.23		

LTE Band 2 Maximum Average Power [dBm]							
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	
10	1	0		23.37	23.44	23.23	
10	1	25		23.32	23.38	23.18	
10	1	49		23.41	23.41	23.25	
10	25	0	QPSK	22.31	22.34	22.22	
10	25	12		22.33	22.35	22.20	
10	25	25		22.36	22.35	22.14	
10	50	0		22.35	22.36	22.21	
10	1	0		22.53	22.71	22.46	
10	1	25		22.49	22.66	22.43	
10	1	49		22.60	22.69	22.50	
10	25	0	16-QAM	21.29	21.38	21.23	
10	25	12		21.32	21.39	21.20	
10	25	25		21.35	21.40	21.15	
10	50	0		21.31	21.38	21.19	
5	1	0		23.29	23.37	23.17	
5	1	12		23.35	23.41	23.22	
5	1	24		23.29	23.34	23.17	
5	12	0	QPSK	22.25	22.30	22.16	
5	12	7		22.30	22.37	22.19	
5	12	13		22.28	22.34	22.14	
5	25	0		22.28	22.33	22.17	
5	1	0		22.46	22.65	22.37	
5	1	12		22.52	22.66	22.43	
5	1	24		22.44	22.61	22.38	
5	12	0	16-QAM	21.24	21.36	21.18	
5	12	7		21.30	21.42	21.21	
5	12	13		21.28	21.39	21.16	
5	25	0		21.26	21.37	21.17	

	LTE Band 2 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest			
3	1	0		23.31	23.41	23.21			
3	1	8		23.25	23.35	23.15			
3	1	14		23.31	23.40	23.21			
3	8	0	QPSK	22.31	22.40	22.22			
3	8	4		22.30	22.39	22.21			
3	8	7		22.31	22.39	22.20			
3	15	0		22.33	22.40	22.23			
3	1	0		22.46	22.68	22.43			
3	1	8		22.41	22.63	22.38			
3	1	14		22.47	22.67	22.42			
3	8	0	16-QAM	21.32	21.47	21.27			
3	8	4		21.31	21.47	21.25			
3	8	7		21.31	21.46	21.24			
3	15	0		21.32	21.45	21.26			
1.4	1	0		23.11	23.22	23.03			
1.4	1	3		23.08	23.19	23.00			
1.4	1	5		23.14	23.24	23.05			
1.4	3	0	QPSK	23.23	23.32	23.14			
1.4	3	1		23.24	23.31	23.14			
1.4	3	3		23.28	23.36	23.18			
1.4	6	0		22.25	22.32	22.14			
1.4	1	0		22.37	22.59	22.35			
1.4	1	3		22.32	22.52	22.28			
1.4	1	5	16-QAM	22.39	22.57	22.33			
1.4	3	0		22.31	22.46	22.25			
1.4	3	1		22.33	22.47	22.26			
1.4	3	3		22.30	22.45	22.24			
1.4	6	0		21.29	21.42	21.21			

LTE Band 5 Maximum Average Power [dBm] BW [MHz] **RB Size RB Offset** Mod Middle Lowest Highest 10 0 23.61 23.68 23.52 10 25 1 23.56 23.50 23.61 10 1 49 23.66 23.50 23.65 10 25 0 **QPSK** 22.59 22.59 22.62 10 25 12 22.61 22.54 22.60 10 25 25 22.66 22.45 22.63 10 50 0 22.66 22.57 22.63 10 1 0 22.80 22.92 22.72 10 1 25 22.84 22.71 22.80 10 22.94 22.70 49 22.71 10 25 16-QAM 0 21.62 21.65 21.61 10 25 12 21.64 21.55 21.62 10 25 25 21.72 21.47 21.62 10 50 0 21.67 21.56 21.61 5 1 0 23.50 23.52 23.55 5 1 12 23.53 23.49 23.59 1 5 24 23.51 23.41 23.56 5 12 QPSK 0 22.50 22.50 22.54 7 5 12 22.54 22.49 22.58 12 13 22.53 22.43 5 22.52 25 0 5 22.53 22.47 22.55 0 22.77 22.78 5 1 22.69 5 1 12 22.79 22.73 22.75 5 1 24 22.78 22.64 22.60 5 12 0 16-QAM 21.55 21.52 21.56 7 5 12 21.59 21.52 21.58 5 12 13 21.60 21.45 21.51 5 25 0 21.55 21.48 21.54

SPORTON LAB.	FCC R	F Test	Report
			LTE B

LTE Band 5 Maximum Average Power [dBm]									
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest			
3	1	0		23.56	23.51	23.59			
3	1	8		23.48	23.41	23.53			
3	1	14		23.53	23.45	23.62			
3	8	0	QPSK	22.58	22.52	22.61			
3	8	4		22.57	22.48	22.61			
3	8	7		22.55	22.48	22.60			
3	15	0		22.60	22.54	22.65			
3	1	0		22.72	22.73	22.75			
3	1	8		22.72	22.65	22.65			
3	1	14		22.77	22.67	22.64			
3	8	0	16-QAM	21.63	21.57	21.63			
3	8	4		21.64	21.54	21.60			
3	8	7		21.63	21.53	21.57			
3	15	0		21.64	21.55	21.62			
1.4	1	0		23.36	23.32	23.41			
1.4	1	3		23.34	23.28	23.38			
1.4	1	5		23.38	23.33	23.44			
1.4	3	0	QPSK	23.50	23.44	23.55			
1.4	3	1		23.50	23.44	23.57			
1.4	3	3		23.54	23.47	23.60			
1.4	6	0		22.52	22.46	22.57			
1.4	1	0		22.62	22.63	22.59			
1.4	1	3		22.59	22.56	22.49			
1.4	1	5		22.63	22.60	22.53			
1.4	3	0	16-QAM	22.58	22.54	22.53			
1.4	3	1		22.61	22.56	22.56			
1.4	3	3		22.57	22.53	22.51			
1.4	6	0		21.58	21.53	21.55			

15

75

LTE Band 7 Maximum Average Power [dBm]									
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest			
20	1	0		21.77	21.90	21.68			
20	1	49		21.09	21.65	21.23			
20	1	99		21.18	21.65	21.25			
20	50	0	QPSK	20.67	20.65	20.67			
20	50	24		20.52	20.62	20.52			
20	50	50		20.58	20.54	20.58			
20	100	0		20.64	20.61	20.64			
20	1	0		20.95	21.00	20.92			
20	1	49		20.78	20.97	20.77			
20	1	99		20.99	21.00	20.96			
20	50	0	16-QAM	19.68	19.69	19.72			
20	50	24		19.55	19.67	19.58			
20	50	50		19.61	19.59	19.62			
20	100	0		19.67	19.66	19.70			
15	1	0		21.78	21.89	21.83			
15	1	37		21.13	21.69	21.30			
15	1	74		21.31	21.70	21.11			
15	36	0	QPSK	20.67	20.71	20.67			
15	36	20		20.54	20.67	20.49			
15	36	39		20.62	20.62	20.52			
15	75	0		20.67	20.67	20.61			
15	1	0		20.95	20.93	20.92			
15	1	37		20.82	21.00	20.76			
15	1	74		20.96	20.92	20.99			
15	36	0	16-QAM	19.70	19.75	19.71			
15	36	20		19.58	19.71	19.54			
15	36	39		19.65	19.65	19.56			

19.69

19.71

19.66

LTE Band 7 Maximum Average Power [dBm]									
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest			
10	1	0		21.68	21.84	21.54			
10	1	25		20.92	21.71	21.33			
10	1	49		20.83	21.64	20.97			
10	25	0	QPSK	20.64	20.72	20.55			
10	25	12		20.57	20.68	20.50			
10	25	25		20.58	20.66	20.51			
10	50	0		20.59	20.68	20.50			
10	1	0		20.99	20.92	20.90			
10	1	25		20.85	20.93	20.79			
10	1	49		20.95	20.99	20.93			
10	25	0	16-QAM	19.65	19.75	19.58			
10	25	12		19.60	19.70	19.53			
10	25	25		19.61	19.70	19.55			
10	50	0		19.63	19.72	19.56			
5	1	0		21.46	21.73	21.30			
5	1	12		21.07	21.70	21.30			
5	1	24	QPSK	20.69	21.67	20.83			
5	12	0		20.55	20.63	20.42			
5	12	7		20.54	20.64	20.44			
5	12	13		20.52	20.59	20.41			
5	25	0		20.55	20.63	20.44			
5	1	0		20.89	20.95	20.76			
5	1	12		20.88	20.99	20.76			
5	1	24	16-QAM	20.96	20.95	20.85			
5	12	0		19.61	19.70	19.50			
5	12	7		19.59	19.69	19.52			
5	12	13		19.56	19.67	19.49			
5	25	0		19.58	19.67	19.49			


## LTE Band 2

# Peak-to-Average Ratio

Mode						
Mod.	QP	SK	16C	Limit: 13dB		
RB Size	1RB	Full RB	1RB	Full RB	Result	
Lowest CH	4.09	5.39	5.22	6.35		
Middle CH	4.61	5.57	5.51	6.49	PASS	
Highest CH	4.93	5.57	5.97	6.52		


Report No. :FG742206-01B

SPORTON INTERNATIONAL INC. Page Number : A2-1 of 39



TEL: 886-3-327-3456 FAX: 886-3-328-4978

Report No. :FG742206-01B




# 26dB Bandwidth


Mode	LTE Band 2 : 26dB BW(MHz)												
BW	1.4MHz		3MHz		5M	5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	
Lowest CH	1.248	1.239	2.997	3.015	5.005	4.985	9.81	9.95	14.685	14.895	20.1	20.18	
Middle CH	1.245	1.276	2.997	3.021	5.025	4.945	10.35	9.95	14.505	14.505	20.26	20.3	
Highest CH	1.231	1.253	2.973	3.021	4.915	4.975	9.61	9.81	14.535	14.236	20.18	20.22	


Report No. :FG742206-01B


SPORTON INTERNATIONAL INC. Page Number : A2-4 of 39


Report No. :FG742206-01B
















## Occupied Bandwidth


Mode	LTE Band 2 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.72	2.74	4.53	4.47	9.11	9.07	13.43	13.52	18.42	18.38
Middle CH	1.09	1.09	2.73	2.73	4.51	4.5	9.15	9.07	13.46	13.52	18.42	18.42
Highest CH	1.08	1.09	2.72	2.7	4.5	4.55	9.07	9.01	13.43	13.49	18.42	18.5


Report No. :FG742206-01B


**SPORTON INTERNATIONAL INC.** Page Number : A2-11 of 39















## **Conducted Band Edge**



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: A2-18 of 39

Report No. :FG742206-01B

Report No.: FG742206-01B LTE Band 2 / 1.4MHz / 16QAM Lowest Band Edge / 1 RB Highest Band Edge / 1 RB Spectrum Ref Level 30.00 dBm Offset 11.70 dB Mode Auto Sweep Ref Level 30.00 dBm Offset 11.70 dB SGL Count 100/100 Mode Auto Sweep SGL Count 100/100 1 AvgPw LINE\_ABS -20 dBm--20 dBm--30 dBm 30 dBm-Start 1.84 GHz Spurious Emissio 3003 pts Stop 1.852 GHz purious Emissions 1.84891 GHz 1.85000 GHz 1.85027 GHz Power Abs -37.10 dBm -28.06 dBm 19.03 dBm Range Low Range Low Range Up 1.849 GHz 1.911 GHz 1.920 GHz Date: 12.OCT.2016 20:50:44 Lowest Band Edge / Full RB **Highest Band Edge / Full RB** Spectrum Spectrum 2 (X) Mode Auto Sweep Mode Auto Sweep Ref Level 30.00 dBm Offset 11.70 dB SGL Count 100/100 Line\_SPURIOUS\_LINE\_ABS SPURIOUS\_LINE\_ABS 20 dBm 10 dBm-10 dBr 0 dBm LINE\_ABS\_ -20 dBm-30 dBn 50 dBm -60 dBm-Start 1.84 GHz Stop 1.852 GHz Start 1.908 GHz purious Emissions

ΔLimit

1.908 GHz 1.910 GHz 1.911 GHz

Date: 12.OCT.2016 21:02:42

Range Up

1,90961 GHz 1,91000 GHz 1,91101 GHz

Frequency 1.84899 GHz 1.84999 GHz 1.85106 GHz -25.95 dBm -33.43 dBm 10.73 dBm

TEL: 886-3-327-3456 FAX: 886-3-328-4978

Range Up 1.849 GHz

ate: 12.OCT.2016 20:53:02

1.850 GHz 1.852 GHz