

# TEST REPORT

**Report Number. :** R14634918-E8

**Applicant :** Sony Corporation  
1-7-1 Konan Minat-Ku  
Tokyo, 108-0075, Japan

**FCC ID :** PY7-12907W

**EUT Description :** GSM/WCDMA/LTE/5G Phone with BT, DTS/UNII a/b/g/n/ac/ax, GPS,  
WPT & NFC

**Test Standard(s) :** FCC 47 CFR PART 15 SUBPART C

**Date Of Issue:**  
2023-03-15

**Prepared by:**  
UL LLC  
12 Laboratory Dr.  
Research Triangle Park, NC 27709 U.S.A.  
TEL: (919) 549-1400



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2023-02-23	Initial Issue	Charles Moody
V2	2023-03-15	Updated Section 5.2 to Reflect 300m Distance E-Field Reading	Charles Moody

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>4. DECISION RULES AND MEASUREMENT UNCERTAINTY .....</b>	<b>6</b>
4.1. METROLOGICAL TRACEABILITY .....	6
4.2. DECISION RULES.....	6
4.3. MEASUREMENT UNCERTAINTY.....	6
4.4. SAMPLE CALCULATION .....	6
<b>5. EQUIPMENT UNDER TEST.....</b>	<b>7</b>
5.1. DESCRIPTION OF EUT .....	7
5.2. MAXIMUM ELECTRIC FIELD STENGTH.....	7
5.3. SOFTWARE AND FIRMWARE.....	7
5.4. WORST-CASE CONFIGURATION AND MODE.....	7
5.5. DESCRIPTION OF TEST SETUP.....	8
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>9</b>
<b>7. 20 dB BANDWIDTH .....</b>	<b>11</b>
7.1.1. CONFIG 1.....	11
7.1.2. CONFIG 2.....	12
<b>8. RADIATED EMISSION TEST RESULTS.....</b>	<b>13</b>
8.1. LIMITS AND PROCEDURE.....	13
8.2. FCC TX FUNDAMENTAL AND SPURIOUS EMISSIONS FROM 9 kHz TO 30 MHz... 14	
8.2.1. CONFIG 1.....	14
8.2.2. CONFIG 2.....	15
<b>9. AC MAINS LINE CONDUCTED EMISSIONS.....</b>	<b>16</b>
9.1.1. CONFIG 1.....	17
9.1.2. CONFIG 2.....	19
<b>10. SETUP PHOTOS .....</b>	<b>21</b>
<b>END OF TEST REPORT .....</b>	<b>21</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** Sony Corporation  
1-7-1 Konan Minato-ku  
Tokyo, 108-0075, Japan

**EUT DESCRIPTION:** GSM/WCDMA/LTE/5G Phone with BT, DTS/UNII a/b/g/n/ac/ax,  
GPS, WPT & NFC

**SERIAL NUMBER:** QV7700ANFN

**SAMPLE RECEIPT DATE:** 2023-01-20

**DATE TESTED:** 2023-01-30 TO 2023-01-31


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	Complies

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.


This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released  
For UL LLC By:



Brian Kiewra  
Project Engineer  
Consumer, Medical and IT Segment  
UL LLC

Prepared By:



Charles Moody  
Engineer  
Consumer, Medical and IT Segment  
UL LLC

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, and FCC CFR 47 Part 15.

## 3. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, Certificate Number 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input type="checkbox"/>	Building 12 Laboratory Dr RTP, NC 27709, U.S.A	US0067	2180C	825374
<input checked="" type="checkbox"/>	Building 2800 Suite Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A		27265	

## 4. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 4.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

### 4.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U <sub>Lab</sub>
Radio Frequency (Spectrum Analyzer)	141.2 Hz
Occupied Channel Bandwidth	1.22%
RF output power, conducted	1.3 dB (PK) 0.45 dB (AV)
Power Spectral Density, conducted	2.47 dB
Unwanted Emissions, conducted	1.94 dB
All emissions, radiated	6.01 dB
Conducted Emissions (0.150-30MHz) - LISN	3.40 dB
Temperature	0.57°C
Humidity	3.39%
DC Supply voltages	1.70%

Uncertainty figures are valid to a confidence level of 95%.

### 4.4. SAMPLE CALCULATION

#### RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

$$\text{Field Strength (dBuV/m)} = \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Preamp Gain (dB)}$$

$$36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$$

#### MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided:

$$\text{Final Voltage (dBuV)} = \text{Measured Voltage (dBuV)} + \text{Cable Loss (dB)} + \text{Limiter Factor (dB)} + \text{LISN Insertion Loss.}$$

$$\text{dBuV} + 0 \text{ dB} + 10.1 \text{ dB} + 0 \text{ dB} = 46.6 \text{ dBuV}$$

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE/5G Phone with BT, DTS,/UNII a/b/g/n/ac/ax, GPS, WPT & NFC. This report covers WPT testing.

### 5.2. MAXIMUM ELECTRIC FIELD STENGTH

The transmitter has maximum peak radiated electric and magnetic field strength as follows:

Fundamental Frequency (KHz)	Mode	E field (300m distance) FCC (dBuV/m)
111.5	Charging Config 1	2.83
139.29	Charging Config 2	-8.12

### 5.3. SOFTWARE AND FIRMWARE

The firmware version installed in the EUT during testing was 0.92

### 5.4. WORST-CASE CONFIGURATION AND MODE

The EUT is a WPT charger operating from 111-145 kHz. Testing on the EUT was performed in the following configurations:

Config	Mode	Descriptions
1	Server: Charging Phone (parallel position)	EUT charging phone in parallel position
2	Server: Charging Phone (perpendicular)	EUT charging phone in perpendicular position

For all radiated emissions tests, both configurations were tested. The device being charged was also tested at several battery percentages. It was determined that a state of 5% charged was the worst case mode of operation. Therefore all emissions testing was performed with the battery at 5%. Both configurations were investigated for worst case emissions. Configuration 1 showed worst case emissions when the phones were off center. Configuration 2 showed worst case emissions when the phones were centered.

For below 30MHz testing, investigation was done on three antenna orientations (parallel, perpendicular, and ground-parallel); parallel and perpendicular are the worst orientations, therefore testing was performed on these two orientations only.

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 300 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788 D01.

## 5.5. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adaptor	Sony	XQZ-UC1	1821W34209742	NA
Sony Phone Client device for WPT	Sony	PY7-12907W	QV7700CRFN	NA

### I/O CABLES

I/O Cable List						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	USB-C	1	USB-C	Shielded	<3m	XQZ-UB1 AI-0164
2	Aux	1	AUX	Shielded	<3m	

### TEST SETUP

The EUT is placed into one of the three configurations prior to testing. Either with the EUT being charged by a client Sony Phone in a parallel, or perpendicular orientation. The EUT was left charging throughout the duration of the test.

### SETUP DIAGRAM

Refer to R14634918-EP8 for setup diagrams.



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

### Test Equipment Used - Line-Conducted Emissions – Voltage (Morrisville – Conducted 1)

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
CBL087	Coax cable, RG223, N-male to BNC-male, 20-ft.	Pasternack	PE3W06143-240	2022-04-05	2023-04-05
HI0091	Environmental Meter	Fisher Scientific	15-077-963	2022-07-20	2023-07-20
LISN003	LISN, 50-ohm/50-uH, 250uH 2-conductor, 25A	Fischer Custom Com.	FCC-LISN-50/250-25-2-01	2022-08-01	2023-08-01
75141	EMI Test Receiver 9kHz-7GHz	Rohde & Schwarz	ESCI 7	2022-08-03	2023-08-03
ATA222	Transient Limiter, 0.009-100MHz	Electro-Metrics	EM-7600	2022-04-05	2023-04-05
PS215	AC Power Source	Elgar	CW2501M (s/n 1523A02397)	NA	NA
SOFTEMI	EMI Software	UL	Version 9.5 (18 Oct 2021)		

### Test Equipment Used - Wireless Conducted Measurement Equipment

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
	<b>Common Equipment</b>				
	<b>Conducted Room 1</b>				
SA0027	Spectrum Analyzer	Keysight Technologies	N9030A	2022-05-24	2023-05-24
207726	Temp/Humid Chamber	Thermotron	SM-32-8200	2023-01-20	2024-01-20
HI0091	Environmental Meter	Fisher Scientific	15-077-963	2022-07-20	2023-07-20

Test Equipment Used - Radiated Disturbance Emissions Test Equipment (Morrisville – Chamber 2)

Equip. ID	Description	Manufacturer/Brand	Model Number	Last Cal.	Next Cal.
	<b>0.009-30MHz</b>				
135144	Active Loop Antenna	ETS-Lindgren	6502	2023-01-17	2024-01-17
	<b>Gain-Loss Chains</b>				
C2-SAC01	Gain-loss string: 0.009-30MHz	Various	Various	2022-05-10	2023-05-10
	<b>Receiver &amp; Software</b>				
197955	Spectrum Analyzer	Rohde & Schwarz	ESW44	2022-03-08	2023-03-08
SOFTEMI	EMI Software	UL	Version 9.5 (18 Oct 2021)		
	<b>Additional Equipment used</b>				
200540	Environmental Meter	Fisher Scientific	15-077-963 s/n 181474409	2022-10-05	2023-10-05

## 7. 20 dB BANDWIDTH


### TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1-5% of the 20dB bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 20dB bandwidth function is utilized.


Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

### RESULTS

#### 7.1.1. CONFIG 1



### 7.1.2. CONFIG 2



## 8. RADIATED EMISSION TEST RESULTS

### 8.1. LIMITS AND PROCEDURE

#### LIMIT

FCC §15.209 (a)  
ICES-001 Section 6.2, IC RSS-216 6.2.2, and IC RSS-GEN Sections 8.9 and 8.10.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (m)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100	3
88 to 216	150	3
216 to 960	200	3
Above 960 MHz	500	3


Note: The lower limit shall apply at the transition frequency.

#### RESULTS

## 8.2. FCC TX FUNDAMENTAL AND SPURIOUS EMISSIONS FROM 9 kHz TO 30 MHz

Note: All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz – 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were  $40 \cdot \log(\text{test distance} / \text{specification distance})$ .

### 8.2.1. CONFIG 1




### DATA

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	135144 (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading (uVolts/meter)	QP/AV Limit (dBUV/m)	PK Limit (dBUV/m)	Margin (dB)	Azimuth (Degs)	Loop Angle
2	.03307	38.71	Pk	13.9	.1	-80	-27.29	37.22	57.22	-64.51	0-360	0 degs
1	.1115	70.53	Pk	12.2	.1	-80	2.83	-	46.66	-43.83	260	0 degs
	.1115	70.37	Av	12.2	.1	-80	2.67	26.66	-	-23.99	260	0 degs
5	.11156	66.84	Pk	12.2	.1	-80	-8.6	-	46.65	-47.51	343	90 degs
	.11156	66.59	Av	12.2	.1	-80	-1.11	26.65	-	-27.76	343	90 degs
8	.1115	66.43	Pk	12.2	.1	-80	-1.27	-	46.66	-47.93	262	Flat
	.1115	66.2	Av	12.2	.1	-80	-1.5	26.66	-	-28.16	262	Flat
9	.33326	47.11	Pk	12.2	.1	-80	-20.59	17.15	37.15	-37.74	0-360	Flat
3	.33445	49.79	Pk	12.2	.1	-80	-17.91	17.12	37.12	-35.03	0-360	0 degs
6	.33513	47.54	Pk	12.2	.1	-80	-20.16	17.1	37.1	-37.26	0-360	90 degs
4	.55324	41.18	Pk	12.2	.1	-40	13.48	32.75	-	-19.27	0-360	0 degs
7	.55324	38.77	Pk	12.2	.1	-40	11.07	32.75	-	-21.68	0-360	90 degs
10	.55324	38.7	Pk	12.2	.1	-40	11	32.75	-	-21.75	0-360	Flat

Pk - Peak detector

Av - Average detection

**8.2.2. CONFIG 2**



**DATA**

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	135144 (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uVolts/meter)	QP/AV Limit (dBuV/m)	PK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Loop Angle
1	.13929	59.58	Pk	12.2	.1	-80	-8.12	-	44.73	-52.85	243	0 degs
	.13929	59.3	Av	12.2	.1	-80	-8.4	24.73	-	-33.13	243	0 degs
4	.14006	57.18	Pk	12.2	.1	-80	-10.52	-	44.68	-55.2	309	90 degs
	.14006	56.81	Av	12.2	.1	-80	-10.89	24.68	-	-35.57	309	90 degs
7	.14017	54.81	Pk	12.2	.1	-80	-12.89	-	44.67	-57.56	224	Flat
	.14017	54.33	Av	12.2	.1	-80	-13.37	24.67	-	-38.04	224	Flat
2	.41656	42.89	Pk	12.2	.1	-80	-24.81	15.21	35.21	-40.02	0-360	0 degs
8	.41673	39.92	Pk	12.2	.1	-80	-27.78	15.21	35.21	-42.99	0-360	Flat
5	.41724	40.84	Pk	12.2	.1	-80	-26.86	15.2	35.2	-42.06	0-360	90 degs
6	.51951	35.18	Pk	12.2	.1	-40	7.48	33.29	-	-25.81	0-360	90 degs
9	.57854	34.66	Pk	12.2	.2	-40	7.06	32.36	-	-25.3	0-360	Flat
3	.97062	31.45	Pk	12.2	.2	-40	3.85	27.86	-	-24.01	0-360	0 degs

Pk - Peak detector

Av - Average detection

## 9. AC MAINS LINE CONDUCTED EMISSIONS

### LIMITS

FCC §15.207 (a)

RSS-Gen 8.8

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

### RESULTS



**9.1.1. CONFIG 1**  
**LINE 1 RESULTS**




**WORST EMISSIONS**

Range 1: Line-L1 .15 - 30MHz										
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN VCF (dB)	Cbl/Limiter (dB)	Corrected Reading dBuV	QP Limit (dBuV)	Margin (dB)	Average Limit (dBuV)	Margin (dB)
1	.153	40.67	Pk	.2	9.8	50.67	65.84	-15.17	-	-
2	.153	19.63	Av	.2	9.8	29.63	-	-	55.84	-26.21
3	.234	32.16	Pk	.1	9.8	42.06	62.31	-20.25	-	-
4	.225	13.55	Av	.1	9.8	23.45	-	-	52.63	-29.18
5	.366	22.89	Pk	.1	9.8	32.79	58.59	-25.8	-	-
6	.375	5.55	Av	.1	9.8	15.45	-	-	48.39	-32.94
7	.603	25.64	Pk	0	9.8	35.44	56	-20.56	-	-
8	.603	9.46	Av	0	9.8	19.26	-	-	46	-26.74
9	3.204	24.45	Pk	0	9.9	34.35	56	-21.65	-	-
10	3.219	6.42	Av	0	9.9	16.32	-	-	46	-29.68
11	6.093	25.06	Pk	0	9.9	34.96	60	-25.04	-	-
12	6.093	-8	Av	0	9.9	9.1	-	-	50	-40.9
13	10.644	17.17	Pk	.1	10	27.27	60	-32.73	-	-
14	10.635	1.05	Av	.1	10	11.15	-	-	50	-38.85

PK - Peak detector  
 Av - Average detection

**LINE 2 RESULTS**




**WORST EMISSIONS**

Range 2: Line-L2 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN VCF (dB)	Cbl/Limiter (dB)	Corrected Reading dBuV	QP Limit (dBuV)	Margin (dB)	Average Limit (dBuV)	Margin (dB)
15	.159	31.65	Pk	.2	9.8	41.65	65.52	-23.87	-	-
16	.153	13.82	Av	.2	9.8	23.82	-	-	55.84	-32.02
17	.219	27.88	Pk	.1	9.8	37.78	62.86	-25.08	-	-
18	.228	8.35	Av	.1	9.8	18.25	-	-	52.52	-34.27
19	.339	22.96	Pk	.1	9.8	32.86	59.23	-26.37	-	-
20	.342	7.75	Av	.1	9.8	17.65	-	-	49.15	-31.5
21	.594	23.62	Pk	0	9.8	33.42	56	-22.58	-	-
22	.6	9.86	Av	0	9.8	19.66	-	-	46	-26.34
23	3.216	26.81	Pk	0	9.9	36.71	56	-19.29	-	-
24	3.234	9.23	Av	0	9.9	19.13	-	-	46	-26.87
25	10.764	19.27	Pk	.1	10	29.37	60	-30.63	-	-
26	10.758	1.41	Av	.1	10	11.51	-	-	50	-38.49

Pk - Peak detector  
 Av - Average detection

**9.1.2. CONFIG 2**  
**LINE 1 RESULTS**




**WORST EMISSIONS**

Range 1: Line-L1 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN VCF (dB)	Cbl/Limiter (dB)	Corrected Reading dBuV	QP Limit (dBuV)	Margin (dB)	Average Limit (dBuV)	Margin (dB)	
1	.168	34.42	Pk	.2	9.8	44.42	65.06	-20.64	-	-	
2	.171	15.63	Av	.2	9.8	25.63	-	-	54.91	-29.28	
3	.249	29.02	Pk	.1	9.8	38.92	61.79	-22.87	-	-	
4	.252	9.03	Av	.1	9.8	18.93	-	-	51.69	-32.76	
5	.342	29.57	Pk	.1	9.8	39.47	59.15	-19.68	-	-	
6	.342	20.56	Av	.1	9.8	30.46	-	-	49.15	-18.69	
7	.735	27.69	Pk	0	9.8	37.49	56	-18.51	-	-	
8	.738	17.45	Av	0	9.8	27.25	-	-	46	-18.75	
9	1.914	31.11	Pk	0	9.8	40.91	56	-15.09	-	-	
10	1.914	22.12	Av	0	9.8	31.92	-	-	46	-14.08	
11	4.857	28.15	Pk	0	9.9	38.05	56	-17.95	-	-	
12	4.857	19.52	Av	0	9.9	29.42	-	-	46	-16.58	
13	5.448	28.78	Pk	0	9.9	38.68	60	-21.32	-	-	
14	5.448	20.32	Av	0	9.9	30.22	-	-	50	-19.78	

Pk - Peak detector  
 Av - Average detection

**LINE 2 RESULTS**



**WORST EMISSIONS**

Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN VCF (dB)	Cbl/Limiter (dB)	Corrected Reading dBuV	QP Limit (dBuV)	Margin (dB)	Average Limit (dBuV)	Margin (dB)	
15	.156	34.25	Pk	.2	9.8	44.25	65.67	-21.42	-	-	
16	.153	13.57	Av	.2	9.8	23.57	-	-	55.84	-32.27	
17	.24	26.57	Pk	.1	9.8	36.47	62.1	-25.63	-	-	
18	.249	7.15	Av	.1	9.8	17.05	-	-	51.79	-34.74	
19	.441	24.69	Pk	0	9.8	34.49	57.04	-22.55	-	-	
20	.441	17.4	Av	0	9.8	27.2	-	-	47.04	-19.84	
21	.735	28.5	Pk	0	9.8	38.3	56	-17.7	-	-	
22	.735	22.07	Av	0	9.8	31.87	-	-	46	-14.13	
23	1.914	33.11	Pk	0	9.8	42.91	56	-13.09	-	-	
24	1.914	27.38	Av	0	9.8	37.18	-	-	46	-8.82	
25	4.857	29.66	Pk	0	9.9	39.56	56	-16.44	-	-	
26	4.857	23.52	Av	0	9.9	33.42	-	-	46	-12.58	
27	5.742	30.07	Pk	0	9.9	39.97	60	-20.03	-	-	
28	5.742	24.76	Av	0	9.9	34.66	-	-	50	-15.34	

Pk - Peak detector  
 Av - Average detection

## 10. SETUP PHOTOS

Please refer to R14634918-EP8 for setup photos

**END OF TEST REPORT**