



# FCC RADIO TEST REPORT

FCC ID : PY7-07452G  
Equipment : GSM/WCDMA/LTE/5G Phone with BT, DTS/UNII a/b/g/n/ac/ax, GPS, WPC and NFC  
Brand Name : Sony  
Applicant : Sony Corporation  
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan  
Manufacturer : Sony Corporation  
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan  
Standard : FCC Part 15 Subpart E §15.407

The product was received on Mar. 02, 2021 and testing was started from Mar. 10, 2021 and completed on Mar. 31, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this spot check data report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

**Sporton International Inc. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



# Table of Contents

**History of this test report..... 3**

**Summary of Test Result..... 4**

**1 General Description ..... 5**

    1.1 Product Feature of Equipment Under Test..... 5

    1.2 Modification of EUT ..... 5

    1.3 Testing Location ..... 6

    1.4 Applicable Standards..... 6

**2 Test Configuration of Equipment Under Test ..... 7**

    2.1 Carrier Frequency and Channel ..... 7

    2.2 Test Mode..... 7

    2.3 Connection Diagram of Test System ..... 8

    2.4 EUT Operation Test Setup ..... 8

**3 Test Result ..... 9**

    3.1 Maximum Conducted Output Power Measurement ..... 9

    3.2 Unwanted Emissions Measurement ..... 10

    3.3 Antenna Requirements ..... 15

**4 List of Measuring Equipment..... 16**

**5 Uncertainty of Evaluation ..... 17**

**Appendix A. Conducted Test Results**

**Appendix B. Radiated Spurious Emission**

**Appendix C. Radiated Spurious Emission Plots**

**Appendix D. Duty Cycle Plots**





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	15.403(i)	6dB & 26dB Bandwidth	-	See Note
-	2.1049	99% Occupied Bandwidth	-	See Note
3.1	15.407(a)	Maximum Conducted Output Power	Pass	-
-	15.407(a)	Power Spectral Density	-	See Note
3.2	15.407(b)	Unwanted Emissions	Pass	Under limit 5.24 dB at 17978.000 MHz
-	15.207	AC Conducted Emission	-	See Note
-	15.407(c)	Automatically Discontinue Transmission	-	See Note
3.3	15.203 15.407(a)	Antenna Requirement	Pass	-

**Note:** The RF circuit, output power level and antenna performance is the same in WLAN function across all two FCC ID PY7-26726G and PY7-07452G, since the change, only verify RF output power and radiated spurious emission test data the worst mode was reported in this report.

<b>Declaration of Conformity:</b> The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b> The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Ruby Zou**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac/ax, NFC, WPC/WPT, and GNSS.

Product Specification subjective to this standard	
Antenna Type / Gain	<Chain 0>: Loop Antenna with gain -1.6 dBi <Chain 1>: Monopole Antenna with gain -9.0 dBi

**Remark:** The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.325	QV7200D16T	RF conducted measurement
	0.325	QV7200466T	Radiated Spurious Emission

Accessory List	
AC Adapter	Model Name : XQZ-UC1
	S/N : 0020W51300105
Earphone	Model Name : MH750
	S/N : N/A
USB Cable	Model Name : XQZ-UB1
	S/N : N/A

**Note:**

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report.
3. For other wireless features of this EUT, test report will be issued separately.

## 1.2 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.3 Testing Location

<b>Test Site</b>	Sporton International Inc. EMC & Wireless Communications Laboratory
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
<b>Test Site No.</b>	<b>Sporton Site No.</b> TH05-HY

<b>Test Site</b>	Sporton International Inc. Wensan Laboratory
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
<b>Test Site No.</b>	<b>Sporton Site No.</b> 03CH16-HY (TAF Code: 3786)
<b>Remark</b>	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

### 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 <sup>#</sup>	5775	165	5825

**Note:**

1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel in "<sup>#</sup>" were 802.11ac VHT80 and 802.11ax HE80.

### 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Ch. #		Band IV : 5725-5850 MHz
		802.11a
L	Low	-
M	Middle	157
H	High	-

**Remark:** For radiation spurious emission, the final modulation and the worst data rate was reference the max RF conducted power.

### 2.3 Connection Diagram of Test System

<WLAN TX Mode>



### 2.4 EUT Operation Test Setup

The RF test items, utility "FTMC\_bridge\_v0.39" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



### 3 Test Result

#### 3.1 Maximum Conducted Output Power Measurement

##### 3.1.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.


##### 3.1.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.2 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

#### 3.2.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:** The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.



### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


### 3.2.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.
  - (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
    - RBW = 120 kHz
    - VBW = 300 kHz
    - Detector = Peak
    - Trace mode = max hold
  - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
    - RBW = 1 MHz
    - VBW  $\geq$  3 MHz
    - Detector = Peak
    - Sweep time = auto
    - Trace mode = max hold
  - (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
    - RBW = 1 MHz
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.


7. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.2.4 Test Setup


**For radiated emissions below 30MHz**




**For radiated emissions from 30MHz to 1GHz**



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





### **3.2.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### **3.2.6 Test Result of Radiated Band Edges**

Please refer to Appendix B and C.

### **3.2.7 Duty Cycle**

Please refer to Appendix D.

### **3.2.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)**

Please refer to Appendix B and C.



### **3.3 Antenna Requirements**

#### **3.3.1 Standard Applicable**

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **3.3.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

#### **3.3.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 03, 2021	Mar. 10, 2021~ Mar. 18, 2021	Mar. 02, 2022	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO12	10MHz~6GHz	Dec. 16, 2020	Mar. 10, 2021~ Mar. 18, 2021	Dec. 15, 2021	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz ~ 40GHz	Jul. 22, 2020	Mar. 10, 2021~ Mar. 18, 2021	Jul. 21, 2021	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 20, 2020	Mar. 10, 2021~ Mar. 18, 2021	Mar. 19, 2021	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	Mar. 25, 2021~ Mar. 31, 2021	Jul. 13, 2021	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01 N-06	47020 & 06	30MHz to 1GHz	Oct. 11, 2020	Mar. 25, 2021~ Mar. 31, 2021	Oct. 10, 2021	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Sep. 30, 2020	Mar. 25, 2021~ Mar. 31, 2021	Sep. 29, 2021	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-152 2	1G~18GHz	Sep. 29, 2020	Mar. 25, 2021~ Mar. 31, 2021	Sep. 28, 2021	Radiation (03CH16-HY)
Amplifier	EMCI	EMC051845S E	980729	1-18GHz	Jul. 10, 2020	Mar. 25, 2021~ Mar. 31, 2021	Jul. 09, 2021	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 576	18GHz ~40GHz	May 22, 2020	Mar. 25, 2021~ Mar. 31, 2021	May 21, 2021	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY532702 64	1GHz~26.5GHz	Dec. 10, 2020	Mar. 25, 2021~ Mar. 31, 2021	Dec. 09, 2021	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A	MY590530 12	3Hz~26.5GHz	Nov. 18, 2020	Mar. 25, 2021~ Mar. 31, 2021	Nov. 17, 2021	Radiation (03CH16-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Jan. 15, 2021	Mar. 25, 2021~ Mar. 31, 2021	Jan. 14, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/ 4PE	NA	Aug. 29, 2020	Mar. 25, 2021~ Mar. 31, 2021	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/ 4PE	NA	Aug. 29, 2020	Mar. 25, 2021~ Mar. 31, 2021	Aug. 28, 2021	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300 -5757	NA	Aug. 29, 2020	Mar. 25, 2021~ Mar. 31, 2021	Aug. 28, 2021	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Mar. 25, 2021~ Mar. 31, 2021	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Mar. 25, 2021~ Mar. 31, 2021	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 25, 2021~ Mar. 31, 2021	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 25, 2021~ Mar. 31, 2021	N/A	Radiation (03CH16-HY)





## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.5
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.3
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7
---	-----

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Eason huang/Shiming Liu	Temperature:	21.8~24.2	°C
Test Date:	2021/3/10~2021/3/18	Relative Humidity:	55.9~59.5	%

**TEST RESULTS DATA**  
**Average Power Table**

Band IV single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Chain 0	Chain 1	SUM	Chain 0	Chain 1	Chain 0	Chain 1	
11a	6Mbps	1	149	5745	11.70	11.60		30.00	30.00	-1.60	-9.00	Pass
11a	6Mbps	1	157	5785	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
11a	6Mbps	1	165	5825	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
HT20	MCS0	1	149	5745	11.60	11.50		30.00	30.00	-1.60	-9.00	Pass
HT20	MCS0	1	157	5785	11.60	11.60		30.00	30.00	-1.60	-9.00	Pass
HT20	MCS0	1	165	5825	11.60	11.60		30.00	30.00	-1.60	-9.00	Pass
HT40	MCS0	1	151	5755	11.50	11.50		30.00	30.00	-1.60	-9.00	Pass
HT40	MCS0	1	159	5795	11.50	11.60		30.00	30.00	-1.60	-9.00	Pass
VHT20	MCS0	1	149	5745	11.60	11.50		30.00	30.00	-1.60	-9.00	Pass
VHT20	MCS0	1	157	5785	11.50	11.60		30.00	30.00	-1.60	-9.00	Pass
VHT20	MCS0	1	165	5825	11.50	11.60		30.00	30.00	-1.60	-9.00	Pass
VHT40	MCS0	1	151	5755	11.50	11.50		30.00	30.00	-1.60	-9.00	Pass
VHT40	MCS0	1	159	5795	11.50	11.60		30.00	30.00	-1.60	-9.00	Pass
VHT80	MCS0	1	155	5775	11.60	11.50		30.00	30.00	-1.60	-9.00	Pass

Band IV MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Chain 0	Chain 1	SUM	Chain 0	Chain 1	Chain 0	Chain 1	
11a	6Mbps	2	149	5745	11.80	11.70	14.76	30.00		-1.60		Pass
11a	6Mbps	2	157	5785	11.80	11.80	14.81	30.00		-1.60		Pass
11a	6Mbps	2	165	5825	11.80	11.80	14.81	30.00		-1.60		Pass
HT20	MCS0	2	149	5745	11.70	11.60	14.66	30.00		-1.60		Pass
HT20	MCS0	2	157	5785	11.70	11.70	14.71	30.00		-1.60		Pass
HT20	MCS0	2	165	5825	11.70	11.70	14.71	30.00		-1.60		Pass
HT40	MCS0	2	151	5755	11.60	11.60	14.61	30.00		-1.60		Pass
HT40	MCS0	2	159	5795	11.60	11.70	14.66	30.00		-1.60		Pass
VHT20	MCS0	2	149	5745	11.70	11.60	14.66	30.00		-1.60		Pass
VHT20	MCS0	2	157	5785	11.70	11.70	14.71	30.00		-1.60		Pass
VHT20	MCS0	2	165	5825	11.70	11.70	14.71	30.00		-1.60		Pass
VHT40	MCS0	2	151	5755	11.60	11.60	14.61	30.00		-1.60		Pass
VHT40	MCS0	2	159	5795	11.60	11.70	14.66	30.00		-1.60		Pass
VHT80	MCS0	2	155	5775	11.70	11.60	14.66	30.00		-1.60		Pass

**TEST RESULTS DATA**  
**Average Power Table**

Band IV single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Chain 0	Chain 1	SUM	Chain 0	Chain 1	Chain 0	Chain 1	
HE20	MCS0	1	149	5745	Full	11.70	11.60		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	149	5745	26/0	8.60	8.60		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	149	5745	52/37	11.70	11.60		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	149	5745	106/53	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	157	5785	Full	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	165	5825	Full	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	165	5825	26/8	8.70	8.60		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	165	5825	52/40	11.60	11.60		30.00	30.00	-1.60	-9.00	Pass
HE20	MCS0	1	165	5825	106/54	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
HE40	MCS0	1	151	5755	Full	11.60	11.60		30.00	30.00	-1.60	-9.00	Pass
HE40	MCS0	1	151	5755	242/61	11.70	11.70		30.00	30.00	-1.60	-9.00	Pass
HE40	MCS0	1	159	5795	Full	11.60	11.70		30.00	30.00	-1.60	-9.00	Pass
HE40	MCS0	1	159	5795	242/62	11.50	11.60		30.00	30.00	-1.60	-9.00	Pass
HE80	MCS0	1	155	5775	Full	11.70	11.60		30.00	30.00	-1.60	-9.00	Pass
HE80	MCS0	1	155	5775	484/65	11.60	11.60		30.00	30.00	-1.60	-9.00	Pass
HE80	MCS0	1	155	5775	484/66	11.60	11.60		30.00	30.00	-1.60	-9.00	Pass

Band IV MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Chain 0	Chain 1	SUM	Chain 0	Chain 1	Chain 0	Chain 1	
HE20	MCS0	2	149	5745	Full	11.80	11.70	14.76	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	149	5745	26/0	8.70	8.70	11.71	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	149	5745	52/37	11.80	11.70	14.76	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	149	5745	106/53	11.80	11.80	14.81	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	157	5785	Full	11.80	11.80	14.81	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	165	5825	Full	11.80	11.80	14.81	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	165	5825	26/8	8.80	8.70	11.76	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	165	5825	52/40	11.70	11.70	14.71	30.00	30.00	-1.60	-1.60	Pass
HE20	MCS0	2	165	5825	106/54	11.80	11.80	14.81	30.00	30.00	-1.60	-1.60	Pass
HE40	MCS0	2	151	5755	Full	11.70	11.70	14.71	30.00	30.00	-1.60	-1.60	Pass
HE40	MCS0	2	151	5755	242/61	11.80	11.80	14.81	30.00	30.00	-1.60	-1.60	Pass
HE40	MCS0	2	159	5795	Full	11.70	11.80	14.76	30.00	30.00	-1.60	-1.60	Pass
HE40	MCS0	2	159	5795	242/62	11.60	11.80	14.71	30.00	30.00	-1.60	-1.60	Pass
HE80	MCS0	2	155	5775	Full	11.80	11.70	14.76	30.00	30.00	-1.60	-1.60	Pass
HE80	MCS0	2	155	5775	484/65	11.70	11.70	14.71	30.00	30.00	-1.60	-1.60	Pass
HE80	MCS0	2	155	5775	484/66	11.70	11.80	14.76	30.00	30.00	-1.60	-1.60	Pass



## Appendix B. Radiated Spurious Emission

Test Engineer :	Karl Hou, CR Liro and Andy Yang	Temperature :	20~25°C
		Relative Humidity :	50~60%

**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Band Edge @ 3m)**

WIFI Chain	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 157 5785MHz		5611.6	54.68	-13.52	68.2	39.12	31.68	13.65	29.77	244	306	P	H
		5653.2	53.75	-16.83	70.58	38.24	31.61	13.69	29.79	244	306	P	H
		5715.6	53.68	-55.89	109.57	37.96	31.79	13.74	29.81	244	306	P	H
		5723.2	53.24	-64.86	118.1	37.46	31.84	13.75	29.81	244	306	P	H
	*	5785	108.76	-	-	92.79	32	13.81	29.84	244	306	P	H
	*	5785	101.3	-	-	85.33	32	13.81	29.84	244	306	A	H
		5852	53.93	-63.71	117.64	37.88	32.1	13.81	29.86	244	306	P	H
		5869	54.77	-52.11	106.88	38.69	32.14	13.81	29.87	244	306	P	H
		5905.2	54.71	-28.1	82.81	38.57	32.21	13.81	29.88	244	306	P	H
		5933.6	54.18	-14.02	68.2	37.99	32.27	13.81	29.89	244	306	P	H
		5613	54.66	-13.54	68.2	39.11	31.67	13.65	29.77	246	4	P	V
		5680.4	54.44	-36.29	90.73	38.87	31.66	13.71	29.8	246	4	P	V
		5707.4	54.4	-52.87	107.27	38.73	31.74	13.74	29.81	246	4	P	V
		5724	53.41	-66.51	119.92	37.64	31.84	13.75	29.82	246	4	P	V
	*	5785	107.05	-	-	91.08	32	13.81	29.84	246	4	P	V
	*	5785	99.03	-	-	83.06	32	13.81	29.84	246	4	A	V
		5853.6	54.02	-59.97	113.99	37.96	32.11	13.81	29.86	246	4	P	V
		5874.8	56	-49.26	105.26	39.91	32.15	13.81	29.87	246	4	P	V
		5875.4	55.22	-49.68	104.9	39.13	32.15	13.81	29.87	246	4	P	V
		5932.2	54.45	-13.75	68.2	38.27	32.26	13.81	29.89	246	4	P	V



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Chain 0+1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11a CH 157 5785MHz		11570	48.59	-25.41	74	44.09	39.76	20.18	55.44	100	0	P	H
		17355	51.51	-16.69	68.2	41.6	41.6	25.21	56.9	100	0	P	H
		17945	58.87	-15.13	74	42.57	48.15	25.43	57.28	100	0	P	H
		17945	48.37	-5.63	54	32.07	48.15	25.43	57.28	100	0	A	H
		11570	48.5	-25.5	74	44	39.76	20.18	55.44	100	0	P	V
		17355	51.55	-16.65	68.2	41.64	41.6	25.21	56.9	100	0	P	V
		17978	59.25	-14.75	74	42.26	48.84	25.44	57.29	100	0	P	V
		17978	48.76	-5.24	54	31.77	48.84	25.44	57.29	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

WIFI 802.11a (SHF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Chain				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
0+1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
802.11a SHF		26558	41.07	-27.13	68.2	39.36	40.1	14.61	53	150	0	P	H	
		36282	45.43	-22.77	68.2	40.72	42.71	18.69	56.69	150	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
			22796	40.32	-33.68	74	42.91	38.58	12.39	53.56	150	0	P	V
			34170	43.21	-24.99	68.2	39.36	41.03	18.03	55.21	150	0	P	V
														V
														V
														V
														V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.													



Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Chain				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
0+1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
802.11a LF		107.6	29.96	-13.54	43.5	44.11	16.86	1.61	32.62	-	-	P	H	
		309.36	22.18	-23.82	46	32.36	19.39	2.96	32.53	-	-	P	H	
		462.62	24.69	-21.31	46	30.09	23.51	3.64	32.55	-	-	P	H	
		571.26	28.06	-17.94	46	30.56	26.08	4.09	32.67	-	-	P	H	
		716.76	33.28	-12.72	46	34.09	27.05	4.62	32.48	-	-	P	H	
		900.09	33.53	-12.47	46	31.49	29.16	5.3	32.42	100	0	P	H	
														H
														H
														H
														H
														H
														H
			63.95	31.17	-8.83	40	50.84	11.94	1.17	32.78	100	0	P	V
			183.26	33.16	-10.34	43.5	48.74	15.05	2.23	32.86	-	-	P	V
			321	27.24	-18.76	46	37.16	19.57	3.02	32.51	-	-	P	V
			558.65	27.85	-18.15	46	30.29	26.19	4.04	32.67	-	-	P	V
			716.76	33.64	-12.36	46	34.45	27.05	4.62	32.48	-	-	P	V
			872.93	32.86	-13.14	46	31.08	29.14	5.18	32.54	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													





**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Chain				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
0+1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Karl Hou, CR Liro and Andy Yang	Temperature :	20~25°C
		Relative Humidity :	50~60%

### Note symbol

-L	Low channel location
-R	High channel location



**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Band Edge @ 3m)**

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
Chain	802.11a CH157 5785MHz	
0+1	Horizontal	Fundamental
<b>Peak</b>	<p>Site : 03CH16-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY            Condition : PEAK(LINE) 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<b>Peak</b>	<p>Site : 03CH16-HY            Condition : PEAK_BE(B4)_16-24 3m 91200_1522 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<b>Left blank</b>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
Chain	802.11a CH157 5785MHz	
0+1	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINE) 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_1522 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



**Band 4 - 5725~5850MHz**  
**WIFI 802.11a (Harmonic @ 3m)**

<b>WIFI</b>	<b>Band 4 5725~5850MHz Harmonic @ 3m</b>	
<b>Chain</b>	<b>802.11a CH157 5785MHz</b>	
<b>0+1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak</b> <b>Avg.</b>	<p>Site : 03CH16-11F          Condition : PEAK(LINE) 3m 9120D_1522 HORIZONTAL</p>	<p>Site : 03CH16-11F          Condition : PEAK(LINE) 3m 9120D_1522 VERTICAL</p>



Emission above 18GHz

WIFI 802.11a (SHF)

WIFI	5GHz WIFI	
Chain	802.11a SHF	
0+1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH16-14F Condition : PEAK(LINE) Im SHF HORN 88HA9170584 HORIZONTAL</p>	<p>Site : 03CH16-14F Condition : PEAK(LINE) Im SHF HORN 88HA9170584 VERTICAL</p>



Emission below 1GHz

WIFI 802.11a (LF)

WIFI	5GHz WIFI	
Chain	802.11a LF	
0+1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH16-11Y Condition : QP-3m-BILOG_47020406 HORIZONTAL</p>	<p>Site : 03CH16-11Y Condition : QP-3m-BILOG_47020406 VERTICAL</p>







### Appendix D. Duty Cycle Plots

Chain	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
0+1	802.11a for Chain 0	99.24	-	-	10Hz	0.03
0+1	802.11a for Chain 1	99.34	-	-	10Hz	0.03

#### MIMO <Chain 0>



#### MIMO <Chain 1>



—THE END—