

RF EXPOSURE REPORT

for

Model Number: D52.1

FCC ID: PY7-32042C

IC ID: 4170B-43153F

Prepared for : Sony Mobile Communications Inc.
Address : 4-12-3 Higashi-Shinagawa, Shinagawa-Ku, Tokyo, 140-0002, Japan

Prepared by : Shenzhen BCTC Technology Co., Ltd.
Address : No.101, Yousong Road, Longhua New District,
Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093, RSS-102, the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right]$$

* $\left[\sqrt{f(\text{GHz})} \right]$

Frequency MHz	tune up power tolerance (dBm)	Maximum Tune up output power (dBm)	max. output power(mW)	Separation distance mm	RF exposure
2402	1±1	2	1.58	5	0.49

The Max RF exposure is 0.49.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.