

TEST REPORT

Report Number: R15103618-E12

Applicant : Sony Corporation
1-7-1 Konan Minato-ku
Tokyo, 108-0075, Japan

FCC ID : PY7-46195Y

EUT Description : LTE/5G Portable Data Transmitter with BT, DTS/UNII a/b/g/n/ac/ax
and GPS

Test Standard(s) : ANSI C63.26:2015 – Conducted output power

Date Of Issue:
2024-03-27

Prepared by:
UL LLC
12 Laboratory Dr.
Research Triangle Park, NC 27709 U.S.A.
TEL: (919) 549-1400

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2024-03-25	Initial issue	Richard Jankovics
V2	2024-03-27	Removed combination list to reference manufacturer documentation.	Richard Jankovics

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS 4

2. SUMMARY OF TEST RESULTS 5

3. TEST METHODOLOGY 5

4. FACILITIES AND ACCREDITATION 6

5. DECISION RULES AND MEASUREMENT UNCERTAINTY 6

5.1. METROLOGICAL TRACEABILITY 6

5.2. DECISION RULES 6

5.3. MEASUREMENT UNCERTAINTY 6

6. EQUIPMENT UNDER TEST 7

6.1. DESCRIPTION OF EUT 7

6.2. SOFTWARE AND FIRMWARE 7

6.3. DESCRIPTION OF TEST SETUP 7

7. TEST AND MEASUREMENT EQUIPMENT 8

8. LTE DOWN-LINK CARRIER AGGREGATION 9

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Sony Corporation
 1-7-1 Konan Minato-ku
 Tokyo, 108-0075, Japan

EUT DESCRIPTION: LTE/5G Portable Data Transmitter with BT, DTS/UNII a/b/g/n/ac/ax and GPS

SERIAL NUMBER: QV77008VJP

FCC ID: PY7-46195Y

SAMPLE RECEIPT DATE: 2023-12-18

DATE TESTED: 2024-03-04 to 2024-03-23

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC KDB 941225 D05A §C.b)3)ii)	Complies

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.


This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released For
 UL LLC. By:



Dan Corona
 Operations Leader
 Consumer Technology Division
 UL Verification Services Inc.

Prepared By:



Richard Jankovics
 Staff Engineer
 Consumer Technology Division
 UL LLC

2. SUMMARY OF TEST RESULTS

This report contains data provided by the applicant which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer. Below is a list of the data provided by the customer:

- 1) Cable loss (port adapter)
- 2) Supported bands, bandwidths, modulations, power settings, supported DLCA combinations, and MPR configurations.
- 3) Worst-case BW and modulation for maximum output power for each band requiring SAR testing.

Measurements confirmed when downlink carrier aggregation is active, uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive, as specified in FCC KDB 941225 D05A §C.b)3)ii).

This report does not address SAR testing; this is a limited scope report addressing the conducted output power for downlink carrier aggregation active relative to inactive in Max power state.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with the following:

- ANSI C63.26:2015
- FCC KDB 971168 D01 v03r01: Power Meas License Digital Systems
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A LTE Rel.10 KDB Inquiry Sheet v01r02
- TCB Workshop April 2016; RF Exposure Procedures (LTE Carrier Aggregation for DL)
- TCB Workshop November 2017; RF Exposure Procedures (LTE UL/DL Carrier Aggregation SAR)
- TCB Workshop April 2018; RF Exposure Procedures (LTE DL CA SAR Test Exclusion)
- TCB Workshop April 2015; RF Exposure Procedures (Overlapping LTE Bands)

4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification # 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input checked="" type="checkbox"/>	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A	US0067	27265	825374

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
RF output power, conducted	0.45 dB (AV)
Temperature	0.57°C
Humidity	3.39%

Uncertainty figures are valid to a confidence level of 95%.

6. EQUIPMENT UNDER TEST

6.1. DESCRIPTION OF EUT

The EUT is an LTE/5G Portable Data Transmitter with BT, DTS/UNII a/b/g/n/ac/ax and GPS. This test report covers the LTE radio portion of the EUT.

The EUT supports the following LTE Bands and their antenna configurations:

LTE and 5G NR Bands	Main 1 Antenna	Main 2 Antenna	Sub Antenna	Sub-UHB Antenna	Cell 3rd Antenna	Cell 4 th Antenna
LTE Band 2	-	Y	Y (EN-DC) ¹	-	-	-
LTE Band 4	-	Y	Y (EN-DC) ¹	-	-	-
LTE Band 5	Y	-	Y	-	-	-
LTE Band 12	Y	-	Y	-	-	-
LTE Band 13	Y	-	Y	-	-	-
LTE Band 17	Y	-	Y	-	-	-
LTE Band 25	-	Y	-	-	-	-
LTE Band 30	-	Y	Y (EN-DC) ¹	-	-	-
LTE Band 41	-	Y	-	-	-	-
LTE Band 48	Y	-	-	Y	-	-
LTE Band 66	-	Y	Y (EN-DC)	-	-	-
LTE Band 71	Y	-	-	-	-	-

Notes:

1. LTE2, LTE30, and LTE66 can transmit on Sub antenna an EN-DC configuration only.

6.2. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was version 0.143..

6.3. DESCRIPTION OF TEST SETUP

Test Setup

The EUT was connected to a base station simulator and set to transmit at max power for LTE testing. All LTE bands conducted average power is obtained from the CMW500 telecommunication test sets connected together via CMWC to support higher DLCA combinations.

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment Used

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Date	Cal. Due Date
Network Analyzer	Keysight	E5063A	MY54100681	8/4/2023	8/4/2024
Base Station Simulator	R & S	CMW 500	170733	1/3/2024	1/3/2025
Base Station Simulator	R & S	CMW 500	170732	12/18/2023	12/18/2024
Base Station Simulator	R & S	CMW 500	170193	1/16/2024	1/16/2025
Base Station Simulator	R & S	CMW 500	170194	6/6/2023	6/6/2024

8. LTE DOWN-LINK CARRIER AGGREGATION

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
256 QAM	≥ 1						≤ 5

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A

Maximum Output Power (Tune-up Limit) for LTE

According to April 2015 TCB workshop, SAR test exclusion can be applied for testing overlapping LTE bands as follows:

- a) The maximum output power, including tolerance, for the smaller band must be \leq the larger band to qualify for the SAR test exclusion.
- b) The channel bandwidth and other operating parameters for the smaller band must be fully supported by the larger band.
 - LTE Band 2 (1850-1910 MHz) is covered by LTE Band 25 (1850-1915 MHz)
 - LTE Band 4 (1710-1755 MHz) is covered by LTE Band 66 (1710-1780 MHz)

Mode / Band	Antenna	Maximum output power (dBm) Max Power State
LTE Band 71	Main1	25.0
LTE Band 12	Main1	25.0
LTE Band 17	Main1	25.0
LTE Band 13	Main1	25.0
LTE Band 5	Main1	25.0
LTE Band 66 (AWS)	Main2	25.0
LTE Band 4 (AWS)	Main2	25.0
LTE Band 25 (PCS)	Main2	25.0
LTE Band 2 (PCS)	Main2	25.0
LTE Band 30	Main2	22.4
LTE Band 41 PC3	Main2	25.0
LTE Band 48	Main1	21.5

The complete list of supported combinations of the device for DL Inter-band and DL Intra-band combinations are included in the manufacturer documentation.

When carrier aggregation is limited to downlink only, uplink maximum output power (single carrier) is measured for the supported combinations of downlink carrier aggregation listed in the table below. In applying the power measurement procedures of KDB 941225 D05A and April 2018 TCB workshop for DL CA to qualify for UL SAR test exclusion, power measurement is required only for the subset in each row with the largest combination of frequency bands and CCs (far right most configuration highlighted in the table below).

5CC DL CA SISO Measured Results

Table with columns: E-UTRA CA configuration, Limitation, CC1 (UL), CC1 (DL), CC2 (DL), CC3 (DL), CC4 (DL), CC5 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Rows include configurations like CA_13A-46D-66A, CA_13A-46E, CA_13A-48A-48C-66A, etc.

6CC DL CA SISO Measured Results

Table with columns: E-UTRA CA configuration, Limitation, CC1 (UL), CC1 (DL), CC2 (DL), CC3 (DL), CC4 (DL), CC5 (DL), CC6 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Rows include configurations like CA_13A-48D-66A-66A, CA_5A-48D-66A-66A, etc.

2CC DL CA MIMO Measured Results

Table with columns: E-UTRA CA configuration, Restrictions, CC1 (UL), CC1 (DL), CC2 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Row includes CA_[4]C.

3CC DL CA MIMO Measured Results

Table with columns: E-UTRA CA configuration, Restrictions, CC1 (UL), CC1 (DL), CC2 (DL), CC3 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Rows include configurations like CA_12B-[66A], CA_13A-46A-[66A], CA_[4]D, etc.

4CC DL CA MIMO Measured Results (continued)

E-UTRA CA configuration	Restrictions	CC1 (UL)				CC1 (DL)				CC2 (DL)				CC3 (DL)				CC4 (DL)				Aggregated BW	CA Inactive (dBm)	CA Active (dBm)	Delta
		Mode	BW (MHz)	Channel	Freq (MHz)	RB Offset	BW (MHz)	Channel	Freq (MHz)	BW (MHz)	Channel	Freq (MHz)	BW (MHz)	Channel	Freq (MHz)	BW (MHz)	Channel	Freq (MHz)	BW (MHz)	Channel	Freq (MHz)				
CA_5A-5A-[66B]	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	10	66837	2150.1	10	66936	2160	40	23.22	23.19	-0.03			
		16QAM	10	132373	1750.1	1.0	10	66837	2150.1	10	66936	2160	10	2450	874	10	2600	889	40	23.57	23.56	-0.01			
CA_5A-[5A]-66B	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	10	66837	2150.1	10	66936	2160	40	23.19	23.23	0.04			
		16QAM	10	132373	1750.1	1.0	10	66837	2150.1	10	66936	2160	10	2450	874	10	2600	889	40	23.51	23.50	-0.01			
CA_5A-[5A]-[66B]	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	10	66837	2150.1	10	66936	2160	40	23.24	23.21	-0.03			
		16QAM	10	132373	1750.1	1.0	10	66837	2150.1	10	66936	2160	10	2450	874	10	2600	889	40	23.50	23.52	0.02			
CA_5A-[5A]-[66B]	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	10	66837	2150.1	10	66936	2160	40	23.21	23.25	0.04			
		16QAM	10	132373	1750.1	1.0	10	66837	2150.1	10	66936	2160	10	2450	874	10	2600	889	40	23.56	23.51	-0.05			
CA_5A]-5A-66C	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	20	66787	2145.1	20	66985	2164.9	60	23.22	23.18	-0.04			
		QPSK	20	132323	1745.1	1.50	20	66787	2145.1	20	66985	2164.9	10	2450	874	10	2600	889	60	24.20	24.23	0.03			
CA_5A-5A-[66C]	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	20	66787	2145.1	20	66985	2164.9	60	23.22	23.27	0.05			
		QPSK	20	132323	1745.1	1.50	20	66787	2145.1	20	66985	2164.9	10	2450	874	10	2600	889	60	24.18	24.23	0.05			
CA_5A]-5A]-66C	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	20	66787	2145.1	20	66985	2164.9	60	23.19	23.21	0.02			
		QPSK	20	132323	1745.1	1.50	20	66787	2145.1	20	66985	2164.9	10	2450	874	10	2600	889	60	24.22	24.25	0.03			
CA_5A]-5A]-[66C]	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	20	66787	2145.1	20	66985	2164.9	60	23.18	23.21	0.03			
		QPSK	20	132323	1745.1	1.50	20	66787	2145.1	20	66985	2164.9	10	2450	874	10	2600	889	60	24.25	24.20	-0.05			
CA_5A]-5A]-[66C]	(none)	16QAM	10	20450	829	1.0	10	2450	874	10	2600	889	20	66787	2145.1	20	66985	2164.9	60	23.20	23.24	0.04			
		QPSK	20	132323	1745.1	1.50	20	66787	2145.1	20	66985	2164.9	10	2450	874	10	2600	889	60	24.20	24.23	0.03			
CA_5B]-46C	B46 SCC Only	16QAM	10	20501	834.1	1.0	10	2501	879.1	10	2600	889	20	50692	5540.2	20	50890	5560	60	23.14	23.11	-0.03			
CA_13A-[48A]-66A-[66A]	B48 SCC Only	16QAM	10	23230	782	1.25	10	5230	751	20	55340	3560	20	55338	3579.8	20	55990	3625	70	23.71	23.76	0.05			
		QPSK	20	132072	1720	1.50	20	66536	2120	20	66786	2145	10	5230	751	20	55990	3625	70	24.03	24.05	0.02			
CA_13A-[48C]-48A	B48 SCC Only	16QAM	10	23230	782	1.25	10	5230	751	20	55340	3560	20	55538	3579.8	20	55990	3625	70	23.72	23.69	-0.03			
CA_13A-48C-[48A]	B48 SCC Only	16QAM	10	23230	782	1.25	10	5230	751	20	55340	3560	20	55538	3579.8	20	55990	3625	70	23.76	23.72	-0.04			
CA_13A-[48C]-[48A]	B48 SCC Only	16QAM	10	23230	782	1.25	10	5230	751	20	55340	3560	20	55538	3579.8	20	55990	3625	70	23.68	23.70	0.02			
CA_48C]-48A-66A	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.28	24.25	-0.03			
CA_48C-[48A]-66A	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.23	24.28	0.03			
CA_48C-48A-[66A]	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.26	24.20	-0.06			
CA_48C]-[48A]-66A	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.21	24.25	0.04			
CA_48C]-[48A]-[66A]	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.28	24.24	-0.04			
CA_48C]-[48A]-[66A]	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.26	24.26	0.00			
CA_48C]-[48A]-[66A]	B48 SCC Only	QPSK	20	132322	1745	1.50	20	66786	2145	20	55340	3560	20	55538	3579.8	20	55990	3625	80	24.23	24.25	0.02			

5CC DL CA MIMO Measured Results

Table with columns: E-UTRA CA configuration, Restrictions, CCI (UL), CCI (DL), CC2 (DL), CC3 (DL), CC4 (DL), CC5 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Rows include configurations like CA_13A-46D-[66A], CA_13A-[48A]-[48C]-[66A], etc.

5CC DL CA MIMO Measured Results (continued)

Table with columns: E-UTRA CA configuration, Restrictions, CCI (UL), CCI (DL), CC2 (DL), CC3 (DL), CC4 (DL), CC5 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Rows include configurations like CA_[5B]-30A-[66A]-66A, CA_[5B]-30A-[66A]-[66A], CA_[5A]-[48D]-[66A], etc.

6CC DL CA MIMO Measured Results

Table with columns: E-UTRA CA configuration, Restrictions, CCI (UL), CCI (DL), CC2 (DL), CC3 (DL), CC4 (DL), CC5 (DL), CC6 (DL), Aggregated BW, CA Inactive (dBm), CA Active (dBm), Delta. Rows include configurations like CA_[13A]-48D-[66A]-66A, CA_[13A]-48D-[66A]-[66A], CA_[13A]-[48D]-[66A]-66A, etc.

END OF REPORT