



MIMO Antenna-2 Power Spectral Density Measurements




Plot 7-181. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 1) – Ch. 36)




Plot 7-182. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 1) – Ch. 40)

MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
FCC ID: PY7-58692W	Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	Page 128 of 189
		EUT Type: Portable Handset	




Plot 7-183. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 1) – Ch. 48)




Plot 7-184. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 1) – Ch. 38)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 129 of 189




Plot 7-185. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 1) – Ch. 46)




Plot 7-186. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – 26 Tones (UNII Band 1) – Ch. 42)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 130 of 189




Plot 7-187. Power Spectral Density Plot MIMO ANT2 (160MHz L BW 802.11ax – 26 Tones (UNII Band 1/2A) – Ch. 50)




Plot 7-188. Power Spectral Density Plot MIMO ANT2 (160MHz L BW 802.11ax – 26 Tones (UNII Band 1/2A) – Ch. 50)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 131 of 189




Plot 7-189. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 2A) – Ch. 52)




Plot 7-190. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 2A) – Ch. 56)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 132 of 189




Plot 7-191. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 2A) – Ch. 64)




Plot 7-192. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 2A) – Ch. 54)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 133 of 189




Plot 7-193. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 2A) – Ch. 62)




Plot 7-194. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – 26 Tones (UNII Band 2A) – Ch. 58)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 134 of 189




Plot 7-195. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 100)




Plot 7-196. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 120)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 135 of 189




Plot 7-197. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 144)




Plot 7-198. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 102)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 136 of 189




Plot 7-199. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 118)




Plot 7-200. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 142)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 137 of 189




Plot 7-201. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 106)




Plot 7-202. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 122)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 138 of 189




Plot 7-203. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 138)




Plot 7-204. Power Spectral Density Plot MIMO ANT2 (160MHz L BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 114)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 139 of 189




Plot 7-205. Power Spectral Density Plot MIMO ANT2 (160MHz U BW 802.11ax – 26 Tones (UNII Band 2C) – Ch. 114)




Plot 7-206. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 3) – Ch. 149)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 140 of 189




Plot 7-207. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 3) – Ch. 157)




Plot 7-208. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – 26 Tones (UNII Band 3) – Ch. 165)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 141 of 189




Plot 7-209. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 3) – Ch. 151)




Plot 7-210. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – 26 Tones (UNII Band 3) – Ch. 159)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 142 of 189




Plot 7-213. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 40)




Plot 7-214. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 48)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 144 of 189




Plot 7-215. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 38)




Plot 7-216. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 46)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 145 of 189




Plot 7-217. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 1) – Ch. 42)




Plot 7-218. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ax – Full Tones (UNII Band 1/2A) – Ch. 50)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 146 of 189




Plot 7-219. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 52)




Plot 7-220. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 56)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 147 of 189




Plot 7-221. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 64)




Plot 7-222. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 54)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 148 of 189




Plot 7-223. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 62)




Plot 7-224. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2A) – Ch. 58)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 149 of 189




Plot 7-225. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 100)




Plot 7-226. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 120)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 150 of 189




Plot 7-227. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 144)




Plot 7-228. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 102)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 151 of 189




Plot 7-229. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 118)




Plot 7-230. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 142)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 152 of 189




Plot 7-231. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 106)




Plot 7-232. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 122)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 153 of 189




Plot 7-233. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 138)




Plot 7-234. Power Spectral Density Plot MIMO ANT2 (160MHz BW 802.11ax – Full Tones (UNII Band 2C) – Ch. 114)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 154 of 189




Plot 7-235. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 149)




Plot 7-236. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 157)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 155 of 189




Plot 7-237. Power Spectral Density Plot MIMO ANT2 (20MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 165)




Plot 7-238. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 151)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 156 of 189



Plot 7-239. Power Spectral Density Plot MIMO ANT2 (40MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 159)



Plot 7-240. Power Spectral Density Plot MIMO ANT2 (80MHz BW 802.11ax – Full Tones (UNII Band 3) – Ch. 155)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 157 of 189

7.6 Radiated Spurious Emission Measurements – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 26 Tones, 52 Tones, 106 Tones, 242 Tones, 484 Tones and 996 Tones), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-29 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-29. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5
KDB 789033 D02 v02r01 – Section G

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span}/\text{RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 158 of 189

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 159 of 189

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-29.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-29. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBµV/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBµV/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. For radiated measurements, emissions were investigated for the fully-loaded RU configuration and for all of the partially-loaded RU configurations. Among all of the available partially-loaded RU configurations, only the configuration with the worst case emissions is reported.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level [dBµV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dBµV/m] – Limit [dBµV/m]


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.6 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 160 of 189

7.6.1 MIMO Radiated Spurious Emission Measurements


26 Tones



Plot 7-241. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 26 Tones)




Plot 7-242. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 26 Tones)



Plot 7-243. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 26 Tones)


FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 161 of 189




Plot 7-244. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 162 of 189

MIMO Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-245. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 26 Tones)



Plot 7-246. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 163 of 189



MIMO Radiated Spurious Emission Measurements (26 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	V	-	-	-69.42	11.20	0.00	48.78	68.20	-19.42
* 15540.00	Average	V	-	-	-81.82	16.02	0.00	41.20	53.98	-12.78
* 15540.00	Peak	V	-	-	-69.23	16.02	0.00	53.79	73.98	-20.19
* 20720.00	Average	V	-	-	-67.56	3.16	-9.54	33.06	53.98	-20.92
* 20720.00	Peak	V	-	-	-57.45	3.16	-9.54	43.16	73.98	-30.82
25900.00	Peak	V	-	-	-57.53	4.77	-9.54	44.70	68.20	-23.50

Table 7-30. Radiated Measurements MIMO (26 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	V	-	-	-69.90	11.14	0.00	48.24	68.20	-19.96
* 15600.00	Average	V	-	-	-81.92	16.27	0.00	41.35	53.98	-12.63
* 15600.00	Peak	V	-	-	-70.19	16.27	0.00	53.08	73.98	-20.90
* 20800.00	Average	V	-	-	-66.82	3.48	-9.54	34.12	53.98	-19.86
* 20800.00	Peak	V	-	-	-56.62	3.48	-9.54	44.32	73.98	-29.66
26000.00	Peak	V	-	-	-57.28	5.16	-9.54	45.34	68.20	-22.86

Table 7-31. Radiated Measurements MIMO (26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 164 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-70.22	11.80	0.00	48.58	68.20	-19.62
* 15720.00	Average	V	-	-	-82.00	16.84	0.00	41.84	53.98	-12.14
* 15720.00	Peak	V	-	-	-70.02	16.84	0.00	53.82	73.98	-20.16
* 20960.00	Average	V	-	-	-68.28	3.47	-9.54	32.65	53.98	-21.33
* 20960.00	Peak	V	-	-	-58.35	3.47	-9.54	42.58	73.98	-31.40
26200.00	Peak	V	-	-	-56.81	4.78	-9.54	45.43	68.20	-22.77

Table 7-32. Radiated Measurements MIMO (26 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	246	224	-68.99	11.91	0.00	49.92	68.20	-18.28
* 15780.00	Average	V	-	-	-82.22	16.44	0.00	41.22	53.98	-12.76
* 15780.00	Peak	V	-	-	-70.73	16.44	0.00	52.71	73.98	-21.27
* 21040.00	Average	V	-	-	-67.93	3.53	-9.54	33.06	53.98	-20.92
* 21040.00	Peak	V	-	-	-58.08	3.53	-9.54	42.91	73.98	-31.06
26300.00	Peak	V	-	-	-57.77	4.64	-9.54	44.33	68.20	-23.87

Table 7-33. Radiated Measurements MIMO (26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 165 of 189

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10560.00	Peak	V	132	235	-69.65	11.82	0.00	49.17	68.20	-19.03
* 15840.00	Average	V	-	-	-82.08	16.25	0.00	41.17	53.98	-12.81
* 15840.00	Peak	V	-	-	-70.43	16.25	0.00	52.82	73.98	-21.16
* 21120.00	Average	V	-	-	-67.52	3.68	-9.54	33.61	53.98	-20.37
* 21120.00	Peak	V	-	-	-57.59	3.68	-9.54	43.55	73.98	-30.43
26400.00	Peak	V	-	-	-58.23	4.78	-9.54	44.01	68.20	-24.19

Table 7-34. Radiated Measurements MIMO (26 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 10640.00	Average	V	-	-	-81.53	11.45	0.00	36.92	53.98	-17.06
* 10640.00	Peak	V	-	-	-70.02	11.45	0.00	48.43	73.98	-25.55
* 15960.00	Average	V	-	-	-82.99	17.22	0.00	41.23	53.98	-12.75
* 15960.00	Peak	V	-	-	-71.09	17.22	0.00	53.13	73.98	-20.85
* 21280.00	Average	V	-	-	-67.80	3.72	-9.54	33.38	53.98	-20.60
* 21280.00	Peak	V	-	-	-58.15	3.72	-9.54	43.03	73.98	-30.95
26600.00	Peak	V	-	-	-58.02	4.72	-9.54	44.15	68.20	-24.05

Table 7-35. Radiated Measurements MIMO (26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 166 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	V	-	-	-80.66	11.86	0.00	38.20	53.98	-15.78
* 11000.00	Peak	V	-	-	-68.81	11.86	0.00	50.05	73.98	-23.93
16500.00	Peak	V	-	-	-70.29	17.48	0.00	54.19	68.20	-14.01
22000.00	Peak	V	-	-	-57.44	3.83	-9.54	43.86	68.20	-24.34
27500.00	Peak	V	-	-	-57.59	4.97	-9.54	44.84	68.20	-23.36

Table 7-36. Radiated Measurements MIMO (26 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	V	-	-	-81.32	11.99	0.00	37.67	53.98	-16.31
* 11200.00	Peak	V	-	-	-68.98	11.99	0.00	50.01	73.98	-23.97
16800.00	Peak	V	-	-	-70.40	17.76	0.00	54.36	68.20	-13.84
* 22400.00	Average	V	-	-	-67.29	3.79	-9.54	33.96	53.98	-20.02
* 22400.00	Peak	V	-	-	-57.01	3.79	-9.54	44.24	73.98	-29.74
28000.00	Peak	V	-	-	-57.78	4.94	-9.54	44.62	68.20	-23.58

Table 7-37. Radiated Measurements MIMO (26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 167 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-82.38	12.84	0.00	37.46	53.98	-16.52
* 11440.00	Peak	V	-	-	-69.51	12.84	0.00	50.33	73.98	-23.65
17160.00	Peak	V	-	-	-69.80	17.33	0.00	54.53	68.20	-13.67
* 22880.00	Average	V	-	-	-67.45	3.79	-9.54	33.80	53.98	-20.18
* 22880.00	Peak	V	-	-	-57.24	3.79	-9.54	44.01	73.98	-29.97
28600.00	Peak	V	-	-	-56.87	5.28	-9.54	45.87	68.20	-22.33

Table 7-38. Radiated Measurements MIMO (26 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	V	-	-	-82.11	12.43	0.00	37.32	53.98	-16.66
* 11490.00	Peak	V	-	-	-70.08	12.43	0.00	49.35	73.98	-24.63
17235.00	Peak	V	-	-	-69.92	17.04	0.00	54.12	68.20	-14.08
* 22980.00	Average	V	-	-	-67.94	3.79	-9.54	33.31	53.98	-20.67
* 22980.00	Peak	V	-	-	-57.58	3.79	-9.54	43.67	73.98	-30.31
28725.00	Peak	V	-	-	-58.35	5.41	-9.54	44.52	68.20	-23.68

Table 7-39. Radiated Measurements MIMO (26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 168 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-69.33	12.34	0.00	50.01	53.98	-3.97
* 11570.00	Peak	V	-	-	-81.48	12.34	0.00	37.86	73.98	-36.12
17355.00	Peak	V	-	-	-70.11	17.83	0.00	54.72	68.20	-13.48
23140.00	Peak	V	-	-	-57.53	3.75	-9.54	43.68	68.20	-24.52
28925.00	Peak	V	-	-	-58.26	5.46	-9.54	44.66	68.20	-23.54

Table 7-40. Radiated Measurements MIMO (26 Tones)


Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 4
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-82.24	12.89	0.00	37.65	53.98	-16.33
* 11650.00	Peak	V	-	-	-70.56	12.89	0.00	49.33	73.98	-24.65
17475.00	Peak	V	-	-	-68.98	17.05	0.00	55.07	68.20	-13.13
23300.00	Peak	V	-	-	-58.49	3.76	-9.54	42.74	68.20	-25.46
29125.00	Peak	V	-	-	-57.64	5.54	-9.54	45.36	68.20	-22.84


Table 7-41. Radiated Measurements MIMO (26 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 169 of 189


242 Tones



Plot 7-247. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U1 Ch. 40 – 242 Tones)




Plot 7-248. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2A Ch. 56 – 242 Tones)



Plot 7-249. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U2C Ch. 120 – 242 Tones)


FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 170 of 189




Plot 7-250. Radiated Spurious Plot above 1GHz MIMO (802.11ax – U3 Ch. 157 – 242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 171 of 189

MIMO Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-251. Radiated Spurious Plot 18GHz - 26.5GHz MIMO (802.11ax – 242 Tones)



Plot 7-252. Radiated Spurious Plot 26.5GHz - 40GHz MIMO (802.11ax – 242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 172 of 189



MIMO Radiated Spurious Emission Measurements (242 Tones)

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	V	-	-	-69.41	11.20	0.00	48.79	68.20	-19.41
* 15540.00	Average	V	-	-	-81.80	16.02	0.00	41.22	53.98	-12.76
* 15540.00	Peak	V	-	-	-69.88	16.02	0.00	53.14	73.98	-20.84
* 20720.00	Average	V	-	-	-67.88	3.16	-9.54	32.74	53.98	-21.24
* 20720.00	Peak	V	-	-	-57.77	3.16	-9.54	42.84	73.98	-31.14
25900.00	Peak	V	-	-	-57.44	4.77	-9.54	44.79	68.20	-23.41

Table 7-42. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	V	-	-	-69.78	11.14	0.00	48.36	68.20	-19.84
* 15600.00	Average	V	-	-	-81.65	16.27	0.00	41.62	53.98	-12.36
* 15600.00	Peak	V	-	-	-70.06	16.27	0.00	53.21	73.98	-20.77
* 20800.00	Average	V	-	-	-66.70	3.48	-9.54	34.24	53.98	-19.74
* 20800.00	Peak	V	-	-	-56.69	3.48	-9.54	44.24	73.98	-29.73
26000.00	Peak	V	-	-	-57.61	5.16	-9.54	45.00	68.20	-23.20

Table 7-43. Radiated Measurements MIMO (242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 173 of 189

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	-	-	-69.78	11.80	0.00	49.02	68.20	-19.18
* 15720.00	Average	V	-	-	-82.00	16.84	0.00	41.84	53.98	-12.14
* 15720.00	Peak	V	-	-	-69.95	16.84	0.00	53.89	73.98	-20.09
* 20960.00	Average	V	-	-	-68.05	3.47	-9.54	32.88	53.98	-21.10
* 20960.00	Peak	V	-	-	-57.74	3.47	-9.54	43.19	73.98	-30.79
26200.00	Peak	V	-	-	-56.79	4.78	-9.54	45.45	68.20	-22.75

Table 7-44. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	-	-	-70.18	11.91	0.00	48.73	68.20	-19.47
* 15780.00	Average	V	-	-	-82.33	16.44	0.00	41.11	53.98	-12.87
* 15780.00	Peak	V	-	-	-70.65	16.44	0.00	52.79	73.98	-21.19
* 21040.00	Average	V	-	-	-67.50	3.53	-9.54	33.49	53.98	-20.49
* 21040.00	Peak	V	-	-	-57.36	3.53	-9.54	43.63	73.98	-30.35
26300.00	Peak	V	-	-	-57.38	4.64	-9.54	44.72	68.20	-23.48

Table 7-45. Radiated Measurements MIMO (242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 174 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	V	-	-	-69.76	11.82	0.00	49.06	68.20	-19.14
* 15840.00	Average	V	-	-	-81.97	16.25	0.00	41.28	53.98	-12.70
* 15840.00	Peak	V	-	-	-70.13	16.25	0.00	53.12	73.98	-20.86
* 21120.00	Average	V	-	-	-67.15	3.68	-9.54	33.99	53.98	-19.99
* 21120.00	Peak	V	-	-	-56.76	3.68	-9.54	44.38	73.98	-29.60
* 26400.00	Peak	V	-	-	-57.41	4.78	-9.54	44.83	68.20	-23.37

Table 7-46. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	V	-	-	-81.49	11.45	0.00	36.96	53.98	-17.02
* 10640.00	Peak	V	-	-	-68.76	11.45	0.00	49.69	73.98	-24.29
* 15960.00	Average	V	-	-	-82.99	17.22	0.00	41.23	53.98	-12.75
* 15960.00	Peak	V	-	-	-71.23	17.22	0.00	52.99	73.98	-20.99
* 21280.00	Average	V	-	-	-67.43	3.72	-9.54	33.75	53.98	-20.23
* 21280.00	Peak	V	-	-	-56.98	3.72	-9.54	44.20	73.98	-29.78
* 26600.00	Peak	V	-	-	-58.21	4.72	-9.54	43.97	68.20	-24.23

Table 7-47. Radiated Measurements MIMO (242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 175 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	V	-	-	-80.76	11.86	0.00	38.10	53.98	-15.88
* 11000.00	Peak	V	-	-	-69.20	11.86	0.00	49.66	73.98	-24.32
16500.00	Peak	V	-	-	-70.05	17.48	0.00	54.43	68.20	-13.77
22000.00	Peak	V	-	-	-57.57	3.83	-9.54	43.73	68.20	-24.47
27500.00	Peak	V	-	-	-56.96	4.97	-9.54	45.46	68.20	-22.74

Table 7-48. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5600MHz
 Channel: 120

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11200.00	Average	V	-	-	-81.36	11.99	0.00	37.63	53.98	-16.35
* 11200.00	Peak	V	-	-	-69.13	11.99	0.00	49.86	73.98	-24.12
16800.00	Peak	V	-	-	-70.49	17.76	0.00	54.27	68.20	-13.93
* 22400.00	Average	V	-	-	-67.19	3.79	-9.54	34.06	53.98	-19.92
* 22400.00	Peak	V	-	-	-56.34	3.79	-9.54	44.91	73.98	-29.07
28000.00	Peak	V	-	-	-57.31	4.94	-9.54	45.08	68.20	-23.12

Table 7-49. Radiated Measurements MIMO (242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 176 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-82.27	12.84	0.00	37.57	53.98	-16.41
* 11440.00	Peak	V	-	-	-70.41	12.84	0.00	49.43	73.98	-24.55
17160.00	Peak	V	-	-	-70.11	17.33	0.00	54.22	68.20	-13.98
* 22880.00	Average	V	-	-	-67.33	3.79	-9.54	33.92	53.98	-20.06
* 22880.00	Peak	V	-	-	-57.13	3.79	-9.54	44.12	73.98	-29.85
* 28600.00	Peak	V	-	-	-56.91	5.28	-9.54	45.83	68.20	-22.37

Table 7-50. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11490.00	Average	V	-	-	-82.19	12.43	0.00	37.24	53.98	-16.74
* 11490.00	Peak	V	-	-	-70.34	12.43	0.00	49.09	73.98	-24.89
17235.00	Peak	V	-	-	-69.95	17.04	0.00	54.09	68.20	-14.11
* 22980.00	Average	V	-	-	-68.09	3.79	-9.54	33.15	53.98	-20.83
* 22980.00	Peak	V	-	-	-56.94	3.79	-9.54	44.30	73.98	-29.68
28725.00	Peak	V	-	-	-57.41	5.41	-9.54	45.46	68.20	-22.74

Table 7-51. Radiated Measurements MIMO (242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 177 of 189



Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5785MHz
 Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11570.00	Average	V	-	-	-81.42	12.34	0.00	37.92	53.98	-16.06
* 11570.00	Peak	V	-	-	-69.31	12.34	0.00	50.03	73.98	-23.95
17355.00	Peak	V	-	-	-70.19	17.83	0.00	54.64	68.20	-13.56
23140.00	Peak	V	-	-	-57.39	3.75	-9.54	43.82	68.20	-24.38
28925.00	Peak	V	-	-	-57.91	5.46	-9.54	45.01	68.20	-23.19

Table 7-52. Radiated Measurements MIMO (242 Tones)

Worst Case Mode: 802.11ax (20MHz BW)
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-82.34	12.89	0.00	37.55	53.98	-16.43
* 11650.00	Peak	V	-	-	-70.46	12.89	0.00	49.43	73.98	-24.55
17475.00	Peak	V	-	-	-69.85	17.05	0.00	54.20	68.20	-14.00
23300.00	Peak	V	-	-	-57.94	3.76	-9.54	43.28	68.20	-24.92
29125.00	Peak	V	-	-	-57.90	5.54	-9.54	45.10	68.20	-23.10

Table 7-53. Radiated Measurements MIMO (242 Tones)


FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 178 of 189

7.6.2 MIMO Antenna-1 Radiated Band Edge Measurements (20MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

106 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	53
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




Plot 7-253. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 106 Tones)




Plot 7-254. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 106 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	54
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64




Plot 7-255. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 106 Tones)




Plot 7-256. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 106Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 179 of 189

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 RU Index: 53
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Plot 7-257. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 106 Tones)



Plot 7-258. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 106 Tones)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 RU Index: 54
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Plot 7-259. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 106 Tones)


FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 180 of 189

242 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




Plot 7-260. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 242 Tones)




Plot 7-261. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 242 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	61
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64




Plot 7-262. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 242 Tones)




Plot 7-263. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 181 of 189

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100




Plot 7-264. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 242 Tones)



Plot 7-265. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 242 Tones)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 RU Index: 61
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165




Plot 7-266. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 242 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 182 of 189


7.6.3 MIMO Antenna-1 Radiated Band Edge Measurements (40MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

484 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	65
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38




Plot 7-267. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 484 Tones)




Plot 7-268. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	65
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62




Plot 7-269. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 484 Tones)




Plot 7-270. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 484 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 183 of 189

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	65
Distance of Measurements:	3 Meters
Operating Frequency:	5510MHz
Channel:	102




Plot 7-271. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 484 Tones)



Plot 7-272. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 484 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	65
Distance of Measurements:	3 Meters
Operating Frequency:	5795MHz
Channel:	159




Plot 7-273. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 484 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 184 of 189


7.6.4 MIMO Antenna-1 Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




Plot 7-274. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 996 Tones)




Plot 7-275. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58




Plot 7-276. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 996 Tones)




Plot 7-277. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 996 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 185 of 189

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5530MHz
Channel:	106




Plot 7-278. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 996 Tones)



Plot 7-279. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5775MHz
Channel:	155



Plot 7-280. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 3 – 996 Tones)


FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 186 of 189

7.6.5 MIMO Antenna-1 Radiated Band Edge Measurements (160MHz BW)


§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5250MHz
Channel:	50




Plot 7-281. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1/2A – 996 Tones)




Plot 7-282. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1/2A – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5250MHz
Channel:	50




Plot 7-283. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 1/2A – 996 Tones)




Plot 7-284. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 1/2A – 996 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 187 of 189

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5570MHz
Channel:	114



Plot 7-285. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 2C – 996 Tones)



Plot 7-286. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 2C – 996 Tones)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 188 of 189

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Sony Corporation Portable Handset FCC ID: PY7-58692W** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules.

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-11.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 189 of 189