

Report No. : FZ133144



FCC DFS TEST REPORT

FCC ID : PY7-53953L

Equipment : GSM/WCDMA/LTE/5G Phone with BT, DTS/UNII

a/b/g/n/ac/ax, GPS and NFC

Brand Name : Sony

Applicant : Sony Corporation

1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

Manufacturer : Sony Corporation

1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

Standard : FCC Part 15 Subpart E

The product was received on Apr. 27, 2021 and testing was started from May 25, 2021 and completed on May 25, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in FCC Part 15 Subpart E and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

Table of Contents

Report No.: FZ133144

His	tory of	f this test report	3
		of Test Result	
1		ral Description	
	1.1	Feature of Equipment Under Test	5
	1.2	Modification of EUT	
	1.3	Testing Site	6
	1.4	Applied Standards	
	1.5	Support Unit used in test configuration and system	6
2	Requi	rements and Parameters for DFS Test	7
	2.1	Summary of Dynamic Frequency Selection Test	7
	2.2	Applicability of DFS Requirements	8
	2.3	Interference Threshold values, Master or Client incorporating In-Service Monitoring	9
	2.4	DFS Response requirement values	9
	2.5	Short Pulse Radar Test Waveforms	10
3	Calib	ation Setup and DFS Test Results	11
	3.1	Calibration of Radar Waveform	11
	3.2	In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and	
		Non-Occupancy Period	13
4	List o	f Measuring Equipment	19

TEL: 886-3-327-3456 Page Number : 2 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

History of this test report

Report No.: FZ133144

Report No.	Version	Description	Issue Date
FZ133144	01	Initial issue of report	Jun. 11, 2021

TEL: 886-3-327-3456 Page Number : 3 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

Summary of Test Result

Report No. : FZ133144

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
		Channel Move Time	Pass	0.1564 sec
3.2	7.8.3	Channel Closing Transmission time	Pass	<200ms + 0 ms (aggregate)
		Non-Occupancy Period and Client Beacon Test	Pass	No transmission or Beacons occurred

Note: Since the product is client without radar detection function, only Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period Test are required to be performed.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Keven Cheng Report Producer: Ruby Zou

TEL: 886-3-327-3456 Page Number : 4 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

1 General Description

1.1 Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac/ax, NFC, FM Receiver, and GNSS.

Product Specification subjective to this standard		
Antenna Type <pre></pre>		
Antenna Gain	<5260 MHz ~5320 MHz> <chain 0="">: -2.6 dBi <chain 1="">: -4.9 dBi <5500 MHz ~ 5720 MHz> <chain 0="">: -3.1 dBi <chain 1="">: -6.0 dBi</chain></chain></chain></chain>	

Report No. : FZ133144

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

EUT Information List				
HW Version	SW Version	S/N	Performed Test Item	
A	0.325	QV7200637P	DFS	

Note:

- 1. Above EUT list used are electrically identical per declared by manufacturer.
- 2. For other wireless features of this EUT, test report will be issued separately.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

TEL: 886-3-327-3456 Page Number : 5 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

1.3 Testing Site

Test Site Sporton International Inc. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No. DFS02-HY	

Report No. : FZ133144

1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
- FCC KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. The TAF code is not including all the FCC KDB listed without accreditation

1.5 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	HW / FW Version	Power Cord
1.	WLAN AP	ASUS	RT-AX88U	MSQ-RTAXHP00	FW: 3.0.0.4.384_4730-g8 g74d3c	Unshielded, 1.8 m
2.	Notebook	acer	N15C1	PPD-QCNFA435	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

TEL: 886-3-327-3456 Page Number : 6 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

2 Requirements and Parameters for DFS Test

2.1 Summary of Dynamic Frequency Selection Test

Bandwidth and Channel	Test Items	Limit			
	160MHz 5570MHz (CH114)				
	Channel Move Time	10 sec			
160Mz CH114 5570MHz	Channel Closing Transmission time	200 ms + aggregate of 60 ms over remaining 10 s period			
	Non-Occupancy Period and Client Beacon Test	30 minutes			

Report No.: FZ133144

TEL: 886-3-327-3456 Page Number : 7 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

2.2 Applicability of DFS Requirements

EUT is client and operates as client without radar detection function.

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

	Operational Mode		
Requirement	Master	Client Without Radar Detection	Client With Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Report No. : FZ133144

Table 2: Applicability of DFS requirements during normal operation

	Operational Mode		
Requirement	Master	Client Without Radar Detection	Client With Radar Detection
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes
Client Beacon Test	N/A	Yes	Yes

	Operational Mode		
Additional requirements for devices with multiple bandwidth modes	Master or Client With Radar Detection	Client Without Radar Detection	
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required	
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link	
All other tests	Any single BW mode	Not required	

Note

Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

TEL: 886-3-327-3456 Page Number: 8 of 19
FAX: 886-3-328-4978 Issued Date: Jun. 11, 2021

2.3 Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes 1 and 2)
≥ 200 milliwatt	-64 dBm
< 200 milliwatt	-62 dBm

Report No. : FZ133144

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

The radar *Detection Threshold*, lowest antenna gain is the parameter of Interference *radar DFS* detection threshold, The Interference *Detection Threshold* is the (-62dBm) + (0) [dBi]+ 1 dB= -61 dBm.

2.4 DFS Response requirement values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the 99% power bandwidth
	See Note 3.

Note 1: The instant that the *Channel Move Time* and the *Channel Closing Transmission Time* begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar *Burst* generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

Note 2: The *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the *U-NII Detection Bandwidth* detection test, radar type 0 is used and for each frequency step the minimum percentage of detection is 90%. Measurements are performed with no data traffic.

TEL: 886-3-327-3456 Page Number : 9 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

2.5 Short Pulse Radar Test Waveforms

As the EUT is a Client Device with no Radar Detection, only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time.

Report No. : FZ133144

Radar Type	Pulse Width (µsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	60%	30
1	1	Test A Test B	Roundup $ \begin{bmatrix} \left(\frac{1}{360}\right). \\ \left(\frac{19 \cdot 10^6}{PRI_{\mu sec}}\right) \end{bmatrix} $	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggrega	Aggregate (Radar Types 1-4)			80%	120

Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μ sec, with a minimum increment of 1 μ sec, excluding PRI values selected in Test A

A minimum of 30 unique waveforms are required for each of the short pulse radar types 2 through 4. For short pulse radar type 1, the same waveform is used a minimum of 30 times. If more than 30 waveforms are used for short pulse radar types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms.

If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

The aggregate is the average of the percentage of successful detections of short pulse radar types 1-4.

TEL: 886-3-327-3456 Page Number : 10 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3 Calibration Setup and DFS Test Results


3.1 Calibration of Radar Waveform

3.1.1 Radar Waveform Calibration Procedure

The Interference Radar Detection Threshold Level is (-62dBm) + (0) [dBi]+ 1 dB= -61dBm that had been taken into account the output power range and antenna gain. The following equipment setup was used to calibrate the radiated Radar Waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the Master or Client Device. The spectrum analyzer was switched to the zero span (Time Domain) at the frequency of the Radar Waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz to measure the type 0 radar waveform. The spectrum analyzer had offset to compensate and RF cable loss. The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was (-62dBm) + (0) [dBi]+ 1 dB= -61 dBm. Capture the spectrum analyzer plots on short pulse radar waveform.

Report No.: FZ133144

3.1.2 Conducted Setup




3.1.3 Calibration Deviation

There is no deviation with the original standard.

TEL: 886-3-327-3456 Page Number : 11 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3.1.4 Radar Waveform Calibration Result



Report No. : FZ133144

TEL: 886-3-327-3456 Page Number : 12 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3.2 In-Service Monitoring: Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period

Report No. : FZ133144

3.2.1 Limit of In-Service Monitoring

The EUT has In-Service Monitoring function to continuously monitor the radar signals, If radar is detected, it must leave the channel (Shutdown). The Channel Move Time to cease all transmissions on the current Channel upon detection of a Radar Waveform above the DFS Detection Threshold within 10 sec. The total duration of *Channel Closing Transmission Time* is comprised of 200 milliseconds starting at the beginning of the *Channel Move Time* plus any additional intermittent control signals required to facilitate *Channel* changes (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Non-Occupancy Period time is 30 minute during which a Channel will not be utilized after a Radar Waveform is detected on that Channel. The non-associated Client Beacon Test is during the 30 minutes observation time. The EUT should not make any transmissions in the DFS band after EUT power up.

TEL: 886-3-327-3456 Page Number : 13 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3.2.2 Test Procedures

1. The radar pulse generator is setup to provide a pulse at frequency that the Master and Client are operating. A type 0 radar pulse with a 1us pulse width and a 1428 us PRI is used for the testing.

Report No. : FZ133144


- 2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62dBm at the antenna of the Master device.
- 3. A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- 4. A U-NII device operating as a Client Device will associate with the Master at Channel. The MPEG file "TestFile.mpg" specified by the FCC is streamed from the "file computer" through the Master to the Client Device and played in full motion video using Media Player Classic Ver. 6.4.8.6 in order to properly load the network for the entire period of the test.
- 5. When a radar Burst with a level equal to the DFS Detection Threshold + 1dB is generated on the Operating Channel of the U-NII device. At time T0 the Radar Waveform generator sends a Burst of pulse of the radar waveform at Detection Threshold + 1dB.
- 6. Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the EUT during the observation time (Channel Move Time). One 12 seconds plot is reported for the Short Pulse Radar Types 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- 7. Measurement of the aggregate duration of the Channel Closing Transmission Time method. With the spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: Dwell (0.4ms)= S (12000ms) / B (30000); where Dwell is the dwell time per spectrum analyzer sampling bin, S is the sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: C (ms)= N X Dwell (0.4 ms); where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.
- 8. Measure the EUT for more than 30 minutes following the channel move time to verify that no transmissions or beacons occur on this Channel.
- 9. The test frequency, bandwidth as following table:

BW / Channel
160MHz/5570MHz

TEL: 886-3-327-3456 Page Number : 14 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3.2.3 Test Setup

Conducted Setup Photo



Report No.: FZ133144

3.2.4 Test Deviation

There is no deviation with the original standard.

TEL: 886-3-327-3456 Page Number : 15 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3.2.5 Result of Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test

Test Mode :	Client without radar detection	Temperature :	24.3 ℃
Test Engineer :	Amber Cheng	Relative Humidity :	41.7%

Report No. : FZ133144


BW / Channel	Test Item	Test Result	Limit	Pass/Fail
4C0MII-/	Channel Move Time	0.1564 s	< 10s	Pass
160MHz/ 5570MHz	Channel Closing Transmission Time	200ms + 0 ms	< 260ms	Pass
	Non-Occupancy Period	≥ 30	≥ 30 min	Pass

Note: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 seconds period. The aggregate duration of control signals will not count quiet periods in between transmissions.

TEL: 886-3-327-3456 Page Number : 16 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021


3.2.6 Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period for Client Beacon Test Plots

Report No. : FZ133144




TEL: 886-3-327-3456 Page Number : 17 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

3.2.7 Data Traffic and Noise Floor Plots



Report No.: FZ133144



TEL: 886-3-327-3456 Page Number : 18 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark	
Signal Generator	Rohde & Schwarz	SMJ100A	101375	100kHz~6GHz	Jan. 15, 2021	May 25, 2021	Jan. 14, 2022	DFS (DFS02-HY)	
Spectrum Analyzer	Rohde & Schwarz	FSV3044	101048	10Hz~44GHz	Apr. 20, 2021	May 25, 2021	Apr. 19, 2022	DFS (DFS02-HY)	
Power Divider	MVE	MVE8546	A300448	0.5GHz-6GHz	Calibration from System	May 25, 2021	Calibration from System	DFS (DFS02-HY)	
Power Divider	MVE	MVE8438	A702508	0.5GHz-6GHz	Calibration from System	May 25, 2021	Calibration from System	DFS (DFS02-HY)	
Power Divider	Woken	SMA 4Way Power Divider	0120A040560 02D	0.5-6GHz	Calibration from System	May 25, 2021	Calibration from System	DFS (DFS02-HY)	
Power Divider	Woken	3Way SMA Power Divider Rated to 20W	STI08-0010(# 2)	2GHz-8GHz	Calibration from System	May 25, 2021	Calibration from System	DFS (DFS02-HY)	
RF Cable	MTJ Cooperstion	SBF405	MTJ-30cm-04	30 kHz~18GHz	Calibration from System	May 25, 2021	Calibration	DFS	
	Cooperstion				Trom Cyclom		from System	(DFS02-HY)	
RF Cable	MTJ Cooperstion	SBF405	MTJ-30cm-05	30 kHz~18GHz	Calibration from System	May 25, 2021	Calibration from System	DFS (DFS02-HY)	
RF Cable	Woken	S05(100cm)	161202-02	30 kHz~18GHz	Calibration from System	May 25, 2021	Calibration	DFS	
					,		from System	(DFS02-HY)	
RF Cable	Woken	S05(100cm)	161202-03	30 kHz~18GHz	Calibration from System	May 25, 2021	Calibration from System	DFS (DFS02-HY)	
DE Oakla	Woken	205/400	C0E(100cm)	404000.04	00.111 40.011	Calibration	M 05, 0004	Calibration	DFS
RF Cable		S05(100cm)	161202-04	30 kHz~18GHz	from System	May 25, 2021	from System	(DFS02-HY)	
RF Cable	Woken	S05(100cm)	161202-05	30 kHz~18GHz	Calibration from System	May 25, 2021	Calibration	DFS	
RF Cable							from System	(DFS02-HY)	
RF Cable	Woken	S05(100cm)	161202-06	30 kHz~18GHz	Calibration from System	May 25, 2021	Calibration	DFS	
							from System	(DFS02-HY)	
RF Cable	Woken	Woken S05(100cm) 10	161202-07	30 kHz~18GHz	Calibration	May 05, 0004	Calibration	DFS	
KF Cable		vvoken	MOVELL 20	200(1000III)	101202 07	00 KI 12~ 10G112	from System	May 25, 2021	from System

Report No.: FZ133144

_____THE END____

TEL: 886-3-327-3456 Page Number : 19 of 19
FAX: 886-3-328-4978 Issued Date : Jun. 11, 2021