



FCC Test Report

APPLICANT : Sony Mobile Communications Inc.
EQUIPMENT : GSM/WCDMA/LTE Phone+Bluetooth, DTS/UNII
a/b/g/n and NFC
BRAND NAME : Sony
FCC ID : PY7-56331Y
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : FCC Class B personal computers and peripherals

The product was received on May 01, 2017 and testing was completed on Jul. 14, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Louis Wu / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : PY7-56331Y

Page Number : 1 of 25

Report Issued Date : Jul. 14, 2017

Report Version : Rev. 01

Report Template No.: BU5-FD15B Version 1.3



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Modification of EUT 6

 1.5. Test Location 7

 1.6. Applicable Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 9

 2.3. Support Unit used in test configuration and system 10

 2.4. EUT Operation Test Setup 10

3. TEST RESULT 11

 3.1. Test of AC Conducted Emission Measurement 11

 3.2. Test of Radiated Emission Measurement 17

4. LIST OF MEASURING EQUIPMENT 24

5. UNCERTAINTY OF EVALUATION 25



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC742209-01	Rev. 01	Initial issue of report	Jul. 14, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 12.00 dB at 0.158 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 10.73 dB at 32.430 MHz



1. General Description

1.1. Applicant

Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

1.2. Manufacturer

Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

1.3. Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n, NFC, and GPS

Product Specification subjective to this standard	
Antenna Type	WWAN: C-feed Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS/Glonass: PIFA Antenna NFC: Loop Antenna

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.32	RQ3004VXE6	Conducted Emission Radiated Spurious Emission



Accessory List	
Earphone 1	Model No. : MH410c
	S/N : 1632A86600000E0
Earphone 2	Model No. : MH410c
	S/N : N/A
USB Cable	Model No. : UCB20
	S/N : 1625A9100003A98

Note:

1. Above EUT list and accessory list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test.
3. For other wireless features of this EUT, test report will be issued separately.

1.4. Modification of EUT

No modifications are made to the EUT during all test items.



1.5. Test Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	CO05-HY	03CH06-HY

1.6. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. For FCC 15 Subpart B - Unintentional Radiators, device supporting USB interface or similar peripherals (defined as the Section 15.3 (r) Peripheral device) acting as a peripheral for personal computers shall be authorized as “The Class B personal computers and peripherals” per the Section 15.101 (a) Equipment authorization of unintentional radiators.
3. For other Unintentional Radiators features of this EUT, test reports are be issued separately.
Per the Note of the Section 15.101, when device supports features (USB, FM Radio, digital devices...etc) more than one category of authorization, type of authorization shall be appropriately chosen for FCC 15B compliance rule, and the Section 15.101 (b), only those receivers that operate (tune) within the frequency range of 30-960 MHz, CB receivers and radar detectors are subject to the authorizations shown in paragraph (a) of the Section 15.101. However, receivers indicated as being subject to Declaration of Conformity that are contained within a transceiver, the transmitter portion of which is subject to certification, shall be authorized under the verification procedure.



2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 1
	Mode 2: Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 2
Radiated Emissions	Mode 1: Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 1
	Mode 2: Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 2

Remark:Data Link with Notebook means data application transferred mode between EUT and Notebook.

2.2. Connection Diagram of Test System



Test Setup									
No.	Setup Peripherals	Connection Type	Test Mode						
			1	2	-	-	-	-	-
C1	Notebook	USB cable	X	X					
C1-2	Music Player	USB Cable to C1	X	X					
C1-3	AP Router	RJ-45 Cable to C1	X	X					
C2	Earphone	Earphone jack	X	X					
C3	SD card	SD I/O interface without cable	X	X					



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Music Player	N/A	N/A	N/A	N/A	N/A
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.4. EUT Operation Test Setup

The data application (each file size is greater than 30Mbytes) is continuously transferred between the EUT and Notebook connected via USB cable, while Flight mode.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	52~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 1		



Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	51.8	Off	L1	19.5	13.8	65.6
0.198000	49.9	Off	L1	19.5	13.8	63.7
0.254000	40.9	Off	L1	19.5	20.7	61.6
0.582000	35.1	Off	L1	19.5	20.9	56.0
3.718000	36.3	Off	L1	19.6	19.7	56.0
5.974000	42.0	Off	L1	19.6	18.0	60.0
15.862000	32.4	Off	L1	19.7	27.6	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	38.6	Off	L1	19.5	17.0	55.6
0.198000	37.4	Off	L1	19.5	16.3	53.7
0.254000	26.2	Off	L1	19.5	25.4	51.6
0.582000	24.8	Off	L1	19.5	21.2	46.0
3.718000	29.1	Off	L1	19.6	16.9	46.0
5.974000	35.6	Off	L1	19.6	14.4	50.0
15.862000	23.7	Off	L1	19.7	26.3	50.0



Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	52~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 1		



Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	53.6	Off	N	19.5	12.0	65.6
0.198000	49.7	Off	N	19.5	14.0	63.7
0.262000	37.3	Off	N	19.5	24.1	61.4
0.574000	37.9	Off	N	19.5	18.1	56.0
3.814000	36.7	Off	N	19.6	19.3	56.0
6.486000	41.6	Off	N	19.6	18.4	60.0
15.646000	34.0	Off	N	19.8	26.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	42.9	Off	N	19.5	12.7	55.6
0.198000	37.7	Off	N	19.5	16.0	53.7
0.262000	27.3	Off	N	19.5	24.1	51.4
0.574000	26.6	Off	N	19.5	19.4	46.0
3.814000	29.2	Off	N	19.6	16.8	46.0
6.486000	35.8	Off	N	19.6	14.2	50.0
15.646000	23.9	Off	N	19.8	26.1	50.0



Test Mode :	Mode 2	Temperature :	23~24°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	52~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 2		



Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.198000	49.7	Off	L1	19.5	14.0	63.7
0.270000	35.7	Off	L1	19.5	25.4	61.1
0.422000	33.3	Off	L1	19.5	24.1	57.4
0.622000	30.7	Off	L1	19.5	25.3	56.0
3.814000	38.5	Off	L1	19.6	17.5	56.0
6.222000	42.3	Off	L1	19.6	17.7	60.0
15.446000	31.5	Off	L1	19.7	28.5	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.198000	31.5	Off	L1	19.5	22.2	53.7
0.270000	26.2	Off	L1	19.5	24.9	51.1
0.422000	19.5	Off	L1	19.5	27.9	47.4
0.622000	22.8	Off	L1	19.5	23.2	46.0
3.814000	28.0	Off	L1	19.6	18.0	46.0
6.222000	35.8	Off	L1	19.6	14.2	50.0
15.446000	23.2	Off	L1	19.7	26.8	50.0



Test Mode :	Mode 2	Temperature :	23~24°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	52~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 2		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	50.6	Off	N	19.5	15.4	66.0
0.198000	48.6	Off	N	19.5	15.1	63.7
0.254000	40.8	Off	N	19.5	20.8	61.6
0.590000	37.7	Off	N	19.5	18.3	56.0
3.774000	38.3	Off	N	19.6	17.7	56.0
6.022000	43.0	Off	N	19.6	17.0	60.0
15.838000	33.5	Off	N	19.8	26.5	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	38.9	Off	N	19.5	17.1	56.0
0.198000	37.2	Off	N	19.5	16.5	53.7
0.254000	26.4	Off	N	19.5	25.2	51.6
0.590000	26.1	Off	N	19.5	19.9	46.0
3.774000	29.5	Off	N	19.6	16.5	46.0
6.022000	36.1	Off	N	19.6	13.9	50.0
15.838000	22.5	Off	N	19.8	27.5	50.0



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.2.4. Test Setup of Radiated Emission


For radiated emissions from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz




For radiated emissions above 18GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	Temperature :	22~25°C
Test Engineer :	Daniel Lee	Relative Humidity :	51~55%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 1		




Site : 03CH06-HY
 Condition : FCC CLASS-B__ 1m 9120D_1156_160817 HORIZONTAL

Power : From System

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	136.65	24.57	-18.93	43.50	36.75	17.51	2.11	31.80	---	---	Peak
2	173.64	27.98	-15.52	43.50	42.53	15.20	2.03	31.78	---	---	Peak
3	221.97	32.33	-13.67	46.00	46.68	15.35	2.06	31.76	---	---	Peak
4	666.10	33.13	-12.87	46.00	35.45	26.44	3.33	32.09	---	---	Peak
5	880.30	31.92	-14.08	46.00	30.99	29.21	3.36	31.64	---	---	Peak
6	944.00	33.22	-12.78	46.00	30.48	30.81	3.09	31.16	100	80	Peak
7	1958.00	42.38	-31.62	74.00	70.50	26.56	6.31	60.99	---	---	Peak
8	4806.00	41.63	-32.37	74.00	58.70	31.46	11.01	59.54	---	---	Peak
9	6646.00	44.69	-29.31	74.00	55.95	35.82	12.26	59.34	---	---	Peak
10	8866.00	46.56	-27.44	74.00	52.21	38.21	14.39	58.25	---	---	Peak
11	10668.00	47.36	-26.64	74.00	49.62	41.00	14.53	57.79	---	---	Peak
12	12602.00	48.15	-25.85	74.00	51.26	39.94	15.54	58.59	---	---	Peak
13	17919.00	48.82	-25.18	74.00	42.11	48.93	15.06	57.28	100	0	Peak
14	27888.00	46.98	-36.56	83.54	73.20	0.00	28.08	54.30	---	---	Peak
15	29388.00	47.83	-35.71	83.54	73.33	0.00	28.80	54.30	---	---	Peak



Test Mode :	Mode 1	Temperature :	22~25°C
Test Engineer :	Daniel Lee	Relative Humidity :	51~55%
Test Distance :	3m	Polarization :	Vertical
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 1		




Site : 03CH06-HY
 Condition : FCC CLASS-B__ 1m SHF-EHF HORN VERTICAL
 Power : From System

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	32.43	29.27	-10.73	40.00	36.49	22.71	1.91	31.84	100	56 Peak	
2	173.91	31.56	-11.94	43.50	46.11	15.20	2.03	31.78	---	---	Peak
3	201.72	30.35	-13.15	43.50	45.27	14.90	1.95	31.77	---	---	Peak
4	511.40	31.91	-14.09	46.00	36.72	24.16	2.96	31.93	---	---	Peak
5	840.40	31.59	-14.41	46.00	30.64	29.44	3.32	31.81	---	---	Peak
6	941.90	33.21	-12.79	46.00	30.51	30.78	3.10	31.18	---	---	Peak
7	1944.00	47.47	-26.53	74.00	75.67	26.56	6.23	60.99	---	---	Peak
8	3126.00	43.33	-30.67	74.00	67.85	28.86	7.95	61.33	---	---	Peak
9	6766.00	44.54	-29.46	74.00	55.96	36.01	11.86	59.29	---	---	Peak
10	8714.00	46.70	-27.30	74.00	52.08	38.33	14.35	58.06	---	---	Peak
11	10700.00	46.78	-27.22	74.00	48.90	41.00	14.60	57.72	---	---	Peak
12	11394.00	48.85	-25.15	74.00	47.49	42.15	15.82	56.61	100	0 Peak	
13	17946.00	47.60	-26.40	74.00	41.90	47.90	15.09	57.29	---	---	Peak
14	27000.00	46.69	-36.85	83.54	34.39	39.70	26.90	54.30	---	---	Peak
15	28788.00	47.82	-35.72	83.54	33.18	40.13	28.85	54.34	---	---	Peak



Test Mode :	Mode 2	Temperature :	22~25°C
Test Engineer :	Daniel Lee	Relative Humidity :	51~55%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 2		




Site : 03CH06-HY
 Condition : FCC CLASS-B 3m 9120D_1156_160817 HORIZONTAL

Power : From System
 Memo : Mode 2
 : NB to SD

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	135.84	25.45	-18.05	43.50	37.64	17.51	2.10	31.80	---	---	Peak
2	176.34	27.62	-15.88	43.50	42.35	15.04	2.01	31.78	---	---	Peak
3	226.02	34.26	-11.74	46.00	48.18	15.76	2.08	31.76	100	114	Peak
4	511.40	34.02	-11.98	46.00	38.83	24.16	2.96	31.93	---	---	Peak
5	905.50	32.07	-13.93	46.00	30.49	29.73	3.36	31.51	---	---	Peak
6	952.40	34.12	-11.88	46.00	31.20	30.96	3.05	31.09	---	---	Peak
7	1898.00	42.94	-31.06	74.00	71.35	26.42	6.15	60.98	---	---	Peak
8	4814.00	41.14	-32.86	74.00	58.21	31.46	11.01	59.54	---	---	Peak
9	6488.00	44.82	-29.18	74.00	56.43	35.57	12.21	59.39	---	---	Peak
10	8734.00	47.01	-26.99	74.00	52.42	38.31	14.35	58.07	---	---	Peak
11	10638.00	47.24	-26.76	74.00	49.67	41.00	14.46	57.89	---	---	Peak
12	12578.00	47.57	-26.43	74.00	50.75	39.85	15.54	58.57	100	0	Peak



Test Mode :	Mode 2	Temperature :	22~25°C
Test Engineer :	Daniel Lee	Relative Humidity :	51~55%
Test Distance :	3m	Polarization :	Vertical
Function Type :	Flight Mode + USB Cable (Data Link with Notebook) + Battery + Earphone 2		



Site : 03CH06-HY
 Condition : FCC CLASS-B 3m 9120D_1156_160817 VERTICAL

Power : From System
 Memo : Mode 2
 : NB to SD

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	32.43	29.19	-10.81	40.00	36.41	22.71	1.91	31.84	100	300	Peak
2	176.61	29.71	-13.79	43.50	44.45	15.04	2.00	31.78	---	---	Peak
3	194.70	30.54	-12.96	43.50	45.55	14.81	1.95	31.77	---	---	Peak
4	511.40	31.14	-14.86	46.00	35.95	24.16	2.96	31.93	---	---	Peak
5	841.80	31.74	-14.26	46.00	30.78	29.44	3.32	31.80	---	---	Peak
6	942.60	33.29	-12.71	46.00	30.56	30.80	3.10	31.17	---	---	Peak
7	1852.00	47.24	-26.76	74.00	75.86	26.28	6.07	60.97	---	---	Peak
8	3054.00	44.49	-29.51	74.00	68.98	29.00	7.82	61.31	---	---	Peak
9	6818.00	44.73	-29.27	74.00	56.18	36.10	11.72	59.27	---	---	Peak
10	8754.00	46.11	-27.89	74.00	51.44	38.30	14.48	58.11	---	---	Peak
11	10600.00	47.50	-26.50	74.00	50.07	41.00	14.39	57.96	---	---	Peak
12	11438.00	48.35	-25.65	74.00	46.73	42.30	15.88	56.56	100	0	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 28, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	May 28, 2017	Aug. 29, 2017	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	May 02, 2017	May 28, 2017	May 01, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	May 28, 2017	Nov. 28, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 06, 2016	May 28, 2017	Dec. 05, 2017	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 05, 2017	May 28, 2017	Jan. 04, 2018	Conduction (CO05-HY)
Test Software	N/A	EMC32	8.40.0	N/A	N/A	May 28, 2017	N/A	Conduction (CO05-HY)
Bilog Antenna	Schaffner	CBL6111C&N-6-06	2725&AT-N0601	30MHz~1GHz	Oct. 15, 2016	May 31, 2017	Oct. 14, 2017	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Dec. 29, 2016	May 31, 2017	Dec. 28, 2017	Radiation (03CH06-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 17, 2016	Jul. 14, 2017	Oct. 16, 2017	Radiation (03CH06-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1156	1GHz~18GHz	Aug. 05, 2016	May 31, 2017	Aug. 04, 2017	Radiation (03CH06-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 08, 2016	May 31, 2017~ Jul. 14, 2017	Nov. 07, 2017	Radiation (03CH06-HY)
Preamplifier	SONOMA	310N	186713	9kHz~1GHz	Apr. 25, 2017	May 31, 2017	Apr. 25, 2018	Radiation (03CH06-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1850117	1GHz ~ 18GHz	Apr. 25, 2017	May 31, 2017	Apr. 24, 2018	Radiation (03CH06-HY)
Preamplifier	MITEQ	TTA 1840-35-HG	1887435	18GHz~40GHz	Oct. 13, 2016	May 31, 2017~ Jul. 14, 2017	Oct. 12, 2017	Radiation (03CH06-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524 MY283184	30MHz~1GHz	Sep. 30, 2016	May 31, 2017	Sep. 29, 2017	Radiation (03CH06-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 MY28419/4M Y28654/4	9KHz~40GHz	Sep. 12, 2016	May 31, 2017~ Jul. 14, 2017	Sep. 11, 2017	Radiation (03CH06-HY)
Controller	INN-CO	EM1000	060782	Control Turn table & Ant Mast	N/A	May 31, 2017~ Jul. 14, 2017	N/A	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF780208212	1m~4m	N/A	May 31, 2017~ Jul. 14, 2017	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0-360 degree	N/A	May 31, 2017~ Jul. 14, 2017	N/A	Radiation (03CH06-HY)
Hygrometer	WISEWIND	410	BU5004	N/A	Mar. 20, 2017	May 31, 2017~ Jul. 14, 2017	Mar. 19, 2018	Radiation (03CH06-HY)
Test Software	Audix	E3	6.2009-8-24	N/A	N/A	May 31, 2017~ Jul. 14, 2017	N/A	Radiation (03CH06-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.90
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 30000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.70
---	------