

APPENDIX E: TEST SEQUENCES

- 1. Test sequence is generated based on below parameters of the DUT:
 - a. Measured maximum power (P_{max})
 - b. Measured Tx_power_at_SAR_design_target (Plimit)
 - c. Reserve_power_margin (dB)
 - P_{reserve} (dBm) = measured P_{limit} (dBm) Reserve_power_margin (dB)
 - d. SAR_time_window (100s for FCC)
- Test Sequence 1 Waveform:

Based on the parameters above, the Test Sequence 1 is generated with one transition between high and low Tx powers. Here, high power = P_{max} ; low power = P_{max} /2, and the transition occurs after 80 seconds at high power P_{max} . As long as the power enforcement is taking into effective during one 100s/60s time window, the validation test with this defined test sequence 1 is valid, otherwise, select other radio configuration (band/DSI within the same technology group) having lower Plimit for this test. The Test sequence 1 waveform is shown below:




Figure E-1 Test sequence 1 waveform

FCC ID: PY7-57325M	PART 2 RF EXPOSURE EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type:		APPENDIX E:
Portable Handset		Page 1 of 3

© 2022 Element **REV 1.0**



3. Test Sequence 2 Waveform:

Based on the parameters described above, the Test Sequence 2 is generated as described in Table E-1, which contains two 170 second-long sequences (yellow and green highlighted rows) that are mirrored around the center row of 20s, resulting in a total duration of 360 seconds:

Table E-1
Test Sequence 2

Time duration (seconds)	dB relative to P _{limit} or P _{reserve}
<mark>15</mark>	P _{reserve} – 2
<mark>20</mark>	P _{limit}
<mark>20</mark>	$(P_{limit} + P_{max})/2$ averaged in mW and rounded to nearest 0.1 dB step
10	P _{reserve} – 6
<mark>20</mark>	P _{max}
<mark>15</mark>	P _{limit}
<mark>15</mark>	P _{reserve} – 5
<mark>20</mark>	P _{max}
<mark>10</mark>	P _{reserve} – 3
<mark>15</mark>	P _{limit}
<mark>10</mark>	P _{reserve} – 4
20	$(P_{limit} + P_{max})/2$ averaged in mW and rounded to nearest 0.1 dB step
10	P _{reserve} – 4
<mark>15</mark>	P _{limit}
<mark>10</mark>	Preserve - 3
<mark>20</mark>	P _{max}
<mark>15</mark>	P _{reserve} – 5
<mark>15</mark>	P _{limit}
<mark>20</mark>	P _{max}
<mark>10</mark>	P _{reserve} – 6
20	$(P_{limit} + P_{max})/2$ averaged in mW and rounded to nearest 0.1 dB step
20	Plimit
15	P _{reserve} – 2

FCC ID: PY7-57325M	PART 2 RF EXPOSURE EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type:		APPENDIX E:
Portable Handset		Page 2 of 3

© 2022 Element REV 1.0



The Test Sequence 2 waveform is shown in Figure E-2.




Figure E-2
Test sequence 2 waveform

FCC ID: PY7-57325M	PART 2 RF EXPOSURE EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type:		APPENDIX E:
Portable Handset		Page 3 of 3

© 2022 Element REV 1.0 04/06/2020