

**PART 27 MEASUREMENT REPORT**

**Applicant Name:**

Sony Corporation  
1-7-1 Konan Minato-ku  
Tokyo, 108-0075  
Japan

**Date of Testing:**

7/14/2022 - 7/28/2022

**Test Report Issue Date:**

7/28/2022

**Test Site/Location:**

Element lab., Columbia, MD, USA

**Test Report Serial No.:**

1M2207200079-04.PY7

<b>FCC ID:</b>	<b>PY7-58692W</b>
<b>Applicant Name:</b>	<b>Sony Corporation</b>

**Application Type:**

Certification

**EUT Type:**

Portable Handset

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part:**

27

**Test Procedure(s):**

ANSI C63.26-2015, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



**RJ Ortanez**  
Executive Vice President



<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 1 of 40

## TABLE OF CONTENTS

1.0	INTRODUCTION .....	4
1.1	Scope .....	4
1.2	Element Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description .....	5
2.2	Device Capabilities.....	5
2.3	Test Configuration .....	5
2.4	Software and Firmware .....	5
2.5	EMI Suppression Device(s)/Modifications .....	5
3.0	DESCRIPTION OF TESTS .....	6
3.1	Evaluation Procedure .....	6
3.2	Radiated Power and Radiated Spurious Emissions .....	6
4.0	MEASUREMENT UNCERTAINTY .....	7
5.0	TEST EQUIPMENT CALIBRATION DATA .....	8
6.0	SAMPLE CALCULATIONS .....	9
7.0	TEST RESULTS .....	10
7.1	Summary.....	10
7.2	Occupied Bandwidth .....	11
7.3	Spurious and Harmonic Emissions at Antenna Terminal .....	18
7.4	Band Edge Emissions at Antenna Terminal .....	24
7.5	Radiated Power (EIRP).....	29
7.6	Radiated Spurious Emissions Measurements.....	32
7.7	Frequency Stability / Temperature Variation .....	38
8.0	CONCLUSION.....	40

<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 2 of 40

## PART 27 MEASUREMENT REPORT

Mode	Bandwidth	Modulation	Tx Frequency Range [MHz]	EIRP		Emission Designator
				Max. Power [W]	Max. Power [dBm]	
LTE Band 41(PC3)	20 MHz	QPSK	2506.0 - 2680.0	0.059	17.70	18M1G7D
		16QAM	2506.0 - 2680.0	0.058	17.63	18M1W7D
		64QAM	2506.0 - 2680.0	0.039	15.88	18M0W7D
	15 MHz	QPSK	2503.5 - 2682.5	0.057	17.59	13M2G7D
		16QAM	2503.5 - 2682.5	0.058	17.63	13M1W7D
		64QAM	2503.5 - 2682.5	0.038	15.79	13M6W7D
	10 MHz	QPSK	2501.0 - 2685.0	0.059	17.73	8M79G7D
		16QAM	2501.0 - 2685.0	0.058	17.63	8M78W7D
		64QAM	2501.0 - 2685.0	0.039	15.86	9M03W7D
	5 MHz	QPSK	2498.5 - 2687.5	0.059	17.70	4M08G7D
		16QAM	2498.5 - 2687.5	0.058	17.64	4M08W7D
		64QAM	2498.5 - 2687.5	0.038	15.84	4M54W7D

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 3 of 40

# 1.0 INTRODUCTION

## 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

## 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

## 1.3 Test Facility / Accreditations

**Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.**

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreement.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 4 of 40

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Sony Corporation Portable Handset FCC ID: PY7-58692W**. The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 27.

**Test Device Serial No.:** 00001, 95101, 84429

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.26-2015. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) Model: Belkin F7U050 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

### 2.4 Software and Firmware

Testing was performed on device(s) using software/firmware version 0.45 installed on the EUT.

### 2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 5 of 40

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedures described in the “American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services” (ANSI C63.26-2015) were used in the measurement of the EUT.

**Deviation from Measurement Procedure.....None**

### 3.2 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

For radiated power measurements, substitution method is used per the guidance of ANSI C63.26-2015. For emissions below 1GHz, a half-wave dipole is substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [dBm] = P_g [dBm] - \text{cable loss} [dB] + \text{antenna gain} [dBd/dBi];$$

where  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to  $P_g [dBm] - \text{cable loss} [dB]$ .

For radiated spurious emissions measurements, the field strength conversion method is used per the formulas in Section 5.2.7 of ANSI C63.26-2015. Field Strength (EIRP) is calculated using the following formulas:

$$E_{[dB\mu V/m]} = \text{Measured amplitude level}_{[dBm]} + 107 + \text{Cable Loss}_{[dB]} + \text{Antenna Factor}_{[dB/m]}$$

And

$$\text{EIRP}_{[dBm]} = E_{[dB\mu V/m]} + 20\log D - 104.8; \text{ where } D \text{ is the measurement distance in meters.}$$

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI C63.26-2015.

<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 6 of 40

## 4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 7 of 40

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial #
-	AP1-002	EMC Cable and Switch System	3/9/2022	Annual	3/9/2023	AP1-002
-	AP2-001	EMC Cable and Switch System	1/4/2022	Annual	1/4/2023	AP2-001
-	AP2-002	EMC Cable and Switch System	3/11/2022	Annual	3/11/2023	AP2-002
-	ETS-001	EMC Cable and Switch System	12/9/2021	Annual	12/9/2022	ETS-001
-	LTx1	Licensed Transmitter Cable Set	12/19/2021	Annual	12/19/2022	LTx1
-	LTx2	Licensed Transmitter Cable Set	12/19/2021	Annual	12/19/2022	LTx2
-	LTx4	Licensed Transmitter Cable Set	12/19/2021	Annual	12/19/2022	LTx4
EMCO	3116	Horn Antenna (18-40GHz)	7/20/2021	Biennial	7/20/2023	9203-2178
Espec	SCP-220	Controller	5/25/2022	Biennial	5/25/2024	OCPS5H0612K05
ETS-Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/20/2021	Biennial	4/20/2023	125518
Keysight Technologies	N9020A	MXA Signal Analyzer	3/4/2022	Annual	3/4/2023	US46470561
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	2/14/2022	Annual	2/14/2023	MY52350166
Keysight Technologies	N9038A	MXE EMI Receiver	1/21/2022	Annual	1/21/2023	MY51210133
Keysight Technologies	N9030A	PXA Signal Analyzer	1/6/2022	Annual	1/6/2023	MY55410501
Keysight Technologies	N9030B	PXA Signal Analyzer, Multi-touch	1/7/2022	Annual	1/7/2023	MY57141001
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	8/3/2021	Annual	8/3/2022	100342
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/28/2022	Annual	3/28/2023	101716
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	5/25/2021	Annual	7/25/2022	100348
Rohde & Schwarz	FSW26	2Hz-26.5GHz Signal and spectrum analyzer	4/14/2022	Annual	4/14/2023	103187

**Table 5-1. Test Equipment**

### Notes:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 8 of 40



## 6.0 SAMPLE CALCULATIONS

### QPSK Modulation

**Emission Designator = 8M62G7D**

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### QAM Modulation

**Emission Designator = 8M45W7D**

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

### Spurious Radiated Emission

**Example: Spurious emission at 3700.40 MHz**

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was  $-81.0$  dBm. The gain of the substituted antenna is  $8.1$  dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of  $-81.0$  dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is  $2.0$  dB at  $3700.40$  MHz. So  $6.1$  dB is added to the signal generator reading of  $-30.9$  dBm yielding  $-24.80$  dBm. The fundamental EIRP was  $25.50$  dBm so this harmonic was  $25.50$  dBm  $- (-24.80) = 50.3$  dBc.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 9 of 40

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: Sony Corporation  
 FCC ID: PY7-58692W  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): LTE

Test Condition	Test Description	FCC Part Section(s)	Test Limit	Test Result	Reference
<b>CONDUCTED</b>	Transmitter Conducted Output Power	2.1046(a), 2.1046(c)	N/A	<b>PASS</b>	See RF Exposure Report
	Occupied Bandwidth	2.1049(h)	N/A	<b>PASS</b>	Section 7.2
	Conducted Band Edge / Spurious Emissions (LTE Band 41)	2.1051, 27.53(m)(4)	Undesirable emissions must meet the limits detailed in 27.53(m)(4)	<b>PASS</b>	Sections 7.3, 7.4
	Frequency Stability	2.1055, 27.54	Fundamental emissions stay within authorized frequency block	<b>PASS</b>	Section 7.7
<b>RADIATED</b>	Equivalent Isotropic Radiated Power (LTE Band 41)	27.50(h)(2)	≤ 2 Watts max. EIRP	<b>PASS</b>	Section 7.5
	Radiated Spurious Emissions (LTE Band 41)	2.1053, 27.53(m)	Undesirable emissions must meet the limits detailed in 27.53(m)	<b>PASS</b>	Section 7.6

**Table 7-1. Summary of Test Results (FCC)**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) All conducted emissions measurements are performed with automated test software to capture the corresponding plots necessary to show compliance. The measurement software utilized is EMC Software Tool v1.1.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 10 of 40

## 7.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used


ANSI C63.26-2015 – Section 5.4.4

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq$  3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 11 of 40

# LTE Band 41(PC3)



Plot 7-1. Occupied Bandwidth Plot (LTE Band 41(PC3) - 20MHz QPSK - Full RB)




Plot 7-2. Occupied Bandwidth Plot (LTE Band 41(PC3) - 20MHz 16-QAM - Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 12 of 40




Plot 7-3. Occupied Bandwidth Plot (LTE Band 41(PC3) - 20MHz 64-QAM - Full RB)




Plot 7-4. Occupied Bandwidth Plot (LTE Band 41(PC3) - 15MHz QPSK - Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 13 of 40




Plot 7-5. Occupied Bandwidth Plot (LTE Band 41(PC3) - 15MHz 16-QAM - Full RB)




Plot 7-6. Occupied Bandwidth Plot (LTE Band 41(PC3) - 15MHz 64-QAM - Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 14 of 40




Plot 7-7. Occupied Bandwidth Plot (LTE Band 41(PC3) - 10MHz QPSK - Full RB)



Plot 7-8. Occupied Bandwidth Plot (LTE Band 41(PC3) - 10MHz 16-QAM - Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 15 of 40




Plot 7-9. Occupied Bandwidth Plot (LTE Band 41(PC3) - 10MHz 64-QAM - Full RB)




Plot 7-10. Occupied Bandwidth Plot (LTE Band 41(PC3) - 5MHz QPSK - Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 16 of 40





Plot 7-11. Occupied Bandwidth Plot (LTE Band 41(PC3) - 5MHz 16-QAM - Full RB)



Plot 7-12. Occupied Bandwidth Plot (LTE Band 41(PC3) - 5MHz 64-QAM - Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 17 of 40

### 7.3 Spurious and Harmonic Emissions at Antenna Terminal

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

***For Band 41, the minimum permissible attenuation level of any spurious emission is  $55 + 10\log_{10}(P_{[Watts]})$ .***

#### Test Procedure Used


ANSI C63.26-2015 – Section 5.7.4

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-2. Test Instrument & Measurement Setup**

#### Test Note


Per Part 27, compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 18 of 40

### LTE Band 41(PC3)




Plot 7-13. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-14. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 19 of 40




Plot 7-15. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - Low Channel)




Plot 7-16. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 20 of 40




Plot 7-17. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)




Plot 7-18. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - Mid Channel)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 21 of 40




Plot 7-19. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)



Plot 7-20. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 22 of 40



Plot 7-21. Conducted Spurious Plot (LTE Band 41(PC3) - 20MHz QPSK - RB Size 1, RB Offset 0 - High Channel)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 23 of 40

## 7.4 Band Edge Emissions at Antenna Terminal

### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

***The minimum permissible attenuation level for Band 41 is as noted in the Test Notes on the following page.***

### Test Procedure Used


ANSI C63.26-2015 – Section 5.7.3

### Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW  $\geq$  1% of the emission bandwidth
4. VBW  $\geq$  3 x RBW
5. Detector = RMS
6. Number of sweep points  $\geq$  2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-3. Test Instrument & Measurement Setup**


### Test Note

Per 27.53(m) for operations in the BRS/EBS bands, the attenuation factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth. In addition, the attenuation factor shall not be less that  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log (P)$  dB at or below 2490.5 MHz.


FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 24 of 40



# LTE Band 41(PC3)




Plot 7-22. Lower ACP Plot (LTE Band 41(PC3) - 20MHz QPSK – Full RB)



Plot 7-23. Upper ACP Plot (LTE Band 41(PC3) - 20MHz QPSK – Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 25 of 40




Plot 7-24. Lower ACP Plot (LTE Band 41(PC3) - 15MHz QPSK – Full RB)




Plot 7-25. Upper ACP Plot (LTE Band 41(PC3) - 15MHz QPSK – Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 26 of 40




Plot 7-26. Lower ACP Plot (LTE Band 41(PC3) - 10MHz QPSK – Full RB)




Plot 7-27. Upper ACP Plot (LTE Band 41(PC3) - 10MHz QPSK – Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 27 of 40



Plot 7-28. Lower ACP Plot (LTE Band 41(PC3) - 5MHz QPSK – Full RB)



Plot 7-29. Upper ACP Plot (LTE Band 41(PC3) - 5MHz QPSK – Full RB)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 28 of 40



## 7.5 Radiated Power (EIRP)

### Test Overview

Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

ANSI C63.26-2015 – Section 5.2.4.4


### Test Settings

1. Radiated power measurements are performed using the signal analyzer’s “channel power” measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer’s “time domain power” measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq 3 \times$  RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq 2 \times$  span / RBW
6. Detector = RMS
7. Trigger is set to “free run” for signals with continuous operation with the sweep times set to “auto”. Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration.
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the “gating” function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 29 of 40

**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-4. Radiated Test Setup >1GHz**

**Test Notes**

- 1) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 2) This unit was tested with its standard battery.

<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 30 of 40



Bandwidth	Mod.	Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Ant. Gain [dBi]	RB Size/Offset	Substitute Level [dBm]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
20 MHz	QPSK	2506.0	H	154	158	9.50	1 / 99	8.01	17.51	0.056	33.01	-15.50
	QPSK	2593.0	H	139	150	9.49	1 / 0	8.21	<b>17.70</b>	0.059	33.01	-15.31
	QPSK	2680.0	H	155	163	9.87	1 / 0	7.68	17.55	0.057	33.01	-15.46
	16-QAM	2593.0	H	139	150	9.49	1 / 0	8.14	17.63	0.058	33.01	-15.38
15 MHz	64-QAM	2593.0	H	139	150	9.49	1 / 99	6.39	15.88	0.039	33.01	-17.13
	QPSK	2503.5	H	154	158	9.50	1 / 74	8.09	17.59	0.057	33.01	-15.42
	QPSK	2593.0	H	139	150	9.49	1 / 74	8.09	17.58	0.057	33.01	-15.43
	QPSK	2682.5	H	155	163	9.87	1 / 74	7.62	17.48	0.056	33.01	-15.53
	16-QAM	2593.0	H	139	150	9.49	1 / 37	8.14	<b>17.63</b>	0.058	33.01	-15.38
10 MHz	64-QAM	2593.0	H	139	150	9.49	75 / 0	6.30	15.79	0.038	33.01	-17.22
	QPSK	2501.0	H	154	158	9.49	1 / 0	8.10	17.59	0.057	33.01	-15.42
	QPSK	2593.0	H	139	150	9.49	1 / 0	8.24	<b>17.73</b>	0.059	33.01	-15.28
	QPSK	2685.0	H	155	163	9.86	1 / 0	7.79	17.65	0.058	33.01	-15.36
	16-QAM	2593.0	H	139	150	9.49	1 / 25	8.14	17.63	0.058	33.01	-15.38
5 MHz	64-QAM	2593.0	H	139	150	9.49	50 / 0	6.37	15.86	0.039	33.01	-17.15
	QPSK	2498.5	H	154	158	9.49	1 / 24	8.17	17.66	0.058	33.01	-15.35
	QPSK	2593.0	H	139	150	9.49	1 / 24	8.21	<b>17.70</b>	0.059	33.01	-15.31
	QPSK	2687.5	H	155	163	9.86	1 / 24	7.83	17.68	0.059	33.01	-15.33
	16-QAM	2593.0	H	139	150	9.49	1 / 24	8.15	17.64	0.058	33.01	-15.37
20 MHz	64-QAM	2593.0	H	139	150	9.49	25 / 0	6.35	15.84	0.038	33.01	-17.17
	Opposite Pol.	2593.0	V	102	364	9.46	1/0	6.77	16.23	0.042	33.01	-16.78
	WCP	2593.0	H	163	162	9.49	1/0	6.65	16.14	0.041	33.01	-16.87

Table 7-2. EIRP Data (LTE Band 41(PC3))

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 31 of 40



## 7.6 Radiated Spurious Emissions Measurements

### Test Overview

Radiated spurious emissions measurements are performed using the field strength conversion method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using hybrid (biconical/log) antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

### Test Procedures Used

ANSI C63.26-2015 – Section 5.5.4

### Test Settings


1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq$  3 x RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq$  2 x span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 32 of 40




**Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-5. Test Instrument & Measurement Setup < 1GHz**



**Figure 7-6. Test Instrument & Measurement Setup >1 GHz**


<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 33 of 40

**Test Notes**


- 1) Field strengths are calculated using the Measurement quantity conversions in ANSI C63.26-2015 Section 5.2.7:
  - a)  $E(\text{dB}\mu\text{V}/\text{m}) = \text{Measured amplitude level (dBm)} + 107 + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$
  - b)  $\text{EIRP (dBm)} = E(\text{dB}\mu\text{V}/\text{m}) + 20\log D - 104.8$ ; where D is the measurement distance in meters.
- 2) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst-case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the tables below.
- 3) This unit was tested with its standard battery.
- 4) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 5) Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 6) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 34 of 40


## LTE Band 41(PC3)



Plot 7-30. Radiated Spurious Plot Below 1GHz (LTE Band 41(PC3))



Plot 7-31. Radiated Spurious Plot (LTE Band 41(PC3))



Plot 7-32. Radiated Spurious Plot above 18GHz (LTE Band 41(PC3))

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 35 of 40



Bandwidth (MHz):	20
Frequency (MHz):	2593.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	ERP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
714.60	H	-	-	-84.35	29.02	51.67	-45.73	-25.00	-20.73

Table 7-3. Radiated Spurious Data Below 1GHz (LTE Band 41(PC3))

Bandwidth (MHz):	20
Frequency (MHz):	2506.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
5012.00	H	-	-	-77.33	4.32	33.99	-61.27	-25.00	-36.27
7518.00	H	-	-	-78.15	7.35	36.20	-59.06	-25.00	-34.06
10024.00	H	-	-	-78.84	10.31	38.47	-56.79	-25.00	-31.79

Table 7-4. Radiated Spurious Data (LTE Band 41(PC3) – Low Channel)

Bandwidth (MHz):	20
Frequency (MHz):	2593.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
5186.00	H	-	-	-77.45	5.02	34.57	-60.68	-25.00	-35.68
7779.00	H	-	-	-77.64	7.21	36.57	-58.69	-25.00	-33.69
10372.00	H	-	-	-79.76	11.09	38.33	-56.93	-25.00	-31.93

Table 7-5. Radiated Spurious Data (LTE Band 41(PC3) – Mid Channel)

Bandwidth (MHz):	20
Frequency (MHz):	2680.0
RB / Offset:	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
5360.00	H	-	-	-76.77	4.81	35.04	-60.21	-25.00	-35.21
8040.00	H	-	-	-77.91	7.87	36.96	-58.29	-25.00	-33.29
10720.00	H	-	-	-79.28	11.74	39.46	-55.79	-25.00	-30.79

Table 7-6. Radiated Spurious Data (LTE Band 41(PC3) – High Channel)

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 36 of 40



<b>Case:</b>	w/ Wireless Charging Pad
<b>Bandwidth (MHz):</b>	20
<b>Frequency (MHz):</b>	2593.0
<b>RB / Offset:</b>	1 / 50

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	EIRP Spurious Emission Level [dBm]	Limit [dBm]	Margin [dB]
5186.00	H	-	-	-76.35	5.02	35.67	-59.58	-25.00	-34.58
7779.00	H	-	-	-76.39	7.21	37.82	-57.44	-25.00	-32.44
10372.00	H	-	-	-78.67	11.09	39.42	-55.84	-25.00	-30.84

Table 7-7. Radiated Spurious Data with WCP (LTE Band 41(PC3))

<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 37 of 40



## 7.7 Frequency Stability / Temperature Variation

### Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

***For Part 27, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.***

### Test Procedure Used

ANSI C63.26-2015 – Section 5.6

### Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

### Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

### Test Notes


None

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 38 of 40

## LTE Band 41

		Operating Frequency (Hz):		2,593,000,000	
		Ref. Voltage (VDC):		4.28	
Voltage (%)	Power (VDC)	Temp (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	4.28	- 30	2,593,089,103	3,074	0.0001185
		- 20	2,593,083,435	-2,594	-0.0001000
		- 10	2,593,092,016	5,987	0.0002309
		0	2,593,089,421	3,392	0.0001308
		+ 10	2,593,091,647	5,618	0.0002167
		+ 20 (Ref)	2,593,086,029	0	0.0000000
		+ 30	2,593,086,341	312	0.0000120
		+ 40	2,593,085,135	-894	-0.0000345
		+ 50	2,593,087,486	1,457	0.0000562
Battery Endpoint	3.69	+ 20	2,593,086,785	756	0.0000292

**Table 7-8. LTE Band 41 Frequency Stability Data**



**Plot 7-33. LTE Band 41 Frequency Stability Chart**

FCC ID: PY7-58692W	PART 27 MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2207200079-04.PY7	Test Dates: 7/14/2022 - 7/28/2022	EUT Type: Portable Handset	Page 39 of 40

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Sony Corporation Portable Handset FCC ID: PY7-58692W** complies with all the requirements of Part 27 of the FCC rules.

<b>FCC ID:</b> PY7-58692W	<b>PART 27 MEASUREMENT REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-04.PY7	<b>Test Dates:</b> 7/14/2022 - 7/28/2022	<b>EUT Type:</b> Portable Handset	Page 40 of 40