



Appendix B

GSM 850 & 1900



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

CONTENT

	Page
1. EFFECTIVE (ISOTROPIC) RADIATED POWER OUTPUT DATA	3
1.1. Test Result	3
2. FIELD STRENGTH OF SPURIOUS RADIATION	4
2.1. Test Band = GSM_850	4
2.1.1. Test Channel = Low Channel	4
2.2. Test Band = GSM_850	4
2.2.1. Test Channel = Low Channel	4



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1. Effective (Isotropic) Radiated Power Output Data

1.1. Test Result

Band	Channel	Slot	Conducted Power (dBm)	ERP (dBm)	Limit(dBm)	Verdict
GSM850	128	---	32.74	27.29	38.45	PASS

Band	Channel	Slot	Conducted Power (dBm)	EIRP (dBm)	Limit(dBm)	Verdict
GSM1900	512	---	27.27	28.67	33.00	PASS

Remark:

a: For getting the EIRP (Efficient Isotropic Radiated Power), the following formula should be taken to calculate it,

ERP [dBm] = Conducted Power [dBm] + Gain [dBd]

EIRP [dBm] = Conducted Power [dBm] + Gain [dBi]



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2. Field Strength of Spurious Radiation

2.1. Test Band = GSM_850

2.1.1. Test Channel = Low Channel

NO.	Freq. [MHz]	Level [dBm]	Limit [dBm]	Margin [dB]	Polarity
1	45.4723	-62.89	-13.00	49.89	Horizontal
2	244.0412	-66.45	-13.00	53.45	Horizontal
3	998.7389	-53.68	-13.00	40.68	Horizontal
4	1648.5297	-49.71	-13.00	36.71	Horizontal
5	2472.6945	-44.78	-13.00	31.78	Horizontal
6	9310.0103	-51.36	-13.00	38.36	Horizontal

2.2. Test Band = GSM_850

2.2.1. Test Channel = Low Channel

NO.	Freq. [MHz]	Level [dBm]	Limit [dBm]	Margin [dB]	Polarity
1	50.9045	-69.34	-13.00	56.34	Vertical
2	113.1817	-60.98	-13.00	47.98	Vertical
3	998.8359	-51.67	-13.00	38.67	Vertical
4	1648.1296	-49.46	-13.00	36.46	Vertical
5	2472.6945	-44.62	-13.00	31.62	Vertical
6	9301.6101	-50.05	-13.00	37.05	Vertical

Remark:

- 1) According to 971168 D01 Power Meas License Digital Systems, The amplitudes of unwanted emissions that are attenuated more than 20 dB below the applicable limit are not required to be reported.
- 2) The disturbance above 12.75GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the worst case data had been displayed.

The End

