

RF EXPOSURE REPORT

for

Model Number: D34.1

FCC ID: PY7-66476M

Prepared for : SONY MOBILE COMMUNICATIONS INC
4-12-3 HIGASHI-SHINAGAWA, SHINAGAWA - KU, TOKYO,
Address : 140-0002, JAPAN

Prepared by : Shenzhen BCTC Technology Co., Ltd.
Address : No.101, Yousong Road, Longhua New District,
Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]

* [$\sqrt{f(\text{GHz})}$]

| Frequency MHz | tune up power tolerance (dBm) | Maximum Tune up output power (dBm) | max. output power(mW) | Separation distance mm | RF exposure |
|------------------|--|---|--------------------------|------------------------------|----------------|
| 2402 | 0±1 | 1 | 1.26 | 5 | 0.39 |

The Max RF exposure is 0.39.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.