



# **CERTIFICATION TEST REPORT**

**Report Number. :** 12097277-E8V1

**Applicant :** SONY MOBILE COMMUNICATIONS INC.  
4-12-3 HIGASHI-SHINAGAWA,  
SHINAGAWA -KU,TOKYO, 140-0002, JAPAN

**FCC ID :** PY7-72474U

**EUT Description :** GSM/WCDMA/LTE Phone with BT,DTS/UNII a/b/g/n/ac, & NFC

**Test Standard(s) :** FCC 47 CFR PART 15 SUBPART B

**Date Of Issue:**

January 24, 2018

**Prepared by:**

UL Verification Services Inc.  
47173 Benicia Street  
Fremont, CA 94538, U.S.A.  
TEL: (510) 771-1000  
FAX: (510) 661-0888



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	01/24/18	Initial Issue	Dan Corona

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY.....</b>	<b>5</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>5</b>
4.1. MEASURING INSTRUMENT CALIBRATION.....	5
4.2. SAMPLE CALCULATION.....	5
4.3. MEASUREMENT UNCERTAINTY .....	6
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>7</b>
5.1. DESCRIPTION OF EUT.....	7
5.2. TEST CONFIGURATIONS.....	7
5.3. MODE(S) OF OPERATION.....	7
5.4. SOFTWARE AND FIRMWARE .....	7
5.5. MODIFICATIONS.....	7
5.6. DETAILS OF TESTED SYSTEM.....	8
<b>6. APPLICABLE EMISSIONS LIMITS AND TEST RESULTS .....</b>	<b>11</b>
6.1. EMISSIONS TEST AND MEASUREMENT EQUIPMENT.....	11
6.2. RADIATED EMISSIONS LIMITS AND RESULTS.....	12
6.2.1. RADIATED EMISSIONS 30 TO 1000 MHz (SYNC MODE).....	13
6.2.2. RADIATED EMISSIONS 1GHz to 18GHz (SYNC MODE).....	15
6.2.3. RADIATED EMISSIONS 18 to 26 GHz (SYNC MODE).....	17
6.2.4. RADIATED EMISSIONS 26 to 40 GHz (SYNC MODE).....	19
6.2.1. RADIATED EMISSIONS 30 TO 1000 MHz (CHARGING MODE).....	21
6.2.2. RADIATED EMISSIONS 1GHz to 18GHz (CHARGING MODE).....	23
6.2.3. RADIATED EMISSIONS 18 to 26 GHz (CHARGING MODE).....	25
6.2.4. RADIATED EMISSIONS 26 to 40 GHz (CHARGING MODE).....	27
6.3. AC MAINS LINE CONDUCTED EMISSIONS.....	29
6.3.1. RESULTS - SYNC MODE .....	30
6.3.2. RESULTS - CHARGING MODE .....	32
<b>7. SETUP PHOTOS.....</b>	<b>34</b>

# 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** SONY MOBILE COMMUNICATIONS INC.  
4-12-3 HIGASHI-SHINAGAWA, SHINAGAWA-KU  
TOKYO, 140-0002, JAPAN

**EUT DESCRIPTION:** GSM/WCDMA/LTE PHONE with BT, DTS/UNII a/b/g/n/ac, & NFC.

**SERIAL NUMBER:** BH90003QAY

**DATE TESTED:** JANUARY 03 – 09, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR PART 15 SUBPART B	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Verification Services Inc By:



Dan Corona  
Operations Leader  
UL Verification Services Inc.

Prepared By:



Kedida Kiya  
Project Engineer  
UL Verification Services Inc.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2014.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
<input type="checkbox"/> Chamber A(IC: 2324B-1)	<input type="checkbox"/> Chamber D(IC: 22541-1)
<input checked="" type="checkbox"/> Chamber B(IC: 2324B-2)	<input type="checkbox"/> Chamber E(IC: 22541-2)
<input type="checkbox"/> Chamber C(IC: 2324B-3)	<input type="checkbox"/> Chamber F(IC: 22541-3)
	<input type="checkbox"/> Chamber G(IC: 22541-4)
	<input type="checkbox"/> Chamber H(IC: 22541-5)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. Chambers A through C are covered under Industry Canada company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under Industry Canada company address code 22541 with site numbers 22541 -1 through 22541-5, respectively.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.84 dB
Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, & NFC.

#### GENERAL INFORMATION

Highest frequency generated or used by the EUT	5825 MHz
--	----------

### 5.2. TEST CONFIGURATIONS

The following configuration was tested:

EUT Configuration	Description
1	Laptop Sync Mode - The EUT was configured as table top equipment. The EUT is installed in a typical configuration. The EUT is connected to a laptop via USB, is charging and transferring data via the laptop.
2	Charging - The EUT was configured as table top equipment. The EUT is installed in a typical configuration. The EUT is connected to an AC adapter for charging and in a functional mode.

### 5.3. MODE(S) OF OPERATION

Mode	Description
Sync mode	Data transfer; Sync video file from laptop to EUT and continued playing video during testing.
Charging Mode	Charging with supplied USB charger. EUT and its charger shall be on back edge of table, with charger connected to extension cord.

### 5.4. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was SONY, s\_atp\_1\_00139\_B\_10\_5.  
The test utility software used during testing was Tera Term Ver 4.79.

### 5.5. MODIFICATIONS

No modifications were made during testing.

## 5.6. DETAILS OF TESTED SYSTEM

### SUPPORT EQUIPMENT & PERIPHERALS

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	Lenovo	2349CW5	PB05HPL	DoC
Earphone	Sony	N/A	N/A	N/A
Audio & Charger Splitter	SONY	1312-8675.1B	YYWWSSPCXXXXXC	N/A
AC Adapter	Lenovo	ADLX90NLT2A	11S45N0307ZLZ436RDM2	N/A
Mouse	Logitech	M-U0026	1304HS02AX68	N/A
Keyboard	Lenovo	KU-0225	54Y9400	N/A
Switch	Netgear	FS105 v2	1D52163304A74	DoC
AC Adapter	Netgear	FA-0751000SUA	332-10154-01	N/A

### I/O CABLES Sync Mode

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC Power	1	AC	Unshielded	1.2m	AC Mains to AC/DC Adapter
2	DC Power	1	DC	Unshielded	1m	AC/DC Adapter to Switch and Laptop
3	USB	2	USB	Unshielded	1m	Laptop to keyboard and mouse
4	USB	1	USB-type-C	Unshielded	1m	EUT to Laptop
5	Ethernet	1	RJ45	Unshielded	>2m	Laptop to Switch

### I/O CABLES Charging Mode

I/O Cable List						
Cable No	Port	# of identi	Connector Type	Cable Type	Cable Length	Remarks
1	USB	1	AC Adapter	Un-shielded	1.2m	No
2	Jack	1	Headset	Shielded	1m	No
3	USB/Headphone Jack	1	USB Type-C/Audio	Un-shielded	.2m	Audio & Charger Splitter


### TEST SETUP

The EUT is installed in a typical configuration. Test software exercised the EUT.




**SETUP DIAGRAM**

**Sync Mode**



NOTE: Switch location is outside chamber (located in the control room).

**Charging Mode**



## 6. APPLICABLE EMISSIONS LIMITS AND TEST RESULTS

### 6.1. EMISSIONS TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	T Number	Cal Date	Cal Due
Amplifier, 1 to 18 GHz	Miteq	AFS43-00101800-25-S-42	493	06/23/2017	06/23/2018
Amplifier, 10KHz to 1GHz, 32dB	Keysight	8447D	10	02/15/2017	02/15/2018
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	346	03/28/2017	03/28/2018
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB3	899	06/15/2017	06/15/2018
PXA Spectrum Analyzer, 3Hz to 44GHz	Agilent	N9030A	907	01/23/2017	01/23/2018
EMI Reciever	Rohde & Schwarz	ESCI 7	212	09/15/2017	09/15/2018
LISN	FISCHER	FCC-LISN-50/250-25-2-01	1310	06/08/2017	06/08/2018
18 - 26.5 GHz Horn Antenna	Seavey Division	MWH-1826/B	89	01/04/2017	01/04/2018
26.5 - 40 GHz Horn Antenna	ARA	MWH-2640/B	90	08/25/2017	08/25/2018
Pre-Amp 1-26.5 GHz	Agilent	8449B	404	07/23/2017	07/23/2018
Pre-Amp, 26-40GHz	MITEQ	NSTTA2640-35-HG	1864	09/21/2017	09/21/2018
PXA Spectrum Analyzer, 3Hz to 44GHz	Keysight	N9030A	1454	12/15/2017	12/15/2018

Test Software List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Ver 9.5, Dec 01, 2016
Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015
Antenna Port Software	UL	UL RF	Ver 7.7, Dec 14, 2017

## 6.2. RADIATED EMISSIONS LIMITS AND RESULTS

### LIMIT

FCC Part 15 Subpart B

§15.109 (a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Limits for radiated disturbance of Class B ITE at measuring distance of 3 m	
Frequency range (MHz)	Quasi-peak limits (dBµV/m)
30 to 88	40
88 to 216	43.5
216 to 960	46
Above 960 MHz	54

Note: The lower limit shall apply at the transition frequency.

### TEST PROCEDURE


ANSI C63.4: 2014


The highest frequency generated or used in the EUT is 5.8 GHz therefore the frequency range was investigated from 30 MHz to 40 GHz.

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower

**RESULTS**

**6.2.1. RADIATED EMISSIONS 30 TO 1000 MHz (SYNC MODE)**





### HORIZONTAL AND VERTICAL DATA



#### Radiated Emissions

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T899 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	Class B QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	32.6362	31.89	Qp	23.6	-28.8	26.69	40	-13.31	212	353	H
4	32.6715	32.53	Qp	23.6	-28.8	27.33	40	-12.67	320	100	V
5	61.9683	46.44	Pk	11.9	-28.4	29.94	40	-10.06	0-360	100	V
2	113.194	42.39	Pk	17.1	-27.8	31.69	43.52	-11.83	0-360	200	H
6	122.2064	35.58	Pk	17.7	-27.7	25.58	43.52	-17.94	0-360	100	V
3	181.8918	43.75	Pk	15.1	-27.1	31.75	43.52	-11.77	0-360	200	H

Pk - Peak detector

Qp - Quasi-Peak detector

### 6.2.2. RADIATED EMISSIONS 1GHz to 18GHz (SYNC MODE)



**HORIZONTAL AND VERTICAL DATA**



**Radiated Emissions**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T863 (dB/m)	Amp/Cbl (dB)	Corrected Reading dBuV/m	Class B Avg Limit (dBuV/m)	Margin (dB)	Class B Pk Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.329	41.99	Pk	28.9	-34.3	36.59	-	-	74	-37.41	350	132	H
	1.33	28.93	Av	28.9	-34.2	23.63	54	-30.37	-	-	350	132	H
4	1.33	50.31	Pk	28.9	-34.2	45.01	-	-	74	-28.99	202	207	V
	1.329	30.64	Av	28.9	-34.3	25.24	54	-28.76	-	-	202	207	V
5	1.994	43.66	Pk	31.3	-33.5	41.46	-	-	74	-32.54	207	167	V
	1.995	28.97	Av	31.3	-33.5	26.77	54	-27.23	-	-	207	167	V
2	2.551	40.47	Pk	32.5	-32.7	40.27	-	-	74	-33.73	302	167	H
	2.55	28	Av	32.5	-32.7	27.8	54	-26.2	-	-	302	167	H
6	4.988	40.64	Pk	34.4	-31	44.04	-	-	74	-29.96	125	219	V
	4.989	27.45	Av	34.4	-31.1	30.75	54	-23.25	-	-	125	219	V
3	5.71	39.85	Pk	35.1	-30.7	44.25	-	-	74	-29.75	257	187	H
	5.707	26.94	Av	35.1	-30.7	31.34	54	-22.66	-	-	257	187	H

Pk - Peak detector  
 Av - Average detection



### 6.2.3. RADIATED EMISSIONS 18 to 26 GHz (SYNC MODE)





**HORIZONTAL AND VERTICAL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	T89 AF (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)
1	26.698	40.38	Pk	35.3	-30.5	-9.5	35.68	54	-18.32	74	-38.32
2	29.329	36.75	Pk	35.9	-32.1	-9.5	31.05	54	-22.95	74	-42.95
3	32.269	35.88	Pk	36.4	-32.8	-9.5	29.98	54	-24.02	74	-44.02
4	26.72	38.7	Pk	35.3	-31.1	-9.5	33.4	54	-20.6	74	-40.6
5	31.474	36.84	Pk	36.2	-33	-9.5	30.54	54	-23.46	74	-43.46
6	34.965	37.68	Pk	37.2	-33.3	-9.5	32.08	54	-21.92	74	-41.92

Pk - Peak detector

**6.2.4. RADIATED EMISSIONS 26 to 40 GHz (SYNC MODE)**





**HORIZONTAL AND VERTICAL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	T90 AF (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)
1	27.011	43.03	Pk	35.5	-31.2	-9.5	37.83	54	-16.17	74	-36.17
2	29.383	41.09	Pk	35.9	-32.3	-9.5	35.19	54	-18.81	74	-38.81
3	32.956	40.87	Pk	36.7	-32.7	-9.5	35.37	54	-18.63	74	-38.63
4	26.706	43	Pk	35.3	-30.8	-9.5	38	54	-16	74	-36
5	31.192	40.05	Pk	36	-32.7	-9.5	33.85	54	-20.15	74	-40.15
6	34.397	40.45	Pk	37.2	-33	-9.5	35.15	54	-18.85	74	-38.85

Pk - Peak detector

### 6.2.1. RADIATED EMISSIONS 30 TO 1000 MHz (CHARGING MODE)





**HORIZONTAL AND VERTICAL DATA**

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T899 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	Class B QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	32.7632	30.21	Pk	23.5	-28.8	24.91	40	-15.09	0-360	100	H
4	38.3747	38.99	Pk	19.4	-28.7	29.69	40	-10.31	0-360	100	V
5	58.2273	40.25	Pk	11.4	-28.4	23.25	40	-16.75	0-360	100	V
2	81.8209	38.72	Pk	11	-28.2	21.52	40	-18.48	0-360	200	H
3	153.7495	35.09	Pk	16.2	-27.3	23.99	43.52	-19.53	0-360	200	H
6	199.1088	30.57	Pk	16.6	-26.9	20.27	43.52	-23.25	0-360	100	V

Pk - Peak detector

### 6.2.2. RADIATED EMISSIONS 1GHz to 18GHz (CHARGING MODE)



**HORIZONTAL AND VERTICAL DATA**



**Radiated Emissions**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T863 (dB/m)	Amp/Cbl (dB)	Corrected Reading dBuV/m	Class B Avg Limit (dBuV/m)	Margin (dB)	Class B Pk Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.856	41.71	Pk	30.8	-33.5	39.01	-	-	74	-34.99	22	197	H
	1.858	28.27	Av	30.8	-33.5	25.57	54	-28.43	-	-	22	197	H
4	2.553	40.93	Pk	32.5	-32.7	40.73	-	-	74	-33.27	135	175	V
	2.555	27.95	Av	32.5	-32.7	27.75	54	-26.25	-	-	135	175	V
2	3.109	40.93	Pk	33.2	-31.7	42.43	-	-	74	-31.57	55	136	H
	3.108	27.58	Av	33.2	-31.7	29.08	54	-24.92	-	-	55	136	H
5	3.708	40.54	Pk	33.3	-31.8	42.04	-	-	74	-31.96	170	216	V
	3.706	27.91	Av	33.3	-31.8	29.41	54	-24.59	-	-	170	216	V
3	6.535	38.35	Pk	35.7	-30	44.05	-	-	74	-29.95	156	221	H
	6.536	25.66	Av	35.7	-30	31.36	54	-22.64	-	-	156	221	H
6	8.88	35.41	Pk	36.2	-26.5	45.11	-	-	74	-28.89	236	222	V
	8.884	22.86	Av	36.2	-26.6	32.46	54	-21.54	-	-	236	222	V

Pk - Peak detector  
 Av - Average detection



### 6.2.3. RADIATED EMISSIONS 18 to 26 GHz (CHARGING MODE)





**HORIZONTAL AND VERTICAL DATA**

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	T89 AF (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)
1	18.869	38.26	Pk	32.4	-25.3	-9.5	35.86	54	-18.14	74	-38.14
2	20.827	36.87	Pk	32.7	-25.3	-9.5	34.77	54	-19.23	74	-39.23
3	23.276	37.12	Pk	33.5	-24.7	-9.5	36.42	54	-17.58	74	-37.58
4	19.579	36.97	Pk	32.5	-25.1	-9.5	34.87	54	-19.13	74	-39.13
5	21.818	38.73	Pk	33.3	-24.5	-9.5	38.03	54	-15.97	74	-35.97
6	23.753	39.06	Pk	33.8	-24.3	-9.5	39.06	54	-14.94	74	-34.94

Pk - Peak detector

### 6.2.4. RADIATED EMISSIONS 26 to 40 GHz (CHARGING MODE)



### HORIZONTAL AND VERTICAL DATA

#### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	T90 AF (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)
1	27.058	44.67	Pk	35.5	-30.8	-9.5	39.87	54	-14.13	74	-34.13
2	29.872	42.96	Pk	36	-32.7	-9.5	36.76	54	-17.24	74	-37.24
3	32.312	43.07	Pk	36.4	-32.8	-9.5	37.17	54	-16.83	74	-36.83
4	28.333	44.16	Pk	35.8	-31.5	-9.5	38.96	54	-15.04	74	-35.04
5	31.339	42.48	Pk	36.1	-32.9	-9.5	36.18	54	-17.82	74	-37.82
6	34.565	44.63	Pk	37.4	-33.2	-9.5	39.33	54	-14.67	74	-34.67

Pk - Peak detector

### 6.3. AC MAINS LINE CONDUCTED EMISSIONS

#### TEST PROCEDURE

ANSI C63.4: 2014

#### LIMIT

§15.107 (a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.


Frequency range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Notes:  
1. The lower limit shall apply at the transition frequencies  
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

### 6.3.1. RESULTS - SYNC MODE

#### 6 WORST EMISSIONS

#### Line-L1 .15 - 30MHz



#### Trace Markers


Range 1: Line-L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L1	LC Cables C1&C3	Limiters (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	Margin (dB)	CFR 47 Part 15 Class B Avg	Margin (dB)
1	.159	51	Pk	.1	0	10.1	61.2	65.52	-4.32	-	-
2	.159	31.79	Av	.1	0	10.1	41.99	-	-	55.52	-13.53
3	.42	41.39	Pk	0	0	10.1	51.49	57.45	-5.96	-	-
4	.429	31.69	Av	0	0	10.1	41.79	-	-	47.27	-5.48
5	.6225	41.22	Pk	0	0	10.1	51.32	56	-4.68	-	-
6	.636	29.86	Av	0	0	10.1	39.96	-	-	46	-6.04
7	.915	42.52	Pk	0	0	10.1	52.62	56	-3.38	-	-
8	.915	31.43	Av	0	0	10.1	41.53	-	-	46	-4.47
9	3.1335	42.64	Pk	0	.1	10.2	52.94	56	-3.06	-	-
10	3.1155	27.96	Av	0	.1	10.1	38.16	-	-	46	-7.84
11	13.3035	34.29	Pk	.1	.2	10.2	44.79	60	-15.21	-	-
12	13.2855	22.47	Av	.1	.2	10.2	32.97	-	-	50	-17.03

Pk - Peak detector

Av - Average detection

**Line-L2 .15 - 30MHz**



**Trace Markers**

Range 2: Line-L2 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L2	LC Cables C2&C3	Limiter (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	Margin (dB)	CFR 47 Part 15 Class B Avg	Margin (dB)
13	.24	45.19	Pk	0	0	10.1	55.29	62.1	-6.81	-	-
14	.2355	37.65	Av	0	0	10.1	47.75	-	-	52.25	-4.5
15	.465	42.38	Pk	0	0	10.1	52.48	56.6	-4.12	-	-
16	.465	36.32	Av	0	0	10.1	46.42	-	-	46.6	-18
17	.699	42.3	Pk	0	0	10.1	52.4	56	-3.6	-	-
18	.699	35.46	Av	0	0	10.1	45.56	-	-	46	-44
19	1.059	42.98	Pk	0	.1	10.1	53.18	56	-2.82	-	-
20	1.05	33.37	Av	0	.1	10.1	43.57	-	-	46	-2.43
21	2.5575	40.85	Pk	0	.1	10.1	51.05	56	-4.95	-	-
22	2.553	27.98	Av	0	.1	10.1	38.18	-	-	46	-7.82
23	12.984	36.3	Pk	.1	.2	10.2	46.8	60	-13.2	-	-
24	12.9885	23.42	Av	.1	.2	10.2	33.92	-	-	50	-16.08


Pk - Peak detector

Av - Average detection

### 6.3.2. RESULTS - CHARGING MODE

#### 6 WORST EMISSIONS

#### Line-L1 .15 - 30MHz



#### Trace Markers


Range 1: Line-L1 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L1	LC Cables C1&C3	Limiter (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	Margin (dB)	CFR 47 Part 15 Class B Avg	Margin (dB)
1	.1635	32.3	Pk	.1	0	10.1	42.5	65.28	-22.78	-	-
2	.168	12.97	Av	.1	0	10.1	23.17	-	-	55.06	-31.89
3	.3435	20.48	Pk	0	0	10.1	30.58	59.12	-28.54	-	-
4	.366	5.01	Av	0	0	10.1	15.11	-	-	48.59	-33.48
5	.5595	24.95	Pk	0	0	10.1	35.05	56	-20.95	-	-
6	.5595	10.68	Av	0	0	10.1	20.78	-	-	46	-25.22
7	1.2255	15.15	Pk	0	.1	10.1	25.35	56	-30.65	-	-
8	1.221	3.83	Av	0	.1	10.1	14.03	-	-	46	-31.97
9	4.263	14.17	Pk	0	.1	10.2	24.47	56	-31.53	-	-
10	4.29	-2.82	Av	0	.1	10.2	7.48	-	-	46	-38.52
11	21.1515	28.72	Pk	.1	.3	10.4	39.52	60	-20.48	-	-
12	21.1515	-3.8	Av	.1	.3	10.4	7	-	-	50	-43

Pk - Peak detector

Av - Average detection



**Line-L2 .15 - 30MHz**



**Trace Markers**

Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L2	LC Cables C2&C3	Limiter (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	Margin (dB)	CFR 47 Part 15 Class B Avg	Margin (dB)
13	.2355	27.06	Pk	0	0	10.1	37.16	62.25	-25.09	-	-
14	.2355	3.78	Av	0	0	10.1	13.88	-	-	52.25	-38.37
15	.555	16.49	Pk	0	0	10.1	26.59	56	-29.41	-	-
16	.564	.87	Av	0	0	10.1	10.97	-	-	46	-35.03
17	1.3965	10.95	Pk	0	.1	10.1	21.15	56	-34.85	-	-
18	1.383	-1.68	Av	0	.1	10.1	8.52	-	-	46	-37.48
19	2.5935	10.02	Pk	0	.1	10.1	20.22	56	-35.78	-	-
20	2.5935	-3.1	Av	0	.1	10.1	7.1	-	-	46	-38.9
21	13.479	18.47	Pk	.1	.2	10.2	28.97	60	-31.03	-	-
22	13.488	3.22	Av	.1	.2	10.2	13.72	-	-	50	-36.28
23	18.3885	22.12	Pk	0	.3	10.3	32.72	60	-27.28	-	-
24	18.051	4.91	Av	0	.3	10.3	15.51	-	-	50	-34.49

Pk - Peak detector

Av - Average detection