



**Sony Mobile Communications, Inc.**

4-12-3 Higashi-shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

Remarks

This document is managed in Infodoc.

Date: August 16, 2019

Federal Communications Commission  
Office of Engineering and Technology  
Laboratory Division  
7435 Oakland Mills Rd.  
Columbia MD 21046

## MIF attestation letter\_FCC ID: PY7-77587Q

HAC Attestation - FCC ID: PY7-77587Q

To whom it may concern:

Sony Mobile Communications Inc. hereby declares that the MIF values detailed below are based on worst case operating modes for all air interfaces for which the HAC rating is provided based on the current methodology for determining MIF values.

Reference Test report Number(s): HA940903-03A.

### SPEAG test files

UID	Communication System Name	MIF (dB)
10021	GSM-FDD (TDMA, GMSK)	3.63
10025	EDGE-FDD (TDMA, 8PSK, TN 0)	3.75
10460	UMTS-FDD (WCDMS, AMR)	-25.43
10225	UMTS-FDD (HSPA+)	-20.39
10170	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-9.76
10172	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	-1.62
10173	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-1.44
10174	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	-1.54
10061	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	-2.02
10077	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	0.12
10427	IEEE 802.11n (HT Greeneld, 150 Mbps, 64-QAM)	-13.44
10069	IEEE 802.11a/n WiFi 5 GHz (OFDM, 54 Mbps)	-3.15
10616	IEEE 802.11ac WiFi (OFDM, MCS0, 90pc duty cycle)	-5.57

Yours sincerely,

Mika Kaneko  
Head of Regulatory, Product Compliance  
Quality & Customer Services  
Sony Mobile Communications Inc.