

<b>9.9 TEST: RF Exposure Requirements</b>		<b>PASS</b>
Parameters required prior to the test	Laboratory Ambient Temperature (°C)	15 to 35 °C
	Relative Humidity (%)	30 to 60 %
Parameters recorded during the test	Laboratory Ambient Temperature (°C)	---
	Relative Humidity (%)	---
	Air pressure (hPa)	1020
---	Power Supply / Frequency	Application Point
Fully configured sample tested at the power line frequency	+3,6V dc	---
Equipment mode:	Operation mode	#1
FCC Standard	§ 1.1310 (1) (B)	
Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines § 1.1310, table (1) (b)		
EUT classification (fixed, mobile or portable devices)	Fixed equipment used in Uncontrolled Exposure environment	
Limits Freq. Range 300+1500MHz	f/1500 (Power Density (mW/cm <sup>2</sup> ))	
Power Density (mW/cm <sup>2</sup> )	$S = P * G / 4\pi r^2$	

**Note:**

P = Conducted Power (mW); G = Numeric Gain (10<sup>(dBi/10)</sup>); r = distance (cm)

<b>Operation Mode: #1</b>							
<b>CH</b>	<b>Frequency</b>	<b>Conducted Output Power</b>	<b>Conducted Output Power (P)</b>	<b>Numeric Gain (G)</b>	<b>Distance (r)</b>	<b>Power Density (S)</b>	<b>Limits (f/1500)</b>
	<b>(MHz)</b>	<b>(dBm)</b>	<b>(mW)</b>		<b>(cm)</b>		
Low	904,00	13,61	22,96	2	20	0,009116	0,6026
Mid	915,50	13,55	22,64	2	20	0,008992	0,6103
High	927,00	13,48	22,28	2	20	0,008846	0,6180
<b>VERDICT</b>							
<p><b>The EUT Radiated Power density at evaluation distance is WHITIN THE LIMIT at the distance of 20cm.</b></p> <p><b>The EUT Radiated Power density is OUT OF THE LIMIT if the distance is &lt; 2,46cm</b></p>							

**END OF TEST REPORT**