



FCC RADIO TEST REPORT

FCC ID : PY7-87607S
Equipment : GSM/WCDMA/LTE Phone with BT, DTS/UNII
a/b/g/n/ac/ax, GPS, WPC and NFC
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Standard : FCC Part 15 Subpart E §15.407

The product was received on Dec. 04, 2019 and testing was started from Jan. 13, 2020 and completed on Feb. 06, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this spot check data report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report 3

Summary of Test Result 4

1 General Description..... 5

 1.1 Product Feature of Equipment Under Test 5

 1.2 Modification of EUT 6

 1.3 Testing Location 6

 1.4 Applicable Standards 6

2 Test Configuration of Equipment Under Test..... 7

 2.1 Carrier Frequency and Channel..... 7

 2.2 Test Mode 7

 2.3 Connection Diagram of Test System 8

 2.4 EUT Operation Test Setup 8

3 Test Result..... 9

 3.1 Maximum Conducted Output Power Measurement..... 9

 3.2 Unwanted Emissions Measurement 10

 3.3 Antenna Requirements 15

4 List of Measuring Equipment 16

5 Uncertainty of Evaluation 18

Appendix A. Conducted Test Results

Appendix B. Radiated Spurious Emission

Appendix C. Radiated Spurious Emission Plots

Appendix D. Duty Cycle Plots



History of this test report

Report No.	Version	Description	Issued Date
FR9O1543-01F	01	Initial issue of report	Feb. 20, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	15.403 (i)	6dB & 26dB Bandwidth	Not Required	-
-	2.1049	99% Occupied Bandwidth	Not Required	-
3.1	15.407 (a)	Maximum Conducted Output Power	Pass	-
-	15.407 (a)	Power Spectral Density	Not Required	-
3.2	15.407(b)	Unwanted Emissions	Pass	Under limit 10.84 dB at 30.540 MHz
-	15.207	AC Conducted Emission	Not Required	-
-	15.407 (c)	Automatically Discontinue Transmission	Not Required	-
3.3	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

Remark: This is a spot check data report and data performed in appendix of this report are chosen from the worst case of the original FCC ID report. All the test cases were performed on original report which can be referred to Sporton Report Number FR901542-02F.

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang
Report Producer: Yvonne Cheng



1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac/ax, NFC, GNSS and WPC.

Product Specification subjective to this standard	
Antenna Type / Gain	<Ant. 1>: Loop Antenna with gain -6.50 dBi <Ant. 2>: Monopole Antenna with gain -3.70 dBi

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.320	QV71000Y2C	RF Conducted Measurement
		QV7100CH2C	Radiated Spurious Emission
		QV7100AM2C	

Accessory List	
AC Adapter	Model Name : UCH32
	S/N: 6218W30200197
Earphone	Model Name : STH40D
	S/N : N/A
Bluetooth Earphone	Model Name : SBH82D
	S/N : N/A
USB Cable	Model Name : UCB24
	S/N : N/A
Audio Cable	Model Name : EC234
	S/N : N/A

Note:

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report.
3. For other wireless features of this EUT, test report will be issued separately.



1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated:, radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40, 802.11ac VHT40, and 802.11ax HE40.
2. The above Frequency and Channel in "#n" were 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Ch. #		Band IV : 5725-5850 MHz	
		802.11n HT20	802.11ax HE40
L	Low		
M	Middle	157	
H	High		159

2.3 Connection Diagram of Test System

< For Radiated Emissions Measurement >



2.4 EUT Operation Test Setup

The RF test items, utility "FTMC_bridge_forURC_v0.39" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3 Test Result

3.1 Maximum Conducted Output Power Measurement

3.1.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.


3.1.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.1.4 Test Setup



3.1.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.2 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.2.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:
 15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.
- (ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.2.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz



For radiated emissions from 18GHz~40GHz



3.2.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.2.6 Test Result of Radiated Band Edges

Please refer to Appendix B and C.

3.2.7 Duty Cycle

Please refer to Appendix D.

3.2.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.3 Antenna Requirements

3.3.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.3.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Feb. 06, 2020	Dec. 25, 2020	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	35419 & 03	30MHz~1GHz	Apr. 30, 2019	Feb. 06, 2020	Apr. 29, 2020	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 06, 2019	Feb. 06, 2020	Dec. 05, 2020	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-001 01800-30-10 P	1590075	1GHz~18GHz	Apr. 24, 2019	Feb. 06, 2020	Apr. 23, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 20, 2019	Feb. 06, 2020	May 19, 2020	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A0236 2	1GHz~26.5GHz	Nov. 01, 2019	Feb. 06, 2020	Oct. 31, 2020	Radiation (03CH07-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 12, 2019	Feb. 06, 2020	Dec. 12, 2020	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY532900 53	20Hz~26.5GHz	Jan. 18, 2020	Feb. 06, 2020	Jan. 17, 2021	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9030A	MY523502 76	3Hz~44GHz	Apr. 02, 2019	Feb. 06, 2020	Apr. 01, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4 MY28655/4	9kHz~30MHz	Feb. 26, 2019	Feb. 06, 2020	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	30MHz~1GHz	Feb. 26, 2019	Feb. 06, 2020	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	1GHz~18GHz	Feb. 26, 2019	Feb. 06, 2020	Feb. 25, 2020	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2858/2	18GHz~40GHz	Feb. 26, 2019	Feb. 06, 2020	Feb. 25, 2020	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 251	18GHz~40GHz	Nov. 26, 2019	Feb. 06, 2020	Nov. 25, 2020	Radiation (03CH07-HY)
Hygrometer	TECPEL	HTC-2	1	N/A	Jun. 17, 2019	Feb. 06, 2020	Jun. 16, 2020	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Feb. 06, 2020	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF7802083 68	Control Ant Mast	N/A	Feb. 06, 2020	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Feb. 06, 2020	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Feb. 06, 2020	N/A	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	805040046 56H	N/A	N/A	Feb. 06, 2020	N/A	Radiation (03CH07-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H2	41410069	N/A	Jun. 17, 2019	Jan. 13, 2020~ Jan. 21, 2020	Jun. 16, 2020	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030S NO32	9kHz~6GHz	Dec. 17, 2019	Jan. 13, 2020~ Jan. 21, 2020	Dec. 16, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Aug. 14, 2019	Jan. 13, 2020~ Jan. 21, 2020	Aug. 13, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1208382	N/A	Mar. 27, 2019	Jan. 13, 2020~ Jan. 21, 2020	Mar. 26, 2020	Conducted (TH05-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Hank Hsu	Temperature:	21~25	°C
Test Date:	2019/1/20~1/22	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

Band IV single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	10.80	11.20		30.00	30.00	-6.50	-3.70	Pass
11a	6Mbps	1	157	5785	11.10	11.30		30.00	30.00	-6.50	-3.70	Pass
11a	6Mbps	1	165	5825	11.40	11.00		30.00	30.00	-6.50	-3.70	Pass
HT20	MCS0	1	149	5745	10.80	11.10		30.00	30.00	-6.50	-3.70	Pass
HT20	MCS0	1	157	5785	11.10	11.30		30.00	30.00	-6.50	-3.70	Pass
HT20	MCS0	1	165	5825	11.40	11.40		30.00	30.00	-6.50	-3.70	Pass
HT40	MCS0	1	151	5755	11.00	11.30		30.00	30.00	-6.50	-3.70	Pass
HT40	MCS0	1	159	5795	11.00	11.10		30.00	30.00	-6.50	-3.70	Pass
VHT20	MCS0	1	149	5745	10.70	11.00		30.00	30.00	-6.50	-3.70	Pass
VHT20	MCS0	1	157	5785	11.00	11.20		30.00	30.00	-6.50	-3.70	Pass
VHT20	MCS0	1	165	5825	11.30	11.30		30.00	30.00	-6.50	-3.70	Pass
VHT40	MCS0	1	151	5755	10.90	11.20		30.00	30.00	-6.50	-3.70	Pass
VHT40	MCS0	1	159	5795	10.90	11.00		30.00	30.00	-6.50	-3.70	Pass
VHT80	MCS0	1	155	5775	11.20	11.20		30.00	30.00	-6.50	-3.70	Pass

Band IV MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	10.80	11.20	14.01	30.00		-3.70		Pass
11a	6Mbps	2	157	5785	11.10	11.30	14.21	30.00		-3.70		Pass
11a	6Mbps	2	165	5825	11.40	11.00	14.21	30.00		-3.70		Pass
HT20	MCS0	2	149	5745	10.80	11.10	13.96	30.00		-3.70		Pass
HT20	MCS0	2	157	5785	11.10	11.30	14.21	30.00		-3.70		Pass
HT20	MCS0	2	165	5825	11.40	11.40	14.41	30.00		-3.70		Pass
HT40	MCS0	2	151	5755	11.00	11.30	14.16	30.00		-3.70		Pass
HT40	MCS0	2	159	5795	11.00	11.10	14.06	30.00		-3.70		Pass
VHT20	MCS0	2	149	5745	10.70	11.00	13.86	30.00		-3.70		Pass
VHT20	MCS0	2	157	5785	11.00	11.20	14.11	30.00		-3.70		Pass
VHT20	MCS0	2	165	5825	11.30	11.30	14.31	30.00		-3.70		Pass
VHT40	MCS0	2	151	5755	10.90	11.20	14.06	30.00		-3.70		Pass
VHT40	MCS0	2	159	5795	10.90	11.00	13.96	30.00		-3.70		Pass
VHT80	MCS0	2	155	5775	11.20	11.20	14.21	30.00		-3.70		Pass

TEST RESULTS DATA
Average Power Table

Band IV single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HE20	MCS0	1	149	5745	Full	11.20	11.10		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	149	5745	26/0	8.50	8.70		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	149	5745	52/37	11.00	11.10		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	149	5745	106/53	11.10	11.30		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	157	5785	Full	11.10	11.30		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	157	5785	26/4	8.70	8.90		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	157	5785	52/38	11.20	11.00		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	157	5785	106/53	10.90	11.10		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	165	5825	Full	10.90	11.00		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	165	5825	26/8	8.50	8.70		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	165	5825	52/40	10.90	11.20		30.00	30.00	-6.50	-3.70	Pass
HE20	MCS0	1	165	5825	106/54	11.30	11.10		30.00	30.00	-6.50	-3.70	Pass
HE40	MCS0	1	151	5755	Full	11.00	11.30		30.00	30.00	-6.50	-3.70	Pass
HE40	MCS0	1	151	5755	242/61	11.20	11.00		30.00	30.00	-6.50	-3.70	Pass
HE40	MCS0	1	159	5795	Full	11.10	11.10		30.00	30.00	-6.50	-3.70	Pass
HE40	MCS0	1	159	5795	242/62	11.10	11.20		30.00	30.00	-6.50	-3.70	Pass
HE80	MCS0	1	155	5775	Full	11.00	11.00		30.00	30.00	-6.50	-3.70	Pass
HE80	MCS0	1	155	5775	484/65	11.10	11.00		30.00	30.00	-6.50	-3.70	Pass
HE80	MCS0	1	155	5775	484/66	11.00	11.20		30.00	30.00	-6.50	-3.70	Pass

Band IV MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
HE20	MCS0	1	149	5745	Full	11.20	11.10	14.16	30.00		-3.70		Pass
HE20	MCS0	1	149	5745	26/0	8.50	8.70	11.61	30.00		-3.70		Pass
HE20	MCS0	1	149	5745	52/37	11.00	11.10	14.06	30.00		-3.70		Pass
HE20	MCS0	1	149	5745	106/53	11.10	11.30	14.21	30.00		-3.70		Pass
HE20	MCS0	1	157	5785	Full	11.10	11.30	14.21	30.00		-3.70		Pass
HE20	MCS0	1	157	5785	26/4	8.70	8.90	11.81	30.00		-3.70		Pass
HE20	MCS0	1	157	5785	52/38	11.20	11.00	14.11	30.00		-3.70		Pass
HE20	MCS0	1	157	5785	106/53	10.90	11.10	14.01	30.00		-3.70		Pass
HE20	MCS0	1	165	5825	Full	10.90	11.00	13.96	30.00		-3.70		Pass
HE20	MCS0	1	165	5825	26/8	8.50	8.70	11.61	30.00		-3.70		Pass
HE20	MCS0	1	165	5825	52/40	10.90	11.20	14.06	30.00		-3.70		Pass
HE20	MCS0	1	165	5825	106/54	11.30	11.10	14.21	30.00		-3.70		Pass
HE40	MCS0	1	151	5755	Full	11.00	11.30	14.16	30.00		-3.70		Pass
HE40	MCS0	1	151	5755	242/61	11.20	11.00	14.11	30.00		-3.70		Pass
HE40	MCS0	1	159	5795	Full	11.10	11.10	14.11	30.00		-3.70		Pass
HE40	MCS0	1	159	5795	242/62	11.10	11.20	14.16	30.00		-3.70		Pass
HE80	MCS0	1	155	5775	Full	11.00	11.00	14.01	30.00		-3.70		Pass
HE80	MCS0	1	155	5775	484/65	11.10	11.00	14.06	30.00		-3.70		Pass
HE80	MCS0	1	155	5775	484/66	11.00	11.20	14.11	30.00		-3.70		Pass



Appendix B. Radiated Spurious Emission

Test Engineer :	Jesse Wang	Temperature :	21~24°C
		Relative Humidity :	53~62%

Band 4 - 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1+2		(MHz)	(dBμV/m)	(dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11n HT20 CH 157 5785MHz		5642	50.49	-17.71	68.2	39.27	34.8	11.73	35.31	100	245	P	H
		5663.2	49.87	-28.13	78	38.71	34.7	11.78	35.32	100	245	P	H
		5707.8	49.53	-57.86	107.39	38.02	35	11.83	35.32	100	245	P	H
		5724.8	48.25	-73.49	121.74	36.74	35	11.83	35.32	100	245	P	H
	*	5785	107.4	-	-	95.8	35	11.93	35.33	100	245	P	H
	*	5785	97.91	-	-	86.31	35	11.93	35.33	100	245	A	H
		5853.2	48.97	-65.93	114.9	37.33	35	11.98	35.34	100	245	P	H
		5859.2	48.66	-60.96	109.62	36.95	35.07	11.98	35.34	100	245	P	H
		5884.8	49.24	-48.68	97.92	37.43	35.13	12.02	35.34	100	245	P	H
		5926.6	48.86	-19.34	68.2	36.93	35.2	12.07	35.34	100	245	P	H
		5611.6	50.32	-17.88	68.2	38.95	35	11.68	35.31	400	295	P	V
		5684.4	50.35	-43.34	93.69	38.89	35	11.78	35.32	400	295	P	V
		5719	49.97	-60.55	110.52	38.46	35	11.83	35.32	400	295	P	V
		5720.4	48.76	-62.95	111.71	37.25	35	11.83	35.32	400	295	P	V
	*	5785	102.23	-	-	90.63	35	11.93	35.33	400	295	P	V
	*	5785	91.79	-	-	80.19	35	11.93	35.33	400	295	A	V
		5851	48.65	-71.27	119.92	37.01	35	11.98	35.34	400	295	P	V
		5873.2	50.29	-55.41	105.7	38.48	35.13	12.02	35.34	400	295	P	V
	5875.8	49.91	-54.7	104.61	38.1	35.13	12.02	35.34	400	295	P	V	
	5930	49.01	-19.19	68.2	37.08	35.2	12.07	35.34	400	295	P	V	



**Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20		11570	48.45	-25.55	74	49.07	38.33	18.41	57.36	100	0	P	H
		17355	53.51	-14.69	68.2	45.15	41.5	22.8	55.94	100	0	P	H
													H
													H
CH 157 5785MHz		11570	46.93	-27.07	74	47.55	38.33	18.41	57.36	100	0	P	V
		17355	54.03	-14.17	68.2	45.67	41.5	22.8	55.94	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz
WIFI 802.11n HT20 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11n HT20 LF		30.27	22.18	-17.82	40	26.36	24.6	1.2	29.98	-	-	P	H	
		156.36	31.81	-11.69	43.5	42.74	16.76	2.22	29.91	-	-	P	H	
		260.31	27.2	-18.8	46	34.69	19.54	2.77	29.8	-	-	P	H	
		456.1	29.38	-16.62	46	32.63	23.08	3.47	29.8	-	-	P	H	
		738.9	30.62	-15.38	46	28.17	27.64	4.28	29.47	-	-	P	H	
		954.5	34.83	-11.17	46	27.71	30.59	5.06	28.53	100	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			30.54	29.16	-10.84	40	33.85	24.09	1.2	29.98	100	0	P	V
			141.51	27.25	-16.25	43.5	37.61	17.36	2.21	29.93	-	-	P	V
			300	24.94	-21.06	46	32.73	19.16	2.81	29.76	-	-	P	V
			642.3	28.72	-17.28	46	28.08	26.22	4.08	29.66	-	-	P	V
			820.1	32.68	-13.32	46	29.38	27.81	4.7	29.21	-	-	P	V
			954.5	34.86	-11.14	46	27.74	30.59	5.06	28.53	-	-	P	V
													V	
												V		
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Band 4 - 5725~5850MHz

WIFI 802.11ax HE40_Partial 242 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11ax HE40 Partial 242/62 CH 159 5795MHz		5623.4	50.59	-17.61	68.2	39.27	34.9	11.73	35.31	102	246	P	H	
		5668	51.4	-30.16	81.56	40.09	34.85	11.78	35.32	102	246	P	H	
		5718.2	52.95	-57.35	110.3	41.44	35	11.83	35.32	102	246	P	H	
		5722.4	55.04	-61.23	116.27	43.53	35	11.83	35.32	102	246	P	H	
	*	5795	104.68	-	-	93.08	35	11.93	35.33	102	246	P	H	
	*	5795	94.03	-	-	82.43	35	11.93	35.33	102	246	A	H	
		5854.8	52.27	-58.99	111.26	40.56	35.07	11.98	35.34	102	246	P	H	
		5861.4	56.78	-52.23	109.01	45.03	35.07	12.02	35.34	102	246	P	H	
		5883.8	51.94	-46.73	98.67	40.13	35.13	12.02	35.34	102	246	P	H	
		5939.2	50.17	-18.03	68.2	38.24	35.2	12.07	35.34	102	246	P	H	
														H
														H
			5643.6	49.71	-18.49	68.2	38.49	34.8	11.73	35.31	400	315	P	V
			5696.4	50.63	-51.92	102.55	39.17	35	11.78	35.32	400	315	P	V
			5710.2	50.36	-57.7	108.06	38.85	35	11.83	35.32	400	315	P	V
			5720.8	49.6	-63.02	112.62	38.09	35	11.83	35.32	400	315	P	V
	*		5795	101.02	-	-	89.42	35	11.93	35.33	400	315	P	V
	*		5795	90.25	-	-	78.65	35	11.93	35.33	400	315	A	V
			5851.2	50.19	-69.27	119.46	38.55	35	11.98	35.34	400	315	P	V
			5872.2	49.07	-56.91	105.98	37.26	35.13	12.02	35.34	400	315	P	V
		5913.4	50.35	-26.41	76.76	38.42	35.2	12.07	35.34	400	315	P	V	
		5947.2	49.39	-18.81	68.2	37.42	35.2	12.11	35.34	400	315	P	V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 													



**Band 4 5725~5850MHz
WIFI 802.11ax HE40_Partial 242 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ax HE40 Partial 242/62 CH 159 5795MHz		11590	47.37	-26.63	74	47.91	38.37	18.43	57.34	100	0	P	H
		17385	53.11	-15.09	68.2	44.61	41.57	22.84	55.91	100	0	P	H
													H
													H
		11590	47.34	-26.66	74	47.88	38.37	18.43	57.34	100	0	P	V
		17385	53.5	-14.7	68.2	45	41.57	22.84	55.91	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2412MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Jesse Wang	Temperature :	21~24°C
		Relative Humidity :	53~62%

Note symbol

-L	Low channel location
-R	High channel location



Band 4 - 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
<p align="center">Peak</p>	<p>Date: 2020-02-06 PEAK_BE(B4)_16-24</p> <p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 901543-01 Mode : 8</p>	<p>Date: 2020-02-06 PEAKLMB AVG_51</p> <p>Site : 03CH07-HY Condition : PEAKLMB 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 901543-01 Mode : 8</p>
<p align="center">Peak</p>	<p>Date: 2020-02-06 PEAK_BE(B4)_16-24</p> <p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 901543-01 Mode : 8</p>	<p align="center">Left blank</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Vertical	Fundamental
<p>Peak</p>	<p>Date: 2020-02-06 PEAK_BE(B4)_16-24</p> <p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 8</p>	<p>Date: 2020-02-06 PEAK(B4)</p> <p>Site : 03CH07-HY Condition : PEAK(LUN1) 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 8</p>
<p>Peak</p>	<p>Date: 2020-02-06 PEAK_BE(B4)_16-24</p> <p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 8</p>	<p>Left blank</p>



Band 4 - 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

Table with 2 columns: Horizontal and Vertical. Each column contains a spectral plot showing Level (dBuV/m) vs Frequency (MHz) with Peak and Avg. markers. Includes metadata like Site, Condition, Detector, Project, and Mode.



Emission below 1GHz
5GHz WIFI 802.11n HT20 (LF)

WIFI	5GHz WIFI	
ANT	802.11n HT20 LF	
1+2	Horizontal	Vertical
QP / Peak	<p>Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(G) HORIZONTAL Detector : Peak Project : 901543-01 Mode : 10</p>	<p>Site : 03CH07-HY Condition : QP 3m LF-ANT-35419(G) VERTICAL Detector : Peak Project : 901543-01 Mode : 10</p>



Band 4 - 5725~5850MHz

WIFI 802.11ax HE40 Partial 242 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	<p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_0007596z HORIZONTAL Detector : Peak Project : 901543-01 Mode : 9</p>	<p>Site : 03CH07-HY Condition : PEAK_LNB() 3m HF_ANT_0007596z HORIZONTAL Detector : Peak Project : 901543-01 Mode : 9</p>
Peak	<p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_0007596z HORIZONTAL Detector : Peak Project : 901543-01 Mode : 9</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
1+2	Vertical	Fundamental
<p>Peak</p>	<p>Date: 2020-02-06 PEAK_BE(B4)_16-24</p> <p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 9</p>	<p>Date: 2020-02-06 PEAK(B4)_16-24 AVG_C1</p> <p>Site : 03CH07-HY Condition : PEAK(LUN1) 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 9</p>
<p>Peak</p>	<p>Date: 2020-02-06 PEAK_BE(B4)_16-24</p> <p>Site : 03CH07-HY Condition : PEAK_BE(B4)_16-24 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 9</p>	<p>Left blank</p>



Band 4 - 5725~5850MHz

WIFI 802.11ax HE40 Partial 242 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	<p>Site : 09CH07-HY Condition : PEAK(UWB) 3m HF_ANT_00075962 HORIZONTAL Detector : Peak Project : 901543-01 Mode : 9</p>	<p>Site : 09CH07-HY Condition : PEAK(UWB) 3m HF_ANT_00075962 VERTICAL Detector : Peak Project : 901543-01 Mode : 9</p>




Appendix D. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1+2	5GHz 802.11n HT20 for Ant. 1	100.00	-	-	10Hz	0.00
1+2	5GHz 802.11n HT20 for Ant. 2	100.00	-	-	10Hz	0.00
1+2	5GHz 802.11ax HE40 for Ant. 1	100.00	-	-	10Hz	0.00
1+2	5GHz 802.11ax HE40 for Ant. 2	100.00	-	-	10Hz	0.00




MIMO <Ant. 1>

802.11n HT20



Date: 1.JAN.2003 02:20:19

802.11ax HE40




Date: 1.JAN.2003 03:02:04




MIMO <Ant. 2>

802.11n HT20



Date: 1.JAN.2003 02:22:50

802.11ax HE40



Date: 1.JAN.2003 03:03:09

—————THE END—————