



FCC SAR TEST REPORT

FCC ID : PY7-88421C
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Jan. 09, 2020 and testing was started from Jan. 10, 2020 and completed on Jan. 21, 2020. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance 4
2. Guidance Applied..... 5
3. Equipment Under Test (EUT) Information 5
3.1 General Information 5
3.2 Device Serial Number 5
3.3 General LTE SAR Test and Reporting Considerations 6
4. RF Exposure Limits..... 8
4.1 Uncontrolled Environment..... 8
4.2 Controlled Environment..... 8
5. Specific Absorption Rate (SAR)..... 9
5.1 Introduction 9
5.2 SAR Definition..... 9
6. System Description and Setup10
6.1 E-Field Probe 11
6.2 Data Acquisition Electronics (DAE) 11
6.3 Phantom..... 12
6.4 Device Holder..... 13
7. Measurement Procedures14
7.1 Spatial Peak SAR Evaluation 14
7.2 Power Reference Measurement..... 15
7.3 Area Scan 15
7.4 Zoom Scan..... 16
7.5 Volume Scan Procedures 16
7.6 Power Drift Monitoring..... 16
8. Test Equipment List17
9. System Verification18
9.1 Tissue Simulating Liquids..... 18
9.2 Tissue Verification 19
9.3 System Performance Check Results..... 20
10. RF Exposure Positions21
10.1 Ear and handset reference point 21
10.2 Definition of the cheek position 22
10.3 Definition of the tilt position 23
10.4 Body Worn Accessory 23
10.5 Product Specific Exposure 24
10.6 Wireless Router..... 24
11. Conducted RF Output Power (Unit: dBm).....25
12. RF Exposure Conditions37
13. SAR Test Results38
13.1 Head SAR 39
13.2 Hotspot SAR 40
13.3 Body Worn Accessory SAR..... 41
14. Simultaneous Transmission Analysis42
14.1 Head Exposure Conditions 43
14.2 Hotspot Exposure Conditions..... 44
14.3 Body-Worn Accessory Exposure Conditions 45
14.4 Product Specific Exposure Conditions 45
15. Uncertainty Assessment46
16. References.....46
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos



History of this test report

Report No.	Version	Description	Issued Date
FA9O1525-01	01	Initial issue of report	Feb. 27, 2020



1. Statement of Compliance

Applicant Name	Sony Mobile Communications Inc.			
EUT Description	GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, GPS and NFC			
Brand Name	Sony			
FCC ID	PY7-88421C			
HW Version	A			
SW Version	0.210			
RF Exposure Conditions	Equipment Class			
	Licensed	DTS	NII	DSS
Head (1g SAR W/kg)	0.40	0.15	0.12	0.23
Body-Worn (1g SAR W/kg)	0.46	0.08	0.13	
Wireless Router (1g SAR W/kg)	0.81	0.17		0.19
Product Specific (10g SAR W/kg)			0.48	
Highest Simultaneous Transmission (1g SAR W/kg)	Head: 0.75 Body-worn: 0.97 Hotspot: 0.97	Head: 0.54 Body-worn: 0.54 Hotspot: 0.95	Head: 0.75 Body-worn: 0.97 Hotspot: NA	Head: 0.75 Body-worn: 0.97 Hotspot: 0.97
Highest Simultaneous Transmission (10g SAR W/kg)			Product Specific: 0.48	
Date Tested	2020/1/10 ~ 2020/1/21			
Test Result	Pass			
Remark:				
1. This device 2.4GHz WLAN support Hotspot operation and Bluetooth support tethering applications.				
2. The FCC ID: PY7-45077R and FCC ID: PY7-88421C are HW identical, the difference is only SW, and each supported bands are handled by only SW. Only WCDMA B4 and LTE B4/B41 are added in this report.				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang
Report Producer: Wan Liu



2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01
- FCC KDB 941225 D07 UMPC Mini Tablet v01r02

3. Equipment Under Test (EUT) Information

3.1 General Information

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	· GSM Voice · GPRS (GMSK) · EDGE (8PSK)	Multi-Slot Class: Class 33
	Does device support dual transfer mode? (Yes)		
W-CDMA (UMTS)	Band 4 Band 5	· AMR / RMC 12.2Kbps · HSDPA (Rel.5) · HSUPA (Rel.6)	
LTE (FDD)	Band 4 Band 5 Band 12	· QPSK · 16QAM · 64QAM	
LTE (TDD)	Band 41	· Rel 12 Carrier Aggregation Downlink only (the detail refer to Section 11)	
WiFi	2.4GHz: 2412 MHz ~ 2462 MHz	· 11b · 11g · 11n (HT20)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5720 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	· 11a · 11n (HT20) · 11n (HT40) · 11ac (VHT20) · 11ac (VHT40) · 11ac (VHT80)	
Bluetooth	2.4GHz	· BR / EDR / LE	
NFC	13.56MHz	· ASK	

3.2 Device Serial Number

Band	SN
WWAN	BH95008ZJL

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.



3.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	PY7-88421C																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 41: 2547.5 MHz ~ 2652.5 MHz																																																														
Channel Bandwidth	LTE Band 04: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 12: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM / 64QAM																																																														
LTE Voice / Data requirements	Voice and Data																																																														
LTE MPR permanently built-in by design	<p>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														
LTE Carrier Aggregation Combinations	Intra-Band possible combinations and the detail power measurement please referred to section 11.																																																														
LTE Carrier Aggregation Additional Information	1. This device supports maximum of 2 carriers in the downlink. Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.																																																														



Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	40165	2547.5	40190	2550	40215	2552.5	40240	2555				
L	40485	2579.5	40490	2580	40495	2580.5	40500	2581				
M	40620	2593	40620	2593	40620	2593	40620	2593				
H	40805	2611.5	40790	2610	40785	2609.5	40770	2608				
H	41215	2652.5	41190	2650	41165	2647.5	41140	2645				



4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.



5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.


6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE


6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g



7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

Table with 3 columns: Parameter, ≤ 3 GHz, > 3 GHz. Rows include: Maximum distance from closest measurement point, Maximum probe angle, and Maximum area scan spatial resolution.

7.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	1750MHz System Validation Kit	D1750V2	1112	Mar. 07, 2019	Mar. 06, 2020
SPEAG	2600MHz System Validation Kit	D2600V2	1078	Mar. 06, 2019	Mar. 05, 2020
SPEAG	Data Acquisition Electronics	DAE4	854	May. 21, 2019	May. 20, 2020
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 14, 2019	Nov. 13, 2020
SPEAG	Dosimetric E-Field Probe	ES3DV3	3184	Sep. 25, 2019	Sep. 24, 2020
SPEAG	Dosimetric E-Field Probe	EX3DV4	3642	Apr. 29, 2019	Apr. 28, 2020
RCPTWN	Thermometer	HTC-1	TM685-1	Nov. 12, 2019	Nov. 11, 2020
RCPTWN	Thermometer	HTC-1	TM560-2	Nov. 12, 2019	Nov. 11, 2020
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Oct. 31, 2019	Oct. 30, 2020
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 27, 2019	May. 26, 2020
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Nov. 20, 2019	Nov. 19, 2020
Agilent	ENA Network Analyzer	E5071C	MY46104758	Sep. 06, 2019	Sep. 05, 2020
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 18, 2019	Sep. 17, 2020
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 10, 2019	Sep. 09, 2020
Anritsu	Power Meter	ML2495A	1036004	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Sensor	MA2411B	1027253	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Meter	ML2495A	1419002	May. 29, 2019	May. 28, 2020
Anritsu	Power Sensor	MA2411B	1339124	May. 29, 2019	May. 28, 2020
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 27, 2019	Aug. 26, 2020
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 27, 2019	Jun. 26, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 16, 2019	Oct. 15, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 12, 2019	Aug. 11, 2020
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR



9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Tissue check appears that head liquid is also used for body SAR test

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
1750	22.2	1.377	41.785	1.37	40.10	0.51	4.20	±5	2020/1/10
2600	22.2	1.987	38.917	1.96	39.00	1.38	-0.21	±5	2020/1/21

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/1/10	1750	250	D1750V2-1112	ES3DV3 - SN3184	DAE4 Sn1399	8.85	36.70	35.4	-3.54
2020/1/21	2600	250	D2600V2-1078	EX3DV4 - SN3642	DAE4 Sn854	14.30	57.60	57.2	-0.69




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



10.5 Product Specific Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



11. Conducted RF Output Power (Unit: dBm)

<WCDMA Conducted Power>

- 1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
b. The RF path losses were compensated into the measurements.
c. A call was established between EUT and Base Station with following setting:
i. Set Gain Factors (beta_c and beta_d) and parameters were set according to each
ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
iii. Set RMC 12.2Kbps + HSDPA mode.
iv. Set Cell Power = -86 dBm
v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
vi. Select HSDPA Uplink Parameters
vii. Set Delta ACK, Delta NACK and Delta CQI = 8
viii. Set Ack-Nack Repetition Factor to 3
ix. Set CQI Feedback Cycle (k) to 4 ms
x. Set CQI Repetition Factor to 2
xi. Power Ctrl Mode = All Up bits
d. The transmitted maximum output power was recorded.

Table C.10.1.4: beta values for transmitter characteristics tests with HS-DPCCH

Table with 8 columns: Sub-test, beta_c, beta_d, beta_d (SF), beta_c/beta_d, beta_hs (Note 1, Note 2), CM (dB) (Note 3), MPR (dB) (Note 3). Rows 1-4 show test configurations. Includes notes 1-4 regarding ACK/NACK/CQI values and MPR calculations.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCl
 - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration



<WCDMA Conducted Power>

General Note:


1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA .

Band		WCDMA IV			Tune-up Limit (dBm)
TX Channel		1312	1413	1513	
Rx Channel		1537	1638	1738	
Frequency (MHz)		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	21.52	21.60	21.55	22.70
3GPP Rel 99	RMC 12.2Kbps	21.51	21.61	21.58	22.70
3GPP Rel 6	HSDPA Subtest-1	20.49	20.62	20.59	22.00
3GPP Rel 6	HSDPA Subtest-2	20.52	20.63	20.60	22.00
3GPP Rel 6	HSDPA Subtest-3	20.05	20.10	20.12	21.50
3GPP Rel 6	HSDPA Subtest-4	20.04	20.09	20.10	21.50
3GPP Rel 6	HSUPA Subtest-1	20.49	20.60	20.59	22.00
3GPP Rel 6	HSUPA Subtest-2	18.49	18.61	18.61	20.00
3GPP Rel 6	HSUPA Subtest-3	19.51	19.60	19.60	21.00
3GPP Rel 6	HSUPA Subtest-4	18.52	18.61	18.60	20.00
3GPP Rel 6	HSUPA Subtest-5	20.50	20.60	20.60	22.00


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	21.76	21.73	21.79	23	0
20	QPSK	1	49	21.82	21.74	21.97		
20	QPSK	1	99	21.65	21.70	21.87		
20	QPSK	50	0	21.31	21.27	21.34	22.5	0.5
20	QPSK	50	24	21.24	21.33	21.35		
20	QPSK	50	50	21.21	21.27	21.47		
20	QPSK	100	0	21.24	21.27	21.37	22.5	0.5
20	16QAM	1	0	21.63	21.62	21.67		
20	16QAM	1	49	21.70	21.67	21.83		
20	16QAM	1	99	21.54	21.60	21.76	21.5	1.5
20	16QAM	50	0	20.45	20.36	20.43		
20	16QAM	50	24	20.34	20.42	20.50		
20	16QAM	50	50	20.31	20.37	20.58	21.5	1.5
20	16QAM	100	0	20.32	20.35	20.44		
20	16QAM	100	0	20.32	20.35	20.44		
20	64QAM	1	0	20.54	20.51	20.60	21.5	1.5
20	64QAM	1	49	20.64	20.53	20.76		
20	64QAM	1	99	20.46	20.47	20.69		
20	64QAM	50	0	19.45	19.36	19.44	20.5	2.5
20	64QAM	50	24	19.35	19.44	19.49		
20	64QAM	50	50	19.30	19.37	19.58		
20	64QAM	100	0	19.34	19.35	19.46	20.5	2.5
20	64QAM	100	0	19.34	19.35	19.46		
20	64QAM	100	0	19.34	19.35	19.46		
Channel				20025	20175	20325		
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	21.79	21.80	21.85	23	0
15	QPSK	1	37	21.83	21.80	21.96		
15	QPSK	1	74	21.69	21.76	21.92		
15	QPSK	36	0	21.37	21.29	21.41	22.5	0.5
15	QPSK	36	20	21.38	21.32	21.53		
15	QPSK	36	39	21.27	21.29	21.51		
15	QPSK	75	0	21.25	21.31	21.36	22.5	0.5
15	16QAM	1	0	21.66	21.63	21.61		
15	16QAM	1	37	21.73	21.66	21.81		
15	16QAM	1	74	21.57	21.59	21.68	21.5	1.5
15	16QAM	36	0	20.45	20.41	20.38		
15	16QAM	36	20	20.50	20.42	20.50		
15	16QAM	36	39	20.37	20.38	20.61	21.5	1.5
15	16QAM	75	0	20.34	20.41	20.47		
15	16QAM	75	0	20.34	20.41	20.47		
15	64QAM	1	0	20.59	20.57	20.56	21.5	1.5
15	64QAM	1	37	20.65	20.60	20.79		
15	64QAM	1	74	20.46	20.52	20.70		
15	64QAM	36	0	19.48	19.42	19.51	20.5	2.5
15	64QAM	36	20	19.54	19.45	19.65		
15	64QAM	36	39	19.39	19.42	19.64		
15	64QAM	75	0	19.34	19.41	19.48	20.5	2.5
15	64QAM	75	0	19.34	19.41	19.48		
15	64QAM	75	0	19.34	19.41	19.48		



Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	21.81	21.82	21.95	23	0
10	QPSK	1	25	21.86	21.84	21.91		
10	QPSK	1	49	21.81	21.79	21.86		
10	QPSK	25	0	21.36	21.36	21.44	22.5	0.5
10	QPSK	25	12	21.39	21.36	21.46		
10	QPSK	25	25	21.38	21.33	21.39		
10	QPSK	50	0	21.38	21.33	21.41	22.5	0.5
10	16QAM	1	0	21.69	21.72	21.80		
10	16QAM	1	25	21.72	21.68	21.80		
10	16QAM	1	49	21.71	21.66	21.74	21.5	1.5
10	16QAM	25	0	20.46	20.41	20.54		
10	16QAM	25	12	20.49	20.47	20.56		
10	16QAM	25	25	20.47	20.43	20.50	21.5	1.5
10	16QAM	50	0	20.48	20.43	20.51		
10	64QAM	1	0	20.60	20.63	20.75		
10	64QAM	1	25	20.65	20.61	20.73	21.5	1.5
10	64QAM	1	49	20.64	20.60	20.69		
10	64QAM	25	0	19.47	19.42	19.55		
10	64QAM	25	12	19.51	19.48	19.58	20.5	2.5
10	64QAM	25	25	19.49	19.43	19.52		
10	64QAM	50	0	19.49	19.46	19.53		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	21.79	21.81	21.87	23	0
5	QPSK	1	12	21.84	21.82	21.88		
5	QPSK	1	24	21.78	21.76	21.84		
5	QPSK	12	0	21.37	21.33	21.44	22.5	0.5
5	QPSK	12	7	21.39	21.40	21.45		
5	QPSK	12	13	21.34	21.33	21.40		
5	QPSK	25	0	21.34	21.35	21.38	22.5	0.5
5	16QAM	1	0	21.65	21.63	21.76		
5	16QAM	1	12	21.70	21.67	21.80		
5	16QAM	1	24	21.66	21.64	21.75	21.5	1.5
5	16QAM	12	0	20.46	20.43	20.52		
5	16QAM	12	7	20.49	20.48	20.56		
5	16QAM	12	13	20.44	20.45	20.54	21.5	1.5
5	16QAM	25	0	20.44	20.40	20.49		
5	64QAM	1	0	20.62	20.61	20.72		
5	64QAM	1	12	20.64	20.60	20.71	21.5	1.5
5	64QAM	1	24	20.60	20.56	20.68		
5	64QAM	12	0	19.51	19.49	19.60		
5	64QAM	12	7	19.54	19.50	19.63	20.5	2.5
5	64QAM	12	13	19.49	19.49	19.59		
5	64QAM	25	0	19.45	19.42	19.53		



FCC SAR TEST REPORT

Report No. : FA901525-01

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	21.78	21.79	21.88	23	0
3	QPSK	1	8	21.82	21.80	21.90		
3	QPSK	1	14	21.79	21.76	21.86		
3	QPSK	8	0	21.31	21.33	21.43	22.5	0.5
3	QPSK	8	4	21.34	21.33	21.43		
3	QPSK	8	7	21.34	21.32	21.39		
3	QPSK	15	0	21.33	21.35	21.40	22.5	0.5
3	16QAM	1	0	21.63	21.61	21.75		
3	16QAM	1	8	21.68	21.65	21.79		
3	16QAM	1	14	21.65	21.58	21.71	21.5	1.5
3	16QAM	8	0	20.46	20.45	20.55		
3	16QAM	8	4	20.50	20.49	20.62		
3	16QAM	8	7	20.49	20.45	20.55	21.5	1.5
3	16QAM	15	0	20.45	20.41	20.51		
3	64QAM	1	0	20.57	20.56	20.70		
3	64QAM	1	8	20.63	20.60	20.71	21.5	1.5
3	64QAM	1	14	20.59	20.56	20.67		
3	64QAM	8	0	19.47	19.46	19.56		
3	64QAM	8	4	19.50	19.51	19.62	20.5	2.5
3	64QAM	8	7	19.51	19.45	19.55		
3	64QAM	15	0	19.45	19.41	19.51		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	21.60	21.74	21.83	23	0
1.4	QPSK	1	3	21.70	21.82	21.91		
1.4	QPSK	1	5	21.59	21.73	21.84		
1.4	QPSK	3	0	21.64	21.74	21.86		
1.4	QPSK	3	1	21.68	21.82	21.93		
1.4	QPSK	3	3	21.65	21.77	21.87		
1.4	QPSK	6	0	21.13	21.28	21.38	22.5	0.5
1.4	16QAM	1	0	21.48	21.60	21.71	22.5	0.5
1.4	16QAM	1	3	21.57	21.70	21.80		
1.4	16QAM	1	5	21.47	21.61	21.70		
1.4	16QAM	3	0	21.27	21.35	21.54		
1.4	16QAM	3	1	21.32	21.45	21.56		
1.4	16QAM	3	3	21.29	21.39	21.53		
1.4	16QAM	6	0	20.30	20.41	20.54	21.5	1.5
1.4	64QAM	1	0	20.42	20.55	20.66	21.5	1.5
1.4	64QAM	1	3	20.50	20.59	20.74		
1.4	64QAM	1	5	20.40	20.53	20.64		
1.4	64QAM	3	0	20.42	20.52	20.65		
1.4	64QAM	3	1	20.46	20.57	20.68		
1.4	64QAM	3	3	20.39	20.53	20.63		
1.4	64QAM	6	0	19.24	19.38	19.47	20.5	2.5

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. "special subframe S" contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	6592 · Ts	2192 · Ts	2560 · Ts	7680 · Ts	2192 · Ts	2560 · Ts
1	19760 · Ts			20480 · Ts		
2	21952 · Ts			23040 · Ts		
3	24144 · Ts			25600 · Ts		
4	26336 · Ts			7680 · Ts	4384 · Ts	5120 · Ts
5	6592 · Ts	4384 · Ts	5120 · Ts	20480 · Ts		
6	19760 · Ts			23040 · Ts		
7	21952 · Ts			12800 · Ts		
8	24144 · Ts			-	-	-
9	13168 · Ts			-	-	-

Special subframe (30720·T_s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T_s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.



<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40240	40500	40770	41140		
Frequency (MHz)				2555	2581	2608	2645		
20	QPSK	1	0	24.18	24.31	24.30	24.25	25	0
20	QPSK	1	49	24.16	24.28	24.35	24.29		
20	QPSK	1	99	24.24	24.34	24.36	24.31		
20	QPSK	50	0	22.32	22.45	22.46	22.26	23	2
20	QPSK	50	24	22.31	22.41	22.40	22.26		
20	QPSK	50	50	22.29	22.44	22.44	22.24		
20	QPSK	100	0	22.31	22.32	22.34	22.20		
20	16QAM	1	0	23.26	23.45	23.40	23.38	24	1
20	16QAM	1	49	23.24	23.37	23.44	23.45		
20	16QAM	1	99	23.33	23.45	23.43	23.37		
20	16QAM	50	0	21.32	21.43	21.47	21.38	22	3
20	16QAM	50	24	21.41	21.56	21.54	21.35		
20	16QAM	50	50	21.41	21.54	21.54	21.42		
20	16QAM	100	0	21.39	21.55	21.42	21.33		
20	64QAM	1	0	22.00	22.22	22.14	22.16	23	2
20	64QAM	1	49	22.00	22.12	22.19	22.18		
20	64QAM	1	99	22.10	22.20	22.16	22.11		
20	64QAM	50	0	20.30	20.44	20.45	20.38	21	4
20	64QAM	50	24	20.40	20.56	20.53	20.35		
20	64QAM	50	50	20.39	20.52	20.53	20.41		
20	64QAM	100	0	20.39	20.53	20.41	20.33		
Channel				40215	40495	40785	41165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2552.5	2580.5	2609.5	2647.5		
15	QPSK	1	0	24.21	24.33	24.43	24.47	25	0
15	QPSK	1	37	24.18	24.29	24.39	24.41		
15	QPSK	1	74	24.38	24.43	24.46	24.42		
15	QPSK	36	0	22.21	22.34	22.42	22.34	23	2
15	QPSK	36	20	22.21	22.46	22.46	22.31		
15	QPSK	36	39	22.27	22.43	22.41	22.26		
15	QPSK	75	0	22.30	22.39	22.42	22.32		
15	16QAM	1	0	23.27	23.41	23.49	23.52	24	1
15	16QAM	1	37	23.24	23.35	23.44	23.44		
15	16QAM	1	74	23.44	23.51	23.48	23.44		
15	16QAM	36	0	21.27	21.38	21.45	21.39	22	3
15	16QAM	36	20	21.30	21.52	21.47	21.41		
15	16QAM	36	39	21.32	21.48	21.47	21.37		
15	16QAM	75	0	21.41	21.53	21.55	21.44		
15	64QAM	1	0	22.02	22.18	22.24	22.25	23	2
15	64QAM	1	37	21.99	22.12	22.21	22.16		
15	64QAM	1	74	22.15	22.27	22.25	22.17		
15	64QAM	36	0	20.28	20.42	20.51	20.44	21	4
15	64QAM	36	20	20.32	20.55	20.53	20.46		
15	64QAM	36	39	20.38	20.51	20.49	20.41		
15	64QAM	75	0	20.40	20.52	20.53	20.50		



FCC SAR TEST REPORT

Report No. : FA901525-01

Channel				40190	40490	40790	41190	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2550	2580	2610	2650		
10	QPSK	1	0	24.19	24.10	24.20	24.15	25	0
10	QPSK	1	25	23.99	24.08	24.19	24.13		
10	QPSK	1	49	24.01	24.21	24.20	24.14		
10	QPSK	25	0	22.08	22.16	22.30	22.23	23	2
10	QPSK	25	12	22.13	22.30	22.31	22.24		
10	QPSK	25	25	22.08	22.32	22.30	22.23		
10	QPSK	50	0	22.12	22.33	22.33	22.27		
10	16QAM	1	0	23.28	23.41	23.47	23.51	24	1
10	16QAM	1	25	23.24	23.38	23.45	23.49		
10	16QAM	1	49	23.26	23.49	23.45	23.47		
10	16QAM	25	0	21.24	21.31	21.42	21.44	22	3
10	16QAM	25	12	21.24	21.44	21.45	21.45		
10	16QAM	25	25	21.22	21.41	21.38	21.41		
10	16QAM	50	0	21.19	21.44	21.43	21.41		
10	64QAM	1	0	22.15	22.33	22.38	22.42	23	2
10	64QAM	1	25	22.17	22.28	22.33	22.39		
10	64QAM	1	49	22.16	22.38	22.35	22.35		
10	64QAM	25	0	20.25	20.34	20.46	20.49	21	4
10	64QAM	25	12	20.28	20.52	20.48	20.52		
10	64QAM	25	25	20.26	20.51	20.48	20.43		
10	64QAM	50	0	20.21	20.43	20.43	20.41		
Channel				40165	40485	40805	41215	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2547.5	2579.5	2611.5	2652.5		
5	QPSK	1	0	24.29	24.29	24.37	24.33	25	0
5	QPSK	1	12	24.28	24.30	24.38	24.33		
5	QPSK	1	24	24.24	24.37	24.35	24.25		
5	QPSK	12	0	22.28	22.28	22.40	22.30	23	2
5	QPSK	12	7	22.33	22.32	22.42	22.39		
5	QPSK	12	13	22.29	22.42	22.39	22.35		
5	QPSK	25	0	22.26	22.39	22.39	22.28		
5	16QAM	1	0	23.33	23.36	23.41	23.40	24	1
5	16QAM	1	12	23.37	23.37	23.46	23.38		
5	16QAM	1	24	23.37	23.47	23.46	23.36		
5	16QAM	12	0	21.33	21.35	21.42	21.44	22	3
5	16QAM	12	7	21.37	21.37	21.46	21.45		
5	16QAM	12	13	21.35	21.48	21.45	21.37		
5	16QAM	25	0	21.37	21.52	21.44	21.46		
5	64QAM	1	0	22.10	22.16	22.20	22.22	23	2
5	64QAM	1	12	22.14	22.14	22.17	22.20		
5	64QAM	1	24	22.13	22.24	22.16	22.19		
5	64QAM	12	0	20.39	20.40	20.49	20.42	21	4
5	64QAM	12	7	20.40	20.41	20.51	20.50		
5	64QAM	12	13	20.39	20.55	20.49	20.49		
5	64QAM	25	0	20.39	20.56	20.51	20.54		

<LTE Carrier Aggregation combinations>

General Note:

1. This device supports Carrier Aggregation on downlink only for inter and intra band, Uplink CA is not supported. For the device supports combination bands and configurations are according to 3GPP.
2. In applying the existing power measurement procedure of KDB 941225 D05A for DL CA SAR test exclusion, only the subset with the largest number of combinations of the frequency band and CCs in each row need consideration, and that configurations require power measurement should be highlighted in the below table.
3. All permutations exist. No restrictions on Pcell & SCell combinations. Only LTE Band 29A is limited to SCell.

2CC Downlink Carrier Aggregation		
Number	Combination	Restriction
1	41C	

<Power verification when LTE Carrier Aggregation Active>

General Note:

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink two carrier aggregation. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band.
- vi. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1|BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$

<Two Carrier power verification>

Configure		PCC							SCC				Power	
		LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Intra-Band	Contiguous	41	20	2618	40870	QPSK	1	99	7	20	2637.80	41068	24.26	24.30

12. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

General Note:

Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge, The detail antenna location please refers to Appendix D.



13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - c. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix 63.3%/62.9% = 1.006 is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA , and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.



13.1 Head SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1413	1732.6	21.61	22.70	1.285	-0.01	0.176	0.226
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1413	1732.6	21.61	22.70	1.285	-0.13	0.089	0.114
01	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1413	1732.6	21.61	22.70	1.285	0.06	0.182	0.234
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1413	1732.6	21.61	22.70	1.285	-0.16	0.118	0.152

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
02	LTE Band 4	20M	QPSK	1	49	Right Cheek	0mm	20175	1732.5	21.74	23.00	1.337	-0.02	0.187	0.250
	LTE Band 4	20M	QPSK	50	24	Right Cheek	0mm	20175	1732.5	21.33	22.50	1.309	0	0.171	0.224
	LTE Band 4	20M	QPSK	1	49	Right Tilted	0mm	20175	1732.5	21.74	23.00	1.337	-0.14	0.078	0.104
	LTE Band 4	20M	QPSK	50	24	Right Tilted	0mm	20175	1732.5	21.33	22.50	1.309	0.07	0.069	0.090
	LTE Band 4	20M	QPSK	1	49	Left Cheek	0mm	20175	1732.5	21.74	23.00	1.337	0.01	0.166	0.222
	LTE Band 4	20M	QPSK	50	24	Left Cheek	0mm	20175	1732.5	21.33	22.50	1.309	0.02	0.152	0.199
	LTE Band 4	20M	QPSK	1	49	Left Tilted	0mm	20175	1732.5	21.74	23.00	1.337	0	0.105	0.140
	LTE Band 4	20M	QPSK	50	24	Left Tilted	0mm	20175	1732.5	21.33	22.50	1.309	-0.07	0.093	0.122

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	LTE Band 41	20M	QPSK	1	99	Right Cheek	0mm	40770	2608	24.36	25.00	1.159	62.9	1.006	0.09	0.116	0.135
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0.06	0.077	0.088
	LTE Band 41	20M	QPSK	1	99	Right Tilted	0mm	40770	2608	24.36	25.00	1.159	62.9	1.006	0.16	0.054	0.063
	LTE Band 41	20M	QPSK	50	0	Right Tilted	0mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0.13	0.034	0.039
	LTE Band 41	20M	QPSK	1	99	Left Cheek	0mm	40770	2608	24.36	25.00	1.159	62.9	1.006	-0.16	0.042	0.049
	LTE Band 41	20M	QPSK	50	0	Left Cheek	0mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0.03	0.029	0.033
	LTE Band 41	20M	QPSK	1	99	Left Tilted	0mm	40770	2608	24.36	25.00	1.159	62.9	1.006	0.09	0.057	0.066
	LTE Band 41	20M	QPSK	50	0	Left Tilted	0mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0.03	0.021	0.024



13.2 Hotspot SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
04	WCDMA IV	RMC 12.2Kbps	Front	10mm	1413	1732.6	21.61	22.70	1.285	-0.04	0.335	0.431
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1413	1732.6	21.61	22.70	1.285	-0.05	0.317	0.407
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	1413	1732.6	21.61	22.70	1.285	-0.05	0.195	0.251
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	1413	1732.6	21.61	22.70	1.285	-0.16	0.169	0.217
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	1413	1732.6	21.61	22.70	1.285	0.03	0.192	0.247

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
05	LTE Band 4	20M	QPSK	1	49	Front	10mm	20175	1732.5	21.74	23.00	1.337	-0.05	0.312	0.417
	LTE Band 4	20M	QPSK	50	24	Front	10mm	20175	1732.5	21.33	22.50	1.309	-0.04	0.283	0.370
	LTE Band 4	20M	QPSK	1	49	Back	10mm	20175	1732.5	21.74	23.00	1.337	-0.04	0.302	0.404
	LTE Band 4	20M	QPSK	50	24	Back	10mm	20175	1732.5	21.33	22.50	1.309	-0.11	0.271	0.355
	LTE Band 4	20M	QPSK	1	49	Left Side	10mm	20175	1732.5	21.74	23.00	1.337	-0.12	0.150	0.200
	LTE Band 4	20M	QPSK	50	24	Left Side	10mm	20175	1732.5	21.33	22.50	1.309	-0.13	0.135	0.177
	LTE Band 4	20M	QPSK	1	49	Right Side	10mm	20175	1732.5	21.74	23.00	1.337	-0.09	0.155	0.207
	LTE Band 4	20M	QPSK	50	24	Right Side	10mm	20175	1732.5	21.33	22.50	1.309	-0.13	0.140	0.183
	LTE Band 4	20M	QPSK	1	49	Bottom Side	10mm	20175	1732.5	21.74	23.00	1.337	-0.03	0.205	0.274
	LTE Band 4	20M	QPSK	50	24	Bottom Side	10mm	20175	1732.5	21.33	22.50	1.309	-0.04	0.185	0.242

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	99	Front	10mm	40770	2608	24.36	25.00	1.159	62.9	1.006	-0.09	0.563	0.656
06	LTE Band 41	20M	QPSK	1	99	Front	10mm	40240	2555	24.24	25.00	1.191	62.9	1.006	-0.04	0.674	0.808
	LTE Band 41	20M	QPSK	1	99	Front	10mm	40500	2581	24.34	25.00	1.164	62.9	1.006	-0.08	0.631	0.739
	LTE Band 41	20M	QPSK	1	99	Front	10mm	41140	2645	24.31	25.00	1.172	62.9	1.006	-0.11	0.411	0.485
	LTE Band 41	20M	QPSK	50	0	Front	10mm	40770	2608	22.46	23.00	1.132	62.9	1.006	-0.09	0.366	0.417
	LTE Band 41	20M	QPSK	100	0	Front	10mm	40770	2608	22.34	23.00	1.164	62.9	1.006	-0.09	0.371	0.434
	LTE Band 41	20M	QPSK	1	99	Back	10mm	40770	2608	24.36	25.00	1.159	62.9	1.006	-0.04	0.589	0.687
	LTE Band 41	20M	QPSK	1	99	Back	10mm	40240	2555	24.24	25.00	1.191	62.9	1.006	-0.07	0.649	0.778
	LTE Band 41	20M	QPSK	1	99	Back	10mm	40500	2581	24.34	25.00	1.164	62.9	1.006	-0.11	0.637	0.746
	LTE Band 41	20M	QPSK	1	99	Back	10mm	41140	2645	24.31	25.00	1.172	62.9	1.006	0.04	0.460	0.542
	LTE Band 41	20M	QPSK	50	0	Back	10mm	40770	2608	22.46	23.00	1.132	62.9	1.006	-0.06	0.445	0.507
	LTE Band 41	20M	QPSK	100	0	Back	10mm	40770	2608	22.34	23.00	1.164	62.9	1.006	-0.09	0.380	0.445
	LTE Band 41	20M	QPSK	1	99	Left Side	10mm	40770	2608	24.36	25.00	1.159	62.9	1.006	0.01	0.095	0.111
	LTE Band 41	20M	QPSK	50	0	Left Side	10mm	40770	2608	22.46	23.00	1.132	62.9	1.006	-0.02	0.059	0.067
	LTE Band 41	20M	QPSK	1	99	Right Side	10mm	40770	2608	24.36	25.00	1.159	62.9	1.006	0.02	0.318	0.371
	LTE Band 41	20M	QPSK	50	0	Right Side	10mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0	0.204	0.232
	LTE Band 41	20M	QPSK	1	99	Bottom Side	10mm	40770	2608	24.36	25.00	1.159	62.9	1.006	-0.09	0.515	0.600
	LTE Band 41	20M	QPSK	1	99	Bottom Side	10mm	40240	2555	24.24	25.00	1.191	62.9	1.006	-0.05	0.503	0.603
	LTE Band 41	20M	QPSK	1	99	Bottom Side	10mm	40500	2581	24.34	25.00	1.164	62.9	1.006	0	0.525	0.615
	LTE Band 41	20M	QPSK	1	99	Bottom Side	10mm	41140	2645	24.31	25.00	1.172	62.9	1.006	-0.02	0.372	0.439
	LTE Band 41	20M	QPSK	50	0	Bottom Side	10mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0	0.318	0.362
	LTE Band 41	20M	QPSK	100	0	Bottom Side	10mm	40770	2608	22.34	23.00	1.164	62.9	1.006	-0.07	0.328	0.384



13.3 Body Worn Accessory SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
07	WCDMA IV	RMC 12.2Kbps	Front	15mm	1413	1732.6	21.61	22.70	1.285	-0.02	0.226	0.290
	WCDMA IV	RMC 12.2Kbps	Back	15mm	1413	1732.6	21.61	22.70	1.285	-0.04	0.215	0.276

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
08	LTE Band 4	20M	QPSK	1	49	Front	15mm	20175	1732.5	21.74	23.00	1.337	-0.04	0.207	0.277
	LTE Band 4	20M	QPSK	50	24	Front	15mm	20175	1732.5	21.33	22.50	1.309	-0.07	0.185	0.242
	LTE Band 4	20M	QPSK	1	49	Back	15mm	20175	1732.5	21.74	23.00	1.337	0.01	0.184	0.246
	LTE Band 4	20M	QPSK	50	24	Back	15mm	20175	1732.5	21.33	22.50	1.309	-0.05	0.165	0.216

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	99	Front	15mm	40770	2608	24.36	25.00	1.159	62.9	1.006	-0.15	0.320	0.373
	LTE Band 41	20M	QPSK	50	0	Front	15mm	40770	2608	22.46	23.00	1.132	62.9	1.006	-0.13	0.209	0.238
09	LTE Band 41	20M	QPSK	1	99	Back	15mm	40770	2608	24.36	25.00	1.159	62.9	1.006	-0.08	0.339	0.395
	LTE Band 41	20M	QPSK	50	0	Back	15mm	40770	2608	22.46	23.00	1.132	62.9	1.006	0.04	0.216	0.246

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product Specific
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes
5.	GSM Voice + Bluetooth	Yes	Yes		Yes
6.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes	Yes
7.	WCDMA+ Bluetooth	Yes	Yes	Yes	Yes
8.	LTE + Bluetooth	Yes	Yes	Yes	Yes
9.	GSM Voice + WLAN5GHz	Yes	Yes		Yes
10.	GPRS/EDGE + WLAN5GHz	Yes	Yes		Yes
11.	WCDMA + WLAN5GHz	Yes	Yes		Yes
12.	LTE + WLAN5GHz	Yes	Yes		Yes
13.	GSM Voice + WLAN5GHz + Bluetooth	Yes	Yes		Yes
14.	GPRS/EDGE + WLAN5GHz + Bluetooth	Yes	Yes		Yes
15.	WCDMA + WLAN5GHz + Bluetooth	Yes	Yes		Yes
16.	LTE + WLAN5GHz + Bluetooth	Yes	Yes		Yes
17.	WLAN5GHz + Bluetooth	Yes	Yes		Yes

General Note:

1. This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
2. 2.4GHz WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. All licensed modes share the same antenna part and cannot transmit simultaneously
4. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
5. The Scaled SAR summation is calculated based on the same configuration and test position.
6. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
7. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 based on the formula below.
 - i) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - ii) When the minimum separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
 - iii) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Bluetooth Max Power	Exposure Position	Body worn
	Test separation	15 mm
14.31 dBm	Estimated SAR (W/kg)	0.378 W/kg



14.1 Head Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	3+4 Summed 1g SAR (W/kg)
		WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)					
GSM850	Right Cheek	0.330	0.148	0.121	0.232	0.478	0.451	0.562	0.683	0.353
	Right Tilted	0.141	0.060	0.030	0.087	0.201	0.171	0.228	0.258	0.117
	Left Cheek	0.260	0.057	0.051	0.090	0.317	0.311	0.350	0.401	0.141
	Left Tilted	0.142	0.031	0.015	0.047	0.173	0.157	0.189	0.204	0.062
GSM1900	Right Cheek	0.030	0.148	0.121	0.232	0.178	0.151	0.262	0.383	0.353
	Right Tilted	0.010	0.060	0.030	0.087	0.070	0.040	0.097	0.127	0.117
	Left Cheek	0.021	0.057	0.051	0.090	0.078	0.072	0.111	0.162	0.141
	Left Tilted	0.018	0.031	0.015	0.047	0.049	0.033	0.065	0.080	0.062
WCDMA IV	Right Cheek	0.226	0.148	0.121	0.232	0.374	0.347	0.458	0.579	0.353
	Right Tilted	0.114	0.060	0.030	0.087	0.174	0.144	0.201	0.231	0.117
	Left Cheek	0.234	0.057	0.051	0.090	0.291	0.285	0.324	0.375	0.141
	Left Tilted	0.152	0.031	0.015	0.047	0.183	0.167	0.199	0.214	0.062
WCDMA V	Right Cheek	0.395	0.148	0.121	0.232	0.543	0.516	0.627	0.748	0.353
	Right Tilted	0.226	0.060	0.030	0.087	0.286	0.256	0.313	0.343	0.117
	Left Cheek	0.347	0.057	0.051	0.090	0.404	0.398	0.437	0.488	0.141
	Left Tilted	0.206	0.031	0.015	0.047	0.237	0.221	0.253	0.268	0.062
LTE Band 4	Right Cheek	0.250	0.148	0.121	0.232	0.398	0.371	0.482	0.603	0.353
	Right Tilted	0.104	0.060	0.030	0.087	0.164	0.134	0.191	0.221	0.117
	Left Cheek	0.222	0.057	0.051	0.090	0.279	0.273	0.312	0.363	0.141
	Left Tilted	0.140	0.031	0.015	0.047	0.171	0.155	0.187	0.202	0.062
LTE Band 5	Right Cheek	0.394	0.148	0.121	0.232	0.542	0.515	0.626	0.747	0.353
	Right Tilted	0.197	0.060	0.030	0.087	0.257	0.227	0.284	0.314	0.117
	Left Cheek	0.271	0.057	0.051	0.090	0.328	0.322	0.361	0.412	0.141
	Left Tilted	0.167	0.031	0.015	0.047	0.198	0.182	0.214	0.229	0.062
LTE Band 12	Right Cheek	0.192	0.148	0.121	0.232	0.340	0.313	0.424	0.545	0.353
	Right Tilted	0.090	0.060	0.030	0.087	0.150	0.120	0.177	0.207	0.117
	Left Cheek	0.187	0.057	0.051	0.090	0.244	0.238	0.277	0.328	0.141
	Left Tilted	0.089	0.031	0.015	0.047	0.120	0.104	0.136	0.151	0.062
LTE Band 41	Right Cheek	0.135	0.148	0.121	0.232	0.283	0.256	0.367	0.488	0.353
	Right Tilted	0.063	0.060	0.030	0.087	0.123	0.093	0.150	0.180	0.117
	Left Cheek	0.049	0.057	0.051	0.090	0.106	0.100	0.139	0.190	0.141
	Left Tilted	0.066	0.031	0.015	0.047	0.097	0.081	0.113	0.128	0.062



14.2 Hotspot Exposure Conditions

WWAN Band	Exposure Position	1	2	4	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
		WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)		
GSM850	Front	0.321	0.043	0.050	0.364	0.371
	Back	0.541	0.168	0.194	0.709	0.735
	Left side	0.159	0.100	0.140	0.259	0.299
	Right side	0.300			0.300	0.300
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.118			0.118	0.118
GSM1900	Front	0.062	0.043	0.050	0.105	0.112
	Back	0.146	0.168	0.194	0.314	0.340
	Left side	0.026	0.100	0.140	0.126	0.166
	Right side	0.023			0.023	0.023
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.107			0.107	0.107
WCDMA IV	Front	0.431	0.043	0.050	0.474	0.481
	Back	0.407	0.168	0.194	0.575	0.601
	Left side	0.251	0.100	0.140	0.351	0.391
	Right side	0.217			0.217	0.217
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.247			0.247	0.247
WCDMA V	Front	0.386	0.043	0.050	0.429	0.436
	Back	0.538	0.168	0.194	0.706	0.732
	Left side	0.230	0.100	0.140	0.330	0.370
	Right side	0.437			0.437	0.437
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.167			0.167	0.167
LTE Band 4	Front	0.417	0.043	0.050	0.460	0.467
	Back	0.404	0.168	0.194	0.572	0.598
	Left side	0.200	0.100	0.140	0.300	0.340
	Right side	0.207			0.207	0.207
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.274			0.274	0.274
LTE Band 5	Front	0.273	0.043	0.050	0.316	0.323
	Back	0.387	0.168	0.194	0.555	0.581
	Left side	0.158	0.100	0.140	0.258	0.298
	Right side	0.298			0.298	0.298
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.123			0.123	0.123
LTE Band 12	Front	0.230	0.043	0.050	0.273	0.280
	Back	0.308	0.168	0.194	0.476	0.502
	Left side	0.201	0.100	0.140	0.301	0.341
	Right side	0.247			0.247	0.247
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.071			0.071	0.071
LTE Band 41	Front	0.808	0.043	0.050	0.851	0.858
	Back	0.778	0.168	0.194	0.946	0.972
	Left side	0.111	0.100	0.140	0.211	0.251
	Right side	0.371			0.371	0.371
	Top side		0.007	0.010	0.007	0.010
	Bottom side	0.615			0.615	0.615



14.3 Body-Worn Accessory Exposure Conditions

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)	3+4 Summed 1g SAR (W/kg)
		WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth Estimated 1g SAR (W/kg)					
GSM850	Front	0.323	0.023	0.018	0.378	0.346	0.341	0.701	0.719	0.396
	Back	0.405	0.079	0.132	0.378	0.484	0.537	0.783	0.915	0.510
GSM1900	Front	0.034	0.023	0.018	0.378	0.057	0.052	0.412	0.430	0.396
	Back	0.074	0.079	0.132	0.378	0.153	0.206	0.452	0.584	0.510
WCDMA IV	Front	0.290	0.023	0.018	0.378	0.313	0.308	0.668	0.686	0.396
	Back	0.276	0.079	0.132	0.378	0.355	0.408	0.654	0.786	0.510
WCDMA V	Front	0.381	0.023	0.018	0.378	0.404	0.399	0.759	0.777	0.396
	Back	0.461	0.079	0.132	0.378	0.540	0.593	0.839	0.971	0.510
LTE Band 4	Front	0.277	0.023	0.018	0.378	0.300	0.295	0.655	0.673	0.396
	Back	0.246	0.079	0.132	0.378	0.325	0.378	0.624	0.756	0.510
LTE Band 5	Front	0.279	0.023	0.018	0.378	0.302	0.297	0.657	0.675	0.396
	Back	0.328	0.079	0.132	0.378	0.407	0.460	0.706	0.838	0.510
LTE Band 12	Front	0.223	0.023	0.018	0.378	0.246	0.241	0.601	0.619	0.396
	Back	0.274	0.079	0.132	0.378	0.353	0.406	0.652	0.784	0.510
LTE Band 41	Front	0.373	0.023	0.018	0.378	0.396	0.391	0.751	0.769	0.396
	Back	0.395	0.079	0.132	0.378	0.474	0.527	0.773	0.905	0.510

14.4 Product Specific Exposure Conditions

Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)	1+3+4 Summed 10g SAR (W/kg)	3+4 Summed 10g SAR (W/kg)
	WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)	Bluetooth 10g SAR (W/kg)					
Front			0.049		0.000	0.049	0.000	0.049	0.049
Back			0.477		0.000	0.477	0.000	0.477	0.477
Left side			0.280		0.000	0.280	0.000	0.280	0.280
Right side					0.000	0.000	0.000	0.000	0.000
Top side			0.003		0.000	0.003	0.000	0.003	0.003
Bottom side					0.000	0.000	0.000	0.000	0.000

Test Engineer : White Huang and Tommy Chen



15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 941225 D07 v01r02, " SAR Evaluation Procedures for UMPC Mini-Tablet Devices", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.