



# ELEMENT WASHINGTON DC LLC

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

## MEASUREMENT REPORT FCC PART 15.407 UNII

**Applicant Name:**

Sony Corporation  
1-7-1 Konan  
Minato-ku  
Tokyo, 108-0075, Japan

**Date of Testing:**

6/3/2022-7/29/2022

**Test Report Issue Date:**

7/29/2022

**Test Site/Location:**

Element lab. Columbia, MD, USA

**Test Report Serial No.:**

1M2207200079-10.PY7

**FCC ID:**

**PY7-58692W**

**APPLICANT:**

**Sony Corporation**

**Application Type:**

Certification

**EUT Type:**

Portable Handset

**Frequency Range:**

5180 – 5825MHz

**Modulation Type:**

OFDM

**FCC Equipment Class:**

Unlicensed National Information Infrastructure TX (NII)

**FCC Rule Part(s):**

Part 15 Subpart E (15.407)

**Test Procedure(s):**

ANSI C63.10-2013, KDB 789033 D02 v02r01, KDB 662911 D01 v02r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**RJ Ortanez**  
**Executive Vice President**



<b>FCC ID:</b> PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-10.PY7	<b>Test Dates:</b> 6/3/2022-7/29/2022	<b>EUT Type:</b> Portable Handset	Page 1 of 209

## T A B L E O F C O N T E N T S

1.0	INTRODUCTION.....	4
1.1	Scope.....	4
1.2	Element Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description.....	5
2.2	Device Capabilities.....	5
2.3	Antenna Description.....	7
2.4	Test Configuration.....	7
2.5	Software and Firmware.....	7
2.6	EMI Suppression Device(s)/Modifications.....	7
3.0	DESCRIPTION OF TESTS.....	8
3.1	Evaluation Procedure.....	8
3.2	AC Line Conducted Emissions.....	8
3.3	Radiated Emissions.....	9
3.4	Environmental Conditions.....	9
4.0	ANTENNA REQUIREMENTS.....	10
5.0	MEASUREMENT UNCERTAINTY.....	11
6.0	TEST EQUIPMENT CALIBRATION DATA.....	12
7.0	TEST RESULTS.....	13
7.1	Summary.....	13
7.2	26dB Bandwidth Measurement – 802.11a/n/ac/ax.....	14
7.3	6dB Bandwidth Measurement – 802.11a.....	73
7.4	UNII Output Power Measurement – 802.11a/n/ac/ax.....	91
7.5	Maximum Power Spectral Density – 802.11a/n/ac/ax.....	99
7.6	Radiated Spurious Emission Measurements – Above 1GHz.....	173
7.6.1	MIMO Radiated Spurious Emission Measurements.....	176
7.6.2	MIMO Radiated Band Edge Measurements (20MHz BW).....	186
7.6.3	MIMO Radiated Band Edge Measurements (40MHz BW).....	189
7.6.4	MIMO Radiated Band Edge Measurements (80MHz BW).....	191
7.6.5	MIMO Radiated Band Edge Measurements (160MHz BW).....	193
7.7	Radiated Spurious Emissions Measurements – Below 1GHz.....	195
7.8	Line-Conducted Test Data.....	199
8.0	CONCLUSION.....	209

<b>FCC ID:</b> PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-10.PY7	<b>Test Dates:</b> 6/3/2022-7/29/2022	<b>EUT Type:</b> Portable Handset	Page 2 of 209

## MEASUREMENT REPORT

UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	ANT1		ANT2		MIMO	
			Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)
1	20	5180 - 5240	14.093	11.49	13.836	11.41	27.797	14.44
2A		5260 - 5320	13.305	11.24	13.996	11.46	26.915	14.30
2C		5500 - 5700	13.932	11.44	14.093	11.49	27.990	14.47
2C		5500 - 5720	13.932	11.44	14.093	11.49	27.990	14.47
3		5745 - 5825	13.677	11.36	14.093	11.49	27.479	14.39
1	40	5190 - 5230	14.093	11.49	12.912	11.11	26.977	14.31
2A		5270 - 5310	13.868	11.42	13.213	11.21	26.546	14.24
2C		5510 - 5670	13.932	11.44	13.092	11.17	26.977	14.31
2C		5510 - 5710	13.932	11.44	13.092	11.17	26.977	14.31
3		5755 - 5795	13.677	11.36	12.134	10.84	25.351	14.04
1	80	5210	12.735	11.05	13.740	11.38	26.242	14.19
2A		5290	12.050	10.81	13.183	11.20	25.003	13.98
2C		5530 - 5610	13.804	11.40	13.677	11.36	26.792	14.28
2C		5530 - 5690	13.804	11.40	13.677	11.36	26.792	14.28
3		5775	11.482	10.60	13.243	11.22	24.491	13.89
1	160	5250	13.032	11.15	14.060	11.48	27.102	14.33
2B		5570	13.397	11.27	12.359	10.92	25.704	14.10

### EUT Overview

<b>FCC ID:</b> PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-10.PY7	<b>Test Dates:</b> 6/3/2022-7/29/2022	<b>EUT Type:</b> Portable Handset	Page 3 of 209

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

**Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.**

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

<b>FCC ID:</b> PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-10.PY7	<b>Test Dates:</b> 6/3/2022-7/29/2022	<b>EUT Type:</b> <b>Portable Handset</b>	Page 4 of 209

## 2.0 PRODUCT INFORMATION

### Equipment Description

The Equipment Under Test (EUT) is the **Sony Corporation Portable Handset FCC ID: PY7-58692W**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

**Test Device Serial No.:** OAMBH, 008DD

### Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900, WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII, Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
:	:	:	:	:	:	:	:
40	5200	56	5280	120	5600	157	5785
:	:	:	:	:	:	:	:
48	5240	64	5320	140	5700	165	5825

Table 2-1. 802.11a (20MHz) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
:	:	:	:	:	:	:	:
46	5230	62	5310	118	5590	159	5795
				:	:		
				142	5710		

Table 2-2. 802.11ax (40MHz BW) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
				:	:		
				138	5690		

Table 2-3. 802.11ax (80MHz BW) Frequency / Channel Operations

Band 1/2A		Band 2C	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
50	5250	114	5570

Table 2-4. 802.11ac / 802.11ax (160MHz BW) Frequency / Channel Operations

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 5 of 209

**Notes:**

- 5GHz NII operation is possible in 20MHz, 40MHz, 80MHz, and 160MHz channel bandwidth. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013 and KDB 789033 D02 v02r01. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles					
802.11 Mode/Band		MIMO (1+2)			
		Duty Cycle [%]	Pulse Width	Period	Radiated DCCF [dB]
5GHz	a	98.9	2.09	2.113	N/A
	n (HT20)	99.4	5.409	5.439	N/A
	ac (HT20)	99.4	5.416	5.447	N/A
	ax (HT20)	99.5	5.432	5.462	N/A
	n (HT40)	99.0	5.386	5.439	N/A
	ac (HT40)	99.0	5.386	5.439	N/A
	ax (HT40)	98.9	5.401	5.462	N/A
	ac (HT80)	99.0	5.379	5.432	N/A
	ax (HT80)	98.9	5.401	5.462	N/A
	ac (HT160)	99.4	5.416	5.447	N/A
ax (HT160)	99.3	5.424	5.462	N/A	

**Table 2-5. Measured Duty Cycles**

- The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CDD/SDM	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
5GHz	11a	x	x	x	x	✓	✓
	11n	x	x	x	x	✓	✓
	11ac	x	x	x	x	✓	✓
	11ax	x	x	x	x	✓	✓

**Table 2-6. Frequency / Channel Operations**

✓ = Support ; x = NOT Support  
**SISO** = Single Input Single Output  
**SDM** = Spatial Diversity Multiplexing – MIMO function  
**CDD** = Cyclic Delay Diversity - 2Tx Function

- This device supports simultaneous transmission operation, which allows for two SISO channels to operate independent of one another in the 2.4GHz and 5GHz bands simultaneously on each antenna. The following table shows the worst-case configuration determined during testing. The data for this configuration is contained in the UNII test report.

<b>FCC ID:</b> PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-10.PY7	<b>Test Dates:</b> 6/3/2022-7/29/2022	<b>EUT Type:</b> Portable Handset	Page 6 of 209

**Configuration 1:** ANT1 and ANT2 both transmitting in 2.4GHz and 5GHz modes simultaneously

Description	2.4 GHz Emission	5 GHz Emission
Antenna	1, 2	1, 2
Channel	6	100
Operating Frequency (MHz)	2437	5500
Data Rate (Mbps)	6	MCS0
Mode	802.11g	802.11ax

**Table 2-7. Config-1 (MIMO 2.4GHz & 5GHz)**

## 2.3 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna 1 Gain (dBi)	Antenna 2 Gain (dBi)	Directional Antenna Gain (dBi)
5.20	-0.7	-9.6	-1.1
5.30	-0.7	-9.6	-1.1
5.50	-3.8	-7.7	-2.5
5.80	-5.5	-6.1	-2.8

**Table 2-8. Antenna Peak Gain**

## 2.4 Test Configuration

The EUT was tested per the guidance of KDB 789033 D02 v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

This device supports wireless charging capability and, thus, is subject to the test requirements of KDB 648474 D03 v01r04. Additional radiated spurious emission measurements were performed with the EUT lying flat on an authorized wireless charging pad (WCP) F7U050 while operating under normal conditions in a simulated call or data transmission configuration. The worst case radiated emissions data is shown in this report.

## 2.5 Software and Firmware

The test was conducted with software/firmware version 3.103 installed on the EUT.

## EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 7 of 209

## 3.0 DESCRIPTION OF TESTS

### Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

### AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section **Error! Reference source not found.** The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 8 of 209





## Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01 v01r01.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

<b>FCC ID:</b> PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2207200079-10.PY7	<b>Test Dates:</b> 6/3/2022-7/29/2022	<b>EUT Type:</b> Portable Handset	Page 9 of 209

## 4.0 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The EUT complies with the requirement of §15.203.

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 10 of 209

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 11 of 209

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	12/19/2021	Annual	12/19/2022	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	12/19/2022	Annual	12/19/2022	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	12/19/2022	Annual	12/19/2022	WL40-1
-	ETS-001	EMC Cable and Switch System	12/9/2021	Annual	12/9/2022	ETS-001
-	ETS-002	EMC Cable and Switch System	3/10/2022	Annual	3/10/2023	ETS-002
-	AP1-002	EMC Cable and Switch System	3/9/2022	Annual	3/9/2023	AP1-002
-	AP2-001	EMC Cable and Switch System	1/4/2022	Annual	1/4/2023	AP2-001
-	AP2-002	EMC Cable and Switch System	3/11/2022	Annual	3/11/2023	AP2-002
Agilent	N9038A	MXE EMI Receiver	1/21/2022	Annual	1/21/2023	MY51210133
Agilent	N9020A	MXA Signal Analyzer	3/4/2022	Annual	3/4/2023	US46470561
Agilent	N9030A	PXA Signal Analyzer (44GHz)	7/21/2021	Annual	7/21/2022	MY49430494
Anritsu	ML2495A	Power Meter	3/17/2022	Annual	3/17/2023	1328004
Anritsu	ML2495A	Power Meter	3/17/2022	Annual	3/17/2023	941001
Com-Power	AL-130	9kHz-30MHz Loop Antenna	4/13/2022	Biennial	4/13/2024	121034
Emco	3115	Horn Antenna (1 - 18GHz)	7/20/2021	Biennial	7/20/2022	9203-2178
ETS-Lindgren	3116	Horn Antenna (18 - 40GHz)	4/20/2021	Biennial	4/20/2023	9704-5182
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	7/9/2020	Biennial	7/9/2022	114451
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	12/19/2021	Annual	12/19/2022	NMLC-2
Rohde & Schwarz	FSV40-N	Spectrum Analyzer	1/14/2021	Annual	8/3/2022	83244
Rohde & Schwarz	SMW200A	Vector Signal Generator		N/A		83365
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	8/3/2021	Annual	8/3/2022	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/25/2021	Annual	7/25/2022	100348
Sunol	DRH-118	Horn Antenna (1-18GHz)	2/14/2022	Biennial	2/14/2024	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/27/2020	Biennial	7/27/2022	A051107

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. Equipment with a calibration date of "N/A" shown in this was not used to make direct calibrated measurements.

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 12 of 209

## 7.0 TEST RESULTS

### Summary

Company Name: Sony Corporation  
 FCC ID: PY7-58692W  
 FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
N/A	RSS-Gen [6.6]	26dB Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
15.407(e)	RSS-Gen [6.6]	6dB Bandwidth	>500kHz(5725-5850MHz)		PASS	Section 7.3
15.407 (a.1.iv), (a.2), (a.3)	RSS-247 [6.2]	Maximum Conducted Output Power	Maximum conducted powers must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.4
15.407 (a.1.iv), (a.2), (a.3)	RSS-247 [6.2]	Maximum Power Spectral Density	Maximum power spectral density must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.5
15.407(h)	RSS-247 [6.3]	Dynamic Frequency Selection	See DFS Test Report		PASS	See DFS Test Report
15.407(b.1), (2), (3), (4)	RSS-247 [6.2]	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b) (RSS-247 [6.2])	RADIATED	PASS	Section 7.6
15.205, 15.407(b.1), (4), (5), (6)	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])		PASS	Section 7.6, 7.7
15.407	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 (RSS-Gen [8.8]) limits	LINE CONDUCTED	PASS	Section 7.8

**Table 7-1. Summary of Test Results**

#### Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “UNII Automation,” Version 4.7.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “Chamber Automation,” Version 1.3.1.

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 13 of 209

## 26dB Bandwidth Measurement – 802.11a/n/ac/ax

RSS-Gen [6.2]

### Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

***The 26dB bandwidth is used to determine the conducted power limits.***

### Test Procedure Used

ANSI C63.10-2013 – Section 12.4  
KDB 789033 D02 v02r01 – Section C

### Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 26$ . The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Test Instrument & Measurement Setup**

### Test Notes

None.


FCC ID: PY7-58692W	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 14 of 209

## MIMO Antenna-1 26 dB Bandwidth Measurements


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 26dB Bandwidth [MHz]	
Band 1	5180	36	a	6	18.54	
	5200	40	a	6	18.75	
	5240	48	a	6	18.71	
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	19.77	
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	20.15	
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	19.80	
	5180	36	ax (20MHz)	6.5/7.2 (MCS0)	20.65	
	5200	40	ax (20MHz)	6.5/7.2 (MCS0)	20.57	
	5240	48	ax (20MHz)	6.5/7.2 (MCS0)	20.89	
	5190	38	n (40MHz)	13.5/15 (MCS0)	39.52	
	5230	46	n (40MHz)	13.5/15 (MCS0)	39.56	
	5190	38	ax (40MHz)	13.5/15 (MCS0)	39.90	
	5230	46	ax (40MHz)	13.5/15 (MCS0)	40.11	
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	80.92	
5210	42	ax (80MHz)	29.3/32.5 (MCS0)	81.50		
Band 1/2A	5250	50	ac (160MHz)	58.5/65 (MCS0)	163.60	
	5250	50	ax (160MHz)	58.5/65 (MCS0)	164.50	
	5260	52	a	6	18.71	
Band 2A	5280	56	a	6	18.80	
	5320	64	a	6	18.69	
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	19.83	
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	20.10	
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	19.95	
	5260	52	ax (20MHz)	6.5/7.2 (MCS0)	20.49	
	5280	56	ax (20MHz)	6.5/7.2 (MCS0)	21.08	
	5320	64	ax (20MHz)	6.5/7.2 (MCS0)	21.04	
	5270	54	n (40MHz)	13.5/15 (MCS0)	39.18	
	5310	62	n (40MHz)	13.5/15 (MCS0)	39.70	
	5270	54	ax (40MHz)	13.5/15 (MCS0)	40.33	
	5310	62	ax (40MHz)	13.5/15 (MCS0)	40.30	
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	81.83	
	5290	58	ax (80MHz)	29.3/32.5 (MCS0)	81.32	
	Band 2C	5500	100	a	6	18.87
		5600	120	a	6	18.61
		5720	144	a	6	18.85
		5500	100	n (20MHz)	6.5/7.2 (MCS0)	19.76
5600		120	n (20MHz)	6.5/7.2 (MCS0)	19.78	
5720		144	n (20MHz)	6.5/7.2 (MCS0)	19.87	
5500		100	ax (20MHz)	6.5/7.2 (MCS0)	20.90	
5600		120	ax (20MHz)	6.5/7.2 (MCS0)	20.66	
5720		144	ax (20MHz)	6.5/7.2 (MCS0)	20.78	
5510		102	n (40MHz)	13.5/15 (MCS0)	39.51	
5590		118	n (40MHz)	13.5/15 (MCS0)	39.23	
5710		142	n (40MHz)	13.5/15 (MCS0)	39.20	
5510		102	ax (40MHz)	13.5/15 (MCS0)	39.89	
5590		118	ax (40MHz)	13.5/15 (MCS0)	39.89	
5710		142	ax (40MHz)	13.5/15 (MCS0)	39.82	
5530		106	ac (80MHz)	29.3/32.5 (MCS0)	81.08	
5610		122	ac (80MHz)	29.3/32.5 (MCS0)	81.24	
5690		138	ac (80MHz)	29.3/32.5 (MCS0)	80.88	
5530		106	ax (80MHz)	29.3/32.5 (MCS0)	81.35	
5610		122	ax (80MHz)	29.3/32.5 (MCS0)	81.06	
5690	138	ax (80MHz)	29.3/32.5 (MCS0)	81.31		
5570	114	ac (160MHz)	58.5/65 (MCS0)	164.80		
5570	114	ax (160MHz)	58.5/65 (MCS0)	162.70		

**Table 7-2. Conducted Bandwidth Measurements MIMO ANT1**

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 15 of 209




Plot 7-1. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 1) – Ch. 36)




Plot 7-2. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 1) – Ch. 40)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 16 of 209






Plot 7-3. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 1) – Ch. 48)




Plot 7-4. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 1) – Ch. 36)

FCC ID: PY7-58692W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset		Page 17 of 209




Plot 7-5. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 1) – Ch. 40)




Plot 7-6. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 1) – Ch. 48)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 18 of 209




Plot 7-7. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 1) – Ch. 36)




Plot 7-8. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 1) – Ch. 40)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 19 of 209




Plot 7-9. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 1) – Ch. 48)




Plot 7-10. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 1) – Ch. 38)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 20 of 209




Plot 7-11. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 1) – Ch. 46)



Plot 7-12. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 1) – Ch. 38)

MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
FCC ID: PY7-58692W	Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	Page 21 of 209
EUT Type: Portable Handset			



Plot 7-13. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 1) – Ch. 46)




Plot 7-14. 26dB Bandwidth Plot MIMO ANT1 (802.11ac – 80MHz BW (UNII Band 1) – Ch. 42)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 22 of 209




Plot 7-15. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 80MHz BW (UNII Band 1) – Ch. 42)




Plot 7-16. 26dB Bandwidth Plot MIMO ANT1 (802.11ac – 160MHz BW (UNII Band 1/2A) – Ch. 50)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 23 of 209




Plot 7-17. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 160MHz BW (UNII Band 1/2A) – Ch. 50)




Plot 7-18. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 24 of 209






Plot 7-19. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 2A) – Ch. 56)




Plot 7-20. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 25 of 209




Plot 7-21. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 2A) – Ch. 52)




Plot 7-22. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 2A) – Ch. 56)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 26 of 209




Plot 7-23. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 2A) – Ch. 64)




Plot 7-24. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 2A) – Ch. 52)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 27 of 209




Plot 7-25. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 2A) – Ch. 56)



Plot 7-26. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 2A) – Ch. 64)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 28 of 209




Plot 7-27. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 2A) – Ch. 54)




Plot 7-28. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 2A) – Ch. 62)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 29 of 209




Plot 7-29. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 2A) – Ch. 54)




Plot 7-30. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 2A) – Ch. 62)

FCC ID: PY7-58692W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset		Page 30 of 209




Plot 7-31. 26dB Bandwidth Plot MIMO ANT1 (802.11ac – 80MHz BW (UNII Band 2A) – Ch. 58)



Plot 7-32. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 80MHz BW (UNII Band 2A) – Ch. 58)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 31 of 209




Plot 7-33. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 2C) – Ch. 100)




Plot 7-34. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 2C) – Ch. 120)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 32 of 209





Plot 7-35. 26dB Bandwidth Plot MIMO ANT1 (802.11a (UNII Band 2C) – Ch. 144)




Plot 7-36. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 2C) – Ch. 100)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 33 of 209




Plot 7-37. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 2C) – Ch. 120)




Plot 7-38. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 20MHz BW (UNII Band 2C) – Ch. 144)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 34 of 209




Plot 7-39. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 2C) – Ch. 100)




Plot 7-40. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 2C) – Ch. 120)

FCC ID: PY7-58692W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset		Page 35 of 209




Plot 7-41. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 20MHz BW (UNII Band 2C) – Ch. 144)




Plot 7-42. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 2C) – Ch. 102)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 36 of 209




Plot 7-43. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 2C) – Ch. 118)




Plot 7-44. 26dB Bandwidth Plot MIMO ANT1 (802.11n – 40MHz BW (UNII Band 2C) – Ch. 142)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 37 of 209




Plot 7-45. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 2C) – Ch. 102)




Plot 7-46. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 2C) – Ch. 118)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 38 of 209




Plot 7-47. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 40MHz BW (UNII Band 2C) – Ch. 142)



Plot 7-48. 26dB Bandwidth Plot MIMO ANT1 (802.11ac – 80MHz BW (UNII Band 2C) – Ch. 106)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 39 of 209




Plot 7-49. 26dB Bandwidth Plot MIMO ANT1 (802.11ac – 80MHz BW (UNII Band 2C) – Ch. 122)




Plot 7-50. 26dB Bandwidth Plot MIMO ANT1 (802.11ac – 80MHz BW (UNII Band 2C) – Ch. 138)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 40 of 209





Plot 7-51. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 80MHz BW (UNII Band 2C) – Ch. 106)



Plot 7-52. 26dB Bandwidth Plot MIMO ANT1 (802.11ax – 80MHz BW (UNII Band 2C) – Ch. 122)

FCC ID: PY7-58692W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2207200079-10.PY7	Test Dates: 6/3/2022-7/29/2022	EUT Type: Portable Handset	Page 41 of 209