

SAR TEST REPORT

The following samples were submitted and identified on behalf of the client as:

| | |
|-----------------------------|--|
| Equipment Under Test | Mobile Phone |
| Brand Name | Sony |
| Type No. | PM-0850-BV |
| Company Name | Sony Mobile Communications AB |
| Company Address | Nya Vattentornet 22188 Lund/Sweden |
| Standards | IEEE /ANSI C95.1, C95.3, IEEE 1528, KDB447498D01v05r02, KDB248227D01v01r02,KDB941225D01v03, KDB941225D05v02r03,KDB941225D06v02,KDB865664D01v01r03, KDB865664D02v01r01, KDB648474D04v01r02. |
| FCC ID | PY7-PM0850 |
| Date of Receipt | Nov. 05,2014 |
| Date of Test(s) | Nov. 13, 2014 ~ Nov. 27, 2014 |
| Date of Issue | Jan. 15, 2015 |

In the configuration tested, the EUT complied with the standards specified above.

Remarks:


This report details the results of the testing carried out on three samples, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan Electronic & Communication Laboratory or testing done by SGS Taiwan Electronic & Communication Laboratory in connection with distribution or use of the product described in this report must be approved by SGS Taiwan Electronic & Communication Laboratory in writing.

Signed on behalf of SGS

Sr. Engineer

Supervisor


Pin Chu

Date: Jan. 15, 2015


Ricky Huang

Date: Jan. 15, 2015

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Version

| Report Number | Revision | Description | Issue Date |
|---------------|----------|------------------------------|---------------|
| EN/2014/B0004 | 00 | Initial Version | Jan. 05, 2015 |
| EN/2014/B0004 | 01 | 1 st modification | Jan. 09, 2015 |
| EN/2014/B0004 | 02 | 2 nd modification | Jan. 15, 2015 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

This test report contains a reference to the previous version test report that it replaces.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Contents

| | |
|--|-----|
| 1. General Information | 4 |
| 1.1 Testing Laboratory | 4 |
| 1.2 Details of Applicant | 4 |
| 1.3 Description of EUT | 5 |
| 1.4 Test Environment | 37 |
| 1.5 Operation Description | 37 |
| 1.6 Positioning Procedure | 42 |
| 1.7 Evaluation Procedures | 43 |
| 1.8 Probe Calibration Procedures | 45 |
| 1.9 The SAR Measurement System | 48 |
| 1.10 System Components | 50 |
| 1.11 SAR System Verification | 52 |
| 1.12 Tissue Simulant Fluid for the Frequency Band | 54 |
| 1.13 Test Standards and Limits | 58 |
| 2. Summary of Results | 60 |
| 3. Simultaneous Transmission Analysis | 73 |
| 4. Instruments List | 86 |
| 5. Measurements | 87 |
| 6. System Verification | 118 |
| 7. DAE & Probe Calibration Certificate | 138 |
| 8. Uncertainty Budget | 186 |
| 9. Phantom Description | 187 |
| 10. System Validation from Original Equipment Supplier | 188 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

1. General Information

1.1 Testing Laboratory

| | |
|--|---|
| SGS Taiwan Ltd. Electronics & Communication Laboratory | |
| No.134, Wu Kung Road, New Taipei Industrial Park | |
| Wuku District, New Taipei City, Taiwan | |
| Tel | +886-2-2299-3279 |
| Fax | +886-2-2298-0488 |
| Internet | http://www.tw.sgs.com/ |

1.2 Details of Applicant

| | |
|-----------------|------------------------------------|
| Company Name | Sony Mobile Communications AB |
| Company Address | Nya Vattentornet 22188 Lund/Sweden |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

1.3 Description of EUT

| | | | | | | | |
|-------------------|--|---|---|---|---|--|--|
| EUT Name | Mobile Phone | | | | | | |
| Brand Name | Sony | | | | | | |
| Type No. | PM-0850-BV | | | | | | |
| HW Version | A | | | | | | |
| SW Version | 25.0.A.0.33 | | | | | | |
| Serial No. | 2G/3G: ZH8005X87T / WLAN: ZH8005X8D9 LTE: ZH8005X8DD | | | | | | |
| IMEI Code | 2G/3G: 004402453394748 / WLAN: 004402453394672 LTE: 004402453394613 | | | | | | |
| FCC ID | PY7-PM0850 | | | | | | |
| Mode of Operation | <input checked="" type="checkbox"/> GSM | <input checked="" type="checkbox"/> GPRS | <input checked="" type="checkbox"/> EDGE | <input checked="" type="checkbox"/> WCDMA | <input checked="" type="checkbox"/> HSDPA | | |
| | <input checked="" type="checkbox"/> HSUPA | <input checked="" type="checkbox"/> HSPA+ | <input checked="" type="checkbox"/> LTE FDD | | | | |
| | <input checked="" type="checkbox"/> WLAN802.11a/b/g/n(20M/40M) | | <input checked="" type="checkbox"/> Bluetooth | | | | |
| Duty Cycle | GSM | | 1/8.3 | | | | |
| | GPRS (support multi class 12 max) | | 1/2 (1Dn4UP) 1/2.76 (1Dn3UP) 1/4.1 (1Dn2UP) 1/8.3 (1Dn1UP) | | | | |
| | EDGE (support multi class 12 max) | | 1/2 (1Dn4UP) 1/2.76 (1Dn3UP) 1/4.1 (1Dn2UP) 1/8.3 (1Dn1UP) | | | | |
| | WCDMA | | 1 | | | | |
| | LTE | | 1 | | | | |
| | WLAN 802.11 a/b/g/n(20M/40M) | | 1 | | | | |
| | Bluetooth | | 1 | | | | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| | | | | |
|--------------------------|-------------------------|--------|---|--------|
| TX Frequency Range (MHz) | GSM850 | 824.2 | — | 848.8 |
| | GSM1900 | 1850.2 | — | 1909.8 |
| | WCDMA Band II | 1852.4 | — | 1907.6 |
| | WCDMA Band V | 826.4 | — | 846.6 |
| | LTE FDD Band II | 1850 | — | 1910 |
| | LTE FDD Band V | 824 | — | 849 |
| | LTE FDD Band VII | 2500 | — | 2570 |
| | WLAN 802.11 b/g/n(20M) | 2412 | — | 2462 |
| | WLAN802.11 n (40M) | 2422 | — | 2452 |
| | WLAN802.11 a 5.2G | 5180 | — | 5240 |
| | WLAN802.11 a 5.3G | 5260 | — | 5320 |
| | WLAN802.11 a 5.5G | 5500 | — | 5700 |
| | WLAN802.11 a 5.8G | 5745 | — | 5825 |
| | WLAN802.11 n (20M) 5.2G | 5180 | — | 5240 |
| | WLAN802.11 n (20M) 5.3G | 5260 | — | 5320 |
| | WLAN802.11 n (20M) 5.5G | 5500 | — | 5700 |
| | WLAN802.11 n (20M) 5.8G | 5745 | — | 5825 |
| | WLAN802.11 n (40M) 5.2G | 5190 | — | 5230 |
| | WLAN802.11 n (40M) 5.3G | 5270 | — | 5310 |
| | WLAN802.11 n (40M) 5.5G | 5510 | — | 5670 |
| | WLAN802.11 n (40M) 5.8G | 5755 | — | 5795 |
| | Bluetooth | 2402 | — | 2480 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| | | | | |
|----------------------------|-------------------------|-------|---|-------|
| Channel Number (ARFCN). | GSM850 | 128 | — | 251 |
| | GSM1900 | 512 | — | 810 |
| | WCDMA Band II | 9262 | — | 9538 |
| | WCDMA Band V | 4132 | — | 4233 |
| | LTE FDD Band II | 18607 | — | 19193 |
| | LTE FDD Band V | 20415 | — | 20643 |
| | LTE FDD Band VII | 20775 | — | 21425 |
| | WLAN 802.11 b/g/n(20M) | 1 | — | 11 |
| | WLAN802.11 n (40M) | 3 | — | 9 |
| | WLAN802.11 a 5.2G | 36 | — | 48 |
| | WLAN802.11 a 5.3G | 52 | — | 64 |
| | WLAN802.11 a 5.5G | 100 | — | 140 |
| | WLAN802.11 a 5.8G | 149 | — | 165 |
| | WLAN802.11 n (20M) 5.2G | 36 | — | 48 |
| | WLAN802.11 n (20M) 5.3G | 52 | — | 64 |
| | WLAN802.11 n (20M) 5.5G | 100 | — | 140 |
| | WLAN802.11 n (20M) 5.8G | 149 | — | 165 |
| | WLAN802.11 n (40M) 5.2G | 38 | — | 46 |
| | WLAN802.11 n (40M) 5.3G | 54 | — | 62 |
| | WLAN802.11 n (40M) 5.5G | 102 | — | 134 |
| | WLAN802.11 n (40M) 5.8G | 151 | — | 159 |
| | Bluetooth | 0 | — | 78 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| Max. SAR (1 g) (Unit: W/Kg) | | | | | |
|-----------------------------|------------------|----------|----------|---|---|
| Mode | Band | Measured | Reported | Position / Channel | |
| Head | GSM 850 | 0.504 | 0.504 | <input checked="" type="checkbox"/> Left | <input type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | GSM 1900 | 0.187 | 0.191 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | WCDMA Band II | 0.282 | 0.288 | <input checked="" type="checkbox"/> Left | <input type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | WCDMA Band V | 0.451 | 0.462 | <input checked="" type="checkbox"/> Left | <input type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | LTE FDD Band II | 0.446 | 0.460 | <input checked="" type="checkbox"/> Left | <input type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | LTE FDD Band V | 0.439 | 0.453 | <input checked="" type="checkbox"/> Left | <input type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | LTE FDD Band VII | 0.247 | 0.249 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | | | | 21350 | Channel |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Max. SAR (1 g) (Unit: W/Kg) | | | | | |
|-----------------------------|-------------------|----------|----------|---|---|
| Mode | Band | Measured | Reported | Position / Channel | |
| Head | WLAN802.11 b | 0.514 | 0.525 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | | | | 6 | Channel |
| | WLAN802.11 a 5.2G | 0.204 | 0.225 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input type="checkbox"/> Cheek | <input checked="" type="checkbox"/> Tilt |
| | | | | 48 | Channel |
| | WLAN802.11 a 5.3G | 0.218 | 0.219 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | | | | 64 | Channel |
| | WLAN802.11 a 5.6G | 0.410 | 0.411 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | | | | 132 | Channel |
| | WLAN802.11 a 5.8G | 0.491 | 0.518 | <input type="checkbox"/> Left | <input checked="" type="checkbox"/> Right |
| | | | | <input checked="" type="checkbox"/> Cheek | <input type="checkbox"/> Tilt |
| | | | | 157 | Channel |
| | | | | | |
| | | | | | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Max. SAR (1 g) (Unit: W/Kg) | | | | |
|-----------------------------|-------------------|----------|----------|--|
| Mode | Band | Measured | Reported | Position / Channel |
| Body worn (speech mode) | GSM 850 | 0.353 | 0.353 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 251 Channel |
| | GSM 1900 | 0.312 | 0.319 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 810 Channel |
| | WCDMA Band II | 0.592 | 0.631 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 9400 Channel |
| | WCDMA Band V | 0.316 | 0.323 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 4123 Channel |
| | LTE FDD Band II | 0.682 | 0.703 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 19100 Channel |
| | LTE FDD Band V | 0.415 | 0.424 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 20600 Channel |
| | LTE FDD Band VII | 0.803 | 0.814 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 21100 Channel |
| | WLAN802.11 a 5.2G | 0.265 | 0.279 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 48 Channel |
| | WLAN802.11 a 5.3G | 0.70 | 0.271 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 56 Channel |
| | WLAN802.11 a 5.6G | 0.388 | 0.389 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 132 Channel |
| | WLAN802.11 a 5.8G | 0.346 | 0.356 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back 161 Channel |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| Max. SAR (1 g) (Unit: W/Kg) | | | | |
|-----------------------------|---------------------|----------|----------|--|
| Mode | Band | Measured | Reported | Position / Channel |
| Hotspot mode | GPRS 850 1Dn1P | 0.690 | 0.690 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back <input type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 251 Channel |
| | GPRS 1900 1Dn1UP | 0.616 | 0.630 | <input type="checkbox"/> Front <input type="checkbox"/> Back <input checked="" type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 810 Channel |
| | WCDMA Band II | 1.120 | 1.143 | <input type="checkbox"/> Front <input type="checkbox"/> Back <input checked="" type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 9538 Channel |
| | WCDMA Band V | 0.788 | 0.790 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back <input type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 4132 Channel |
| | LTE FDD Band II | 1.260 | 1.298 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back <input type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 19100 Channel - repeated at the highest SAR |
| | LTE FDD Band V | 0.534 | 0.545 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back <input type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 20600 Channel |
| | LTE FDD Band VII | 1.160 | 1.171 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back <input type="checkbox"/> Bottom <input type="checkbox"/> Right <input type="checkbox"/> Left 21350 Channel |
| | WLAN802.11 b | 0.546 | 0.549 | <input type="checkbox"/> Front <input checked="" type="checkbox"/> Back <input type="checkbox"/> Top <input type="checkbox"/> Right <input type="checkbox"/> Left 11 Channel |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

#. GSM/GPRS/EDGE conducted power table:

| EUT mode | Frequency (MHz) | CH | Max. Rated Avg. Power + Max. Tolerance (dBm) | Burst average power | Source-based time average power |
|--|-----------------|-----|--|---------------------|---------------------------------|
| | | | | Avg. (dBm) | Avg. (dBm) |
| GSM850 (GMSK) | 824.2 | 128 | 33.5 | 33.2 | 24.17 |
| | 836.6 | 190 | 33.5 | 33.4 | 24.37 |
| | 848.8 | 251 | 33.5 | 33.5 | 24.47 |
| The division factor compared to the number of TX time slot | | | | | |
| Division factor | | | 1 TX time slot | | -9.03 |

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 33.5 | 30.5 | 28.5 | 27.5 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| GPRS850 (GMSK) | 824.2 | 128 | 33.2 | 29.5 | 27.7 | 26.9 |
| | 836.6 | 190 | 33.4 | 29.5 | 27.8 | 26.9 |
| | 848.8 | 251 | 33.5 | 29.6 | 28 | 27.1 |
| Source-based time average power | | | | | | |
| GPRS850 (GMSK) | 824.2 | 128 | 24.17 | 23.48 | 23.44 | 23.89 |
| | 836.6 | 190 | 24.37 | 23.48 | 23.54 | 23.89 |
| | 848.8 | 251 | 24.47 | 23.58 | 23.74 | 24.09 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| | | | -9.03 | -6.02 | -4.26 | -3.01 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 33.5 | 30.5 | 28.5 | 27.5 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| EDGE850 (MCS4) | 824.2 | 128 | 33.2 | 29.5 | 27.7 | 26.9 |
| | 836.6 | 190 | 33.4 | 29.5 | 27.8 | 26.9 |
| | 848.8 | 251 | 33.4 | 29.5 | 27.8 | 27.1 |
| Source-based time average power | | | | | | |
| EDGE850 (MCS4) | 824.2 | 128 | 24.17 | 23.48 | 23.44 | 23.89 |
| | 836.6 | 190 | 24.37 | 23.48 | 23.54 | 23.89 |
| | 848.8 | 251 | 24.37 | 23.48 | 23.54 | 24.09 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| -9.03 | | | -6.02 | -4.26 | -3.01 | |

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 28 | 25.5 | 25 | 25 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| EDGE850 (MCS5) | 824.2 | 128 | 27.6 | 25 | 25 | 25 |
| | 836.6 | 190 | 27.5 | 25 | 25 | 25 |
| | 848.8 | 251 | 27.7 | 25.1 | 25 | 25 |
| Source-based time average power | | | | | | |
| EDGE850 (MCS5) | 824.2 | 128 | 18.57 | 18.98 | 20.74 | 21.99 |
| | 836.6 | 190 | 18.47 | 18.98 | 20.74 | 21.99 |
| | 848.8 | 251 | 18.67 | 19.08 | 20.74 | 21.99 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| -9.03 | | | -6.02 | -4.26 | -3.01 | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Burst average power | | | | | | |
|--|-------|-----------------|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 28 | 25.5 | 25 | 25 |
| EUT mode | | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| EDGE850 (MCS9) | 824.2 | 128 | 27.6 | 25 | 25 | 25 |
| | 836.6 | 190 | 27.5 | 25 | 25 | 25 |
| | 848.8 | 251 | 27.7 | 25.1 | 25 | 25 |
| Source-based time average power | | | | | | |
| EDGE850 (MCS9) | 824.2 | 128 | 18.57 | 18.98 | 20.74 | 21.99 |
| | 836.6 | 190 | 18.47 | 18.98 | 20.74 | 21.99 |
| | 848.8 | 251 | 18.67 | 19.08 | 20.74 | 21.99 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| -9.03 | | | -6.02 | -4.26 | -3.01 | |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | | | |
| -9.03 | | | | | | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 30.5 | 27 | 25 | 24.5 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| GPRS1900 (GMSK) | 1850.2 | 512 | 30 | 26.5 | 24.7 | 23.8 |
| | 1800 | 661 | 30 | 26.5 | 24.7 | 23.8 |
| | 1909.8 | 810 | 30.4 | 26.6 | 24.8 | 24.3 |
| Source-based time average power | | | | | | |
| GPRS1900 (GMSK) | 1850.2 | 512 | 20.97 | 20.48 | 20.44 | 20.79 |
| | 1800 | 661 | 20.97 | 20.48 | 20.44 | 20.79 |
| | 1909.8 | 810 | 21.37 | 20.58 | 20.54 | 21.29 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| Division factor | | | -9.03 | -6.02 | -4.26 | -3.01 |

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 30.5 | 27 | 25 | 24.5 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| EDGE1900 (MCS4) | 1850.2 | 512 | 30.1 | 26.5 | 24.7 | 23.8 |
| | 1800 | 661 | 30 | 26.5 | 24.7 | 23.8 |
| | 1909.8 | 810 | 30.4 | 26.6 | 24.8 | 24.1 |
| Source-based time average power | | | | | | |
| EDGE1900 (MCS4) | 1850.2 | 512 | 21.07 | 20.48 | 20.44 | 20.79 |
| | 1800 | 661 | 20.97 | 20.48 | 20.44 | 20.79 |
| | 1909.8 | 810 | 21.37 | 20.58 | 20.54 | 21.09 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| Division factor | | | -9.03 | -6.02 | -4.26 | -3.01 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 27.5 | 24.5 | 23.5 | 22.5 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| | 1850.2 | 512 | 27.2 | 24.3 | 23.2 | 22.2 |
| | 1800 | 661 | 27.2 | 24.3 | 23.3 | 22.2 |
| | 1909.8 | 810 | 27.5 | 24.5 | 23.5 | 22.5 |
| Source-based time average power | | | | | | |
| EDGE1900 (MCS5) | 1850.2 | 512 | 18.17 | 18.28 | 18.94 | 19.19 |
| | 1800 | 661 | 18.17 | 18.28 | 19.04 | 19.19 |
| | 1909.8 | 810 | 18.47 | 18.48 | 19.24 | 19.49 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| | | | -9.03 | -6.02 | -4.26 | -3.01 |

| Burst average power | | | | | | |
|--|-----------------|-----|----------------|----------------|----------------|----------------|
| Max. Rated Avg. Power + Max. Tolerance (dBm) | | | 27.5 | 24.5 | 23.5 | 22.5 |
| | | | 1Dn1UP | 1Dn2UP | 1Dn3UP | 1Dn4UP |
| EUT mode | Frequency (MHz) | CH | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) | Avg. (dBm) |
| | 1850.2 | 512 | 27.2 | 24.3 | 23.2 | 22.2 |
| | 1800 | 661 | 27.2 | 24.3 | 23.3 | 22.2 |
| | 1909.8 | 810 | 27.5 | 24.5 | 23.5 | 22.5 |
| Source-based time average power | | | | | | |
| EDGE1900 (MCS9) | 1850.2 | 512 | 18.17 | 18.28 | 18.94 | 19.19 |
| | 1800 | 661 | 18.17 | 18.28 | 19.04 | 19.19 |
| | 1909.8 | 810 | 18.47 | 18.48 | 19.24 | 19.49 |
| The division factor compared to the number of TX time slot | | | | | | |
| Division factor | | | 1 TX time slot | 2 TX time slot | 3 TX time slot | 4 TX time slot |
| | | | -9.03 | -6.02 | -4.26 | -3.01 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

#. WCDMA Band II / Band V / HSDPA / HSUPA/ HSPA+ _conducted power table:

| Band | CH | Max. Rated Avg. Power + Max. Tolerance (dBm) | Rel99 AV(dBm) | HSDPA mode AV(dBm) | | | | HSUPA mode AV(dBm) | | | | | HSPA+ mode AV(dBm) | | | | |
|---------------|------|--|---------------|--------------------|-------|-------|-------|--------------------|-------|-------|-------|-------|--------------------|-------|-------|-------|-------|
| | | | | SUB-1 | SUB-2 | SUB-3 | SUB-4 | SUB-1 | SUB-2 | SUB-3 | SUB-4 | SUB-5 | SUB-1 | SUB-2 | SUB-3 | SUB-4 | SUB-5 |
| WCDMA Band II | 9262 | 24.5 | 24.23 | 23.29 | 24.11 | 22.81 | 22.88 | 24.15 | 22.20 | 23.21 | 22.33 | 23.25 | 24.16 | 22.14 | 23.13 | 22.25 | 23.96 |
| | 9400 | 24.5 | 24.22 | 23.23 | 24.08 | 22.78 | 22.79 | 24.20 | 22.27 | 23.22 | 22.32 | 23.21 | 24.19 | 22.23 | 23.18 | 22.27 | 24.04 |
| | 9538 | 24.5 | 24.41 | 23.36 | 24.26 | 22.83 | 22.95 | 24.35 | 22.39 | 23.43 | 22.43 | 23.43 | 24.36 | 22.35 | 23.37 | 22.39 | 24.22 |
| WCDMA Band V | 4132 | 24.5 | 24.49 | 23.44 | 24.42 | 22.98 | 23.03 | 24.45 | 22.51 | 23.19 | 22.56 | 23.42 | 24.46 | 22.49 | 23.44 | 22.52 | 24.27 |
| | 4183 | 24.5 | 24.48 | 23.35 | 24.37 | 22.87 | 22.91 | 24.41 | 22.49 | 23.17 | 22.55 | 23.39 | 24.40 | 22.42 | 23.40 | 22.48 | 24.17 |
| | 4233 | 24.5 | 24.40 | 23.22 | 24.27 | 22.73 | 22.79 | 24.32 | 22.36 | 23.10 | 22.44 | 23.19 | 24.31 | 22.28 | 23.30 | 22.34 | 24.13 |

HSDPA

| SUB-TEST | β_c | β_d | $\beta_{d(SF)}$ | β_c/β_d | β_{HS} (Note 1, Note 2) | CM (dB) (Note 3) | MPR (dB) (Note 3) |
|----------|-----------|-----------|-----------------|-------------------|----------------------------------|---------------------|----------------------|
| 1 | 2/15 | 15/15 | 64 | 2/15 | 4/15 | 0.0 | 0.0 |
| 2 | 12/15 | 15/15 | 64 | 12/15 | 24/15 | 1.0 | 0.0 |
| 3 | 15/15 | 8/15 | 64 | 15/8 | 30/15 | 1.5 | 0.5 |
| 4 | 15/15 | 4/15 | 64 | 15/4 | 30/15 | 1.5 | 0.5 |

HSUPA

| SUB-TEST | β_c | β_d | $\beta_{d(SF)}$ | β_c/β_d | β_{HS} (Note 1) | β_{ec} | β_{ed} (Note 5) (Note 6) | β_{ed} (SF) | β_{ed} (Codes) | CM (dB) (Note 2) | MPR (dB) (Note 2) | AG Index (Note 6) | E-TFCI |
|----------|-----------|-----------|-----------------|-------------------|--------------------------|--------------|--|----------------------|-------------------------|------------------------|-------------------------|-------------------------|--------|
| 1 | 11/15 | 15/15 | 64 | 11/15 | 22/15 | 209/225 | 1309/225 | 4 | 1 | 1.0 | 0.0 | 20 | 75 |
| 2 | 6/15 | 15/15 | 64 | 6/15 | 12/15 | 12/15 | 94/75 | 4 | 1 | 3.0 | 2.0 | 12 | 67 |
| 3 | 15/15 | 9/15 | 64 | 15/9 | 30/15 | 30/15 | $\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$ | 4 | 2 | 2.0 | 1.0 | 15 | 92 |
| 4 | 2/15 | 15/15 | 64 | 2/15 | 4/15 | 2/15 | 56/75 | 4 | 1 | 3.0 | 2.0 | 17 | 71 |
| 5 | 15/15 | 15/15 | 64 | 15/15 | 30/15 | 24/15 | 134/15 | 4 | 1 | 1.0 | 0.0 | 21 | 81 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

台灣檢驗科技股份有限公司

Member of SGS Group

LTE FDD Band II / Band V/ Band VII power table:

| LTE Band2 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 1.4 | QPSK | 1 | 0 | 1850.7 | 18607 | 23.96 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.01 | 24.5 | 0 |
| | | | | 1909.3 | 19193 | 24.21 | 24.5 | 0 |
| | | | 2 | 1850.7 | 18607 | 24.05 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.15 | 24.5 | 0 |
| | | | | 1909.3 | 19193 | 24.25 | 24.5 | 0 |
| | | | 5 | 1850.7 | 18607 | 23.95 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.03 | 24.5 | 0 |
| | | | | 1909.3 | 19193 | 24.33 | 24.5 | 0 |
| | | 3 | 0 | 1850.7 | 18607 | 23.14 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.22 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.40 | 24 | 0-1 |
| | | | 2 | 1850.7 | 18607 | 23.05 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.15 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.39 | 24 | 0-1 |
| | | | 3 | 1850.7 | 18607 | 23.14 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.18 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.38 | 24 | 0-1 |
| | | 6 | 0 | 1850.7 | 18607 | 23.20 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.19 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.34 | 24 | 0-1 |
| 16QAM | 16QAM | 1 | 0 | 1850.7 | 18607 | 23.04 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.24 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.30 | 24 | 0-1 |
| | | | 2 | 1850.7 | 18607 | 23.13 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.33 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.34 | 24 | 0-1 |
| | | | 5 | 1850.7 | 18607 | 23.03 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.22 | 24 | 0-1 |
| | | | | 1909.3 | 19193 | 23.24 | 24 | 0-1 |
| | | 3 | 0 | 1850.7 | 18607 | 23.00 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.97 | 23 | 0-2 |
| | | | | 1909.3 | 19193 | 22.92 | 23 | 0-2 |
| | | | 2 | 1850.7 | 18607 | 22.88 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.81 | 23 | 0-2 |
| | | | | 1909.3 | 19193 | 22.94 | 23 | 0-2 |
| | | | 3 | 1850.7 | 18607 | 22.96 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.86 | 23 | 0-2 |
| | | | | 1909.3 | 19193 | 22.87 | 23 | 0-2 |
| | | 6 | 0 | 1850.7 | 18607 | 22.18 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.36 | 23 | 0-2 |
| | | | | 1909.3 | 19193 | 22.51 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band2 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 3 | QPSK | 1 | 0 | 1851.5 | 18615 | 24.07 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.08 | 24.5 | 0 |
| | | | | 1908.5 | 19185 | 24.18 | 24.5 | 0 |
| | | | 7 | 1851.5 | 18615 | 24.02 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.05 | 24.5 | 0 |
| | | | | 1908.5 | 19185 | 24.27 | 24.5 | 0 |
| | | | 14 | 1851.5 | 18615 | 24.02 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.06 | 24.5 | 0 |
| | | | | 1908.5 | 19185 | 24.31 | 24.5 | 0 |
| | | 8 | 0 | 1851.5 | 18615 | 23.14 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.19 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.43 | 24 | 0-1 |
| | | | 4 | 1851.5 | 18615 | 23.09 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.17 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.36 | 24 | 0-1 |
| | | | 7 | 1851.5 | 18615 | 23.13 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.19 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.43 | 24 | 0-1 |
| | | 15 | 0 | 1851.5 | 18615 | 23.11 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.13 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.35 | 24 | 0-1 |
| | | | 1 | 1851.5 | 18615 | 23.08 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.03 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.11 | 24 | 0-1 |
| | | | 7 | 1851.5 | 18615 | 23.15 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.03 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.05 | 24 | 0-1 |
| | | 16QAM | 14 | 1851.5 | 18615 | 23.1 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.07 | 24 | 0-1 |
| | | | | 1908.5 | 19185 | 23.04 | 24 | 0-1 |
| | | | 0 | 1851.5 | 18615 | 22.27 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.34 | 23 | 0-2 |
| | | | | 1908.5 | 19185 | 22.49 | 23 | 0-2 |
| | | | 4 | 1851.5 | 18615 | 22.29 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.31 | 23 | 0-2 |
| | | | | 1908.5 | 19185 | 22.46 | 23 | 0-2 |
| | | | 7 | 1851.5 | 18615 | 22.3 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.32 | 23 | 0-2 |
| | | | | 1908.5 | 19185 | 22.47 | 23 | 0-2 |
| | | | 15 | 1851.5 | 18615 | 22.19 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.22 | 23 | 0-2 |
| | | | | 1908.5 | 19185 | 22.39 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band2 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 5 | QPSK | 1 | 0 | 1922.5 | 18025 | 24.14 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.08 | 24.5 | 0 |
| | | | | 1907.5 | 19175 | 24.22 | 24.5 | 0 |
| | | | 12 | 1922.5 | 18025 | 24.09 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.07 | 24.5 | 0 |
| | | | | 1907.5 | 19175 | 24.27 | 24.5 | 0 |
| | | | 24 | 1922.5 | 18025 | 24.05 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.15 | 24.5 | 0 |
| | | | | 1907.5 | 19175 | 24.29 | 24.5 | 0 |
| | | 12 | 0 | 1922.5 | 18025 | 23.12 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.22 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.31 | 24 | 0-1 |
| | | | 6 | 1922.5 | 18025 | 23.14 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.17 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.37 | 24 | 0-1 |
| | | | 13 | 1922.5 | 18025 | 23.12 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.22 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.44 | 24 | 0-1 |
| | | 25 | 0 | 1922.5 | 18025 | 23.09 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.2 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.39 | 24 | 0-1 |
| | 16QAM | 1 | 0 | 1922.5 | 18025 | 23.39 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.47 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.47 | 24 | 0-1 |
| | | | 12 | 1922.5 | 18025 | 23.39 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.32 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.49 | 24 | 0-1 |
| | | | 24 | 1922.5 | 18025 | 23.4 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.41 | 24 | 0-1 |
| | | | | 1907.5 | 19175 | 23.42 | 24 | 0-1 |
| | | 12 | 0 | 1922.5 | 18025 | 22.15 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.27 | 23 | 0-2 |
| | | | | 1907.5 | 19175 | 22.47 | 23 | 0-2 |
| | | | 6 | 1922.5 | 18025 | 22.12 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.26 | 23 | 0-2 |
| | | | | 1907.5 | 19175 | 22.45 | 23 | 0-2 |
| | | | 13 | 1922.5 | 18025 | 22.26 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.29 | 23 | 0-2 |
| | | | | 1907.5 | 19175 | 22.39 | 23 | 0-2 |
| | | 25 | 0 | 1922.5 | 18025 | 22.1 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.16 | 23 | 0-2 |
| | | | | 1907.5 | 19175 | 22.36 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band2 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 10 | QPSK | 1 | 0 | 1855 | 18650 | 24.13 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.14 | 24.5 | 0 |
| | | | | 1905 | 19150 | 24.17 | 24.5 | 0 |
| | | | 25 | 1855 | 18650 | 24.03 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.14 | 24.5 | 0 |
| | | | | 1905 | 19150 | 24.17 | 24.5 | 0 |
| | | | 49 | 1855 | 18650 | 24.06 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.17 | 24.5 | 0 |
| | | | | 1905 | 19150 | 24.29 | 24.5 | 0 |
| | | 25 | 0 | 1855 | 18650 | 23.15 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.17 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.4 | 24 | 0-1 |
| | | | 12 | 1855 | 18650 | 23.11 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.25 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.37 | 24 | 0-1 |
| | | | 25 | 1855 | 18650 | 23.08 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.26 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.42 | 24 | 0-1 |
| | | 50 | 0 | 1855 | 18650 | 23.26 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.24 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.39 | 24 | 0-1 |
| 16QAM | 16QAM | 1 | 0 | 1855 | 18650 | 23.52 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.24 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.28 | 24 | 0-1 |
| | | | 25 | 1855 | 18650 | 23.52 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.28 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.45 | 24 | 0-1 |
| | | | 49 | 1855 | 18650 | 23.56 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.58 | 24 | 0-1 |
| | | | | 1905 | 19150 | 23.34 | 24 | 0-1 |
| | | 25 | 0 | 1855 | 18650 | 22.18 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.27 | 23 | 0-2 |
| | | | | 1905 | 19150 | 22.41 | 23 | 0-2 |
| | | | 12 | 1855 | 18650 | 22.16 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.25 | 23 | 0-2 |
| | | | | 1905 | 19150 | 22.46 | 23 | 0-2 |
| | | | 25 | 1855 | 18650 | 22.15 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.29 | 23 | 0-2 |
| | | | | 1905 | 19150 | 22.47 | 23 | 0-2 |
| | | 50 | 0 | 1855 | 18650 | 22.24 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.26 | 23 | 0-2 |
| | | | | 1905 | 19150 | 22.44 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band2 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 15 | QPSK | 1 | 0 | 1857.5 | 18675 | 24.1 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.08 | 24.5 | 0 |
| | | | | 1902.5 | 19125 | 24.19 | 24.5 | 0 |
| | | | 36 | 1857.5 | 18675 | 24.01 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.1 | 24.5 | 0 |
| | | | | 1902.5 | 19125 | 24.28 | 24.5 | 0 |
| | | | 74 | 1857.5 | 18675 | 24.02 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.21 | 24.5 | 0 |
| | | | | 1902.5 | 19125 | 24.36 | 24.5 | 0 |
| | | 36 | 0 | 1857.5 | 18675 | 23.2 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.12 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.32 | 24 | 0-1 |
| | | | 18 | 1857.5 | 18675 | 23.19 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.21 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.27 | 24 | 0-1 |
| | | | 37 | 1857.5 | 18675 | 23.2 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.23 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.43 | 24 | 0-1 |
| | | 75 | 0 | 1857.5 | 18675 | 23.17 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.17 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.39 | 24 | 0-1 |
| | 16QAM | 1 | 0 | 1857.5 | 18675 | 23.24 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.31 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.17 | 24 | 0-1 |
| | | | 36 | 1857.5 | 18675 | 23.22 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.27 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.29 | 24 | 0-1 |
| | | | 74 | 1857.5 | 18675 | 23.24 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.24 | 24 | 0-1 |
| | | | | 1902.5 | 19125 | 23.41 | 24 | 0-1 |
| | | 36 | 0 | 1857.5 | 18675 | 22.19 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.25 | 23 | 0-2 |
| | | | | 1902.5 | 19125 | 22.33 | 23 | 0-2 |
| | | | 18 | 1857.5 | 18675 | 22.16 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.24 | 23 | 0-2 |
| | | | | 1902.5 | 19125 | 22.4 | 23 | 0-2 |
| | | | 37 | 1857.5 | 18675 | 22.2 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.25 | 23 | 0-2 |
| | | | | 1902.5 | 19125 | 22.45 | 23 | 0-2 |
| | | 75 | 0 | 1857.5 | 18675 | 22.17 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.24 | 23 | 0-2 |
| | | | | 1902.5 | 19125 | 22.4 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band2 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 20 | QPSK | 1 | 0 | 1860 | 18700 | 24.11 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.07 | 24.5 | 0 |
| | | | | 1900 | 19100 | 24.18 | 24.5 | 0 |
| | | | 50 | 1860 | 18700 | 24.06 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.09 | 24.5 | 0 |
| | | | | 1900 | 19100 | 24.22 | 24.5 | 0 |
| | | | 99 | 1860 | 18700 | 24.16 | 24.5 | 0 |
| | | | | 1880 | 18900 | 24.17 | 24.5 | 0 |
| | | | | 1900 | 19100 | 24.37 | 24.5 | 0 |
| | | 50 | 0 | 1860 | 18700 | 23.15 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.15 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.32 | 24 | 0-1 |
| | | | 25 | 1860 | 18700 | 23.15 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.14 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.33 | 24 | 0-1 |
| | | | 50 | 1860 | 18700 | 23.17 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.31 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.42 | 24 | 0-1 |
| | | 100 | 0 | 1860 | 18700 | 23.12 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.14 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.37 | 24 | 0-1 |
| 16QAM | 16QAM | 1 | 0 | 1860 | 18700 | 23.51 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.39 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.32 | 24 | 0-1 |
| | | | 50 | 1860 | 18700 | 23.5 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.17 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.39 | 24 | 0-1 |
| | | | 99 | 1860 | 18700 | 23.57 | 24 | 0-1 |
| | | | | 1880 | 18900 | 23.48 | 24 | 0-1 |
| | | | | 1900 | 19100 | 23.26 | 24 | 0-1 |
| | | 50 | 0 | 1860 | 18700 | 22.18 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.17 | 23 | 0-2 |
| | | | | 1900 | 19100 | 22.24 | 23 | 0-2 |
| | | | 25 | 1860 | 18700 | 22.21 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.17 | 23 | 0-2 |
| | | | | 1900 | 19100 | 22.26 | 23 | 0-2 |
| | | | 50 | 1860 | 18700 | 22.25 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.24 | 23 | 0-2 |
| | | | | 1900 | 19100 | 22.37 | 23 | 0-2 |
| | | 100 | 0 | 1860 | 18700 | 22.2 | 23 | 0-2 |
| | | | | 1880 | 18900 | 22.16 | 23 | 0-2 |
| | | | | 1900 | 19100 | 22.29 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band5 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 1.4 | QPSK | 1 | 0 | 824.7 | 20407 | 24.2 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.15 | 24.5 | 0 |
| | | | | 848.3 | 20643 | 24.27 | 24.5 | 0 |
| | | | 2 | 824.7 | 20407 | 24.25 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.25 | 24.5 | 0 |
| | | | | 848.3 | 20643 | 24.29 | 24.5 | 0 |
| | | | 5 | 824.7 | 20407 | 24.14 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.17 | 24.5 | 0 |
| | | | | 848.3 | 20643 | 24.22 | 24.5 | 0 |
| | | 3 | 0 | 824.7 | 20407 | 23.23 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.20 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.27 | 24 | 0-1 |
| | | | 2 | 824.7 | 20407 | 23.17 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.10 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.19 | 24 | 0-1 |
| | | | 3 | 824.7 | 20407 | 23.21 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.18 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.25 | 24 | 0-1 |
| | | 6 | 0 | 824.7 | 20407 | 23.25 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.21 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.22 | 24 | 0-1 |
| | | | 0 | 824.7 | 20407 | 23.4 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.36 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.45 | 24 | 0-1 |
| | | | 2 | 824.7 | 20407 | 23.49 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.5 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.51 | 24 | 0-1 |
| | | | 5 | 824.7 | 20407 | 23.36 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.43 | 24 | 0-1 |
| | | | | 848.3 | 20643 | 23.43 | 24 | 0-1 |
| | | 16QAM | 0 | 824.7 | 20407 | 22.26 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.27 | 23 | 0-2 |
| | | | | 848.3 | 20643 | 22.30 | 23 | 0-2 |
| | | | 2 | 824.7 | 20407 | 22.26 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.19 | 23 | 0-2 |
| | | | | 848.3 | 20643 | 22.26 | 23 | 0-2 |
| | | | 3 | 824.7 | 20407 | 22.27 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.22 | 23 | 0-2 |
| | | | | 848.3 | 20643 | 22.28 | 23 | 0-2 |
| | | | 6 | 824.7 | 20407 | 22.3 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.3 | 23 | 0-2 |
| | | | | 848.3 | 20643 | 22.33 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band5 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 3 | QPSK | 1 | 0 | 825.5 | 20415 | 24.26 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.14 | 24.5 | 0 |
| | | | | 847.5 | 20635 | 24.25 | 24.5 | 0 |
| | | | 7 | 825.5 | 20415 | 24.23 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.1 | 24.5 | 0 |
| | | | | 847.5 | 20635 | 24.25 | 24.5 | 0 |
| | | | 14 | 825.5 | 20415 | 24.24 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.1 | 24.5 | 0 |
| | | | | 847.5 | 20635 | 24.19 | 24.5 | 0 |
| | | 8 | 0 | 825.5 | 20415 | 23.36 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.22 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.34 | 24 | 0-1 |
| | | | 4 | 825.5 | 20415 | 23.28 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.2 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.3 | 24 | 0-1 |
| | | | 7 | 825.5 | 20415 | 23.35 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.22 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.3 | 24 | 0-1 |
| | | 15 | 0 | 825.5 | 20415 | 23.3 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.22 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.3 | 24 | 0-1 |
| | 16QAM | 1 | 0 | 825.5 | 20415 | 23.31 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.17 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.28 | 24 | 0-1 |
| | | | 7 | 825.5 | 20415 | 23.34 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.21 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.32 | 24 | 0-1 |
| | | | 14 | 825.5 | 20415 | 23.29 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.21 | 24 | 0-1 |
| | | | | 847.5 | 20635 | 23.26 | 24 | 0-1 |
| | | 8 | 0 | 825.5 | 20415 | 22.39 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.28 | 23 | 0-2 |
| | | | | 847.5 | 20635 | 22.39 | 23 | 0-2 |
| | | | 4 | 825.5 | 20415 | 22.37 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.29 | 23 | 0-2 |
| | | | | 847.5 | 20635 | 22.37 | 23 | 0-2 |
| | | | 7 | 825.5 | 20415 | 22.4 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.31 | 23 | 0-2 |
| | | | | 847.5 | 20635 | 22.44 | 23 | 0-2 |
| | | 15 | 0 | 825.5 | 20415 | 22.28 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.18 | 23 | 0-2 |
| | | | | 847.5 | 20635 | 22.33 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band5 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 5 | QPSK | 1 | 0 | 826.5 | 20425 | 24.37 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.25 | 24.5 | 0 |
| | | | | 846.5 | 20625 | 24.4 | 24.5 | 0 |
| | | | 12 | 826.5 | 20425 | 24.31 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.25 | 24.5 | 0 |
| | | | | 846.5 | 20625 | 24.35 | 24.5 | 0 |
| | | | 24 | 826.5 | 20425 | 24.33 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.24 | 24.5 | 0 |
| | | | | 846.5 | 20625 | 24.31 | 24.5 | 0 |
| | | 12 | 0 | 826.5 | 20425 | 23.4 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.26 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.35 | 24 | 0-1 |
| | | | 6 | 826.5 | 20425 | 23.3 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.23 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.33 | 24 | 0-1 |
| | | | 13 | 826.5 | 20425 | 23.37 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.25 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.3 | 24 | 0-1 |
| | | 16QAM | 25 | 826.5 | 20425 | 23.27 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.21 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.3 | 24 | 0-1 |
| | | | 0 | 826.5 | 20425 | 23.54 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.38 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.53 | 24 | 0-1 |
| | | | 12 | 826.5 | 20425 | 23.5 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.42 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.5 | 24 | 0-1 |
| | | | 24 | 826.5 | 20425 | 23.4 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.4 | 24 | 0-1 |
| | | | | 846.5 | 20625 | 23.39 | 24 | 0-1 |
| | | | 0 | 826.5 | 20425 | 22.46 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.41 | 23 | 0-2 |
| | | | | 846.5 | 20625 | 22.46 | 23 | 0-2 |
| | | | 12 | 826.5 | 20425 | 22.44 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.36 | 23 | 0-2 |
| | | | | 846.5 | 20625 | 22.44 | 23 | 0-2 |
| | | | 13 | 826.5 | 20425 | 22.42 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.4 | 23 | 0-2 |
| | | | | 846.5 | 20625 | 22.44 | 23 | 0-2 |
| | | | 25 | 826.5 | 20425 | 22.41 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.35 | 23 | 0-2 |
| | | | | 846.5 | 20625 | 22.37 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band5 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 10 | QPSK | 1 | 0 | 829 | 20450 | 24.36 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.28 | 24.5 | 0 |
| | | | | 844 | 20600 | 24.35 | 24.5 | 0 |
| | | | 25 | 829 | 20450 | 24.34 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.32 | 24.5 | 0 |
| | | | | 844 | 20600 | 24.39 | 24.5 | 0 |
| | | | 49 | 829 | 20450 | 24.28 | 24.5 | 0 |
| | | | | 836.5 | 20525 | 24.37 | 24.5 | 0 |
| | | | | 844 | 20600 | 24.41 | 24.5 | 0 |
| | | 25 | 0 | 829 | 20450 | 23.46 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.46 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.44 | 24 | 0-1 |
| | | | 12 | 829 | 20450 | 23.47 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.44 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.48 | 24 | 0-1 |
| | | | 25 | 829 | 20450 | 23.48 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.50 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.51 | 24 | 0-1 |
| | | 50 | 0 | 829 | 20450 | 23.51 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.50 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.49 | 24 | 0-1 |
| | 16QAM | 1 | 0 | 829 | 20450 | 23.3 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.21 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.72 | 24 | 0-1 |
| | | | 25 | 829 | 20450 | 23.3 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.3 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.75 | 24 | 0-1 |
| | | | 49 | 829 | 20450 | 23.27 | 24 | 0-1 |
| | | | | 836.5 | 20525 | 23.37 | 24 | 0-1 |
| | | | | 844 | 20600 | 23.62 | 24 | 0-1 |
| | | 25 | 0 | 829 | 20450 | 22.44 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.44 | 23 | 0-2 |
| | | | | 844 | 20600 | 22.57 | 23 | 0-2 |
| | | | 12 | 829 | 20450 | 22.44 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.46 | 23 | 0-2 |
| | | | | 844 | 20600 | 22.56 | 23 | 0-2 |
| | | | 25 | 829 | 20450 | 22.44 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.49 | 23 | 0-2 |
| | | | | 844 | 20600 | 22.55 | 23 | 0-2 |
| | | 50 | 0 | 829 | 20450 | 22.52 | 23 | 0-2 |
| | | | | 836.5 | 20525 | 22.51 | 23 | 0-2 |
| | | | | 844 | 20600 | 22.54 | 23 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band7 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 5 | QPSK | 1 | 0 | 2502.5 | 20775 | 22.28 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.27 | 22.5 | 0 |
| | | | | 2567.5 | 21425 | 22.18 | 22.5 | 0 |
| | | | 12 | 2502.5 | 20775 | 22.24 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.25 | 22.5 | 0 |
| | | | | 2567.5 | 21425 | 22.26 | 22.5 | 0 |
| | | | 24 | 2502.5 | 20775 | 22.27 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.29 | 22.5 | 0 |
| | | | | 2567.5 | 21425 | 22.28 | 22.5 | 0 |
| | | 12 | 0 | 2502.5 | 20775 | 21.29 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.21 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.26 | 22 | 0-1 |
| | | | 6 | 2502.5 | 20775 | 21.29 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.28 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.29 | 22 | 0-1 |
| | | | 13 | 2502.5 | 20775 | 21.30 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.29 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.32 | 22 | 0-1 |
| | | 25 | 0 | 2502.5 | 20775 | 21.32 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.33 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.29 | 22 | 0-1 |
| 16QAM | 16QAM | 1 | 0 | 2502.5 | 20775 | 21.61 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.71 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.29 | 22 | 0-1 |
| | | | 12 | 2502.5 | 20775 | 21.80 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.48 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.40 | 22 | 0-1 |
| | | | 24 | 2502.5 | 20775 | 21.85 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.83 | 22 | 0-1 |
| | | | | 2567.5 | 21425 | 21.45 | 22 | 0-1 |
| | | 12 | 0 | 2502.5 | 20775 | 20.25 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.22 | 21 | 0-2 |
| | | | | 2567.5 | 21425 | 20.27 | 21 | 0-2 |
| | | | 6 | 2502.5 | 20775 | 20.23 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.23 | 21 | 0-2 |
| | | | | 2567.5 | 21425 | 20.26 | 21 | 0-2 |
| | | | 13 | 2502.5 | 20775 | 20.28 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.22 | 21 | 0-2 |
| | | | | 2567.5 | 21425 | 20.34 | 21 | 0-2 |
| | | 25 | 0 | 2502.5 | 20775 | 20.27 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.26 | 21 | 0-2 |
| | | | | 2567.5 | 21425 | 20.26 | 21 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band7 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 10 | QPSK | 1 | 0 | 2505 | 20800 | 22.02 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.09 | 22.5 | 0 |
| | | | | 2565 | 21400 | 22.18 | 22.5 | 0 |
| | | | 25 | 2505 | 20800 | 22.06 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.19 | 22.5 | 0 |
| | | | | 2565 | 21400 | 22.18 | 22.5 | 0 |
| | | | 49 | 2505 | 20800 | 22.13 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.28 | 22.5 | 0 |
| | | | | 2565 | 21400 | 22.29 | 22.5 | 0 |
| | | 25 | 0 | 2505 | 20800 | 21.09 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.21 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.23 | 22 | 0-1 |
| | | | 12 | 2505 | 20800 | 21.14 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.22 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.26 | 22 | 0-1 |
| | | | 25 | 2505 | 20800 | 21.30 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.28 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.31 | 22 | 0-1 |
| | | 50 | 0 | 2505 | 20800 | 21.15 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.21 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.23 | 22 | 0-1 |
| 16QAM | 16QAM | 1 | 0 | 2505 | 20800 | 21.27 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.32 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.36 | 22 | 0-1 |
| | | | 25 | 2505 | 20800 | 21.28 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.45 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.39 | 22 | 0-1 |
| | | | 49 | 2505 | 20800 | 21.34 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.62 | 22 | 0-1 |
| | | | | 2565 | 21400 | 21.69 | 22 | 0-1 |
| | | 25 | 0 | 2505 | 20800 | 20.14 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.12 | 21 | 0-2 |
| | | | | 2565 | 21400 | 20.14 | 21 | 0-2 |
| | | | 12 | 2505 | 20800 | 20.40 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.16 | 21 | 0-2 |
| | | | | 2565 | 21400 | 20.16 | 21 | 0-2 |
| | | | 25 | 2505 | 20800 | 20.10 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.22 | 21 | 0-2 |
| | | | | 2565 | 21400 | 20.21 | 21 | 0-2 |
| | | 50 | 0 | 2505 | 20800 | 20.11 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.18 | 21 | 0-2 |
| | | | | 2565 | 21400 | 20.19 | 21 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band7 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 15 | QPSK | 1 | 0 | 2507.5 | 20825 | 21.92 | 22.5 | 0 |
| | | | | 2535 | 21100 | 21.99 | 22.5 | 0 |
| | | | | 2562.5 | 21375 | 22.08 | 22.5 | 0 |
| | | | 36 | 2507.5 | 20825 | 21.96 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.09 | 22.5 | 0 |
| | | | | 2562.5 | 21375 | 22.08 | 22.5 | 0 |
| | | | 74 | 2507.5 | 20825 | 22.03 | 22.5 | 0 |
| | | | | 2535 | 21100 | 22.19 | 22.5 | 0 |
| | | | | 2562.5 | 21375 | 22.22 | 22.5 | 0 |
| | | 36 | 0 | 2507.5 | 20825 | 20.99 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.11 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.13 | 22 | 0-1 |
| | | | 18 | 2507.5 | 20825 | 21.04 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.12 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.16 | 22 | 0-1 |
| | | | 37 | 2507.5 | 20825 | 21.2 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.18 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.21 | 22 | 0-1 |
| | | 75 | 0 | 2507.5 | 20825 | 21.05 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.11 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.13 | 22 | 0-1 |
| | 16QAM | 1 | 0 | 2507.5 | 20825 | 21.17 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.22 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.26 | 22 | 0-1 |
| | | | 36 | 2507.5 | 20825 | 21.18 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.35 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.29 | 22 | 0-1 |
| | | | 74 | 2507.5 | 20825 | 21.24 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.52 | 22 | 0-1 |
| | | | | 2562.5 | 21375 | 21.59 | 22 | 0-1 |
| | | 36 | 0 | 2507.5 | 20825 | 20.04 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.02 | 21 | 0-2 |
| | | | | 2562.5 | 21375 | 20.04 | 21 | 0-2 |
| | | | 18 | 2507.5 | 20825 | 20.30 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.06 | 21 | 0-2 |
| | | | | 2562.5 | 21375 | 20.06 | 21 | 0-2 |
| | | | 37 | 2507.5 | 20825 | 20 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.12 | 21 | 0-2 |
| | | | | 2562.5 | 21375 | 20.11 | 21 | 0-2 |
| | | 75 | 0 | 2507.5 | 20825 | 20.01 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.08 | 21 | 0-2 |
| | | | | 2562.5 | 21375 | 20.09 | 21 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| LTE Band7 Conducted power table | | | | | | | | |
|---------------------------------|------------|---------|-----------|-----------------|---------|-----------------------|-------------------------------|--------------------------|
| BW (MHz) | Modulation | RB Size | RB Offset | Frequency (MHz) | Channel | Conducted Power (dBm) | Target Power + Max. Tolerance | MPR Allowed per 3GPP(dB) |
| 20 | QPSK | 1 | 0 | 2510 | 20850 | 22.01 | 22.3 | 0 |
| | | | | 2535 | 21100 | 22.08 | 22.3 | 0 |
| | | | | 2560 | 21350 | 22.10 | 22.3 | 0 |
| | | | 50 | 2510 | 20850 | 22.02 | 22.3 | 0 |
| | | | | 2535 | 21100 | 22.14 | 22.3 | 0 |
| | | | | 2560 | 21350 | 22.18 | 22.3 | 0 |
| | | | 99 | 2510 | 20850 | 22.17 | 22.3 | 0 |
| | | | | 2535 | 21100 | 22.24 | 22.3 | 0 |
| | | | | 2560 | 21350 | 22.26 | 22.3 | 0 |
| | | 50 | 0 | 2510 | 20850 | 21.19 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.21 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.25 | 22 | 0-1 |
| | | | 25 | 2510 | 20850 | 21.18 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.22 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.28 | 22 | 0-1 |
| | | | 50 | 2510 | 20850 | 21.25 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.32 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.37 | 22 | 0-1 |
| | | 100 | 0 | 2510 | 20850 | 21.15 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.20 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.30 | 22 | 0-1 |
| | 16QAM | 1 | 0 | 2510 | 20850 | 21.61 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.29 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.26 | 22 | 0-1 |
| | | | 50 | 2510 | 20850 | 21.34 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.26 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.65 | 22 | 0-1 |
| | | | 99 | 2510 | 20850 | 21.71 | 22 | 0-1 |
| | | | | 2535 | 21100 | 21.89 | 22 | 0-1 |
| | | | | 2560 | 21350 | 21.98 | 22 | 0-1 |
| | | 50 | 0 | 2510 | 20850 | 20.15 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.10 | 21 | 0-2 |
| | | | | 2560 | 21350 | 20.24 | 21 | 0-2 |
| | | | 25 | 2510 | 20850 | 20.11 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.19 | 21 | 0-2 |
| | | | | 2560 | 21350 | 20.28 | 21 | 0-2 |
| | | | 50 | 2510 | 20850 | 20.16 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.23 | 21 | 0-2 |
| | | | | 2560 | 21350 | 20.26 | 21 | 0-2 |
| | | 100 | 0 | 2510 | 20850 | 20.10 | 21 | 0-2 |
| | | | | 2535 | 21100 | 20.22 | 21 | 0-2 |
| | | | | 2560 | 21350 | 20.26 | 21 | 0-2 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

#. WLAN802.11 a/b/g/n (20M/40M) conducted power table:

| 802.11 b | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | |
|----------|-----------------|--|----------------------------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | |
| | | | 1 | 2 | 5.5 | 11 | |
| 1 | 2412 | 16 | 15.71 | 15.65 | 15.51 | 15.44 | |
| 6 | 2437 | 16 | 15.91 | 15.88 | 15.82 | 15.71 | |
| 11 | 2462 | 16 | 15.98 | 15.92 | 15.84 | 15.77 | |

| 802.11 g | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|----------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6 | 9 | 12 | 18 | 24 | 36 | 48 | 54 | |
| 1 | 2412 | 15 | 14.66 | 14.59 | 14.53 | 14.5 | 14.45 | 14.34 | 14.27 | 14.2 | |
| 6 | 2437 | 15 | 14.99 | 14.92 | 14.87 | 14.84 | 14.74 | 14.64 | 14.5 | 14.44 | |
| 11 | 2462 | 15 | 14.5 | 14.42 | 14.38 | 14.33 | 14.32 | 14.22 | 14.18 | 14.08 | |

| 802.11 n (20M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|----------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6.5 | 13 | 19.5 | 26 | 39 | 52 | 58.5 | 65 | |
| 1 | 2412 | 11.5 | 11.37 | 11.28 | 11.18 | 11.14 | 11.01 | 10.94 | 10.55 | 10.52 | |
| 6 | 2437 | 11.5 | 11.19 | 11.08 | 10.97 | 10.91 | 10.84 | 10.72 | 10.67 | 10.55 | |
| 11 | 2462 | 11.5 | 11.11 | 11.02 | 10.96 | 10.88 | 10.75 | 10.7 | 10.64 | 10.55 | |

| 802.11 n (40M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|----------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 13.5 | 27 | 40.5 | 54 | 81 | 108 | 121.5 | 135 | |
| 3 | 2422 | 11.5 | 11.25 | 11.18 | 11.09 | 11.01 | 10.95 | 10.87 | 10.82 | 10.75 | |
| 6 | 2437 | 11.5 | 11.24 | 11.1 | 11.01 | 10.88 | 10.84 | 10.74 | 10.66 | 10.62 | |
| 9 | 2452 | 11.5 | 11.33 | 11.21 | 11.18 | 11.08 | 10.99 | 10.87 | 10.82 | 10.77 | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

台灣檢驗科技股份有限公司

Member of SGS Group

| 802.11 n 5.2G (20M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6.5 | 13 | 19.5 | 26 | 39 | 52 | 58.5 | 65 | |
| 36 | 5180 | 13 | 12.75 | 12.72 | 12.69 | 12.65 | 12.63 | 12.59 | 12.57 | 12.51 | |
| 40 | 5200 | 13 | 12.75 | 12.65 | 12.57 | 12.51 | 12.45 | 12.41 | 12.35 | 12.26 | |
| 44 | 5220 | 13 | 12.69 | 12.55 | 12.5 | 12.42 | 12.37 | 12.31 | 12.24 | 12.17 | |
| 48 | 5240 | 13 | 12.77 | 12.71 | 12.64 | 12.53 | 12.41 | 12.32 | 12.28 | 12.14 | |

| 802.11 n 5.3G (20M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6.5 | 13 | 19.5 | 26 | 39 | 52 | 58.5 | 65 | |
| 52 | 5260 | 13 | 12.9 | 12.84 | 12.73 | 12.62 | 12.54 | 12.47 | 12.33 | 12.15 | |
| 56 | 5280 | 13 | 12.43 | 12.37 | 12.33 | 12.27 | 12.21 | 12.17 | 12.11 | 12.05 | |
| 60 | 5300 | 13 | 12.48 | 12.42 | 12.35 | 12.27 | 12.25 | 12.21 | 12.17 | 12.09 | |
| 64 | 5320 | 13 | 12.58 | 12.54 | 12.42 | 12.38 | 12.25 | 12.21 | 12.12 | 12.07 | |

| 802.11 n 5.6G (20M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6.5 | 13 | 19.5 | 26 | 39 | 52 | 58.5 | 65 | |
| 100 | 5500 | 13 | 12.72 | 12.63 | 12.58 | 12.44 | 12.39 | 12.24 | 12.17 | 12.02 | |
| 104 | 5520 | 13 | 12.74 | 12.67 | 12.53 | 12.45 | 12.42 | 12.35 | 12.33 | 12.25 | |
| 108 | 5540 | 13 | 12.85 | 12.74 | 12.62 | 12.44 | 12.38 | 12.22 | 12.17 | 12.05 | |
| 112 | 5560 | 13 | 12.77 | 12.69 | 12.61 | 12.56 | 12.44 | 12.37 | 12.24 | 12.15 | |
| 116 | 5580 | 13 | 12.81 | 12.75 | 12.64 | 12.51 | 12.47 | 12.35 | 12.28 | 12.18 | |
| 132 | 5660 | 13 | 12.99 | 12.87 | 12.77 | 12.54 | 12.31 | 12.17 | 12.08 | 12.01 | |
| 136 | 5680 | 13 | 12.97 | 12.85 | 12.74 | 12.62 | 12.51 | 12.42 | 12.38 | 12.21 | |
| 140 | 5700 | 13 | 12.74 | 12.67 | 12.52 | 12.42 | 12.34 | 12.25 | 12.12 | 12.07 | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

台灣檢驗科技股份有限公司

Member of SGS Group

| 802.11 n 5.8G (20M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6.5 | 13 | 19.5 | 26 | 39 | 52 | 58.5 | 65 | |
| 149 | 5745 | 13 | 12.79 | 12.62 | 12.54 | 12.41 | 12.37 | 12.21 | 12.19 | 12.11 | |
| 153 | 5765 | 13 | 12.87 | 12.81 | 12.74 | 12.61 | 12.52 | 12.47 | 12.4 | 12.25 | |
| 157 | 5785 | 13 | 12.98 | 12.87 | 12.81 | 12.75 | 12.64 | 12.57 | 12.51 | 12.42 | |
| 161 | 5805 | 13 | 12.7 | 12.64 | 12.55 | 12.43 | 12.38 | 12.31 | 12.25 | 12.17 | |
| 165 | 5825 | 13 | 12.81 | 12.74 | 12.62 | 12.54 | 12.41 | 12.37 | 12.32 | 12.24 | |

| 802.11 n 5.2G (40M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 13.5 | 27 | 40.5 | 54 | 81 | 108 | 121.5 | 135 | |
| 38 | 5190 | 10.5 | 10.27 | 10.22 | 10.16 | 10.09 | 10.01 | 9.92 | 9.83 | 9.71 | |
| 46 | 5230 | 12 | 11.98 | 11.91 | 11.82 | 11.74 | 11.63 | 11.54 | 11.41 | 11.35 | |

| 802.11 n 5.3G (40M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 13.5 | 27 | 40.5 | 54 | 81 | 108 | 121.5 | 135 | |
| 54 | 5270 | 12 | 11.86 | 11.79 | 11.72 | 11.63 | 11.53 | 11.44 | 11.35 | 11.21 | |
| 62 | 5310 | 11.5 | 11.41 | 11.32 | 11.25 | 11.11 | 11.02 | 10.93 | 10.81 | 10.76 | |

| 802.11 n 5.6G (40M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 13.5 | 27 | 40.5 | 54 | 81 | 108 | 121.5 | 135 | |
| 102 | 5510 | 11.5 | 11.26 | 11.18 | 11.1 | 11.02 | 10.96 | 10.81 | 10.73 | 10.62 | |
| 110 | 5550 | 12 | 11.84 | 11.74 | 11.63 | 11.59 | 11.51 | 11.43 | 11.36 | 11.21 | |
| 134 | 5670 | 12 | 11.98 | 11.88 | 11.82 | 11.77 | 11.69 | 11.54 | 11.45 | 11.36 | |

| 802.11 n 5.8G (40M) | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 13.5 | 27 | 40.5 | 54 | 81 | 108 | 121.5 | 135 | |
| 151 | 5755 | 12 | 11.69 | 11.62 | 11.57 | 11.45 | 11.36 | 11.29 | 11.21 | 11.15 | |
| 159 | 5795 | 12 | 11.94 | 11.86 | 11.72 | 11.65 | 11.59 | 11.46 | 11.35 | 11.28 | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| 802.11 a 5.2G | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6 | 9 | 12 | 18 | 24 | 36 | 48 | 54 | |
| 36 | 5180 | 14 | 13.76 | 13.69 | 13.65 | 13.52 | 13.51 | 13.44 | 13.33 | 13.29 | |
| 40 | 5200 | 14 | 13.66 | 13.61 | 13.54 | 13.47 | 13.42 | 13.35 | 13.27 | 13.21 | |
| 44 | 5220 | 14 | 13.3 | 13.21 | 12.19 | 13.17 | 13.15 | 13.1 | 13.07 | 13.01 | |
| 48 | 5240 | 14 | 13.77 | 13.71 | 13.64 | 13.55 | 13.48 | 13.28 | 13.1 | 13.05 | |

| 802.11 a 5.3G | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6 | 9 | 12 | 18 | 24 | 36 | 48 | 54 | |
| 52 | 5260 | 14 | 13.84 | 13.75 | 13.62 | 13.57 | 13.48 | 13.45 | 13.35 | 12.33 | |
| 56 | 5280 | 14 | 13.89 | 13.78 | 13.61 | 13.52 | 13.42 | 13.37 | 13.22 | 13.15 | |
| 60 | 5300 | 14 | 13.4 | 13.36 | 13.3 | 13.27 | 13.24 | 13.18 | 13.15 | 13.08 | |
| 64 | 5320 | 14 | 13.99 | 13.94 | 13.85 | 13.72 | 13.67 | 13.59 | 13.45 | 13.34 | |

| 802.11 a 5.6G | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6 | 9 | 12 | 18 | 24 | 36 | 48 | 54 | |
| 100 | 5500 | 14 | 13.71 | 13.65 | 13.54 | 13.48 | 13.31 | 13.29 | 13.22 | 13.17 | |
| 104 | 5520 | 14 | 13.64 | 13.57 | 13.42 | 13.34 | 13.28 | 13.21 | 13.14 | 13.05 | |
| 108 | 5540 | 14 | 13.72 | 13.64 | 13.53 | 13.42 | 13.38 | 13.25 | 13.14 | 13.03 | |
| 112 | 5560 | 14 | 13.76 | 13.71 | 13.65 | 13.54 | 13.41 | 13.32 | 13.25 | 13.16 | |
| 116 | 5580 | 14 | 13.44 | 13.35 | 13.28 | 13.22 | 13.17 | 13.14 | 13.11 | 13.03 | |
| 132 | 5660 | 14 | 13.99 | 13.92 | 13.84 | 13.74 | 13.61 | 13.53 | 13.47 | 13.36 | |
| 136 | 5680 | 14 | 13.97 | 13.74 | 13.62 | 13.51 | 13.41 | 13.32 | 13.17 | 13.05 | |
| 140 | 5700 | 14 | 13.68 | 13.57 | 13.51 | 13.42 | 13.32 | 13.25 | 13.14 | 13.11 | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

台灣檢驗科技股份有限公司

Member of SGS Group

| 802.11 a 5.8G | | Max. Rated Avg. Power + Max. Tolerance | Average Power Output (dBm) | | | | | | | | |
|---------------|-----------------|--|----------------------------|-------|-------|-------|-------|-------|-------|-------|--|
| CH | Frequency (MHz) | | Data Rate (Mbps) | | | | | | | | |
| | | | 6 | 9 | 12 | 18 | 24 | 36 | 48 | 54 | |
| 149 | 5745 | 14 | 13.7 | 13.62 | 13.54 | 13.42 | 13.33 | 13.28 | 13.22 | 13.14 | |
| 153 | 5765 | 14 | 13.78 | 13.71 | 13.64 | 13.51 | 13.35 | 13.27 | 13.17 | 13.08 | |
| 157 | 5785 | 14 | 13.77 | 13.64 | 13.57 | 13.42 | 13.39 | 13.24 | 13.23 | 13.18 | |
| 161 | 5805 | 14 | 13.88 | 13.72 | 13.65 | 13.55 | 13.48 | 13.35 | 13.31 | 13.24 | |
| 165 | 5825 | 14 | 13.62 | 13.57 | 13.52 | 13.47 | 13.36 | 13.28 | 13.18 | 13.01 | |

#. Bluetooth conducted power table:

| Frequency (MHz) | Peak (dBm) | | |
|-----------------|------------|---------|---------|
| | BR-DH5 | ER-2DH5 | ER-3DH5 |
| 2402 | 3.50 | 3.13 | 3.24 |
| 2441 | 5.38 | 4.74 | 4.80 |
| 2480 | 4.42 | 3.80 | 3.90 |

| Frequency (MHz) | Avg (dBm) | |
|-----------------|-----------|--|
| | BT4.0 | |
| 2402 | -6 | |
| 2442 | -3.86 | |
| 2480 | -5.21 | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

1.4 Test Environment

Ambient Temperature : $22 \pm 2^\circ \text{C}$

Tissue Simulating Liquid: $22 \pm 2^\circ \text{C}$

1.5 Operation Description

General:

1. The EUT is controlled by using a Radio Communication Tester (R&S CMU200 and Antrisu MT8820C), and the communication between the EUT and the tester is established by air link.
2. Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s). The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.
3. During the SAR testing, the DASY 5 system checks power drift by comparing the e-field strength of one specific location measured at the beginning with that measured at the end of the SAR testing.
4. Testing head SAR at lowest, middle and highest channel for all bands with Left Tilt /Left Cheek/Right Tilt/Right Cheek conditions.
5. Testing body-worn SAR by separating the EUT and the phantom **15mm** distance when performing GSM850/1900, WCDMA Band II/V, LTE Band 2/5/7 and WLAN 5G. (Both front side & back side)
6. Testing hotspot mode SAR by separating the EUT and the phantom **10mm** distance.
 - #. The SAR testing for portable devices with wireless router capability is referred as test guidance of **KDB 941225D06v02** (SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities).
 - #. The following procedures are applicable when the overall device length and width are $\geq 9 \text{ cm} \times 5 \text{ cm}$ respectively. A test separation of 10 mm is required. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25 mm from that surface or edge, for the data modes, wireless technologies and frequency bands supporting hotspot mode.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

For WLAN 2.4G (15mm separation): the testing device support mobile hotspot function, the separation distance is 10mm **{No need to perform body-worn SAR testing due to the hotspot mode(10mm separation distance) is more conservative than body-worn mode (15mm separation distance).}**

Test configurations:

- (1) Front side
- (2) Back side
- (3) Top side. (WWAN antenna to edge distance >25mm_ No SAR measurement is necessary for this configuration)
- (4) Bottom side. (WLAN antenna to edge distance >25mm_ No SAR measurement is necessary for this configuration)
- (5) Right side. (WLAN antenna to edge distance >25mm_ No SAR measurement is necessary for this configuration)
- (6) Left side.

7. According to **KDB447498D01v05r02** – The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, SAR evaluation is not required. (**Max power of Bluetooth = 5.38 dBm**)

When SAR evaluation is not required to be measured, per FCC KDB447498D01v05r02, the following equation must be used to estimate the 1g SAR for simultaneous transmission assessment involving that transmitter.

Estimated SAR = $[\sqrt{f(\text{GHz})}/7.5] \cdot [(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})]$

Estimated 10g SAR = $[\sqrt{f(\text{GHz})}/18.75] \cdot [(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})]$

| Mode | Frequency (MHz) | Maximum Power (dBm) | Separation Distance (Body) (mm) | Estimated SAR 1g (Body) (W/kg) |
|-----------|-----------------|---------------------|---------------------------------|--------------------------------|
| Bluetooth | 2441 | 5.38 | 15 | 0.048 |
| Bluetooth | 2441 | 5.38 | 10 | 0.072 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

8. The SAR measurement for EDGE mode is not required since the source-based time-averaged power for EDGE mode is lower than that for GPRS mode.
9. The SAR measurement is not required for HSPA since its maximum output power is less than $\frac{1}{4}$ dB higher than RMC without HSPA.
10. The SAR measurement is not required for HSPA+ since its maximum output power is less than $\frac{1}{4}$ dB higher than RMC without HSPA+.
11. LTE modes test according to **KDB 941225D05v02r03**.
 - a. Per Section 5.2.1, the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation.
 - Using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
 - When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.
 - When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
 - b. Per Section 5.2.2, the largest channel bandwidth and measure SAR for QPSK with 50% RB allocation
 - The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.
 - c. Per Section 5.2.3, the largest channel bandwidth and measure SAR for QPSK with 100% RB allocation
 - For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg.
 - Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
 - d. Per Section 5.2.4, Higher order modulations
 - For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

procedures in sections 5.2.1, 5.2.2 and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

e. Per Section 5.3, other channel bandwidth standalone SAR test requirements

- For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section 5.2 to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.
- The equivalent channel configuration for the RB allocation, RB offset and modulation etc. is determined for the smaller channel bandwidth according to the same number of RB allocated in the largest channel bandwidth.

12. The SAR measurement is not required for 802.11g/n since its maximum output power is less than 1/4 dB higher than 802.11b.

13. The SAR measurement is not required for 802.11n since its maximum output power is less than 1/4 dB higher than 802.11a.

14. The highest body SAR configuration is repeated with a headset (MH410C) attached.

15. According to KDB447498D01v05r02, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is ≤ 0.8 W/kg, when the transmission band is ≤ 100 MHz.

16. According to KDB447498D01v05r02, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is ≤ 0.6 W/kg, when the transmission band is between 100 MHz and 200MHz.

17. According to KDB447498 D01v05r02, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is ≤ 0.4 W/kg, when the transmission band is ≥ 200 MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

18. According to KDB865664D01v01r03, SAR measurement variability must be assessed for each frequency band. When the original highest measured SAR is ≥ 0.8 W/kg, repeated that measurement once. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司


t (886-2) 2299-3279

f (886-2) 2298-0488


www.tw.sgs.com

Member of SGS Group

1.6 Positioning Procedure



Phone position 1, "cheek" or "touch" position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.



Phone position 2, "tilted position." The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.

Cheek/Touch Position:

The handset was brought toward the mouth of the head phantom by pivoting against the ear reference point until any point of the mouthpiece or keypad touched the phantom.

Ear/Tilt Position:

With the phone aligned in the Cheek/Touch position, the handset was tilted away from

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

the mouth with respect to the test device reference point by 15 degrees.

1.7 Evaluation Procedures

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan.
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters).
3. The generation of a high-resolution mesh within the measured volume.
4. The interpolation of all measured values from the measurement grid to the high-resolution grid.
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface.
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2 dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

The maximum search is automatically performed after each area scan measurement. It

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7x7x7 scans.

The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found.

If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

1.8 Probe Calibration Procedures

For the calibration of E-field probes in lossy liquids, an electric field with an accurately known field strength must be produced within the measured liquid. For standardization purposes it would be desirable if all measurements which are necessary to assess the correct field strength would be traceable to standardized measurement procedures. In the following two different calibration techniques are summarized:

1.8.1 Transfer Calibration with Temperature Probes

In lossy liquids the specific absorption rate (SAR) is related both to the electric field (E) and the temperature gradient ($\delta T / \delta t$) in the liquid.

$$SAR = \frac{\sigma}{\rho} |E|^2 = c \frac{\delta T}{\delta t}$$

Whereby σ is the conductivity, ρ the density and c the heat capacity of the liquid.

Hence, the electric field in lossy liquid can be measured indirectly by measuring the temperature gradient in the liquid. Non-disturbing temperature probes (optical probes or thermistor probes with resistive lines) with high spatial resolution (<1-2 mm) and fast reaction time (<1 s) are available and can be easily calibrated with high precision [1]. The setup and the exciting source have no influence on the calibration; only the relative positioning uncertainties of the standard temperature probe and the E-field probe to be calibrated must be considered. However, several problems limit the available accuracy of probe calibrations with temperature probes:

- The temperature gradient is not directly measurable but must be evaluated from temperature measurements at different time steps. Special precaution is necessary to avoid measurement errors caused by temperature gradients due to energy equalizing effects or convection currents in the liquid. Such effects cannot be completely avoided, as the measured field itself destroys the thermal equilibrium in the liquid. With a careful setup these errors can be kept small.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

- The measured volume around the temperature probe is not well defined. It is difficult to calculate the energy transfer from a surrounding gradient temperature field into the probe. These effects must be considered, since temperature probes are calibrated in liquid with homogeneous temperatures. There is no traceable standard for temperature rise measurements.
- The calibration depends on the assessment of the specific density, the heat capacity and the conductivity of the medium. While the specific density and heat capacity can be measured accurately with standardized procedures (~ 2% for c ; much better for ρ), there is no standard for the measurement of the conductivity. Depending on the method and liquid, the error can well exceed $\pm 5\%$.
- Temperature rise measurements are not very sensitive and therefore are often performed at a higher power level than the E-field measurements. The nonlinearities in the system (e.g., power measurements, different components, etc.) must be considered.

Considering these problems, the possible accuracy of the calibration of E-field probes with temperature gradient measurements in a carefully designed setup is about $\pm 10\%$ (RSS) [2]. Recently, a setup which is a combination of the waveguide techniques and the thermal measurements was presented in [3]. The estimated uncertainty of the setup is $\pm 5\%$ (RSS) when the same liquid is used for the calibration and for actual measurements and $\pm 7\text{--}9\%$ (RSS) when not, which is in good agreement with the estimates given in [2].

1.8.2 Calibration with Analytical Fields

In this method a technical setup is used in which the field can be calculated analytically from measurements of other physical magnitudes (e.g., input power). This corresponds to the standard field method for probe calibration in air; however, there is no standard defined for fields in lossy liquids.

When using calculated fields in lossy liquids for probe calibration, several points must be considered in the assessment of the uncertainty:

- The setup must enable accurate determination of the incident power.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

- The accuracy of the calculated field strength will depend on the assessment of the dielectric parameters of the liquid.
- Due to the small wavelength in liquids with high permittivity, even small setups might be above the resonant cutoff frequencies. The field distribution in the setup must be carefully checked for conformity with the theoretical field distribution.

References

- [1] N. Kuster, Q. Balzano, and J.C. Lin, Eds., *Mobile Communications Safety*, Chapman & Hall, London, 1997.
- [2] K. Meier, M. Burkhardt, T. Schmid, and N. Kuster, "Broadband calibration of E-field probes in lossy media", *IEEE Transactions on Microwave Theory and Techniques*, vol. 44, no. 10, pp. 1954-1962, Oct. 1996.
- [3] K. Jokela, P. Hyysalo, and L. Puranen, "Calibration of specific absorption rate (SAR) probes in waveguide at 900 MHz", *IEEE Transactions on Instrumentation and Measurements*, vol. 47, no. 2, pp. 432-438, Apr. 1998.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

1.9 The SAR Measurement System

A block diagram of the SAR measurement system is given in Fig. a. This SAR measurement system uses a Computer-controlled 3-D stepper motor system (SPEAG DASY 5 professional system). Model EX3DV4 field probes are used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E_i|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-simulant.




Fig. a A block diagram of the SAR measurement system

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

The DASY 5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension is for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows7
- DASY 5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validate the proper functioning of the system.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

1.10 System Components

EX3DV4 E-Field Probe

| | | |
|---------------|--|---|
| Construction | Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |  |
| Calibration | Basic Broad Band Calibration in air Conversion Factors (CF) for HSL835/1900/2450/2600/5200/5300/5600/5800MHz Additional CF for other liquids and frequencies upon request | |
| Frequency | 10 MHz to > 6 GHz, Linearity: ± 0.6 dB | |
| Directivity | ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis) | |
| Dynamic Range | 10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g) | |
| Dimensions | Tip diameter: 2.5 mm | |
| Application | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

SAM PHANTOM V4.0C

| | |
|------------------|--|
| Construction: | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot. |
| Shell Thickness: | 2 ± 0.2 mm |
| Filling Volume: | Approx. 25 liters |
| Dimensions: | Height: 850 mm; Length: 1000 mm; Width: 500 mm |

**DEVICE HOLDER**

| | | |
|--------------|---|--|
| Construction | In combination with the Twin SAM Phantom V4.0/V4.0C or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom). |  Device Holder |
|--------------|---|--|

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

台灣檢驗科技股份有限公司

Member of SGS Group

1.11 SAR System Verification

The microwave circuit arrangement for system verification is sketched in Fig. b. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within +/- 10% (according to KDB865664D01v01r03) from the target SAR values.

These tests were done at 850/1900/2450/2600/5200/5300/5600/5800 MHz. The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed in the table 1. During the tests, the ambient temperature of the laboratory was 21.7°C, the relative humidity was 62% and the liquid depth above the ear reference points was above 15 cm ($\leq 3G$) or 10 cm ($> 3G$) in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig. b The block diagram of system verification

- A. Signal Generator
- B. Amplifier
- C. Power Sensor
- D. Dual Directional Coupling
- E. Reference Dipole Antenna



Photograph of the Dipole Antenna

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Validation Kit | S/N | Frequency (MHz) | | Target SAR (1g) (Pin=250mW) (mW/g) | Measured SAR (1g)(mW/g) | Deviation (%) | Measured Date |
|----------------|-------|-----------------|------|--|-------------------------|---------------|---------------|
| D835V2 | 4d063 | 835 | Head | 2.47 | 2.34 | 5.26% | Nov 13,2014 |
| D835V2 | 4d063 | 835 | Body | 2.41 | 2.42 | -0.41% | Nov 15,2014 |
| D1900V2 | 5d027 | 1900 | Head | 9.71 | 9.77 | -0.62% | Nov 14,2014 |
| D1900V2 | 5d027 | 1900 | Body | 10.1 | 9.81 | 2.87% | Nov 15,2014 |
| D835V2 | 4d063 | 835 | Head | 2.47 | 2.36 | 4.45% | Nov 18,2014 |
| D835V2 | 4d063 | 835 | Body | 2.41 | 2.37 | 1.66% | Nov 19,2014 |
| D1900V2 | 5d027 | 1900 | Head | 9.71 | 9.95 | -2.47% | Nov 20,2014 |
| D1900V2 | 5d027 | 1900 | Body | 10.1 | 10.1 | 0.00% | Nov 24,2014 |
| D2450V2 | 922 | 2450 | Head | 13.3 | 13.4 | -0.75% | Nov 23,2014 |
| D2450V2 | 922 | 2450 | Body | 12.9 | 13.1 | -1.55% | Nov 23,2014 |
| D2600V2 | 1005 | 2600 | Head | 14.7 | 15.1 | -2.72% | Nov 22,2014 |
| D2600V2 | 1005 | 2600 | Body | 14.3 | 14.7 | -2.80% | Nov 27,2014 |
| D5GHzV2 | 1104 | 5200 | Head | 8.27 | 8.37 | -1.21% | Nov 17,2014 |
| D5GHzV2 | 1104 | 5200 | Body | 7.64 | 7.59 | 0.65% | Nov 19,2014 |
| D5GHzV2 | 1104 | 5300 | Head | 8.51 | 8.32 | 2.23% | Nov 18,2014 |
| D5GHzV2 | 1104 | 5300 | Body | 7.77 | 7.83 | -0.77% | Nov 19,2014 |
| D5GHzV2 | 1104 | 5600 | Head | 8.62 | 8.74 | -1.39% | Nov 17,2014 |
| D5GHzV2 | 1104 | 5600 | Body | 8.25 | 8.4 | -1.82% | Nov 19,2014 |
| D5GHzV2 | 1104 | 5800 | Head | 8.09 | 8.11 | -0.25% | Nov 18,2014 |
| D5GHzV2 | 1104 | 5800 | Body | 7.6 | 7.72 | -1.58% | Nov 19,2014 |

Table 1. System validation (follow manufacture target value)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

1.12 Tissue Simulant Fluid for the Frequency Band

The dielectric properties for this Head-simulant fluid were measured by using the Agilent Model 85070E Dielectric Probe (rates frequency band 200 MHz to 20 GHz) in conjunction with Network Analyzer.

All dielectric parameters of tissue simulates were measured within 24 hours of SAR measurements. The depth of the tissue simulant in the flat section of the phantom was at least 15 cm ($\leq 3G$) or 10 cm ($> 3G$) during all tests. (Appendix Fig. 2)

| Measurement Date | Measured Frequency (MHz) | Tissue Type | Target Dielectric Constant, ϵ_r | Target Conductivity, σ (S/m) | Measured Dielectric Constant, ϵ_r | Measured Conductivity, σ (S/m) | % dev ϵ_r | % dev σ |
|------------------|--------------------------|-------------|--|-------------------------------------|--|---------------------------------------|--------------------|----------------|
| 2014/11/13 | 824.2 | Head | 41.56 | 0.90 | 41.28 | 0.87 | 0.65% | 3.00% |
| | 826.4 | | 41.55 | 0.90 | 41.26 | 0.87 | 0.69% | 2.78% |
| | 835 | | 41.50 | 0.90 | 41.15 | 0.88 | 0.85% | 1.89% |
| | 836.6 | | 41.50 | 0.90 | 41.12 | 0.89 | 0.91% | 1.88% |
| | 846.6 | | 41.50 | 0.91 | 41.00 | 0.89 | 1.21% | 1.97% |
| | 848.8 | | 41.50 | 0.92 | 40.97 | 0.90 | 1.28% | 2.08% |
| 2014/11/14 | 1850.2 | Body | 40.00 | 1.40 | 39.75 | 1.34 | 0.62% | 4.43% |
| | 1852.4 | | 40.00 | 1.40 | 39.74 | 1.34 | 0.65% | 4.29% |
| | 1880 | | 40.00 | 1.40 | 39.65 | 1.39 | 0.88% | 0.79% |
| | 1900 | | 40.00 | 1.40 | 39.57 | 1.39 | 1.08% | 0.79% |
| | 1907.6 | | 40.00 | 1.40 | 39.54 | 1.42 | 1.16% | -1.21% |
| | 1909.8 | | 40.00 | 1.40 | 39.53 | 1.40 | 1.18% | 0.07% |
| 2014/11/15 | 824.2 | Body | 55.24 | 0.97 | 52.97 | 1.00 | 4.11% | -3.30% |
| | 826.4 | | 55.23 | 0.97 | 52.95 | 1.00 | 4.13% | -3.51% |
| | 835 | | 55.20 | 0.97 | 52.88 | 1.01 | 4.21% | -4.33% |
| | 836.6 | | 55.20 | 0.97 | 52.86 | 1.01 | 4.23% | -4.32% |
| | 846.6 | | 55.16 | 0.98 | 52.77 | 1.03 | 4.34% | -4.17% |
| | 848.8 | | 55.16 | 0.99 | 52.75 | 1.03 | 4.36% | -4.05% |
| | 1850.2 | | 53.30 | 1.52 | 51.87 | 1.45 | 2.68% | 4.80% |
| | 1852.4 | | 53.30 | 1.52 | 51.86 | 1.45 | 2.70% | 4.67% |
| | 1880 | | 53.30 | 1.52 | 51.69 | 1.47 | 3.02% | 3.09% |
| | 1900 | | 53.30 | 1.52 | 51.60 | 1.50 | 3.20% | 1.51% |
| | 1907.6 | | 53.30 | 1.52 | 51.58 | 1.51 | 3.23% | 0.86% |
| | 1909.8 | | 53.30 | 1.52 | 51.58 | 1.51 | 3.23% | 0.72% |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| Measurement Date | Measured Frequency (MHz) | Tissue Type | Target Dielectric Constant, ϵ_r | Target Conductivity, σ (S/m) | Measured Dielectric Constant, ϵ_r | Measured Conductivity, σ (S/m) | % dev ϵ_r | % dev σ |
|------------------|--------------------------|-------------|--|-------------------------------------|--|---------------------------------------|--------------------|----------------|
| 2014/11/18 | 829 | Head | 41.53 | 0.90 | 40.24 | 0.88 | 3.12% | 2.67% |
| | 835 | | 41.50 | 0.90 | 40.23 | 0.88 | 3.06% | 2.33% |
| | 836.6 | | 41.50 | 0.90 | 40.23 | 0.88 | 3.06% | 2.55% |
| | 844 | | 41.50 | 0.91 | 40.17 | 0.88 | 3.21% | 2.86% |
| 2014/11/19 | 829 | Body | 55.22 | 0.97 | 53.75 | 0.98 | 2.66% | -0.72% |
| | 835 | | 55.20 | 0.97 | 53.66 | 0.98 | 2.78% | -1.13% |
| | 836.6 | | 55.20 | 0.97 | 53.65 | 0.98 | 2.81% | -1.23% |
| | 844 | | 55.17 | 0.98 | 53.57 | 0.99 | 2.90% | -1.02% |
| 2014/11/20 | 1860 | Head | 40.00 | 1.40 | 39.41 | 1.42 | 1.49% | -1.36% |
| | 1880 | | 40.00 | 1.40 | 39.35 | 1.42 | 1.63% | -1.71% |
| | 1900 | | 40.00 | 1.40 | 39.26 | 1.43 | 1.86% | -2.29% |
| 2014/11/24 | 1860 | Body | 53.30 | 1.52 | 54.41 | 1.52 | -2.08% | -0.07% |
| | 1880 | | 53.30 | 1.52 | 52.24 | 1.54 | 1.98% | -1.12% |
| | 1900 | | 53.30 | 1.52 | 54.07 | 1.55 | -1.44% | -2.11% |
| 2014/11/22 | 2510 | Head | 39.12 | 1.87 | 40.77 | 1.90 | -4.21% | -1.88% |
| | 2535 | | 39.09 | 1.89 | 40.63 | 1.93 | -3.93% | -1.80% |
| | 2560 | | 39.06 | 1.92 | 40.49 | 1.95 | -3.65% | -1.46% |
| | 2600 | | 39.01 | 1.96 | 40.38 | 1.98 | -3.52% | -0.87% |
| 2014/11/27 | 2510 | Body | 52.62 | 2.04 | 53.13 | 2.00 | -0.96% | 1.52% |
| | 2535 | | 52.59 | 2.07 | 52.99 | 2.02 | -0.76% | 2.51% |
| | 2560 | | 52.56 | 2.11 | 52.81 | 2.04 | -0.48% | 2.94% |
| | 2600 | | 52.51 | 2.16 | 52.598 | 2.071 | -0.17% | 4.25% |
| 2014/11/23 | 2412 | Head | 39.27 | 1.77 | 39.30 | 1.78 | -0.08% | -0.72% |
| | 2437 | | 39.22 | 1.79 | 39.23 | 1.81 | -0.02% | -1.09% |
| | 2450 | | 39.20 | 1.80 | 39.19 | 1.82 | 0.04% | -1.28% |
| | 2462 | | 39.18 | 1.81 | 39.12 | 1.84 | 0.17% | -1.26% |
| | 2412 | Body | 52.75 | 1.91 | 50.24 | 1.99 | 4.77% | -4.09% |
| | 2437 | | 52.72 | 1.94 | 50.14 | 2.03 | 4.89% | -4.62% |
| | 2450 | | 52.70 | 1.95 | 50.10 | 2.05 | 4.93% | -4.87% |
| | 2462 | | 52.68 | 1.97 | 50.06 | 2.06 | 4.98% | -4.88% |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

| Measurement Date | Measured Frequency (MHz) | Tissue Type | Target Dielectric Constant, ϵ_r | Target Conductivity, σ (S/m) | Measured Dielectric Constant, ϵ_r | Measured Conductivity, σ (S/m) | % dev ϵ_r | % dev σ |
|------------------|--------------------------|-------------|--|-------------------------------------|--|---------------------------------------|--------------------|----------------|
| 2014/11/17 | 5180 | Head | 36.01 | 4.63 | 36.13 | 4.59 | -0.33% | 0.98% |
| | 5200 | | 35.99 | 4.66 | 36.07 | 4.62 | -0.25% | 0.79% |
| | 5240 | | 35.94 | 4.70 | 36.07 | 4.67 | -0.37% | 0.60% |
| | 5280 | | 35.89 | 4.74 | 35.89 | 4.71 | 0.01% | 0.68% |
| | 5300 | | 35.87 | 4.76 | 35.83 | 4.73 | 0.12% | 0.56% |
| | 5320 | | 35.85 | 4.78 | 35.80 | 4.77 | 0.14% | 0.23% |
| | 5540 | | 35.60 | 5.00 | 35.29 | 5.02 | 0.87% | -0.27% |
| | 5600 | | 35.53 | 5.07 | 35.14 | 5.08 | 1.09% | -0.32% |
| | 5660 | | 35.46 | 5.13 | 35.03 | 5.15 | 1.21% | -0.52% |
| | 5680 | | 35.44 | 5.15 | 34.98 | 5.18 | 1.28% | -0.68% |
| | 5765 | | 35.34 | 5.23 | 34.76 | 5.28 | 1.65% | -0.80% |
| | 5785 | | 35.32 | 5.25 | 34.72 | 5.31 | 1.68% | -0.96% |
| 2014/11/18 | 5800 | Body | 35.30 | 5.27 | 34.70 | 5.32 | 1.70% | -0.85% |
| | 5805 | | 35.29 | 5.28 | 34.68 | 5.32 | 1.75% | -0.87% |
| | 5180 | | 49.04 | 5.28 | 48.66 | 5.39 | 0.78% | -2.22% |
| | 5200 | | 49.01 | 5.30 | 48.60 | 5.41 | 0.84% | -2.03% |
| | 5240 | | 48.96 | 5.35 | 48.35 | 5.47 | 1.25% | -2.39% |
| | 5280 | | 48.91 | 5.39 | 48.36 | 5.56 | 1.11% | -3.03% |
| | 5300 | | 48.88 | 5.42 | 48.32 | 5.57 | 1.14% | -2.86% |
| | 5320 | | 48.85 | 5.44 | 48.20 | 5.59 | 1.34% | -2.77% |
| | 5540 | | 48.55 | 5.70 | 47.54 | 5.95 | 2.09% | -4.36% |
| | 5600 | | 48.47 | 5.77 | 47.50 | 6.04 | 2.00% | -4.76% |
| | 5660 | | 48.39 | 5.84 | 47.18 | 6.06 | 2.50% | -3.80% |
| | 5680 | | 48.36 | 5.86 | 47.19 | 6.04 | 2.43% | -3.11% |
| | 5765 | | 48.25 | 5.96 | 46.91 | 6.16 | 2.78% | -3.39% |
| | 5785 | | 48.22 | 5.98 | 46.91 | 6.18 | 2.72% | -3.37% |
| 2014/11/19 | 5800 | Body | 48.20 | 6.00 | 46.94 | 6.20 | 2.61% | -3.33% |
| | 5805 | | 48.19 | 6.01 | 46.94 | 6.21 | 2.61% | -3.45% |

Table 2. Dielectric Parameters of Tissue Simulant Fluid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

The composition of the tissue simulating liquid:

| Frequency (MHz) | Mode | Ingredient | | | | | | Total amount |
|--------------------|------|------------|----------|---------|------------------|-----------|-------|-----------------|
| | | DGMBE | Water | Salt | Preventol D-7 | Cellulose | Sugar | |
| 850 | Head | — | 532.98 g | 18.3 g | 2.4 g | 3.2 g | 766 g | 1.3L(Kg) |
| | Body | — | 631.68 g | 11.72 g | 1.2 g | — | 600 g | 1.0L(Kg) |
| 1900 | Head | 444.52 g | 552.42 g | 3.06 g | — | — | — | 1.0L(Kg) |
| | Body | 300.67 g | 716.56 g | 4.0 g | — | — | — | 1.0L(Kg) |
| 2450 | Head | 550ml | 450ml | — | — | — | — | 1.0L(Kg) |
| | Body | 301.7ml | 698.3ml | — | — | — | — | 1.0L(Kg) |
| 2600 | Head | 550ml | 450ml | — | — | — | — | 1.0L(Kg) |
| | Body | 301.7ml | 698.3ml | — | — | — | — | 1.0L(Kg) |

Simulating Liquids for 5 GHz, Manufactured by SPEAG:

| Ingredients | Water | Esters, Emulsifiers, Inhibitors | Sodium and Salt |
|---------------|-------|---------------------------------|-----------------|
| (% by weight) | 60-80 | 20-40 | 0-1.5 |

Table 3. Recipes for tissue simulating liquid

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

1.13 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1-1992, Copyright 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.

These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter.

Measurements and calculations to demonstrate compliance with MPE field strength or power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

(1) Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over a 10 grams of tissue (defined as a tissue volume in the shape of a cube).

Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

or by specific training or education through appropriate means, such as an RF safety program in a work environment.

(2) Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube).

Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube).

General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure.

Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.(Table .6)

| Human Exposure | Uncontrolled Environment General Population | Controlled Environment Occupational |
|--|--|--|
| Spatial Peak SAR (Brain) | 1.60 m W/g | 8.00 m W/g |
| Spatial Average SAR (Whole Body) | 0.08 m W/g | 0.40 m W/g |
| Spatial Peak SAR (Hands/Feet/Ankle/Wrist) | 4.00 m W/g | 20.00 m W/g |

Table 4. RF exposure limits

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

2. Summary of Results

GSM 850 MHz

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-----------------------------|-------------|---------------|-----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| GSM850 (GMSK) (Head) | Re Cheek | - | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.420 | 0.420 | - |
| | Re Tilt | - | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.220 | 0.220 | - |
| | Le Cheek | - | 128 | 824.2 | 33.50 | 33.20 | 7.15% | 0.383 | 0.410 | - |
| | Le Cheek | - | 190 | 836.6 | 33.50 | 33.40 | 2.33% | 0.441 | 0.451 | - |
| | Le Cheek | - | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.504 | 0.504 | 87 |
| | Le Tilt | - | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.225 | 0.225 | - |
| GSM850 (GMSK) (Speech mode) | Front side | 15mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.262 | 0.262 | - |
| | Back side | 15mm | 128 | 824.2 | 33.50 | 33.20 | 7.15% | 0.230 | 0.246 | - |
| | Back side | 15mm | 190 | 836.6 | 33.50 | 33.40 | 2.33% | 0.292 | 0.299 | - |
| | Back side | 15mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.353 | 0.353 | 88 |
| GPRS850 (GMSK) (Hotspot) | Front side | 10mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.512 | 0.512 | - |
| | Back side | 10mm | 128 | 824.2 | 33.50 | 33.20 | 7.15% | 0.461 | 0.494 | - |
| | Back side | 10mm | 190 | 836.6 | 33.50 | 33.40 | 2.33% | 0.580 | 0.594 | - |
| | Back side | 10mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.690 | 0.690 | 89 |
| | Bottom side | 10mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.209 | 0.209 | - |
| | Right side | 10mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.216 | 0.216 | - |
| | Left side | 10mm | 251 | 848.8 | 33.50 | 33.50 | 0.00% | 0.463 | 0.463 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

GSM 1900 MHz

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|------------------------------|-------------|---------------|-----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| GSM1900 (GMSK) (Head) | Re Cheek | - | 512 | 1850.2 | 30.50 | 30.00 | 12.20% | 0.140 | 0.157 | - |
| | Re Cheek | - | 661 | 1880 | 30.50 | 30.00 | 12.20% | 0.132 | 0.148 | - |
| | Re Cheek | - | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.187 | 0.191 | 90 |
| | Re Tilt | - | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.072 | 0.074 | - |
| | Le Cheek | - | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.163 | 0.167 | - |
| | Le Tilt | - | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.069 | 0.071 | - |
| GSM1900 (GMSK) (Speech mode) | Front side | 15mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.222 | 0.227 | - |
| | Back side | 15mm | 512 | 1850.2 | 30.50 | 30.00 | 12.20% | 0.265 | 0.297 | - |
| | Back side | 15mm | 661 | 1880 | 30.50 | 30.00 | 12.20% | 0.283 | 0.318 | - |
| | Back side | 15mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.312 | 0.319 | 91 |
| GPRS1900 (GMSK) (Hotspot) | Front side | 10mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.422 | 0.432 | - |
| | Back side | 10mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.582 | 0.596 | - |
| | Bottom side | 10mm | 512 | 1850.2 | 30.50 | 30.00 | 12.20% | 0.453 | 0.508 | - |
| | Bottom side | 10mm | 661 | 1880 | 30.50 | 30.00 | 12.20% | 0.511 | 0.573 | - |
| | Bottom side | 10mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.616 | 0.630 | 92 |
| | Right side | 10mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.117 | 0.120 | - |
| | Left side | 10mm | 810 | 1909.8 | 30.50 | 30.40 | 2.33% | 0.107 | 0.109 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

WCDMA Band II

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-----------------------------|--------------|---------------|------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| R99 (Head) | Re Cheek | - | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.237 | 0.242 | - |
| | Re Tilt | - | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.110 | 0.112 | - |
| | Le Cheek | - | 9262 | 1852.4 | 24.50 | 24.23 | 6.41% | 0.182 | 0.194 | - |
| | Le Cheek | - | 9400 | 1880 | 24.50 | 24.22 | 6.66% | 0.219 | 0.234 | - |
| | Le Cheek | - | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.282 | 0.288 | 93 |
| | Le Tilt | - | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.118 | 0.120 | - |
| R99 (Body-worn speech mode) | Front side | 15mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.407 | 0.416 | - |
| | Back side | 15mm | 9262 | 1852.4 | 24.50 | 24.23 | 6.41% | 0.552 | 0.587 | - |
| | Back side | 15mm | 9400 | 1880 | 24.50 | 24.22 | 6.66% | 0.592 | 0.631 | 94 |
| | Back side | 15mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.607 | 0.620 | - |
| R99 (Hotspot) | Front side | 10mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.743 | 0.759 | - |
| | Back side | 10mm | 9262 | 1852.4 | 24.50 | 24.23 | 6.41% | 0.892 | 0.949 | - |
| | Back side | 10mm | 9400 | 1880 | 24.50 | 24.22 | 6.66% | 0.928 | 0.990 | - |
| | Back side | 10mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 1.040 | 1.062 | - |
| | Bottom side | 10mm | 9262 | 1852.4 | 24.50 | 24.23 | 6.41% | 0.908 | 0.966 | - |
| | Bottom side | 10mm | 9400 | 1880 | 24.50 | 24.22 | 6.66% | 0.975 | 1.040 | - |
| | Bottom side | 10mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 1.120 | 1.143 | 95 |
| | Bottom side* | 10mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 1.110 | 1.133 | - |
| | Right | 10mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.211 | 0.215 | - |
| | Left | 10mm | 9538 | 1907.6 | 24.50 | 24.41 | 2.09% | 0.186 | 0.190 | - |

* - repeated at the highest SAR measurement according to the KDB 865664 D01v01r03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

WCDMA Band V

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-----------------------------|-------------|---------------|------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| R99 (Head) | Re Cheek | - | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.360 | 0.361 | - |
| | Re Tilt | - | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.208 | 0.208 | - |
| | Le Cheek | - | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.435 | 0.436 | - |
| | Le Cheek | - | 4183 | 836.6 | 24.50 | 24.48 | 0.46% | 0.420 | 0.422 | - |
| | Le Cheek | - | 4233 | 846.6 | 24.50 | 24.40 | 2.33% | 0.451 | 0.462 | 96 |
| | Le Tilt | - | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.220 | 0.221 | - |
| R99 (Body-worn speech mode) | Front side | 15mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.201 | 0.201 | - |
| | Back side | 15mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.259 | 0.260 | - |
| | Back side | 15mm | 4183 | 836.6 | 24.50 | 24.48 | 0.46% | 0.246 | 0.247 | - |
| | Back side | 15mm | 4123 | 846.6 | 24.50 | 24.40 | 2.33% | 0.316 | 0.323 | 97 |
| R99 (Hotspot) | Front side | 10mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.528 | 0.529 | - |
| | Back side | 10mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.788 | 0.790 | 98 |
| | Back side | 10mm | 4183 | 836.6 | 24.50 | 24.48 | 0.46% | 0.742 | 0.745 | - |
| | Back side | 10mm | 4233 | 846.6 | 24.50 | 24.40 | 2.33% | 0.757 | 0.775 | - |
| | Bottom side | 10mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.191 | 0.191 | - |
| | Right side | 10mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.232 | 0.233 | - |
| | Left side | 10mm | 4132 | 826.4 | 24.50 | 24.49 | 0.23% | 0.466 | 0.467 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

LTE FDD Band II

| Mode | Bandwidth (MHz) | Modulation | RB Size | RB Offset | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-------------------|-----------------|------------|---------|-----------|------------|---------------|-------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | | | | | Measured | Reported | |
| Band2 (Head) | 20Mhz | QPSK | 1 | 99 | Re Cheek | - | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.403 | 0.415 | - |
| | | | | | Re Tilt | - | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.190 | 0.196 | - |
| | | | | | Le Cheek | - | 18700 | 1860 | 24.5 | 24.16 | 8.14% | 0.326 | 0.353 | - |
| | | | | | Le Cheek | - | 18900 | 1880 | 24.5 | 24.17 | 7.89% | 0.385 | 0.415 | - |
| | | | | | Le Cheek | - | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.446 | 0.460 | 99 |
| | | | | | Le Tilt | - | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.158 | 0.163 | - |
| | | | 50 | 50 | Re Cheek | - | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.320 | 0.366 | - |
| | | | | | Re Tilt | - | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.153 | 0.175 | - |
| | | | | | Le Cheek | - | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.356 | 0.407 | - |
| | | | | | Le Tilt | - | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.129 | 0.147 | - |
| | | | 100 | - | Re Cheek | - | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.309 | 0.357 | - |
| | | | | | Re Tilt | - | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.145 | 0.168 | - |
| | | | | | Le Cheek | - | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.334 | 0.386 | - |
| | | | | | Le Tilt | - | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.123 | 0.142 | - |
| Band2 (Body-worn) | 20Mhz | QPSK | 1 | 99 | Front side | 15 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.549 | 0.566 | - |
| | | | | | Back side | 15 | 19100 | 1900 | 24.5 | 24.16 | 8.14% | 0.589 | 0.637 | - |
| | | | | | Back side | 15 | 19100 | 1900 | 24.5 | 24.17 | 7.89% | 0.613 | 0.661 | - |
| | | | | | Back side | 15 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.682 | 0.703 | 100 |
| | | | 50 | 50 | Front side | 15 | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.455 | 0.520 | - |
| | | | | | Back side | 15 | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.549 | 0.627 | - |
| | | | 100 | - | Front side | 15 | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.440 | 0.509 | - |
| | | | | | Back side | 15 | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.536 | 0.620 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| Mode | Bandwidth (MHz) | Modulation | RB Size | RB Offset | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-----------------|-----------------|------------|---------|-----------|-------------------------|---------------|-------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | | | | | Measured | Reported | |
| Band2 (Hotspot) | 20Mhz | QPSK | 1 | 99 | Front side | 10 | 18700 | 1860 | 24.5 | 24.16 | 8.14% | 0.759 | 0.821 | - |
| | | | | | Front side | 10 | 18900 | 1880 | 24.5 | 24.17 | 7.89% | 0.828 | 0.893 | - |
| | | | | | Front side | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.915 | 0.943 | - |
| | | | | | Back side | 10 | 18700 | 1860 | 24.5 | 24.16 | 8.14% | 1.170 | 1.265 | - |
| | | | | | Back side | 10 | 18900 | 1880 | 24.5 | 24.17 | 7.89% | 1.080 | 1.165 | - |
| | | | | | Back side | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 1.240 | 1.278 | - |
| | | | | | Back side* | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 1.260 | 1.298 | 101 |
| | | | | | Back side -with headset | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.962 | 0.991 | - |
| | | | | | Bottom | 10 | 18700 | 1860 | 24.5 | 24.16 | 8.14% | 0.995 | 1.076 | - |
| | | | 50 | 50 | Bottom | 10 | 18900 | 1880 | 24.5 | 24.17 | 7.89% | 1.070 | 1.154 | - |
| | | | | | Bottom | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 1.080 | 1.113 | - |
| | | | | | Right side | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.207 | 0.213 | - |
| | | | | | Left side | 10 | 19100 | 1900 | 24.5 | 24.37 | 3.04% | 0.225 | 0.232 | - |
| | | | | | Front side | 10 | 18700 | 1860 | 24 | 23.17 | 21.06% | 0.631 | 0.764 | - |
| | | | | | Front side | 10 | 18900 | 1880 | 24 | 23.31 | 17.22% | 0.685 | 0.803 | - |
| | | | | | Front side | 10 | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.855 | 0.977 | - |
| | | | | | Back side | 10 | 18700 | 1860 | 24 | 23.17 | 21.06% | 0.897 | 1.086 | - |
| | | | | | Back side | 10 | 18900 | 1880 | 24 | 23.31 | 17.22% | 0.943 | 1.105 | - |
| | | | | | Back side | 10 | 19100 | 1900 | 24 | 23.42 | 14.29% | 1.030 | 1.177 | - |
| | | | 100 | - | Bottom | 10 | 18700 | 1860 | 24 | 23.17 | 21.06% | 0.810 | 0.981 | - |
| | | | | | Bottom | 10 | 18900 | 1880 | 24 | 23.31 | 17.22% | 0.869 | 1.019 | - |
| | | | | | Bottom | 10 | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.707 | 0.808 | - |
| | | | | | Right side | 10 | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.190 | 0.217 | - |
| | | | | | Left side | 10 | 19100 | 1900 | 24 | 23.42 | 14.29% | 0.183 | 0.209 | - |
| | | | | | Front side | 10 | 18700 | 1860 | 24 | 23.12 | 22.46% | 0.612 | 0.749 | - |
| | | | | | Front side | 10 | 18900 | 1880 | 24 | 23.14 | 21.90% | 0.668 | 0.814 | - |
| | | | | | Front side | 10 | 19100 | 1900 | 24 | 23.37 | 15.61% | 0.798 | 0.923 | - |
| | | | | | Back side | 10 | 18700 | 1860 | 24 | 23.12 | 22.46% | 0.902 | 1.105 | - |
| | | | | | Back side | 10 | 18900 | 1880 | 24 | 23.14 | 21.90% | 0.927 | 1.130 | - |

* - repeated at the highest SAR measurement according to the FCC KDB 865664 D01v01r03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

LTE FDD Band V

| Mode | Bandwidth (MHz) | Modulation | RB Size | RB Offset | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-------------------|-----------------|------------|---------|-----------|------------|---------------|-------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | | | | | Measured | Reported | |
| Band5 (Head) | 10Mhz | QPSK | 1 | 49 | Re Cheek | - | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.357 | 0.364 | - |
| | | | | | Re Tilt | - | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.255 | 0.260 | - |
| | | | | 0 | Le Cheek | - | 20450 | 829 | 24.5 | 24.36 | 3.28% | 0.439 | 0.453 | 102 |
| | | | | 49 | Le Cheek | - | 20525 | 836.5 | 24.5 | 24.37 | 3.04% | 0.412 | 0.425 | - |
| | | | | | Le Cheek | - | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.421 | 0.430 | - |
| | | | | | Le Tilt | - | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.256 | 0.261 | - |
| | | | 25 | 25 | Re Cheek | - | 20600 | 844 | 24 | 23.51 | 11.94% | 0.295 | 0.330 | - |
| | | | | | Re Tilt | - | 20600 | 844 | 24 | 23.51 | 11.94% | 0.202 | 0.226 | - |
| | | | | | Le Cheek | - | 20600 | 844 | 24 | 23.51 | 11.94% | 0.342 | 0.383 | - |
| | | | | | Le Tilt | - | 20600 | 844 | 24 | 23.51 | 11.94% | 0.205 | 0.229 | - |
| | 20Mhz | QPSK | 50 | - | Re Cheek | - | 20450 | 829 | 24 | 23.51 | 11.94% | 0.291 | 0.326 | - |
| | | | | | Re Tilt | - | 20450 | 829 | 24 | 23.51 | 11.94% | 0.191 | 0.214 | - |
| | | | | | Le Cheek | - | 20450 | 829 | 24 | 23.51 | 11.94% | 0.347 | 0.388 | - |
| | | | | | Le Tilt | - | 20450 | 829 | 24 | 23.51 | 11.94% | 0.195 | 0.218 | - |
| Band5 (Body-worn) | 20Mhz | QPSK | 1 | 49 | Front side | 15 | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.330 | 0.337 | - |
| | | | | | Back side | 15 | 20450 | 829 | 24.5 | 24.36 | 3.28% | 0.374 | 0.386 | - |
| | | | | | Back side | 15 | 20525 | 836.5 | 24.5 | 24.37 | 3.04% | 0.407 | 0.419 | - |
| | | | | | Back side | 15 | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.415 | 0.424 | 103 |
| | | | 25 | 25 | Front side | 15 | 20600 | 844 | 24 | 23.51 | 11.94% | 0.262 | 0.293 | - |
| | | | | | Back side | 15 | 20600 | 844 | 24 | 23.51 | 11.94% | 0.292 | 0.327 | - |
| | | | 50 | - | Front side | 15 | 20450 | 829 | 24 | 23.51 | 11.94% | 0.219 | 0.245 | - |
| | | | | | Back side | 15 | 20450 | 829 | 24 | 23.51 | 11.94% | 0.238 | 0.266 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Mode | Bandwidth (MHz) | Modulation | RB Size | RB Offset | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-----------------|-----------------|------------|---------|-----------|------------|---------------|-------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | | | | | Measured | Reported | |
| Band5 (Hotspot) | 10Mhz | QPSK | 1 | 49 | Front side | 10mm | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.374 | 0.382 | - |
| | | | | | Back side | 10mm | 20450 | 829 | 24.5 | 24.36 | 3.28% | 0.470 | 0.485 | - |
| | | | | | Back side | 10mm | 20525 | 836.5 | 24.5 | 24.37 | 3.04% | 0.523 | 0.539 | - |
| | | | | | Back side | 10mm | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.534 | 0.545 | 104 |
| | | | | 49 | Bottom | 10mm | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.203 | 0.207 | - |
| | | | | | Right side | 10mm | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.270 | 0.276 | - |
| | | | | | Left side | 10mm | 20600 | 844 | 24.5 | 24.41 | 2.09% | 0.508 | 0.519 | - |
| | | | 25 | 25 | Front side | 10mm | 20450 | 844 | 24 | 23.51 | 11.94% | 0.302 | 0.338 | - |
| | | | | | Back side | 10mm | 20600 | 844 | 24 | 23.51 | 11.94% | 0.455 | 0.509 | - |
| | | | | | Bottom | 10mm | 20600 | 844 | 24 | 23.51 | 11.94% | 0.143 | 0.160 | - |
| | | | | | Right side | 10mm | 20450 | 844 | 24 | 23.51 | 11.94% | 0.210 | 0.235 | - |
| | | | | | Left side | 10mm | 20450 | 844 | 24 | 23.51 | 11.94% | 0.409 | 0.458 | - |
| | | | 50 | - | Front side | 10mm | 20450 | 829 | 24 | 23.51 | 11.94% | 0.301 | 0.337 | - |
| | | | | | Back side | 10mm | 20450 | 829 | 24 | 23.51 | 11.94% | 0.427 | 0.478 | - |
| | | | | | Bottom | 10mm | 20450 | 829 | 24 | 23.51 | 11.94% | 0.162 | 0.181 | - |
| | | | | | Right side | 10mm | 20450 | 844 | 24 | 23.51 | 11.94% | 0.149 | 0.167 | - |
| | | | | | Left side | 10mm | 20450 | 829 | 24 | 23.51 | 11.94% | 0.350 | 0.392 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

LTE FDD Band VII

| Mode | Bandwidth (MHz) | Modulation | RB Size | RB Offset | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-------------------|-----------------|------------|---------|-----------|------------|---------------|-------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | | | | | Measured | Reported | |
| Band7 (Head) | 20Mhz | QPSK | 1 | 99 | Re Cheek | - | 20850 | 2510 | 22.3 | 22.17 | 3.04% | 0.168 | 0.173 | - |
| | | | | | Re Cheek | - | 21100 | 2535 | 22.3 | 22.24 | 1.39% | 0.210 | 0.213 | - |
| | | | | | Re Cheek | - | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.247 | 0.249 | 105 |
| | | | | | Re Tilt | - | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.038 | 0.038 | - |
| | | | | | Le Cheek | - | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.209 | 0.211 | - |
| | | | | | Le Tilt | - | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.055 | 0.056 | - |
| | | | 50 | 50 | Re Cheek | - | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.190 | 0.220 | - |
| | | | | | Re Tilt | - | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.047 | 0.054 | - |
| | | | | | Le Cheek | - | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.140 | 0.162 | - |
| | | | | | Le Tilt | - | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.044 | 0.051 | - |
| | | | 100 | - | Re Cheek | - | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.183 | 0.215 | - |
| | | | | | Re Tilt | - | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.046 | 0.054 | - |
| | | | | | Le Cheek | - | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.136 | 0.160 | - |
| | | | | | Le Tilt | - | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.042 | 0.049 | - |
| Band7 (Body-worn) | 20Mhz | QPSK | 1 | 99 | Front side | 15 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.413 | 0.417 | - |
| | | | | | Back side | 15 | 20850 | 2510 | 22.3 | 22.17 | 3.04% | 0.734 | 0.756 | - |
| | | | | | Back side | 15 | 21100 | 2535 | 22.3 | 22.24 | 1.39% | 0.803 | 0.814 | 106 |
| | | | | | Back side | 15 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.748 | 0.755 | - |
| | | | 50 | 50 | Front side | 15 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.309 | 0.357 | - |
| | | | | | Back side | 15 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.596 | 0.689 | - |
| | | | 100 | - | Front side | 15 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.294 | 0.345 | - |
| | | | | | Back side | 15 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.594 | 0.698 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

| Mode | Bandwidth (MHz) | Modulation | RB Size | RB Offset | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|-----------------|-----------------|------------|---------|-----------|------------|---------------|-------|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | | | | | Measured | Reported | |
| Band7 (Hotspot) | 20Mhz | QPSK | 1 | 99 | Front side | 10 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.563 | 0.568 | - |
| | | | | | Back side | 10 | 20850 | 2510 | 22.3 | 22.17 | 3.04% | 1.040 | 1.072 | - |
| | | | | | Back side | 10 | 21100 | 2535 | 22.3 | 22.24 | 1.39% | 1.100 | 1.115 | - |
| | | | | | Back side | 10 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 1.160 | 1.171 | 107 |
| | | | | | Back side* | 10 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 1.110 | 1.120 | - |
| | | | | | Bottom | 10 | 20850 | 2510 | 22.3 | 22.17 | 3.04% | 0.943 | 0.972 | - |
| | | | | | Bottom | 10 | 21100 | 2535 | 22.3 | 22.24 | 1.39% | 1.050 | 1.065 | - |
| | | | | | Bottom | 10 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 1.100 | 1.110 | - |
| | | | | | Right side | 10 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.106 | 0.107 | - |
| | | | 50 | 50 | Left side | 10 | 21350 | 2560 | 22.3 | 22.26 | 0.93% | 0.096 | 0.097 | - |
| | | | | | Front side | 10 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.460 | 0.532 | - |
| | | | | | Back side | 10 | 20850 | 2510 | 22 | 21.25 | 18.85% | 0.842 | 1.001 | - |
| | | | | | Back side | 10 | 21100 | 2535 | 22 | 21.32 | 16.95% | 0.907 | 1.061 | - |
| | | | | | Back side | 10 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.940 | 1.087 | - |
| | | | | | Bottom | 10 | 20850 | 2510 | 22 | 21.25 | 18.85% | 0.754 | 0.896 | - |
| | | | | | Bottom | 10 | 21100 | 2535 | 22 | 21.32 | 16.95% | 0.830 | 0.971 | - |
| | | | | | Bottom | 10 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.872 | 1.008 | - |
| | | | | | Right side | 10 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.084 | 0.097 | - |
| | | | 100 | - | Left side | 10 | 21350 | 2560 | 22 | 21.37 | 15.61% | 0.078 | 0.090 | - |
| | | | | | Front side | 10 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.422 | 0.496 | - |
| | | | | | Back side | 10 | 20850 | 2510 | 22 | 21.15 | 21.62% | 0.833 | 1.013 | - |
| | | | | | Back side | 10 | 21100 | 2535 | 22 | 21.2 | 20.23% | 0.896 | 1.077 | - |
| | | | | | Back side | 10 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.930 | 1.093 | - |
| | | | | | Bottom | 10 | 20850 | 2510 | 22 | 21.15 | 21.62% | 0.753 | 0.916 | - |
| | | | | | Bottom | 10 | 21100 | 2535 | 22 | 21.2 | 20.23% | 0.814 | 0.979 | - |
| | | | | | Bottom | 10 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.867 | 1.019 | - |
| | | | | | Right side | 10 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.084 | 0.099 | - |
| | | | | | Left side | 10 | 21350 | 2560 | 22 | 21.3 | 17.49% | 0.076 | 0.089 | - |

* - repeated at the highest SAR measurement according to the FCC KDB 865664 D01v01r03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

WLAN802.11 b

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|--------------------|------------|---------------|----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| 802.11 b (Head) | RE Cheek | - | 1 | 2412 | 16.00 | 15.71 | 6.91% | 0.372 | 0.398 | - |
| | RE Cheek | - | 6 | 2437 | 16.00 | 15.91 | 2.09% | 0.514 | 0.525 | 108 |
| | RE Cheek | - | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.430 | 0.432 | - |
| | RE Tilt | - | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.297 | 0.298 | - |
| | LE Cheek | - | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.243 | 0.244 | - |
| | LE Tilt | - | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.171 | 0.172 | - |
| 802.11 b (Hotspot) | Front side | 10mm | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.188 | 0.189 | - |
| | Back side | 10mm | 1 | 2412 | 16.00 | 15.71 | 6.91% | 0.331 | 0.354 | - |
| | Back side | 10mm | 6 | 2437 | 16.00 | 15.91 | 2.09% | 0.441 | 0.450 | - |
| | Back side | 10mm | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.546 | 0.549 | 109 |
| | Top side | 10mm | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.076 | 0.076 | - |
| | Left side | 10mm | 11 | 2462 | 16.00 | 15.98 | 0.46% | 0.242 | 0.243 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

WLAN802.11 a 5.2G

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|---------------------------|------------|---------------|----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| 802.11 a 5.2G (Head) | RE Cheek | - | 48 | 5240 | 14.00 | 13.77 | 5.44% | 0.196 | 0.207 | - |
| | RE Tilt | - | 36 | 5180 | 14.00 | 13.76 | 5.68% | 0.190 | 0.201 | - |
| | RE Tilt | - | 48 | 5240 | 14.00 | 13.77 | 5.44% | 0.204 | 0.215 | 110 |
| | LE Cheek | - | 48 | 5240 | 14.00 | 13.77 | 5.44% | 0.160 | 0.169 | - |
| | LE Tilt | - | 48 | 5240 | 14.00 | 13.77 | 5.44% | 0.176 | 0.186 | - |
| 802.11 a 5.2G (Body-worn) | Front side | 15mm | 48 | 5240 | 14.00 | 13.77 | 5.44% | 0.039 | 0.041 | - |
| | Back side | 15mm | 36 | 5180 | 14.00 | 13.76 | 5.68% | 0.253 | 0.267 | - |
| | Back side | 15mm | 48 | 5240 | 14.00 | 13.77 | 5.44% | 0.265 | 0.279 | 111 |

WLAN802.11 a 5.3G

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|---------------------------|------------|---------------|----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| 802.11 a 5.3G (Head) | RE Cheek | - | 56 | 5280 | 14.00 | 13.89 | 2.57% | 0.192 | 0.197 | - |
| | RE Cheek | - | 64 | 5320 | 14.00 | 13.99 | 0.23% | 0.218 | 0.219 | 112 |
| | RE Tilt | - | 64 | 5320 | 14.00 | 13.99 | 0.23% | 0.208 | 0.208 | - |
| | LE Cheek | - | 64 | 5320 | 14.00 | 13.99 | 0.23% | 0.155 | 0.155 | - |
| | LE Tilt | - | 64 | 5320 | 14.00 | 13.99 | 0.23% | 0.190 | 0.190 | - |
| 802.11 a 5.3G (Body-worn) | Front side | 15mm | 64 | 5320 | 14.00 | 13.99 | 0.23% | 0.053 | 0.053 | - |
| | Back side | 15mm | 56 | 5280 | 14.00 | 13.89 | 2.57% | 0.266 | 0.273 | - |
| | Back side | 15mm | 64 | 5320 | 14.00 | 13.99 | 0.23% | 0.270 | 0.271 | 113 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

WLAN802.11 a 5.6G

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|---------------------------|------------|---------------|-----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| 802.11 a 5.6G (Head) | RE Cheek | - | 108 | 5540 | 14.00 | 13.72 | 6.66% | 0.310 | 0.331 | - |
| | RE Cheek | - | 132 | 5660 | 14.00 | 13.99 | 0.23% | 0.410 | 0.411 | 114 |
| | RE Cheek | - | 136 | 5680 | 14.00 | 13.97 | 0.69% | 0.392 | 0.395 | - |
| | RE Tilt | - | 132 | 5660 | 14.00 | 13.99 | 0.23% | 0.403 | 0.404 | - |
| | LE Cheek | - | 132 | 5660 | 14.00 | 13.99 | 0.23% | 0.222 | 0.223 | - |
| | LE Tilt | - | 132 | 5660 | 14.00 | 13.99 | 0.23% | 0.266 | 0.267 | - |
| 802.11 a 5.6G (Body-worn) | Front side | 15mm | 132 | 5660 | 14.00 | 13.99 | 0.23% | 0.037 | 0.037 | - |
| | Back side | 15mm | 108 | 5540 | 14.00 | 13.72 | 6.66% | 0.305 | 0.325 | - |
| | Back side | 15mm | 132 | 5660 | 14.00 | 13.99 | 0.23% | 0.388 | 0.389 | 115 |
| | Back side | 15mm | 136 | 5680 | 14.00 | 13.97 | 0.69% | 0.373 | 0.376 | - |

WLAN802.11 a 5.8G

| Mode | Position | Distance (mm) | CH | Freq. (MHz) | Max. Rated Avg. Power + Max. Tolerance (dBm) | Measured Avg. Power (dBm) | Scaling | Averaged SAR over 1g (W/kg) | | Plot page |
|---------------------------|------------|---------------|-----|-------------|--|---------------------------|---------|-----------------------------|----------|-----------|
| | | | | | | | | Measured | Reported | |
| 802.11 a 5.8G (Head) | RE Cheek | - | 153 | 5765 | 14.00 | 13.78 | 5.20% | 0.423 | 0.445 | - |
| | RE Cheek | - | 157 | 5785 | 14.00 | 13.77 | 5.44% | 0.491 | 0.518 | 116 |
| | RE Cheek | - | 161 | 5805 | 14.00 | 13.88 | 2.80% | 0.490 | 0.504 | - |
| | RE Tilt | - | 161 | 5805 | 14.00 | 13.88 | 2.80% | 0.455 | 0.468 | - |
| | LE Cheek | - | 161 | 5805 | 14.00 | 13.88 | 2.80% | 0.283 | 0.291 | - |
| | LE Tilt | - | 161 | 5805 | 14.00 | 13.88 | 2.80% | 0.314 | 0.323 | - |
| 802.11 a 5.8G (Body-worn) | Front side | 15mm | 161 | 5805 | 14.00 | 13.88 | 2.80% | 0.083 | 0.085 | - |
| | Back side | 15mm | 153 | 5765 | 14.00 | 13.78 | 5.20% | 0.342 | 0.360 | - |
| | Back side | 15mm | 157 | 5785 | 14.00 | 13.77 | 5.44% | 0.344 | 0.363 | - |
| | Back side | 15mm | 161 | 5805 | 14.00 | 13.88 | 2.80% | 0.346 | 0.356 | 117 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

3. Simultaneous Transmission Analysis

Simultaneous Transmission Scenarios:

| Simultaneous Transmit Configurations | Head | Body-Worn | Hotspot |
|--------------------------------------|------|-----------|---------|
| GSM850/1900 + 2.4GHz Wi-Fi | Yes | No | No |
| GPRS850/1900 + 2.4GHz Wi-Fi | No | No | Yes |
| UMTS B2/B5 + 2.4GHz Wi-Fi | Yes | No | Yes |
| LTE FDD B2/B5/B7 + 2.4GHz Wi-Fi | Yes | No | Yes |
| GSM850/1900 + 5GHz Wi-Fi | Yes | Yes | No |
| GPRS850/1900 + 5GHz Wi-Fi | No | No | No |
| UMTS B2/B5 + 5GHz Wi-Fi | Yes | Yes | No |
| LTE FDD B2/B5/B7 + 5GHz Wi-Fi | Yes | Yes | No |
| GSM850/1900 + Bluetooth | No | Yes | No |
| GPRS850/1900 + Bluetooth | No | No | Yes |
| UMTS B2/B5 + Bluetooth | No | Yes | Yes |
| LTE FDD B2/B5/B7 + Bluetooth | No | Yes | Yes |

Notes:

1. GSM & WCDMA & LTE share the same antenna path and cannot transmit simultaneously
2. Bluetooth, 5GHz WiFi, and 2.4GHz WiFi share the same antenna path and cannot transmit simultaneously.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

3.1 Estimated SAR calculation

According to KDB447498 D01v05 – When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$\text{Estimated SAR} = \frac{\text{Max. tune up power(mW)}}{\text{MIn. test separation distance(mm)}} \times \frac{\sqrt{f(\text{GHz})}}{7.5}$$

If the minimum test separation distance is < 5mm, a distance of 5mm is used for estimated SAR calculation. When the test separation distance is >50mm, the 0.4W/kg is used for SAR-1g.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

3.2 SPLSR evaluation and analysis

Per KDB447498D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR sum to peak location separation ratio(SPLSR).

The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion.

The ratio is determined by **(SAR1 + SAR2)^1.5/Ri**, rounded to two decimal digits, and must be **≤ 0.04** for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

SAR1 and SAR2 are the highest reported or estimated SAR for each antenna in the pair, and Ri is the separation distance between the peak SAR locations for the antenna pair in mm.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Simultaneous Transmission Combination

| reported SAR WWAN and WLAN DTS 2.4GHz, Σ SAR evaluation | | | | | | |
|--|----------|---------------------|------|--------------|--------------------------|-----------------------|
| Frequency band | Position | reported SAR / W/kg | | Σ SAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | <1.6W/kg | | |
| GSM 850 | Head | Right cheek | 0.42 | 0.52 | 0.940 | - |
| | | Right tilt | 0.22 | 0.30 | 0.517 | - |
| | | Left cheek | 0.50 | 0.24 | 0.747 | - |
| | | Left tilt | 0.23 | 0.17 | 0.396 | - |
| GPRS 850 (1Dn1UP) | Hotspot | Front | 0.51 | 0.19 | 0.702 | - |
| | | Back | 0.69 | 0.55 | 1.236 | - |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 0.21 | - | - | - |
| | | Right | 0.22 | - | - | - |
| | | Left | 0.46 | 0.24 | 0.705 | - |
| GSM 1900 | Head | Right cheek | 0.19 | 0.52 | 0.707 | - |
| | | Right tilt | 0.07 | 0.30 | 0.369 | - |
| | | Left cheek | 0.17 | 0.24 | 0.413 | - |
| | | Left tilt | 0.07 | 0.17 | 0.240 | - |
| GPRS 1900 (1Dn1UP) | Hotspot | Front | 0.43 | 0.19 | 0.620 | - |
| | | Back | 0.60 | 0.55 | 1.146 | - |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 0.63 | - | - | - |
| | | Right | 0.12 | - | - | - |
| | | Left | 0.11 | 0.24 | 0.349 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and WLAN DTS 2.4GHz, Σ SAR evaluation | | | | | | |
|--|----------|---------------------|------|--------------|--------------------------|-----------------------|
| Frequency band | Position | reported SAR / W/kg | | Σ SAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | <1.6W/kg | | |
| WCDMA Band II | Head | Right cheek | 0.24 | 0.52 | 0.757 | - |
| | | Right tilt | 0.11 | 0.30 | 0.407 | - |
| | | Left cheek | 0.28 | 0.24 | 0.525 | - |
| | | Left tilt | 0.12 | 0.17 | 0.289 | - |
| | Hotspot | Front | 0.74 | 0.19 | 0.933 | - |
| | | Back | 1.04 | 0.55 | 1.586 | - |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 1.12 | - | - | - |
| | | Right | 0.21 | - | - | - |
| | | Left | 0.19 | 0.24 | 0.428 | - |
| WCDMA Band V | Head | Right cheek | 0.36 | 0.52 | 0.880 | - |
| | | Right tilt | 0.21 | 0.30 | 0.505 | - |
| | | Left cheek | 0.46 | 0.24 | 0.703 | - |
| | | Left tilt | 0.22 | 0.17 | 0.391 | - |
| | Hotspot | Front | 0.53 | 0.19 | 0.718 | - |
| | | Back | 0.79 | 0.55 | 1.334 | - |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 0.19 | - | - | - |
| | | Right | 0.23 | - | - | - |
| | | Left | 0.47 | 0.24 | 0.708 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and WLAN DTS 2.4GHz, Σ SAR evaluation | | | | | | |
|--|----------|---------------------|------|--------------|--------------------------|-----------------------|
| Frequency band | Position | reported SAR / W/kg | | Σ SAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | <1.6W/kg | | |
| LTE FDD Band 2 | Head | Right cheek | 0.42 | 0.52 | 0.940 | - |
| | | Right tilt | 0.20 | 0.30 | 0.497 | - |
| | | Left cheek | 0.46 | 0.24 | 0.703 | - |
| | | Left tilt | 0.16 | 0.17 | 0.331 | - |
| | Hotspot | Front | 0.98 | 0.19 | 1.170 | - |
| | | Back | 1.30 | 0.55 | 1.846 | 107.5 |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 1.15 | - | - | - |
| | | Right | 0.22 | - | - | - |
| | | Left | 0.23 | 0.24 | 0.472 | - |
| LTE FDD Band 5 | Head | Right cheek | 0.36 | 0.52 | 0.880 | - |
| | | Right tilt | 0.26 | 0.30 | 0.557 | - |
| | | Left cheek | 0.45 | 0.24 | 0.693 | - |
| | | Left tilt | 0.26 | 0.17 | 0.431 | - |
| | Hotspot | Front | 0.38 | 0.19 | 0.570 | - |
| | | Back | 0.55 | 0.55 | 1.096 | - |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 0.21 | - | - | - |
| | | Right | 0.28 | - | - | - |
| | | Left | 0.52 | 0.24 | 0.762 | - |
| LTE FDD Band 7 | Head | Right cheek | 0.25 | 0.52 | 0.770 | - |
| | | Right tilt | 0.05 | 0.30 | 0.347 | - |
| | | Left cheek | 0.21 | 0.24 | 0.453 | - |
| | | Left tilt | 0.06 | 0.17 | 0.231 | - |
| | Hotspot | Front | 0.57 | 0.19 | 0.760 | - |
| | | Back | 1.17 | 0.55 | 1.716 | 109 |
| | | Top | - | 0.08 | - | - |
| | | Bottom | 1.11 | - | - | - |
| | | Right | 0.11 | - | - | - |
| | | Left | 0.10 | 0.24 | 0.342 | - |


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| Conditions | Position | SAR Value (W/kg) | Coordinates (cm) | | | Σ SAR (W/kg) | Peak Location Separation Distance (mm) | SPLSR | Simultaneous Transmission SAR Test |
|------------------------|-----------|------------------|------------------|-------|-------|---------------------|--|-------|------------------------------------|
| | | | x | y | z | | | | |
| LTE Band 2 CH 19100 | Back side | 1.3 | 1.07 | 5.39 | -0.01 | 1.85 | 107.5 | 0.023 | SPLSR<0.04, Not required |
| 802.11b CH 11 | | 0.55 | -3.28 | -4.44 | -0.09 | | | | |



| Conditions | Position | SAR Value (W/kg) | Coordinates (cm) | | | Σ SAR (W/kg) | Peak Location Separation Distance (mm) | SPLSR | Simultaneous Transmission SAR Test |
|------------------------|-----------|------------------|------------------|-------|-------|---------------------|--|-------|------------------------------------|
| | | | x | y | z | | | | |
| LTE Band 7 CH 21350 | Back side | 1.17 | -0.5 | 6.1 | -0.02 | 1.72 | 109 | 0.021 | SPLSR<0.04, Not required |
| 802.11b CH 11 | | 0.55 | -3.28 | -4.44 | -0.09 | | | | |



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and WLAN DTS 5.8 GHz, ΣSAR evaluation | | | | | | |
|---|-----------|---------------------|------|------------------|--------------------------|----------------|
| Frequency band | Position | reported SAR / W/kg | | ΣSAR <1.6W/kg | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | | | |
| GSM 850 | Head | RE cheek | 0.42 | 0.52 | 0.94 | - |
| | | RE tilt | 0.22 | 0.47 | 0.69 | - |
| | | LE cheek | 0.50 | 0.29 | 0.794 | - |
| | | LE tilt | 0.23 | 0.32 | 0.545 | - |
| | Body-Worn | Front | 0.26 | 0.09 | 0.35 | - |
| | | Back | 0.35 | 0.36 | 0.71 | - |
| GSM 1900 | Head | RE cheek | 0.19 | 0.52 | 0.707 | - |
| | | RE tilt | 0.07 | 0.47 | 0.542 | - |
| | | LE cheek | 0.16 | 0.29 | 0.453 | - |
| | | LE tilt | 0.07 | 0.32 | 0.389 | - |
| | Body-Worn | Front | 0.42 | 0.09 | 0.51 | - |
| | | Back | 0.62 | 0.36 | 0.98 | - |
| WCDMA Band II | Head | RE cheek | 0.24 | 0.52 | 0.757 | - |
| | | RE tilt | 0.11 | 0.47 | 0.58 | - |
| | | LE cheek | 0.28 | 0.29 | 0.572 | - |
| | | LE tilt | 0.12 | 0.32 | 0.438 | - |
| | Body-Worn | Front | 0.42 | 0.09 | 0.51 | - |
| | | Back | 0.62 | 0.36 | 0.98 | - |
| WCDMA Band V | Head | RE cheek | 0.36 | 0.52 | 0.88 | - |
| | | RE tilt | 0.21 | 0.47 | 0.678 | - |
| | | LE cheek | 0.45 | 0.29 | 0.741 | - |
| | | LE tilt | 0.22 | 0.32 | 0.54 | - |
| | Body-Worn | Front | 0.20 | 0.09 | 0.29 | - |
| | | Back | 0.32 | 0.36 | 0.68 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and WLAN DTS 5.8 GHz, ΣSAR evaluation | | | | | | |
|---|-----------|---------------------|------|----------|--------------------------|----------------|
| Frequency band | Position | reported SAR / W/kg | | ΣSAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | <1.6W/kg | | |
| LTE FDD Band 2 | Head | RE cheek | 0.42 | 0.52 | 0.94 | - |
| | | RE tilt | 0.20 | 0.47 | 0.67 | - |
| | | LE cheek | 0.46 | 0.29 | 0.75 | - |
| | | LE tilt | 0.16 | 0.32 | 0.48 | - |
| | Body-Worn | Front | 0.57 | 0.09 | 0.66 | - |
| | | Back | 0.7 | 0.36 | 1.06 | - |
| LTE FDD Band 5 | Head | RE cheek | 0.36 | 0.52 | 0.88 | - |
| | | RE tilt | 0.26 | 0.47 | 0.73 | - |
| | | LE cheek | 0.45 | 0.29 | 0.74 | - |
| | | LE tilt | 0.26 | 0.32 | 0.58 | - |
| | Body-Worn | Front | 0.34 | 0.09 | 0.43 | - |
| | | Back | 0.42 | 0.36 | 0.78 | - |
| LTE FDD Band 7 | Head | RE cheek | 0.25 | 0.52 | 0.77 | - |
| | | RE tilt | 0.05 | 0.47 | 0.52 | - |
| | | LE cheek | 0.21 | 0.29 | 0.5 | - |
| | | LE tilt | 0.06 | 0.32 | 0.38 | - |
| | Body-Worn | Front | 0.42 | 0.09 | 0.51 | - |
| | | Back | 0.81 | 0.36 | 1.17 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and WLAN UNIT 5 GHz, ΣSAR evaluation | | | | | | |
|--|-----------|---------------------|------|----------|--------------------------|----------------|
| Frequency band | Position | reported SAR / W/kg | | ΣSAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | <1.6W/kg | | |
| GSM 850 | Head | RE cheek | 0.42 | 0.41 | 0.83 | - |
| | | RE tilt | 0.22 | 0.4 | 0.62 | - |
| | | LE cheek | 0.50 | 0.22 | 0.724 | - |
| | | LE tilt | 0.23 | 0.27 | 0.495 | - |
| | Body-Worn | Front | 0.26 | 0.05 | 0.31 | - |
| | | Back | 0.35 | 0.39 | 0.74 | - |
| GSM 1900 | Head | RE cheek | 0.19 | 0.41 | 0.597 | - |
| | | RE tilt | 0.07 | 0.4 | 0.472 | - |
| | | LE cheek | 0.16 | 0.22 | 0.383 | - |
| | | LE tilt | 0.07 | 0.27 | 0.339 | - |
| | Body-Worn | Front | 0.23 | 0.05 | 0.28 | - |
| | | Back | 0.32 | 0.39 | 0.71 | - |
| WCDMA Band II | Head | RE cheek | 0.24 | 0.41 | 0.647 | - |
| | | RE tilt | 0.11 | 0.4 | 0.51 | - |
| | | LE cheek | 0.28 | 0.22 | 0.502 | - |
| | | LE tilt | 0.12 | 0.27 | 0.388 | - |
| | Body-Worn | Front | 0.42 | 0.05 | 0.47 | - |
| | | Back | 0.62 | 0.39 | 1.01 | - |
| WCDMA Band V | Head | RE cheek | 0.36 | 0.41 | 0.77 | - |
| | | RE tilt | 0.21 | 0.4 | 0.608 | - |
| | | LE cheek | 0.45 | 0.22 | 0.671 | - |
| | | LE tilt | 0.22 | 0.27 | 0.49 | - |
| | Body-Worn | Front | 0.20 | 0.05 | 0.25 | - |
| | | Back | 0.32 | 0.39 | 0.71 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and WLAN UNIT 5 GHz, Σ SAR evaluation | | | | | | |
|--|-----------|---------------------|------|--------------|--------------------------|-----------------------|
| Frequency band | Position | reported SAR / W/kg | | Σ SAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | WLAN | <1.6W/kg | | |
| LTE FDD Band2 | Head | RE cheek | 0.42 | 0.41 | 0.83 | - |
| | | RE tilt | 0.20 | 0.4 | 0.6 | - |
| | | LE cheek | 0.46 | 0.22 | 0.68 | - |
| | | LE tilt | 0.16 | 0.27 | 0.43 | - |
| | Body-Worn | Front | 0.57 | 0.05 | 0.62 | - |
| | | Back | 0.7 | 0.39 | 1.09 | - |
| LTE FDD Band5 | Head | RE cheek | 0.36 | 0.41 | 0.77 | - |
| | | RE tilt | 0.26 | 0.4 | 0.66 | - |
| | | LE cheek | 0.45 | 0.22 | 0.67 | - |
| | | LE tilt | 0.26 | 0.27 | 0.53 | - |
| | Body-Worn | Front | 0.34 | 0.05 | 0.39 | - |
| | | Back | 0.42 | 0.39 | 0.81 | - |
| LTE FDD Band7 | Head | RE cheek | 0.25 | 0.41 | 0.66 | - |
| | | RE tilt | 0.05 | 0.4 | 0.45 | - |
| | | LE cheek | 0.21 | 0.22 | 0.43 | - |
| | | LE tilt | 0.06 | 0.27 | 0.33 | - |
| | Body-Worn | Front | 0.42 | 0.05 | 0.47 | - |
| | | Back | 0.81 | 0.39 | 1.2 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and Bluetooth, ΣSAR evaluation | | | | | | |
|--|-----------|---------------------|-----------|----------|--------------------------|----------------|
| Frequency band | Position | reported SAR / W/kg | | ΣSAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | Bluetooth | <1.6W/kg | | |
| GSM 850 | Body-Worn | Front | 0.26 | 0.048 | 0.308 | - |
| | | Back | 0.35 | 0.048 | 0.398 | - |
| GPRS 850 (1Dn1UP) | Hotspot | Front | 0.51 | 0.072 | 0.584 | - |
| | | Back | 0.69 | 0.072 | 0.762 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 0.21 | - | - | - |
| | | Right | 0.22 | - | - | - |
| | | Left | 0.46 | 0.072 | 0.535 | - |
| GSM 1900 | Body-Worn | Front | 0.42 | 0.048 | 0.468 | - |
| | | Back | 0.62 | 0.048 | 0.668 | - |
| GPRS 1900 (1Dn1UP) | Hotspot | Front | 0.43 | 0.072 | 0.502 | - |
| | | Back | 0.60 | 0.072 | 0.672 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 0.63 | - | - | - |
| | | Right | 0.12 | - | - | - |
| | | Left | 0.11 | 0.072 | 0.179 | - |
| WCDMA Band II | Body-Worn | Front | 0.42 | 0.048 | 0.468 | - |
| | | Back | 0.62 | 0.048 | 0.668 | - |
| WCDMA Band V | Hotspot | Front | 0.74 | 0.072 | 0.815 | - |
| | | Back | 1.04 | 0.072 | 1.112 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 1.12 | - | - | - |
| | | Right | 0.21 | - | - | - |
| | | Left | 0.19 | 0.072 | 0.258 | - |
| WCDMA Band V | Body-Worn | Front | 0.20 | 0.048 | 0.248 | - |
| | | Back | 0.32 | 0.048 | 0.368 | - |
| WCDMA Band V | Hotspot | Front | 0.53 | 0.072 | 0.6 | - |
| | | Back | 0.79 | 0.072 | 0.86 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 0.19 | - | - | - |
| | | Right | 0.23 | - | - | - |
| | | Left | 0.47 | 0.072 | 0.538 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

| reported SAR WWAN and Bluetooth, Σ SAR evaluation | | | | | | |
|--|-----------|---------------------|-----------|--------------|--------------------------|-----------------------|
| Frequency band | Position | reported SAR / W/kg | | Σ SAR | Calculated distance (mm) | SPLSR (≤ 0.04) |
| | | WWAN | Bluetooth | <1.6W/kg | | |
| LTE FDD Band2 | Body-Worn | Front | 0.57 | 0.048 | 0.618 | - |
| | | Back | 0.7 | 0.048 | 0.748 | - |
| | Hotspot | Front | 0.98 | 0.072 | 1.052 | - |
| | | Back | 1.30 | 0.072 | 1.372 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 1.15 | - | - | - |
| | | Right | 0.22 | - | - | - |
| | | Left | 0.23 | 0.072 | 0.302 | - |
| LTE FDD Band5 | Body-Worn | Front | 0.34 | 0.048 | 0.388 | - |
| | | Back | 0.42 | 0.048 | 0.468 | - |
| | Hotspot | Front | 0.38 | 0.072 | 0.452 | - |
| | | Back | 0.55 | 0.072 | 0.622 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 0.21 | - | - | - |
| | | Right | 0.28 | - | - | - |
| | | Left | 0.52 | 0.072 | 0.592 | - |
| LTE FDD Band7 | Body-Worn | Front | 0.42 | 0.048 | 0.468 | - |
| | | Back | 0.81 | 0.048 | 0.858 | - |
| | Hotspot | Front | 0.57 | 0.072 | 0.642 | - |
| | | Back | 1.17 | 0.072 | 1.242 | - |
| | | Top | - | 0.072 | - | - |
| | | Bottom | 1.11 | - | - | - |
| | | Right | 0.11 | - | - | - |
| | | Left | 0.10 | 0.072 | 0.172 | - |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

4. Instruments List

| Device | Manufacturer | Type | Serial number | Date of last calibration | Date of next calibration |
|------------------------------|---------------------------------|-----------------|---------------|--------------------------|--------------------------|
| Dosimetric E-Field Probe | Schmid & Partner Engineering AG | EX3DV4 | 3923 | Aug.28,2014 | Aug.27,2015 |
| | | | 3831 | Jan.31,2014 | Jan.30,2015 |
| | | | 3770 | Apr.24,2014 | Apr.23,2015 |
| System Validation Dipole | Schmid & Partner Engineering AG | D835V2 | 4d063 | Aug.28,2014 | Aug.27,2015 |
| | | D1900V2 | 5d027 | Apr.23,2014 | Apr.22,2015 |
| | | D2450V2 | 727 | Apr.23,2014 | Apr.22,2015 |
| | | D2600V2 | 1005 | Jan.28,2014 | Jan.27,2015 |
| | | D5GHzV2 | 1104 | Apr.16,2014 | Apr.15,2015 |
| Data acquisition Electronics | Schmid & Partner Engineering AG | DAE4 | 1260 | Aug.26,2014 | Aug.25,2015 |
| | | | 915 | Jun.18,2014 | Jun.17,2015 |
| | | | 856 | Aug.27,2014 | Aug.26,2015 |
| Software | Schmid & Partner Engineering AG | DASY 52 V52.8.8 | N/A | Calibration not required | Calibration not required |
| Phantom | Schmid & Partner Engineering AG | SAM | N/A | Calibration not required | Calibration not required |
| Network Analyzer | Agilent | E5071C | MY46108212 | Aug.28,2014 | Aug.27,2015 |
| Dielectric Probe Kit | Agilent | 85070E | MY44300677 | Calibration not required | Calibration not required |
| Dual-directional coupler | Agilent | 772D | MY46151242 | Jul.14,2014 | Jul.13,2015 |
| | | 778D | MY48220468 | Apr.01,2014 | Mar.31,2015 |
| RF Signal Generator | Agilent | N5181A | MY50141235 | Dec.14,2013 | Dec.13,2016 |
| Power Meter | Agilent | E4417A | MY51410006 | Oct.25,2013 | Oct.24,2015 |
| Power Sensor | Agilent | E9301H | MY51470001 | Dec.16,2013 | Dec.15,2015 |
| Radio Communication Test | R&S | CMU200 | 113505 | Aug.14,2014 | Aug.13,2015 |
| Radio Communication Test | Anritsu | MT8820C | 6200930984 | Aug.28,2014 | Aug.27,2015 |
| TECPEL | Digital thermometer | DTM-303A | TP130074 | Mar.20,2014 | Mar.19,2015 |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

5. Measurements

Date: 2014/11/13

GSM 850_Head_Le Cheek_CH 251

Communication System: GSM; Frequency: 848.8 MHz, Duty factor: 1:8.3

Medium parameters used: $f = 849$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 40.97$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.14, 9.14, 9.14); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.589 W/kg


Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.944 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.654 W/kg

SAR(1 g) = 0.504 W/kg; SAR(10 g) = 0.367 W/kg

Maximum value of SAR (measured) = 0.586 W/kg



0 dB = 0.586 W/kg = -2.32 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

GSM 850_Speech mode_Back side_CH 251_15mm

Communication System: GSM; Frequency: 848.8 MHz, Duty factor: 1:8.3

Medium parameters used: $f = 849$ MHz; $\sigma = 1.027$ S/m; $\epsilon_r = 52.754$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.03, 9.03, 9.03); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.456 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 15.97 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.540 W/kg

SAR(1 g) = 0.353 W/kg; SAR(10 g) = 0.242 W/kg

Maximum value of SAR (measured) = 0.445 W/kg



0 dB = 0.445 W/kg = -3.52 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

GPRS 850_Hotspot mode_Back side_CH 251_10mm

Communication System: GPRS (1Dn1Up); Frequency: 848.8 MHz, Duty factor: 1:8.3

Medium parameters used: $f = 849$ MHz; $\sigma = 1.027$ S/m; $\epsilon_r = 52.754$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.03, 9.03, 9.03); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.815 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 25.94 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.910 W/kg

SAR(1 g) = 0.690 W/kg; SAR(10 g) = 0.503 W/kg

Maximum value of SAR (measured) = 0.814 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 25.94 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.871 W/kg

SAR(1 g) = 0.548 W/kg; SAR(10 g) = 0.358 W/kg

Maximum value of SAR (measured) = 0.708 W/kg



0 dB = 0.708 W/kg = -1.50 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/14

GSM 1900 _Head_Re Cheek_CH 810

Communication System: GSM; Frequency: 1909.8 MHz, Duty factor: 1:8.3

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.399$ S/m; $\epsilon_r = 39.529$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.79, 7.79, 7.79); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.231 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.712 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.292 W/kg

SAR(1 g) = 0.187 W/kg; SAR(10 g) = 0.117 W/kg

Maximum value of SAR (measured) = 0.237 W/kg



0 dB = 0.237 W/kg = -6.25 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

GSM 1900_Speech mode_Back side_CH 810_15mm

Communication System: GSM; Frequency: 1909.8 MHz, Duty factor: 1:8.3

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.509$ S/m; $\epsilon_r = 51.576$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.19, 7.19, 7.19); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.411 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.265 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.496 W/kg

SAR(1 g) = 0.312 W/kg; SAR(10 g) = 0.191 W/kg

Maximum value of SAR (measured) = 0.407 W/kg



0 dB = 0.407 W/kg = -3.90 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

GPRS 1900_Hotspot mode_Bottom side_CH 810_10mm

Communication System: GPRS (1Dn1Up); Frequency: 1909.8 MHz, Duty factor: 1:8.3

Medium parameters used: $f = 1910$ MHz; $\sigma = 1.509$ S/m; $\epsilon_r = 51.576$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.19, 7.19, 7.19); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (41x61x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.818 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 19.33 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.616 W/kg; SAR(10 g) = 0.338 W/kg

Maximum value of SAR (measured) = 0.841 W/kg



0 dB = 0.841 W/kg = -0.75 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/14

WCDMA Band 2 _Head_Le Cheek_CH 9538

Communication System: WCDMA; Frequency: 1907.6 MHz, Duty factor: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.417$ S/m; $\epsilon_r = 39.537$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.79, 7.79, 7.79); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.371 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.658 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.426 W/kg

SAR(1 g) = 0.282 W/kg; SAR(10 g) = 0.174 W/kg

Maximum value of SAR (measured) = 0.357 W/kg



0 dB = 0.357 W/kg = -4.47 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

WCDMA Band 2_Speech mode_Back side_CH 9400

Communication System: WCDMA; Frequency: 1880 MHz, Duty factor: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.473$ S/m; $\epsilon_r = 51.693$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.19, 7.19, 7.19); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.766 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 11.20 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.957 W/kg

SAR(1 g) = 0.592 W/kg; SAR(10 g) = 0.367 W/kg

Maximum value of SAR (measured) = 0.775 W/kg



0 dB = 0.775 W/kg = -1.11 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

WCDMA Band 2_Hotspot mode_Bottom side_CH 9538_10mm

Communication System: WCDMA; Frequency: 1907.6 MHz, Duty factor: 1:1

Medium parameters used: $f = 1908$ MHz; $\sigma = 1.507$ S/m; $\epsilon_r = 51.579$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.19, 7.19, 7.19); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (51x71x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 1.51 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 27.47 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.83 W/kg

SAR(1 g) = 1.12 W/kg; SAR(10 g) = 0.611 W/kg

Maximum value of SAR (measured) = 1.51 W/kg



0 dB = 1.51 W/kg = 1.79 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/13

WCDMA Band 5_Head_Le Cheek_CH 4233

Communication System: WCDMA; Frequency: 846.6 MHz, Duty factor: 1:1

Medium parameters used: $f = 847 \text{ MHz}$; $\sigma = 0.894 \text{ S/m}$; $\epsilon_r = 40.997$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.14, 9.14, 9.14); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15 \text{ mm}$, $dy=15 \text{ mm}$

Maximum value of SAR (interpolated) = 0.480 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8 \text{ mm}$, $dy=8 \text{ mm}$, $dz=5 \text{ mm}$

Reference Value = 5.524 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.586 W/kg

SAR(1 g) = 0.451 W/kg; SAR(10 g) = 0.330 W/kg

Maximum value of SAR (measured) = 0.519 W/kg



0 dB = 0.519 W/kg = -2.85 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

WCDMA Band 5_Speech mode_Back side_CH 4233_15mm

Communication System: WCDMA; Frequency: 846.6 MHz, Duty factor: 1:1

Medium parameters used: $f = 847 \text{ MHz}$; $\sigma = 1.025 \text{ S/m}$; $\epsilon_r = 52.772$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.03, 9.03, 9.03); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (71x111x1): Interpolated grid: $dx=15 \text{ mm}$, $dy=15 \text{ mm}$

Maximum value of SAR (interpolated) = 0.382 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8 \text{ mm}$, $dy=8 \text{ mm}$, $dz=5 \text{ mm}$

Reference Value = 16.15 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.444 W/kg

SAR(1 g) = 0.316 W/kg; SAR(10 g) = 0.226 W/kg

Maximum value of SAR (measured) = 0.383 W/kg



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

WCDMA Band 5_Hotspot mode_Back side_CH 4132_10mm

Communication System: WCDMA; Frequency: 826.4 MHz, Duty factor: 1:1

Medium parameters used: $f = 826.4$ MHz; $\sigma = 1.003$ S/m; $\epsilon_r = 52.954$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.03, 9.03, 9.03); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body/Area Scan (71x111x1): Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.921 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.36 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.788 W/kg; SAR(10 g) = 0.577 W/kg

Maximum value of SAR (measured) = 0.922 W/kg

Configuration/Body/Zoom Scan (5x5x7)/Cube 1: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.36 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.968 W/kg

SAR(1 g) = 0.622 W/kg; SAR(10 g) = 0.410 W/kg

Maximum value of SAR (measured) = 0.783 W/kg



0 dB = 0.783 W/kg = -1.06 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/20

LTE Band 2 (20MHz)_Head_Le Cheek_CH 19100_QPSK_1-99

Communication System: LTE; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.432$ S/m; $\epsilon_r = 39.256$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.42, 8.42, 8.42); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 0.597 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.270 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.674 W/kg

SAR(1 g) = 0.446 W/kg; SAR(10 g) = 0.278 W/kg

Maximum value of SAR (measured) = 0.564 W/kg



0 dB = 0.597 W/kg = -2.24 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/24

LTE Band 2 (20MHz)_Body-worn_Back side_CH 19100_QPSK_1-99_15mm

Communication System: LTE; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.552$ S/m; $\epsilon_r = 54.065$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.03, 8.03, 8.03); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.883 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 11.38 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.682 W/kg; SAR(10 g) = 0.402 W/kg

Maximum value of SAR (measured) = 0.913 W/kg



0 dB = 0.883 W/kg = -0.54 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/24

LTE Band 2 (20MHz)_Hotspot_Back side_CH 19100_QPSK_1-99_10mm_repeated

Communication System: LTE; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.552$ S/m; $\epsilon_r = 54.065$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.03, 8.03, 8.03); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 1.72 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 15.01 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 1.26 W/kg; SAR(10 g) = 0.721 W/kg

Maximum value of SAR (measured) = 1.71 W/kg



0 dB = 1.72 W/kg = 2.36 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/18

LTE Band 5 (10MHz)_Head_Le Cheek_CH 20450_QPSK_1-0

Communication System: LTE; Frequency: 829 MHz, Duty factor: 1:1

Medium parameters used: $f = 829$ MHz; $\sigma = 0.876$ S/m; $\epsilon_r = 40.237$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(10.48, 10.48, 10.48); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.508 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.817 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.546 W/kg

SAR(1 g) = 0.439 W/kg; SAR(10 g) = 0.332 W/kg

Maximum value of SAR (measured) = 0.495 W/kg



0 dB = 0.508 W/kg = -2.94 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/19

LTE Band 5 (10MHz)_Body-worn_Back side_CH 20600_QPSK_1-49_15mm

Communication System: LTE; Frequency: 844 MHz, Duty factor: 1:1

Medium parameters used: $f = 844$ MHz; $\sigma = 0.991$ S/m; $\epsilon_r = 53.572$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(10.32, 10.32, 10.32); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.476 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 22.70 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.530 W/kg

SAR(1 g) = 0.415 W/kg; SAR(10 g) = 0.312 W/kg

Maximum value of SAR (measured) = 0.481 W/kg



0 dB = 0.476 W/kg = -3.22 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

LTE Band 5 (10MHz)_Hotspot_Back side_CH 20600_QPSK_1-49_10mm

Communication System: LTE; Frequency: 844 MHz, Duty factor: 1:1

Medium parameters used: $f = 844 \text{ MHz}$; $\sigma = 0.991 \text{ S/m}$; $\epsilon_r = 53.572$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(10.32, 10.32, 10.32); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (71x111x1): Interpolated grid: $dx=15 \text{ mm}$, $dy=15 \text{ mm}$

Maximum value of SAR (interpolated) = 0.622 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8 \text{ mm}$, $dy=8 \text{ mm}$, $dz=5 \text{ mm}$

Reference Value = 25.26 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.685 W/kg

SAR(1 g) = 0.431 W/kg; SAR(10 g) = 0.294 W/kg

Maximum value of SAR (measured) = 0.549 W/kg

Configuration/Head/Zoom Scan (5x5x7)/Cube 1: Measurement grid:


$dx=8 \text{ mm}$, $dy=8 \text{ mm}$, $dz=5 \text{ mm}$

Reference Value = 25.26 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.678 W/kg

SAR(1 g) = 0.534 W/kg; SAR(10 g) = 0.405 W/kg

Maximum value of SAR (measured) = 0.615 W/kg



0 dB = 0.622 W/kg = -2.06 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/22

LTE Band 7 (20MHz)_Head_Re_Cheek_CH 21350_QPSK_1-99

Communication System: LTE; Frequency: 2560 MHz, Duty factor: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 1.948$ S/m; $\epsilon_r = 40.487$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.41, 7.41, 7.41); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (81x141x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.375 W/kg

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.895 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.476 W/kg

SAR(1 g) = 0.247 W/kg; SAR(10 g) = 0.128 W/kg

Maximum value of SAR (measured) = 0.351 W/kg



0 dB = 0.375 W/kg = -4.26 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/27

LTE Band 7 (20MHz)_Body-worn_Back side_CH 21100_QPSK_1-99_15mm

Communication System: LTE; Frequency: 2535 MHz, Duty factor: 1:1

Medium parameters used: $f = 2535$ MHz; $\sigma = 2.019$ S/m; $\epsilon_r = 52.992$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.36, 7.36, 7.36); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (81x131x1): Interpolated grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (interpolated) = 1.19 W/kg

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 6.994 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.803 W/kg; SAR(10 g) = 0.401 W/kg

Maximum value of SAR (measured) = 1.19 W/kg



0 dB = 1.19 W/kg = 0.76 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/27

LTE Band 7 (20MHz)_Hotspot_Back side_CH 21350_QPSK_1-99_10mm

Communication System: LTE; Frequency: 2560 MHz, Duty factor: 1:1

Medium parameters used: $f = 2560$ MHz; $\sigma = 2.044$ S/m; $\epsilon_r = 52.811$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.36, 7.36, 7.36); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Head/Area Scan (81x141x1): Interpolated grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (interpolated) = 1.76 W/kg

Configuration/Head/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.42 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 2.31 W/kg

SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.561 W/kg

Maximum value of SAR (measured) = 1.71 W/kg



0 dB = 1.76 W/kg = 2.46 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/23

WLAN802.11b_Head_RE Cheek_CH 6

Communication System: WLAN802.11 b & g & n(20M)(40M) ; Frequency: 2437 MHz, Duty factor: 1:1

Medium parameters used: $f = 2437$ MHz; $\sigma = 1.808$ S/m; $\epsilon_r = 39.231$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(6.97, 6.97, 6.97); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom:Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/RE Cheek/Area Scan (91x141x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.867 W/kg


Configuration/RE Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.885 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.514 W/kg; SAR(10 g) = 0.237 W/kg

Maximum value of SAR (measured) = 0.773 W/kg



$$0 \text{ dB} = 0.867 \text{ W/kg} = -0.62 \text{ dBW/kg}$$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/23

WLAN802.11b_Hotspot_Back side_CH 11_10mm

Communication System: WLAN802.11 b & g & n(20M)(40M) ; Frequency: 2462 MHz, Duty factor: 1:1

Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.063 \text{ S/m}$; $\epsilon_r = 50.06$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(7.15, 7.15, 7.15); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/ Hotspot /Area Scan (91x151x1): Interpolated grid: $dx=12 \text{ mm}$, $dy=12 \text{ mm}$

Maximum value of SAR (interpolated) = 0.859 W/kg


Configuration/ Hotspot /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5 \text{ mm}$, $dy=5 \text{ mm}$, $dz=5 \text{ mm}$

Reference Value = 3.287 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.16 W/kg

SAR(1 g) = 0.546 W/kg; SAR(10 g) = 0.245 W/kg

Maximum value of SAR (measured) = 0.842 W/kg



$$0 \text{ dB} = 0.859 \text{ W/kg} = -0.66 \text{ dBW/kg}$$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/17

WLAN802.11a 5.2G_Head_RE Tilt_CH 48

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5240 MHz, Duty factor: 1:1

Medium parameters used: $f = 5240$ MHz; $\sigma = 4.668$ S/m; $\epsilon_r = 36.072$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(5.25, 5.25, 5.25); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/RE Tilt/Area Scan (111x181x1): Interpolated grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (interpolated) = 0.356 W/kg

Configuration/RE Tilt/Zoom Scan (7x7x12)/Cube 0: Measurement grid:


$dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 5.062 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.823 W/kg

SAR(1 g) = 0.204 W/kg; SAR(10 g) = 0.070 W/kg

Maximum value of SAR (measured) = 0.392 W/kg



0 dB = 0.356 W/kg = -4.49 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/19

WLAN802.11a 5.2G_Body-worn_Back side_CH 48_15mm

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5240 MHz, Duty factor: 1:1

Medium parameters used: $f = 5240$ MHz; $\sigma = 5.474$ S/m; $\epsilon_r = 48.347$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.56, 4.56, 4.56); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body-worn_Area Scan (111x181x1): Interpolated grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (interpolated) = 0.482 W/kg


Configuration/Body-worn_Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 1.587 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.917 W/kg

SAR(1 g) = 0.265 W/kg; SAR(10 g) = 0.112 W/kg

Maximum value of SAR (measured) = 0.473 W/kg



$$0 \text{ dB} = 0.482 \text{ W/kg} = -3.17 \text{ dBW/kg}$$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/18

WLAN802.11a 5.3G_Head_RE Cheek_CH 64

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5320 MHz, Duty factor: 1:1

Medium parameters used: $f = 5320$ MHz; $\sigma = 4.767$ S/m; $\epsilon_r = 35.798$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(5.07, 5.07, 5.07); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/RE Cheek/Area Scan (111x181x1): Interpolated grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (interpolated) = 0.424 W/kg


Configuration/RE Cheek/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 4.481 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.218 W/kg; SAR(10 g) = 0.088 W/kg

Maximum value of SAR (measured) = 0.440 W/kg



$$0 \text{ dB} = 0.424 \text{ W/kg} = -3.73 \text{ dBW/kg}$$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/19

WLAN802.11a 5.3G_Body-worn_Back side_CH 64_15mm

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5320 MHz, Duty factor: 1:1

Medium parameters used: $f = 5320$ MHz; $\sigma = 5.59$ S/m; $\epsilon_r = 48.196$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.38, 4.38, 4.38); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body-worn_Area Scan (111x181x1): Interpolated grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (interpolated) = 0.507 W/kg


Configuration/Body-worn_Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 1.600 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 0.978 W/kg

SAR(1 g) = 0.270 W/kg; SAR(10 g) = 0.109 W/kg

Maximum value of SAR (measured) = 0.489 W/kg



$$0 \text{ dB} = 0.507 \text{ W/kg} = -2.95 \text{ dBW/kg}$$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/17

WLAN802.11a 5.6G_Head_RE Cheek_CH 132

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5660 MHz, Duty factor: 1:1

Medium parameters used: $f = 5660$ MHz; $\sigma = 5.153$ S/m; $\epsilon_r = 35.031$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.48, 4.48, 4.48); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/RE Cheek/Area Scan (111x181x1): Interpolated grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (interpolated) = 0.771 W/kg

Configuration/RE Cheek/Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 6.271 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.78 W/kg

SAR(1 g) = 0.410 W/kg; SAR(10 g) = 0.136 W/kg

Maximum value of SAR (measured) = 0.792 W/kg


Configuration/RE Cheek/Zoom Scan (7x7x12)/Cube 1: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 6.271 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.83 W/kg

SAR(1 g) = 0.359 W/kg; SAR(10 g) = 0.127 W/kg

Maximum value of SAR (measured) = 0.732 W/kg



0 dB = 0.771 W/kg = -1.13 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

WLAN802.11a 5.6G_Body-worn_Back side_CH 132_15mm

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5660 MHz, Duty factor: 1:1

Medium parameters used: $f = 5660$ MHz; $\sigma = 6.058$ S/m; $\epsilon_r = 47.18$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(3.76, 3.76, 3.76); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body-worn_Area Scan (111x181x1): Interpolated grid:

$dx=10$ mm, $dy=10$ mm

Maximum value of SAR (interpolated) = 0.728 W/kg


Configuration/Body-worn_Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 1.463 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.388 W/kg; SAR(10 g) = 0.157 W/kg

Maximum value of SAR (measured) = 0.714 W/kg



0 dB = 0.728 W/kg = -1.38 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/18

WLAN802.11a 5.8G_Head_RE Cheek_CH 157

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5785 MHz, Duty factor: 1:1

Medium parameters used : $f = 5785$ MHz; $\sigma = 5.305$ S/m; $\epsilon_r = 34.724$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.65, 4.65, 4.65); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/RE Cheek/Area Scan (111x181x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.02 W/kg

Configuration/RE Cheek/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.151 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.14 W/kg

SAR(1 g) = 0.491 W/kg; SAR(10 g) = 0.159 W/kg

Maximum value of SAR (measured) = 1.01 W/kg


Configuration/RE Cheek/Zoom Scan (7x7x12)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.151 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 0.400 W/kg; SAR(10 g) = 0.129 W/kg

Maximum value of SAR (measured) = 0.846 W/kg



0 dB = 1.02 W/kg = 0.07 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

WLAN802.11 a 5.8G_Body-worn_Back side_CH 161_15mm

Communication System: WLAN 802.11n/a(5G) FCC ; Frequency: 5805 MHz, Duty factor: 1:1

Medium parameters used : $f = 5805 \text{ MHz}$; $\sigma = 6.213 \text{ S/m}$; $\epsilon_r = 46.936$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.13, 4.13, 4.13); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Body-worn_Area Scan (111x181x1): Interpolated grid:

$dx=10 \text{ mm}$, $dy=10 \text{ mm}$

Maximum value of SAR (interpolated) = 0.671 W/kg


Configuration/Body-worn_Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4 \text{ mm}$, $dy=4 \text{ mm}$, $dz=2 \text{ mm}$

Reference Value = 1.747 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.346 W/kg; SAR(10 g) = 0.131 W/kg

Maximum value of SAR (measured) = 0.661 W/kg



$$0 \text{ dB} = 0.671 \text{ W/kg} = -1.73 \text{ dBW/kg}$$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

6. System Verification

Date: 2014/11/13

Dipole 835 MHz_SN:4d063_Head

Communication System: CW; Frequency: 835 MHz, Duty factor: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.883 \text{ S/m}$; $\epsilon_r = 41.147$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.14, 9.14, 9.14); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (41x121x1): Interpolated grid:

$dx=15 \text{ mm}$, $dy=15 \text{ mm}$

Maximum value of SAR (interpolated) = 3.75 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 66.27 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 4.45 W/kg

SAR(1 g) = 2.34 W/kg; SAR(10 g) = 1.49 W/kg

Maximum value of SAR (measured) = 3.76 W/kg



0 dB = 3.76 W/kg = 5.75 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

Dipole 835 MHz_SN:4d063_Body

Communication System: CW; Frequency: 835 MHz, Duty factor: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1.012 \text{ S/m}$; $\epsilon_r = 52.878$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(9.03, 9.03, 9.03); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (51x131x1): Interpolated grid:

$dx=15 \text{ mm}$, $dy=15 \text{ mm}$

Maximum value of SAR (interpolated) = 3.46 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 59.62 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 4.13 W/kg

SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.54 W/kg

Maximum value of SAR (measured) = 3.49 W/kg



0 dB = 3.49 W/kg = 5.43 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/14

Dipole 1900 MHz_SN: 5d027_Head

Communication System: CW; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.389$ S/m; $\epsilon_r = 39.566$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.79, 7.79, 7.79); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (51x61x1): Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 15.7 W/kg


Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 103.7 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 19.1 W/kg

SAR(1 g) = 9.77 W/kg; SAR(10 g) = 5.16 W/kg

Maximum value of SAR (measured) = 14.7 W/kg



0 dB = 14.7 W/kg = 11.67 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/15

Dipole 1900 MHz_SN: 5d027_Body

Communication System: CW; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.497$ S/m; $\epsilon_r = 51.597$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(7.19, 7.19, 7.19); Calibrated: 2014/1/31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn915; Calibrated: 2014/6/18
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (51x61x1): Interpolated grid: dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 23.9 W/kg


Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 124.6 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 33.9 W/kg

SAR(1 g) = 9.81 W/kg; SAR(10 g) = 5.26 W/kg

Maximum value of SAR (measured) = 23.7 W/kg



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/18

Dipole 835 MHz_SN:4d063_Head

Communication System: CW; Frequency: 835 MHz, Duty factor: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.879$ S/m; $\epsilon_r = 40.231$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(10.48, 10.48, 10.48); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (51x121x1): Interpolated grid:

dx=15 mm, dy=15 mm

Maximum value of SAR (interpolated) = 2.96 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.41 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.54 W/kg

SAR(1 g) = 2.36 W/kg; SAR(10 g) = 1.55 W/kg

Maximum value of SAR (measured) = 2.99 W/kg



0 dB = 2.96 W/kg = 4.71 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

Dipole 835 MHz_SN:4d063_Body

Communication System: CW; Frequency: 835 MHz, Duty factor: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.981$ S/m; $\epsilon_r = 53.663$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(10.32, 10.32, 10.32); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (51x111x1): Interpolated grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 2.91 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 54.00 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.42 W/kg

SAR(1 g) = 2.37 W/kg; SAR(10 g) = 1.5 W/kg

Maximum value of SAR (measured) = 2.91 W/kg



0 dB = 2.91 W/kg = 4.64 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/20

Dipole 1900 MHz_SN:5d027_Head

Communication System: CW; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.432$ S/m; $\epsilon_r = 39.256$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.42, 8.42, 8.42); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (41x81x1): Interpolated grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 14.7 W/kg


Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 97.131 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 19.3 W/kg

SAR(1 g) = 9.95 W/kg; SAR(10 g) = 5.17 W/kg

Maximum value of SAR (measured) = 14.8 W/kg



0 dB = 14.7 W/kg = 11.67 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/24

Dipole 1900 MHz_SN:5d027_Body

Communication System: CW; Frequency: 1900 MHz, Duty factor: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.552$ S/m; $\epsilon_r = 54.065$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(8.03, 8.03, 8.03); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (51x101x1): Interpolated grid:

$dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 14.4 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 95.91 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 18.2 W/kg

SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.32 W/kg

Maximum value of SAR (measured) = 14.5 W/kg



0 dB = 14.5 W/kg = 11.61 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/23

Dipole 2450 MHz_SN:727_Head

Communication System: CW; Frequency: 2450 MHz, Duty factor: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.823$ S/m; $\epsilon_r = 39.185$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(6.97, 6.97, 6.97); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=250mW, dist=2mm: Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 22.3 W/kg


Configuration/d=10mm, Pin=250mW, dist=2mm /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.77 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 29.0 W/kg

SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.02 W/kg

Maximum value of SAR (measured) = 20.9 W/kg



0 dB = 22.3 W/kg = 13.47 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/23

Dipole 2450 MHz_SN:727_Body

Communication System: CW; Frequency: 2450 MHz, Duty factor: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.045$ S/m; $\epsilon_r = 50.104$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(7.15, 7.15, 7.15); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=250mW, dist=2mm: Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 23.8 W/kg


Configuration/d=10mm, Pin=250mW, dist=2mm /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.07 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 30.7 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 5.85 W/kg

Maximum value of SAR (measured) = 22.3 W/kg



0 dB = 23.8 W/kg = 13.76 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/22

Dipole 2600 MHz_SN:1005_Head

Communication System: CW; Frequency: 2600 MHz, Duty factor: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.981$ S/m; $\epsilon_r = 40.383$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.41, 7.41, 7.41); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (61x121x1): Interpolated grid:

$dx=12$ mm, $dy=12$ mm

Maximum value of SAR (interpolated) = 24.7 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 99.68 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 33.6 W/kg

SAR(1 g) = 15.1 W/kg; SAR(10 g) = 6.64 W/kg

Maximum value of SAR (measured) = 23.8 W/kg



0 dB = 24.7 W/kg = 13.93 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/27

Dipole 2600 MHz_SN:1005_Body

Communication System: CW; Frequency: 2600 MHz, Duty factor: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.071$ S/m; $\epsilon_r = 52.598$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3923; ConvF(7.56, 7.56, 7.56); Calibrated: 2014/8/28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1260; Calibrated: 2014/8/26
- Phantom: Head
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Pin=250mW/Area Scan (61x121x1): Interpolated grid:

$dx=12$ mm, $dy=12$ mm

Maximum value of SAR (interpolated) = 21.5 W/kg

Configuration/Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 97.05 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 26.2 W/kg

SAR(1 g) = 14.7 W/kg; SAR(10 g) = 6.5 W/kg

Maximum value of SAR (measured) = 21.1 W/kg



0 dB = 21.5 W/kg = 13.32 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/17

Dipole 5200 MHz_SN:1104_Head

Communication System: CW; Frequency: 5200 MHz, Duty factor: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.618$ S/m; $\epsilon_r = 36.074$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(5.25, 5.25, 5.25); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 18.4 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm /Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 59.62 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 36.6 W/kg

SAR(1 g) = 8.37 W/kg; SAR(10 g) = 2.43 W/kg

Maximum value of SAR (measured) = 18.4 W/kg



0 dB = 18.4 W/kg = 12.66 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

Dipole 5200 MHz_SN:1104_Body

Communication System: CW; Frequency: 5200 MHz, Duty factor: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.407$ S/m; $\epsilon_r = 48.601$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.56, 4.56, 4.56); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 19.2 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm /Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 48.19 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 29.8 W/kg

SAR(1 g) = 7.59 W/kg; SAR(10 g) = 2.06 W/kg

Maximum value of SAR (measured) = 15.3 W/kg



0 dB = 19.2 W/kg = 12.82 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/18

Dipole 5300 MHz_SN:1104_Head

Communication System: CW; Frequency: 5300 MHz, Duty factor: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.731$ S/m; $\epsilon_r = 35.828$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(5.07, 5.07, 5.07); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 17.4 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm /Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 57.38 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 34.8 W/kg

SAR(1 g) = 8.32 W/kg; SAR(10 g) = 2.32 W/kg

Maximum value of SAR (measured) = 17.1 W/kg



0 dB = 17.4 W/kg = 12.40 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

Dipole 5300 MHz_SN:1104_Body

Communication System: CW; Frequency: 5300 MHz, Duty factor: 1:1

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.571$ S/m; $\epsilon_r = 48.323$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.38, 4.38, 4.38); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 16.5 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 44.03 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 32.5 W/kg

SAR(1 g) = 7.83 W/kg; SAR(10 g) = 2.24 W/kg

Maximum value of SAR (measured) = 16.9 W/kg



0 dB = 16.5 W/kg = 12.17 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/17

Dipole 5600 MHz_SN:1104_Head

Communication System: CW; Frequency: 5600 MHz, Duty factor: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.081$ S/m; $\epsilon_r = 35.142$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.48, 4.48, 4.48); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 19.7 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm /Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.23 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 39.8 W/kg

SAR(1 g) = 8.74 W/kg; SAR(10 g) = 2.58 W/kg

Maximum value of SAR (measured) = 19.1 W/kg



0 dB = 19.7 W/kg = 12.93 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

Dipole 5600 MHz_SN:1104_Body

Communication System: CW; Frequency: 5600 MHz, Duty factor: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 6.041$ S/m; $\epsilon_r = 47.501$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(3.76, 3.76, 3.76); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 18.2 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 54.52 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 37.3 W/kg

SAR(1 g) = 8.4 W/kg; SAR(10 g) = 2.35 W/kg

Maximum value of SAR (measured) = 18.2 W/kg



0 dB = 18.2 W/kg = 12.59 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Date: 2014/11/18

Dipole 5800 MHz_SN:1104_Head

Communication System: CW; Frequency: 5800 MHz, Duty factor: 1:1

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.315$ S/m; $\epsilon_r = 34.701$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.65, 4.65, 4.65); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 17.8 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm /Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 56.30 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 38.6 W/kg

SAR(1 g) = 8.11 W/kg; SAR(10 g) = 2.33 W/kg

Maximum value of SAR (measured) = 17.7 W/kg



0 dB = 17.8 W/kg = 12.50 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Date: 2014/11/19

Dipole 5800 MHz_SN:1104_Body

Communication System: CW; Frequency: 5800 MHz, Duty factor: 1:1

Medium parameters used: $f = 5800$ MHz; $\sigma = 6.2$ S/m; $\epsilon_r = 46.941$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3770; ConvF(4.13, 4.13, 4.13); Calibrated: 4/24/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn856; Calibrated: 8/27/2014
- Phantom: Head;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/d=10mm, Pin=100mW, dist=2mm: Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 16.9 W/kg


Configuration/d=10mm, Pin=100mW, dist=2mm/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 51.84 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 36.2 W/kg

SAR(1 g) = 7.72 W/kg; SAR(10 g) = 2.16 W/kg

Maximum value of SAR (measured) = 16.9 W/kg



0 dB = 16.9 W/kg = 12.28 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

7. DAE & Probe Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di Isotipage
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client SGS-TW (Auden)

Certificate No.: DAE4-1260_Aug14

CALIBRATION CERTIFICATE

Object DAE4 - SD 000 D04 BM - SN: 1260

Calibrator procedure(s) QA CAL-06.v26
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: August 26, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility environment (temperature (22 ± 3)°C and humidity < 70%).

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|--|--|--|--|
| Kathley Multimeter Type 2001 | SN: 0610278 | 01-Oct-13 (No:13976) | Oct-14 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| Auto DAE Calibration Unit Calibrator Box V2.1 | SE UWE 053 AA 1001 SE UWE 008 AA 1002 | 07-Jan-14 (in house check) 07-Jan-14 (in house check) | In house check: Jan-15 In house check: Jan-15 |

| | | | |
|----------------|-----------------------------|--------------------------|----------------|
| Calibrated by: | Name: Dominique Stettler | Function: Technician | Signature: |
| Approved by: | Fin Bonhag | Deputy Technical Manager | |

Issued: August 26, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: DAE4-1260_Aug14

Page 1 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalementage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAB)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary

| | |
|-----------------|---|
| DAE | data acquisition electronics |
| Connector angle | information used in DASY system to align probe sensor X to the robot coordinate system. |

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement*: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - *DC Voltage Measurement Linearity*: Verification of the linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - *Common mode sensitivity*: Influence of a positive or negative common mode voltage on the differential measurement.
 - *Channel separation*: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - *AD Converter Values with inputs shorted*: Values on the internal AD converter corresponding to zero input voltage
 - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
 - *Input Offset Current*: Typical value for information: Maximum channel input offset current, not considering the input resistance.
 - *Input resistance*: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - *Low Battery Alarm Voltage*: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - *Power consumption*: Typical value for information: Supply currents in various operating modes.

DC Voltage Measurement

A/D : Converter Resolution nominal
High Range: 1LSB = 6.1µV, full range = -100...+800 mV
Low Range: 1LSB = 81mV, full range = -1.....+3mV
DASY measurement parameters: Auto Zero Time: 5 sec; Measuring time: 3 sec

| Calibration Factors | X | Y | Z |
|---------------------|-----------------------|-----------------------|-----------------------|
| High Range | 406.033 ± 0.02% (k=2) | 405.001 ± 0.02% (k=2) | 405.579 ± 0.02% (k=2) |
| Low Range | 3.55663 ± 1.50% (k=2) | 4.01886 ± 1.50% (k=2) | 4.00466 ± 1.50% (k=2) |

Connector Angle

| | |
|---|------------|
| Connector Angle to be used in DASY system | 84.0° ± 1° |
|---|------------|

Appendix (Additional assessments outside the scope of SCS108)**1. DC Voltage Linearity**

| High Range | Reading (µV) | Difference (µV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 19997.43 | -0.04 | -0.00 |
| Channel X + Input | 20003.49 | 2.46 | 0.01 |
| Channel X - Input | -19998.62 | 2.32 | -0.01 |
| Channel Y + Input | 199988.97 | 1.33 | 0.00 |
| Channel Y + Input | 20001.53 | 0.51 | 0.00 |
| Channel Y - Input | -20100.52 | 0.34 | -0.00 |
| Channel Z + Input | 199998.52 | 1.01 | 0.00 |
| Channel Z + Input | 19999.80 | -1.11 | -0.01 |
| Channel Z - Input | -20001.65 | -0.71 | 0.00 |

| Low Range | Reading (µV) | Difference (µV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 2000.98 | 0.17 | 0.01 |
| Channel X + Input | 201.72 | 0.48 | 0.24 |
| Channel X - Input | -198.19 | 0.50 | -0.25 |
| Channel Y + Input | 1999.92 | -1.02 | -0.05 |
| Channel Y + Input | 201.16 | -0.25 | -0.12 |
| Channel Y - Input | -198.53 | 0.05 | -0.03 |
| Channel Z + Input | 2001.06 | 0.16 | 0.01 |
| Channel Z + Input | 200.04 | -1.27 | -0.63 |
| Channel Z - Input | -200.02 | -1.46 | 0.74 |

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Common mode Input Voltage (mV) | High Range | Low Range |
|-----------|-----------------------------------|----------------------|----------------------|
| | | Average Reading (µV) | Average Reading (µV) |
| Channel X | 200 | 1.17 | -0.56 |
| | -200 | 1.57 | -0.48 |
| Channel Y | 200 | 12.06 | 12.37 |
| | -200 | 12.16 | -12.07 |
| Channel Z | 200 | -0.46 | -0.74 |
| | -200 | -1.73 | -1.63 |

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Input Voltage (mV) | Channel X (µV) | Channel Y (µV) | Channel Z (µV) |
|-----------|--------------------|----------------|----------------|----------------|
| Channel X | 200 | | 5.89 | -2.24 |
| Channel Y | 200 | 9.64 | - | 7.49 |
| Channel Z | 200 | 9.68 | 7.16 | - |

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 15814 | 14950 |
| Channel Y | 15817 | 16075 |
| Channel Z | 16045 | 16582 |

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10MΩ

| | Average (µV) | min. Offset (µV) | max. Offset (µV) | Std. Deviation (µV) |
|-----------|--------------|------------------|------------------|---------------------|
| Channel X | 0.26 | -0.76 | 1.42 | 0.43 |
| Channel Y | -0.44 | -1.36 | 0.61 | 0.43 |
| Channel Z | -1.66 | -2.60 | -0.69 | 0.44 |

6. Input Offset Current

Nominal input circuitry offset current on all channels: <25nA

7. Input Resistance (Typical values for information)

| | Zeroing (kOhm) | Measuring (MOhm) |
|-----------|----------------|------------------|
| Channel X | 200 | 200 |
| Channel Y | 200 | 200 |
| Channel Z | 200 | 200 |

8. Low Battery Alarm Voltage (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.9 |
| Supply (- Vcc) | -7.5 |

9. Power Consumption (Typical values for information)

| Typical values | Switched off (mA) | Stand-by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01 | +6 | +14 |
| Supply (- Vcc) | -0.01 | -6 | -9 |

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary

| | |
|-----------------|---|
| DAE | data acquisition electronics |
| Connector angle | information used in DASY system to align probe sensor X to the robot coordinate system. |

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement*: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - *DC Voltage Measurement Linearity*: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - *Common mode sensitivity*: Influence of a positive or negative common mode voltage on the differential measurement.
 - *Channel separation*: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - *AD Converter Values with inputs shorted*: Values on the internal AD converter corresponding to zero input voltage
 - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
 - *Input Offset Current*: Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - *Input resistance*: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - *Low Battery Alarm Voltage*: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - *Power consumption*: Typical value for information. Supply currents in various operating modes.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = $6.1\mu V$, full range = $-100...+300\text{ mV}$
Low Range: 1LSB = 61nV , full range = $-1.....+3\text{mV}$

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X | Y | Z |
|---------------------|------------------------------------|------------------------------------|------------------------------------|
| High Range | $404.307 \pm 0.02\% \text{ (k=2)}$ | $404.432 \pm 0.02\% \text{ (k=2)}$ | $404.778 \pm 0.02\% \text{ (k=2)}$ |
| Low Range | $3.97786 \pm 1.50\% \text{ (k=2)}$ | $4.00889 \pm 1.50\% \text{ (k=2)}$ | $3.98763 \pm 1.50\% \text{ (k=2)}$ |

Connector Angle

| | |
|---|---------------------------|
| Connector Angle to be used in DASY system | $115.0^\circ \pm 1^\circ$ |
|---|---------------------------|

Appendix (Additional assessments outside the scope of SCS108)**1. DC Voltage Linearity**

| High Range | Reading (μV) | Difference (μV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 199998.08 | 1.14 | 0.00 |
| Channel X + Input | 20000.26 | -0.79 | -0.00 |
| Channel X - Input | -19999.34 | 1.47 | -0.01 |
| Channel Y + Input | 200000.17 | 3.04 | 0.00 |
| Channel Y + Input | 19999.35 | -1.60 | -0.01 |
| Channel Y - Input | -20000.40 | 0.40 | -0.00 |
| Channel Z + Input | 199996.89 | -0.05 | -0.00 |
| Channel Z + Input | 19999.67 | -1.07 | -0.01 |
| Channel Z - Input | -20001.83 | -0.82 | 0.00 |

| Low Range | Reading (μV) | Difference (μV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 2000.78 | -0.15 | -0.01 |
| Channel X + Input | 201.37 | -0.01 | -0.00 |
| Channel X - Input | -198.71 | -0.07 | 0.04 |
| Channel Y + Input | 2001.08 | 0.23 | 0.01 |
| Channel Y + Input | 201.11 | -0.04 | -0.02 |
| Channel Y - Input | -198.95 | -0.16 | 0.08 |
| Channel Z + Input | 2000.69 | -0.17 | -0.01 |
| Channel Z + Input | 200.66 | -0.48 | -0.24 |
| Channel Z - Input | -200.04 | -1.33 | 0.67 |

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Common mode Input Voltage (mV) | High Range Average Reading (μV) | Low Range Average Reading (μV) |
|-----------|-----------------------------------|------------------------------------|-----------------------------------|
| Channel X | 200 | -15.73 | -17.62 |
| | -200 | 17.95 | 16.40 |
| Channel Y | 200 | -5.63 | -5.61 |
| | -200 | 4.75 | 4.70 |
| Channel Z | 200 | -0.98 | -1.03 |
| | -200 | -0.88 | -0.86 |

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Input Voltage (mV) | Channel X (μV) | Channel Y (μV) | Channel Z (μV) |
|-----------|--------------------|----------------|----------------|----------------|
| Channel X | 200 | - | 4.09 | -3.56 |
| Channel Y | 200 | 7.89 | - | 5.02 |
| Channel Z | 200 | 8.61 | 6.69 | - |

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 16112 | 13093 |
| Channel Y | 15985 | 14777 |
| Channel Z | 15881 | 15729 |

5. Input Offset MeasurementDASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec
Input 10MΩ

| | Average (µV) | min. Offset (µV) | max. Offset (µV) | Std. Deviation (µV) |
|-----------|--------------|------------------|------------------|---------------------|
| Channel X | 0.08 | -1.17 | 1.32 | 0.43 |
| Channel Y | -0.58 | -1.57 | 0.70 | 0.47 |
| Channel Z | -0.51 | -1.47 | 1.80 | 0.44 |

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

| | Zeroing (kOhm) | Measuring (MOhm) |
|-----------|----------------|------------------|
| Channel X | 200 | 200 |
| Channel Y | 200 | 200 |
| Channel Z | 200 | 200 |

8. Low Battery Alarm Voltage (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.9 |
| Supply (- Vcc) | -7.6 |

9. Power Consumption (Typical values for information)

| Typical values | Switched off (mA) | Stand by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01 | +6 | +14 |
| Supply (- Vcc) | -0.01 | -8 | -9 |

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di Isolatura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client SGS - TW (Auden)

Certificate No: DAE4-856_Aug14

CALIBRATION CERTIFICATE

Object: DAE4 - SD 000 D04 BM - SN: 856

Calibration procedure(s) QA CAL-06.v26
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: August 27, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration):

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|------------------------------|--------------------|----------------------------|------------------------|
| KellHey Multimeter Type 2001 | SN: 0810278 | 01-Oct-13 (No:13976) | Oct-14 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| Auto DAE Calibration Unit | SE UWS 053 AA 1001 | 07-Jan-14 (in house check) | In house check: Jan-15 |
| Calibrator Box V2.1 | SE UMS 006 AA 1002 | 07-Jan-14 (in house check) | In house check: Jan-15 |

Calibrated by: Dominique Stettler Function: Technician
Approved by: Fin Bomhoff Deputy Technical Manager

Issued: August 27, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: DAE4-856_Aug14

Page 1 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeugmaustrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS).
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates.

Accreditation No.: SCS 108

Glossary

| | |
|-----------------|---|
| DAE | data acquisition electronics |
| Connector angle | information used in DASY system to align probe sensor X to the robot coordinate system. |

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement*: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - *DC Voltage Measurement Linearity*: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - *Common mode sensitivity*: Influence of a positive or negative common mode voltage on the differential measurement.
 - *Channel separation*: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - *AD Converter Values with inputs shorted*: Values on the internal AD converter corresponding to zero input voltage
 - *Input Offset Measurement*: Output voltage and statistical results over a large number of zero voltage measurements.
 - *Input Offset Current*: Typical value for information: Maximum channel input offset current, not considering the input resistance.
 - *Input resistance*: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - *Low Battery Alarm Voltage*: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - *Power consumption*: Typical value for information. Supply currents in various operating modes.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1µV, full range = -100...+300 mV
Low Range: 1LSB = 61nV, full range = -1...+3mV

DASY measurement parameters: Auto Zero Time: 3 sec, Measuring time: 3 sec

| Calibration Factors | X | Y | Z |
|---------------------|----------------------------|----------------------------|----------------------------|
| High Range | $403.468 \pm 0.02\% (k=2)$ | $404.581 \pm 0.02\% (k=2)$ | $403.903 \pm 0.02\% (k=2)$ |
| Low Range | $3.97581 \pm 1.50\% (k=2)$ | $3.97783 \pm 1.50\% (k=2)$ | $3.97815 \pm 1.50\% (k=2)$ |

Connector Angle

| | |
|---|--------------------------|
| Connector Angle to be used in DASY system | $52.5^\circ \pm 1^\circ$ |
|---|--------------------------|

Appendix (Additional assessments outside the scope of SCS108)**1. DC Voltage Linearity**

| High Range | Reading (μV) | Difference (μV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 199998.33 | 0.64 | 0.00 |
| Channel X + Input | 19998.90 | -2.25 | -0.01 |
| Channel X - Input | -20000.45 | 0.34 | -0.00 |
| Channel Y + Input | 199998.95 | 0.98 | 0.00 |
| Channel Y + Input | 19997.51 | -3.82 | -0.02 |
| Channel Y - Input | -20000.77 | 0.07 | -0.00 |
| Channel Z + Input | 199987.26 | -0.19 | -0.00 |
| Channel Z + Input | 19997.65 | -3.57 | -0.02 |
| Channel Z - Input | -20002.47 | -1.55 | 0.01 |

| Low Range | Reading (μV) | Difference (μV) | Error (%) |
|-------------------|--------------|-----------------|-----------|
| Channel X + Input | 2001.05 | -0.09 | -0.00 |
| Channel X + Input | 202.34 | 0.80 | 0.40 |
| Channel X - Input | -198.21 | 0.26 | -0.13 |
| Channel Y + Input | 2001.39 | 0.26 | 0.01 |
| Channel Y + Input | 201.08 | -0.36 | -0.18 |
| Channel Y - Input | -199.24 | -0.78 | 0.39 |
| Channel Z + Input | 2000.92 | -0.18 | -0.01 |
| Channel Z + Input | 200.26 | -1.22 | -0.60 |
| Channel Z - Input | -199.91 | -1.47 | 0.74 |

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Common mode Input Voltage (mV) | High Range Average Reading (μV) | Low Range Average Reading (μV) |
|-----------|-----------------------------------|------------------------------------|-----------------------------------|
| Channel X | 200 | -14.76 | -16.42 |
| | -200 | 17.19 | 15.88 |
| Channel Y | 200 | -2.17 | -2.25 |
| | -200 | 0.36 | 0.61 |
| Channel Z | 200 | 10.27 | 10.05 |
| | -200 | -13.06 | -13.03 |

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | Input Voltage (mV) | Channel X (μV) | Channel Y (μV) | Channel Z (μV) |
|-----------|--------------------|----------------|----------------|----------------|
| Channel X | 200 | - | 2.81 | -1.15 |
| Channel Y | 200 | 7.93 | - | 3.07 |
| Channel Z | 200 | 8.55 | 5.24 | - |

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| | High Range (LSB) | Low Range (LSB) |
|-----------|------------------|-----------------|
| Channel X | 16226 | 16620 |
| Channel Y | 15942 | 16803 |
| Channel Z | 15875 | 16811 |

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10MΩ

| | Average (µV) | min. Offset (µV) | max. Offset (µV) | Std. Deviation (µV) |
|-----------|--------------|------------------|------------------|---------------------|
| Channel X | 0.72 | -0.77 | 1.69 | 0.38 |
| Channel Y | -0.24 | -1.57 | 1.49 | 0.42 |
| Channel Z | -0.98 | -2.01 | 0.07 | 0.40 |

6. Input Offset Current

Nominal input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

| | Zeroing (kOhm) | Measuring (MOhm) |
|-----------|----------------|------------------|
| Channel X | 200 | 200 |
| Channel Y | 200 | 200 |
| Channel Z | 200 | 200 |

8. Low Battery Alarm Voltage (Typical values for information)

| Typical values | Alarm Level (VDC) |
|----------------|-------------------|
| Supply (+ Vcc) | +7.8 |
| Supply (- Vcc) | -7.6 |

9. Power Consumption (Typical values for information)

| Typical values | Switched off (mA) | Stand by (mA) | Transmitting (mA) |
|----------------|-------------------|---------------|-------------------|
| Supply (+ Vcc) | +0.01 | +8 | +14 |
| Supply (- Vcc) | -0.01 | -8 | -8 |

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8034 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'évaluation
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No: SCS 108

Client: SGS-TW (Auden)

Certificate No: EX3-3923_Aug14

CALIBRATION CERTIFICATE

Object: EX3DV4 - SN:3923

Calibration procedure(s): QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes

Calibration date: August 28, 2014

The calibration certificate documents the traceability to national standards, which realize the physical units of measurements (S).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID | Cal Date (Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|-----------------------------------|-----------------------|
| Power meter E44198 | GD41293874 | 03-Apr-14 (No. 217-01911) | Apr-15 |
| Power meter E4412A | MY41498087 | 03-Apr-14 (No. 217-01911) | Apr-15 |
| Reference 3 dB Attenuator | SN: 85064 (3u) | 03-Apr-14 (No. 217-01915) | Apr-15 |
| Reference 20 dB Attenuator | SN: 85277 (20u) | 03-Apr-14 (No. 217-01919) | Apr-15 |
| Reference 30 dB Attenuator | SN: 85129 (30u) | 03-Apr-14 (No. 217-01920) | Apr-15 |
| Reference Probe E83DV2 | SN: 3013 | 30-Dec-13 (No. E83-3013_Dec13) | Dec-14 |
| DAE4 | SN: 660 | 13-Dec-13 (No. DAE4-660 Dec13) | Dec-14 |
| Secondary Standards | ID | Check Date (in house) | Scheduled Check |
| RF generator HP 8648C | US3642U01700 | 4-Aug-99 (in house check Apr-13) | In house check Apr-16 |
| Network Analyzer HP 8753E | US37390585 | 18-Oct-01 (in house check Oct-13) | In house check Oct-14 |

| Calibrated by: | Name | Function | Signature |
|----------------|----------------------|-----------------------|-----------|
| | Stephane L. - Valout | Laboratory Technician | |
| Approved by: | Kathy Lekewo | Technical Manager | |

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Issued: August 28, 2014

Certificate No: EX3-3923_Aug14

Page 1 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zürcherstrasse 43, 8004 Zürich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di servizi
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the ECE
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

| | |
|-----------------------|---|
| TSL | tissue simulating liquid |
| NORM _{x,y,z} | sensitivity in free space |
| ConvF | sensitivity in TSL / NORM _{x,y,z} |
| DOP | diode compression point |
| CF | crest factor (1/duty_cycle) of the RF signal |
| A, B, C, D | modulation dependent linearization parameters |
| Polarization α | rotation around probe axis |
| Polarization β | rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\beta = 0$ is normal to probe axis |
| Connector Angle | information used in DASY system to align probe sensor X to the robot coordinate system |

Calibration is Performed According to the Following Standards:

- IEEE Std 1526-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\beta = 0$ ($\beta = 100$ MHz in TEM-cell; $\beta > 1000$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E-field uncertainty inside TSL (see below ConvF).
- NORM_{(f)x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DOP_{x,y,z}: DOP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DOP does not depend on frequency nor media.
- PAR: PAR is the Peak In Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}, B_{x,y,z}, C_{x,y,z}, D_{x,y,z}: VR_{x,y,z} A, B, C, D are numerical linearization parameters assessed based on the data of power sweeps for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $\beta \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $\beta > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_{x,y,z} (no uncertainty required).

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4 - SOURCE

Report No. 155

Probe EX3DV4

SN:3923

Manufactured: March 8, 2013
Calibrated: August 28, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

Certificate No: EX3DV4-3923_Aug14

Page 1 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wukoo District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

EX3DV4-SN:3923

August 20, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923**Basic Calibration Parameters**

| | Sensor X | Sensor Y | Sensor Z | Unc. (k=2) |
|---|----------|----------|----------|--------------|
| Norm ($\mu\text{V}/(\text{V}/\text{m})^{0.5}$) ^a | 0.58 | 0.48 | 0.47 | $\pm 10.1\%$ |
| DCLP (mV) ^b | 99.2 | 102.3 | 103.3 | |

Modulation Calibration Parameters

| UID | Communication System Name | A dB | B dB/ μV | C | D dB | VR mV | Unc ^c (k=2) |
|-----|---------------------------|---------|------------------------|-----|---------|----------|---------------------------|
| 0 | EW | X | 0.0 | 0.0 | 1.0 | 0.00 | 132.9 $\pm 1.0\%$ |
| | | Y | 0.0 | 0.0 | 1.0 | | 134.8 |
| | | Z | 0.0 | 0.0 | 1.0 | | 135.0 |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^a The uncertainties of NormX,Y,Z do not affect the E-field uncertainty inside TEC (see Pages 5 and 6).

^b Nominal measurement parameter uncertainty not required.

^c Uncertainty is determined using the rank deviation from linear response applying rectangular estimation and is expressed for the square of the true value.

EX3DV4-SN:3923

August 20, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923

Calibration Parameter Determined in Head Tissue Simulating Media

| F (MHz) ^a | Relative Permittivity ^b | Conductivity (S/m) ^c | ConvF X | ConvF Y | ConvF Z | Alpha ^d | Depth ^e (mm) | Uncrt. (n=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------|
| 750 | 41.9 | 0.89 | 10.91 | 10.91 | 10.91 | 0.26 | 1.16 | ± 12.0 % |
| 835 | 41.5 | 0.90 | 10.48 | 10.48 | 10.48 | 0.27 | 1.07 | ± 12.0 % |
| 900 | 41.5 | 0.87 | 10.26 | 10.26 | 10.26 | 0.17 | 1.53 | ± 12.0 % |
| 1750 | 40.1 | 1.37 | 8.72 | 8.72 | 8.72 | 0.75 | 0.57 | ± 12.0 % |
| 1900 | 40.0 | 1.40 | 8.42 | 8.42 | 8.42 | 0.45 | 0.77 | ± 12.0 % |
| 2000 | 40.0 | 1.40 | 8.46 | 8.46 | 8.46 | 0.67 | 0.83 | ± 12.0 % |
| 2300 | 38.5 | 1.67 | 8.02 | 8.02 | 8.02 | 0.35 | 0.66 | ± 12.0 % |
| 2450 | 39.2 | 1.80 | 7.66 | 7.66 | 7.66 | 0.33 | 0.87 | ± 12.0 % |
| 2600 | 39.0 | 1.96 | 7.41 | 7.41 | 7.41 | 0.35 | 0.86 | ± 12.0 % |
| 5200 | 36.0 | 4.88 | 5.17 | 5.17 | 5.17 | 0.35 | 1.80 | ± 13.1 % |
| 5300 | 35.9 | 4.76 | 4.99 | 4.99 | 4.99 | 0.35 | 1.80 | ± 13.1 % |
| 5600 | 35.5 | 5.07 | 4.71 | 4.71 | 4.71 | 0.40 | 1.80 | ± 13.1 % |
| 5800 | 35.3 | 5.27 | 4.67 | 4.67 | 4.67 | 0.40 | 1.80 | ± 13.1 % |

^a Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the employed frequency band. Frequency validity below 300 MHz (i.e. 10, 25, 40, 50 and 70 MHz for ConvF measurements at 30, 60, 125, 150 and 220 MHz respectively). Above ± 5 GHz frequency validity can be extended to ± 110 MHz.

^b At frequencies below 3 GHz, the validity of tissue parameters (i- and n) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (i- and n) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^c Alpha/Depth are determined during calibration. SPMAG warrants that the scattering behavior due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923**Calibration Parameter Determined in Body Tissue Simulating Media**

| f (MHz) ^a | Relative Permittivity ^b | Conductivity (S/m) ^c | ConvF X | ConvF Y | ConvF Z | Alpha ^d | Depth ^e (mm) | Uncrt. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------|
| 750 | 55.5 | 0.96 | 10.29 | 10.29 | 10.29 | 0.30 | 1.04 | ± 12.0 % |
| 835 | 55.2 | 0.97 | 10.32 | 10.32 | 10.32 | 0.55 | 0.78 | ± 12.0 % |
| 900 | 55.0 | 1.05 | 10.04 | 10.04 | 10.04 | 0.44 | 0.88 | ± 12.0 % |
| 1750 | 53.4 | 1.49 | 8.30 | 8.30 | 8.30 | 0.39 | 0.85 | ± 12.0 % |
| 1900 | 53.3 | 1.52 | 8.03 | 8.03 | 8.03 | 0.30 | 0.95 | ± 12.0 % |
| 2000 | 53.3 | 1.52 | 8.16 | 8.16 | 8.16 | 0.23 | 1.16 | ± 12.0 % |
| 2300 | 52.9 | 1.01 | 7.76 | 7.76 | 7.76 | 0.44 | 0.77 | ± 12.0 % |
| 2450 | 52.7 | 1.95 | 7.56 | 7.56 | 7.56 | 0.80 | 0.50 | ± 12.0 % |
| 2600 | 52.5 | 2.16 | 7.36 | 7.36 | 7.36 | 0.80 | 0.50 | ± 12.0 % |
| 5200 | 49.0 | 5.30 | 4.71 | 4.71 | 4.71 | 0.35 | 1.90 | ± 13.1 % |
| 5300 | 48.9 | 5.42 | 4.58 | 4.58 | 4.58 | 0.35 | 1.90 | ± 13.1 % |
| 5600 | 48.5 | 5.77 | 4.09 | 4.09 | 4.09 | 0.40 | 1.90 | ± 13.1 % |
| 5800 | 48.2 | 6.00 | 4.33 | 4.33 | 4.33 | 0.40 | 1.90 | ± 13.1 % |


^a Frequency validity above 300 MHz of ± 10% only applies for DASY v4.4 and higher (see Page 2), when it is corrected to ± 50 MHz. The uncertainty is the RSD of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF measurements at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be expected to ± 110 MHz.

All frequencies below 3 GHz, the validity of tissue parameters (α and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SVA values. All frequencies above 3 GHz, the validity of tissue parameters (α and σ) is restricted to ± 5%. The uncertainty is the RSD of the ConvF uncertainty for indicated target tissue parameters.

^b AlphaDepth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-8 GHz at any distance larger than half the probe tip diameter from the boundary.

EX30V4- SN:3923

August 28, 2014

Frequency Response of E-Field
(TEM-Cell:if110 EXX, Waveguide: R22)Uncertainty of Frequency Response of E-field: $\pm 6.3\% (k=2)$

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX3DV4-SN:3823


August 26, 2014

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz, TEM





f=1800 MHz, R22



EX3DV4- SN:3923

August 26, 2014

**Dynamic Range f(SAR_{head})
(TEM cell, f_{eval}= 1900 MHz)**Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX30V4- SN:3923

August 29, 2014

Conversion Factor Assessment

Deviation from Isotropy in Liquid
Error (ϕ , θ), $f = 900$ MHz

Certificate No: EX3-3923_Aug14

Page 10 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

EXODV4-SN3923

August 26, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3923**Other Probe Parameters**

| | |
|---|------------|
| Sensor Arrangement: | Triangular |
| Connector Angle (°) | -57 |
| Mechanical Surface Detection Mode | enabled |
| Optical Surface Detection Mode | disabled |
| Probe Overall Length | 337 mm |
| Probe Body Diameter | 10 mm |
| Tip Length | 9 mm |
| Tip Diameter | 2.5 mm |
| Probe Tip to Sensor X Calibration Point | 1 mm |
| Probe Tip to Sensor Y Calibration Point | 1 mm |
| Probe Tip to Sensor Z Calibration Point | 1 mm |
| Recommended Measurement Distance from Surface | 1.4 mm |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client SGS-TW (Auden)

Certificate No: EX3-3831_Jan14

CALIBRATION CERTIFICATE

Object EX3DV4 - SN:3831

Calibration procedure(s) QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes

Calibration date: January 31, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID | Cal Date (Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|--------------------------------|-----------------------|
| Power meter E4419B | GB41293874 | 04-Apr-13 (No. 217-01733) | Apr-14 |
| Power sensor E4412A | MY41498087 | 04-Apr-13 (No. 217-01733) | Apr-14 |
| Reference 3 dB Attenuator | SN: S6054 (3c) | 04-Apr-13 (No. 217-01737) | Apr-14 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735) | Apr-14 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738) | Apr-14 |
| Reference Probe ES3DV2 | SN: 3013 | 30-Dec-13 (No. E83-3013_Dec13) | Dec-14 |
| DAE4 | SN: 660 | 13-Dec-13 (No. DAE4-660_Dec13) | Dec-14 |

| Secondary Standards | ID | Check Date (in house) | Scheduled Check |
|---------------------------|--------------|-----------------------------------|------------------------|
| RF generator HP 8648C | US3642U01700 | 4-Aug-99 (in house check Apr-13) | In house check: Apr-16 |
| Network Analyzer HP 8753E | US37390585 | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

Calibrated by: Name: Issam El-Nawari Function: Laboratory Technician Signature:

Approved by: Name: Ketja Pokovic Function: Technical Manager Signature:

Issued: January 31, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-3831_Jan14

Page 1 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

| | |
|-----------------------|--|
| TSL | tissue simulating liquid |
| NORM _{x,y,z} | sensitivity in free space |
| ConvF | sensitivity in TSL / NORM _{x,y,z} |
| DCP | diode compression point |
| CF | crest factor (1/duty_cycle) of the RF signal |
| A, B, C, D | modulation dependent linearization parameters |
| Polarization ϕ | ϕ rotation around probe axis |
| Polarization θ | θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle | information used in DASY system to align probe sensor X to the robot coordinate system |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}:** Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)x,y,z = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}:** A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical Isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

EX3DV4 – SN:3831

January 31, 2014

Probe EX3DV4

SN:3831

Manufactured: September 6, 2011
Calibrated: January 31, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

Certificate No: EX3-3831_Jan14

Page 3 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

EX3DV4- SN:3831

January 31, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831

Basic Calibration Parameters

| | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|------------------------------------|----------|----------|----------|--------------|
| Norm (μ V/(V/m)) ^a | 0.45 | 0.42 | 0.43 | \pm 10.1 % |
| DCP (mV) ^b | 102.4 | 100.1 | 97.7 | |

Modulation Calibration Parameters

| UID | Communication System Name | | A dB | B dB $\sqrt{\mu}$ V | C | D dB | VR mV | Unc ^c (k=2) |
|-----|---------------------------|---|---------|------------------------|-----|---------|----------|---------------------------|
| 0 | CW | X | 0.0 | 0.0 | 1.0 | 0.00 | 153.1 | \pm 3.0 % |
| | | Y | 0.0 | 0.0 | 1.0 | | 146.3 | |
| | | Z | 0.0 | 0.0 | 1.0 | | 154.8 | |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^a The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^b Numerical linearization parameter: uncertainty not required.

^c Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831**Calibration Parameter Determined in Head Tissue Simulating Media**

| f (MHz) ^c | Relative Permittivity ^f | Conductivity (S/m) ^g | ConvF X | ConvF Y | ConvF Z | Alpha ^g | Depth ^g (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750 | 41.9 | 0.89 | 9.59 | 9.59 | 9.59 | 0.74 | 0.64 | ± 12.0 % |
| 835 | 41.5 | 0.90 | 9.14 | 9.14 | 9.14 | 0.22 | 1.36 | ± 12.0 % |
| 900 | 41.5 | 0.97 | 9.17 | 9.17 | 9.17 | 0.28 | 0.96 | ± 12.0 % |
| 1750 | 40.1 | 1.37 | 8.00 | 8.00 | 8.00 | 0.26 | 0.99 | ± 12.0 % |
| 1900 | 40.0 | 1.40 | 7.79 | 7.79 | 7.79 | 0.60 | 0.65 | ± 12.0 % |
| 2000 | 40.0 | 1.40 | 7.71 | 7.71 | 7.71 | 0.39 | 0.79 | ± 12.0 % |
| 2300 | 39.5 | 1.67 | 7.35 | 7.35 | 7.35 | 0.43 | 0.76 | ± 12.0 % |
| 2450 | 39.2 | 1.80 | 6.99 | 6.99 | 6.99 | 0.37 | 0.85 | ± 12.0 % |
| 2600 | 39.0 | 1.96 | 6.62 | 6.62 | 6.62 | 0.38 | 0.87 | ± 12.0 % |
| 5200 | 36.0 | 4.66 | 4.67 | 4.67 | 4.67 | 0.35 | 1.80 | ± 13.1 % |
| 5300 | 35.9 | 4.76 | 4.41 | 4.41 | 4.41 | 0.40 | 1.80 | ± 13.1 % |
| 5600 | 35.5 | 5.07 | 3.99 | 3.99 | 3.99 | 0.50 | 1.80 | ± 13.1 % |
| 5800 | 35.3 | 5.27 | 4.12 | 4.12 | 4.12 | 0.45 | 1.80 | ± 13.1 % |

^c Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^f At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831**Calibration Parameter Determined in Body Tissue Simulating Media**

| f (MHz) ^C | Relative Permittivity ^F | Conductivity (S/m) ^F | ConvF X | ConvF Y | ConvF Z | Alpha ^G | Depth ^H (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750 | 55.5 | 0.96 | 9.10 | 9.10 | 9.10 | 0.50 | 0.80 | ± 12.0 % |
| 835 | 55.2 | 0.97 | 9.03 | 9.03 | 9.03 | 0.28 | 1.15 | ± 12.0 % |
| 900 | 55.0 | 1.05 | 8.84 | 8.84 | 8.84 | 0.29 | 1.08 | ± 12.0 % |
| 1750 | 53.4 | 1.49 | 7.63 | 7.63 | 7.63 | 0.26 | 1.16 | ± 12.0 % |
| 1900 | 53.3 | 1.52 | 7.19 | 7.19 | 7.19 | 0.32 | 1.01 | ± 12.0 % |
| 2000 | 53.3 | 1.52 | 7.17 | 7.17 | 7.17 | 0.44 | 0.83 | ± 12.0 % |
| 2300 | 52.9 | 1.81 | 6.90 | 6.90 | 6.90 | 0.52 | 0.76 | ± 12.0 % |
| 2450 | 52.7 | 1.95 | 6.68 | 6.68 | 6.68 | 0.80 | 0.56 | ± 12.0 % |
| 2600 | 52.5 | 2.16 | 6.50 | 6.50 | 6.50 | 0.80 | 0.50 | ± 12.0 % |
| 5200 | 49.0 | 5.30 | 4.08 | 4.08 | 4.08 | 0.50 | 1.90 | ± 13.1 % |
| 5300 | 48.9 | 5.42 | 3.87 | 3.87 | 3.87 | 0.50 | 1.90 | ± 13.1 % |
| 5600 | 48.5 | 5.77 | 3.36 | 3.36 | 3.36 | 0.60 | 1.90 | ± 13.1 % |
| 5800 | 48.2 | 6.00 | 3.78 | 3.78 | 3.78 | 0.55 | 1.90 | ± 13.1 % |


^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3831

January 31, 2014




Frequency Response of E-Field
(TEM-Cell:ifi110 EXX, Waveguide: R22)Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.




SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Receiving Pattern (ϕ), $\theta = 0^\circ$ $f=600 \text{ MHz, TEM}$  $f=1800 \text{ MHz, R22}$ 

Dynamic Range f(SAR_{head})
(TEM cell, f = 900 MHz)**Uncertainty of Linearity Assessment: $\pm 0.6\% (k=2)$**

EX3DV4- SN:3831

January 31, 2014

Conversion Factor Assessment $f = 835 \text{ MHz, WG}LS \text{ R9 (H_convF)}$  $f = 1900 \text{ MHz, WG}LS \text{ R22 (H_convF)}$ **Deviation from Isotropy in Liquid**Error (ϕ, θ), $f = 900 \text{ MHz}$ 

Certificate No: EX3-3831_Jan14

Page 10 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

EX3DV4- SN:3831

January 31, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3831

Other Probe Parameters

| | |
|---|------------|
| Sensor Arrangement | Triangular |
| Connector Angle (°) | -20.6 |
| Mechanical Surface Detection Mode | enabled |
| Optical Surface Detection Mode | disabled |
| Probe Overall Length | 337 mm |
| Probe Body Diameter | 10 mm |
| Tip Length | 9 mm |
| Tip Diameter | 2.5 mm |
| Probe Tip to Sensor X Calibration Point | 1 mm |
| Probe Tip to Sensor Y Calibration Point | 1 mm |
| Probe Tip to Sensor Z Calibration Point | 1 mm |
| Recommended Measurement Distance from Surface | 2 mm |

Certificate No: EX3-3831_Jan14

Page 11 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di isettura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: SGS-TW (Auden)

Certificate No.: EX3-3770_Apr14

CALIBRATION CERTIFICATE

Object: EX3DV4 - SN: 3770

Calibration procedure: QA CAL-01.v8, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes

Calibration date: April 24, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (WATEC critical for calibration)

| Primary Standards | ID | Cal Date (Certificate No.) | Scheduled Calibration |
|----------------------------|-----------------|----------------------------------|-----------------------|
| Power meter E4419B | GB41293874 | 03-Apr-14 (No. 217-01911) | Apr-15 |
| Power sensor E4412A | MY414930097 | 03-Apr-14 (No. 217-01911) | Apr-15 |
| Reference 3 dB Attenuator | SN: 38054 (3c) | 03-Apr-14 (No. 217-01915) | Apr-15 |
| Reference 20 dB Attenuator | SN: 38277 (20a) | 03-Apr-14 (No. 217-01919) | Apr-15 |
| Reference 30 dB Attenuator | SN: 55129 (00b) | 03-Apr-14 (No. 217-01920) | Apr-15 |
| Reference Probe E33DV2 | SN: 3913 | 30-Dec-13 (No. E53-3013_Dic13) | Dec-14 |
| DNE4 | SN: 660 | 13-Dec-13 (No. DNE4-660 (Dec13)) | Dec-14 |

| Secondary Standards | ID | Check Date (in house) | Scheduled Check |
|---------------------------|--------------|-----------------------------------|------------------------|
| RF generator HP 8848C | US3842U01700 | 4-Aug-09 (in house check Apr-13) | In house check: Apr-15 |
| Network Analyzer HP 8753E | US37390566 | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

Calibrated by: Name: Jason Kastell Function: Laboratory Technician Signature:

Approved by: Name: Kaja Polnic Function: Technical Manager Signature:

Issued: April 24, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No.: EX3-3770_Apr14

Page 1 of 11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

| | |
|------------------------|---|
| TSL | tissue simulating liquid |
| NORM _{x,y,z} | sensitivity in free space |
| ConvF | sensitivity in TSL / NORM _{x,y,z} |
| DCP | diode compression point |
| CF | crest factor (1/duty_cycle) of the RF signal |
| A, B, C, D | modulation dependent linearization parameters |
| Polarization φ | φ rotation around probe axis |
| Polarization θ | θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle | information used in DASY system to align probe sensor X to the robot coordinate system |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- $NORM_{x,y,z}$: Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). $NORM_{x,y,z}$ are only intermediate values, i.e., the uncertainties of $NORM_{x,y,z}$ does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- $NORM(f)_{x,y,z} = NORM_{x,y,z} * \text{frequency_response}$ (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- $A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}$: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters*: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to $NORM_{x,y,z} * ConvF$ whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical Isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle*: The angle is assessed using the information gained by determining the $NORM_x$ (no uncertainty required).

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4 – SN:3770

April 24, 2014

Probe EX3DV4

SN:3770

Manufactured: July 6, 2010
Calibrated: April 24, 2014

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX3DV4-SN:3770

April 24, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3770**Basic Calibration Parameters**

| | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|---|----------|----------|----------|--------------|
| Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A | 0.31 | 0.61 | 0.40 | $\pm 10.1\%$ |
| DCP (mV) ^B | 104.0 | 96.9 | 102.5 | |

Modulation Calibration Parameters

| UID | Communication System Name | | A dB | B dB $\sqrt{\mu\text{V}}$ | C | D dB | VR mV | Unc ^C (k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0 | CW | X | 0.0 | 0.0 | 1.0 | 0.00 | 141.8 | $\pm 3.5\%$ |
| | | Y | 0.0 | 0.0 | 1.0 | | 132.9 | |
| | | Z | 0.0 | 0.0 | 1.0 | | 135.7 | |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 6 and 8).^B Numerical linearization parameter: uncertainty not required.^C Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4-SN-3770

April 24, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3770

Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) ^c | Relative Permittivity ^f | Conductivity (S/m) ^f | ConvF X | ConvF Y | ConvF Z | Alpha ^g | Depth ^h (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750 | 41.9 | 0.89 | 9.70 | 9.70 | 9.70 | 0.27 | 1.09 | ± 12.0 % |
| 835 | 41.5 | 0.90 | 9.32 | 9.32 | 9.32 | 0.52 | 0.77 | ± 12.0 % |
| 900 | 41.5 | 0.97 | 9.16 | 9.16 | 9.16 | 0.14 | 1.68 | ± 12.0 % |
| 1750 | 40.1 | 1.37 | 8.08 | 8.08 | 8.08 | 0.28 | 0.92 | ± 12.0 % |
| 1900 | 40.0 | 1.40 | 7.79 | 7.79 | 7.79 | 0.36 | 0.81 | ± 12.0 % |
| 2000 | 40.0 | 1.40 | 7.75 | 7.75 | 7.75 | 0.40 | 0.78 | ± 12.0 % |
| 2300 | 39.5 | 1.57 | 7.35 | 7.35 | 7.35 | 0.26 | 0.95 | ± 12.0 % |
| 2450 | 39.2 | 1.80 | 6.97 | 6.97 | 6.97 | 0.35 | 0.82 | ± 12.0 % |
| 2600 | 39.0 | 1.96 | 6.73 | 6.73 | 6.73 | 0.45 | 0.73 | ± 12.0 % |
| 5200 | 36.0 | 4.86 | 5.25 | 5.25 | 5.25 | 0.35 | 1.80 | ± 13.1 % |
| 5300 | 35.9 | 4.76 | 5.07 | 5.07 | 5.07 | 0.35 | 1.80 | ± 13.1 % |
| 5600 | 35.5 | 5.07 | 4.48 | 4.48 | 4.48 | 0.45 | 1.80 | ± 13.1 % |
| 5800 | 35.3 | 5.27 | 4.65 | 4.65 | 4.65 | 0.45 | 1.80 | ± 13.1 % |

^c Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 60 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.^f At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.


DASY/EASY - Parameters of Probe: EX3DV4 - SN:3770**Calibration Parameter Determined in Body Tissue Simulating Media**

| f (MHz) ^c | Relative Permittivity ^f | Conductivity (S/m) ^f | ConvF X | ConvF Y | ConvF Z | Alpha ^g | Depth ^g (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750 | 55.5 | 0.96 | 9.54 | 9.54 | 9.54 | 0.53 | 0.79 | ± 12.0 % |
| 835 | 55.2 | 0.97 | 9.40 | 9.40 | 9.40 | 0.19 | 1.60 | ± 12.0 % |
| 900 | 55.0 | 1.05 | 9.23 | 9.23 | 9.23 | 0.27 | 1.20 | ± 12.0 % |
| 1750 | 53.4 | 1.49 | 7.79 | 7.79 | 7.79 | 0.37 | 0.87 | ± 12.0 % |
| 1900 | 53.3 | 1.52 | 7.51 | 7.51 | 7.51 | 0.47 | 0.78 | ± 12.0 % |
| 2000 | 53.3 | 1.52 | 7.59 | 7.59 | 7.59 | 0.61 | 0.69 | ± 12.0 % |
| 2300 | 52.9 | 1.81 | 7.27 | 7.27 | 7.27 | 0.60 | 0.69 | ± 12.0 % |
| 2450 | 52.7 | 1.95 | 7.15 | 7.15 | 7.15 | 0.52 | 0.72 | ± 12.0 % |
| 2600 | 52.5 | 2.16 | 6.90 | 6.90 | 6.90 | 0.80 | 0.50 | ± 12.0 % |
| 5200 | 49.0 | 5.30 | 4.56 | 4.56 | 4.56 | 0.50 | 1.90 | ± 13.1 % |
| 5300 | 48.9 | 5.42 | 4.38 | 4.38 | 4.38 | 0.50 | 1.90 | ± 13.1 % |
| 5600 | 48.5 | 5.77 | 3.76 | 3.76 | 3.76 | 0.55 | 1.90 | ± 13.1 % |
| 5800 | 48.2 | 6.00 | 4.13 | 4.13 | 4.13 | 0.55 | 1.90 | ± 13.1 % |

^c Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-8 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3770

April 24, 2014

Frequency Response of E-Field
(TEM-Cell:ifi110 EXX, Waveguide: R22)Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX3DV4—SN:3770


April 24, 2014

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz, TEM



f=1800 MHz, R22



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX3DV4-SN:3770

April 24, 2014

Dynamic Range f(SAR_{head})
(TEM cell, f_{eval}= 1900 MHz)Uncertainty of Linearity Assessment: $\pm 0.6\% (k=2)$



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX3DV4-SN-3770

April 24, 2014

Conversion Factor Assessment**Deviation from Isotropy in Liquid**Error (ϕ , θ), $f = 900$ MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

EX3DV4- SN:3770

April 24, 2014

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3770

Other Probe Parameters

| | |
|---|------------|
| Sensor Arrangement | Triangular |
| Connector Angle (") | -34.3 |
| Mechanical Surface Detection Mode | enabled |
| Optical Surface Detection Mode | disabled |
| Probe Overall Length | 337 mm |
| Probe Body Diameter | 10 mm |
| Tip Length | 9 mm |
| Tip Diameter | 2.5 mm |
| Probe Tip to Sensor X Calibration Point | 1 mm |
| Probe Tip to Sensor Y Calibration Point | 1 mm |
| Probe Tip to Sensor Z Calibration Point | 1 mm |
| Recommended Measurement Distance from Surface | 2 mm |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

8. Uncertainty Budget

Measurement Uncertainty evaluation template for DUT SAR test
 IEEE 1528

| A | c | D | e | f | g | h=c * f / e | i=c * g / e | k |
|--|--------------------------------|-----------------------------|------------|---------|----------|-------------------------|-------------------------|----------------|
| Source of Uncertainty | Tolerance/ Uncertainty % | Probability Distribution | Div | ci (1g) | ci (10g) | Standard uncertainty | Standard uncertainty | vi, or Veff |
| Measurement system | | | | | | | | |
| Probe calibration(under 6Ghz) | 6.55% | N | 1 | 1 | 1 | 6.55% | 6.55% | ∞ |
| <i>Isotropy, Axial</i> | 3.50% | R | $\sqrt{3}$ | 1 | 1 | 2.02% | 2.02% | ∞ |
| <i>Isotropy, Hemispherical</i> | 9.60% | R | $\sqrt{3}$ | 1 | 1 | 5.54% | 5.54% | ∞ |
| Boundary Effect | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.58% | 0.58% | ∞ |
| Linearity | 4.70% | R | $\sqrt{3}$ | 1 | 1 | 2.71% | 2.71% | ∞ |
| Detection Limits | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.58% | 0.58% | ∞ |
| Readout Electronics | 0.30% | N | 1 | 1 | 1 | 0.30% | 0.30% | ∞ |
| Response time | 0.80% | R | $\sqrt{3}$ | 1 | 1 | 0.46% | 0.46% | ∞ |
| Integration Time | 2.60% | R | $\sqrt{3}$ | 1 | 1 | 1.50% | 1.50% | ∞ |
| <i>Measurement drift (class A evaluation)</i> | 1.75% | R | $\sqrt{3}$ | 1 | 1 | 1.01% | 1.01% | ∞ |
| RF ambient condition - noise | 3.00% | R | $\sqrt{3}$ | 1 | 1 | 1.73% | 1.73% | ∞ |
| RF ambient conditions -reflections | 3.00% | R | $\sqrt{3}$ | 1 | 1 | 1.73% | 1.73% | ∞ |
| Probe positioner Mechanical restrictions | 0.40% | R | $\sqrt{3}$ | 1 | 1 | 0.23% | 0.23% | ∞ |
| Probe Positioning with respect to phantom | 2.90% | R | $\sqrt{3}$ | 1 | 1 | 1.67% | 1.67% | ∞ |
| Post-processing | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.58% | 0.58% | ∞ |
| Max SAR Eval | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.58% | 0.58% | ∞ |
| Test Sample related | | | | | | | | |
| Test sample | 2.90% | N | 1 | 1 | 1 | 2.90% | 2.90% | M-1 |
| Device Holder Uncertainty | 3.60% | N | 1 | 1 | 1 | 3.60% | 3.60% | M-1 |
| Drift of output power | 5.00% | R | $\sqrt{3}$ | 1 | 1 | 2.89% | 2.89% | ∞ |
| Phantom and Setup | | | | | | | | |
| Phantom Uncertainty | 4.00% | R | $\sqrt{3}$ | 1 | 1 | 2.31% | 2.31% | ∞ |
| Liquid conductivity(meas.) | 4.98% | N | 1 | 0.64 | 0.43 | 3.19% | 2.14% | M |
| Liquid permittivity(meas.) | 4.80% | N | 1 | 0.6 | 0.49 | 2.88% | 2.35% | M |
| Combined standard uncertainty | | RSS | | | | 12.34% | 12.00% | |
| Expan uncertainty (95% confidence interval), K=2 | | | | | | 24.68% | 24.00% | |

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

9. Phantom Description

Schmid & Partner Engineering AG

s p e a gZeughausstrasse 43, 8004 Zurich, Switzerland
Phone +41 1 245 9700, Fax +41 1 245 9778
info@speag.com, http://www.speag.com**Certificate of Conformity / First Article Inspection**

| | |
|--------------|--|
| Item | SAM Twin Phantom V4.0 |
| Type No. | QD 000 P40 C |
| Series No. | TP-1150 and higher |
| Manufacturer | SPEAG Zeughausstrasse 43 CH-8004 Zurich Switzerland |

Tests

The series production process used allows the limitation to test of first articles.
Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series items (called samples) or are tested at each item.

| Test | Requirement | Details | Units tested |
|-----------------------------|--|--|---|
| Dimensions | Compliant with the geometry according to the CAD model. | IT'IS CAD File (*) | First article, Samples |
| Material thickness of shell | Compliant with the requirements according to the standards | 2mm +/- 0.2mm in flat and specific areas of head section | First article, Samples, TP-1314 fl. |
| Material thickness at ERP | Compliant with the requirements according to the standards | 6mm +/- 0.2mm at ERP | First article, All items |
| Material parameters | Dielectric parameters for required frequencies | 300 MHz - 6 GHz: Relative permittivity < 5, Loss tangent < 0.05 | Material samples |
| Material resistivity | The material has been tested to be compatible with the liquids defined in the standards if handled and cleaned according to the instructions. Observe technical Note for material compatibility. | DEGMBe based simulating liquids | Pre-series, First article, Material samples |
| Sagging | Compliant with the requirements according to the standards. Sagging of the flat section when filled with tissue simulating liquid. | < 1% typical < 0.8% if filled with 155mm of HSL900 and without DUT below | Prototypes, Sample testing |

Standards

- [1] CENELEC EN 50361
- [2] IEEE Std 1528-2003
- [3] IEC 62209 Part 1
- [4] FCC OET Bulletin 65, Supplement C, Edition 01-01

(*) The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of the other documents.

Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standards [1] to [4].

Date 07.07.2005

s p e a gSchmid & Partner Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland
Phone +41 1 245 9700, Fax +41 1 245 9778
info@speag.com, http://www.speag.com

Doc No. 881 - QD 000 P40 C - F

Page 1/1

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

10. System Validation from Original Equipment Supplier

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**Client **SGS-TW (Auden)**Certificate No: **D835V2-4d063_Aug14**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d063**Calibration procedure(s) **QA CAL-05.v9**
Calibration procedure for dipole validation kits above 700 MHzCalibration date: **August 28, 2014**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (MUST be critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A | GB37480704 | 04-Oct-13 (No. 217-01627) | Oct-14 |
| Power sensor HP 8461A | US37292783 | 09-Oct-13 (No. 217-01827) | Oct-14 |
| Power sensor HP 8481A | MY41092317 | 09-Oct-13 (No. 217-01828) | Oct-14 |
| Reference 20 dB Attenuator | SN: 5006 (20K) | 03-Apr-14 (No. 217-01816) | Apr-15 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 03-Apr-14 (No. 217-01821) | Apr-15 |
| Reference Probe E830V1 | SN: 3205 | 30-Dec-13 (No. E83-3205_Dic13) | Dec-14 |
| DAE4 | SN: 601 | 18-Aug-14 (No. DAE4-601_Aug14) | Aug-15 |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
| RF generator R&S SMT-06 | 100005 | 04-Aug-14 (in house check Oct-13) | In house check: Oct-16 |
| Network Analyzer HP 8753E | US37290685 54206 | 18-Oct-14 (in house check Oct-15) | In house check: Oct-14 |

| Calibrated by: | Name | Function | Signature |
|----------------|----------------|-----------------------|-----------|
| | Michael Weiler | Laboratory Technician | |
| Approved by: | Kenji Poljevic | Technical Manager | |

Issued: August 28, 2014

The calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: **D835V2-4d063_Aug14**

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zaughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Servizio Svizzero di Calibrazione
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS).
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates.

Accreditation No.: SCS 108

Glossary:

| | |
|-------|---------------------------------|
| TSI | tissue simulating liquid |
| ConVF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices; Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|------------------------------|------------------------|-------------|
| DASY Version | DASY5 | V52.8.8 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom | |
| Distance Dipole Center - TSL | 15 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 835 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 41.5 | 0.90 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 42.0 ± 6 % | 0.94 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Head TSL

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 2.38 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 9.24 W/kg ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 1.55 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 8.05 W/kg ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 55.2 | 0.97 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 55.2 ± 6 % | 1.01 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 2.41 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 9.35 W/kg ± 17.0 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 1.59 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 8.21 W/kg ± 16.5 % (k=2) |

Appendix (Additional assessments outside the scope of SCS108)**Antenna Parameters with Head TSL**

| | |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.7 Ω -3.6 $\mu\Omega$ |
| Return Loss | -26.2 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 47.1 Ω -5.8 $\mu\Omega$ |
| Return Loss | -23.7 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.087 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semi-rigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|-------------------|
| Manufactured by | SPEAB |
| Manufactured on | November 27, 2006 |

DASY5 Validation Report for Head TSL

Date: 28.08.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d063


Communication System: UID 0 - CW; Frequency: 835 MHz
Medium parameters used: $f = 835$ MHz; $\sigma = 0.94$ S/m; $\epsilon_r = 42$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:


- Probe: ES3DV3 - SN3205; ConvF(6.22, 6.22, 6.22); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 18.08.2014
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 56.23 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 3.53 W/kg
SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.55 W/kg
Maximum value of SAR (measured) = 2.78 W/kg



Impedance Measurement Plot for Head TSL



Certificate No: D835V2-4d063_Aug14

Page 6 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY5 Validation Report for Body TSL

Date: 27.08.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d063Communication System: UID 0 - CW; Frequency: 835 MHz
Medium parameters used: $f = 835$ MHz; $\sigma = 1.01$ S/m; $\epsilon_r = 55.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.09, 6.09, 6.09); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 18.08.2014
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.65 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 3.53 W/kg

SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.59 W/kg

Maximum value of SAR (measured) = 2.80 W/kg

 $0 \text{ dB} = 2.80 \text{ W/kg} = 4.47 \text{ dBW/kg}$

Impedance Measurement Plot for Body TSL



Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: SGS-TW (Auden)

Certificate No: D1900V2-5d027_Apr14

CALIBRATION CERTIFICATE

| Object | D1900V2 - SN: 5d027 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-----------------------------------|------------------------|---------------------|------|----------------------------|-----------------------|--------------------------|------------|-----------------------------------|------------------------|---------------------------|------------------|-----------------------------------|------------------------|-----------------------|------------|---------------------------|--------|----------------------------|----------------|---------------------------|--------|-----------------------------|-------------------|---------------------------|--------|------------------------|----------|--------------------------------|--------|------|---------|--------------------------------|--------|
| Calibration procedure(s) | QA/CAL-05.v9 Calibration procedure for dipole validation kits above 700 MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibration date: | April 23, 2014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility; environment temperature $05^{\circ} \pm 3^{\circ}\text{C}$ and humidity $< 70\%$.</p> <p>Calibration Equipment used (MUST be critical for calibration)</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>Primary Standards</th><th>ID #</th><th>Cal Date (Certificate No.)</th><th>Scheduled Calibration</th></tr></thead><tbody><tr><td>Power meter EPM-442A</td><td>GB37480704</td><td>09-Oct-13 (No. 217-01827)</td><td>Oct-14</td></tr><tr><td>Power sensor HF 8481A</td><td>US37292763</td><td>08-Oct-13 (No. 217-01827)</td><td>Oct-14</td></tr><tr><td>Power sensor HF 8481A</td><td>MY41092317</td><td>08-Oct-13 (No. 217-01828)</td><td>Oct-14</td></tr><tr><td>Reference 25 dB Attenuator</td><td>SN: 5058 (20K)</td><td>03-Apr-14 (No. 217-01918)</td><td>Apr-15</td></tr><tr><td>Type-N mismatch combination</td><td>SN: 5047.2J 06327</td><td>03-Apr-14 (No. 217-01921)</td><td>Apr-15</td></tr><tr><td>Reference Probe E35DV3</td><td>SN: 3205</td><td>30-Dec-13 (No. E33-0205_Dec13)</td><td>Dec-14</td></tr><tr><td>DAE4</td><td>SN: 601</td><td>25-Apr-13 (No. DAE4-601_Apr13)</td><td>Apr-14</td></tr></tbody></table> | | | | Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration | Power meter EPM-442A | GB37480704 | 09-Oct-13 (No. 217-01827) | Oct-14 | Power sensor HF 8481A | US37292763 | 08-Oct-13 (No. 217-01827) | Oct-14 | Power sensor HF 8481A | MY41092317 | 08-Oct-13 (No. 217-01828) | Oct-14 | Reference 25 dB Attenuator | SN: 5058 (20K) | 03-Apr-14 (No. 217-01918) | Apr-15 | Type-N mismatch combination | SN: 5047.2J 06327 | 03-Apr-14 (No. 217-01921) | Apr-15 | Reference Probe E35DV3 | SN: 3205 | 30-Dec-13 (No. E33-0205_Dec13) | Dec-14 | DAE4 | SN: 601 | 25-Apr-13 (No. DAE4-601_Apr13) | Apr-14 |
| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power meter EPM-442A | GB37480704 | 09-Oct-13 (No. 217-01827) | Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power sensor HF 8481A | US37292763 | 08-Oct-13 (No. 217-01827) | Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power sensor HF 8481A | MY41092317 | 08-Oct-13 (No. 217-01828) | Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reference 25 dB Attenuator | SN: 5058 (20K) | 03-Apr-14 (No. 217-01918) | Apr-15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type-N mismatch combination | SN: 5047.2J 06327 | 03-Apr-14 (No. 217-01921) | Apr-15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reference Probe E35DV3 | SN: 3205 | 30-Dec-13 (No. E33-0205_Dec13) | Dec-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DAE4 | SN: 601 | 25-Apr-13 (No. DAE4-601_Apr13) | Apr-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>Secondary Standards</th><th>ID #</th><th>Check Date (in house)</th><th>Scheduled Check</th></tr></thead><tbody><tr><td>HF generator R&S 25MT-00</td><td>100005</td><td>04-Aug-13 (in house check Oct-13)</td><td>In house check: Oct-14</td></tr><tr><td>Network Analyzer HP 8753E</td><td>US37390585 54208</td><td>18-Oct-13 (in house check Oct-13)</td><td>In house check: Oct-14</td></tr></tbody></table> | | | | Secondary Standards | ID # | Check Date (in house) | Scheduled Check | HF generator R&S 25MT-00 | 100005 | 04-Aug-13 (in house check Oct-13) | In house check: Oct-14 | Network Analyzer HP 8753E | US37390585 54208 | 18-Oct-13 (in house check Oct-13) | In house check: Oct-14 | | | | | | | | | | | | | | | | | | | | |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| HF generator R&S 25MT-00 | 100005 | 04-Aug-13 (in house check Oct-13) | In house check: Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Network Analyzer HP 8753E | US37390585 54208 | 18-Oct-13 (in house check Oct-13) | In house check: Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibrated by: | Name: Jeton Kastrati | Function: Laboratory Technician | Signature: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Approved by: | Name: Katja Pokovic | Function: Technical Manager | Signature: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Issued: April 23, 2014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Certificate No: D1900V2-5d027_Apr14

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

| | |
|-------|---------------------------------|
| TSI | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|------------------------------|------------------------|-------------|
| DASY Version | DASY5 | V52.8.7 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 1900 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 40.0 | 1.40 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 39.1 ± 6 % | 1.36 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | ---- | ---- |

SAR result with Head TSL

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 9.71 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 39.3 W/kg ± 17.0 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
| SAR measured | 250 mW input power | 5.10 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 20.6 W/kg ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 53.3 | 1.52 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 52.4 ± 6 % | 1.52 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | ---- | ---- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 9.87 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 39.3 W/kg ± 17.0 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | Condition | |
| SAR measured | 250 mW input power | 5.22 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 20.8 W/kg ± 16.5 % (k=2) |

Appendix

Antenna Parameters with Head TSL

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 52.5 Ω + 6.8 $j\Omega$ |
| Return Loss | - 23.0 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 46.3 Ω + 2.8 $j\Omega$ |
| Return Loss | - 26.4 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.199 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|-------------------|
| Manufactured by | SPEAG |
| Manufactured on | December 17, 2002 |

DASY5 Validation Report for Head TSL

Date: 23.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d027

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $\epsilon = 1.36$ S/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.06, 5.06, 5.06); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000UP50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.825 V/m; Power Drift = 0.06 dB


Peak SAR (extrapolated) = 17.8 W/kg

SAR(1 g) = 9.71 W/kg; SAR(10 g) = 5.1 W/kg

Maximum value of SAR (measured) = 12.3 W/kg



Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY5 Validation Report for Body TSL

Date: 22.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d027

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used: $\epsilon_r = 1.52$ S/m; $\mu_r = 52.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.76, 4.76, 4.76); Calibrated: 30.12.2013
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY5 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm 2/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.526 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 17.2 W/kg

SAR(1 g) = 9.87 W/kg; SAR(10 g) = 5.22 W/kg

Maximum value of SAR (measured) = 12.5 W/kg



Impedance Measurement Plot for Body TSL



Certificate No: D1900V2-5d027_Apr14

Page 8 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: SGS-TW (Auden)

Certificate No: D2450V2-727_Apr14

CALIBRATION CERTIFICATE

| Object | D2450V2 - SN: 727 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|-----------------------------------|------------------------|-------------------|------|----------------------------|-----------------------|----------------------|------------|---------------------------|--------|-----------------------|------------|---------------------------|--------|-----------------------|------------|---------------------------|--------|----------------------------|----------------|---------------------------|--------|-----------------------------|--------------------|---------------------------|--------|------------------------|----------|--------------------------------|--------|------|---------|----------------------------------|--------|
| Calibration procedure(s) | QA CAL-05.v9 Calibration procedure for dipole validation kits above 700 MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibration date | April 23, 2014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibration have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.</p> <p>Calibration Equipment used (WAVE critical for calibration)</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>Primary Standards</th><th>ID #</th><th>Cal Date (Certificate No.)</th><th>Scheduled Calibration</th></tr></thead><tbody><tr><td>Power meter EPM-442A</td><td>GB37490704</td><td>09-Oct-13 (No. 217-01827)</td><td>Oct-14</td></tr><tr><td>Power sensor HP 6487A</td><td>US37292783</td><td>09-Oct-13 (No. 217-01827)</td><td>Oct-14</td></tr><tr><td>Power sensor HP 6487A</td><td>MY41092317</td><td>09-Oct-13 (No. 217-01828)</td><td>Oct-14</td></tr><tr><td>Reference 20 dB Attenuator</td><td>SN: 5056 (20k)</td><td>03-Apr-14 (No. 217-01918)</td><td>Apr-15</td></tr><tr><td>Type-N mismatch combination</td><td>SN: 5047.2 / 09327</td><td>03-Apr-14 (No. 217-01921)</td><td>Apr-15</td></tr><tr><td>Reference Probe ESG0V3</td><td>SN: 3285</td><td>30-Dec-13 (No. E53-3203_Dec13)</td><td>Dec-14</td></tr><tr><td>DAE4</td><td>EN: 601</td><td>25-Apr-13 (No. DAE4-601, Apr-13)</td><td>Apr-14</td></tr></tbody></table> | | | | Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration | Power meter EPM-442A | GB37490704 | 09-Oct-13 (No. 217-01827) | Oct-14 | Power sensor HP 6487A | US37292783 | 09-Oct-13 (No. 217-01827) | Oct-14 | Power sensor HP 6487A | MY41092317 | 09-Oct-13 (No. 217-01828) | Oct-14 | Reference 20 dB Attenuator | SN: 5056 (20k) | 03-Apr-14 (No. 217-01918) | Apr-15 | Type-N mismatch combination | SN: 5047.2 / 09327 | 03-Apr-14 (No. 217-01921) | Apr-15 | Reference Probe ESG0V3 | SN: 3285 | 30-Dec-13 (No. E53-3203_Dec13) | Dec-14 | DAE4 | EN: 601 | 25-Apr-13 (No. DAE4-601, Apr-13) | Apr-14 |
| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power meter EPM-442A | GB37490704 | 09-Oct-13 (No. 217-01827) | Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power sensor HP 6487A | US37292783 | 09-Oct-13 (No. 217-01827) | Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power sensor HP 6487A | MY41092317 | 09-Oct-13 (No. 217-01828) | Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reference 20 dB Attenuator | SN: 5056 (20k) | 03-Apr-14 (No. 217-01918) | Apr-15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Type-N mismatch combination | SN: 5047.2 / 09327 | 03-Apr-14 (No. 217-01921) | Apr-15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reference Probe ESG0V3 | SN: 3285 | 30-Dec-13 (No. E53-3203_Dec13) | Dec-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DAE4 | EN: 601 | 25-Apr-13 (No. DAE4-601, Apr-13) | Apr-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Secondary Standards | ID # | Check Date (in house) | Scheduled Check | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| RF generator P&S SMT-06 | 100015 | 04-Aug-26 (in house check Oct-13) | In house check: Oct-16 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Network Analyzer HP 5735E | US37390585 54206 | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibrated by | Name: Jason Kastell | Function: Laboratory Technician | Signature: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Approved by | Name: Radja Popovic | Function: Technical Manager | Signature: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Issued: April 23, 2014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Certificate No: D2450V2-727_Apr14

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di tambara
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

| | |
|--------------|---------------------------------|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|------------------------------|------------------------|-------------|
| DASY Version | DASY5 | V52.8.7 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 2450 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 39.2 | 1.80 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 38.2 ± 6 % | 1.81 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Head TSL

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 13.1 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 52.0 W/kg ± 17.0 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Head TSL | condition | |
| SAR measured | 250 mW input power | 6.09 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 24.2 W/kg ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 52.7 | 1.95 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 50.6 ± 6 % | 2.01 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 12.8 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 50.0 W/kg ± 17.0 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | |
| SAR measured | 250 mW input power | 5.90 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 23.3 W/kg ± 16.5 % (k=2) |

Appendix

Antenna Parameters with Head TSL

| | |
|--------------------------------------|---------------------------------|
| Impedance, transformed to feed point | 54.6 Ω + 1.9 $\mu\Omega$ |
| Return Loss | - 26.5 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|---------------------------------|
| Impedance, transformed to feed point | 51.1 Ω + 3.5 $\mu\Omega$ |
| Return Loss | - 28.7 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.148 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|------------------|
| Manufactured by | SPEAG |
| Manufactured on | January 09, 2003 |

DASY5 Validation Report for Head TSL

Date: 23.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 727

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $\epsilon' = 2450 \text{ MHz}$; $\sigma = 1.8 \text{ S/m}$; $\epsilon_r = 38.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Si601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)


Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 100.01 V/m; Power Drift = 0.03 dB


Peak SAR (extrapolated) = 27.0 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.09 W/kg

Maximum value of SAR (measured) = 17.1 W/kg



Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY5 Validation Report for Body TSL

Date: 23.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 727

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $\epsilon_r = 2.01$ S/m; $\epsilon_r = 50.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.35, 4.35, 4.35); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.356 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 26.9 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.9 W/kg

Maximum value of SAR (measured) = 16.7 W/kg



Impedance Measurement Plot for Body TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zaughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: SGS-TW (Auden)

Certificate No.: D2600V2-1005_Jan14

CALIBRATION CERTIFICATE

Object: D2600V2 - SN: 1005

Calibration procedure(s): QA CAL-05.v9
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: January 28, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-----------------------------|-------------------|--------------------------------|-----------------------|
| Power meter EPM-442A | GB37480704 | 09-Oct-13 (No. 217-01827) | Oct-14 |
| Power sensor HP 8481A | US37292783 | 08-Oct-13 (No. 217-01827) | Oct-14 |
| Power sensor HP 8481A | MY41082217 | 09-Oct-13 (No. 217-01828) | Oct-14 |
| Reference 20 dB Attenuator | SN 5058 (20) | 04-Apr-13 (No. 217-01736) | Apr-14 |
| Type-N mismatch combination | SN 5047 3 / 08327 | 04-Apr-13 (No. 217-01739) | Apr-14 |
| Reference Probe ES3DVA | SN: 3205 | 30-Dec-13 (No. E53-3205_Dec13) | Dec-14 |
| DAE4 | SN: 501 | 25-Apr-13 (No. DAE4-501_Apr13) | Apr-14 |

| Secondary Standards | ID # | Check Date (In house) | Scheduled Check |
|---------------------------|------------------|-----------------------------------|------------------------|
| RF generator R&S SMT-06 | 100005 | 04-Aug-99 (In house check Oct-13) | In house check: Oct-16 |
| Network Analyzer HP 8753E | US37390585 S4200 | 19-Oct-01 (In house check Oct-13) | In house check: Oct-14 |

| Calibrated by | Name | Function | Signature |
|---------------|-----------------|-----------------------|-----------|
| | Claudio Lüscher | Laboratory Technician | |
| Approved by | Kelja Pavovic | Technical Manager | |

Issued: January 28, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No.: D2600V2-1005_Jan14

Page 1 of 8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

| | |
|-------|---------------------------------|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| DASY Version | DASY5 | V52.8.7 |
|------------------------------|------------------------|-------------|
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | dx, dy, dz = 5 mm | |
| Frequency | 2600 MHz ± 1 MHz | |

Head TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 39.0 | 1.96 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 38.2 ± 6 % | 2.02 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Head TSL

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 14.7 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 57.7 W/kg ± 17.0 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
| SAR measured | 250 mW input power | 6.57 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 26.0 W/kg ± 16.5 % (k=2) |

Body TSL parameters

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 52.5 | 2.16 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 50.9 ± 6 % | 2.21 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 250 mW input power | 14.3 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 56.2 W/kg ± 17.0 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | Condition | |
| SAR measured | 250 mW input power | 6.33 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 25.1 W/kg ± 16.5 % (k=2) |

Appendix

Antenna Parameters with Head TSL

| | |
|--------------------------------------|-----------------|
| Impedance, transformed to feed point | 50.1 Ω - 3.2 jΩ |
| Return Loss | - 30.0 dB |

Antenna Parameters with Body TSL

| | |
|--------------------------------------|-----------------|
| Impedance, transformed to feed point | 46.5 Ω - 2.6 jΩ |
| Return Loss | - 26.6 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.155 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|-------------------|
| Manufactured by | SPEAG |
| Manufactured on | December 23, 2006 |

DASY5 Validation Report for Head TSL

Date: 28.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1005Communication System: UID 0 - CW; Frequency: 2600 MHz
Medium parameters used: $\epsilon_r = 2.02$ S/m; $\mu_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.46, 4.46, 4.46); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 98.590 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 31.3 W/kg

SAR(1 g) = 14.7 W/kg; SAR(10 g) = 6.57 W/kg

Maximum value of SAR (measured) = 19.3 W/kg



Impedance Measurement Plot for Head TSL

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY5 Validation Report for Body TSL

Date: 28.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1005

Communication System: UID 0 - CW; Frequency: 2600 MHz

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.21$ S/m; $\epsilon_r = 50.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.24, 4.24, 4.24); Calibrated: 30.12.2013;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.624 V/m; Power Drift = -0.00 dB


Peak SAR (extrapolated) = 30.8 W/kg

SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.33 W/kg

Maximum value of SAR (measured) = 19.3 W/kg



Impedance Measurement Plot for Body TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client SGS-TW (Auden)

Certificate No: D5GHzV2-1104_Apr14

CALIBRATION CERTIFICATE

Object D5GHzV2 - SN: 1104

Calibration procedure(s) QA CAL-22.v2
Calibration procedure for dipole validation kits between 3-8 GHz

Calibration date April 16, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurement (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature (22 ± 3) $^{\circ}$ C and humidity < 70%.

Calibration Equipment used (MSTE used in calibration)

| Primary Standards | ID # | Cal Date (Certificate No.) | Scheduled Calibration |
|-----------------------------|-------------------|---------------------------------|-----------------------|
| Power meter EPM-442A | GB37480704 | 09-Oct-13 (No. 217-01627) | Oct-14 |
| Power sensor HF 8481A | US37292753 | 09-Oct-13 (No. 217-01627) | Oct-14 |
| Power sensor HF 8481A | MY41092517 | 09-Oct-13 (No. 217-01628) | Oct-14 |
| Reference 20 dB Attenuator | SN 5056 (20k) | 03-Apr-14 (No. 217-01618) | Apr-15 |
| Type-N mismatch combination | SN 5047.2 / 06327 | 03-Apr-14 (No. 217-01621) | Apr-15 |
| Reference Probe EX30V4 | SN 5603 | 30-Dec-13 (No. EX3-3503, Dec13) | Dec-14 |
| DAE4 | SN 001 | 25-Apr-13 (No. DAE4-601_Apr13) | Apr-14 |

| Secondary Standards | ID # | Check Date (in house) | Scheduled Check |
|----------------------------|------------------|-----------------------------------|------------------------|
| HF generator R&S SM140B | 100005 | 04-Aug-09 (in house check Oct-13) | In house check: Oct-15 |
| Network Analyzer R&S 0753E | US37390565-S4205 | 18-Oct-11 (in house check Oct-12) | In house check: Oct-14 |

| | | | |
|----------------|------------------------|------------------------------------|----------------|
| Calibrated by: | Name: Uteka Kazimli | Function: Laboratory Technician | Signature: |
| Approved by: | Kalja Pekovic | Technical Manager | |

Issued, April 17, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D5GHzV2-1104_Apr14

Page 1 of 15

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

t (886-2) 2299-3279

f (886-2) 2298-0488

www.tw.sgs.com

台灣檢驗科技股份有限公司

Member of SGS Group

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

| | |
|-------|---------------------------------|
| TSL | tissue simulating liquid |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A | not applicable or not measured |

Calibration is Performed According to the Following Standards:

- a) IEC 62209-2, "Evaluation of Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices in the Frequency Range of 30 MHz to 6 GHz: Human models, Instrumentation, and Procedures"; Part 2: "Procedure to determine the Specific Absorption Rate (SAR) for including accessories and multiple transmitters", March 2010
- b) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"
- c) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

Additional Documentation:

- d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- **Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- **Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- **Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- **Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- **SAR measured:** SAR measured at the stated antenna input power.
- **SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- **SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

| | | |
|-------------------------------------|--|----------------------------------|
| DASY Version | DASY5 | V52.8.7 |
| Extrapolation | Advanced Extrapolation | |
| Phantom | Modular Flat Phantom V5.0 | |
| Distance Dipole Center - TSL | 10 mm | with Spacer |
| Zoom Scan Resolution | $dx, dy = 4.0 \text{ mm}, dz = 1.4 \text{ mm}$ | Graded Ratio = 1.4 (Z direction) |
| Frequency | 5200 MHz $\pm 1 \text{ MHz}$ 5300 MHz $\pm 1 \text{ MHz}$ 5600 MHz $\pm 1 \text{ MHz}$ 5800 MHz $\pm 1 \text{ MHz}$ | |

Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|--|----------------------|------------------------|------------------------------|
| Nominal Head TSL parameters | 22.0 °C | 36.0 | 4.66 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 35.8 $\pm 6 \text{ %}$ | 4.43 mho/m $\pm 6 \text{ %}$ |
| Head TSL temperature change during test | < 0.5 °C | ---- | ---- |

SAR result with Head TSL at 5200 MHz

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------------------|
| SAR measured | 100 mW input power | 8.02 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 80.0 W/kg $\pm 19.9 \text{ %} (k=2)$ |

| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
|---|--------------------|--------------------------------------|
| SAR measured | 100 mW input power | 2.29 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 22.6 W/kg $\pm 19.5 \text{ %} (k=2)$ |

Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 35.9 | 4.76 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 35.7 ± 6 % | 4.54 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Head TSL at 5300 MHz

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|----------------------------|
| SAR measured | 100 mW input power | 8.45 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 84.3 W / kg ± 19.9 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
| SAR measured | 100 mW input power | 2.41 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 24.0 W/kg ± 19.5 % (k=2) |

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 35.5 | 5.07 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 35.3 ± 6 % | 4.83 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Head TSL at 5600 MHz

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW input power | 8.31 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 82.8 W/kg ± 19.9 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
| SAR measured | 100 mW input power | 2.36 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 23.5 W/kg ± 19.5 % (k=2) |

Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters | 22.0 °C | 35.3 | 5.27 mho/m |
| Measured Head TSL parameters | (22.0 ± 0.2) °C | 35.0 ± 6 % | 5.03 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C | ---- | ----- |

SAR result with Head TSL at 5800 MHz

| SAR averaged over 1 cm ³ (1 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW input power | 7.95 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 79.2 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm ³ (10 g) of Head TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW input power | 2.26 W/kg |
| SAR for nominal Head TSL parameters | normalized to 1W | 22.5 W/kg ± 19.5 % (k=2) |

Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|--|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 49.0 | 5.30 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 47.0 ± 6 % | 5.44 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL at 5200 MHz

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW input power | 7.69 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 76.3 W/kg ± 19.9 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | |
| SAR measured | 100 mW input power | 2.15 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 21.3 W/kg ± 19.5 % (k=2) |

Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|--|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 48.9 | 5.42 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 46.8 ± 6 % | 5.57 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL at 5300 MHz

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW input power | 7.84 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 77.8 W/kg ± 19.9 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | condition | |
| SAR measured | 100 mW input power | 2.19 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 21.7 W/kg ± 19.5 % (k=2) |

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|--|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 48.5 | 5.77 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 46.3 ± 6 % | 5.98 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL at 5600 MHz

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW Input power | 8.21 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 81.4 W/kg ± 19.9 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | Condition | |
| SAR measured | 100 mW Input power | 2.28 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 22.6 W/kg ± 19.5 % (k=2) |

Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

| | Temperature | Permittivity | Conductivity |
|--|-----------------|--------------|------------------|
| Nominal Body TSL parameters | 22.0 °C | 48.2 | 6.00 mho/m |
| Measured Body TSL parameters | (22.0 ± 0.2) °C | 46.0 ± 6 % | 6.23 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C | --- | --- |

SAR result with Body TSL at 5800 MHz

| SAR averaged over 1 cm ³ (1 g) of Body TSL | Condition | |
|---|--------------------|--------------------------|
| SAR measured | 100 mW Input power | 7.73 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 76.7 W/kg ± 19.9 % (k=2) |
| SAR averaged over 10 cm ³ (10 g) of Body TSL | Condition | |
| SAR measured | 100 mW Input power | 2.13 W/kg |
| SAR for nominal Body TSL parameters | normalized to 1W | 21.1 W/kg ± 19.5 % (k=2) |

Appendix**Antenna Parameters with Head TSL at 5200 MHz**

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 48.2 Ω - 4.8 $j\Omega$ |
| Return Loss | - 25.6 dB |

Antenna Parameters with Head TSL at 5300 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 48.5 Ω - 7.6 $j\Omega$ |
| Return Loss | - 22.2 dB |

Antenna Parameters with Head TSL at 5600 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 53.9 Ω + 0.5 $j\Omega$ |
| Return Loss | - 28.5 dB |

Antenna Parameters with Head TSL at 5800 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 58.3 Ω - 4.4 $j\Omega$ |
| Return Loss | - 21.2 dB |

Antenna Parameters with Body TSL at 5200 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 52.6 Ω - 9.2 $j\Omega$ |
| Return Loss | - 20.6 dB |

Antenna Parameters with Body TSL at 5300 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 53.3 Ω - 1.8 $j\Omega$ |
| Return Loss | - 28.7 dB |

Antenna Parameters with Body TSL at 5600 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 58.7 Ω - 5.2 $j\Omega$ |
| Return Loss | - 20.6 dB |

Antenna Parameters with Body TSL at 5800 MHz

| | |
|--------------------------------------|-------------------------------|
| Impedance, transformed to feed point | 57.0 Ω + 2.2 $j\Omega$ |
| Return Loss | - 23.3 dB |

General Antenna Parameters and Design

| | |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.207 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

| | |
|-----------------|--------------------|
| Manufactured by | SPEAG |
| Manufactured on | September 24, 2010 |

DASY5 Validation Report for Head TSL

Date: 16.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1104

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200 \text{ MHz}$; $\sigma = 4.43 \text{ S/m}$; $\epsilon_r = 35.8$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5300 \text{ MHz}$; $\sigma = 4.54 \text{ S/m}$; $\epsilon_r = 35.7$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 4.83 \text{ S/m}$; $\epsilon_r = 35.3$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 5.03 \text{ S/m}$; $\epsilon_r = 35$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.52, 5.52, 5.52); Calibrated: 30.12.2013, ConvF(5.2, 5.2, 5.2); Calibrated: 30.12.2013, ConvF(4.86, 4.86, 4.86); Calibrated: 30.12.2013, ConvF(4.91, 4.91, 4.91); Calibrated: 30.12.2013;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.950 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 29.4 W/kg

SAR(1 g) = 8.02 W/kg; SAR(10 g) = 2.29 W/kg

Maximum value of SAR (measured) = 18.2 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.460 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 32.1 W/kg

SAR(1 g) = 8.45 W/kg; SAR(10 g) = 2.41 W/kg

Maximum value of SAR (measured) = 19.4 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.602 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 33.3 W/kg

SAR(1 g) = 8.31 W/kg; SAR(10 g) = 2.36 W/kg


Maximum value of SAR (measured) = 19.7 W/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 62.293 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 33.5 W/kg
SAR(1 g) = 7.95 W/kg; SAR(10 g) = 2.26 W/kg
Maximum value of SAR (measured) = 19.1 W/kg



Impedance Measurement Plot for Head TSL



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

DASY5 Validation Report for Body TSL

Date: 15.04.2014

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1104

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200 \text{ MHz}$; $\sigma = 5.44 \text{ S/m}$; $\epsilon_r = 47$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5300 \text{ MHz}$; $\sigma = 5.57 \text{ S/m}$; $\epsilon_r = 46.8$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 5.96 \text{ S/m}$; $\epsilon_r = 46.3$; $\rho = 1000 \text{ kg/m}^3$, Medium parameters used: $f = 5800 \text{ MHz}$; $\sigma = 6.23 \text{ S/m}$; $\epsilon_r = 46$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.01, 5.01, 5.01); Calibrated: 30.12.2013, ConvF(4.76, 4.76, 4.76); Calibrated: 30.12.2013, ConvF(4.43, 4.43, 4.43); Calibrated: 30.12.2013, ConvF(4.47, 4.47, 4.47); Calibrated: 30.12.2013;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.628 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 30.7 W/kg

SAR(1 g) = 7.69 W/kg; SAR(10 g) = 2.15 W/kg

Maximum value of SAR (measured) = 18.2 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 59.482 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 32.5 W/kg

SAR(1 g) = 7.84 W/kg; SAR(10 g) = 2.19 W/kg

Maximum value of SAR (measured) = 18.7 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.886 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 36.9 W/kg

SAR(1 g) = 8.21 W/kg; SAR(10 g) = 2.28 W/kg

Maximum value of SAR (measured) = 20.1 W/kg

Certificate No: D5GHzV2-1104_Apr14

Page 13 of 15

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號

台灣檢驗科技股份有限公司


t (886-2) 2299-3279

f (886-2) 2298-0488


www.tw.sgs.com

Member of SGS Group

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 56.160 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 36.8 W/kg
SAR(1 g) = 7.73 W/kg; SAR(10 g) = 2.13 W/kg
Maximum value of SAR (measured) = 19.4 W/kg



Impedance Measurement Plot for Body TSL

**End of 1st part of report**

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan 24803/新北市五股區新北產業園區五工路134號