


FCC SAR Test Report

APPLICANT : Sony Mobile Communications Inc.
BRAND NAME : Sony
FCC ID : PY7-PM0910
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Attestation of Test Results	4
2. Administration Data	5
3. Guidance Standard	5
4. Equipment Under Test (EUT) Information	6
4.1 Wireless Technologies	6
4.2 Device Serial Number	6
4.3 Maximum Tune-up Limit	7
5. RF Exposure Limits	9
5.1 Uncontrolled Environment	9
5.2 Controlled Environment	9
6. Specific Absorption Rate (SAR)	10
6.1 Introduction	10
6.2 SAR Definition	10
7. System Description and Setup	11
8. Measurement Procedures	12
8.1 Spatial Peak SAR Evaluation	12
8.2 Power Reference Measurement	13
8.3 Area Scan	13
8.4 Zoom Scan	14
8.5 Volume Scan Procedures	14
8.6 Power Drift Monitoring	14
9. Test Equipment List	15
10. System Verification	16
10.1 Tissue Verification	16
10.2 System Performance Check Results	18
11. RF Exposure Positions	20
11.1 Ear and handset reference point	20
11.2 Definition of the cheek position	21
11.3 Definition of the tilt position	22
11.4 Body Worn Accessory	22
11.5 Wireless Router	23
11.6 Extremity Exposure Configurations	23
12. Conducted RF Output Power (Unit: dBm)	24
13. Bluetooth Exclusions Applied	42
14. RF Exposure Conditions	42
15. SAR Test Results	43
15.1 Head SAR	45
15.2 Hotspot SAR	47
15.3 Phablet SAR Test Considerations	49
15.4 Extremity SAR	49
15.5 Body Worn Accessory SAR	51
15.6 Repeated SAR Measurement	52
16. Simultaneous Transmission Analysis	53
16.1 Head Exposure Conditions	54
16.2 Hotspot Exposure Conditions	55
16.3 Extremity Exposure Conditions	56
16.4 Body-Worn Accessory Exposure Conditions	57
17. Uncertainty Assessment	58
18. References	61
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Antenna location and Test Setup Photo	



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA571620	Rev. 01	Initial issue of report	Sep. 16, 2015
FA571620	Rev. 02	Revised LTE RB offset	Sep. 17, 2015
FA571620	Rev. 03	Revised section 15.4 and 16.3	Sep. 18, 2015
FA571620	Rev. 04	Added Extremity SAR testing.	Sep. 25, 2015



1. Attestation of Test Results

Applicant Name	Sony Mobile Communications Inc.		
EUT Description	GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n/ac, ANT+, and NFC		
FCC ID	PY7-PM0910		
HW Version	A		
SW Version	32.0.B.0.233		
RF Exposure Conditions	Equipment Class		
	Licensed	DTS	U-NII
Head (1g SAR W/kg)	0.34	0.32	0.27
Body-Worn (1g SAR W/kg)	0.34	0.04	0.08
Wireless Router (1g SAR W/kg)	1.13	0.10	NA
Extremity (10g SAR W/kg)	2.47	NA	0.69
Highest Simultaneous Transmission (1g SAR W/kg)	Head: 0.69 Body-worn: 0.64 Hotspot: 1.13	Head: 0.69 Body-worn: 0.41 Hotspot: 1.13	Head: 0.61 Body-worn: 0.64 Hotspot: NA
Highest Simultaneous Transmission (10g SAR W/kg)	Extremity: 3.66	Extremity: 2.47	Extremity: 3.66
Date Tested	2015/09/03 ~ 2015/09/24		
Test Result	Pass		
Remark:			
1. This device 2.4GHz WLAN supports Hotspot operation, and 2.4GHz / 5.2GHz / 5.3GHz / 5.5GHz / 5.8GHz WLAN supports WiFi Direct.			
2. GSM1900 power reduction is activated in hotspot mode.			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for partial-body, 4.0 W/kg for Extremity) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Sony Mobile Communications Inc.
Address	Nya Vattentornet, 22188 Lund, Sweden

Manufacturer	
Company Name	Sony Mobile Communications Inc.
Address	1-8-15 Konan, Minato-ku, Tokyo, 108-0075, Japan

3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r01
- FCC KDB 941225 D01 3G SAR Procedures v03
- FCC KDB 941225 D05 SAR for LTE Devices v02r03
- FCC KDB 941225 D06 Hotspot Mode SAR v02

4. Equipment Under Test (EUT) Information

4.1 Wireless Technologies

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	· GSM Voice · GPRS (GMSK) · EDGE (8PSK)	Multi-Slot Class: Class 33
	Does device support dual transfer mode? (Yes)		
W-CDMA (UMTS)	Band 5	· AMR / RMC 12.2Kbps · HSDPA · HSUPA	
LTE (FDD)	Band 17 Band 7	· QPSK · 16QAM	
WiFi	2.4GHz: 2412 MHz ~ 2472 MHz	· 11b · 11g · 11n (HT20)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5720 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	· 11a · 11n (HT20) · 11n (HT40) · 11ac (VHT20) · 11ac (VHT40) · 11ac (VHT80)	
Bluetooth	2.4GHz	Version 4.1 with LE	

4.2 Device Serial Number

Exposure Position	Head	Hotspot	Body-Worn	Extremity
Band				
GSM850	CB5A27R46W	CB5A27R45Y	CB5A27R45Y	
GSM1900	CB5A27R46W	CB5A27R46W	CB5A27R46W	CB5A27R46W
UMTS 850	CB5A27R46S	CB5A27R46S	CB5A27R46S	
LTE Band 17	CB5A27R931	CB5A27R931	CB5A27R931	
LTE Band 7	CB5A27R479	CB5A27R479	CB5A27R479	
2.4GHZ WLAN	CB5A27R4A0 CB5A27R932	CB5A27R4A0 CB5A27R932	CB5A27R4A0 CB5A27R932	
5GHZ WLAN	CB5A27R405 CB5A27R41T		CB5A27R405 CB5A27R41T	
GSM Conducted	CB5A27R477			
UMTS Conducted	CB5A27R477			
LTE Conducted	CB5A27R4A1			
WiFi Conducted	CB5A27R4AE			

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

4.3 Maximum Tune-up Limit

<WWAN Tune-up Limit>

Mode		Burst Average Power (dBm)	
		GSM 850	GSM 1900
Output power states			Full Power Mode Reduced power mode
GSM (GMSK, 1 Tx slot)		33.40	30.40 30.40
GPRS/EDGE (GMSK, 1 Tx slot)		33.40	30.40 30.40
GPRS/EDGE (GMSK, 2 Tx slots)		31.90	28.90 27.70
GPRS/EDGE (GMSK, 3 Tx slots)		30.10	27.10 25.70
GPRS/EDGE (GMSK, 4 Tx slots)		28.90	25.90 24.20
EDGE (8PSK, 1 Tx slot)		28.00	27.00 27.00
EDGE (8PSK, 2 Tx slots)		26.50	25.50 25.50
EDGE (8PSK, 3 Tx slots)		24.70	23.70 23.70
EDGE (8PSK, 4 Tx slots)		23.50	21.00 21.00
DTM 5	GSM (GMSK, 1 Tx slot)	31.90	28.90 27.70
	GPRS (GMSK, 1 Tx slot)	31.90	28.90 27.70
DTM 9	GSM (GMSK, 1 Tx slot)	31.90	28.90 27.70
	GPRS (GMSK, 1 Tx slot)	31.90	28.90 27.70
DTM11	GSM (GMSK, 1 Tx slot)	30.10	27.10 25.70
	GPRS (GMSK, 2 Tx slots)	30.10	27.10 25.70
DTM 5	GSM (GMSK, 1 Tx slot)	31.90	28.90 27.70
	EDGE (8PSK, 1 Tx slot)	26.50	25.50 25.50
DTM 9	GSM (GMSK, 1 Tx slot)	31.90	28.90 27.70
	EDGE (8PSK, 1 Tx slot)	26.50	25.50 25.50
DTM 11	GSM (GMSK, 1 Tx slot)	30.10	27.10 25.70
	EDGE (8PSK, 2 Tx slots)	24.70	23.70 23.70

Mode		Average Power (dBm)
WCDMA	Band V	24.90
LTE	Band 17	24.00
	Band 7	20.50

<WLAN and Bluetooth Tune-up Limit>
Remark:

1. The table applies to both SISO and MIMO operation.

Band	Channel	Average Power (dBm)					
		11b		11g		11n (HT20)	
		Chain 0	Chan 1	Chain 0	Chan 1	Chain 0	Chan 1
2.4GHz WLAN	CH 1	14.00	14.00	14.00	14.00	14.00	14.00
	CH 6	14.00	14.00	14.00	14.00	14.00	14.00
	CH 11	14.00	14.00	14.00	14.00	14.00	14.00
	CH 12	14.00	14.00	10.75	9.75	9.00	8.00
	CH 13	13.25	12.75	4.25	3.25	3.50	2.50

Band	Average Power (dBm)					
	11a		11n (HT20)		11n (HT40)	
	Chain 0	Chan 1	Chain 0	Chan 1	Chain 0	Chan 1
5.2GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00
5.3GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00
5.5GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00
5.8GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00

Band	Average Power (dBm)					
	11ac (VHT20)		11ac (VHT40)		11ac (VHT80)	
	Chain 0	Chan 1	Chain 0	Chan 1	Chain 0	Chan 1
5.2GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00
5.3GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00
5.5GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00
5.8GHz WLAN	10.00	10.00	10.00	10.00	10.00	10.00

Mode Band	Average power(dBm)		
2.4GHz Bluetooth Version 4.1 with LE	BR	EDR	BLE
	11.50	8.50	7.50

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1012	May. 28, 2015	May. 27, 2016
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 20, 2015	Mar. 19, 2016
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Mar. 24, 2015	Mar. 23, 2016
SPEAG	2450MHz System Validation Kit	D2450V2	735	Dec. 08, 2014	Dec. 07, 2015
SPEAG	2600MHz System Validation Kit	D2600V2	1058	Jun. 19, 2015	Jun. 18, 2016
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 25, 2014	Sep. 24, 2015
SPEAG	5GHz System Validation Kit	D5GHzV2	1040	Jun. 22, 2015	Jun. 21, 2016
SPEAG	Data Acquisition Electronics	DAE4	1388	Sep. 24, 2014	Sep. 23, 2015
SPEAG	Data Acquisition Electronics	DAE3	577	Oct. 06, 2014	Oct. 05, 2015
SPEAG	Data Acquisition Electronics	DAE4	1279	Jul. 21, 2015	Jul. 20, 2016
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 13, 2014	Nov. 12, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3697	Sep. 29, 2014	Sep. 28, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Sep. 25, 2014	Sep. 24, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3954	Nov. 21, 2014	Nov. 20, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3943	Jan. 29, 2015	Jan. 28, 2016
WonDer	Thermometer	WD-5015	TM685	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	HTC-1	TM642	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	HTC-1	TM281	Oct. 21, 2014	Oct. 20, 2015
Wisewind	Thermometer	ETP-101	TM560	Oct. 21, 2014	Oct. 20, 2015
Anritsu	Radio Communication Analyzer	MT8820C	6201074414	Feb. 06, 2015	Feb. 05, 2016
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 14, 2015	May. 13, 2016
R&S	Radio communication Tester	CMW500	113998	Sep. 30, 2014	Sep. 29, 2015
SPEAG	Device Holder	N/A	N/A	N/A	N/A
R&S	Signal Generator	MG3710A	6201502524	May. 25, 2015	May. 24, 2016
Agilent	ENA Network Analyzer	E5071C	MY46316648	Feb. 11, 2015	Feb. 10, 2016
SPEAG	Dielectric Probe Kit	DAK-3.5	1138	Nov. 18, 2014	Nov. 17, 2015
LINE SEIKI	Digital Thermometer	LKMeletronic	DTM3000SPEZIAL	Jul. 17, 2015	Jul. 16, 2016
Anritsu	Power Meter	ML2495A	1349001	Dec. 03, 2014	Dec. 02, 2015
Anritsu	Power Sensor	MA2411B	1306099	Dec. 03, 2014	Dec. 02, 2015
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 17, 2015	Jun. 16, 2016
Agilent	Dual Directional Coupler	778D	50422	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	
AR	Power Amplifier	5S1G4M2	0328767	Note 1	
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.5	0.893	42.633	0.89	41.90	0.34	1.75	±5	2015/9/4
750	MSL	22.3	0.970	54.646	0.96	55.50	1.04	-1.54	±5	2015/9/4
835	HSL	22.5	0.899	43.004	0.90	41.50	-0.11	3.62	±5	2015/9/4
835	MSL	22.3	0.981	55.337	0.97	55.20	1.13	0.25	±5	2015/9/4
1900	HSL	22.2	1.428	40.987	1.40	40.00	2.00	2.47	±5	2015/9/4
1900	MSL	22.4	1.527	54.259	1.52	53.30	0.46	1.80	±5	2015/9/3
1900	MSL	22.5	1.570	51.400	1.52	53.30	3.29	-3.56	±5	2015/9/7
1900	MSL	22.5	1.550	51.900	1.52	53.30	1.97	-2.63	±5	2015/9/14
2450	HSL	22.3	1.850	39.196	1.80	39.20	2.78	-0.01	±5	2015/9/5
2450	MSL	22.3	1.964	51.596	1.95	52.70	0.72	-2.09	±5	2015/9/5
2600	HSL	22.5	2.018	38.523	1.96	39.00	2.96	-1.22	±5	2015/9/11
2600	MSL	22.5	2.199	52.751	2.16	52.50	1.81	0.48	±5	2015/9/11
5300	HSL	22.3	4.636	36.215	4.76	35.90	-2.61	0.88	±5	2015/9/6
5300	MSL	22.3	5.578	48.180	5.42	48.90	2.92	-1.47	±5	2015/9/5
5300	MSL	22.4	5.270	47.255	5.42	48.90	-2.77	-3.36	±5	2015/9/24
5600	HSL	22.3	4.929	35.796	5.07	35.50	-2.78	0.83	±5	2015/9/6
5600	MSL	22.3	5.904	46.956	5.77	48.50	2.32	-3.18	±5	2015/9/6
5600	MSL	22.4	5.653	46.801	5.77	48.50	-2.03	-3.50	±5	2015/9/24
5800	HSL	22.3	5.137	35.551	5.27	35.30	-2.52	0.71	±5	2015/9/6
5800	MSL	22.3	6.198	46.572	6.00	48.20	3.30	-3.38	±5	2015/9/6
5800	MSL	22.4	5.991	46.521	6.00	48.20	-0.15	-3.48	±5	2015/9/24

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2015/9/4	750	HSL	250	D750V3-1012	EX3DV4 - SN3954	DAE4 Sn1279	2.00	8.22	8.00	-2.68
2015/9/4	750	MSL	250	D750V3-1012	EX3DV4 - SN3954	DAE4 Sn1279	2.07	8.61	8.28	-3.83
2015/9/4	835	HSL	250	D835V2-499	EX3DV4 - SN3954	DAE4 Sn1279	2.35	9.20	9.40	2.17
2015/9/4	835	MSL	250	D835V2-499	EX3DV4 - SN3954	DAE4 Sn1279	2.48	9.30	9.92	6.67
2015/9/4	1900	HSL	250	D1900V2-5d041	EX3DV4 - SN3954	DAE4 Sn1279	9.24	40.00	36.96	-7.60
2015/9/3	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3954	DAE4 Sn1279	9.97	39.80	39.88	0.20
2015/9/7	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3697	DAE4 Sn1388	9.88	39.80	39.52	-0.70
2015/9/14	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3931	DAE3 Sn577	10.20	39.80	40.80	2.51
2015/9/5	2450	HSL	250	D2450V2-735	EX3DV4 - SN3954	DAE4 Sn1279	13.20	54.20	52.80	-2.58
2015/9/5	2450	MSL	250	D2450V2-735	EX3DV4 - SN3954	DAE4 Sn1279	12.10	51.10	48.40	-5.28
2015/9/11	2600	HSL	250	D2600V2-1058	EX3DV4 - SN3697	DAE4 Sn1388	14.80	57.20	59.20	3.50
2015/9/11	2600	HSL	250	D2600V2-1058	EX3DV4 - SN3697	DAE4 Sn1388	15.00	57.20	60.00	4.90
2015/9/6	5300	HSL	100	D5GHzV2-1006-5300	EX3DV4 - SN3954	DAE4 Sn1279	8.35	86.60	83.50	-3.58
2015/9/5	5300	MSL	100	D5GHzV2-1006-5300	EX3DV4 - SN3954	DAE4 Sn1279	7.65	80.00	76.50	-4.38
2015/9/24	5300	MSL	100	D5GHzV2-1040-5300	EX3DV4 - SN3943	DAE4 Sn1399	7.79	75.20	77.90	3.59
2015/9/6	5600	HSL	100	D5GHzV2-1006-5600	EX3DV4 - SN3954	DAE4 Sn1279	8.55	85.80	85.50	-0.35
2015/9/6	5600	MSL	100	D5GHzV2-1006-5600	EX3DV4 - SN3954	DAE4 Sn1279	7.81	85.20	78.10	-8.33
2015/9/24	5600	MSL	100	D5GHzV2-1040-5600	EX3DV4 - SN3943	DAE4 Sn1399	8.34	79.00	83.40	5.57
2015/9/6	5800	HSL	100	D5GHzV2-1006-5800	EX3DV4 - SN3954	DAE4 Sn1279	8.84	82.90	88.40	6.63
2015/9/6	5800	MSL	100	D5GHzV2-1006-5800	EX3DV4 - SN3954	DAE4 Sn1279	7.75	78.40	77.50	-1.15
2015/9/24	5800	MSL	100	D5GHzV2-1040-5800	EX3DV4 - SN3943	DAE4 Sn1399	7.51	76.60	75.10	-1.96

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2015/9/4	750	HSL	250	D750V3-1012	EX3DV4 - SN3954	DAE4 Sn1279	1.36	5.41	5.44	0.55
2015/9/4	750	MSL	250	D750V3-1012	EX3DV4 - SN3954	DAE4 Sn1279	1.39	5.72	5.56	-2.80
2015/9/4	835	HSL	250	D835V2-499	EX3DV4 - SN3954	DAE4 Sn1279	1.54	6.02	6.16	2.33
2015/9/4	835	MSL	250	D835V2-499	EX3DV4 - SN3954	DAE4 Sn1279	1.61	6.12	6.44	5.23
2015/9/4	1900	HSL	250	D1900V2-5d041	EX3DV4 - SN3954	DAE4 Sn1279	4.74	20.90	18.96	-9.28
2015/9/3	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3954	DAE4 Sn1279	5.19	21.20	20.76	-2.08
2015/9/7	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3697	DAE4 Sn1388	5.18	21.20	20.72	-2.26
2015/9/14	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3931	DAE3 Sn577	5.45	21.20	21.80	2.83
2015/9/5	2450	HSL	250	D2450V2-735	EX3DV4 - SN3954	DAE4 Sn1279	6.24	25.60	24.96	-2.50
2015/9/5	2450	MSL	250	D2450V2-735	EX3DV4 - SN3954	DAE4 Sn1279	5.68	23.60	22.72	-3.73
2015/9/11	2600	HSL	250	D2600V2-1058	EX3DV4 - SN3697	DAE4 Sn1388	6.82	25.90	27.28	5.33
2015/9/11	2600	HSL	250	D2600V2-1058	EX3DV4 - SN3697	DAE4 Sn1388	6.62	25.90	26.48	2.24
2015/9/6	5300	HSL	100	D5GHzV2-1006-5300	EX3DV4 - SN3954	DAE4 Sn1279	2.36	24.70	23.60	-4.45
2015/9/5	5300	MSL	100	D5GHzV2-1006-5300	EX3DV4 - SN3954	DAE4 Sn1279	2.17	22.30	21.70	-2.69
2015/9/24	5300	MSL	100	D5GHzV2-1040-5300	EX3DV4 - SN3943	DAE4 Sn1399	2.23	21.10	22.30	5.69
2015/9/6	5600	HSL	100	D5GHzV2-1006-5600	EX3DV4 - SN3954	DAE4 Sn1279	2.36	24.40	23.60	-3.28
2015/9/6	5600	MSL	100	D5GHzV2-1006-5600	EX3DV4 - SN3954	DAE4 Sn1279	2.27	23.60	22.70	-3.81
2015/9/24	5600	MSL	100	D5GHzV2-1040-5600	EX3DV4 - SN3943	DAE4 Sn1399	2.27	21.90	22.70	3.65
2015/9/6	5800	HSL	100	D5GHzV2-1006-5800	EX3DV4 - SN3954	DAE4 Sn1279	2.44	23.50	24.40	3.83
2015/9/6	5800	MSL	100	D5GHzV2-1006-5800	EX3DV4 - SN3954	DAE4 Sn1279	2.25	21.60	22.50	4.17
2015/9/24	5800	MSL	100	D5GHzV2-1040-5800	EX3DV4 - SN3943	DAE4 Sn1399	2.05	21.10	20.50	-2.84



Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.



Fig 9.1.1 Front, back, and side views of SAM twin phantom



Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.



Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"



Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06 v02 where SAR test considerations for handsets (L x W $\geq$ 9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

11.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR exclusion thresholds found in KDB Publication 447498 D01v05 should be applied to determine SAR test requirements.

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless mode and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold. The normal tablet procedures in KDB 616217 are required when the over diagonal dimension of the device is > 20.0 cm. Hotspot mode SAR is not required when normal tablet procedures are applied. Extremity 10-g SAR is also not required for the front (top) surface of large form factor full size tablets. The more conservative tablet SAR results can be used to support the 10-g extremity SAR for phablet mode. The simultaneous transmission operating configurations applicable to voice and data transmissions for both phone and mini-tablet modes must be taken into consideration separately for 1-g and 10-g SAR to determine the simultaneous transmission SAR test exclusion and measurement requirements for the relevant wireless mode and exposure conditions

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table above, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 \cdot \log [\sum (\text{power of each slot, in mW}) / 8]$$

- Per KDB 447498 D01v05r02, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- Per KDB 941225 D01v03, Head / Hotspot / Body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850 and GPRS (4Tx slots) for GSM1900, when hotspot is enabled power reduction will be activated to limit the maximum power, therefore, the EUT was set in GPRS (2Tx slots) for GSM1900.

<Full Power Mode>

Band GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM (GMSK, 1 Tx slot)		32.90	32.98	33.01	33.40	23.90	23.98	24.01	24.40
GPRS (GMSK, 1 Tx slot)		32.91	33.00	33.05	33.40	23.91	24.00	24.05	24.40
GPRS (GMSK, 2 Tx slots)		31.48	31.61	31.72	31.90	25.48	25.61	25.72	25.90
GPRS (GMSK, 3 Tx slots)		29.21	29.97	30.09	30.10	24.95	25.71	25.83	25.84
GPRS (GMSK, 4 Tx slots)		28.75	28.88	28.89	28.90	25.75	25.88	25.89	25.90
EDGE (8PSK, 1 Tx slot)		26.94	27.07	27.15	28.00	17.94	18.07	18.15	19.00
EDGE (8PSK, 2 Tx slots)		25.60	25.75	25.86	26.50	19.60	19.75	19.86	20.50
EDGE (8PSK, 3 Tx slots)		23.81	23.95	24.05	24.70	19.55	19.69	19.79	20.44
EDGE (8PSK, 4 Tx slots)		22.91	23.10	23.14	23.50	19.91	20.10	20.14	20.50
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	31.46	31.56	31.65	31.90	25.37	25.47	25.56	25.88
	GPRS (GMSK, 1 Tx slot)	31.32	31.42	31.51	31.90				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	31.45	31.55	31.64	31.90	25.36	25.46	25.55	25.88
	GPRS (GMSK, 1 Tx slot)	31.30	31.41	31.50	31.90				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	29.26	29.36	29.46	30.10	24.92	25.02	25.11	25.84
	GPRS (GMSK, 2 Tx slots)	29.14	29.24	29.33	30.10				
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	31.39	31.55	31.65	31.90	23.36	23.52	23.62	23.97
	EDGE (8PSK, 1 Tx slot)	25.53	25.68	25.81	26.50				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	31.53	31.64	31.73	31.90	23.48	23.59	23.69	23.97
	EDGE (8PSK, 1 Tx slot)	25.56	25.70	25.82	26.50				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	29.32	29.44	29.55	30.10	22.18	22.31	22.42	23.05
	EDGE (8PSK, 2 Tx slots)	23.68	23.84	23.95	24.70				

Band GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)		29.93	29.93	29.94	30.40	20.93	20.93	20.94	21.40
GPRS (GMSK, 1 Tx slot)		29.95	29.94	29.95	30.40	20.95	20.94	20.95	21.40
GPRS (GMSK, 2 Tx slots)		28.85	28.89	28.82	28.90	22.85	22.89	22.82	22.90
GPRS (GMSK, 3 Tx slots)		27.06	26.98	26.97	27.10	22.80	22.72	22.71	22.84
GPRS (GMSK, 4 Tx slots)		25.83	25.88	25.82	25.90	22.83	22.88	22.82	22.90
EDGE (8PSK, 1 Tx slot)		25.99	25.96	25.89	27.00	16.99	16.96	16.89	18.00
EDGE (8PSK, 2 Tx slots)		24.70	24.66	24.58	25.50	18.70	18.66	18.58	19.50
EDGE (8PSK, 3 Tx slots)		22.70	22.65	22.60	23.70	18.44	18.39	18.34	19.44
EDGE (8PSK, 4 Tx slots)		20.53	20.50	20.51	21.00	17.53	17.50	17.51	18.00
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	28.86	28.85	28.60	28.90	22.84	22.83	22.63	22.88
	GPRS (GMSK, 1 Tx slot)	28.87	28.86	28.70	28.90				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	28.81	28.87	28.64	28.90	22.79	22.85	22.67	22.88
	GPRS (GMSK, 1 Tx slot)	28.82	28.88	28.74	28.90				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	27.09	27.07	26.91	27.10	22.77	22.74	22.58	22.84
	GPRS (GMSK, 2 Tx slots)	27.00	26.97	26.80	27.10				
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	28.83	28.88	28.56	28.90	21.22	21.24	20.98	21.50
	EDGE (8PSK, 1 Tx slot)	24.70	24.65	24.54	25.50				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	28.85	28.84	28.64	28.90	21.22	21.18	21.00	21.50
	EDGE (8PSK, 1 Tx slot)	24.65	24.52	24.41	25.50				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	26.97	26.96	26.92	27.10	20.33	20.30	20.24	20.89
	EDGE (8PSK, 2 Tx slots)	22.61	22.57	22.48	23.70				

<Reduced Power Mode>

Band GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)		30.03	30.05	30.00	30.40	21.03	21.05	21.00	21.40
GPRS (GMSK, 1 Tx slot)		30.04	30.08	30.02	30.40	21.04	21.08	21.02	21.40
GPRS (GMSK, 2 Tx slots)		27.42	27.52	27.38	27.70	21.42	21.52	21.38	21.70
GPRS (GMSK, 3 Tx slots)		25.37	25.34	25.27	25.70	21.11	21.08	21.01	21.44
GPRS (GMSK, 4 Tx slots)		23.88	23.89	23.85	24.20	20.88	20.89	20.85	21.20
EDGE (8PSK, 1 Tx slot)		25.98	25.91	25.86	27.00	16.98	16.91	16.86	18.00
EDGE (8PSK, 2 Tx slots)		24.66	24.67	24.65	25.50	18.66	18.67	18.65	19.50
EDGE (8PSK, 3 Tx slots)		22.67	22.64	22.57	23.70	18.41	18.38	18.31	19.44
EDGE (8PSK, 4 Tx slots)		20.49	20.49	20.43	21.00	17.49	17.49	17.43	18.00
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.34	27.35	27.31	27.70	21.36	21.37	21.33	21.68
	GPRS (GMSK, 1 Tx slot)	27.43	27.44	27.40	27.70				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.29	27.35	27.30	27.70	21.32	21.37	21.33	21.68
	GPRS (GMSK, 1 Tx slot)	27.40	27.43	27.40	27.70				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	25.29	25.26	25.19	25.70	21.08	21.05	20.98	21.44
	GPRS (GMSK, 2 Tx slots)	25.36	25.34	25.27	25.70				
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.40	27.42	27.38	27.70	20.24	20.25	20.20	20.72
	EDGE (8PSK, 1 Tx slot)	24.71	24.70	24.62	25.50				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.40	27.49	27.46	27.70	20.22	20.26	20.21	20.72
	EDGE (8PSK, 1 Tx slot)	24.64	24.59	24.51	25.50				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	25.37	25.35	25.28	25.70	19.50	19.48	19.40	20.21
	EDGE (8PSK, 2 Tx slots)	22.66	22.63	22.55	23.70				

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

Band		WCDMA V		
TX Channel		4132	4182	4233
Rx Channel		4357	4407	4458
Frequency (MHz)		826.4	836.4	846.6
3GPP Rel 99	AMR 12.2Kbps	24.52	24.68	24.72
3GPP Rel 99	RMC 12.2Kbps	24.57	24.72	24.75
3GPP Rel 6	HSDPA Subtest-1	23.00	23.08	23.26
3GPP Rel 6	HSDPA Subtest-2	23.02	23.13	23.32
3GPP Rel 6	HSDPA Subtest-3	22.51	22.59	22.77
3GPP Rel 6	HSDPA Subtest-4	22.52	22.61	22.78
3GPP Rel 6	HSUPA Subtest-1	22.25	22.38	22.50
3GPP Rel 6	HSUPA Subtest-2	22.01	22.11	22.28
3GPP Rel 6	HSUPA Subtest-3	21.36	21.47	21.63
3GPP Rel 6	HSUPA Subtest-4	22.28	22.38	22.54
3GPP Rel 6	HSUPA Subtest-5	23.01	23.10	23.27

**<LTE Conducted Power>****General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.

<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23780	23790	23800	
Frequency (MHz)				709	710	711	
10	QPSK	1	0	23.42	23.79	23.81	24
10	QPSK	1	25	23.25	23.31	23.50	
10	QPSK	1	49	23.15	23.12	23.34	
10	QPSK	25	0	22.15	22.44	22.45	23
10	QPSK	25	12	22.08	22.37	22.38	
10	QPSK	25	25	22.11	22.17	22.14	
10	QPSK	50	0	22.14	22.47	22.38	23
10	16QAM	1	0	22.42	22.74	22.75	
10	16QAM	1	25	22.38	22.46	22.52	
10	16QAM	1	49	22.54	22.36	22.30	22
10	16QAM	25	0	21.18	21.35	21.34	
10	16QAM	25	12	21.16	21.34	21.32	
10	16QAM	25	25	21.11	21.23	22.30	22
10	16QAM	25	25	21.11	21.23	22.30	
10	16QAM	50	0	21.16	21.41	21.34	
Channel				23755	23790	23825	
Frequency (MHz)				706.5	710	713.5	
5	QPSK	1	0	23.48	23.45	23.00	24
5	QPSK	1	12	23.42	23.44	22.94	
5	QPSK	1	24	22.82	22.89	22.56	
5	QPSK	12	0	22.40	22.37	21.84	23
5	QPSK	12	7	22.31	22.34	22.31	
5	QPSK	12	13	22.16	22.29	22.11	
5	QPSK	25	0	22.38	22.41	21.93	23
5	16QAM	1	0	22.75	22.65	22.26	
5	16QAM	1	12	22.73	22.83	22.29	
5	16QAM	1	24	22.58	22.77	22.07	22
5	16QAM	12	0	21.34	21.33	20.88	
5	16QAM	12	7	21.31	21.30	21.06	
5	16QAM	12	13	21.26	21.29	21.11	22
5	16QAM	25	0	21.34	21.35	20.85	



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Measured Power			Tune-up limit (dBm)
Channel				20850	21100	21350	
Frequency (MHz)				2510	2535	2560	
20	QPSK	1	0	19.67	19.74	19.63	20.5
20	QPSK	1	49	19.46	19.62	19.45	
20	QPSK	1	99	19.41	19.57	19.51	
20	QPSK	50	0	19.53	19.62	19.56	20.5
20	QPSK	50	24	19.49	19.59	19.51	
20	QPSK	50	50	18.81	19.11	18.96	
20	QPSK	100	0	19.50	19.58	19.57	20.5
20	16QAM	1	0	19.21	19.41	19.35	
20	16QAM	1	49	19.22	19.28	19.21	
20	16QAM	1	99	19.41	19.28	19.29	20.5
20	16QAM	50	0	19.04	19.15	19.16	
20	16QAM	50	24	19.05	19.16	19.09	
20	16QAM	50	50	19.44	19.43	19.67	20.5
20	16QAM	100	0	19.06	19.24	19.14	
Channel				20825	21100	21375	Tune-up limit (dBm)
Frequency (MHz)				2507.5	2535	2562.5	
15	QPSK	1	0	19.29	19.55	19.51	
15	QPSK	1	37	19.34	19.40	19.29	20.5
15	QPSK	1	74	19.42	19.54	19.40	
15	QPSK	36	0	19.29	19.55	19.41	20.5
15	QPSK	36	20	19.20	19.22	19.25	
15	QPSK	36	39	19.22	19.34	19.11	
15	QPSK	75	0	19.33	19.52	19.50	20.5
15	16QAM	1	0	19.01	19.30	19.22	
15	16QAM	1	37	19.03	19.19	19.13	
15	16QAM	1	74	19.15	19.29	19.15	20.5
15	16QAM	36	0	18.81	19.11	18.96	
15	16QAM	36	20	18.79	19.06	19.04	
15	16QAM	36	39	18.86	18.86	18.95	20.5
15	16QAM	75	0	18.91	19.08	19.02	
Channel				20800	21100	21400	Tune-up limit (dBm)
Frequency (MHz)				2505	2535	2565	
10	QPSK	1	0	19.62	19.75	19.90	
10	QPSK	1	25	19.44	19.69	19.84	20.5
10	QPSK	1	49	19.70	19.65	19.93	
10	QPSK	25	0	19.55	19.63	19.76	20.5
10	QPSK	25	12	19.64	19.55	19.88	
10	QPSK	25	25	19.63	19.43	19.84	
10	QPSK	50	0	19.59	19.59	19.90	20.5
10	16QAM	1	0	19.40	19.48	19.72	
10	16QAM	1	25	19.36	19.48	19.67	
10	16QAM	1	49	19.44	19.43	19.67	20.5
10	16QAM	25	0	19.10	19.15	19.32	
10	16QAM	25	12	19.18	19.14	19.37	
10	16QAM	25	25	19.22	19.11	19.24	20.5
10	16QAM	50	0	19.10	19.15	19.40	



Channel				20775	21100	21425	Tune-up limit (dBm)
Frequency (MHz)				2502.5	2535	2567.5	
5	QPSK	1	0	19.60	19.61	19.86	20.5
5	QPSK	1	12	19.34	19.38	19.79	
5	QPSK	1	24	19.50	19.46	19.87	
5	QPSK	12	0	19.48	19.40	19.83	20.5
5	QPSK	12	7	19.49	19.59	19.51	
5	QPSK	12	13	19.42	19.48	19.37	
5	QPSK	25	0	19.40	19.42	19.75	20.5
5	16QAM	1	0	19.25	19.31	19.50	
5	16QAM	1	12	19.28	19.32	19.59	
5	16QAM	1	24	19.27	19.27	19.58	20.5
5	16QAM	12	0	19.03	19.02	19.34	
5	16QAM	12	7	19.01	19.07	19.01	
5	16QAM	12	13	19.06	19.01	19.05	20.5
5	16QAM	25	0	18.91	19.08	19.34	

<WLAN Conducted Power>**General Note:**

1. For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
2. Per KDB 248227 D01v02r01, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is $< 1.6\text{W/kg}$ and SAR peak to location ratio < 0.04 , no additional SAR measurements for MIMO.
3. Per KDB 248227 D01v02r01, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
4. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
5. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
6. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is $\leq 0.4\text{ W/kg}$, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is $> 0.4\text{ W/kg}$, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is $\leq 0.8\text{ W/kg}$ or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is $> 0.8\text{ W/kg}$, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2\text{ W/kg}$ or all required channels are tested.

<2.4GHz WLAN Chain 0>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
2.4GHz WLAN Chain 0	802.11b	CH 1	2412	1Mbps	13.38	98.93
		CH 6	2437		13.29	
		CH 11	2462		13.18	
		CH 12	2467		13.40	
		CH 13	2472		12.60	
	802.11g	CH 1	2412	6Mbps	13.69	100.00
		CH 6	2437		13.52	
		CH 11	2462		13.49	
		CH 12	2467		9.88	
		CH 13	2472		3.75	
	802.11n-HT20	CH 1	2412	MCS0	13.38	98.39
		CH 6	2437		13.56	
		CH 11	2462		13.48	
		CH 12	2467		8.12	
		CH 13	2472		2.48	

<2.4GHz WLAN Chain 1>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
2.4GHz WLAN Chain 1	802.11b	CH 1	2412	1Mbps	13.88	98.66
		CH 6	2437		13.91	
		CH 11	2462		13.58	
		CH 12	2467		13.82	
		CH 13	2472		12.52	
	802.11g	CH 1	2412	6Mbps	13.99	100.00
		CH 6	2437		13.95	
		CH 11	2462		13.75	
		CH 12	2467		9.73	
		CH 13	2472		2.91	
	802.11n-HT20	CH 1	2412	MCS0	13.88	97.85
		CH 6	2437		13.79	
		CH 11	2462		13.68	
		CH 12	2467		7.68	
		CH 13	2472		1.64	

<2.4GHz WLAN Chain 0+1>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
2.4GHz WLAN Chain 0+1	802.11g	CH 1	2412	6Mbps	17.00	100.00
		CH 6	2437		16.75	
		CH 11	2462		16.47	
		CH 12	2467		12.98	
		CH 13	2472		6.02	
	802.11n-HT20	CH 1	2412	MCS0	16.83	98.40
		CH 6	2437		16.67	
		CH 11	2462		16.57	
		CH 12	2467		11.05	
		CH 13	2472		4.96	

<5GHz WLAN Chain 0>

5.2GHz WLAN Chain 0	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 36	5180	6Mbps	9.61	98.11
		CH 40	5200		9.43	
		CH 44	5220		9.55	
		CH 48	5240		8.98	
	802.11n-HT20	CH 36	5180	MCS0	9.50	97.97
		CH 40	5200		9.29	
		CH 44	5220		9.31	
		CH 48	5240		9.22	
	802.11n-HT40	CH 38	5190	MCS0	9.44	96.62
		CH 46	5230		9.10	
	802.11ac-VHT20	CH 36	5180	MCS0	9.45	97.99
		CH 40	5200		9.42	
		CH 44	5220		8.61	
		CH 48	5240		8.66	
	802.11ac-VHT40	CH 38	5190	MCS0	8.97	96.62
		CH 46	5230		8.56	
	802.11ac-VHT80	CH 42	5210	MCS0	8.78	91.89

5.3GHz WLAN Chain 0	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 52	5260	6Mbps	9.35	98.11
		CH 56	5280		9.63	
		CH 60	5300		9.64	
		CH 64	5320		9.31	
	802.11n-HT20	CH 52	5260	MCS0	9.42	97.97
		CH 56	5280		9.49	
		CH 60	5300		9.59	
		CH 64	5320		9.33	
	802.11n-HT40	CH 54	5270	MCS0	9.48	96.62
		CH 62	5310		9.21	
	802.11ac-VHT20	CH 52	5260	MCS0	9.21	97.99
		CH 56	5280		9.19	
		CH 60	5300		8.93	
		CH 64	5320		8.67	
	802.11ac-VHT40	CH 54	5270	MCS0	9.02	96.62
		CH 62	5310		8.73	
	802.11ac-VHT80	CH 58	5290	MCS0	9.14	91.89

5.5GHz WLAN Chain 0	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 100	5500	6Mbps	9.91	98.11
		CH 116	5580		9.89	
		CH 124	5620		9.44	
		CH 132	5660		9.60	
		CH 144	5720		9.78	
	802.11n-HT20	CH 100	5500	MCS0	9.87	97.97
		CH 116	5580		9.84	
		CH 124	5620		9.57	
		CH 132	5660		9.52	
		CH 144	5720		9.59	
	802.11n-HT40	CH 102	5510	MCS0	9.17	96.62
		CH 110	5550		9.23	
		CH 126	5630		9.20	
		CH 134	5670		9.61	
		CH 142	5710		9.59	
	802.11ac-VHT20	CH 100	5500	MCS0	8.97	97.99
		CH 116	5580		9.36	
		CH 124	5620		9.34	
		CH 132	5660		9.47	
		CH 144	5720		8.98	
	802.11ac-VHT40	CH 102	5510	MCS0	9.09	96.62
		CH 110	5550		9.03	
		CH 126	5630		9.20	
		CH 134	5670		9.23	
		CH 142	5710		9.62	
	802.11ac-VHT80	CH 106	5530	MCS0	9.26	91.89
		CH 122	5610		9.34	
		CH 138	5690		9.58	

5.8GHz WLAN Chain 0	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 149	5745	MCS0	9.14	98.11
		CH 157	5785		9.16	
		CH 165	5825		9.07	
	802.11n-HT20	CH 149	5745	MCS0	9.11	97.97
		CH 157	5785		9.03	
		CH 165	5825		8.87	
	802.11n-HT40	CH 151	5755	MCS0	9.36	96.62
		CH 159	5795		8.96	
	802.11ac-VHT20	CH 149	5745	MCS0	9.16	97.99
		CH 157	5785		8.94	
		CH 165	5825		9.21	
	802.11ac-VHT40	CH 151	5755	MCS0	9.35	96.62
		CH 159	5795		8.93	
	802.11ac-VHT80	CH 155	5775	MCS0	9.16	91.89

<5GHz WLAN Chain 1>

5.2GHz WLAN Chain 1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 36	5180	6Mbps	9.70	98.13
		CH 40	5200		9.61	
		CH 44	5220		9.44	
		CH 48	5240		9.43	
	802.11n-HT20	CH 36	5180	MCS0	9.62	97.97
		CH 40	5200		9.57	
		CH 44	5220		9.60	
		CH 48	5240		9.65	
	802.11n-HT40	CH 38	5190	MCS0	9.48	95.95
		CH 46	5230		9.72	
	802.11ac-VHT20	CH 36	5180	MCS0	9.17	97.97
		CH 40	5200		9.15	
		CH 44	5220		9.56	
		CH 48	5240		9.61	
	802.11ac-VHT40	CH 38	5190	MCS0	9.82	96.62
		CH 46	5230		9.84	
	802.11ac-VHT80	CH 42	5210	MCS0	9.47	91.78

5.3GHz WLAN Chain 1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 52	5260	6Mbps	9.74	98.13
		CH 56	5280		9.58	
		CH 60	5300		9.59	
		CH 64	5320		9.63	
	802.11n-HT20	CH 52	5260	MCS0	9.64	97.97
		CH 56	5280		9.47	
		CH 60	5300		9.51	
		CH 64	5320		9.58	
	802.11n-HT40	CH 54	5270	MCS0	9.44	95.95
		CH 62	5310		9.52	
	802.11ac-VHT20	CH 52	5260	MCS0	9.26	97.97
		CH 56	5280		9.22	
		CH 60	5300		9.19	
		CH 64	5320		9.54	
	802.11ac-VHT40	CH 54	5270	MCS0	9.83	96.62
		CH 62	5310		9.84	
	802.11ac-VHT80	CH 58	5290	MCS0	9.47	91.78

5.5GHz WLAN Chain 1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 100	5500	6Mbps	9.68	98.13
		CH 116	5580		9.55	
		CH 124	5620		9.51	
		CH 132	5660		9.50	
		CH 144	5720		9.85	
	802.11n-HT20	CH 100	5500	MCS0	9.58	97.97
		CH 116	5580		9.59	
		CH 124	5620		9.54	
		CH 132	5660		9.35	
		CH 144	5720		9.79	
	802.11n-HT40	CH 102	5510	MCS0	9.37	95.95
		CH 110	5550		9.67	
		CH 126	5630		9.58	
		CH 134	5670		9.51	
		CH 142	5710		9.65	
	802.11ac-VHT20	CH 100	5500	MCS0	9.26	97.97
		CH 116	5580		8.69	
		CH 124	5620		9.49	
		CH 132	5660		9.51	
		CH 144	5720		9.90	
	802.11ac-VHT40	CH 102	5510	MCS0	9.81	96.62
		CH 110	5550		9.83	
		CH 126	5630		9.82	
		CH 134	5670		9.80	
		CH 142	5710		8.95	
	802.11ac-VHT80	CH 106	5530	MCS0	9.41	91.78
		CH 122	5610		9.50	
		CH 138	5690		9.62	

5.8GHz WLAN Chain 1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 149	5745	MCS0	9.41	98.13
		CH 157	5785		9.19	
		CH 165	5825		9.39	
	802.11n-HT20	CH 149	5745	MCS0	9.31	97.97
		CH 157	5785		9.17	
		CH 165	5825		9.64	
	802.11n-HT40	CH 151	5755	MCS0	9.68	95.95
		CH 159	5795		9.63	
	802.11ac-VHT20	CH 149	5745	MCS0	9.33	97.97
		CH 157	5785		9.13	
		CH 165	5825		9.44	
	802.11ac-VHT40	CH 151	5755	MCS0	9.56	96.62
		CH 159	5795		9.22	
	802.11ac-VHT80	CH 155	5775	MCS0	9.65	91.78

<5GHz WLAN Chain 0+1>

5.2GHz WLAN Chain 0+1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 36	5180	6Mbps	12.65	99.12
		CH 40	5200		12.52	
		CH 44	5220		12.53	
		CH 48	5240		12.35	
	802.11n-HT20	CH 36	5180	MCS0	12.60	98.01
		CH 40	5200		12.42	
		CH 44	5220		12.41	
		CH 48	5240		12.36	
	802.11n-HT40	CH 38	5190	MCS0	12.31	97.37
		CH 46	5230		12.55	
	802.11ac-VHT20	CH 36	5180	MCS0	12.31	98.68
		CH 40	5200		12.25	
		CH 44	5220		12.15	
		CH 48	5240		12.17	
	802.11ac-VHT40	CH 38	5190	MCS0	12.09	96.05
		CH 46	5230		12.03	
	802.11ac-VHT80	CH 42	5210	MCS0	12.25	94.57

5.5GHz WLAN Chain 0+1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 52	5260	6Mbps	12.52	99.12
		CH 56	5280		12.50	
		CH 60	5300		12.51	
		CH 64	5320		12.59	
	802.11n-HT20	CH 52	5260	MCS0	12.51	98.01
		CH 56	5280		12.52	
		CH 60	5300		12.55	
		CH 64	5320		12.35	
	802.11n-HT40	CH 54	5270	MCS0	12.28	97.37
		CH 62	5310		12.41	
	802.11ac-VHT20	CH 52	5260	MCS0	12.19	98.68
		CH 56	5280		12.15	
		CH 60	5300		11.92	
		CH 64	5320		12.07	
	802.11ac-VHT40	CH 54	5270	MCS0	12.19	96.05
		CH 62	5310		12.33	
	802.11ac-VHT80	CH 58	5290	MCS0	12.23	94.57

5.5GHz WLAN Chain 0+1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 100	5500	6Mbps	12.75	99.12
		CH 116	5580		12.60	
		CH 124	5620		12.54	
		CH 132	5660		12.57	
		CH 144	5720		12.90	
	802.11n-HT20	CH 100	5500	MCS0	12.74	98.01
		CH 116	5580		12.74	
		CH 124	5620		12.65	
		CH 132	5660		12.41	
		CH 144	5720		12.89	
	802.11n-HT40	CH 102	5510	MCS0	12.29	97.37
		CH 110	5550		12.47	
		CH 126	5630		12.46	
		CH 134	5670		12.46	
		CH 142	5710		12.55	
	802.11ac-VHT20	CH 100	5500	MCS0	12.03	98.68
		CH 116	5580		12.09	
		CH 124	5620		11.98	
		CH 132	5660		11.96	
		CH 144	5720		12.71	
	802.11ac-VHT40	CH 102	5510	MCS0	12.09	96.05
		CH 110	5550		12.36	
		CH 126	5630		12.21	
		CH 134	5670		12.13	
		CH 142	5710		12.86	
	802.11ac-VHT80	CH 106	5530	MCS0	12.13	94.57
		CH 122	5610		12.21	
		CH 138	5690		12.34	

5.8GHz WLAN Chain 0+1	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 149	5745	MCS0	12.16	99.12
		CH 157	5785		12.22	
		CH 165	5825		12.17	
	802.11n-HT20	CH 149	5745	MCS0	12.04	98.01
		CH 157	5785		11.95	
		CH 165	5825		12.16	
	802.11n-HT40	CH 151	5755	MCS0	12.29	97.37
		CH 159	5795		12.09	
	802.11ac-VHT20	CH 149	5745	MCS0	11.98	98.68
		CH 157	5785		12.00	
		CH 165	5825		12.16	
	802.11ac-VHT40	CH 151	5755	MCS0	12.16	96.05
		CH 159	5795		12.14	
	802.11ac-VHT80	CH 155	5775	MCS0	12.25	94.57

13. Bluetooth Exclusions Applied

Mode Band	Average power(dBm)		
2.4GHz Bluetooth Version 4.1 with LE	BR	EDR	BLE
	11.50	8.50	7.50

Note:

- Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Exposure position: body-worn accessory			
Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
11.5	15mm	2.48	1.47

Note:

Per KDB 447498 D01v05r02, The test exclusion threshold is 1.47 which is ≤ 3 for 1g SAR and ≤ 7.5 for 10g SAR, therefore SAR testing is not required.

14. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	$\leq 25\text{mm}$	$\leq 25\text{mm}$	$> 25\text{mm}$	$\leq 25\text{mm}$	$\leq 25\text{mm}$	$\leq 25\text{mm}$
BT & WLAN MIMO	$\leq 25\text{mm}$	$\leq 25\text{mm}$	$\leq 25\text{mm}$	$> 25\text{mm}$	$\leq 25\text{mm}$	$\leq 25\text{mm}$

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT & WLAN MIMO	Yes	Yes	Yes	No	Yes	Yes

General Note:

- Referring to KDB 941225 D06 v02, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
- Since the device supports 2x2 MIMO Tx for IEEE 802.11, only bottom side can be excluded according to antenna location.
- The detail antenna location please refers to Appendix D.

15. SAR Test Results

General Note:

1. Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
4. When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900.

GSM Note:

1. Per KDB 941225 D01v03, Head / Hotspot / Body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850 and GPRS (4Tx slots) for GSM1900, when hotspot is enabled power reduction will be activated to limit the maximum power, therefore, the EUT was set in GPRS (2Tx slots) for GSM1900.

UMTS Note:

1. Per KDB 941225 D01v03, SAR for Head / Hotspot / Body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq 1/4$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

**LTE Note:**

1. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r03, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r03, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.

WLAN Note:

1. Per KDB 248227 D01v02r01, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r01, for U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
6. Per KDB 248227 D01v02r01, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg and SAR peak to location ratio < 0.04 , no additional SAR measurements for MIMO.
7. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

15.1 Head SAR

<GSM SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
01	GSM850	GMSK	GPRS (4 Tx slots)	Right Cheek	0mm	251	848.8	28.89	28.90	1.002	-0.04	0.276	0.277	0.220	0.221
	GSM850	GMSK	GPRS (4 Tx slots)	Right Tilted	0mm	251	848.8	28.89	28.90	1.002	-0.01	0.112	0.112	0.088	0.088
	GSM850	GMSK	GPRS (4 Tx slots)	Left Cheek	0mm	251	848.8	28.89	28.90	1.002	-0.03	0.229	0.230	0.185	0.185
	GSM850	GMSK	GPRS (4 Tx slots)	Left Tilted	0mm	251	848.8	28.89	28.90	1.002	-0.05	0.109	0.109	0.086	0.086
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Cheek	0mm	661	1880	25.88	25.90	1.005	-0.02	0.087	0.087	0.057	0.057
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Tilted	0mm	661	1880	25.88	25.90	1.005	0.02	0.059	0.059	0.033	0.033
02	GSM1900	GMSK	GPRS (4 Tx slots)	Left Cheek	0mm	661	1880	25.88	25.90	1.005	-0.11	0.180	0.181	0.113	0.114
	GSM1900	GMSK	GPRS (4 Tx slots)	Left Tilted	0mm	661	1880	25.88	25.90	1.005	0.17	0.033	0.033	0.018	0.018

<WCDMA SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
03	WCDMA V	QPSK	RMC 12.2Kbps	Right Cheek	0mm	4233	846.6	24.75	24.90	1.035	0.04	0.330	0.342	0.262	0.271
	WCDMA V	QPSK	RMC 12.2Kbps	Right Tilted	0mm	4233	846.6	24.75	24.90	1.035	-0.04	0.138	0.143	0.110	0.114
	WCDMA V	QPSK	RMC 12.2Kbps	Left Cheek	0mm	4233	846.6	24.75	24.90	1.035	-0.03	0.274	0.284	0.221	0.229
	WCDMA V	QPSK	RMC 12.2Kbps	Left Tilted	0mm	4233	846.6	24.75	24.90	1.035	-0.13	0.129	0.134	0.104	0.108

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
04	LTE Band 17	10M	QPSK	1	0	Right Cheek	0mm	23800	711	23.81	24.00	1.045	-0.01	0.141	0.147	0.113	0.118
	LTE Band 17	10M	QPSK	25	0	Right Cheek	0mm	23800	711	22.45	23.00	1.135	-0.02	0.110	0.125	0.087	0.099
	LTE Band 17	10M	QPSK	1	0	Right Tilted	0mm	23800	711	23.81	24.00	1.045	-0.1	0.065	0.068	0.053	0.055
	LTE Band 17	10M	QPSK	25	0	Right Tilted	0mm	23800	711	22.45	23.00	1.135	0.04	0.048	0.054	0.039	0.044
	LTE Band 17	10M	QPSK	1	0	Left Cheek	0mm	23800	711	23.81	24.00	1.045	-0.06	0.118	0.123	0.097	0.101
	LTE Band 17	10M	QPSK	25	0	Left Cheek	0mm	23800	711	22.45	23.00	1.135	-0.01	0.091	0.103	0.074	0.084
	LTE Band 17	10M	QPSK	1	0	Left Tilted	0mm	23800	711	23.81	24.00	1.045	0.14	0.062	0.065	0.051	0.053
	LTE Band 17	10M	QPSK	25	0	Left Tilted	0mm	23800	711	22.45	23.00	1.135	0.1	0.046	0.052	0.038	0.043
	LTE Band 7	20M	QPSK	1	0	Right Cheek	0mm	21100	2535	19.74	20.50	1.191	-0.15	0.084	0.100	0.048	0.057
	LTE Band 7	20M	QPSK	50	0	Right Cheek	0mm	21100	2535	19.62	20.50	1.225	-0.01	0.087	0.107	0.046	0.056
	LTE Band 7	20M	QPSK	1	0	Right Tilted	0mm	21100	2535	19.74	20.50	1.191	0.13	0.061	0.073	0.028	0.033
	LTE Band 7	20M	QPSK	50	0	Right Tilted	0mm	21100	2535	19.62	20.50	1.225	0.13	0.066	0.081	0.031	0.038
	LTE Band 7	20M	QPSK	1	0	Left Cheek	0mm	21100	2535	19.74	20.50	1.191	-0.04	0.203	0.242	0.106	0.126
05	LTE Band 7	20M	QPSK	50	0	Left Cheek	0mm	21100	2535	19.62	20.50	1.225	-0.04	0.205	0.251	0.106	0.130
	LTE Band 7	20M	QPSK	1	0	Left Tilted	0mm	21100	2535	19.74	20.50	1.191	0.12	0.047	0.056	0.02	0.024
	LTE Band 7	20M	QPSK	50	0	Left Tilted	0mm	21100	2535	19.62	20.50	1.225	-0.07	0.048	0.059	0.021	0.026

**<WLAN SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Chain	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
06	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Cheek	0mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.04	0.090	0.105	0.052	0.061
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Tilted	0mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.09	0.081	0.094	0.039	0.045
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Cheek	0mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.02	0.277	0.323	0.135	0.157
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Cheek	0mm	Chain 0	13	2472	12.60	13.25	1.161	98.93	1.011	-0.13	0.164	0.193	0.079	0.093
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Tilted	0mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.19	0.110	0.128	0.052	0.061
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Cheek	0mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.05	0.221	0.229	0.104	0.108
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Tilted	0mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.07	0.129	0.134	0.054	0.056
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Cheek	0mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	0.02	0.077	0.080	0.030	0.031
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Tilted	0mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.08	0.049	0.051	0.021	0.022
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	-0.15	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0.02	0.007	0.010	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0.04	0.006	0.008	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0.1	0.069	0.085	0.009	0.011
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0.19	0.002	0.002	0.001	0.001
07	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	-0.1	0.012	0.015	0.002	0.002
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	-0.11	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	0.15	0.006	0.007	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	-0.05	0.067	0.080	0.009	0.011
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	0.01	0.010	0.012	0.001	0.002
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	0.15	0.226	0.269	0.057	0.068
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	0.15	0.110	0.131	0.031	0.037
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	-0.12	0.098	0.117	0.022	0.026
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	0	0.001	0.001	0.001	0.001
08	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.04	0.001	0.002	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.07	0.003	0.004	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.02	0.010	0.013	0.002	0.002
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.01	0.014	0.018	0.002	0.002
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0.17	0.168	0.198	0.037	0.044
09	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0.1	0.097	0.115	0.018	0.021
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	-0.1	0.012	0.014	0.002	0.002
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0	0.001	0.001	0.001	0.001

**15.2 Hotspot SAR****<GSM SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GMSK	GPRS (4 Tx slots)	Front	10mm	OFF	251	848.8	28.89	28.90	1.002	-0.09	0.322	0.323	0.243	0.244
	GSM850	GMSK	GPRS (4 Tx slots)	Back	10mm	OFF	251	848.8	28.89	28.90	1.002	-0.07	0.342	0.343	0.255	0.256
	GSM850	GMSK	GPRS (4 Tx slots)	Left Side	10mm	OFF	251	848.8	28.89	28.90	1.002	-0.01	0.114	0.114	0.081	0.081
10	GSM850	GMSK	GPRS (4 Tx slots)	Right Side	10mm	OFF	251	848.8	28.89	28.90	1.002	-0.03	0.389	0.390	0.270	0.271
	GSM850	GMSK	GPRS (4 Tx slots)	Bottom Side	10mm	OFF	251	848.8	28.89	28.90	1.002	0.04	0.133	0.133	0.074	0.074
	GSM1900	GMSK	GPRS (2 Tx slots)	Front	10mm	ON	661	1880	27.52	27.70	1.042	-0.12	0.563	0.587	0.300	0.313
	GSM1900	GMSK	GPRS (2 Tx slots)	Back	10mm	ON	661	1880	27.52	27.70	1.042	-0.05	0.628	0.655	0.339	0.353
	GSM1900	GMSK	GPRS (2 Tx slots)	Left side	10mm	ON	661	1880	27.52	27.70	1.042	-0.08	0.196	0.204	0.120	0.125
	GSM1900	GMSK	GPRS (2 Tx slots)	Right Side	10mm	ON	661	1880	27.52	27.70	1.042	-0.14	0.031	0.032	0.018	0.019
11	GSM1900	GMSK	GPRS (2 Tx slots)	Bottom Side	10mm	ON	661	1880	27.52	27.70	1.042	-0.19	1.080	1.126	0.567	0.591
	GSM1900	GMSK	GPRS (2 Tx slots)	Bottom Side	10mm	ON	512	1850.2	27.42	27.70	1.067	-0.021	1.010	1.077	0.516	0.550
	GSM1900	GMSK	GPRS (2 Tx slots)	Bottom Side	10mm	ON	810	1909.8	27.38	27.70	1.076	0.029	1.040	1.120	0.516	0.555

<WCDMA SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA V	QPSK	RMC 12.2Kbps	Front	10mm	OFF	4233	846.6	24.75	24.90	1.035	-0.08	0.393	0.407	0.301	0.312
	WCDMA V	QPSK	RMC 12.2Kbps	Back	10mm	OFF	4233	846.6	24.75	24.90	1.035	-0.09	0.415	0.430	0.312	0.323
	WCDMA V	QPSK	RMC 12.2Kbps	Left Side	10mm	OFF	4233	846.6	24.75	24.90	1.035	-0.04	0.161	0.167	0.114	0.118
12	WCDMA V	QPSK	RMC 12.2Kbps	Right Side	10mm	OFF	4233	846.6	24.75	24.90	1.035	-0.02	0.497	0.514	0.340	0.352
	WCDMA V	QPSK	RMC 12.2Kbps	Bottom Side	10mm	OFF	4233	846.6	24.75	24.90	1.035	-0.08	0.050	0.052	0.028	0.029



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 17	10M	QPSK	1	0	Front	10mm	OFF	23800	711	23.81	24.00	1.045	-0.06	0.241	0.252	0.192	0.201
	LTE Band 17	10M	QPSK	25	0	Front	10mm	OFF	23800	711	22.45	23.00	1.135	-0.04	0.192	0.218	0.153	0.174
13	LTE Band 17	10M	QPSK	1	0	Back	10mm	OFF	23800	711	23.81	24.00	1.045	0.07	0.260	0.272	0.205	0.214
	LTE Band 17	10M	QPSK	25	0	Back	10mm	OFF	23800	711	22.45	23.00	1.135	-0.05	0.205	0.233	0.161	0.183
	LTE Band 17	10M	QPSK	1	0	Left Side	10mm	OFF	23800	711	23.81	24.00	1.045	-0.08	0.149	0.156	0.109	0.114
	LTE Band 17	10M	QPSK	25	0	Left Side	10mm	OFF	23800	711	22.45	23.00	1.135	-0.08	0.115	0.131	0.084	0.095
	LTE Band 17	10M	QPSK	1	0	Right Side	10mm	OFF	23800	711	23.81	24.00	1.045	-0.05	0.206	0.215	0.148	0.155
	LTE Band 17	10M	QPSK	25	0	Right Side	10mm	OFF	23800	711	22.45	23.00	1.135	0.05	0.162	0.184	0.116	0.132
	LTE Band 17	10M	QPSK	1	0	Bottom Side	10mm	OFF	23800	711	23.81	24.00	1.045	0.01	0.029	0.030	0.018	0.019
	LTE Band 17	10M	QPSK	25	0	Bottom Side	10mm	OFF	23800	711	22.45	23.00	1.135	0.08	0.023	0.026	0.014	0.016
	LTE Band 7	20M	QPSK	1	0	Front	10mm	OFF	21100	2535	19.74	20.50	1.191	-0.03	0.351	0.418	0.185	0.220
	LTE Band 7	20M	QPSK	50	0	Front	10mm	OFF	21100	2535	19.62	20.50	1.225	-0.03	0.351	0.430	0.185	0.227
	LTE Band 7	20M	QPSK	1	0	Back	10mm	OFF	21100	2535	19.74	20.50	1.191	-0.01	0.382	0.455	0.196	0.233
14	LTE Band 7	20M	QPSK	50	0	Back	10mm	OFF	21100	2535	19.62	20.50	1.225	-0.09	0.388	0.475	0.198	0.242
	LTE Band 7	20M	QPSK	1	0	Left Side	10mm	OFF	21100	2535	19.74	20.50	1.191	-0.03	0.327	0.390	0.166	0.198
	LTE Band 7	20M	QPSK	50	0	Left Side	10mm	OFF	21100	2535	19.62	20.50	1.225	-0.04	0.320	0.392	0.162	0.198
	LTE Band 7	20M	QPSK	1	0	Right Side	10mm	OFF	21100	2535	19.74	20.50	1.191	-0.04	0.003	0.003	0.001	0.001
	LTE Band 7	20M	QPSK	50	0	Right Side	10mm	OFF	21100	2535	19.62	20.50	1.225	0.01	0.001	0.001	0.001	0.001
	LTE Band 7	20M	QPSK	1	0	Bottom Side	10mm	OFF	21100	2535	19.74	20.50	1.191	-0.07	0.353	0.421	0.170	0.203
	LTE Band 7	20M	QPSK	50	0	Bottom Side	10mm	OFF	21100	2535	19.62	20.50	1.225	-0.1	0.341	0.418	0.164	0.201

<WLAN SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Chain	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	10mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.02	0.042	0.049	0.024	0.028
15	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	10mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.14	0.089	0.104	0.039	0.045
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Side	10mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.04	0.003	0.003	0.001	0.001
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Side	10mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	0.07	0.012	0.014	0.005	0.006
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Top Side	10mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.12	0.022	0.026	0.010	0.012
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	10mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.17	0.024	0.025	0.012	0.012
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	10mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.13	0.066	0.068	0.025	0.026
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Side	10mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.06	0.017	0.018	0.005	0.005
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Side	10mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	0	0.001	0.002	0.001	0.001
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Top Side	10mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.04	0.006	0.006	0.002	0.002

15.3 Phablet SAR Test Considerations

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM1900	GMSK	GPRS (2 Tx slots)	Bottom Side	10mm	661	1880	27.52	28.90	1.374	-0.19	1.080	1.484

General Note:

- When hotspot mode is enabled, power reduction will be activated to limit the maximum output power of GSM1900. The scaled SAR above is used to determine the phablet SAR test reduction, not for reporting
- Per KDB648474 D04v01r02, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g extremity SAR is required with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.
- Extremity SAR test is required as hotspot mode 1-g reported SAR is > 1.2 W/kg

15.4 Extremity SAR

<GSM SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM1900	GMSK	GPRS (4 Tx slots)	Front	0mm	661	1880	25.88	25.90	1.005	0	1.930	1.939
	GSM1900	GMSK	GPRS (4 Tx slots)	Back	0mm	661	1880	25.88	25.90	1.005	0.01	2.330	2.341
	GSM1900	GMSK	GPRS (4 Tx slots)	Back	0mm	512	1850.2	25.83	25.90	1.016	0.002	2.400	2.439
16	GSM1900	GMSK	GPRS (4 Tx slots)	Back	0mm	810	1909.8	25.82	25.90	1.019	-0.057	2.420	2.465
	GSM1900	GMSK	GPRS (4 Tx slots)	Left Side	0mm	661	1880	25.88	25.90	1.005	0.027	0.502	0.504
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Side	0mm	661	1880	25.88	25.90	1.005	-0.166	0.027	0.027
	GSM1900	GMSK	GPRS (4 Tx slots)	Bottom Side	0mm	661	1880	25.88	25.90	1.005	0.032	0.426	0.428
	GSM1900	GMSK	GPRS (4 Tx slots)	Bottom Side	0mm	512	1850.2	25.83	25.90	1.016	0.014	0.440	0.447
	GSM1900	GMSK	GPRS (4 Tx slots)	Bottom Side	0mm	810	1850.2	25.82	25.90	1.019	0.051	0.373	0.380



<WLAN SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Chain	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0.15	0.025	0.033
17	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0.17	0.340	0.451
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0.01	0.016	0.021
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Side	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	-0.09	0.024	0.032
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0.19	0.002	0.002
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0.1	0.039	0.048
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	-0.13	0.174	0.214
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	-0.1	0.013	0.016
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Side	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0.11	0.004	0.005
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0.18	0.003	0.003
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	-0.05	0.051	0.061
18	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	0.12	0.573	0.687
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	-0.13	0.007	0.009
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Side	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	0.1	0.060	0.072
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	0.06	0.005	0.006
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	0.1	0.089	0.106
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	-0.19	0.227	0.270
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	-0.07	0.022	0.026
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Side	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	0	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	-0.07	0.017	0.020
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.1	0.008	0.010
19	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.1	0.420	0.554
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	-0.13	0.006	0.007
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Side	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.05	0.039	0.051
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.18	0.003	0.004
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0.07	0.072	0.085
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	-0.12	0.176	0.208
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	-0.1	0.019	0.022
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Right Side	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	-0.17	0.021	0.025



15.5 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
20	GSM850	GMSK	GPRS (4 Tx slots)	Front	15mm	251	848.8	28.89	28.90	1.002	-0.04	0.243	0.244	0.192	0.192
	GSM850	GMSK	GPRS (4 Tx slots)	Back	15mm	251	848.8	28.89	28.90	1.002	-0.08	0.238	0.239	0.188	0.188
	GSM1900	GMSK	GPRS (4 Tx slots)	Front	15mm	661	1880	25.88	25.90	1.005	-0.08	0.287	0.288	0.165	0.166
21	GSM1900	GMSK	GPRS (4 Tx slots)	Back	15mm	661	1880	25.88	25.90	1.005	-0.16	0.337	0.339	0.194	0.195

<WCDMA SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
22	WCDMA V	QPSK	RMC 12.2Kbps	Front	15mm	4233	846.6	24.75	24.90	1.035	-0.03	0.304	0.315	0.241	0.249
	WCDMA V	QPSK	RMC 12.2Kbps	Back	15mm	4233	846.6	24.75	24.90	1.035	-0.03	0.300	0.311	0.237	0.245

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 17	10M	QPSK	1	0	Front	15mm	23800	711	23.81	24.00	1.045	-0.03	0.226	0.236	0.180	0.188
	LTE Band 17	10M	QPSK	25	0	Front	15mm	23800	711	22.45	23.00	1.135	-0.03	0.177	0.201	0.141	0.160
23	LTE Band 17	10M	QPSK	1	0	Back	15mm	23800	711	23.81	24.00	1.045	-0.13	0.236	0.247	0.187	0.195
	LTE Band 17	10M	QPSK	25	0	Back	15mm	23800	711	22.45	23.00	1.135	-0.09	0.185	0.210	0.147	0.167
	LTE Band 7	20M	QPSK	1	0	Front	15mm	21100	2535	19.74	20.50	1.191	0.01	0.16	0.191	0.087	0.104
	LTE Band 7	20M	QPSK	50	0	Front	15mm	21100	2535	19.62	20.50	1.225	-0.02	0.161	0.197	0.087	0.107
	LTE Band 7	20M	QPSK	1	0	Back	15mm	21100	2535	19.74	20.50	1.191	-0.15	0.171	0.204	0.09	0.107
24	LTE Band 7	20M	QPSK	50	0	Back	15mm	21100	2535	19.62	20.50	1.225	-0.06	0.172	0.211	0.091	0.111

<WLAN SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Chain	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
25	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	15mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	0	0.025	0.029	0.014	0.016
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	15mm	Chain 0	1	2412	13.38	14.00	1.153	98.93	1.011	-0.14	0.038	0.044	0.018	0.021
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	15mm	Chain 0	13	2472	12.60	13.25	1.161	98.93	1.011	-0.1	0.025	0.029	0.011	0.013
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	15mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.14	0.010	0.010	0.004	0.004
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	15mm	Chain 1	6	2437	13.91	14.00	1.021	98.66	1.014	-0.11	0.021	0.022	0.008	0.008
26	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	15mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	0	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	15mm	Chain 0	58	5290	9.14	10.00	1.219	91.89	1.088	-0.16	0.016	0.021	0.003	0.004
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	15mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	15mm	Chain 1	58	5290	9.47	10.00	1.130	91.78	1.090	0.1	0.011	0.014	0.002	0.003
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	15mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	0	0.001	0.001	0.001	0.001
27	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	15mm	Chain 0	138	5690	9.58	10.00	1.102	91.89	1.088	-0.1	0.066	0.079	0.022	0.026
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	15mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	0	0.013	0.015	0.004	0.005
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	15mm	Chain 1	138	5690	9.62	10.00	1.091	91.78	1.090	-0.16	0.019	0.023	0.004	0.005
28	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	15mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0	0.001	0.001	0.001	0.001
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	15mm	Chain 0	155	5775	9.16	10.00	1.213	91.89	1.088	0.09	0.056	0.074	0.019	0.025
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Front	15mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0.12	0.015	0.018	0.004	0.004
	WLAN5GHz	OFDM	802.11ac-VHT80 MCS0	Back	15mm	Chain 1	155	5775	9.65	10.00	1.084	91.78	1.090	0.14	0.020	0.024	0.003	0.004

15.6 Repeated SAR Measurement
<1g Repeated SAR>

No.	Band	Modulation	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	GSM1900	GMSK	GPRS (2 Tx slots)	Bottom Side	10mm	ON	661	1880	27.52	27.70	1.042	-0.19	1.080	-	1.126
2nd	GSM1900	GMSK	GPRS (2 Tx slots)	Bottom Side	10mm	ON	661	1880	27.52	27.70	1.042	-0.011	1.050	1.03	1.094

<10g Repeated SAR>

No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	GSM1900	GMSK	GPRS (4 Tx slots)	Back	0mm	810	1909.8	25.82	25.90	1.019	-0.057	2.420	-	2.465
2nd	GSM1900	GMSK	GPRS (4 Tx slots)	Back	0mm	810	1909.8	25.82	25.90	1.019	0.04	2.310	1.05	2.439

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. Per KDB 865664 D01v01r03, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The ratio is the difference in percentage between original and repeated *measured SAR*.
5. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset				Note
		Head	Body-worn	Hotspot	Extremity	
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes	
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes	Hotspot
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes	Hotspot
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes	Hotspot
5.	GSM Voice + Bluetooth		Yes		Yes	
6.	GPRS/EDGE + Bluetooth		Yes		Yes	WWAN VoIP
7.	WCDMA+ Bluetooth		Yes		Yes	WWAN VoIP
8.	LTE + Bluetooth		Yes		Yes	WWAN VoIP
9.	GSM Voice + WLAN5GHz	Yes	Yes		Yes	
10.	GPRS/EDGE + WLAN5GHz	Yes	Yes		Yes	WWAN VoIP
11.	WCDMA + WLAN5GHz	Yes	Yes		Yes	WWAN VoIP
12.	LTE + WLAN5GHz	Yes	Yes		Yes	WWAN VoIP
13.	GSM Voice + WLAN5GHz + Bluetooth		Yes		Yes	
14.	GPRS/EDGE + WLAN5GHz + Bluetooth		Yes		Yes	
15.	WCDMA + WLAN5GHz + Bluetooth		Yes		Yes	
16.	LTE + WLAN5GHz + Bluetooth		Yes		Yes	
17.	WLAN Chain 0 + WLAN Chain 1	Yes	Yes	Yes	Yes	

General Note:

- The worst case WLAN reported SAR for each configuration was used for SAR summation. Therefore, the following summations represent the absolute worst cases for simultaneous transmission with WLAN.
- For WLAN, the transmit power of each chain transmit power in SISO mode is equal or higher than that in MIMO operation, and the assessment for MIMO mode can be performed in the simultaneous transmission analysis of standalone SAR of each chain tested in SISO mode. In this report, the assessment was performed in the simultaneous transmission analysis of WWAN and WLAN transmitters.
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
- Standalone SAR in the same exposure positions are summed
- Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation < 1.6W/kg.
 - $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
- For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v05r02 based on the formula below.
 - $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - When the minimum separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
 - 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Bluetooth Max Power	Exposure Position	Body-worn	Extremity
	Test separation	15 mm	< 5 mm
11.5dBm	Estimated SAR (W/kg)	0.196 1g SAR W/kg	0.235 10g SAR W/kg



16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	5	6	1+2+3 Summed 1g SAR (W/kg)	1+5+6 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	5GHz WALN Chain 0	5GHz WALN Chain 1		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Right Cheek	0.277	0.105	0.229	0.002	0.269	0.61	0.55
		Right Tilted	0.112	0.094	0.134	0.007	0.131	0.34	0.25
		Left Cheek	0.230	0.323	0.080	0.080	0.117	0.63	0.43
		Left Tilted	0.109	0.128	0.051	0.018	0.001	0.29	0.13
	GSM1900	Right Cheek	0.087	0.105	0.229	0.002	0.269	0.42	0.36
		Right Tilted	0.059	0.094	0.134	0.007	0.131	0.29	0.20
		Left Cheek	0.181	0.323	0.080	0.080	0.117	0.58	0.38
		Left Tilted	0.033	0.128	0.051	0.018	0.001	0.21	0.05
WCDMA	WCDMA V	Right Cheek	0.342	0.105	0.229	0.002	0.269	0.68	0.61
		Right Tilted	0.143	0.094	0.134	0.007	0.131	0.37	0.28
		Left Cheek	0.284	0.323	0.080	0.080	0.117	0.69	0.48
		Left Tilted	0.134	0.128	0.051	0.018	0.001	0.31	0.15
LTE	LTE Band 17	Right Cheek	0.147	0.105	0.229	0.002	0.269	0.48	0.42
		Right Tilted	0.068	0.094	0.134	0.007	0.131	0.30	0.21
		Left Cheek	0.123	0.323	0.080	0.080	0.117	0.53	0.32
		Left Tilted	0.065	0.128	0.051	0.018	0.001	0.24	0.08
	LTE Band 7	Right Cheek	0.107	0.105	0.229	0.002	0.269	0.44	0.38
		Right Tilted	0.081	0.094	0.134	0.007	0.131	0.31	0.22
		Left Cheek	0.251	0.323	0.080	0.080	0.117	0.65	0.45
		Left Tilted	0.059	0.128	0.051	0.018	0.001	0.24	0.08

WWAN Band		Exposure Position	1	2	3	5	6	1+2+3 Summed 10g SAR (W/kg)	1+5+6 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	5GHz WALN Chain 0	5GHz WALN Chain 1		
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)		
GSM	GSM850	Right Cheek	0.221	0.061	0.108	0.001	0.068	0.39	0.29
		Right Tilted	0.088	0.045	0.056	0.001	0.037	0.19	0.13
		Left Cheek	0.185	0.157	0.031	0.011	0.026	0.37	0.22
		Left Tilted	0.086	0.061	0.022	0.002	0.001	0.17	0.09
	GSM1900	Right Cheek	0.057	0.061	0.108	0.001	0.068	0.23	0.13
		Right Tilted	0.033	0.045	0.056	0.001	0.037	0.13	0.07
		Left Cheek	0.114	0.157	0.031	0.011	0.026	0.30	0.15
		Left Tilted	0.018	0.061	0.022	0.002	0.001	0.10	0.02
WCDMA	WCDMA V	Right Cheek	0.271	0.061	0.108	0.001	0.068	0.44	0.34
		Right Tilted	0.114	0.045	0.056	0.001	0.037	0.22	0.15
		Left Cheek	0.229	0.157	0.031	0.011	0.026	0.42	0.27
		Left Tilted	0.108	0.061	0.022	0.002	0.001	0.19	0.11
LTE	LTE Band 17	Right Cheek	0.118	0.061	0.108	0.001	0.068	0.29	0.19
		Right Tilted	0.055	0.045	0.056	0.001	0.037	0.16	0.09
		Left Cheek	0.101	0.157	0.031	0.011	0.026	0.29	0.14
		Left Tilted	0.053	0.061	0.022	0.002	0.001	0.14	0.06
	LTE Band 7	Right Cheek	0.057	0.061	0.108	0.001	0.068	0.23	0.13
		Right Tilted	0.038	0.045	0.056	0.001	0.037	0.14	0.08
		Left Cheek	0.130	0.157	0.031	0.011	0.026	0.32	0.17
		Left Tilted	0.026	0.061	0.022	0.002	0.001	0.11	0.03

16.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2+3 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	
GSM	GSM850	Front	0.323	0.049	0.025	0.40
		Back	0.343	0.104	0.068	0.52
		Left side	0.114	0.003	0.018	0.14
		Right side	0.390	0.014	0.002	0.41
		Top side		0.026	0.006	0.03
		Bottom side	0.133			0.13
	GSM1900	Front	0.587	0.049	0.025	0.66
		Back	0.655	0.104	0.068	0.83
		Left side	0.204	0.003	0.018	0.23
		Right side	0.032	0.014	0.002	0.05
		Top side		0.026	0.006	0.03
		Bottom side	1.126			1.13
WCDMA	WCDMA V	Front	0.407	0.049	0.025	0.48
		Back	0.430	0.104	0.068	0.60
		Left side	0.167	0.003	0.018	0.19
		Right side	0.514	0.014	0.002	0.53
		Top side		0.026	0.006	0.03
		Bottom side	0.052			0.05
LTE	LTE Band 17	Front	0.252	0.049	0.025	0.33
		Back	0.272	0.104	0.068	0.44
		Left side	0.156	0.003	0.018	0.18
		Right side	0.215	0.014	0.002	0.23
		Top side		0.026	0.006	0.03
		Bottom side	0.030			0.03
	LTE Band 7	Front	0.430	0.049	0.025	0.50
		Back	0.475	0.104	0.068	0.65
		Left side	0.392	0.003	0.018	0.41
		Right side	0.003	0.014	0.002	0.02
		Top side		0.026	0.006	0.03
		Bottom side	0.421			0.42

WWAN Band		Exposure Position	1	2	3	1+2+3 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	
GSM	GSM850	Front	0.244	0.028	0.012	0.28
		Back	0.256	0.045	0.026	0.33
		Left side	0.081	0.001	0.005	0.09
		Right side	0.271	0.006	0.001	0.28
		Top side		0.012	0.002	0.01
		Bottom side	0.074			0.07
	GSM1900	Front	0.313	0.028	0.012	0.35
		Back	0.353	0.045	0.026	0.42
		Left side	0.125	0.001	0.005	0.13
		Right side	0.019	0.006	0.001	0.03
		Top side		0.012	0.002	0.01
		Bottom side	0.591			0.59
WCDMA	WCDMA V	Front	0.312	0.028	0.012	0.35
		Back	0.323	0.045	0.026	0.39
		Left side	0.118	0.001	0.005	0.12
		Right side	0.352	0.006	0.001	0.36
		Top side		0.012	0.002	0.01
		Bottom side	0.029			0.03
LTE	LTE Band 17	Front	0.201	0.028	0.012	0.24
		Back	0.214	0.045	0.026	0.29
		Left side	0.114	0.001	0.005	0.12
		Right side	0.155	0.006	0.001	0.16
		Top side		0.012	0.002	0.01
		Bottom side	0.019			0.02
	LTE Band 7	Front	0.227	0.028	0.012	0.27
		Back	0.242	0.045	0.026	0.31
		Left side	0.198	0.001	0.005	0.20
		Right side	0.001	0.006	0.001	0.01
		Top side		0.012	0.002	0.01
		Bottom side	0.203			0.20

16.3 Extremity Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	5	6	1+2+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)	1+5+6 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	2.4GHz Bluetooth	5GHz WALN Chain 0	5GHz WALN Chain 1			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	Estimated 10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
GSM	GSM1900	Front	1.939	-	-	0.235	0.061	0.106	1.94	2.17	2.34
		Back	2.465	-	-	0.235	0.687	0.270	2.47	2.70	3.66
		Left side	0.504	-	-	0.235	0.021	0.026	0.50	0.74	0.79
		Right side	0.027	-	-	0.235	0.072	0.005	0.03	0.26	0.34
		Top side		-	-	0.235	0.006	0.025		0.24	0.27
		Bottom side	0.447			0.235			0.45	0.45	0.45

Remark:

- According to KDB 648474 D04v01r01, for 2.4GHz WLAN hand SAR ("-") was excluded, since 2.4GHz WLAN hotspot SAR was < 1.2W/kg.

16.4 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	5	6	1+2+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	1+4+5+6 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	2.4GHz Bluetooth	5GHz WALN Chain 0	5GHz WALN Chain 1			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Front	0.244	0.029	0.010	0.196	0.001	0.018	0.28	0.44	0.46
		Back	0.239	0.044	0.022	0.196	0.079	0.024	0.31	0.44	0.54
	GSM1900	Front	0.288	0.029	0.010	0.196	0.001	0.018	0.33	0.48	0.50
		Back	0.339	0.044	0.022	0.196	0.079	0.024	0.41	0.54	0.64
WCDMA	WCDMA V	Front	0.315	0.029	0.010	0.196	0.001	0.018	0.35	0.51	0.53
		Back	0.311	0.044	0.022	0.196	0.079	0.024	0.38	0.51	0.61
LTE	LTE Band 17	Front	0.236	0.029	0.010	0.196	0.001	0.018	0.28	0.43	0.45
		Back	0.247	0.044	0.022	0.196	0.079	0.024	0.31	0.44	0.55
	LTE Band 7	Front	0.197	0.029	0.010	0.196	0.001	0.018	0.24	0.39	0.41
		Back	0.211	0.044	0.022	0.196	0.079	0.024	0.28	0.41	0.51

WWAN Band		Exposure Position	1	2	3	5	6	1+2+3 Summed 10g SAR (W/kg)	1+5+6 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WALN Chain 0	2.4GHz WALN Chain 1	5GHz WALN Chain 0	5GHz WALN Chain 1		
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)		
GSM	GSM850	Front	0.192	0.016	0.004	0.001	0.005	0.21	0.20
		Back	0.188	0.021	0.008	0.026	0.005	0.22	0.22
	GSM1900	Front	0.166	0.016	0.004	0.001	0.005	0.19	0.17
		Back	0.195	0.021	0.008	0.026	0.005	0.22	0.23
WCDMA	WCDMA V	Front	0.249	0.016	0.004	0.001	0.005	0.27	0.26
		Back	0.245	0.021	0.008	0.026	0.005	0.27	0.28
LTE	LTE Band 17	Front	0.188	0.016	0.004	0.001	0.005	0.21	0.19
		Back	0.195	0.021	0.008	0.026	0.005	0.22	0.23
	LTE Band 7	Front	0.107	0.016	0.004	0.001	0.005	0.13	0.11
		Back	0.111	0.021	0.008	0.026	0.005	0.14	0.14

Test Engineer : Tommy Chen, Thomas Wang, Poa Chen, Vic Yang, Iran Wang and Aaron Chen

17. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	$1/k^{(b)}$	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Table 17.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g) (±%)	Standard Uncertainty (10g) (±%)
Measurement System							
Probe Calibration	6.0	N	1	1	1	6.0	6.0
Axial Isotropy	4.7	R	1.732	0.7	0.7	1.9	1.9
Hemispherical Isotropy	9.6	R	1.732	0.7	0.7	3.9	3.9
Boundary Effects	1.0	R	1.732	1	1	0.6	0.6
Linearity	4.7	R	1.732	1	1	2.7	2.7
System Detection Limits	1.0	R	1.732	1	1	0.6	0.6
Modulation Response	3.2	R	1.732	1	1	1.8	1.8
Readout Electronics	0.3	N	1	1	1	0.3	0.3
Response Time	0.0	R	1.732	1	1	0.0	0.0
Integration Time	2.6	R	1.732	1	1	1.5	1.5
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7
Probe Positioner	0.4	R	1.732	1	1	0.2	0.2
Probe Positioning	2.9	R	1.732	1	1	1.7	1.7
Max. SAR Eval.	2.0	R	1.732	1	1	1.2	1.2
Test Sample Related							
Device Positioning	3.0	N	1	1	1	3.0	3.0
Device Holder	3.6	N	1	1	1	3.6	3.6
Power Drift	5.0	R	1.732	1	1	2.9	2.9
Power Scaling	0.0	R	1.732	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty	6.1	R	1.732	1	1	3.5	3.5
SAR correction	0.0	R	1.732	1	0.84	0.0	0.0
Liquid Conductivity Repeatability	0.2	N	1	0.78	0.71	0.1	0.1
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0
Liquid Conductivity (mea.)	2.5	R	1.732	0.78	0.71	1.1	1.0
Temp. unc. - Conductivity	3.4	R	1.732	0.78	0.71	1.5	1.4
Liquid Permittivity Repeatability	0.15	N	1	0.23	0.26	0.0	0.0
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8
Liquid Permittivity (mea.)	2.5	R	1.732	0.23	0.26	0.3	0.4
Temp. unc. - Permittivity	0.83	R	1.732	0.23	0.26	0.1	0.1
Combined Std. Uncertainty						11.4%	11.4%
Coverage Factor for 95 %						K=2	K=2
Expanded STD Uncertainty						22.9%	22.7%

Table 17.1. Uncertainty Budget for frequency range 300 MHz to 3 GHz

Error Description	Uncertainty Value (±%)	Probability	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g) (±%)	Standard Uncertainty (10g) (±%)
Measurement System							
Probe Calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	1.732	0.7	0.7	1.9	1.9
Hemispherical Isotropy	9.6	R	1.732	0.7	0.7	3.9	3.9
Boundary Effects	2.0	R	1.732	1	1	1.2	1.2
Linearity	4.7	R	1.732	1	1	2.7	2.7
System Detection Limits	1.0	R	1.732	1	1	0.6	0.6
Modulation Response	3.2	R	1.732	1	1	1.8	1.8
Readout Electronics	0.3	N	1	1	1	0.3	0.3
Response Time	0.0	R	1.732	1	1	0.0	0.0
Integration Time	2.6	R	1.732	1	1	1.5	1.5
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7
Probe Positioner	0.4	R	1.732	1	1	0.2	0.2
Probe Positioning	6.7	R	1.732	1	1	3.9	3.9
Max. SAR Eval.	4.0	R	1.732	1	1	2.3	2.3
Test Sample Related							
Device Positioning	3.0	N	1	1	1	3.0	3.0
Device Holder	3.6	N	1	1	1	3.6	3.6
Power Drift	5.0	R	1.732	1	1	2.9	2.9
Power Scaling	0.0	R	1.732	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty	6.6	R	1.732	1	1	3.8	3.8
SAR correction	0.0	R	1.732	1	0.84	0.0	0.0
Liquid Conductivity Repeatability	0.2	N	1	0.78	0.71	0.1	0.1
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0
Liquid Conductivity (mea.)	2.5	R	1.732	0.78	0.71	1.1	1.0
Temp. unc. - Conductivity	3.4	R	1.732	0.78	0.71	1.5	1.4
Liquid Permittivity Repeatability	0.15	N	1	0.23	0.26	0.0	0.0
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8
Liquid Permittivity (mea.)	2.5	R	1.732	0.23	0.26	0.3	0.4
Temp. unc. - Permittivity	0.83	R	1.732	0.23	0.26	0.1	0.1
Combined Std. Uncertainty						12.5%	12.5%
Coverage Factor for 95 %						K=2	K=2
Expanded STD Uncertainty						25.0%	24.9%

Table 17.2. Uncertainty Budget for frequency range 3 GHz to 6 GHz

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013.
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r01, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Jun 2015.
- [6] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [7] FCC KDB 648474 D04 v01r02, "SAR Evaluation Considerations for Wireless Handsets", Dec 2013.
- [8] FCC KDB 941225 D01 v03, "3G SAR MEAUREMENT PROCEDURES", Oct 2014
- [9] FCC KDB 941225 D05 v02r03, "SAR Evaluation Considerations for LTE Devices", Dec 2013
- [10] FCC KDB 941225 D06 v02, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2014.
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013.