

Sony Mobile Communications
Prepared by
SEM/CGLQKC RYOKO KUNIMURA
Contents responsible if other than preparer

Document number
144/0061-LXE 110 0350 Uen
Date
2016-04-09
Remarks

Revision
A

Approved by
SEM/CGLQKC (MIKA KANEKO)

This document is managed in metaDoc.

Federal Communications Commission
Office of Engineering and Technology
Laboratory Division
7435 Oakland Mills Rd.
Columbia MD 21046

MIF attestation letter_FCC ID: PY7-PM0944

Attn: Office of Engineering and Technology

HAC Attestation - FCC ID: PY7-PM0944

To whom it may concern:

Sony Mobile Communications Inc. hereby declares that the MIF values detailed below are based on worst case operating modes for all air interfaces for which the HAC rating is provided based on the current methodology for determining MIF values.

Reference Test report Number(s): UL Verification Services Test Report 16J22997-S6V1

SPEAG test files

UID	Communication System Name	MIF (dB)
10021-DAB	GSM-FDD (TDMA, GMSK)	3.63
10011-CAA	UMTS-FDD (WCDMA)	-27.23
10170-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16QAM)	-9.76
10182-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16QAM)	-9.76
10176-CAB	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16QAM)	-9.76
10173-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16QAM)	-1.44
10069-CAA	IEEE 802.11a/n WiFi 5 GHz (OFDM, 54 Mbps)	-3.15
10061-CAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	-2.02
10077-CAA	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	0.12

Yours sincerely



Mika Kaneko
Head of Regulatory, Global Type Approval
Quality & Customer Services
Sony Mobile Communications Inc.