


# FCC SAR Test Report

**APPLICANT** : Sony Mobile Communications Inc.  
**BRAND NAME** : Sony  
**FCC ID** : PY7-PM0954  
**STANDARD** : FCC 47 CFR Part 2 (2.1093)  
ANSI/IEEE C95.1-1992  
IEEE 1528-2013

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance ..... 4
2. Administration Data ..... 5
3. Guidance Standard ..... 5
4. Equipment Under Test (EUT) Information ..... 6
4.1 General Information ..... 6
4.1 Device Serial Number ..... 6
5. RF Exposure Limits ..... 7
5.1 Uncontrolled Environment ..... 7
5.2 Controlled Environment ..... 7
6. Specific Absorption Rate (SAR) ..... 8
6.1 Introduction ..... 8
6.2 SAR Definition ..... 8
7. System Description and Setup ..... 9
7.1 E-Field Probe ..... 10
7.2 Data Acquisition Electronics (DAE) ..... 10
7.3 Phantom ..... 11
7.4 Device Holder ..... 12
8. Measurement Procedures ..... 13
8.1 Spatial Peak SAR Evaluation ..... 13
8.2 Power Reference Measurement ..... 14
8.3 Area Scan ..... 14
8.4 Zoom Scan ..... 15
8.5 Volume Scan Procedures ..... 15
8.6 Power Drift Monitoring ..... 15
9. Test Equipment List ..... 16
10. System Verification ..... 17
10.1 Tissue Verification ..... 17
10.2 System Performance Check Results ..... 18
11. RF Exposure Positions ..... 20
11.1 Ear and handset reference point ..... 20
11.2 Definition of the cheek position ..... 21
11.3 Definition of the tilt position ..... 22
11.4 Body Worn Accessory ..... 23
11.5 Product Specific Exposure ..... 23
11.6 Wireless Router ..... 24
12. Conducted RF Output Power (Unit: dBm) ..... 25
13. Bluetooth Exclusions Applied ..... 43
14. RF Exposure Conditions ..... 43
15. SAR Test Results ..... 44
15.1 Head SAR ..... 46
15.2 Hotspot SAR ..... 49
15.3 Product Specific SAR ..... 52
15.4 Body Worn Accessory SAR ..... 53
15.5 Repeated SAR Measurement ..... 56
16. Simultaneous Transmission Analysis ..... 57
16.1 Head Exposure Conditions ..... 58
16.2 Hotspot Exposure Conditions ..... 60
16.3 Product Specific Exposure Conditions ..... 62
16.4 Body-Worn Accessory Exposure Conditions ..... 62
17. Uncertainty Assessment ..... 64
18. References ..... 67
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos





**1. Statement of Compliance**

Applicant Name	Sony Mobile Communications Inc.		
EUT Description	Smart phone		
Brand Name	Sony		
FCC ID	PY7-PM0954		
HW Version	A		
SW Version	36.0.A.1.42		
RF Exposure Conditions	<b>Equipment Class</b>		
	<b>Licensed</b>	<b>DTS</b>	<b>U-NII</b>
Head (1g SAR W/kg)	0.27	1.09	1.20
Body-Worn (1g SAR W/kg)	0.39	0.16	0.22
Wireless Router (1g SAR W/kg)	0.85	0.33	
Product Specific (10g SAR W/kg)			0.58
Highest Simultaneous Transmission (1g SAR W/kg)	Head: 1.36 Body-worn: 0.54 Hotspot: 1.17	Head: 1.36 Body-worn: 0.54 Hotspot: 1.17	Head: 1.35 Body-worn: 0.50 Hotspot: NA
Date Tested	2016/2/23 ~ 2016/3/10		
Test Result	Pass		
<b>Remark:</b>	<ol style="list-style-type: none"> <li>This device 2.4GHz WLAN supports Hotspot and WiFi Direct (GC/GO), and 5GHz WLAN supports WiFi Direct (GC) only.</li> <li>The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report all the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same.</li> </ol>		

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



## 2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Sony Mobile Communications Inc.
Address	4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

Manufacturer	
Company Name	Sony Mobile Communications Inc.
Address	4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

## 3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01



**4. Equipment Under Test (EUT) Information**

**4.1 General Information**

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	· GSM Voice · GPRS (GMSK) · EDGE (8PSK)	Multi-Slot Class: Class 12
	Does device support dual transfer mode? (No)		
W-CDMA (UMTS)	Band 5 Band 4 Band 2	· AMR / RMC 12.2Kbps · HSDPA · HSUPA · DC-HSDPA	
LTE (FDD)	Band 12 Band 13 Band 17 Band 5 Band 4 Band 2 Band 7	· QPSK · 16QAM	
WiFi	2.4GHz: 2412 MHz ~ 2462 MHz	· 11b · 11g · 11n (HT20) · 11n (HT40)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5700 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	· 11a · 11n (HT20) · 11n (HT40)	
Bluetooth	2.4GHz	Version 4.1 with LE	
NFC	13.56MHz	ASK	

**4.1 Device Serial Number**

Band	SN
GSM & UMTS	WUJ01M8ERF
LTE	WUJ01M8ES9
WLAN	0123456789ABCDEF A201RXP10202
	0123456789ABCDEF-A201RYLB0201

**Note:** Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.



**5. RF Exposure Limits**

**5.1 Uncontrolled Environment**

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

**5.2 Controlled Environment**

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

**Limits for General Population/Uncontrolled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## **6. Specific Absorption Rate (SAR)**

### **6.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **6.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.



## 7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.


**7.1 E-Field Probe**

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

**<ES3DV3 Probe>**

<b>Construction</b>	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
<b>Frequency</b>	10 MHz – 4 GHz; Linearity: ±0.2 dB (30 MHz – 4 GHz)	
<b>Directivity</b>	±0.2 dB in TSL (rotation around probe axis) ±0.3 dB in TSL (rotation normal to probe axis)	
<b>Dynamic Range</b>	5 µW/g – >100 mW/g; Linearity: ±0.2 dB	
<b>Dimensions</b>	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

**<EX3DV4 Probe>**

<b>Construction</b>	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
<b>Frequency</b>	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)	
<b>Directivity</b>	±0.3 dB in TSL (rotation around probe axis) ±0.5 dB in TSL (rotation normal to probe axis)	
<b>Dynamic Range</b>	10 µW/g – >100 mW/g Linearity: ±0.2 dB (noise: typically <1 µW/g)	
<b>Dimensions</b>	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

**7.2 Data Acquisition Electronics (DAE)**

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



**Fig 5.1 Photo of DAE**


**7.3 Phantom**

**<SAM Twin Phantom>**

<b>Shell Thickness</b>	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
<b>Filling Volume</b>	Approx. 25 liters	
<b>Dimensions</b>	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
<b>Measurement Areas</b>	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

**<ELI Phantom>**

<b>Shell Thickness</b>	2 ± 0.2 mm (sagging: <1%)	
<b>Filling Volume</b>	Approx. 30 liters	
<b>Dimensions</b>	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

## **7.4 Device Holder**

### **<Mounting Device for Hand-Held Transmitter>**

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

### **<Mounting Device for Laptops and other Body-Worn Transmitters>**

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops



## 8. Measurement Procedures

The measurement procedures are as follows:

### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### 8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

**8.2 Power Reference Measurement**

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

**8.3 Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	



### 8.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm	
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm	
Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

### 8.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



**9. Test Equipment List**

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1012	May. 28, 2015	May. 27, 2016
SPEAG	835MHz System Validation Kit	D835V2	4d200	Aug. 20, 2015	Aug. 19, 2016
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 23, 2015	Nov. 22, 2016
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Oct. 22, 2015	Oct. 21, 2016
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 20, 2015	Aug. 19, 2016
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Aug. 19, 2015	Aug. 18, 2016
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Oct. 06, 2015	Oct. 05, 2016
SPEAG	5GHz System Validation Kit	D5GHzV2	1128	Jul. 20, 2015	Jul. 19, 2016
SPEAG	Data Acquisition Electronics	DAE3	495	May. 22, 2015	May. 21, 2016
SPEAG	Data Acquisition Electronics	DAE3	577	Sep. 24, 2015	Sep. 23, 2016
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 23, 2015	Nov. 22, 2016
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	May. 27, 2015	May. 26, 2016
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Oct. 01, 2015	Sep. 30, 2016
SPEAG	Dosimetric E-Field Probe	EX3DV4	3955	Nov. 24, 2015	Nov. 23, 2016
WonDer	Thermometer	WD-5015	TM642	Oct. 16, 2015	Oct. 15, 2016
Wisewind	Thermometer	HTC-1	TM560	Oct. 16, 2015	Oct. 15, 2016
Wisewind	Thermometer	HTC-1	TM225	Oct. 16, 2015	Oct. 15, 2016
Anritsu	Radio Communication Analyzer	MT8820C	6201341950	Dec. 18, 2015	Dec. 17, 2016
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 14, 2015	May. 13, 2016
SPEAG	Device Holder	N/A	N/A	N/A	N/A
R&S	Signal Generator	MG3710A	6201502524	Dec. 18, 2015	Dec. 17, 2016
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 12, 2016	Jan. 11, 2017
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Jul. 21, 2015	Jul. 20, 2016
LINE SEIKI	Digital Thermometer	LKMelectronic	DTM3000SPEZIAL/90900	Aug. 26, 2015	Aug. 25, 2016
Anritsu	Power Meter	ML2495A	1419002	May. 13, 2015	May. 12, 2016
Anritsu	Power Sensor	MA2411B	1339124	May. 13, 2015	May. 12, 2016
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 17, 2015	Jun. 16, 2016
ATM	Dual Directional Coupler	C122H-10	P610410z-02		Note 1
Woken	Attenuator 1	WK0602-XX	N/A		Note 1
PE	Attenuator 2	PE7005-10	N/A		Note 1
PE	Attenuator 3	PE7005- 3	N/A		Note 1
AR	Power Amplifier	5S1G4M2	0328767		Note 1
Mini-Circuits	Power Amplifier	ZVE-3W	162601250		Note 1

**General Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.





## 10. System Verification

### 10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

#### Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

#### <Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )	Conductivity Target ( $\sigma$ )	Permittivity Target ( $\epsilon_r$ )	Delta ( $\sigma$ ) (%)	Delta ( $\epsilon_r$ ) (%)	Limit (%)	Date
750	HSL	22.2	0.892	42.591	0.89	41.90	0.22	1.65	±5	2016/2/28
750	MSL	22.5	0.969	55.276	0.96	55.50	0.94	-0.40	±5	2016/2/26
835	HSL	22.2	0.891	41.616	0.90	41.50	-1.00	0.28	±5	2016/2/28
835	MSL	22.5	0.971	55.694	0.97	55.20	0.10	0.89	±5	2016/2/25
1750	HSL	22.3	1.374	40.199	1.37	40.10	0.29	0.25	±5	2016/2/27
1750	MSL	22.8	1.486	53.090	1.49	53.40	-0.27	-0.58	±5	2016/2/24
1900	HSL	22.3	1.455	41.126	1.40	40.00	3.93	2.81	±5	2016/2/27
1900	MSL	22.8	1.564	55.158	1.52	53.30	2.89	3.49	±5	2016/2/23
2450	HSL	22.8	1.809	39.650	1.80	39.20	0.50	1.15	±5	2016/3/5
2450	HSL	22.7	1.807	40.194	1.80	39.20	0.39	2.54	±5	2016/3/10
2450	MSL	22.1	1.979	53.435	1.95	52.70	1.49	1.39	±5	2016/3/6
2600	HSL	22.6	1.998	38.088	1.96	39.00	1.94	-2.34	±5	2016/2/27
2600	MSL	22.8	2.215	53.404	2.16	52.50	2.55	1.72	±5	2016/2/23
5250	HSL	22.3	4.628	36.461	4.71	35.95	-1.74	1.42	±5	2016/3/1
5250	HSL	22.3	4.597	36.529	4.71	35.95	-2.40	1.61	±5	2016/3/2
5250	MSL	22.7	5.539	47.632	5.36	48.93	3.34	-2.65	±5	2016/3/3
5250	MSL	22.8	5.537	46.941	5.36	48.93	3.30	-4.06	±5	2016/3/4
5600	HSL	22.3	4.975	35.956	5.07	35.50	-1.87	1.28	±5	2016/3/1
5600	HSL	22.3	4.948	36.021	5.07	35.50	-2.41	1.47	±5	2016/3/2
5600	MSL	22.7	6.008	47.030	5.77	48.50	4.12	-3.03	±5	2016/3/3
5600	MSL	22.8	5.990	46.330	5.77	48.50	3.81	-4.47	±5	2016/3/4
5750	HSL	22.3	5.127	35.757	5.22	35.35	-1.78	1.15	±5	2016/3/1
5750	HSL	22.3	5.104	35.819	5.22	35.35	-2.22	1.33	±5	2016/3/2
5750	MSL	22.7	6.217	46.796	5.94	48.28	4.66	-3.07	±5	2016/3/3
5750	MSL	22.8	6.190	46.080	5.94	48.28	4.21	-4.56	±5	2016/3/4




**10.2 System Performance Check Results**

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2016/2/28	750	HSL	250	D750V3-1012	EX3DV4 - SN3925	DAE3 Sn495	2.09	8.22	8.36	1.70
2016/2/26	750	MSL	250	D750V3-1012	EX3DV4 - SN3925	DAE3 Sn495	2.30	8.61	9.20	6.85
2016/2/28	835	HSL	250	D835V2-4d200	EX3DV4 - SN3925	DAE3 Sn495	2.44	9.15	9.76	6.67
2016/2/25	835	MSL	250	D835V2-4d200	EX3DV4 - SN3925	DAE3 Sn495	2.44	9.55	9.76	2.20
2016/2/27	1750	HSL	250	D1750V2-1068	EX3DV4 - SN3925	DAE3 Sn495	9.37	36.80	37.48	1.85
2016/2/24	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3925	DAE3 Sn495	9.35	35.70	37.40	4.76
2016/2/27	1900	HSL	250	D1900V2-5d041	EX3DV4 - SN3925	DAE3 Sn495	10.20	39.80	40.80	2.51
2016/2/23	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3925	DAE3 Sn495	10.20	40.00	40.80	2.00
2016/3/5	2450	HSL	250	D2450V2-736	EX3DV4 - SN3955	DAE4 Sn1399	13.40	53.40	53.60	0.37
2016/3/10	2450	HSL	250	D2450V2-736	EX3DV4 - SN3925	DAE3 Sn495	12.90	53.40	51.60	-3.37
2016/3/6	2450	MSL	250	D2450V2-736	EX3DV4 - SN3955	DAE4 Sn1399	12.40	51.90	49.60	-4.43
2016/2/27	2600	HSL	250	D2600V2-1008	EX3DV4 - SN3925	DAE3 Sn495	13.80	56.30	55.20	-1.95
2016/2/23	2600	MSL	250	D2600V2-1008	EX3DV4 - SN3925	DAE3 Sn495	14.00	55.80	56.00	0.36
2016/3/1	5250	HSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	8.63	80.80	86.30	6.81
2016/3/2	5250	HSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	8.58	80.80	85.80	6.19
2016/3/3	5250	MSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	7.21	76.20	72.10	-5.38
2016/3/4	5250	MSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	7.28	76.20	72.80	-4.46
2016/3/1	5600	HSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	7.77	82.00	77.70	-5.24
2016/3/2	5600	HSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	7.73	82.00	77.30	-5.73
2016/3/3	5600	MSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	7.86	79.30	78.60	-0.88
2016/3/4	5600	MSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	7.76	79.30	77.60	-2.14
2016/3/1	5750	HSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	7.90	79.70	79.00	-0.88
2016/3/2	5750	HSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	7.86	79.70	78.60	-1.38
2016/3/3	5750	MSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	7.29	75.90	72.90	-3.95
2016/3/4	5750	MSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	7.07	75.90	70.70	-6.85

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2016/2/28	750	HSL	250	D750V3-1012	EX3DV4 - SN3925	DAE3 Sn495	1.38	5.41	5.52	2.03
2016/2/26	750	MSL	250	D750V3-1012	EX3DV4 - SN3925	DAE3 Sn495	1.57	5.72	6.28	9.79
2016/2/28	835	HSL	250	D835V2-4d200	EX3DV4 - SN3925	DAE3 Sn495	1.61	5.97	6.44	7.87
2016/2/25	835	MSL	250	D835V2-4d200	EX3DV4 - SN3925	DAE3 Sn495	1.62	6.30	6.48	2.86
2016/2/27	1750	HSL	250	D1750V2-1068	EX3DV4 - SN3925	DAE3 Sn495	5.05	19.30	20.20	4.66
2016/2/24	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3925	DAE3 Sn495	5.02	19.00	20.08	5.68
2016/2/27	1900	HSL	250	D1900V2-5d041	EX3DV4 - SN3925	DAE3 Sn495	5.27	20.80	21.08	1.35
2016/2/23	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3925	DAE3 Sn495	5.35	21.20	21.40	0.94
2016/3/5	2450	HSL	250	D2450V2-736	EX3DV4 - SN3955	DAE4 Sn1399	6.26	25.20	25.04	-0.63
2016/3/10	2450	HSL	250	D2450V2-736	EX3DV4 - SN3925	DAE3 Sn495	5.95	25.20	23.80	-5.56
2016/3/6	2450	MSL	250	D2450V2-736	EX3DV4 - SN3955	DAE4 Sn1399	5.77	24.20	23.08	-4.63
2016/2/27	2600	HSL	250	D2600V2-1008	EX3DV4 - SN3925	DAE3 Sn495	6.17	25.60	24.68	-3.59
2016/2/23	2600	MSL	250	D2600V2-1008	EX3DV4 - SN3925	DAE3 Sn495	6.35	25.10	25.40	1.20
2016/3/1	5250	HSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	2.35	23.20	23.50	1.29
2016/3/2	5250	HSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	2.34	23.20	23.40	0.86
2016/3/3	5250	MSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	2.00	21.40	20.00	-6.54
2016/3/4	5250	MSL	100	D5GHzV2-1128-5250	EX3DV4 - SN3955	DAE4 Sn1399	2.00	21.40	20.00	-6.54
2016/3/1	5600	HSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	2.17	23.40	21.70	-7.26
2016/3/2	5600	HSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	2.16	23.40	21.60	-7.69
2016/3/3	5600	MSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	2.14	22.10	21.40	-3.17
2016/3/4	5600	MSL	100	D5GHzV2-1128-5600	EX3DV4 - SN3955	DAE4 Sn1399	2.13	22.10	21.30	-3.62
2016/3/1	5750	HSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	2.21	22.70	22.10	-2.64
2016/3/2	5750	HSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	2.20	22.70	22.00	-3.08
2016/3/3	5750	MSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	2.01	21.20	20.10	-5.19
2016/3/4	5750	MSL	100	D5GHzV2-1128-5750	EX3DV4 - SN3955	DAE4 Sn1399	1.95	21.20	19.50	-8.02



**Fig 8.3.1 System Performance Check Setup**



**Fig 8.3.2 Setup Photo**

## 11. RF Exposure Positions

### 11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.






Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

**11.2 Definition of the cheek position**


1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width  $w_t$  of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width  $w_b$  of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.



**Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”**




**Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”**



**Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.**

**11.3 Definition of the tilt position**

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




**Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.**



**11.4 Body Worn Accessory**

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is < 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.



**Fig 9.4 Body Worn Position**

**11.5 Product Specific Exposure**

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge, in direct contact with a flat phantom, for 10-g Product Specific SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g Product Specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.



## **11.6 Wireless Router**

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets (L x W  $\geq$  9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.





## 12. Conducted RF Output Power (Unit: dBm)

### <GSM Conducted Power>

**General Note:**

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq \frac{1}{4}$  dB higher than the primary mode, SAR measurement is not required for the secondary mode

Band GSM850 TX Channel	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot	32.20	32.25	32.10	33.00	23.20	23.25	23.10	24.00
GPRS 1 Tx slot	32.22	32.28	32.13	33.00	23.22	23.28	23.13	24.00
GPRS 2 Tx slots	30.07	30.11	30.00	31.00	24.07	24.11	24.00	25.00
GPRS 3 Tx slots	28.34	28.37	28.23	30.00	24.08	24.11	23.97	25.74
GPRS 4 Tx slots	27.24	27.28	27.13	29.00	24.24	24.28	24.13	26.00
EDGE 1 Tx slot	27.21	27.23	27.06	27.50	18.21	18.23	18.06	18.50
EDGE 2 Tx slots	24.52	24.59	24.51	26.50	18.52	18.59	18.51	20.50
EDGE 3 Tx slots	22.88	22.94	22.74	24.50	18.62	18.68	18.48	20.24
EDGE 4 Tx slots	21.72	21.73	21.59	23.00	18.72	18.73	18.59	20.00

Band GSM1900 TX Channel	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot	29.20	29.23	29.46	30.00	20.20	20.23	20.46	21.00
GPRS 1 Tx slot	29.21	29.25	29.49	30.00	20.21	20.25	20.49	21.00
GPRS 2 Tx slots	26.20	26.55	26.71	27.00	20.20	20.55	20.71	21.00
GPRS 3 Tx slots	25.27	25.63	25.80	26.00	21.01	21.37	21.54	21.74
GPRS 4 Tx slots	24.20	24.56	24.72	25.00	21.20	21.56	21.72	22.00
EDGE 1 Tx slot	25.82	26.01	26.34	26.50	16.82	17.01	17.34	17.50
EDGE 2 Tx slots	23.57	23.60	23.94	25.50	17.57	17.60	17.94	19.50
EDGE 3 Tx slots	21.57	21.87	22.22	23.50	17.31	17.61	17.96	19.24
EDGE 4 Tx slots	20.45	20.77	21.12	22.00	17.45	17.77	18.12	19.00

**<WCDMA Conducted Power>**

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

**HSDPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each
  - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
  - iii. Set RMC 12.2Kbps + HSDPA mode.
  - iv. Set Cell Power = -86 dBm
  - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - vi. Select HSDPA Uplink Parameters
  - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
  - viii. Set Ack-Nack Repetition Factor to 3
  - ix. Set CQI Feedback Cycle (k) to 4 ms
  - x. Set CQI Repetition Factor to 2
  - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

**Table C.10.1.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}$ (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 24/15$  with  $\beta_{hs} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**Setup Configuration**

**HSUPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting \* :
  - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - ii. Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - iii. Set Cell Power = -86 dBm
  - iv. Set Channel Type = 12.2k + HSPA
  - v. Set UE Target Power
  - vi. Power Ctrl Mode= Alternating bits
  - vii. Set and observe the E-TFCl
  - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

**Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1)	$\beta_{ec}$	$\beta_{ed}$ (Note 5) (Note 6)	$\beta_{ed}$ (SF)	$\beta_{ed}$ (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15, \beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6:  $\beta_{ed}$  can not be set directly, it is set by Absolute Grant Value.

**Setup Configuration**

**DC-HSDPA 3GPP release 8 Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set RMC 12.2Kbps + HSDPA mode.
  - ii. Set Cell Power = -25 dBm
  - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
  - iv. Select HSDPA Uplink Parameters
  - v. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
    - a). Subtest 1:  $\beta_c/\beta_d=2/15$
    - b). Subtest 2:  $\beta_c/\beta_d=12/15$
    - c). Subtest 3:  $\beta_c/\beta_d=15/8$
    - d). Subtest 4:  $\beta_c/\beta_d=15/4$
  - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
  - vii. Set Ack-Nack Repetition Factor to 3
  - viii. Set CQI Feedback Cycle (k) to 4 ms
  - ix. Set CQI Repetition Factor to 2
  - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

**C.8.1.12 Fixed Reference Channel Definition H-Set 12**

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload ( $N_{INF}$ )	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		



**Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)**

**Setup Configuration**



**<WCDMA Conducted Power>**

**General Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

Band		WCDMA V			Tune-up Limit (dBm)	WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		4132	4182	4233		9262	9400	9538		1312	1413	1513	
Rx Channel		4357	4407	4458		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		826.4	836.4	846.6		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	23.92	23.92	23.95	24.00	23.75	23.80	23.94	24.00	22.83	22.88	22.92	23.00
3GPP Rel 99	RMC 12.2Kbps	23.95	23.96	23.99	24.00	23.78	23.82	23.96	24.00	22.85	22.90	22.95	23.00
3GPP Rel 6	HSDPA Subtest-1	22.88	22.91	22.81	23.00	22.74	22.80	22.93	23.00	21.73	21.85	21.87	22.00
3GPP Rel 6	HSDPA Subtest-2	22.90	22.89	22.82	23.00	22.74	22.72	22.85	23.00	21.70	21.83	21.84	22.00
3GPP Rel 6	HSDPA Subtest-3	22.30	22.35	22.27	22.50	22.36	22.40	22.48	22.50	21.41	21.36	21.49	21.50
3GPP Rel 6	HSDPA Subtest-4	22.28	22.25	22.26	22.50	22.39	22.43	22.44	22.50	21.36	21.48	21.48	21.50
3GPP Rel 8	DC-HSDPA Subtest-1	22.89	22.85	22.81	23.00	22.54	22.64	22.92	23.00	21.60	21.71	21.69	22.00
3GPP Rel 8	DC-HSDPA Subtest-2	22.84	22.77	22.80	23.00	22.55	22.60	22.65	23.00	21.54	21.65	21.66	22.00
3GPP Rel 8	DC-HSDPA Subtest-3	22.38	22.27	22.30	22.50	22.36	22.20	22.45	22.50	21.30	21.23	21.48	21.50
3GPP Rel 8	DC-HSDPA Subtest-4	22.28	22.24	22.25	22.50	22.33	22.23	22.29	22.50	21.33	21.35	21.48	21.50
3GPP Rel 6	HSUPA Subtest-1	21.03	21.02	21.02	22.00	21.06	21.10	21.11	22.00	20.07	20.10	20.08	21.00
3GPP Rel 6	HSUPA Subtest-2	20.99	20.98	20.95	21.00	20.81	20.90	20.93	21.00	19.83	19.94	19.91	20.00
3GPP Rel 6	HSUPA Subtest-3	22.00	21.99	21.90	22.00	21.77	21.87	21.84	22.00	20.80	20.97	20.85	21.00
3GPP Rel 6	HSUPA Subtest-4	20.62	20.53	20.54	21.00	20.36	20.48	20.48	21.00	19.40	19.55	19.48	20.00
3GPP Rel 6	HSUPA Subtest-5	22.00	21.98	21.91	22.00	21.86	21.97	21.94	22.00	20.95	20.98	21.00	21.00

**<LTE Conducted Power>****General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B12 / B5 / B4 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 17 SAR test was covered by Band 12 ; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
  - a. the maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion
  - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band



<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power	Power	Power	Tune-up limit (dBm)	MPR (dB)
				Low Ch. / Freq.	Middle Ch. / Freq.	High Ch. / Freq.		
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	22.89	22.92	22.90	24	0
20	QPSK	1	49	22.83	22.83	22.80		
20	QPSK	1	99	22.78	22.80	22.79		
20	QPSK	50	0	21.94	21.95	21.91	23	1
20	QPSK	50	24	21.91	21.89	21.87		
20	QPSK	50	50	21.88	21.84	21.78		
20	QPSK	100	0	21.89	21.90	21.84	23	1
20	16QAM	1	0	22.12	22.21	22.26		
20	16QAM	1	49	22.12	22.15	22.15		
20	16QAM	1	99	22.09	22.17	21.99	22	2
20	16QAM	50	0	20.92	20.96	20.98		
20	16QAM	50	24	20.90	20.91	20.92		
20	16QAM	50	50	20.89	20.86	20.81	22	2
20	16QAM	100	0	20.89	20.91	20.88		
Channel				18675	18900	19125		
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	22.86	22.89	22.87	24	0
15	QPSK	1	37	22.88	22.88	22.82		
15	QPSK	1	74	22.80	22.83	22.77		
15	QPSK	36	0	21.92	21.94	21.92	23	1
15	QPSK	36	20	21.92	21.92	21.91		
15	QPSK	36	39	21.90	21.88	21.81		
15	QPSK	75	0	21.91	21.90	21.86	23	1
15	16QAM	1	0	22.11	22.22	22.24		
15	16QAM	1	37	22.15	22.20	22.14		
15	16QAM	1	74	22.10	22.20	22.00	22	2
15	16QAM	36	0	20.91	20.96	20.96		
15	16QAM	36	20	20.92	20.95	20.94		
15	16QAM	36	39	20.91	20.92	20.83	22	2
15	16QAM	75	0	20.90	20.92	20.90		
Channel				18650	18900	19150		
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	22.85	22.90	22.85	24	0
10	QPSK	1	25	22.87	22.89	22.85		
10	QPSK	1	49	22.87	22.88	22.83		
10	QPSK	25	0	21.89	21.91	21.92	23	1
10	QPSK	25	12	21.91	21.91	21.90		
10	QPSK	25	25	21.91	21.87	21.78		
10	QPSK	50	0	21.94	21.93	21.89	23	1
10	16QAM	1	0	22.08	22.22	22.17		
10	16QAM	1	25	22.13	22.22	22.12		
10	16QAM	1	49	22.15	22.24	22.07	22	2
10	16QAM	25	0	20.89	20.95	20.96		
10	16QAM	25	12	20.91	20.95	20.93		
10	16QAM	25	25	20.91	20.92	20.80	22	2
10	16QAM	50	0	20.92	20.95	20.90		
Channel				18625	18900	19175		
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	22.78	22.83	22.78	24	0
5	QPSK	1	12	22.87	22.91	22.85		
5	QPSK	1	24	22.78	22.82	22.75		
5	QPSK	12	0	21.80	21.87	21.87	23	1
5	QPSK	12	7	21.86	21.91	21.85		
5	QPSK	12	13	21.84	21.88	21.77		
5	QPSK	25	0	21.83	21.87	21.83	23	1
5	16QAM	1	0	22.00	22.17	22.04		
5	16QAM	1	12	22.08	22.23	22.08		
5	16QAM	1	24	22.02	22.16	21.98	22	2
5	16QAM	12	0	20.81	20.92	20.91		
5	16QAM	12	7	20.87	20.97	20.90		
5	16QAM	12	13	20.86	20.94	20.81	22	2
5	16QAM	25	0	20.81	20.89	20.84		



Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	22.77	22.84	22.76	24	0
3	QPSK	1	8	22.79	22.85	22.77		
3	QPSK	1	14	22.78	22.83	22.75		
3	QPSK	8	0	21.84	21.91	21.86	23	1
3	QPSK	8	4	21.87	21.93	21.85		
3	QPSK	8	7	21.84	21.90	21.81		
3	QPSK	15	0	21.87	21.91	21.87	23	1
3	16QAM	1	0	22.00	22.15	22.01		
3	16QAM	1	8	22.03	22.17	22.02		
3	16QAM	1	14	22.01	22.16	21.96	22	2
3	16QAM	8	0	20.91	21.03	20.95		
3	16QAM	8	4	20.94	21.04	20.95		
3	16QAM	8	7	20.90	21.00	20.91	22	2
3	16QAM	15	0	20.86	20.95	20.90		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	22.64	22.73	22.64	24	0
1.4	QPSK	1	3	22.63	22.71	22.63		
1.4	QPSK	1	5	22.68	22.74	22.66		
1.4	QPSK	3	0	22.83	22.89	22.82	23	1
1.4	QPSK	3	1	22.84	22.91	22.83		
1.4	QPSK	3	3	22.84	22.91	22.84		
1.4	QPSK	6	0	21.86	21.91	21.86	23	1
1.4	16QAM	1	0	21.98	22.13	21.96		
1.4	16QAM	1	3	21.97	22.12	21.95		
1.4	16QAM	1	5	21.98	22.14	21.94	23	1
1.4	16QAM	3	0	21.86	21.98	21.85		
1.4	16QAM	3	1	21.90	22.01	21.88		
1.4	16QAM	3	3	21.85	21.97	21.84	22	2
1.4	16QAM	6	0	20.93	21.04	20.96		





<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	21.90	21.91	21.84	23	0
20	QPSK	1	49	21.78	21.76	21.72		
20	QPSK	1	99	21.74	21.66	21.65		
20	QPSK	50	0	20.90	20.91	20.90	22	1
20	QPSK	50	24	20.81	20.77	20.74		
20	QPSK	50	50	20.75	20.62	20.59		
20	QPSK	100	0	20.82	20.83	20.77	22	1
20	16QAM	1	0	21.19	21.18	21.17		
20	16QAM	1	49	21.10	21.10	21.08		
20	16QAM	1	99	21.07	21.02	21.04	21	2
20	16QAM	50	0	19.91	19.89	19.93		
20	16QAM	50	24	19.84	19.79	19.77		
20	16QAM	50	50	19.76	19.64	19.62	21	2
20	16QAM	100	0	19.83	19.77	19.79		
Channel				20025	20175	20325		
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	21.89	21.86	21.80	23	0
15	QPSK	1	37	21.85	21.82	21.76		
15	QPSK	1	74	21.76	21.70	21.67		
15	QPSK	36	0	20.90	20.86	20.84	22	1
15	QPSK	36	20	20.86	20.82	20.77		
15	QPSK	36	39	20.80	20.73	20.69		
15	QPSK	75	0	20.85	20.79	20.77	22	1
15	16QAM	1	0	21.19	21.18	21.14		
15	16QAM	1	37	21.16	21.14	21.14		
15	16QAM	1	74	21.09	21.03	21.04	21	2
15	16QAM	36	0	19.92	19.88	19.87		
15	16QAM	36	20	19.88	19.83	19.82		
15	16QAM	36	39	19.81	19.74	19.73	21	2
15	16QAM	75	0	19.87	19.81	19.81		
Channel				20000	20175	20350		
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	21.87	21.84	21.78	23	0
10	QPSK	1	25	21.86	21.82	21.78		
10	QPSK	1	49	21.83	21.78	21.73		
10	QPSK	25	0	20.87	20.82	20.80	22	1
10	QPSK	25	12	20.86	20.80	20.76		
10	QPSK	25	25	20.79	20.71	20.67		
10	QPSK	50	0	20.85	20.78	20.76	22	1
10	16QAM	1	0	21.16	21.17	21.15		
10	16QAM	1	25	21.16	21.14	21.15		
10	16QAM	1	49	21.15	21.11	21.12	21	2
10	16QAM	25	0	19.89	19.85	19.86		
10	16QAM	25	12	19.90	19.84	19.81		
10	16QAM	25	25	19.82	19.75	19.73	21	2
10	16QAM	50	0	19.87	19.81	19.80		
Channel				19975	20175	20375		
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	21.82	21.79	21.73	23	0
5	QPSK	1	12	21.91	21.85	21.79		
5	QPSK	1	24	21.80	21.73	21.68		
5	QPSK	12	0	20.82	20.77	20.75	22	1
5	QPSK	12	7	20.89	20.81	20.77		
5	QPSK	12	13	20.83	20.76	20.71		
5	QPSK	25	0	20.83	20.77	20.73	22	1
5	16QAM	1	0	21.10	21.11	21.10		
5	16QAM	1	12	21.21	21.16	21.18		
5	16QAM	1	24	21.11	21.05	21.05	21	2
5	16QAM	12	0	19.85	19.82	19.83		
5	16QAM	12	7	19.92	19.86	19.86		
5	16QAM	12	13	19.87	19.80	19.79	21	2
5	16QAM	25	0	19.85	19.78	19.78		



Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	21.81	21.76	21.70	23	0
3	QPSK	1	8	21.83	21.77	21.71		
3	QPSK	1	14	21.82	21.74	21.67		
3	QPSK	8	0	20.86	20.82	20.77	22	1
3	QPSK	8	4	20.90	20.83	20.78		
3	QPSK	8	7	20.87	20.80	20.74		
3	QPSK	15	0	20.86	20.78	20.73	22	1
3	16QAM	1	0	21.09	21.09	21.07		
3	16QAM	1	8	21.12	21.11	21.09		
3	16QAM	1	14	21.11	21.06	21.06	21	2
3	16QAM	8	0	19.97	19.92	19.90		
3	16QAM	8	4	19.98	19.93	19.91		
3	16QAM	8	7	19.96	19.89	19.87	21	2
3	16QAM	15	0	19.89	19.83	19.80		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	21.69	21.65	21.58	23	0
1.4	QPSK	1	3	21.69	21.63	21.57		
1.4	QPSK	1	5	21.71	21.66	21.60		
1.4	QPSK	3	0	21.86	21.81	21.76	22	1
1.4	QPSK	3	1	21.87	21.82	21.76		
1.4	QPSK	3	3	21.88	21.83	21.78		
1.4	QPSK	6	0	20.85	20.79	20.74	22	1
1.4	16QAM	1	0	21.04	21.04	21.03		
1.4	16QAM	1	3	21.04	21.00	21.00		
1.4	16QAM	1	5	21.06	21.03	21.02	22	1
1.4	16QAM	3	0	20.91	20.89	20.88		
1.4	16QAM	3	1	20.95	20.93	20.91		
1.4	16QAM	3	3	20.91	20.89	20.87	21	2
1.4	16QAM	6	0	19.98	19.94	19.91		



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	22.60	22.63	22.52	24	0
10	QPSK	1	25	22.58	22.58	22.46		
10	QPSK	1	49	22.59	22.50	22.50		
10	QPSK	25	0	21.64	21.66	21.56	23	1
10	QPSK	25	12	21.62	21.59	21.52		
10	QPSK	25	25	21.60	21.60	21.50		
10	QPSK	50	0	21.60	21.65	21.54		
10	16QAM	1	0	21.94	21.95	21.82		
10	16QAM	1	25	21.94	21.91	21.78	23	1
10	16QAM	1	49	21.93	21.78	21.88		
10	16QAM	25	0	20.59	20.54	20.53		
10	16QAM	25	12	20.65	20.60	20.49	22	2
10	16QAM	25	25	20.71	20.58	20.48		
10	16QAM	50	0	20.67	20.57	20.52		
Channel				20425	20525	20625		
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.60	22.56	22.42	24	0
5	QPSK	1	12	22.65	22.62	22.52		
5	QPSK	1	24	22.58	22.49	22.48		
5	QPSK	12	0	21.59	21.56	21.50	23	1
5	QPSK	12	7	21.68	21.63	21.55		
5	QPSK	12	13	21.68	21.61	21.53		
5	QPSK	25	0	21.62	21.58	21.51		
5	16QAM	1	0	21.94	21.90	21.74		
5	16QAM	1	12	21.96	21.95	21.87	23	1
5	16QAM	1	24	21.90	21.82	21.84		
5	16QAM	12	0	20.57	20.54	20.48		
5	16QAM	12	7	20.66	20.61	20.54	22	2
5	16QAM	12	13	20.66	20.59	20.53		
5	16QAM	25	0	20.58	20.54	20.47		
Channel				20415	20525	20635		
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.60	22.55	22.44	24	0
3	QPSK	1	8	22.60	22.54	22.48		
3	QPSK	1	14	22.57	22.50	22.48		
3	QPSK	8	0	21.69	21.63	21.56	23	1
3	QPSK	8	4	21.72	21.65	21.59		
3	QPSK	8	7	21.68	21.62	21.58		
3	QPSK	15	0	21.67	21.60	21.56		
3	16QAM	1	0	21.93	21.87	21.76		
3	16QAM	1	8	21.93	21.88	21.83	23	1
3	16QAM	1	14	21.88	21.82	21.83		
3	16QAM	8	0	20.73	20.66	20.61		
3	16QAM	8	4	20.74	20.69	20.65	22	2
3	16QAM	8	7	20.70	20.65	20.63		
3	16QAM	15	0	20.66	20.60	20.56		
Channel				20407	20525	20643		
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	22.50	22.43	22.36	24	0
1.4	QPSK	1	3	22.49	22.41	22.37		
1.4	QPSK	1	5	22.52	22.43	22.41		
1.4	QPSK	3	0	22.67	22.59	22.54		
1.4	QPSK	3	1	22.68	22.60	22.55		
1.4	QPSK	3	3	22.69	22.61	22.57	23	1
1.4	QPSK	6	0	21.71	21.62	21.59		
1.4	16QAM	1	0	21.90	21.82	21.78		
1.4	16QAM	1	3	21.87	21.78	21.78	23	1
1.4	16QAM	1	5	21.87	21.80	21.80		
1.4	16QAM	3	0	21.77	21.70	21.65		
1.4	16QAM	3	1	21.81	21.73	21.69		
1.4	16QAM	3	3	21.76	21.68	21.66		
1.4	16QAM	6	0	20.77	20.69	20.67		
1.4	16QAM	6	0	20.77	20.69	20.67		



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)		
Channel				20850	21100	21350				
Frequency (MHz)				2510	2535	2560				
20	QPSK	1	0	21.76	21.85	21.84	22.5	0		
20	QPSK	1	49	21.71	21.82	21.83				
20	QPSK	1	99	21.75	21.84	21.80				
20	QPSK	50	0	20.80	20.90	20.89	21.5	1		
20	QPSK	50	24	20.79	20.87	20.87				
20	QPSK	50	50	20.75	20.84	20.84				
20	QPSK	100	0	20.75	20.91	20.90				
20	16QAM	1	0	20.90	20.94	21.01				
20	16QAM	1	49	20.99	21.09	21.21	21.5	1		
20	16QAM	1	99	21.00	21.09	21.20				
20	16QAM	50	0	19.65	19.83	19.92				
20	16QAM	50	24	19.74	19.84	19.93	20.5	2		
20	16QAM	50	50	19.77	19.79	19.84				
20	16QAM	100	0	19.70	19.80	19.88				
Channel				20825	21100	21375			Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5				
15	QPSK	1	0	21.67	21.70	21.79	22.5	0		
15	QPSK	1	37	21.72	21.82	21.90				
15	QPSK	1	74	21.71	21.80	21.86				
15	QPSK	36	0	20.73	20.83	20.92	21.5	1		
15	QPSK	36	20	20.79	20.87	20.94				
15	QPSK	36	39	20.80	20.85	20.88				
15	QPSK	75	0	20.77	20.84	20.89				
15	16QAM	1	0	20.91	20.94	21.07				
15	16QAM	1	37	20.99	21.08	21.21	21.5	1		
15	16QAM	1	74	20.97	21.06	21.20				
15	16QAM	36	0	19.68	19.78	19.89				
15	16QAM	36	20	19.75	19.82	19.91	20.5	2		
15	16QAM	36	39	19.75	19.80	19.87				
15	16QAM	75	0	19.72	19.79	19.88				
Channel				20800	21100	21400			Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565				
10	QPSK	1	0	21.69	21.74	21.82	22.5	0		
10	QPSK	1	25	21.73	21.82	21.86				
10	QPSK	1	49	21.74	21.83	21.87				
10	QPSK	25	0	20.72	20.84	20.90	21.5	1		
10	QPSK	25	12	20.78	20.86	20.91				
10	QPSK	25	25	20.79	20.84	20.84				
10	QPSK	50	0	20.78	20.86	20.88				
10	16QAM	1	0	20.95	20.99	21.13				
10	16QAM	1	25	21.00	21.09	21.21	21.5	1		
10	16QAM	1	49	21.03	21.11	21.23				
10	16QAM	25	0	19.67	19.79	19.89				
10	16QAM	25	12	19.74	19.82	19.91	20.5	2		
10	16QAM	25	25	19.76	19.80	19.84				
10	16QAM	50	0	19.73	19.81	19.87				
Channel				20775	21100	21425			Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5				
5	QPSK	1	0	21.69	21.75	21.80	22.5	0		
5	QPSK	1	12	21.79	21.86	21.90				
5	QPSK	1	24	21.70	21.78	21.81				
5	QPSK	12	0	20.72	20.81	20.87	21.5	1		
5	QPSK	12	7	20.80	20.87	20.91				
5	QPSK	12	13	20.80	20.86	20.89				
5	QPSK	25	0	20.77	20.84	20.88				
5	16QAM	1	0	20.95	21.01	21.13				
5	16QAM	1	12	21.06	21.12	21.22	21.5	1		
5	16QAM	1	24	20.97	21.05	21.16				
5	16QAM	12	0	19.69	19.77	19.87				
5	16QAM	12	7	19.77	19.83	19.92	20.5	2		
5	16QAM	12	13	19.77	19.81	19.89				
5	16QAM	12	13	19.77	19.81	19.89				
5	16QAM	25	0	19.71	19.78	19.86				



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	22.40	22.41	22.38	24	0
10	QPSK	1	25	22.39	22.36	22.34		
10	QPSK	1	49	22.38	22.40	22.37		
10	QPSK	25	0	21.35	21.38	21.37	23	1
10	QPSK	25	12	21.32	21.30	21.35		
10	QPSK	25	25	21.30	21.31	21.29		
10	QPSK	50	0	21.30	21.31	21.29	23	1
10	16QAM	1	0	21.60	21.60	21.56		
10	16QAM	1	25	21.67	21.63	21.61		
10	16QAM	1	49	21.67	21.68	21.64	22	2
10	16QAM	25	0	20.29	20.29	20.37		
10	16QAM	25	12	20.39	20.37	20.37		
10	16QAM	25	25	20.40	20.33	20.31	22	2
10	16QAM	25	0	20.35	20.32	20.35		
10	16QAM	50	0	20.35	20.32	20.35		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.33	22.30	22.29	24	0
5	QPSK	1	12	22.42	22.42	22.40		
5	QPSK	1	24	22.37	22.35	22.33		
5	QPSK	12	0	21.29	21.33	21.33	23	1
5	QPSK	12	7	21.40	21.39	21.37		
5	QPSK	12	13	21.41	21.34	21.32		
5	QPSK	25	0	21.35	21.33	21.32	23	1
5	16QAM	1	0	21.59	21.56	21.57		
5	16QAM	1	12	21.69	21.67	21.67		
5	16QAM	1	24	21.66	21.59	21.59	22	2
5	16QAM	12	0	20.33	20.35	20.35		
5	16QAM	12	7	20.44	20.42	20.41		
5	16QAM	12	13	20.44	20.36	20.34	22	2
5	16QAM	12	0	20.36	20.33	20.32		
5	16QAM	25	0	20.36	20.33	20.32		
Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.34	22.32	22.29	24	0
3	QPSK	1	8	22.37	22.34	22.32		
3	QPSK	1	14	22.36	22.34	22.32		
3	QPSK	8	0	21.40	21.39	21.37	23	1
3	QPSK	8	4	21.44	21.41	21.39		
3	QPSK	8	7	21.41	21.39	21.36		
3	QPSK	15	0	21.39	21.37	21.36	23	1
3	16QAM	1	0	21.62	21.57	21.54		
3	16QAM	1	8	21.67	21.60	21.58		
3	16QAM	1	14	21.65	21.59	21.57	22	2
3	16QAM	8	0	20.52	20.46	20.45		
3	16QAM	8	4	20.54	20.50	20.47		
3	16QAM	8	7	20.50	20.45	20.43	22	2
3	16QAM	8	0	20.43	20.39	20.38		
3	16QAM	15	0	20.43	20.39	20.38		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.23	22.22	22.19	24	0
1.4	QPSK	1	3	22.24	22.22	22.18		
1.4	QPSK	1	5	22.27	22.26	22.21		
1.4	QPSK	3	0	22.41	22.40	22.36	23	1
1.4	QPSK	3	1	22.43	22.41	22.38		
1.4	QPSK	3	3	22.44	22.42	22.39		
1.4	QPSK	6	0	21.41	21.41	21.37	23	1
1.4	16QAM	1	0	21.59	21.56	21.52		
1.4	16QAM	1	3	21.58	21.53	21.50		
1.4	16QAM	1	5	21.62	21.54	21.53	23	1
1.4	16QAM	3	0	21.46	21.44	21.40		
1.4	16QAM	3	1	21.51	21.46	21.43		
1.4	16QAM	3	3	21.48	21.43	21.40	22	2
1.4	16QAM	3	0	21.48	21.43	21.40		
1.4	16QAM	6	0	20.56	20.50	20.48	22	2



<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23230				
Frequency (MHz)				782				
10	QPSK	1	0	23.00			24	0
10	QPSK	1	25	22.90				
10	QPSK	1	49	22.88				
10	QPSK	25	0	21.94			23	1
10	QPSK	25	12	21.96				
10	QPSK	25	25	21.89				
10	QPSK	50	0	21.94				
10	16QAM	1	0	22.28			23	1
10	16QAM	1	25	22.23				
10	16QAM	1	49	22.25				
10	16QAM	25	0	20.95			22	2
10	16QAM	25	12	20.96				
10	16QAM	25	25	20.89				
10	16QAM	50	0	20.94				
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				779.5	782	784.5		
5	QPSK	1	0	22.92	22.89	22.87	24	0
5	QPSK	1	12	22.99	22.96	22.95		
5	QPSK	1	24	22.89	22.87	22.84		
5	QPSK	12	0	21.95	21.97	21.99	23	1
5	QPSK	12	7	22.02	21.99	21.98		
5	QPSK	12	13	22.00	21.93	21.92		
5	QPSK	25	0	21.97	21.94	21.96		
5	16QAM	1	0	22.27	22.26	22.20	23	1
5	16QAM	1	12	22.37	22.28	22.29		
5	16QAM	1	24	22.22	22.20	22.21		
5	16QAM	12	0	20.98	20.96	20.98	22	2
5	16QAM	12	7	21.04	20.99	20.99		
5	16QAM	12	13	21.00	20.93	20.92		
5	16QAM	25	0	20.96	20.92	20.93		



<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800		
Frequency (MHz)				709	710	711		
10	QPSK	1	0	22.40	22.41	22.37		
10	QPSK	1	25	22.39	22.38	22.35	24	0
10	QPSK	1	49	22.37	22.38	22.34		
10	QPSK	25	0	21.40	21.42	21.40	23	1
10	QPSK	25	12	21.39	21.38	21.37		
10	QPSK	25	25	21.36	21.33	21.30		
10	QPSK	50	0	21.39	21.40	21.36		
10	16QAM	1	0	21.60	21.60	21.58	23	1
10	16QAM	1	25	21.65	21.63	21.62		
10	16QAM	1	49	21.65	21.65	21.65		
10	16QAM	25	0	20.39	20.40	20.40	22	2
10	16QAM	25	12	20.43	20.41	20.39		
10	16QAM	25	25	20.38	20.35	20.31		
10	16QAM	50	0	20.40	20.39	20.39		
Channel				23755	23790	23825		
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	22.32	22.32	22.32		
5	QPSK	1	12	22.46	22.43	22.37	24	0
5	QPSK	1	24	22.38	22.34	22.33		
5	QPSK	12	0	21.34	21.38	21.32	23	1
5	QPSK	12	7	21.43	21.40	21.35		
5	QPSK	12	13	21.39	21.40	21.33		
5	QPSK	25	0	21.38	21.40	21.32		
5	16QAM	1	0	21.59	21.58	21.58	23	1
5	16QAM	1	12	21.71	21.67	21.62		
5	16QAM	1	24	21.64	21.62	21.59		
5	16QAM	12	0	20.37	20.39	20.35	22	2
5	16QAM	12	7	20.46	20.43	20.39		
5	16QAM	12	13	20.42	20.42	20.37		
5	16QAM	25	0	20.37	20.39	20.33		

**<WLAN Conducted Power>**

**General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
  - a. When the reported SAR of the initial test position is  $\leq 0.4$  W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
  - b. When the reported SAR of the test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is  $\leq 0.8$  W/kg or all required test position are tested.
  - c. For all positions/configurations, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.





<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b	CH 1	2412	1Mbps	17.73	18.00	100.00
		CH 6	2437		17.81	18.00	
		CH 11	2462		17.65	18.00	
	802.11g	CH 1	2412	6Mbps	14.63	15.00	97.20
		CH 6	2437		14.78	15.00	
		CH 11	2462		14.68	15.00	
	802.11n-HT20	CH 1	2412	MCS0	11.29	11.50	97.02
		CH 6	2437		11.36	11.50	
		CH 11	2462		11.19	11.50	
	802.11n-HT40	CH 3	2422	MCS0	11.19	11.50	94.71
		CH 6	2437		11.36	11.50	
		CH 9	2452		11.25	11.50	

<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a	CH 36	5180	6Mbps	13.90	14.00	97.20
		CH 40	5200		13.83	14.00	
		CH 44	5220		13.83	14.00	
		CH 48	5240		13.87	14.00	
	802.11n-HT20	CH 36	5180	MCS0	11.42	11.50	97.02
		CH 40	5200		11.49	11.50	
		CH 44	5220		11.38	11.50	
		CH 48	5240		11.34	11.50	
	802.11n-HT40	CH 38	5190	MCS0	11.49	11.50	94.15
		CH 46	5230		11.47	11.50	

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a	CH 52	5260	6Mbps	13.67	14.00	97.20
		CH 56	5280		13.76	14.00	
		CH 60	5300		13.68	14.00	
		CH 64	5320		13.73	14.00	
	802.11n-HT20	CH 52	5260	MCS0	11.25	11.50	97.02
		CH 56	5280		11.28	11.50	
		CH 60	5300		11.26	11.50	
		CH 64	5320		11.34	11.50	
	802.11n-HT40	CH 54	5270	MCS0	11.30	11.50	94.15
		CH 62	5310		10.42	10.50	



	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a	CH 100	5500	6Mbps	13.73	14.00	97.20
		CH 116	5580		13.65	14.00	
		CH 124	5620		13.62	14.00	
		CH 132	5660		13.68	14.00	
		CH 140	5700		13.60	14.00	
	802.11n-HT20	CH 100	5500	MCS0	11.31	11.50	97.02
		CH 116	5580		11.22	11.50	
		CH 124	5620		11.23	11.50	
		CH 132	5660		11.24	11.50	
		CH 140	5700		11.10	11.50	
	802.11n-HT40	CH 102	5510	MCS0	11.47	11.50	94.15
		CH 110	5550		11.34	11.50	
		CH 126	5630		11.39	11.50	
		CH 134	5670		11.30	11.50	

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a	CH 149	5745	MCS0	9.77	10.00	97.20
		CH 157	5785		13.74	14.00	
		CH 165	5825		13.89	14.00	
	802.11n-HT20	CH 149	5745	MCS0	11.28	11.50	97.02
		CH 157	5785		11.36	11.50	
		CH 165	5825		11.44	11.50	
	802.11n-HT40	CH 151	5755	MCS0	9.21	9.50	94.15
		CH 159	5795		11.44	11.50	

### 13. Bluetooth Exclusions Applied

Mode Band	Average power(dBm)	
	Bluetooth3.0+EDR	Bluetooth4.1+LE
2.4GHz Bluetooth	7	1

**Note:**

- Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:  

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g Product Specific SAR
  - f(GHz) is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation
  - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
7	15	2.48	0.52

**Note:**

Per KDB 447498 D01v06, The test exclusion threshold is 0.52 which is ≤ 3, SAR testing is not required.

### 14. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	> 25mm	> 25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

**General Note:**

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm\*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge
- The detail antenna location please refers to Appendix D.

## 15. SAR Test Results

### General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
  - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
  - d. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
  - $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8$ W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$  W/kg, SAR testing with a headset connected to the handset is not required.
5. Per KDB 648474 D04v01r03, Product Specific SAR test is required when the display diagonal dimension  $> 15$ cm or an overall diagonal dimension  $> 16$ cm.
6. Per KDB 648474 D04v01r03, for Product Specific must also be applied to test of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge.
7. The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report all the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same and the spot check results will compare with original results to found worse case to perform simultaneous transmission analysis.

### GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode, SAR measurement is not required for the secondary mode.

### UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq 1/4$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

**LTE Note:**

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B12 / B5 / B4 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 17 SAR test was covered by Band 12 ; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
  - a. the maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion
  - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band

**WLAN Note:**

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.
2. Per KDB 248227 D01v02r02, for U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is  $\leq 0.8$  W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.



**15.1 Head SAR**

**<GSM SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GMSK	GPRS (4 Tx slots)	Right Cheek	0mm	189	836.4	27.28	29.00	1.486	0.08	0.138	0.205	0.111	0.165
	GSM850	GMSK	GPRS (4 Tx slots)	Right Tilted	0mm	189	836.4	27.28	29.00	1.486	0.03	0.087	0.129	0.069	0.103
	GSM850	GMSK	GPRS (4 Tx slots)	Left Cheek	0mm	189	836.4	27.28	29.00	1.486	-0.06	0.165	0.245	0.128	0.190
	GSM850	GMSK	GPRS (4 Tx slots)	Left Cheek	0mm	128	824.2	27.24	29.00	1.500	0.05	0.155	0.232	0.123	0.184
01	GSM850	GMSK	GPRS (4 Tx slots)	Left Cheek	0mm	251	848.8	27.13	29.00	1.538	0.05	0.175	0.269	0.136	0.209
	GSM850	GMSK	GPRS (4 Tx slots)	Left Tilted	0mm	189	836.4	27.28	29.00	1.486	-0.01	0.085	0.126	0.067	0.100
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Cheek	0mm	810	1909.8	24.72	25.00	1.067	0.07	0.127	0.135	0.079	0.084
02	GSM1900	GMSK	GPRS (4 Tx slots)	Right Cheek	0mm	512	1850.2	24.20	25.00	1.202	0.07	0.181	0.218	0.115	0.138
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Cheek	0mm	661	1880	24.56	25.00	1.107	0.14	0.155	0.172	0.098	0.108
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Tilted	0mm	810	1909.8	24.72	25.00	1.067	-0.05	0.036	0.038	0.023	0.025
	GSM1900	GMSK	GPRS (4 Tx slots)	Left Cheek	0mm	810	1909.8	24.72	25.00	1.067	0.09	0.095	0.101	0.057	0.061
	GSM1900	GMSK	GPRS (4 Tx slots)	Left Tilted	0mm	810	1909.8	24.72	25.00	1.067	0.02	0.054	0.058	0.029	0.031

**<WCDMA SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
03	WCDMA II	QPSK	RMC 12.2Kbps	Right Cheek	0mm	9538	1907.6	23.96	24.00	1.009	-0.19	0.252	0.254	0.159	0.160
	WCDMA II	QPSK	RMC 12.2Kbps	Right Cheek	0mm	9262	1852.4	23.78	24.00	1.052	0.17	0.198	0.208	0.126	0.133
	WCDMA II	QPSK	RMC 12.2Kbps	Right Cheek	0mm	9400	1880	23.82	24.00	1.042	0.05	0.213	0.222	0.135	0.141
	WCDMA II	QPSK	RMC 12.2Kbps	Right Tilted	0mm	9538	1907.6	23.96	24.00	1.009	-0.01	0.077	0.078	0.049	0.049
	WCDMA II	QPSK	RMC 12.2Kbps	Left Cheek	0mm	9538	1907.6	23.96	24.00	1.009	0	0.173	0.175	0.107	0.108
	WCDMA II	QPSK	RMC 12.2Kbps	Left Tilted	0mm	9538	1907.6	23.96	24.00	1.009	0.13	0.106	0.107	0.059	0.060
04	WCDMA IV	QPSK	RMC 12.2Kbps	Right Cheek	0mm	1513	1752.6	22.95	23.00	1.012	-0.06	0.270	0.273	0.177	0.179
	WCDMA IV	QPSK	RMC 12.2Kbps	Right Cheek	0mm	1312	1712.4	22.85	23.00	1.035	-0.05	0.201	0.208	0.135	0.140
	WCDMA IV	QPSK	RMC 12.2Kbps	Right Cheek	0mm	1413	1732.6	22.90	23.00	1.023	-0.06	0.251	0.257	0.168	0.172
	WCDMA IV	QPSK	RMC 12.2Kbps	Right Tilted	0mm	1513	1752.6	22.95	23.00	1.012	0.05	0.101	0.102	0.066	0.067
	WCDMA IV	QPSK	RMC 12.2Kbps	Left Cheek	0mm	1513	1752.6	22.95	23.00	1.012	0.05	0.171	0.173	0.112	0.113
	WCDMA IV	QPSK	RMC 12.2Kbps	Left Tilted	0mm	1513	1752.6	22.95	23.00	1.012	0.11	0.070	0.071	0.042	0.042
	WCDMA V	QPSK	RMC 12.2Kbps	Right Cheek	0mm	4233	846.6	23.99	24.00	1.002	0.07	0.176	0.176	0.140	0.140
	WCDMA V	QPSK	RMC 12.2Kbps	Right Tilted	0mm	4233	846.6	23.99	24.00	1.002	-0.05	0.113	0.113	0.089	0.089
05	WCDMA V	QPSK	RMC 12.2Kbps	Left Cheek	0mm	4233	846.6	23.99	24.00	1.002	0.05	0.217	0.218	0.167	0.167
	WCDMA V	QPSK	RMC 12.2Kbps	Left Cheek	0mm	4132	826.4	23.95	24.00	1.012	0.07	0.141	0.143	0.110	0.111
	WCDMA V	QPSK	RMC 12.2Kbps	Left Cheek	0mm	4182	836.4	23.96	24.00	1.009	0.02	0.173	0.175	0.134	0.135
	WCDMA V	QPSK	RMC 12.2Kbps	Left Tilted	0mm	4233	846.6	23.99	24.00	1.002	-0.02	0.109	0.109	0.086	0.086



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	18900	1880	22.92	24.00	1.282	0.1	0.188	0.241	0.117	0.150
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	18700	1860	22.89	24.00	1.291	0.01	0.179	0.231	0.113	0.146
06	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	19100	1900	22.90	24.00	1.288	-0.06	0.188	0.242	0.118	0.152
	LTE Band 2	20M	QPSK	50	0	Right Cheek	0mm	18900	1880	21.95	23.00	1.274	0.03	0.157	0.200	0.099	0.126
	LTE Band 2	20M	QPSK	1	0	Right Tilted	0mm	18900	1880	22.92	24.00	1.282	-0.14	0.049	0.063	0.030	0.038
	LTE Band 2	20M	QPSK	50	0	Right Tilted	0mm	18900	1880	21.95	23.00	1.274	0.13	0.039	0.050	0.024	0.031
	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	18900	1880	22.92	24.00	1.282	-0.04	0.118	0.151	0.074	0.095
	LTE Band 2	20M	QPSK	50	0	Left Cheek	0mm	18900	1880	21.95	23.00	1.274	0.03	0.094	0.120	0.060	0.076
	LTE Band 2	20M	QPSK	1	0	Left Tilted	0mm	18900	1880	22.92	24.00	1.282	0.03	0.068	0.087	0.038	0.049
	LTE Band 2	20M	QPSK	50	0	Left Tilted	0mm	18900	1880	21.95	23.00	1.274	0.09	0.056	0.071	0.031	0.039
07	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	20175	1732.5	21.91	23.00	1.285	-0.01	0.177	0.227	0.117	0.150
	LTE Band 4	20M	QPSK	50	0	Right Cheek	0mm	20175	1732.5	20.91	22.00	1.285	-0.04	0.150	0.193	0.099	0.127
	LTE Band 4	20M	QPSK	1	0	Right Tilted	0mm	20175	1732.5	21.91	23.00	1.285	0	0.093	0.120	0.061	0.078
	LTE Band 4	20M	QPSK	50	0	Right Tilted	0mm	20175	1732.5	20.91	22.00	1.285	0.02	0.076	0.098	0.049	0.063
	LTE Band 4	20M	QPSK	1	0	Left Cheek	0mm	20175	1732.5	21.91	23.00	1.285	-0.01	0.118	0.152	0.079	0.102
	LTE Band 4	20M	QPSK	50	0	Left Cheek	0mm	20175	1732.5	20.91	22.00	1.285	0.04	0.096	0.123	0.063	0.081
	LTE Band 4	20M	QPSK	1	0	Left Tilted	0mm	20175	1732.5	21.91	23.00	1.285	0.11	0.061	0.078	0.039	0.050
	LTE Band 4	20M	QPSK	50	0	Left Tilted	0mm	20175	1732.5	20.91	22.00	1.285	0.01	0.049	0.063	0.032	0.041
	LTE Band 5	10M	QPSK	1	0	Right Cheek	0mm	20525	836.5	22.63	24.00	1.371	0.04	0.123	0.169	0.099	0.136
	LTE Band 5	10M	QPSK	25	0	Right Cheek	0mm	20525	836.5	21.66	23.00	1.361	-0.01	0.101	0.138	0.081	0.110
	LTE Band 5	10M	QPSK	1	0	Right Tilted	0mm	20525	836.5	22.63	24.00	1.371	0.12	0.033	0.045	0.026	0.036
	LTE Band 5	10M	QPSK	25	0	Right Tilted	0mm	20525	836.5	21.66	23.00	1.361	-0.13	0.028	0.038	0.023	0.031
08	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	20525	836.5	22.63	24.00	1.371	0.07	0.156	0.214	0.121	0.166
	LTE Band 5	10M	QPSK	25	0	Left Cheek	0mm	20525	836.5	21.66	23.00	1.361	0.05	0.129	0.176	0.100	0.136
	LTE Band 5	10M	QPSK	1	0	Left Tilted	0mm	20525	836.5	22.63	24.00	1.371	0.16	0.028	0.038	0.022	0.030
	LTE Band 5	10M	QPSK	25	0	Left Tilted	0mm	20525	836.5	21.66	23.00	1.361	-0.01	0.022	0.030	0.017	0.023
	LTE Band 7	20M	QPSK	1	0	Right Cheek	0mm	21100	2535	21.85	22.50	1.161	0.11	0.068	0.079	0.036	0.042
09	LTE Band 7	20M	QPSK	1	0	Right Cheek	0mm	20850	2510	21.76	22.50	1.186	0.03	0.086	0.102	0.046	0.055
	LTE Band 7	20M	QPSK	1	0	Right Cheek	0mm	21350	2560	21.84	22.50	1.164	-0.16	0.070	0.081	0.036	0.042
	LTE Band 7	20M	QPSK	50	0	Right Cheek	0mm	21100	2535	20.90	21.50	1.148	0.08	0.057	0.065	0.030	0.034
	LTE Band 7	20M	QPSK	1	0	Right Tilted	0mm	21100	2535	21.85	22.50	1.161	0.12	0.060	0.070	0.035	0.041
	LTE Band 7	20M	QPSK	50	0	Right Tilted	0mm	21100	2535	20.90	21.50	1.148	0.02	0.057	0.065	0.030	0.034
	LTE Band 7	20M	QPSK	1	0	Left Cheek	0mm	21100	2535	21.85	22.50	1.161	0.13	0.030	0.035	0.014	0.016
	LTE Band 7	20M	QPSK	50	0	Left Cheek	0mm	21100	2535	20.90	21.50	1.148	0.11	0.018	0.021	0.007	0.009
	LTE Band 7	20M	QPSK	1	0	Left Tilted	0mm	21100	2535	21.85	22.50	1.161	-0.11	0.025	0.029	0.010	0.012
	LTE Band 7	20M	QPSK	50	0	Left Tilted	0mm	21100	2535	20.90	21.50	1.148	-0.1	0.022	0.025	0.009	0.010
	LTE Band 12	10M	QPSK	1	0	Right Cheek	0mm	23095	707.5	22.41	24.00	1.442	0.06	0.035	0.050	0.030	0.043
	LTE Band 12	10M	QPSK	25	0	Right Cheek	0mm	23095	707.5	21.38	23.00	1.452	0.06	0.025	0.036	0.021	0.030
	LTE Band 12	10M	QPSK	1	0	Right Tilted	0mm	23095	707.5	22.41	24.00	1.442	0.03	0.006	0.008	0.005	0.007
	LTE Band 12	10M	QPSK	25	0	Right Tilted	0mm	23095	707.5	21.38	23.00	1.452	-0.11	0.003	0.005	0.003	0.004
10	LTE Band 12	10M	QPSK	1	0	Left Cheek	0mm	23095	707.5	22.41	24.00	1.442	-0.12	0.038	0.055	0.032	0.046
	LTE Band 12	10M	QPSK	25	0	Left Cheek	0mm	23095	707.5	21.38	23.00	1.452	0.14	0.027	0.039	0.022	0.032
	LTE Band 12	10M	QPSK	1	0	Left Tilted	0mm	23095	707.5	22.41	24.00	1.442	0.14	0.019	0.027	0.017	0.025
	LTE Band 12	10M	QPSK	25	0	Left Tilted	0mm	23095	707.5	21.38	23.00	1.452	-0.01	0.014	0.020	0.012	0.017
	LTE Band 13	10M	QPSK	1	0	Right Cheek	0mm	23230	782	23.00	24.00	1.259	0.09	0.104	0.131	0.086	0.108
	LTE Band 13	10M	QPSK	25	12	Right Cheek	0mm	23230	782	21.96	23.00	1.271	0.1	0.086	0.109	0.071	0.090
	LTE Band 13	10M	QPSK	1	0	Right Tilted	0mm	23230	782	23.00	24.00	1.259	0.07	0.067	0.084	0.055	0.069
	LTE Band 13	10M	QPSK	25	12	Right Tilted	0mm	23230	782	21.96	23.00	1.271	-0.18	0.056	0.071	0.046	0.058
11	LTE Band 13	10M	QPSK	1	0	Left Cheek	0mm	23230	782	23.00	24.00	1.259	0.07	0.135	0.170	0.107	0.135
	LTE Band 13	10M	QPSK	25	12	Left Cheek	0mm	23230	782	21.96	23.00	1.271	0.06	0.112	0.142	0.089	0.113
	LTE Band 13	10M	QPSK	1	0	Left Tilted	0mm	23230	782	23.00	24.00	1.259	0.07	0.074	0.093	0.061	0.077
	LTE Band 13	10M	QPSK	25	12	Left Tilted	0mm	23230	782	21.96	23.00	1.271	0.01	0.062	0.079	0.050	0.064





<WLAN SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	Note	
12	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Cheek	0mm	6	2437	17.81	18.00	1.045	100	1.000	0.01	1.010	1.055	0.495	0.517		
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Cheek	0mm	1	2412	17.73	18.00	1.064	100	1.000	0.18	1.020	1.085	0.508	0.541		
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Tilted	0mm	6	2437	17.81	18.00	1.045	100	1.000	-0.01	0.777	0.812	0.367	0.383		
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Tilted	0mm	1	2412	17.73	18.00	1.064	100	1.000	-0.01	0.794	0.845	0.379	0.403		
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Cheek	0mm	6	2437	17.81	18.00	1.045	100	1.000	-0.01	0.496	0.518	0.247	0.258		
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Tilted	0mm	6	2437	17.81	18.00	1.045	100	1.000	0.03	0.492	0.514	0.240	0.251		
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Right Cheek	0mm	1	2412	17.64	18.00	1.086	100	1.000	0.18	0.836	0.908	0.416	0.452	(3)	
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Cheek	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	-0.18	0.167	0.182	0.038	0.041		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	0.14	0.506	0.550	0.141	0.153		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	64	5280	13.73	14.00	1.064	97.2	1.029	0.15	0.581	0.636	0.150	0.164		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Cheek	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	-0.15	0.378	0.411	0.126	0.137		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Tilted	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	-0.08	0.405	0.440	0.136	0.148		
	13	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	64	5320	13.54	14.00	1.112	97.22	1.029	0.04	0.611	0.699	0.174	0.199	(3)
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Cheek	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	0.18	0.811	0.888	0.219	0.240		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Cheek	0mm	132	5660	13.68	14.00	1.076	97.2	1.029	-0.16	0.972	1.077	0.254	0.281		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	0.17	0.816	0.894	0.228	0.250		
	14	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	132	5660	13.68	14.00	1.076	97.2	1.029	0.04	1.080	1.196	0.291	0.322	
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Cheek	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	-0.08	0.708	0.775	0.240	0.263		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Tilted	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	-0.07	0.778	0.852	0.262	0.287		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Tilted	0mm	132	5660	13.68	14.00	1.076	97.2	1.029	-0.19	1.030	1.141	0.251	0.278		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	132	5660	13.68	14.00	1.076	97.22	1.029	0.14	0.958	1.061	0.257	0.285	(3)	
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Cheek	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	0.09	0.861	0.909	0.225	0.237		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Cheek	0mm	157	5785	13.74	14.00	1.062	97.2	1.029	0.14	0.843	0.921	0.215	0.235		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	0.12	0.926	0.977	0.244	0.258		
	WLAN5GHz	OFDM	802.11a 6Mbps	Right Tilted	0mm	157	5785	13.74	14.00	1.062	97.2	1.029	0.12	0.911	0.995	0.239	0.261		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Cheek	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.13	0.945	0.997	0.318	0.336		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Cheek	0mm	157	5785	13.74	14.00	1.062	97.2	1.029	0.06	0.893	0.976	0.296	0.323		
	15	WLAN5GHz	OFDM	802.11a 6Mbps	Left Tilted	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.01	0.988	1.043	0.330	0.348	
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Tilted	0mm	157	5785	13.74	14.00	1.062	97.2	1.029	-0.11	0.940	1.027	0.308	0.336		
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Tilted	0mm	165	5825	13.83	14.00	1.040	97.22	1.029	-0.16	0.799	0.855	0.264	0.283	(3)	

Note:

- (1). The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same, and the spot check results will compare with original results to found worse case to perform simultaneous transmission analysis.
- (2). The conducted power for spot check was re-measured to ensure that both devices are the same.
- (3). Spot check verification on PY7-PM0954.





15.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GMSK	GPRS (4 Tx slots)	Front	10mm	189	836.4	27.28	29.00	1.486	-0.03	0.184	0.273	0.141	0.210
	GSM850	GMSK	GPRS (4 Tx slots)	Back	10mm	189	836.4	27.28	29.00	1.486	-0.02	0.531	0.789	0.299	0.444
	GSM850	GMSK	GPRS (4 Tx slots)	Back	10mm	128	824.2	27.24	29.00	1.500	-0.06	0.439	0.658	0.249	0.373
16	GSM850	GMSK	GPRS (4 Tx slots)	Back	10mm	251	848.8	27.13	29.00	1.538	0.05	0.551	0.848	0.307	0.472
	GSM850	GMSK	GPRS (4 Tx slots)	Left Side	10mm	189	836.4	27.28	29.00	1.486	-0.1	0.310	0.461	0.211	0.314
	GSM850	GMSK	GPRS (4 Tx slots)	Right Side	10mm	189	836.4	27.28	29.00	1.486	-0.08	0.137	0.204	0.093	0.138
	GSM850	GMSK	GPRS (4 Tx slots)	Bottom Side	10mm	189	836.4	27.28	29.00	1.486	0.13	0.208	0.309	0.121	0.180
	GSM1900	GMSK	GPRS (4 Tx slots)	Front	10mm	810	1909.8	24.72	25.00	1.067	-0.1	0.307	0.327	0.173	0.185
	GSM1900	GMSK	GPRS (4 Tx slots)	Back	10mm	810	1909.8	24.72	25.00	1.067	0.16	0.322	0.343	0.178	0.190
	GSM1900	GMSK	GPRS (4 Tx slots)	Back	10mm	661	1880	24.56	25.00	1.107	0.11	0.407	0.450	0.222	0.246
17	GSM1900	GMSK	GPRS (4 Tx slots)	Back	10mm	512	1850.2	24.20	25.00	1.202	0.02	0.446	0.536	0.247	0.297
	GSM1900	GMSK	GPRS (4 Tx slots)	Left Side	10mm	810	1909.8	24.72	25.00	1.067	-0.19	0.026	0.028	0.012	0.013
	GSM1900	GMSK	GPRS (4 Tx slots)	Right Side	10mm	810	1909.8	24.72	25.00	1.067	0.12	0.189	0.202	0.107	0.114
	GSM1900	GMSK	GPRS (4 Tx slots)	Bottom Side	10mm	810	1909.8	24.72	25.00	1.067	-0.08	0.176	0.188	0.100	0.107

<WCDMA SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	QPSK	RMC 12.2Kbps	Front	10mm	9538	1907.6	23.96	24.00	1.009	-0.11	0.541	0.546	0.308	0.311
	WCDMA II	QPSK	RMC 12.2Kbps	Back	10mm	9538	1907.6	23.96	24.00	1.009	-0.13	0.613	0.619	0.338	0.341
18	WCDMA II	QPSK	RMC 12.2Kbps	Back	10mm	9400	1880	23.82	24.00	1.042	0.11	0.623	0.649	0.339	0.353
	WCDMA II	QPSK	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.78	24.00	1.052	-0.16	0.532	0.560	0.291	0.306
	WCDMA II	QPSK	RMC 12.2Kbps	Left Side	10mm	9538	1907.6	23.96	24.00	1.009	-0.07	0.038	0.038	0.022	0.022
	WCDMA II	QPSK	RMC 12.2Kbps	Right Side	10mm	9538	1907.6	23.96	24.00	1.009	-0.13	0.363	0.366	0.210	0.212
	WCDMA II	QPSK	RMC 12.2Kbps	Bottom Side	10mm	9538	1907.6	23.96	24.00	1.009	-0.11	0.256	0.258	0.145	0.146
	WCDMA IV	QPSK	RMC 12.2Kbps	Front	10mm	1513	1752.6	22.95	23.00	1.012	-0.11	0.542	0.548	0.325	0.329
	WCDMA IV	QPSK	RMC 12.2Kbps	Back	10mm	1513	1752.6	22.95	23.00	1.012	-0.01	0.557	0.563	0.333	0.337
	WCDMA IV	QPSK	RMC 12.2Kbps	Back	10mm	1312	1712.4	22.85	23.00	1.035	-0.13	0.448	0.464	0.264	0.273
19	WCDMA IV	QPSK	RMC 12.2Kbps	Back	10mm	1413	1732.6	22.90	23.00	1.023	-0.04	0.563	0.576	0.331	0.339
	WCDMA IV	QPSK	RMC 12.2Kbps	Left Side	10mm	1513	1752.6	22.95	23.00	1.012	0.02	0.180	0.182	0.109	0.110
	WCDMA IV	QPSK	RMC 12.2Kbps	Right Side	10mm	1513	1752.6	22.95	23.00	1.012	-0.03	0.494	0.500	0.290	0.293
	WCDMA IV	QPSK	RMC 12.2Kbps	Bottom Side	10mm	1513	1752.6	22.95	23.00	1.012	0.08	0.549	0.555	0.323	0.327
	WCDMA V	QPSK	RMC 12.2Kbps	Front	10mm	4233	846.6	23.99	24.00	1.002	0.09	0.207	0.207	0.130	0.130
20	WCDMA V	QPSK	RMC 12.2Kbps	Back	10mm	4233	846.6	23.99	24.00	1.002	0.14	0.570	0.571	0.320	0.321
	WCDMA V	QPSK	RMC 12.2Kbps	Back	10mm	4132	826.4	23.95	24.00	1.012	0.01	0.408	0.413	0.230	0.233
	WCDMA V	QPSK	RMC 12.2Kbps	Back	10mm	4182	836.4	23.96	24.00	1.009	0.04	0.493	0.498	0.277	0.280
	WCDMA V	QPSK	RMC 12.2Kbps	Left Side	10mm	4233	846.6	23.99	24.00	1.002	-0.07	0.358	0.359	0.243	0.244
	WCDMA V	QPSK	RMC 12.2Kbps	Right Side	10mm	4233	846.6	23.99	24.00	1.002	-0.08	0.159	0.159	0.107	0.107
	WCDMA V	QPSK	RMC 12.2Kbps	Bottom Side	10mm	4233	846.6	23.99	24.00	1.002	0.14	0.268	0.269	0.155	0.155



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	10mm	18900	1880	22.92	24.00	1.282	-0.14	0.406	0.521	0.232	0.298
	LTE Band 2	20M	QPSK	50	0	Front	10mm	18900	1880	21.95	23.00	1.274	-0.1	0.341	0.434	0.193	0.246
	LTE Band 2	20M	QPSK	1	0	Back	10mm	18900	1880	22.92	24.00	1.282	0.13	0.452	0.580	0.249	0.319
	LTE Band 2	20M	QPSK	1	0	Back	10mm	18700	1860	22.89	24.00	1.291	0.1	0.451	0.582	0.253	0.327
21	LTE Band 2	20M	QPSK	1	0	Back	10mm	19100	1900	22.90	24.00	1.288	0.11	0.522	0.672	0.283	0.365
	LTE Band 2	20M	QPSK	50	0	Back	10mm	18900	1880	21.95	23.00	1.274	0.13	0.369	0.470	0.203	0.259
	LTE Band 2	20M	QPSK	1	0	Left Side	10mm	18900	1880	22.92	24.00	1.282	0.01	0.045	0.058	0.026	0.033
	LTE Band 2	20M	QPSK	50	0	Left Side	10mm	18900	1880	21.95	23.00	1.274	0.16	0.040	0.051	0.022	0.028
	LTE Band 2	20M	QPSK	1	0	Right Side	10mm	18900	1880	22.92	24.00	1.282	0.02	0.277	0.355	0.160	0.205
	LTE Band 2	20M	QPSK	50	0	Right Side	10mm	18900	1880	21.95	23.00	1.274	-0.04	0.224	0.285	0.129	0.164
	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	18900	1880	22.92	24.00	1.282	0	0.277	0.355	0.156	0.200
	LTE Band 2	20M	QPSK	50	0	Bottom Side	10mm	18900	1880	21.95	23.00	1.274	0	0.225	0.287	0.126	0.160
	LTE Band 4	20M	QPSK	1	0	Front	10mm	20175	1732.5	21.91	23.00	1.285	-0.04	0.335	0.431	0.200	0.257
	LTE Band 4	20M	QPSK	50	0	Front	10mm	20175	1732.5	20.91	22.00	1.285	-0.14	0.282	0.362	0.167	0.215
	LTE Band 4	20M	QPSK	1	0	Back	10mm	20175	1732.5	21.91	23.00	1.285	-0.04	0.373	0.479	0.216	0.278
	LTE Band 4	20M	QPSK	50	0	Back	10mm	20175	1732.5	20.91	22.00	1.285	-0.08	0.315	0.405	0.184	0.236
	LTE Band 4	20M	QPSK	1	0	Left Side	10mm	20175	1732.5	21.91	23.00	1.285	0.02	0.173	0.222	0.105	0.135
	LTE Band 4	20M	QPSK	50	0	Left Side	10mm	20175	1732.5	20.91	22.00	1.285	0.07	0.142	0.183	0.085	0.109
	LTE Band 4	20M	QPSK	1	0	Right Side	10mm	20175	1732.5	21.91	23.00	1.285	0.04	0.336	0.432	0.198	0.254
	LTE Band 4	20M	QPSK	50	0	Right Side	10mm	20175	1732.5	20.91	22.00	1.285	0.03	0.281	0.361	0.165	0.212
22	LTE Band 4	20M	QPSK	1	0	Bottom Side	10mm	20175	1732.5	21.91	23.00	1.285	0.04	0.402	0.517	0.237	0.305
	LTE Band 4	20M	QPSK	50	0	Bottom Side	10mm	20175	1732.5	20.91	22.00	1.285	0.05	0.325	0.418	0.191	0.245
	LTE Band 5	10M	QPSK	1	0	Front	10mm	20525	836.5	22.63	24.00	1.371	0.01	0.192	0.263	0.118	0.162
	LTE Band 5	10M	QPSK	25	0	Front	10mm	20525	836.5	21.66	23.00	1.361	0.01	0.157	0.214	0.096	0.131
23	LTE Band 5	10M	QPSK	1	0	Back	10mm	20525	836.5	22.63	24.00	1.371	0.02	0.562	0.770	0.312	0.428
	LTE Band 5	10M	QPSK	25	0	Back	10mm	20525	836.5	21.66	23.00	1.361	0.04	0.462	0.629	0.256	0.349
	LTE Band 5	10M	QPSK	1	0	Left Side	10mm	20525	836.5	22.63	24.00	1.371	-0.04	0.295	0.404	0.202	0.277
	LTE Band 5	10M	QPSK	25	0	Left Side	10mm	20525	836.5	21.66	23.00	1.361	-0.03	0.238	0.324	0.163	0.222
	LTE Band 5	10M	QPSK	1	0	Right Side	10mm	20525	836.5	22.63	24.00	1.371	0.01	0.119	0.163	0.081	0.111
	LTE Band 5	10M	QPSK	25	0	Right Side	10mm	20525	836.5	21.66	23.00	1.361	-0.04	0.095	0.129	0.064	0.087
	LTE Band 5	10M	QPSK	1	0	Bottom Side	10mm	20525	836.5	22.63	24.00	1.371	0.11	0.229	0.314	0.131	0.180
	LTE Band 5	10M	QPSK	25	0	Bottom Side	10mm	20525	836.5	21.66	23.00	1.361	0.12	0.189	0.257	0.107	0.146
	LTE Band 7	20M	QPSK	1	0	Front	10mm	21100	2535	21.85	22.50	1.161	-0.11	0.221	0.257	0.117	0.136
	LTE Band 7	20M	QPSK	50	0	Front	10mm	21100	2535	20.90	21.50	1.148	-0.17	0.182	0.209	0.096	0.110
	LTE Band 7	20M	QPSK	1	0	Back	10mm	21100	2535	21.85	22.50	1.161	-0.13	0.402	0.467	0.180	0.209
24	LTE Band 7	20M	QPSK	1	0	Back	10mm	20850	2510	21.76	22.50	1.186	0.16	0.437	0.518	0.199	0.236
	LTE Band 7	20M	QPSK	1	0	Back	10mm	21350	2560	21.84	22.50	1.164	-0.17	0.372	0.433	0.166	0.193
	LTE Band 7	20M	QPSK	50	0	Back	10mm	21100	2535	20.90	21.50	1.148	-0.12	0.331	0.380	0.148	0.170
	LTE Band 7	20M	QPSK	1	0	Left Side	10mm	21100	2535	21.85	22.50	1.161	0	0.001	0.001	0.001	0.001
	LTE Band 7	20M	QPSK	50	0	Left Side	10mm	21100	2535	20.90	21.50	1.148	0	0.001	0.001	0.001	0.001
	LTE Band 7	20M	QPSK	1	0	Right Side	10mm	21100	2535	21.85	22.50	1.161	-0.07	0.104	0.121	0.052	0.060
	LTE Band 7	20M	QPSK	50	0	Right Side	10mm	21100	2535	20.90	21.50	1.148	0.01	0.087	0.100	0.045	0.052
	LTE Band 7	20M	QPSK	1	0	Bottom Side	10mm	21100	2535	21.85	22.50	1.161	-0.08	0.307	0.357	0.148	0.172
	LTE Band 7	20M	QPSK	50	0	Bottom Side	10mm	21100	2535	20.90	21.50	1.148	-0.03	0.258	0.296	0.124	0.142



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 12	10M	QPSK	1	0	Front	10mm	23095	707.5	22.41	24.00	1.442	-0.08	0.066	0.095	0.054	0.078
	LTE Band 12	10M	QPSK	25	0	Front	10mm	23095	707.5	21.38	23.00	1.452	-0.08	0.047	0.068	0.039	0.057
25	LTE Band 12	10M	QPSK	1	0	Back	10mm	23095	707.5	22.41	24.00	1.442	0.08	0.100	0.144	0.061	0.088
	LTE Band 12	10M	QPSK	25	0	Back	10mm	23095	707.5	21.38	23.00	1.452	0.11	0.073	0.106	0.044	0.064
	LTE Band 12	10M	QPSK	1	0	Left Side	10mm	23095	707.5	22.41	24.00	1.442	-0.04	0.038	0.055	0.027	0.039
	LTE Band 12	10M	QPSK	25	0	Left Side	10mm	23095	707.5	21.38	23.00	1.452	0.02	0.028	0.041	0.019	0.028
	LTE Band 12	10M	QPSK	1	0	Right Side	10mm	23095	707.5	22.41	24.00	1.442	0.1	0.023	0.033	0.016	0.023
	LTE Band 12	10M	QPSK	25	0	Right Side	10mm	23095	707.5	21.38	23.00	1.452	0.07	0.017	0.025	0.012	0.017
	LTE Band 12	10M	QPSK	1	0	Bottom Side	10mm	23095	707.5	22.41	24.00	1.442	0.16	0.027	0.039	0.015	0.022
	LTE Band 12	10M	QPSK	25	0	Bottom Side	10mm	23095	707.5	21.38	23.00	1.452	0.11	0.019	0.028	0.011	0.016
	LTE Band 13	10M	QPSK	1	0	Front	10mm	23230	782	23.00	24.00	1.259	-0.04	0.188	0.237	0.147	0.185
	LTE Band 13	10M	QPSK	25	12	Front	10mm	23230	782	21.96	23.00	1.271	-0.03	0.159	0.202	0.125	0.159
26	LTE Band 13	10M	QPSK	1	0	Back	10mm	23230	782	23.00	24.00	1.259	0.13	0.361	0.454	0.204	0.257
	LTE Band 13	10M	QPSK	25	12	Back	10mm	23230	782	21.96	23.00	1.271	0.13	0.310	0.394	0.175	0.222
	LTE Band 13	10M	QPSK	1	0	Left Side	10mm	23230	782	23.00	24.00	1.259	0	0.126	0.159	0.087	0.110
	LTE Band 13	10M	QPSK	25	12	Left Side	10mm	23230	782	21.96	23.00	1.271	-0.06	0.106	0.135	0.073	0.093
	LTE Band 13	10M	QPSK	1	0	Right Side	10mm	23230	782	23.00	24.00	1.259	0.05	0.037	0.047	0.025	0.031
	LTE Band 13	10M	QPSK	25	12	Right Side	10mm	23230	782	21.96	23.00	1.271	0	0.027	0.034	0.018	0.023
	LTE Band 13	10M	QPSK	1	0	Bottom Side	10mm	23230	782	23.00	24.00	1.259	0.13	0.133	0.167	0.075	0.094
	LTE Band 13	10M	QPSK	25	12	Bottom Side	10mm	23230	782	21.96	23.00	1.271	0.11	0.115	0.146	0.065	0.083

<WLAN SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	Note
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	10mm	6	2437	17.81	18.00	1.045	100	1.000	-0.06	0.232	0.242	0.125	0.131	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	10mm	6	2437	17.81	18.00	1.045	100	1.000	0.03	0.305	0.319	0.136	0.142	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	10mm	1	2412	17.73	18.00	1.064	100	1.000	-0.07	0.271	0.288	0.133	0.142	
27	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	10mm	11	2462	17.65	18.00	1.084	100	1.000	-0.08	0.301	0.326	0.138	0.150	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Left Side	10mm	6	2437	17.81	18.00	1.045	100	1.000	-0.14	0.149	0.156	0.074	0.077	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Top Side	10mm	6	2437	17.81	18.00	1.045	100	1.000	0.07	0.181	0.189	0.091	0.095	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	10mm	11	2462	17.56	18.00	1.107	100	1.000	-0.08	0.293	0.324	0.134	0.148	(3)

Note:

- (1). The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same, and the spot check results will compare with original results to found worse case to perform simultaneous transmission analysis.
- (2). The conducted power for spot check was re-measured to ensure that both devices are the same.
- (3). Spot check verification on PY7-PM0954.



**15.3 Product Specific SAR**

**<WLAN SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	Note
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	0	0.176	0.191	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	0.13	0.266	0.289	
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Side	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	0.11	0.026	0.028	
	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	56	5280	13.76	14.00	1.057	97.2	1.029	-0.09	0.286	0.311	
28	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	64	5320	13.73	14.00	1.064	97.2	1.029	0.18	0.313	0.343	
	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	64	5320	13.54	14.00	1.112	97.22	1.029	0.14	0.296	0.339	(3)
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	0.03	0.352	0.385	
29	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	-0.1	0.530	0.580	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	132	5660	13.68	14.00	1.076	97.2	1.029	0.14	0.476	0.527	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	116	5580	13.65	14.00	1.084	97.2	1.029	0.04	0.488	0.544	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	140	5700	13.60	14.00	1.096	97.2	1.029	0.05	0.432	0.487	
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Side	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	-0.03	0.063	0.069	
	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	100	5500	13.73	14.00	1.064	97.2	1.029	0.11	0.440	0.482	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	100	5500	13.56	14.00	1.107	97.22	1.029	0.18	0.482	0.549	(3)
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.06	0.231	0.244	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.1	0.314	0.331	
	WLAN5GHz	OFDM	802.11a 6Mbps	Left Side	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.02	0.048	0.051	
	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.12	0.402	0.424	
	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	149	5745	9.77	10.00	1.054	97.2	1.029	0.05	0.120	0.130	
30	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	157	5785	13.74	14.00	1.062	97.2	1.029	-0.19	0.406	0.444	
	WLAN5GHz	OFDM	802.11a 6Mbps	Top Side	0mm	157	5785	13.68	14.00	1.076	97.22	1.029	0.18	0.380	0.421	(3)

**Note:**

- (1). The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same, and the spot check results will compare with original results to found worse case to perform simultaneous transmission analysis.
- (2). The conducted power for spot check was re-measured to ensure that both devices are the same.
- (3). Spot check verification on PY7-PM0954.



**15.4 Body Worn Accessory SAR**

**<GSM SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GMSK	GPRS (4 Tx slots)	Front	15mm	189	836.4	27.28	29.00	1.486	0	0.172	0.256	0.128	0.190
	GSM850	GMSK	GPRS (4 Tx slots)	Back	15mm	189	836.4	27.28	29.00	1.486	0	0.218	0.324	0.129	0.192
31	GSM850	GMSK	GPRS (4 Tx slots)	Back	15mm	128	824.2	27.24	29.00	1.500	-0.05	0.260	0.390	0.201	0.301
	GSM850	GMSK	GPRS (4 Tx slots)	Back	15mm	251	848.8	27.13	29.00	1.538	0.12	0.243	0.374	0.144	0.221
	GSM1900	GMSK	GPRS (4 Tx slots)	Front	15mm	810	1909.8	24.72	25.00	1.067	-0.17	0.149	0.159	0.087	0.093
	GSM1900	GMSK	GPRS (4 Tx slots)	Back	15mm	810	1909.8	24.72	25.00	1.067	0.11	0.163	0.174	0.093	0.099
	GSM1900	GMSK	GPRS (4 Tx slots)	Back	15mm	661	1880	24.56	25.00	1.107	0.16	0.180	0.199	0.104	0.115
32	GSM1900	GMSK	GPRS (4 Tx slots)	Back	15mm	512	1850.2	24.20	25.00	1.202	0.02	0.203	0.244	0.119	0.143

**<WCDMA SAR>**

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	QPSK	RMC 12.2Kbps	Front	15mm	9538	1907.6	23.96	24.00	1.009	-0.16	0.253	0.255	0.148	0.149
	WCDMA II	QPSK	RMC 12.2Kbps	Back	15mm	9538	1907.6	23.96	24.00	1.009	0.1	0.307	0.310	0.176	0.178
33	WCDMA II	QPSK	RMC 12.2Kbps	Back	15mm	9400	1880	23.82	24.00	1.042	0.16	0.299	0.312	0.171	0.178
	WCDMA II	QPSK	RMC 12.2Kbps	Back	15mm	9262	1852.4	23.78	24.00	1.052	0	0.261	0.275	0.151	0.159
	WCDMA IV	QPSK	RMC 12.2Kbps	Front	15mm	1513	1752.6	22.95	23.00	1.012	-0.12	0.271	0.274	0.164	0.166
34	WCDMA IV	QPSK	RMC 12.2Kbps	Back	15mm	1513	1752.6	22.95	23.00	1.012	-0.04	0.281	0.284	0.169	0.171
	WCDMA IV	QPSK	RMC 12.2Kbps	Back	15mm	1312	1712.4	22.85	23.00	1.035	0.02	0.253	0.262	0.162	0.168
	WCDMA IV	QPSK	RMC 12.2Kbps	Back	15mm	1413	1732.6	22.90	23.00	1.023	0.01	0.269	0.275	0.163	0.167
	WCDMA V	QPSK	RMC 12.2Kbps	Front	15mm	4233	846.6	23.99	24.00	1.002	0.08	0.190	0.190	0.145	0.145
35	WCDMA V	QPSK	RMC 12.2Kbps	Back	15mm	4233	846.6	23.99	24.00	1.002	-0.04	0.261	0.262	0.178	0.178
	WCDMA V	QPSK	RMC 12.2Kbps	Back	15mm	4132	826.4	23.95	24.00	1.012	0.02	0.204	0.206	0.158	0.160
	WCDMA V	QPSK	RMC 12.2Kbps	Back	15mm	4182	836.4	23.96	24.00	1.009	0	0.232	0.234	0.151	0.152



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	15mm	18900	1880	22.92	24.00	1.282	-0.16	0.195	0.250	0.116	0.149
	LTE Band 2	20M	QPSK	50	0	Front	15mm	18900	1880	21.95	23.00	1.274	-0.11	0.163	0.208	0.096	0.122
	LTE Band 2	20M	QPSK	1	0	Back	15mm	18900	1880	22.92	24.00	1.282	0.12	0.210	0.269	0.122	0.156
	LTE Band 2	20M	QPSK	1	0	Back	15mm	18700	1860	22.89	24.00	1.291	0.07	0.198	0.256	0.116	0.150
36	LTE Band 2	20M	QPSK	1	0	Back	15mm	19100	1900	22.90	24.00	1.288	0.17	0.228	0.294	0.131	0.169
	LTE Band 2	20M	QPSK	50	0	Back	15mm	18900	1880	21.95	23.00	1.274	0.11	0.174	0.222	0.101	0.129
	LTE Band 4	20M	QPSK	1	0	Front	15mm	20175	1732.5	21.91	23.00	1.285	-0.02	0.162	0.208	0.099	0.127
	LTE Band 4	20M	QPSK	50	0	Front	15mm	20175	1732.5	20.91	22.00	1.285	-0.06	0.138	0.177	0.084	0.108
37	LTE Band 4	20M	QPSK	1	0	Back	15mm	20175	1732.5	21.91	23.00	1.285	0.01	0.167	0.215	0.099	0.127
	LTE Band 4	20M	QPSK	50	0	Back	15mm	20175	1732.5	20.91	22.00	1.285	0.02	0.143	0.184	0.084	0.108
	LTE Band 5	10M	QPSK	1	0	Front	15mm	20525	836.5	22.63	24.00	1.371	0.01	0.166	0.228	0.128	0.175
	LTE Band 5	10M	QPSK	25	0	Front	15mm	20525	836.5	21.66	23.00	1.361	0.01	0.135	0.184	0.104	0.142
38	LTE Band 5	10M	QPSK	1	0	Back	15mm	20525	836.5	22.63	24.00	1.371	0.07	0.227	0.311	0.134	0.184
	LTE Band 5	10M	QPSK	25	0	Back	15mm	20525	836.5	21.66	23.00	1.361	0.1	0.186	0.253	0.110	0.150
	LTE Band 7	20M	QPSK	1	0	Front	15mm	21100	2535	21.85	22.50	1.161	-0.05	0.121	0.141	0.065	0.075
	LTE Band 7	20M	QPSK	50	0	Front	15mm	21100	2535	20.90	21.50	1.148	-0.08	0.101	0.116	0.054	0.062
	LTE Band 7	20M	QPSK	1	0	Back	15mm	21100	2535	21.85	22.50	1.161	-0.17	0.169	0.196	0.084	0.098
39	LTE Band 7	20M	QPSK	1	0	Back	15mm	20850	2510	21.76	22.50	1.186	-0.17	0.187	0.222	0.093	0.110
	LTE Band 7	20M	QPSK	1	0	Back	15mm	21350	2560	21.84	22.50	1.164	-0.18	0.158	0.184	0.078	0.091
	LTE Band 7	20M	QPSK	50	0	Back	15mm	21100	2535	20.90	21.50	1.148	-0.06	0.140	0.161	0.069	0.079
	LTE Band 12	10M	QPSK	1	0	Front	15mm	23095	707.5	22.41	24.00	1.442	-0.04	0.067	0.097	0.054	0.078
	LTE Band 12	10M	QPSK	25	0	Front	15mm	23095	707.5	21.38	23.00	1.452	-0.04	0.049	0.071	0.040	0.058
40	LTE Band 12	10M	QPSK	1	0	Back	15mm	23095	707.5	22.41	24.00	1.442	-0.04	0.100	0.144	0.081	0.117
	LTE Band 12	10M	QPSK	25	0	Back	15mm	23095	707.5	21.38	23.00	1.452	0.03	0.073	0.106	0.059	0.086
	LTE Band 13	10M	QPSK	1	0	Front	15mm	23230	782	23.00	24.00	1.259	0	0.201	0.253	0.157	0.198
	LTE Band 13	10M	QPSK	25	12	Front	15mm	23230	782	21.96	23.00	1.271	-0.02	0.169	0.215	0.132	0.168
41	LTE Band 13	10M	QPSK	1	0	Back	15mm	23230	782	23.00	24.00	1.259	-0.04	0.269	0.339	0.212	0.267
	LTE Band 13	10M	QPSK	25	12	Back	15mm	23230	782	21.96	23.00	1.271	-0.1	0.219	0.278	0.173	0.220



<WLAN SAR>

Plot No.	Band	Modulation	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	Note
42	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	15mm	6	2437	17.81	18.00	1.045	100	1.000	0.08	0.151	0.158	0.084	0.088	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	15mm	1	2412	17.73	18.00	1.064	100	1.000	0.02	0.125	0.133	0.070	0.074	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	15mm	11	2462	17.65	18.00	1.084	100	1.000	-0.04	0.136	0.147	0.075	0.081	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Back	15mm	6	2437	17.81	18.00	1.045	100	1.000	0.04	0.140	0.146	0.075	0.078	
	WLAN2.4GHz	DSSS	802.11b 1Mbps	Front	15mm	6	2437	17.72	18.00	1.067	100	1.000	0.1	0.118	0.126	0.066	0.070	(3)
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	56	5280	13.76	14.00	1.057	97.2	1.029	-0.12	0.061	0.066	0.024	0.026	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	64	5320	13.73	14.00	1.064	97.2	1.029	0.11	0.065	0.071	0.026	0.028	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	15mm	56	5280	13.76	14.00	1.057	97.2	1.029	0.05	0.024	0.026	0.009	0.010	
43	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	64	5320	13.54	14.00	1.112	97.22	1.029	-0.01	0.068	0.078	0.027	0.031	(3)
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	100	5500	13.73	14.00	1.064	97.2	1.029	-0.04	0.124	0.136	0.048	0.053	
44	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	132	5660	13.68	14.00	1.076	97.2	1.029	0.1	0.182	0.202	0.073	0.081	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	116	5580	13.65	14.00	1.084	97.2	1.029	-0.05	0.153	0.171	0.059	0.066	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	140	5700	13.60	14.00	1.096	97.2	1.029	0.05	0.179	0.202	0.072	0.081	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	15mm	100	5500	13.73	14.00	1.064	97.2	1.029	-0.16	0.036	0.039	0.014	0.015	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	132	5660	13.68	14.00	1.076	97.22	1.029	-0.02	0.167	0.185	0.065	0.072	(3)
45	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.06	0.212	0.224	0.082	0.087	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	157	5785	13.74	14.00	1.062	97.2	1.029	0	0.204	0.223	0.080	0.087	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	149	5745	9.77	10.00	1.054	97.2	1.029	0.04	0.141	0.153	0.054	0.059	
	WLAN5GHz	OFDM	802.11a 6Mbps	Back	15mm	165	5825	13.89	14.00	1.026	97.2	1.029	-0.09	0.052	0.055	0.019	0.020	
	WLAN5GHz	OFDM	802.11a 6Mbps	Front	15mm	165	5825	13.83	14.00	1.040	97.22	1.029	-0.18	0.185	0.198	0.043	0.046	(3)

Note:

- (1). The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same, and the spot check results will compare with original results to found worse case to perform simultaneous transmission analysis.
- (2). The conducted power for spot check was re-measured to ensure that both devices are the same.
- (3). Spot check verification on PY7-PM0954.





15.5 Repeated SAR Measurement

Table with 16 columns: No., Band, Modulation, Mode, Test Position, Gap (mm), Ch., Freq. (MHz), Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Duty Cycle %, Duty Cycle Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Ratio, Reported 1g SAR (W/kg). Rows include WLAN2.4GHz and WLAN5GHz measurements.

General Note:

- 1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥0.8W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR <1.45W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated measured SAR.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.



**16. Simultaneous Transmission Analysis**

NO.	Simultaneous Transmission Configurations	Portable Handset				Note
		Head	Body-worn	Hotspot	Product Specific	
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes	
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes	Hotspot
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes	Hotspot
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes	Hotspot
5.	GSM Voice + Bluetooth		Yes		Yes	
6.	GPRS/EDGE + Bluetooth		Yes		Yes	WWAN VoIP
7.	WCDMA+ Bluetooth		Yes		Yes	WWAN VoIP
8.	LTE + Bluetooth		Yes		Yes	WWAN VoIP
9.	GSM Voice + WLAN5GHz	Yes	Yes		Yes	
10.	GPRS/EDGE + WLAN5GHz	Yes	Yes		Yes	WWAN VoIP
11.	WCDMA + WLAN5GHz	Yes	Yes		Yes	WWAN VoIP
12.	LTE + WLAN5GHz	Yes	Yes		Yes	WWAN VoIP

**General Note:**

- The FCC ID: PY7-PM0952 and FCC ID: PY7-PM0954 due to the WLAN transmitter circuitry/layout and antenna is identical between and tune up power targets are identical for WLAN operations, in this report all the WLAN SAR test results are referred to PY7-PM0952, Sporton Report No: FA620405 and spot checks were performed on PY7-PM0954 to ensure that the SAR measurements for both devices are the same and the spot check results will compare with original results to found worse case to perform simultaneous transmission analysis.
- This device supported VoIP in EGPRS, WCDMA, LTE (e.g. 3rd party VoIP).
- This device 2.4GHz WLAN supports Hotspot and WiFi Direct (GC/GO), and 5GHz WLAN supports WiFi Direct (GC) only.
- The worst case WLAN reported SAR for each configuration was used for SAR summation. Therefore, the following summations represent the absolute worst cases for simultaneous transmission with WLAN.
- WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - Scalar SAR summation < 1.6W/kg.
  - $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
  - If  $SPLSR \leq 0.04$ , simultaneously transmission SAR measurement is not necessary.
  - Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
- For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 based on the formula below.
  - (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm) ·  $[\sqrt{f(\text{GHz})}/x]$  W/kg for test separation distances ≤ 50 mm; where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
  - When the minimum separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
  - 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Bluetooth Max Power	Exposure Position	Body worn
	Test separation	15 mm
7.0 dBm	Estimated 1g SAR (W/kg)	0.07 W/kg



**16.1 Head Exposure Conditions**

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)		
GSM	GSM850	Right Cheek	0.205	1.085	1.077	1.29	1.28
		Right Tilted	0.129	0.845	1.196	0.97	1.33
		Left Cheek	0.269	0.518	0.997	0.79	1.27
		Left Tilted	0.126	0.514	1.141	0.64	1.27
	GSM1900	Right Cheek	0.218	1.085	1.077	1.30	1.30
		Right Tilted	0.038	0.845	1.196	0.88	1.23
		Left Cheek	0.101	0.518	0.997	0.62	1.10
		Left Tilted	0.058	0.514	1.141	0.57	1.20
WCDMA	WCDMA II	Right Cheek	0.254	1.085	1.077	1.34	1.33
		Right Tilted	0.078	0.845	1.196	0.92	1.27
		Left Cheek	0.175	0.518	0.997	0.69	1.17
		Left Tilted	0.107	0.514	1.141	0.62	1.25
	WCDMA IV	Right Cheek	0.273	1.085	1.077	1.36	1.35
		Right Tilted	0.102	0.845	1.196	0.95	1.30
		Left Cheek	0.173	0.518	0.997	0.69	1.17
		Left Tilted	0.071	0.514	1.141	0.59	1.21
	WCDMA V	Right Cheek	0.176	1.085	1.077	1.26	1.25
		Right Tilted	0.113	0.845	1.196	0.96	1.31
		Left Cheek	0.218	0.518	0.997	0.74	1.22
		Left Tilted	0.109	0.514	1.141	0.62	1.25
LTE	LTE Band 2	Right Cheek	0.242	1.085	1.077	1.33	1.32
		Right Tilted	0.063	0.845	1.196	0.91	1.26
		Left Cheek	0.151	0.518	0.997	0.67	1.15
		Left Tilted	0.087	0.514	1.141	0.60	1.23
	LTE Band 4	Right Cheek	0.227	1.085	1.077	1.31	1.30
		Right Tilted	0.120	0.845	1.196	0.97	1.32
		Left Cheek	0.152	0.518	0.997	0.67	1.15
		Left Tilted	0.078	0.514	1.141	0.59	1.22
	LTE Band 5	Right Cheek	0.169	1.085	1.077	1.25	1.25
		Right Tilted	0.045	0.845	1.196	0.89	1.24
		Left Cheek	0.214	0.518	0.997	0.73	1.21
		Left Tilted	0.038	0.514	1.141	0.55	1.18
	LTE Band 7	Right Cheek	0.102	1.085	1.077	1.19	1.18
		Right Tilted	0.070	0.845	1.196	0.92	1.27
		Left Cheek	0.035	0.518	0.997	0.55	1.03
		Left Tilted	0.029	0.514	1.141	0.54	1.17
	LTE Band 12	Right Cheek	0.050	1.085	1.077	1.14	1.13
		Right Tilted	0.008	0.845	1.196	0.85	1.20
		Left Cheek	0.055	0.518	0.997	0.57	1.05
		Left Tilted	0.027	0.514	1.141	0.54	1.17
	LTE Band 13	Right Cheek	0.131	1.085	1.077	1.22	1.21
		Right Tilted	0.084	0.845	1.196	0.93	1.28
		Left Cheek	0.170	0.518	0.997	0.69	1.17
		Left Tilted	0.093	0.514	1.141	0.61	1.23



WWAN Band		Exposure Position	1	2	3	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)
			WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)		
GSM	GSM850	Right Cheek	0.165	0.541	0.281	0.71	0.45
		Right Tilted	0.103	0.403	0.322	0.51	0.43
		Left Cheek	0.209	0.258	0.336	0.47	0.55
		Left Tilted	0.100	0.251	0.348	0.35	0.45
	GSM1900	Right Cheek	0.138	0.541	0.281	0.68	0.42
		Right Tilted	0.025	0.403	0.322	0.43	0.35
		Left Cheek	0.061	0.258	0.336	0.32	0.40
		Left Tilted	0.031	0.251	0.348	0.28	0.38
WCDMA	WCDMA II	Right Cheek	0.160	0.541	0.281	0.70	0.44
		Right Tilted	0.049	0.403	0.322	0.45	0.37
		Left Cheek	0.108	0.258	0.336	0.37	0.44
		Left Tilted	0.060	0.251	0.348	0.31	0.41
	WCDMA IV	Right Cheek	0.179	0.541	0.281	0.72	0.46
		Right Tilted	0.067	0.403	0.322	0.47	0.39
		Left Cheek	0.113	0.258	0.336	0.37	0.45
		Left Tilted	0.042	0.251	0.348	0.29	0.39
	WCDMA V	Right Cheek	0.140	0.541	0.281	0.68	0.42
		Right Tilted	0.089	0.403	0.322	0.49	0.41
		Left Cheek	0.167	0.258	0.336	0.43	0.50
		Left Tilted	0.086	0.251	0.348	0.34	0.43
LTE	LTE Band 2	Right Cheek	0.152	0.541	0.281	0.69	0.43
		Right Tilted	0.038	0.403	0.322	0.44	0.36
		Left Cheek	0.095	0.258	0.336	0.35	0.43
		Left Tilted	0.049	0.251	0.348	0.30	0.40
	LTE Band 4	Right Cheek	0.150	0.541	0.281	0.69	0.43
		Right Tilted	0.078	0.403	0.322	0.48	0.40
		Left Cheek	0.102	0.258	0.336	0.36	0.44
		Left Tilted	0.050	0.251	0.348	0.30	0.40
	LTE Band 5	Right Cheek	0.136	0.541	0.281	0.68	0.42
		Right Tilted	0.036	0.403	0.322	0.44	0.36
		Left Cheek	0.166	0.258	0.336	0.42	0.50
		Left Tilted	0.030	0.251	0.348	0.28	0.38
	LTE Band 7	Right Cheek	0.055	0.541	0.281	0.60	0.34
		Right Tilted	0.041	0.403	0.322	0.44	0.36
		Left Cheek	0.016	0.258	0.336	0.27	0.35
		Left Tilted	0.012	0.251	0.348	0.26	0.36
	LTE Band 12	Right Cheek	0.043	0.541	0.281	0.58	0.32
		Right Tilted	0.007	0.403	0.322	0.41	0.33
		Left Cheek	0.046	0.258	0.336	0.30	0.38
		Left Tilted	0.025	0.251	0.348	0.28	0.37
LTE Band 13	Right Cheek	0.108	0.541	0.281	0.65	0.39	
	Right Tilted	0.069	0.403	0.322	0.47	0.39	
	Left Cheek	0.135	0.258	0.336	0.39	0.47	
	Left Tilted	0.077	0.251	0.348	0.33	0.43	



**16.2 Hotspot Exposure Conditions**

WWAN Band		Exposure Position	1	2	1+2 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	
GSM	GSM850	Front	0.273	0.242	0.52
		Back	0.848	0.326	1.17
		Left side	0.461	0.156	0.62
		Right side	0.204		0.20
		Top side		0.189	0.19
	Bottom side	0.309		0.31	
	GSM1900	Front	0.327	0.242	0.57
		Back	0.536	0.326	0.86
		Left side	0.028	0.156	0.18
		Right side	0.202		0.20
Top side			0.189	0.19	
Bottom side	0.188		0.19		
WCDMA	WCDMA II	Front	0.546	0.242	0.79
		Back	0.649	0.326	0.98
		Left side	0.038	0.156	0.19
		Right side	0.366		0.37
		Top side		0.189	0.19
	Bottom side	0.258		0.26	
	WCDMA IV	Front	0.548	0.242	0.79
		Back	0.576	0.326	0.90
		Left side	0.182	0.156	0.34
		Right side	0.500		0.50
		Top side		0.189	0.19
	Bottom side	0.555		0.56	
	WCDMA V	Front	0.207	0.242	0.45
		Back	0.571	0.326	0.90
		Left side	0.359	0.156	0.52
Right side		0.159		0.16	
Top side			0.189	0.19	
Bottom side	0.269		0.27		
LTE	LTE Band 2	Front	0.521	0.242	0.76
		Back	0.672	0.326	1.00
		Left side	0.058	0.156	0.21
		Right side	0.355		0.36
		Top side		0.189	0.19
	Bottom side	0.355		0.36	
	LTE Band 4	Front	0.431	0.242	0.67
		Back	0.479	0.326	0.81
		Left side	0.222	0.156	0.38
		Right side	0.432		0.43
		Top side		0.189	0.19
	Bottom side	0.517		0.52	
	LTE Band 5	Front	0.263	0.242	0.51
		Back	0.770	0.326	1.10
		Left side	0.404	0.156	0.56
		Right side	0.163		0.16
		Top side		0.189	0.19
	Bottom side	0.314		0.31	
	LTE Band 7	Front	0.257	0.242	0.50
		Back	0.518	0.326	0.84
		Left side	0.001	0.156	0.16
		Right side	0.121		0.12
		Top side		0.189	0.19
	Bottom side	0.357		0.36	
LTE Band 12	Front	0.095	0.242	0.34	
	Back	0.144	0.326	0.47	
	Left side	0.055	0.156	0.21	
	Right side	0.033		0.03	
	Top side		0.189	0.19	
Bottom side	0.039		0.04		
LTE Band 13	Front	0.237	0.242	0.48	
	Back	0.454	0.326	0.78	
	Left side	0.159	0.156	0.32	
	Right side	0.047		0.05	
	Top side		0.189	0.19	
Bottom side	0.167		0.17		



WWAN Band		Exposure Position	1	2	1+2 Summed 10g SAR (W/kg)
			WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	
GSM	GSM850	Front	0.210	0.131	0.34
		Back	0.472	0.150	0.62
		Left side	0.314	0.077	0.39
		Right side	0.138		0.14
		Top side		0.095	0.10
		Bottom side	0.180		0.18
	GSM1900	Front	0.185	0.131	0.32
		Back	0.297	0.150	0.45
		Left side	0.013	0.077	0.09
		Right side	0.114		0.11
	Top side		0.095	0.10	
	Bottom side	0.107		0.11	
WCDMA	WCDMA II	Front	0.311	0.131	0.44
		Back	0.353	0.150	0.50
		Left side	0.022	0.077	0.10
		Right side	0.212		0.21
		Top side		0.095	0.10
		Bottom side	0.146		0.15
	WCDMA IV	Front	0.329	0.131	0.46
		Back	0.339	0.150	0.49
		Left side	0.110	0.077	0.19
		Right side	0.293		0.29
		Top side		0.095	0.10
		Bottom side	0.327		0.33
	WCDMA V	Front	0.130	0.131	0.26
		Back	0.321	0.150	0.47
		Left side	0.244	0.077	0.32
		Right side	0.107		0.11
		Top side		0.095	0.10
		Bottom side	0.155		0.16
LTE	LTE Band 2	Front	0.298	0.131	0.43
		Back	0.365	0.150	0.52
		Left side	0.033	0.077	0.11
		Right side	0.205		0.21
		Top side		0.095	0.10
		Bottom side	0.200		0.20
	LTE Band 4	Front	0.257	0.131	0.39
		Back	0.278	0.150	0.43
		Left side	0.135	0.077	0.21
		Right side	0.254		0.25
		Top side		0.095	0.10
		Bottom side	0.305		0.31
	LTE Band 5	Front	0.162	0.131	0.29
		Back	0.428	0.150	0.58
		Left side	0.277	0.077	0.35
		Right side	0.111		0.11
		Top side		0.095	0.10
		Bottom side	0.180		0.18
	LTE Band 7	Front	0.136	0.131	0.27
		Back	0.236	0.150	0.39
		Left side	0.001	0.077	0.08
		Right side	0.060		0.06
		Top side		0.095	0.10
		Bottom side	0.172		0.17
	LTE Band 12	Front	0.078	0.131	0.21
		Back	0.088	0.150	0.24
		Left side	0.039	0.077	0.12
		Right side	0.023		0.02
		Top side		0.095	0.10
		Bottom side	0.022		0.02
LTE Band 13	Front	0.185	0.131	0.32	
	Back	0.257	0.150	0.41	
	Left side	0.110	0.077	0.19	
	Right side	0.031		0.03	
	Top side		0.095	0.10	
	Bottom side	0.094		0.09	

**16.3 Product Specific Exposure Conditions**

Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
	WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)	Bluetooth Estimated 10g SAR (W/kg)			
Product Specific	-	-	0.580	-	-	<b>0.58</b>	-

**Remark:**

1. According to KDB 648474 D04v01r03, for WWAN / 2.4GHz WLAN hand SAR (“-“) was excluded, due to 1-g reported SAR was < 1.2W/kg.

**16.4 Body-Worn Accessory Exposure Conditions**

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth Estimated 1g SAR (W/kg)			
GSM	GSM850	Front	0.256	0.158	0.224	0.070	<b>0.41</b>	<b>0.48</b>	<b>0.33</b>
		Back	0.390	0.146	0.055	0.070	<b>0.54</b>	<b>0.45</b>	<b>0.46</b>
	GSM1900	Front	0.159	0.158	0.224	0.070	<b>0.32</b>	<b>0.38</b>	<b>0.23</b>
		Back	0.244	0.146	0.055	0.070	<b>0.39</b>	<b>0.30</b>	<b>0.31</b>
WCDMA	WCDMA II	Front	0.255	0.158	0.224	0.070	<b>0.41</b>	<b>0.48</b>	<b>0.33</b>
		Back	0.312	0.146	0.055	0.070	<b>0.46</b>	<b>0.37</b>	<b>0.38</b>
	WCDMA IV	Front	0.274	0.158	0.224	0.070	<b>0.43</b>	<b>0.50</b>	<b>0.34</b>
		Back	0.284	0.146	0.055	0.070	<b>0.43</b>	<b>0.34</b>	<b>0.35</b>
	WCDMA V	Front	0.190	0.158	0.224	0.070	<b>0.35</b>	<b>0.41</b>	<b>0.26</b>
		Back	0.262	0.146	0.055	0.070	<b>0.41</b>	<b>0.32</b>	<b>0.33</b>
LTE	LTE Band 2	Front	0.250	0.158	0.224	0.070	<b>0.41</b>	<b>0.47</b>	<b>0.32</b>
		Back	0.294	0.146	0.055	0.070	<b>0.44</b>	<b>0.35</b>	<b>0.36</b>
	LTE Band 4	Front	0.208	0.158	0.224	0.070	<b>0.37</b>	<b>0.43</b>	<b>0.28</b>
		Back	0.215	0.146	0.055	0.070	<b>0.36</b>	<b>0.27</b>	<b>0.29</b>
	LTE Band 5	Front	0.228	0.158	0.224	0.070	<b>0.39</b>	<b>0.45</b>	<b>0.30</b>
		Back	0.311	0.146	0.055	0.070	<b>0.46</b>	<b>0.37</b>	<b>0.38</b>
	LTE Band 7	Front	0.141	0.158	0.224	0.070	<b>0.30</b>	<b>0.37</b>	<b>0.21</b>
		Back	0.222	0.146	0.055	0.070	<b>0.37</b>	<b>0.28</b>	<b>0.29</b>
	LTE Band 12	Front	0.097	0.158	0.224	0.070	<b>0.26</b>	<b>0.32</b>	<b>0.17</b>
		Back	0.144	0.146	0.055	0.070	<b>0.29</b>	<b>0.20</b>	<b>0.21</b>
	LTE Band 13	Front	0.253	0.158	0.224	0.070	<b>0.41</b>	<b>0.48</b>	<b>0.32</b>
		Back	0.339	0.146	0.055	0.070	<b>0.49</b>	<b>0.39</b>	<b>0.41</b>



WWAN Band		Exposure Position	1	2	3	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)
			WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)		
GSM	GSM850	Front	0.190	0.088	0.087	<b>0.28</b>	<b>0.28</b>
		Back	0.301	0.078	0.020	<b>0.38</b>	<b>0.32</b>
	GSM1900	Front	0.093	0.088	0.087	<b>0.18</b>	<b>0.18</b>
		Back	0.143	0.078	0.020	<b>0.22</b>	<b>0.16</b>
WCDMA	WCDMA II	Front	0.149	0.088	0.087	<b>0.24</b>	<b>0.24</b>
		Back	0.178	0.078	0.020	<b>0.26</b>	<b>0.20</b>
	WCDMA IV	Front	0.166	0.088	0.087	<b>0.25</b>	<b>0.25</b>
		Back	0.171	0.078	0.020	<b>0.25</b>	<b>0.19</b>
	WCDMA V	Front	0.145	0.088	0.087	<b>0.23</b>	<b>0.23</b>
		Back	0.178	0.078	0.020	<b>0.26</b>	<b>0.20</b>
LTE	LTE Band 2	Front	0.149	0.088	0.087	<b>0.24</b>	<b>0.24</b>
		Back	0.169	0.078	0.020	<b>0.25</b>	<b>0.19</b>
	LTE Band 4	Front	0.127	0.088	0.087	<b>0.22</b>	<b>0.21</b>
		Back	0.127	0.078	0.020	<b>0.21</b>	<b>0.15</b>
	LTE Band 5	Front	0.175	0.088	0.087	<b>0.26</b>	<b>0.26</b>
		Back	0.184	0.078	0.020	<b>0.26</b>	<b>0.20</b>
	LTE Band 7	Front	0.075	0.088	0.087	<b>0.16</b>	<b>0.16</b>
		Back	0.110	0.078	0.020	<b>0.19</b>	<b>0.13</b>
	LTE Band 12	Front	0.078	0.088	0.087	<b>0.17</b>	<b>0.17</b>
		Back	0.117	0.078	0.020	<b>0.20</b>	<b>0.14</b>
	LTE Band 13	Front	0.198	0.088	0.087	<b>0.29</b>	<b>0.29</b>
		Back	0.267	0.078	0.020	<b>0.35</b>	<b>0.29</b>

**Test Engineer :** Bevis Chang Tommy Chen Poa Pan and Lawrence Chen

## **17. Uncertainty Assessment**

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture’s specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

<b>Uncertainty Distributions</b>	<b>Normal</b>	<b>Rectangular</b>	<b>Triangular</b>	<b>U-Shape</b>
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $\kappa$  is the coverage factor

**Table 17.1. Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual “root-sum-squares” (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.





Error Description	Uncertainty Value (±%)	Probability	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g) (±%)	Standard Uncertainty (10g) (±%)
<b>Measurement System</b>							
Probe Calibration	6.0	N	1	1	1	6.0	6.0
Axial Isotropy	4.7	R	1.732	0.7	0.7	1.9	1.9
Hemispherical Isotropy	9.6	R	1.732	0.7	0.7	3.9	3.9
Boundary Effects	1.0	R	1.732	1	1	0.6	0.6
Linearity	4.7	R	1.732	1	1	2.7	2.7
System Detection Limits	1.0	R	1.732	1	1	0.6	0.6
Modulation Response	3.2	R	1.732	1	1	1.8	1.8
Readout Electronics	0.3	N	1	1	1	0.3	0.3
Response Time	0.0	R	1.732	1	1	0.0	0.0
Integration Time	2.6	R	1.732	1	1	1.5	1.5
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7
Probe Positioner	0.4	R	1.732	1	1	0.2	0.2
Probe Positioning	2.9	R	1.732	1	1	1.7	1.7
Max. SAR Eval.	2.0	R	1.732	1	1	1.2	1.2
<b>Test Sample Related</b>							
Device Positioning	3.0	N	1	1	1	3.0	3.0
Device Holder	3.6	N	1	1	1	3.6	3.6
Power Drift	5.0	R	1.732	1	1	2.9	2.9
Power Scaling	0.0	R	1.732	1	1	0.0	0.0
<b>Phantom and Setup</b>							
Phantom Uncertainty	6.1	R	1.732	1	1	3.5	3.5
SAR correction	0.0	R	1.732	1	0.84	0.0	0.0
Liquid Conductivity Repeatability	0.2	N	1	0.78	0.71	0.1	0.1
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0
Liquid Conductivity (mea.)	2.5	R	1.732	0.78	0.71	1.1	1.0
Temp. unc. - Conductivity	3.4	R	1.732	0.78	0.71	1.5	1.4
Liquid Permittivity Repeatability	0.15	N	1	0.23	0.26	0.0	0.0
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8
Liquid Permittivity (mea.)	2.5	R	1.732	0.23	0.26	0.3	0.4
Temp. unc. - Permittivity	0.83	R	1.732	0.23	0.26	0.1	0.1
<b>Combined Std. Uncertainty</b>						11.4%	11.4%
<b>Coverage Factor for 95 %</b>						K=2	K=2
<b>Expanded STD Uncertainty</b>						22.9%	22.7%

Table 17.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz



Error Description	Uncertainty Value (±%)	Probability	Divisor	(Ci) 1g	(Ci) 10g	Standard Uncertainty (1g) (±%)	Standard Uncertainty (10g) (±%)
<b>Measurement System</b>							
Probe Calibration	7.0	N	1	1	1	7.0	7.0
Axial Isotropy	4.7	R	1.732	0.7	0.7	1.9	1.9
Hemispherical Isotropy	9.6	R	1.732	0.7	0.7	3.9	3.9
Boundary Effects	2.0	R	1.732	1	1	1.2	1.2
Linearity	4.7	R	1.732	1	1	2.7	2.7
System Detection Limits	1.0	R	1.732	1	1	0.6	0.6
Modulation Response	3.2	R	1.732	1	1	1.8	1.8
Readout Electronics	0.3	N	1	1	1	0.3	0.3
Response Time	0.0	R	1.732	1	1	0.0	0.0
Integration Time	2.6	R	1.732	1	1	1.5	1.5
RF Ambient Noise	3.0	R	1.732	1	1	1.7	1.7
RF Ambient Reflections	3.0	R	1.732	1	1	1.7	1.7
Probe Positioner	0.4	R	1.732	1	1	0.2	0.2
Probe Positioning	6.7	R	1.732	1	1	3.9	3.9
Max. SAR Eval.	4.0	R	1.732	1	1	2.3	2.3
<b>Test Sample Related</b>							
Device Positioning	3.0	N	1	1	1	3.0	3.0
Device Holder	3.6	N	1	1	1	3.6	3.6
Power Drift	5.0	R	1.732	1	1	2.9	2.9
Power Scaling	0.0	R	1.732	1	1	0.0	0.0
<b>Phantom and Setup</b>							
Phantom Uncertainty	6.6	R	1.732	1	1	3.8	3.8
SAR correction	0.0	R	1.732	1	0.84	0.0	0.0
Liquid Conductivity Repeatability	0.2	N	1	0.78	0.71	0.1	0.1
Liquid Conductivity (target)	5.0	R	1.732	0.78	0.71	2.3	2.0
Liquid Conductivity (mea.)	2.5	R	1.732	0.78	0.71	1.1	1.0
Temp. unc. - Conductivity	3.4	R	1.732	0.78	0.71	1.5	1.4
Liquid Permittivity Repeatability	0.15	N	1	0.23	0.26	0.0	0.0
Liquid Permittivity (target)	5.0	R	1.732	0.23	0.26	0.7	0.8
Liquid Permittivity (mea.)	2.5	R	1.732	0.23	0.26	0.3	0.4
Temp. unc. - Permittivity	0.83	R	1.732	0.23	0.26	0.1	0.1
<b>Combined Std. Uncertainty</b>						12.8%	12.7%
<b>Coverage Factor for 95 %</b>						K=2	K=2
<b>Expanded STD Uncertainty</b>						25.5%	25.4%

**Table 17.3. Uncertainty Budget for frequency range 3 GHz to 6 GHz**

## **18. References**

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992
- [3] IEEE Std. 1528-2013, “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, “SAR Guidance for IEEE 802.11 (WiFi) Transmitters”, Oct 2015.
- [6] FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 2015
- [7] FCC KDB 648474 D04 v01r03, “SAR Evaluation Considerations for Wireless Handsets”, Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, “3G SAR MEAUREMENT PROCEDURES”, Oct 2015
- [9] FCC KDB 941225 D05 v02r05, “SAR Evaluation Considerations for LTE Devices”, Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations” Oct 2015.