

Public

Prepared (also subject responsible if other)

LD/SEM/BGUU Magnus Nilsson

Approved

LD/SEM/BGUU (Magnus Nilsson)

Checked

ecsnlnl

No.

151 86-SVV 107 057/4 Uen

Date

2003-10-28

Rev

A

Reference

Approved according to: 000 21 – LXE 107 42/1

Type 1022101-BV.

Label

The label used for marking is defined in the Manufacturing Specification on the SVF 930 808.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88) for the KRH.

Print layout

Sony Ericsson stylized name	Model Name	"DPY" number R-state
Type number	G – H field	
Production week	KRC number	
Country approval mark 1	R-state	
Country approval mark 2	Repair week	
IMEI-numbers as barcode	CDA number	
IMEI-numbers as characters		
Serial number as barcode		
Serial number as characters		
Marking of origin	Additional Field	

Print sample



Definitions:

Sony Ericsson trademark

Sony Ericsson and the Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347.

Additional field

The field shall be left blank unless otherwise stated in a separate 151 86 document for the SVV.



Prepared (also subject responsible if other)

LD/SEM/BGUU Magnus Nilsson

Approved

LD/SEM/BGUU (Magnus Nilsson)

No.

151 86-SVV 107 057/4 Uen

Checked

Date

Rev

Reference

ecsnlnl

2003-10-28

A

Type number	The type number is 1022101-BV and shall be printed "Type 1022101-BV"
G-field	R-state identification of the CXC-module according to the Marking data 1/151 86 for the SVV.
H-field	R-state identification of the hardware according to the Marking data 1/151 86 for the SVV.
Country approval mark 1	Consist of text: FCC ID: PY71022101 Within a frame with height > 1,5 mm.
CDA number	The number of the CDA file loaded including the R-state of the file.
Country approval mark 2	Consist of text: IC:4170B-1022101
Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)
Production week	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.
IMEI number as bar code	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no-).
IMEI number as characters	The IMEI number has format: TAC-SNR-CD TAC = TBD (New TAC is coming) Example: 01021900-000000-0 SNR = A serial number from 000 000 to 999 999 CD = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Serial number as bar code	According to Ericsson corporate standard 102 01 - 109.
Serial number as characters	According to Ericsson group standard 0012-101. Ericsson group factory number system according the Ericsson corporate standard 1120-101 Factory codes: Beijing CB5 Dashi TP7 Yingko Factory TP8 Flex, Mexico TF5 Flex, Brazil SOR 1. The notified body number according to the TTE Annex III certificate for the production plant. If this is not available, use the notified body number from the type approval certificate



Public

Prepared (also subject responsible if other)

LD/SEM/BGUU Magnus Nilsson

Approved

LD/SEM/BGUU (Magnus Nilsson)

Checked

ecsnln

No.

151 86-SVV 107 057/4 Uen

Date

2003-10-28

Rev

A

Reference

(normally 0682). The print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.

2. According to 1424 - SVF 930 196

The model name T106¹⁹⁰⁰

The field shall be left blank unless otherwise stated in a separate 2/151 86-SVV document.

The DPY number for the product without DPY 101 e.g. if you are producing DPY 101 2595/2 the printing should be 2595/2.

Model name

Marking of origin

“DPY” number

R-state

The R-state for the DPY according to the 1095 for the DPY.

Print regulations

The printing shall be well readable and permanent.

Typeface	OCR-B
Type size	min 1.1 mm
Line spacing	min 1.5 mm
Trademark	min 1.5 mm
Approval marks	min 5.0 mm

