

Prepared (also subject responsible if other)

ESM/PU3 Erik Lehman

Approved

ESM/PU3 (Erik Lehman)

Checked

 Limited Internal
 MARKING DRAWING

No.

151 86 – SVV 107 019/1 Uen

Date

Rev

Reference

2002-07-03

PB1

HANDHELD PHONE
T200 Standard

Approved according to: 000 21 – LXE 107 42/1

Type 1130501-BV.

Label

The label used for marking is defined in the Manufacturing Specification 131 32 for the DPY.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88) for the KRH.

Print layout

Company Name	Additional Field	Model Name Marking of Origin
IMEI-numbers as barcode		
IMEI-numbers as characters		
Approval Mark (1)	<input type="text"/>	Approval Mark (2)
Serial number as barcode		
Serial number as characters		Repair Week
Type number	G – H – field	Support Indicator
FCC number		IC number
KRH number		
CDA number		
Production week		

Definitions:

Company name

Sony Ericsson and Sony Ericsson Mobile Communications AB according to the corporate standard 190 89-EN/LZT 108 5347 Uen

Approval marks

1. According to 1424 - SVF 930 52
2. The notified body number according to the TTE Annex III certificate for the production plant. If this is not available, use the notified body number from the type approval certificate (normally 0682). The

Prepared (also subject responsible if other)

ESM/PU3 Erik Lehman

Approved

ESM/PU3 (Erik Lehman)

Checked

Limited Internal
MARKING DRAWING

No.

151 86 – SVV 107 019/1 Uen

Date

Rev

Reference

2002-07-03

PB1

HANDHELD PHONE

T200 Standard

print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.

Model name	The product name should be T200
IMEI number as bar code	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -).
IMEI number as characters	The IMEI number has format: TAC-FAC-SNR-CD TAC = 1) 350403 2) 350404 3) 350405 FAC = 82 for the GVC factory FAC = 62 for the Beijing factory FAC = 45 for Hungary factory FAC = 71 for Shah Alam factory FAC = 61 for Linköping factory SNR = A serial number from 000 000 to 999 999 CD = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Serial number as barcode	According to Ericsson Corporate Standard 102 01 – 109
Serial number as characters	According to Ericsson Group Standard 0012 – 101. Ericsson Group factory number system according to the Ericsson Corporate Standard 1120 – 101. Factory codes: GVC TV4 Beijing CB5 Hungary TZ4 Shah Alam BD3
KRH number	The KRH number for the product.
CDA number	The CDA number for the product.
Support Indicator	Normally BLANK unless Full Support is requested when marking FS is required.
Production week	The production week shall be given as yyWww (yy = year, ww = week)
Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be

Prepared (also subject responsible if other)

ESM/PU3 Erik Lehman

Approved

ESM/PU3 (Erik Lehman)

Checked

Limited Internal
MARKING DRAWING

No.

151 86 – SVV 107 019/1 Uen

Date

Rev

Reference

2002-07-03

PB1

HANDHELD PHONE

T200 Standard

given as Ryww

(R = repair, y = year, ww = week)

FCC number	The FCC number is PY71130501 and shall be printed "FCC ID: PY71130501"
IC number	Shall be printed "IC: 4170B-1130501"
Type number	The type number is 1130501-BV and shall be printed "Type 1130501-BV"
G-field	R-state identification of the CXC-module according to the Marking data 1/151 86 for the SVV. (The Signaling Software)
H-field	R-state identification of the hardware according to the Marking data 1/151 86 for the SVV.
Additional field	The field shall be left blank unless otherwise stated in a separate 3/151 86- document for the SVV.
Marking of origin	Described in a separate document 2/151 86-SVV.

Print regulations

The printing shall be well readable and permanent.

Typeface	Triumvirate
Type size	min 1.1 mm
Line spacing	min 1.0 mm
Trademark	min 2.25 mm
Approval marks	min 5.0 mm