



FCC RADIO TEST REPORT

FCC ID : PY7-26817E
Equipment : GSM/WCDMA/LTE Phone with BT, DTS/UNII
a/b/g/n/ac, GPS and NFC
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 25, 2019 and testing was started from May 29, 2019 and completed on Jun. 21, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	9
3 Test Result	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	31
3.6 AC Conducted Emission Measurement.....	35
3.7 Antenna Requirements.....	37
4 List of Measuring Equipment.....	38
5 Uncertainty of Evaluation.....	40
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR932517-01C	01	Initial issue of report	Jun. 26, 2019
FR932517-01C	02	Revising applicable standard.	Jul. 03, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 3.16 dB at 2483.680 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 13.57 dB at 0.159 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Yimin Ho

1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac, NFC, and GNSS.

Standards-related Product Specification	
Antenna Type / Gain	Inverted-F Antenna with gain -3.3 dBi

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.96	BH9300YGGP	RF conducted measurement
		BH9300BJGP	Radiated Spurious Emission
		BH9300ZHGP	AC Conducted Emission

Accessory List	
AC Adapter	Model Name : UCH20
	S/N: 1116W37712433
Earphone	Model Name.: STH40D
	S/N : N/A
USB Cable	Model Name.: UCB20
	S/N : N/A

Note:

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report. .
3. For other wireless features of this EUT, test report will be issued separately.
4. The firmware installed in the EUT during testing was 0_30089_A_69_7_IETS-5102.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH15-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + MP3 + USB Cable (Charging from Adapter) + Battery + Earphone

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony	SBH82D	PY7-RD0010	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “Tera Term” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Howard Lin	Temperature :	21~25°C
		Relative Humidity :	51~54%


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Channel Plot

Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	12
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	13
-------------	---------	----------------	----


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 19 JUN 2019 11:31:09

Channel Plot




Date: 21 JUN 2019 08:12:32

Spurious Emission 30MHz~3GHz



Date: 21 JUN 2019 08:14:04

Spurious Emission 2GHz~25GHz




Date: 21 JUN 2019 08:14:18




Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Channel Plot

Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	12
-------------	---------	----------------	----





Test Mode :	802.11g	Test Channel :	13
-------------	---------	----------------	----







Test Mode : 802.11n HT20

Test Channel : 01


100kHz PSD reference Level




Channel Plot




Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz









Test Mode : 802.11n HT20

Test Channel : 11


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT20	Test Channel :	12
-------------	--------------	----------------	----







Test Mode : 802.11n HT20

Test Channel : 13


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	DTM-303A	TP157075	N/A	Nov. 05, 2018	May 29, 2019~ Jun. 21, 2019	Nov. 04, 2019	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SN O10	10MHz~6GHz	Dec. 19, 2018	May 29, 2019~ Jun. 21, 2019	Dec. 18, 2019	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	May 29, 2019~ Jun. 21, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1208382	N/A	Mar. 27, 2019	May 29, 2019~ Jun. 21, 2019	Mar. 26, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 13, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jun. 13, 2019	Nov. 11, 2019	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 19, 2019	Jun. 13, 2019	Mar. 18, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jun. 13, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Jun. 13, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 13, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jun. 13, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jun. 13, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Jun. 13, 2019~ Jun. 19, 2019	Jan. 06, 2020	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D& 00800N1D0 1N-06	41912&05	30MHz to 1GHz	Feb. 12, 2019	Jun. 13, 2019~ Jun. 19, 2019	Feb. 11, 2020	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-1620	1G~18GHz	Oct. 17, 2018	Jun. 13, 2019~ Jun. 19, 2019	Oct. 16, 2019	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA91705 84	18GHz- 40GHz	Dec. 05, 2018	Jun. 13, 2019~ Jun. 19, 2019	Dec. 04, 2019	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 28, 2018	Jun. 13, 2019~ Jun. 19, 2019	Dec. 27, 2019	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JAP0010180 0-30-10P	1601185500 04	1GHz~18GHz	Apr. 16, 2019	Jun. 13, 2019~ Jun. 19, 2019	Apr. 15, 2020	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY5327019 5	1GHz~26.5GHz	Aug. 23, 2018	Jun. 13, 2019~ Jun. 19, 2019	Aug. 22, 2019	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Jun. 13, 2019~ Jun. 19, 2019	Dec. 05, 2019	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY5413008 5	20Hz ~ 8.4GHz	Nov. 01, 2018	Jun. 13, 2019~ Jun. 19, 2019	Oct. 31, 2019	Radiation (03CH15-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECEPEL	DTM-302	SN1	N/A	Jul. 22, 2018	Jun. 13, 2019~ Jun. 19, 2019	Jul. 21, 2019	Radiation (03CH15-HY)
Filter	Wainwright	WLK4-1000- 1530-8000-4 0SS	SN11	1G Low Pass	Sep. 16, 2018	Jun. 13, 2019~ Jun. 19, 2019	Sep. 15, 2019	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12-27 00-3000-180 00-60ST	SN1	3 GHz Highpass	Sep. 16, 2018	Jun. 13, 2019~ Jun. 19, 2019	Sep. 15, 2019	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36980/4	30M-18G	Apr. 15, 2019	Jun. 13, 2019~ Jun. 19, 2019	Apr. 14, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9838/4	30M-18G	Apr. 15, 2019	Jun. 13, 2019~ Jun. 19, 2019	Apr. 14, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY802430/4	30M~18GHz	May 13, 2019	Jun. 13, 2019~ Jun. 19, 2019	May 12, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Jun. 13, 2019~ Jun. 19, 2019	Mar. 12, 2020	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	Jun. 13, 2019~ Jun. 19, 2019	Mar. 12, 2020	Radiation (03CH15-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Jun. 13, 2019~ Jun. 19, 2019	N/A	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jun. 13, 2019~ Jun. 19, 2019	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jun. 13, 2019~ Jun. 19, 2019	N/A	Radiation (03CH15-HY)
Software	Audix	E3 6.2009-8-24(k5)	RK-000451	N/A	N/A	Jun. 13, 2019~ Jun. 19, 2019	N/A	Radiation (03CH15-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.20
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
---	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Howard Lin	Temperature:	21~25	°C
Test Date:	2019/5/29~2019/6/21	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	12.69	-	7.05	-	0.50	Pass
11b	1Mbps	1	6	2437	12.79	-	7.55	-	0.50	Pass
11b	1Mbps	1	11	2462	12.74	-	7.07	-	0.50	Pass
11b	1Mbps	1	12	2467	12.79	-	7.53	-	0.50	Pass
11b	1Mbps	1	13	2472	12.74	-	7.53	-	0.50	Pass
11g	6Mbps	1	1	2412	16.58	-	13.87	-	0.50	Pass
11g	6Mbps	1	6	2437	16.58	-	15.09	-	0.50	Pass
11g	6Mbps	1	11	2462	16.58	-	13.83	-	0.50	Pass
11g	6Mbps	1	12	2467	16.48	-	15.03	-	0.50	Pass
11g	6Mbps	1	13	2472	16.98	-	15.07	-	0.50	Pass
HT20	MCS0	1	1	2412	17.63	-	15.05	-	0.50	Pass
HT20	MCS0	1	6	2437	17.63	-	15.03	-	0.50	Pass
HT20	MCS0	1	11	2462	17.58	-	15.09	-	0.50	Pass
HT20	MCS0	1	12	2467	17.63	-	15.33	-	0.50	Pass
HT20	MCS0	1	13	2472	17.93	-	14.13	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	15.00	-	-	30.00	-	-3.30	-	11.70	-	36.00	-	Pass
11b	1Mbps	1	6	2437	14.90	-		30.00	-	-3.30	-	11.60	-	36.00	-	Pass
11b	1Mbps	1	11	2462	14.90	-		30.00	-	-3.30	-	11.60	-	36.00	-	Pass
11b	1Mbps	1	12	2467	15.10	-		30.00	-	-3.30	-	11.80	-	36.00	-	Pass
11b	1Mbps	1	13	2472	15.00	-		30.00	-	-3.30	-	11.70	-	36.00	-	Pass
11g	6Mbps	1	1	2412	15.10	-		30.00	-	-3.30	-	11.80	-	36.00	-	Pass
11g	6Mbps	1	6	2437	15.20	-		30.00	-	-3.30	-	11.90	-	36.00	-	Pass
11g	6Mbps	1	11	2462	14.90	-		30.00	-	-3.30	-	11.60	-	36.00	-	Pass
11g	6Mbps	1	12	2467	10.70	-		30.00	-	-3.30	-	7.40	-	36.00	-	Pass
11g	6Mbps	1	13	2472	-2.60	-		30.00	-	-3.30	-	-5.90	-	36.00	-	Pass
HT20	MCS0	1	1	2412	15.20	-		30.00	-	-3.30	-	11.90	-	36.00	-	Pass
HT20	MCS0	1	6	2437	15.10	-		30.00	-	-3.30	-	11.80	-	36.00	-	Pass
HT20	MCS0	1	11	2462	15.10	-		30.00	-	-3.30	-	11.80	-	36.00	-	Pass
HT20	MCS0	1	12	2467	6.80	-		30.00	-	-3.30	-	3.50	-	36.00	-	Pass
HT20	MCS0	1	13	2472	-2.60	-		30.00	-	-3.30	-	-5.90	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-7.43	-	-	-3.30	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-7.23	-	-	-3.30	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-7.33	-	-	-3.30	-	8.00	-	Pass
11b	1Mbps	1	12	2467	-6.97	-	-	-3.30	-	8.00	-	Pass
11b	1Mbps	1	13	2472	-7.61	-	-	-3.30	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-9.98	-	-	-3.30	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-8.60	-	-	-3.30	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-10.09	-	-	-3.30	-	8.00	-	Pass
11g	6Mbps	1	12	2467	-14.56	-	-	-3.30	-	8.00	-	Pass
11g	6Mbps	1	13	2472	-28.91	-	-	-3.30	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-9.74	-	-	-3.30	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-10.02	-	-	-3.30	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-10.01	-	-	-3.30	-	8.00	-	Pass
HT20	MCS0	1	12	2467	-18.57	-	-	-3.30	-	8.00	-	Pass
HT20	MCS0	1	13	2472	-28.65	-	-	-3.30	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	24~26℃
		Relative Humidity :	53~55%

EUT Information

Report NO : 932517-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	---	35.11	55.52	20.41	L1	OFF	19.5
0.159000	51.95	---	65.52	13.57	L1	OFF	19.5
0.161250	---	33.53	55.40	21.87	L1	OFF	19.5
0.161250	50.65	---	65.40	14.75	L1	OFF	19.5
0.186000	---	33.98	54.21	20.23	L1	OFF	19.5
0.186000	48.62	---	64.21	15.59	L1	OFF	19.5
0.210750	---	29.36	53.18	23.82	L1	OFF	19.5
0.210750	43.93	---	63.18	19.25	L1	OFF	19.5
0.426750	---	25.31	47.32	22.01	L1	OFF	19.5
0.426750	36.15	---	57.32	21.17	L1	OFF	19.5
2.289750	---	26.33	46.00	19.67	L1	OFF	19.5
2.289750	30.61	---	56.00	25.39	L1	OFF	19.5
8.018250	---	25.25	50.00	24.75	L1	OFF	19.8
8.018250	26.48	---	60.00	33.52	L1	OFF	19.8
26.540250	---	25.28	50.00	24.72	L1	OFF	20.4
26.540250	26.14	---	60.00	33.86	L1	OFF	20.4

EUT Information

Report NO : 932517-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	30.74	55.40	24.66	N	OFF	19.5
0.161250	44.97	---	65.40	20.43	N	OFF	19.5
0.186000	---	30.84	54.21	23.37	N	OFF	19.5
0.186000	43.74	---	64.21	20.47	N	OFF	19.5
0.413250	---	26.16	47.58	21.42	N	OFF	19.5
0.413250	34.70	---	57.58	22.88	N	OFF	19.5
0.469500	---	29.43	46.52	17.09	N	OFF	19.5
0.469500	37.06	---	56.52	19.46	N	OFF	19.5
2.287500	---	26.11	46.00	19.89	N	OFF	19.5
2.287500	32.07	---	56.00	23.93	N	OFF	19.5
3.880500	---	25.89	46.00	20.11	N	OFF	19.7
3.880500	28.66	---	56.00	27.34	N	OFF	19.7
11.602500	---	24.91	50.00	25.09	N	OFF	20.0
11.602500	25.94	---	60.00	34.06	N	OFF	20.0
23.833500	---	25.13	50.00	24.87	N	OFF	20.5
23.833500	26.14	---	60.00	33.86	N	OFF	20.5



Appendix C. Radiated Spurious Emission

Test Engineer :	Karl Hou and BigShow Wang	Temperature :	24~26°C
		Relative Humidity :	45~65%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2311.995	53.31	-20.69	74	40.45	27.83	16.06	31.03	344	273	P	H
		2389.59	42.61	-11.39	54	29.84	27.6	16.16	30.99	344	273	A	H
	*	2412	104.43	-	-	91.63	27.6	16.18	30.98	344	273	P	H
	*	2412	101.03	-	-	88.23	27.6	16.18	30.98	344	273	A	H
													H
		2337.405	53.97	-20.03	74	41.19	27.7	16.09	31.01	386	230	P	V
		2311.155	42.52	-11.48	54	29.67	27.83	16.05	31.03	386	230	A	V
	*	2412	101.48	-	-	88.68	27.6	16.18	30.98	386	230	P	V
	*	2412	98.07	-	-	85.27	27.6	16.18	30.98	386	230	A	V
													V
802.11b CH 06 2437MHz		2355.64	53.23	-20.77	74	40.46	27.67	16.11	31.01	375	272	P	H
		2311.82	42.51	-11.49	54	29.65	27.83	16.06	31.03	375	272	A	H
	*	2437	105.05	-	-	92.21	27.6	16.21	30.97	375	272	P	H
	*	2437	102.04	-	-	89.2	27.6	16.21	30.97	375	272	A	H
		2488.8	53.51	-20.49	74	40.8	27.4	16.26	30.95	375	272	P	H
		2483.55	42.39	-11.61	54	29.62	27.47	16.25	30.95	375	272	A	H
		2380.84	53.35	-20.65	74	40.56	27.63	16.15	30.99	375	226	P	V
		2310.14	42.47	-11.53	54	29.62	27.83	16.05	31.03	375	226	A	V
	*	2437	101.15	-	-	88.31	27.6	16.21	30.97	375	226	P	V
	*	2437	98.02	-	-	85.18	27.6	16.21	30.97	375	226	A	V
		2491.53	52.92	-21.08	74	40.2	27.4	16.26	30.94	375	226	P	V
		2485.44	42.25	-11.75	54	29.47	27.47	16.26	30.95	375	226	A	V



802.11b CH 11 2462MHz	*	2462	104.95	-	-	92.15	27.53	16.23	30.96	371	272	P	H
	*	2462	101.79	-	-	88.99	27.53	16.23	30.96	371	272	A	H
		2489.08	53.54	-20.46	74	40.83	27.4	16.26	30.95	371	272	P	H
		2484.8	42.44	-11.56	54	29.67	27.47	16.25	30.95	371	272	A	H
													H
													H
	*	2462	101.6	-	-	88.8	27.53	16.23	30.96	369	220	P	V
	*	2462	98.44	-	-	85.64	27.53	16.23	30.96	369	220	A	V
		2496.68	53.29	-20.71	74	40.56	27.4	16.27	30.94	369	220	P	V
		2483.6	42.36	-11.64	54	29.59	27.47	16.25	30.95	369	220	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBμV/m)	Limit (dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11b CH 12 2467MHz	*	2467	104.28	-	-	91.47	27.53	16.24	30.96	371	270	P	H
	*	2467	101.13	-	-	88.32	27.53	16.24	30.96	371	270	A	H
		2486.2	53.81	-20.19	74	41.03	27.47	16.26	30.95	371	270	P	H
		2484.16	43.15	-10.85	54	30.38	27.47	16.25	30.95	371	270	A	H
													H
													H
	*	2467	101.04	-	-	88.23	27.53	16.24	30.96	369	219	P	V
	*	2467	97.89	-	-	85.08	27.53	16.24	30.96	369	219	A	V
		2493.08	53.24	-20.76	74	40.52	27.4	16.26	30.94	369	219	P	V
		2483.96	42.6	-11.4	54	29.83	27.47	16.25	30.95	369	219	A	V
													V
													V
802.11b CH 13 2472MHz	*	2472	105.22	-	-	92.46	27.47	16.24	30.95	372	272	P	H
	*	2472	102.09	-	-	89.33	27.47	16.24	30.95	372	272	A	H
		2483.56	54.92	-19.08	74	42.15	27.47	16.25	30.95	372	272	P	H
		2483.52	47.28	-6.72	54	34.51	27.47	16.25	30.95	372	272	A	H
													H
													H
	*	2472	101.22	-	-	88.46	27.47	16.24	30.95	368	228	P	V
	*	2472	98.09	-	-	85.27	27.53	16.24	30.95	368	228	A	V
		2498.04	54.12	-19.88	74	41.39	27.4	16.27	30.94	368	228	P	V
		2483.52	44.92	-9.08	54	32.15	27.47	16.25	30.95	368	228	A	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	40.23	-33.77	74	57.57	31.3	9.59	58.23	100	0	P	H
													H
													H
													H
		4824	38.89	-35.11	74	56.23	31.3	9.59	58.23	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	41.24	-32.76	74	58.61	31.3	9.58	58.25	100	0	P	H
		7311	44.16	-29.84	74	54.89	36.2	11.66	58.59	100	0	P	H
													H
													H
		4874	39.37	-34.63	74	56.75	31.3	9.58	58.26	100	0	P	V
		7311	44.63	-29.37	74	55.36	36.2	11.66	58.59	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	39.75	-34.25	74	57.12	31.37	9.56	58.3	100	0	P	H
		7386	44.35	-29.65	74	54.73	36.5	11.67	58.55	100	0	P	H
													H
													H
		4924	39.27	-34.73	74	56.64	31.37	9.56	58.3	100	0	P	V
		7386	45.19	-28.81	74	55.57	36.5	11.67	58.55	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBμV/m)	Limit (dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11b CH 12 2467MHz		4934	40.65	-33.35	74	58.02	31.37	9.56	58.3	100	0	P	H
		7401	45.1	-28.9	74	55.45	36.53	11.67	58.55	100	0	P	H
													H
													H
		4934	38.76	-35.24	74	56.13	31.37	9.56	58.3	100	0	P	V
		7401	44.54	-29.46	74	54.89	36.53	11.67	58.55	100	0	P	V
													V
													V
802.11b CH 13 2472MHz		4944	39.55	-34.45	74	56.9	31.4	9.56	58.31	100	0	P	H
		7416	44.11	-29.89	74	54.43	36.53	11.69	58.54	100	0	P	H
													H
													H
		4944	39.27	-34.73	74	56.62	31.4	9.56	58.31	100	0	P	V
		7416	44.79	-29.21	74	55.11	36.53	11.69	58.54	100	0	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.8	54.1	-19.9	74	41.33	27.6	16.16	30.99	345	278	P	H
		2390	45.04	-8.96	54	32.27	27.6	16.16	30.99	345	278	A	H
	*	2412	106.15	-	-	93.35	27.6	16.18	30.98	345	278	P	H
	*	2412	98.05	-	-	85.25	27.6	16.18	30.98	345	278	A	H
													H
													H
		2313.99	53.66	-20.34	74	40.8	27.83	16.06	31.03	382	242	P	V
		2390	44.55	-9.45	54	31.78	27.6	16.16	30.99	382	242	A	V
	*	2412	103.98	-	-	91.18	27.6	16.18	30.98	382	242	P	V
	*	2412	96	-	-	83.2	27.6	16.18	30.98	382	242	A	V
													V
													V
802.11g CH 06 2437MHz		2322.04	53.85	-20.15	74	41.03	27.77	16.07	31.02	377	272	P	H
		2359	43.67	-10.33	54	30.88	27.67	16.12	31	377	272	A	H
	*	2437	107.56	-	-	94.72	27.6	16.21	30.97	377	272	P	H
	*	2437	100.05	-	-	87.21	27.6	16.21	30.97	377	272	A	H
		2487.61	52.95	-21.05	74	40.24	27.4	16.26	30.95	377	272	P	H
		2484.81	43.65	-10.35	54	30.88	27.47	16.25	30.95	377	272	A	H
		2320.92	53.35	-20.65	74	40.53	27.77	16.07	31.02	376	227	P	V
		2311.82	43.7	-10.3	54	30.84	27.83	16.06	31.03	376	227	A	V
	*	2437	103.7	-	-	90.86	27.6	16.21	30.97	376	227	P	V
	*	2437	96.06	-	-	83.22	27.6	16.21	30.97	376	227	A	V
		2498.95	53.35	-20.65	74	40.62	27.4	16.27	30.94	376	227	P	V
		2485.65	43.42	-10.58	54	30.64	27.47	16.26	30.95	376	227	A	V



802.11g CH 11 2462MHz	*	2462	107.4	-	-	94.6	27.53	16.23	30.96	372	273	P	H
	*	2462	100.04	-	-	87.24	27.53	16.23	30.96	372	273	A	H
		2494.96	54.12	-19.88	74	41.4	27.4	16.26	30.94	372	273	P	H
		2483.52	44.97	-9.03	54	32.2	27.47	16.25	30.95	372	273	A	H
													H
													H
	*	2462	101.38	-	-	88.58	27.53	16.23	30.96	400	136	P	V
	*	2462	93.94	-	-	81.14	27.53	16.23	30.96	400	136	A	V
		2495.6	53.63	-20.37	74	40.9	27.4	16.27	30.94	400	136	P	V
		2483.52	43.86	-10.14	54	31.09	27.47	16.25	30.95	400	136	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBμV/m)	Limit (dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11g CH 12 2467MHz	*	2467	104.4	-	-	91.59	27.53	16.24	30.96	371	275	P	H
	*	2467	96.6	-	-	83.79	27.53	16.24	30.96	371	275	A	H
		2483.6	60.25	-13.75	74	47.48	27.47	16.25	30.95	371	275	P	H
		2483.68	50.84	-3.16	54	38.07	27.47	16.25	30.95	371	275	A	H
													H
													H
	*	2467	97.6	-	-	84.79	27.53	16.24	30.96	400	136	P	V
	*	2467	89.59	-	-	76.78	27.53	16.24	30.96	400	136	A	V
		2483.52	57.28	-16.72	74	44.51	27.47	16.25	30.95	400	136	P	V
		2483.52	46.95	-7.05	54	34.18	27.47	16.25	30.95	400	136	A	V
													V
													V
802.11g CH 13 2472MHz	*	2472	88.63	-	-	75.87	27.47	16.24	30.95	371	273	P	H
	*	2472	81.4	-	-	68.64	27.47	16.24	30.95	371	273	A	H
		2483.64	61.11	-12.89	74	48.34	27.47	16.25	30.95	371	273	P	H
		2483.52	50.02	-3.98	54	37.25	27.47	16.25	30.95	371	273	A	H
													H
													H
	*	2472	82.98	-	-	70.22	27.47	16.24	30.95	400	135	P	V
	*	2472	74.88	-	-	62.12	27.47	16.24	30.95	400	135	A	V
		2484	56.63	-17.37	74	43.86	27.47	16.25	30.95	400	135	P	V
		2483.56	46.93	-7.07	54	34.16	27.47	16.25	30.95	400	135	A	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	40.44	-33.56	74	57.78	31.3	9.59	58.23	100	0	P	H
													H
													H
													H
		4824	38.72	-35.28	74	56.06	31.3	9.59	58.23	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	38.66	-35.34	74	56.04	31.3	9.58	58.26	100	0	P	H
		7311	43.81	-30.19	74	54.54	36.2	11.66	58.59	100	0	P	H
													H
													H
		4874	39.14	-34.86	74	56.52	31.3	9.58	58.26	100	0	P	V
		7311	43.68	-30.32	74	54.41	36.2	11.66	58.59	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	38.8	-35.2	74	56.17	31.37	9.56	58.3	100	0	P	H
		7386	44.87	-29.13	74	55.25	36.5	11.67	58.55	100	0	P	H
													H
													H
		4924	38.43	-35.57	74	55.8	31.37	9.56	58.3	100	0	P	V
		7386	44.26	-29.74	74	54.64	36.5	11.67	58.55	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBμV/m)	Limit (dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11g CH 12 2467MHz		4934	38.63	-35.37	74	56	31.37	9.56	58.3	100	0	P	H
		7401	44.43	-29.57	74	54.78	36.53	11.67	58.55	100	0	P	H
													H
													H
		4934	39.11	-34.89	74	56.48	31.37	9.56	58.3	100	0	P	V
		7401	44.66	-29.34	74	55.01	36.53	11.67	58.55	100	0	P	V
													V
													V
802.11g CH 13 2472MHz		4944	39.15	-34.85	74	56.5	31.4	9.56	58.31	100	0	P	H
		7416	44.7	-29.3	74	55.02	36.53	11.69	58.54	100	0	P	H
													H
													H
		4944	38.43	-35.57	74	55.78	31.4	9.56	58.31	100	0	P	V
		7416	44.69	-29.31	74	55.01	36.53	11.69	58.54	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2366.28	54.78	-19.22	74	41.98	27.67	16.13	31	345	282	P	H
		2390	45.75	-8.25	54	32.98	27.6	16.16	30.99	345	282	A	H
	*	2412	106.13	-	-	93.33	27.6	16.18	30.98	345	282	P	H
	*	2412	97.97	-	-	85.17	27.6	16.18	30.98	345	282	A	H
													H
													H
		2389.905	54.46	-19.54	74	41.69	27.6	16.16	30.99	385	233	P	V
		2390	44.68	-9.32	54	31.91	27.6	16.16	30.99	385	233	A	V
	*	2412	104.32	-	-	91.52	27.6	16.18	30.98	385	233	P	V
	*	2412	96.14	-	-	83.34	27.6	16.18	30.98	385	233	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2389.66	53.81	-20.19	74	41.04	27.6	16.16	30.99	376	272	P	H
		2388.12	43.16	-10.84	54	30.4	27.6	16.15	30.99	376	272	A	H
	*	2437	107.87	-	-	95.03	27.6	16.21	30.97	376	272	P	H
	*	2437	99.58	-	-	86.74	27.6	16.21	30.97	376	272	A	H
		2485.72	52.85	-21.15	74	40.07	27.47	16.26	30.95	376	272	P	H
		2483.76	43.16	-10.84	54	30.39	27.47	16.25	30.95	376	272	A	H
		2317.56	53.91	-20.09	74	41.1	27.77	16.06	31.02	378	226	P	V
		2383.36	43.01	-10.99	54	30.22	27.63	16.15	30.99	378	226	A	V
	*	2437	104.22	-	-	91.38	27.6	16.21	30.97	378	226	P	V
	*	2437	95.54	-	-	82.7	27.6	16.21	30.97	378	226	A	V
		2494.47	53.29	-20.71	74	40.57	27.4	16.26	30.94	378	226	P	V
		2498.32	42.83	-11.17	54	30.1	27.4	16.27	30.94	378	226	A	V



802.11n HT20 CH 11 2462MHz	*	2462	106.95	-	-	94.15	27.53	16.23	30.96	373	263	P	H
	*	2462	98.51	-	-	85.71	27.53	16.23	30.96	373	263	A	H
		2483.68	53.93	-20.07	74	41.16	27.47	16.25	30.95	373	263	P	H
		2483.52	44.53	-9.47	54	31.76	27.47	16.25	30.95	373	263	A	H
													H
													H
	*	2462	104.05	-	-	91.25	27.53	16.23	30.96	370	244	P	V
	*	2462	96.27	-	-	83.47	27.53	16.23	30.96	370	244	A	V
		2484.52	54.14	-19.86	74	41.37	27.47	16.25	30.95	370	244	P	V
		2483.56	44.16	-9.84	54	31.39	27.47	16.25	30.95	370	244	A	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBμV/m)	Limit (dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11n HT20 CH 12 2467MHz	*	2467	99.03	-	-	86.22	27.53	16.24	30.96	361	274	P	H
	*	2467	91.32	-	-	78.51	27.53	16.24	30.96	361	274	A	H
		2483.8	57.28	-16.72	74	44.51	27.47	16.25	30.95	361	274	P	H
		2483.52	47.72	-6.28	54	34.95	27.47	16.25	30.95	361	274	A	H
													H
													H
	*	2467	93.76	-	-	80.95	27.53	16.24	30.96	400	135	P	V
	*	2467	85.47	-	-	72.66	27.53	16.24	30.96	400	135	A	V
		2483.84	55.72	-18.28	74	42.95	27.47	16.25	30.95	400	135	P	V
		2483.52	44.85	-9.15	54	32.08	27.47	16.25	30.95	400	135	A	V
													V
													V
802.11n HT20 CH 13 2472MHz	*	2472	87.27	-	-	74.45	27.53	16.24	30.95	370	265	P	H
	*	2472	79.28	-	-	66.46	27.53	16.24	30.95	370	265	A	H
		2483.52	61.89	-12.11	74	49.12	27.47	16.25	30.95	370	265	P	H
		2483.52	50.14	-3.86	54	37.37	27.47	16.25	30.95	370	265	A	H
													H
													H
	*	2472	86.11	-	-	73.29	27.53	16.24	30.95	369	245	P	V
	*	2472	78.2	-	-	65.38	27.53	16.24	30.95	369	245	A	V
		2483.64	59.55	-14.45	74	46.78	27.47	16.25	30.95	369	245	P	V
		2483.52	49.1	-4.9	54	36.33	27.47	16.25	30.95	369	245	A	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	38.99	-35.01	74	56.33	31.3	9.59	58.23	100	0	P	H
													H
													H
													H
		4824	39.27	-34.73	74	56.61	31.3	9.59	58.23	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	38.7	-35.3	74	56.08	31.3	9.58	58.26	100	0	P	H
		7311	43.31	-30.69	74	54.04	36.2	11.66	58.59	100	0	P	H
													H
													H
		4874	38.19	-35.81	74	55.57	31.3	9.58	58.26	100	0	P	V
		7311	44.46	-29.54	74	55.19	36.2	11.66	58.59	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	39.18	-34.82	74	56.55	31.37	9.56	58.3	100	0	P	H
		7386	43.98	-30.02	74	54.36	36.5	11.67	58.55	100	0	P	H
													H
													H
		4924	39.06	-34.94	74	56.43	31.37	9.56	58.3	100	0	P	V
		7386	43.78	-30.22	74	54.16	36.5	11.67	58.55	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant. 1		(MHz)	(dBμV/m)	Limit (dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
802.11n HT20 CH 12 2467MHz		4934	38.84	-35.16	74	56.21	31.37	9.56	58.3	100	0	P	H
		7401	44.25	-29.75	74	54.6	36.53	11.67	58.55	100	0	P	H
													H
													H
		4934	38.75	-35.25	74	56.12	31.37	9.56	58.3	100	0	P	V
		7401	44.2	-29.8	74	54.55	36.53	11.67	58.55	100	0	P	V
													V
													V
802.11n HT20 CH 13 2472MHz		4944	38.45	-35.55	74	55.8	31.4	9.56	58.31	100	0	P	H
		7416	45.03	-28.97	74	55.3	36.57	11.7	58.54	100	0	P	H
													H
													H
		4944	38.04	-35.96	74	55.39	31.4	9.56	58.31	100	0	P	V
		7416	45.62	-28.38	74	55.95	36.53	11.68	58.54	100	0	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	24.31	-15.69	40	31.03	25.2	0.7	32.62	-	-	P	H
		123.12	23.13	-20.37	43.5	36.59	17.6	1.45	32.51	-	-	P	H
		282.2	22.47	-23.53	46	33.83	18.89	2.28	32.53	-	-	P	H
		426.73	23.3	-22.7	46	30.51	22.7	2.65	32.56	-	-	P	H
		555.74	26.68	-19.32	46	30.17	25.96	3.14	32.59	-	-	P	H
		889.42	32.36	-13.64	46	31.23	28.9	3.94	31.71	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		30	30.3	-9.7	40	37.02	25.2	0.7	32.62	100	0	P	V
		84.32	23.23	-16.77	40	40.49	14.03	1.25	32.54	-	-	P	V
		122.15	26.4	-17.1	43.5	39.87	17.6	1.44	32.51	-	-	P	V
		256.98	20.02	-25.98	46	30.85	19.52	2.17	32.52	-	-	P	V
		353.01	21.74	-24.26	46	31.36	20.52	2.41	32.55	-	-	P	V
		924.34	33.79	-12.21	46	31.64	29.59	4	31.44	-	-	P	V
													V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

$$1. \text{ Path Loss(dB)} = \text{Cable loss(dB)} + \text{Filter loss(dB)} + \text{Attenuator loss(dB)}$$

$$2. \text{ Level(dB}\mu\text{V/m)} =$$

$$\text{Antenna Factor(dB/m)} + \text{Path Loss(dB)} + \text{Read Level(dB}\mu\text{V)} - \text{Preamp Factor(dB)}$$

$$3. \text{ Over Limit(dB)} = \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$$

For Peak Limit @ 2390MHz:

$$1. \text{ Level(dB}\mu\text{V/m)}$$

$$= \text{Antenna Factor(dB/m)} + \text{Path Loss(dB)} + \text{Read Level(dB}\mu\text{V)} - \text{Preamp Factor(dB)}$$

$$= 32.22(\text{dB/m}) + 4.58(\text{dB}) + 54.51(\text{dB}\mu\text{V}) - 35.86(\text{dB})$$

$$= 55.45(\text{dB}\mu\text{V/m})$$

$$2. \text{ Over Limit(dB)}$$

$$= \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$$

$$= 55.45(\text{dB}\mu\text{V/m}) - 74(\text{dB}\mu\text{V/m})$$

$$= -18.55(\text{dB})$$

For Average Limit @ 2390MHz:

$$1. \text{ Level(dB}\mu\text{V/m)}$$

$$= \text{Antenna Factor(dB/m)} + \text{Path Loss(dB)} + \text{Read Level(dB}\mu\text{V)} - \text{Preamp Factor(dB)}$$

$$= 32.22(\text{dB/m}) + 4.58(\text{dB}) + 42.6(\text{dB}\mu\text{V}) - 35.86(\text{dB})$$

$$= 43.54(\text{dB}\mu\text{V/m})$$

$$2. \text{ Over Limit(dB)}$$

$$= \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$$

$$= 43.54(\text{dB}\mu\text{V/m}) - 54(\text{dB}\mu\text{V/m})$$

$$= -10.46(\text{dB})$$

Both peak and average measured complies with the limit line, so test result is "PASS".







Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Karl Hou and BigShow Wang	Temperature :	24~26°C
		Relative Humidity :	45~65%





Note symbol

-L	Low channel location
-R	High channel location





2.4GHz 2400~2483.5MHz
WIFI 802.11b (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 19	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 19
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 19	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 19









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 19	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 19
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 19	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 19







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 20	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 20
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 20	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 20





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 9120D_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z0	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 9120D_15_1620 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z0	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : 20	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : 20
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : 20	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : 20
Avg.		





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z0	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z0	Left blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z1	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z1
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z1	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z1

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z1	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z1
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z1	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z1





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH12 2467MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z2	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z2
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z2	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z2

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH12 2467MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z2	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z2
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z2	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z2







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH13 2472MHz	
1	Horizontal	Fundamental
Peak	Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z3	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z3
Avg.	Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z3	Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z3







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH13 2472MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z3	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z3
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z3	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z3





2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 24	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 24
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 24	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : 24







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 24	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 24
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:1000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 24	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000kHz VBW:1000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 24





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 9120D_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 9120D_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z5







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z5	Left Blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z5	Left Blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z6	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z6
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z6	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z6







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z6	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z6
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z6	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : Z6



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH12 2467MHz	
1	Horizontal	Fundamental
Peak	 Level (dBm/100kHz) vs Frequency (MHz) plot showing a peak at 2467 MHz. The y-axis ranges from 10.0 to 140.0 dBm/100kHz, and the x-axis ranges from 2460 to 2500 MHz. A red line marks the peak at 2467 MHz, labeled 'PEAK_BE_74'. Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z7 Setting : 0x21	 Level (dBm/100kHz) vs Frequency (MHz) plot showing a peak at 2467 MHz. The y-axis ranges from 10.0 to 140.0 dBm/100kHz, and the x-axis ranges from 1000 to 3000 MHz. A red line marks the peak at 2467 MHz, labeled 'PEAK_74'. Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z7 Setting : 0x21
Avg.	 Level (dBm/100kHz) vs Frequency (MHz) plot showing an average spectrum. The y-axis ranges from 10.0 to 140.0 dBm/100kHz, and the x-axis ranges from 2460 to 2500 MHz. A red line marks the average level at 2467 MHz, labeled 'AVG_BE_54'. Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:1000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z7 Setting : 0x21	 Level (dBm/100kHz) vs Frequency (MHz) plot showing an average spectrum. The y-axis ranges from 10.0 to 140.0 dBm/100kHz, and the x-axis ranges from 1000 to 3000 MHz. A red line marks the average level at 2467 MHz, labeled 'AVG_54'. Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000kHz VBW:1000kHz SWT:Auto Detector : Peak Project : 932517-01 Mode : Z7 Setting : 0x21







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH12 2467MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 27 Setting : 0x21	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 27 Setting : 0x21
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 27 Setting : 0x21	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : 27 Setting : 0x21







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH13 2472MHz	
1	Horizontal	Fundamental
Peak	Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : ZB	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : ZB
Avg.	Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : ZB	Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak Project : 932517-01 Mode : ZB



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH13 2472MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : ZB	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : ZB
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : ZB	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 932517-01 Mode : ZB

2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z9	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z9
	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z9	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 932517-01 Mode : Z9