



Limited Internal
MARKING DRAWING

Prepared (also subject responsible if other) BA/SEM/MD/V José A. Rodrigo		No. 151 86-KRD 102 436+ Uen		
Approved BA/SEM/MD/P (Hilary Brownlow)	Checked	Date 2002-02-01	Rev E	Reference Lilium-Cecilia

Marking Drawing Type 6220501-BV


Label

The label used for marking is defined in the Manufacturing Specification on the SVF 930 2159.

Placing

The label shall be placed on the back of the module according to the Assembly Drawing (151 88) for the KRD.

Print layout



Definitions

Sony Ericsson trademark

Sony Ericsson and the Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347.

Approval marks

1. FCC approval marking: consists of the text:

FCC ID: PY76220501-BV

Within a frame with height > 1.5 mm.

2. This field shall be blank.



Limited Internal
MARKING DRAWING

Prepared (also subject responsible if other) BA/SEM/MD/V José A. Rodrigo		No. 151 86-KRD 102 436+ Uen		
Approved BA/SEM/MD/P (Hilary Brownlow)	Checked	Date 2002-02-01	Rev E	Reference Lilium-Cecilia

- 3. This field shall be blank.
- 4. Canada approval marking: consists of text:
CAN XXXXXXXXXXX
- 5. This field shall be blank.

Local approval marks

6. This field shall be blank.
This field shall be used for local approval marks in countries where special marking is required.

IMEI number as bar code

See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -).

IMEI number as characters

The IMEI number has format:
TAC-FAC-SNR-CD
TAC = Type Approval code after assignment from the Notified Body
FAC = The corresponding Final Assembly Code of the factory used for the production (i.e. 69 for the Bilbao factory).
SNR = A serial number from 000 001 to 999 999.
CD = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.

Serial number as bar code

According to Ericsson corporate standard 102 01 - 109.

Serial number as characters

According to Ericsson group standard 0012-101.
Ericsson group factory number system according to the Ericsson corporate standard 1120-101 Factory codes:
Bilbao S69
Tecom (Taiwan) S48

Type number

The type number is 6220501-BV and shall be printed "Type 6220501-BV".

G-field

R-state identification of the CXC-module according to the Marking data 1/151 86 for the KRD.

H-field

R-state identification of the hardware version used during the current Type Approval according to the Marking data 1/151 86 for the KRD.

Y₁-field

R-state identification of the current KRD

Limited Internal
 MARKING DRAWING

Prepared (also subject responsible if other) BA/SEM/MD/V José A. Rodrigo		No. 151 86-KRD 102 436+ Uen		
Approved BA/SEM/MD/P (Hilary Brownlow)	Checked	Date 2002-02-01	Rev E	Reference Lilium-Cecilia

Y ₂ -field	according to the Marking data 1/151 86 for the KRD. ROA structure identification according to the Marking data 1/151 86 for the KRD.
Y ₃ -field	R-state identification of the ROA according to the Marking data 1/151 86 for the KRD.
Production week	The production week shall be given as yyWww (yy = year, ww = week)
KRD number	The KRD number for the product.
R-state	The R-state for the KRD according to the 1095 for the KRD.
Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as RyyWww (yy = year, ww = week)
Manufacturing country	The text "Made by Sony Ericsson" printed horizontally for phones produced in Bilbao. For phones produced in Tecom (Taiwan) the horizontal text shall be "Made in Taiwan".
*	Text "GM48" printed vertically.

Print regulations

The printing shall be well readable and permanent.

Other texts different whose definition is not specified formerly have the following characteristics:

Typeface:	ZPL II standard font D
Type size:	min 1.1 mm
Line spacing:	min 1.5 mm
Trademark:	min 1.5 mm
Approval marks:	min 5.0 mm