



FCC RADIO TEST REPORT

FCC ID : PY7-77587Q
Equipment : GSM/WCDMA/LTE Phone with BT, DTS/UNII
a/b/g/n/ac, GPS and NFC
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Standard : 47 CFR Part 2, 22(H), 24(E), 27

The product was received on Jun. 04, 2019 and testing was started from Jul. 29, 2019 and completed on Aug. 07, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this partial apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description.....	6
1.1 Product Feature of Equipment Under Test	6
1.2 Modification of EUT	6
1.3 Emission Designator	7
1.4 Testing Location	8
1.5 Applicable Standards	8
2 Test Configuration of Equipment Under Test.....	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration and system.....	10
2.4 Frequency List of Low/Middle/High Channels.....	11
3 Conducted Test Items	13
3.1 Measuring Instruments.....	13
3.2 Conducted Output Power and ERP/EIRP	14
3.3 Peak-to-Average Ratio	15
3.4 Occupied Bandwidth	16
3.5 Conducted Band Edge	17
3.6 Conducted Spurious Emission	19
3.7 Frequency Stability	20
4 Radiated Test Items	21
4.1 Measuring Instruments.....	21
4.2 Radiated Spurious Emission Measurement.....	22
5 List of Measuring Equipment	23
6 Uncertainty of Evaluation.....	25
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of ERP/EIRP and Radiated Test	
Appendix C. Verification and Validation of Using Mobile Country Code	



History of this test report

Report No.	Version	Description	Issued Date
FG940903-03A	01	Initial issue of report	Aug. 20, 2019



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
	§22.913 (a)(2)	Effective Radiated Power (Band 26)	Pass	
	§27.50 (b)(10)	Effective Radiated Power (Band 13)		
	§24.232 (c)	Equivalent Isotropic Radiated Power (Band 25)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (Band 66)		
3.3	§24.232 (d) §27.50 (d)(5)	Peak-to-Average Ratio	Pass	-
3.4	§2.1049	Occupied Bandwidth	Pass	-
3.5	§2.1051 §22.917 (a) §24.238 (a) §27.53 (c)(2)(4) §27.53 (h)	Conducted Band Edge Measurement (Band 13) (Band 25) (Band 26) (Band 66)	Pass	-
3.6	§2.1051 §22.917 (a) §24.238 (a) §27.53 (c)(2) §27.53 (h)	Conducted Spurious Emission (Band 13) (Band 25) (Band 26) (Band 66)	Pass	-
3.7	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	Pass	-



Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
4.2	§2.1053 §22.917 (a) §24.238 (a) §27.53 (c)(2) §27.53 (f) §27.53 (h)	Radiated Spurious Emission (Band 13) (Band 25) (Band 26) (Band 66)	Pass	Under limit 21.13 dB at 1568.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Yimin Ho



1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac, NFC, and GNSS.

Product Specification subjective to this standard	
Antenna Type	Loop Antenna

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	3.122	BH93000MH0	Conducted Measurement
		BH93012NGX	Radiated Spurious Emission ERP/EIRP Test

Accessory List	
AC Adapter	Model Name : UCH32
	S/N: 6218W30200140
Earphone	Model Name.: MH750
	S/N : N/A
USB Cable	Model Name.: UCB24
	S/N : N/A
2 in 1 USB Audio Cable	Model Name.: EC270
	S/N : N/A

Note:

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report. .
3. For other wireless features of this EUT, test report will be issued separately.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.



1.3 Emission Designator

LTE Band 13		QPSK			16QAM			64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	779.5~784.5	4M51G7D	-	0.0889	4M49W7D	-	0.0670	4M53W7D	-	0.0528
10	782.0	9M03G7D	0.0066	0.0891	9M05W7D	-	0.0670	9M01W7D	-	0.0527
LTE Band 25		QPSK			16QAM			64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7~1914.3	1M10G7D	-	0.1660	1M09W7D	-	0.1253	1M10W7D	-	0.0986
3	1851.5~1913.5	2M73G7D	-	0.1671	2M72W7D	-	0.1245	2M73W7D	-	0.0982
5	1852.5~1912.5	4M51G7D	-	0.1667	4M50W7D	-	0.1262	4M50W7D	-	0.0986
10	1855.0~1910.0	9M07G7D	0.0041	0.1641	9M07W7D	-	0.1233	9M05W7D	-	0.0979
15	1857.5~1907.5	13M4G7D	-	0.1754	13M5W7D	-	0.1318	13M5W7D	-	0.1040
20	1860.0~1905.0	17M9G7D	-	0.1758	17M9W7D	-	0.1321	17M9W7D	-	0.1042
LTE Band 26		QPSK			16QAM			64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	824.7~848.3	1M10G7D	-	0.0849	1M09W7D	-	0.0653	1M09W7D	-	0.0514
3	825.5~847.5	2M73G7D	-	0.0841	2M72W7D	-	0.0646	2M73W7D	-	0.0518
5	826.5~846.5	4M50G7D	-	0.0839	4M49W7D	-	0.0652	4M50W7D	-	0.0514
10	829.0~844.0	9M03G7D	0.0061	0.0851	9M05W7D	-	0.0655	9M05W7D	-	0.0519
15	831.5~841.5	13M4G7D	-	0.0859	13M4W7D	-	0.0665	13M5W7D	-	0.0518
LTE Band 66		QPSK			16QAM			64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7~1779.3	1M09G7D	-	0.2173	1M10W7D	-	0.1618	1M09W7D	-	0.1276
3	1711.5~1778.5	2M73G7D	-	0.2148	2M73W7D	-	0.1607	2M73W7D	-	0.1271
5	1712.5~1777.5	4M50G7D	-	0.2178	4M49W7D	-	0.1629	4M52W7D	-	0.1279
10	1715.0~1775.0	9M07G7D	0.0033	0.2138	9M05W7D	-	0.1611	9M11W7D	-	0.1276
15	1717.5~1772.5	13M5G7D	-	0.2218	13M5W7D	-	0.1730	13M4W7D	-	0.1330
20	1720.0~1770.0	17M9G7D	-	0.2223	17M9W7D	-	0.1714	17M9W7D	-	0.1358



1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH05-HY
Test Engineer	Aking Chang
Temperature	24~26 °C
Relative Humidity	55~57 %

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH13-HY
Test Engineer	Ryan Lin, JC Linag, and Wilson Wu
Temperature	21.5~23.5 °C
Relative Humidity	46.5~49.5 %

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ 47 CFR Part 2, 22(H), 24(E), 27
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.


For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z, and Accessory. The worst cases (Z plane with Adapter) were recorded in this report.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	13	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v
	25	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
	66	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	13	-	-		v	-	-	v	v	v	v		v	v	v	v
	25						v	v	v	v	v		v	v	v	v
	26					v	-	v	v	v	v		v	v	v	v
	66						v	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	13	-	-	v	v	-	-	v	v	v			v	v	v	v
	25	v	v	v	v	v	v	v	v	v			v	v	v	v
	26	v	v	v	v	v	-	v	v	v			v	v	v	v
	66	v	v	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	13	-	-	v	v	-	-	v	v	v	v		v	v		v
	25	v	v	v	v	v	v	v	v	v	v		v	v		v
	26	v	v	v	v	v	-	v	v	v	v		v	v		v
	66	v	v	v	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	13	-	-	v	v	-	-	v	v	v	v			v	v	v
	25	v	v	v	v	v	v	v	v	v	v			v	v	v
	26	v	v	v	v	v	-	v	v	v	v			v	v	v
	66	v	v	v	v	v	v	v	v	v	v			v	v	v
Frequency Stability	13	-	-		v	-	-	v					v		v	
	25				v			v					v		v	
	26				v		-	v					v		v	
	66				v			v					v		v	

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
E.R.P / E.I.R.P	13	-	-	v	v	-	-	v	v	v	v			v	v	v
	25	v	v	v	v	v	v	v	v	v	v	v		v	v	v
	26	v	v	v	v	v	-	v	v	v	v			v	v	v
	66	v	v	v	v	v	v	v	v	v	v	v		v	v	v
Radiated Spurious Emission	13	Worst Case											v	v	v	
	25	Worst Case											v	v	v	
	26	Worst Case											v	v	v	
	66	Worst Case											v	v	v	
Remark	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 															

2.2 Connection Diagram of Test System

<EUT with Adapter>



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	8820C	N/A	N/A	Unshielded, 1.8 m



2.4 Frequency List of Low/Middle/High Channels

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5

LTE Band 25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	26140	26340	26590
	Frequency	1860	1880	1905
15	Channel	26115	26340	26615
	Frequency	1857.5	1880	1907.5
10	Channel	26090	26340	26640
	Frequency	1855	1880	1910
5	Channel	26065	26340	26665
	Frequency	1852.5	1880	1912.5
3	Channel	26055	26340	26675
	Frequency	1851.5	1880	1913.5
1.4	Channel	26047	26340	26683
	Frequency	1850.7	1880	1914.3

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5
10	Channel	26840	26915	26990
	Frequency	829.0	836.5	844.0
5	Channel	26815	26915	27015
	Frequency	826.5	836.5	846.5
3	Channel	26805	26915	27025
	Frequency	825.5	836.5	847.5
1.4	Channel	26797	26915	27033
	Frequency	824.7	836.5	848.3



LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 26.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 13.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 25.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 66.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.



3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (c)

For operations in the 776-788 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least $65 + 10 \log_{10} p(\text{watts})$, dB, for mobile and portable equipment.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.



3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1 and ANSI C63.26-2015 Section 5.7.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1 and ANSI C63.26-2015 Section 5.7.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

22.355

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

24.235 & 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.1.1 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.1.2 Test Result of Radiated Test

Please refer to Appendix B.



4.2 Radiated Spurious Emission Measurement

4.2.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	GSM/GPRS /WCDMA/LTE	Oct. 14, 2018	Jul. 29, 2019~ Aug. 01, 2019	Oct. 13, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Jul. 29, 2019~ Aug. 01, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40°C~90°C	Aug. 29, 2018	Jul. 29, 2019~ Aug. 01, 2019	Aug. 28, 2019	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 02, 2018	Jul. 29, 2019~ Aug. 01, 2019	Oct. 01, 2019	Conducted (TH05-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#A	1-18GHz	Jan. 14, 2019	Jul. 29, 2019~ Aug. 01, 2019	Jan. 13, 2020	Conducted (TH05-HY)
Hygrometer	TECEPEL	HTC-1	2	N/A	Mar. 05, 2019	Jul. 29, 2019~ Aug. 01, 2019	Mar. 04, 2020	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 22, 2018	Aug. 06, 2019~ Aug. 07, 2019	Nov. 21, 2019	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&0080 0N1D01N-06	40103&07	30MHz to 1GHz	Apr. 30, 2019	Aug. 06, 2019~ Aug. 07, 2019	Apr. 29, 2020	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1212	1GHz ~ 18GHz	May 14, 2019	Aug. 06, 2019~ Aug. 07, 2019	May 13, 2020	Radiation (03CH13-HY)
Horn Antenna	ESCO	3117	00143261	1GHz ~ 18GHz	Jan. 07, 2019	Aug. 06, 2019~ Aug. 07, 2019	Jan. 06, 2020	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91705 84	18GHz- 40GHz	Dec. 05, 2018	Aug. 06, 2019~ Aug. 07, 2019	Dec. 04, 2019	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91702 51	18GHz- 40GHz	Nov. 20, 2018	Aug. 06, 2019~ Aug. 07, 2019	Nov. 19, 2019	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 18, 2018	Aug. 06, 2019~ Aug. 07, 2019	Dec. 17, 2019	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Aug. 06, 2019~ Aug. 07, 2019	Dec. 05, 2019	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY5327014 7	1GHz~26.5GHz	Mar. 15, 2019	Aug. 06, 2019~ Aug. 07, 2019	Mar. 14, 2020	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY5537052 6	10Hz~44GHz	Mar. 19, 2019	Aug. 06, 2019~ Aug. 07, 2019	Mar. 18, 2020	Radiation (03CH13-HY)
Hygrometer	TECEPEL	DTM-303A	TP157075	N/A	May 18, 2019	Aug. 06, 2019~ Aug. 07, 2019	May 17, 2020	Radiation (03CH13-HY)
Notch Filter	Wainwright	WTRCT5-82 4-849-20-70-60SSK	SN1	824-849	Mar. 21, 2019	Aug. 06, 2019~ Aug. 07, 2019	Mar. 20, 2020	Radiation (03CH13-HY)
Notch Filter	Wainwright	WRCT2500/ 2570-10/40-10SSK	SN1 R	LTE Band 7	Aug. 23, 2018	Aug. 06, 2019~ Aug. 07, 2019	Aug. 22, 2019	Radiation (03CH13-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Filter	Wainwright	WLJ4-1000-1530-6000-40ST	SN3	1.53 GHz Lowpass	Mar. 20, 2019	Aug. 06, 2019~ Aug. 07, 2019	Mar. 19, 2020	Radiation (03CH13-HY)
Filter	Microwave	H1G013G1	SN477215	1.0G High Pass	Nov. 02, 2018	Aug. 06, 2019~ Aug. 07, 2019	Nov. 01, 2019	Radiation (03CH13-HY)
Filter	Microwave	H3G018G1	SN477220	3.0G High Pass	Nov. 02, 2018	Aug. 06, 2019~ Aug. 07, 2019	Nov. 01, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SF102/2*11 SK252	MY4278/2	9kHz~40GHz	May 16, 2019	Aug. 06, 2019~ Aug. 07, 2019	May 15, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M-18G	Feb. 13, 2019	Aug. 06, 2019~ Aug. 07, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30M~40GHz	Mar. 13, 2019	Aug. 06, 2019~ Aug. 07, 2019	Mar. 12, 2020	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 06, 2019~ Aug. 07, 2019	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Aug. 06, 2019~ Aug. 07, 2019	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Aug. 06, 2019~ Aug. 07, 2019	N/A	Radiation (03CH13-HY)
Signal Generator	Anritsu	MG3694C	163401	0.1Hz~40GHz	Jan. 21, 2019	Aug. 06, 2019~ Aug. 07, 2019	Jan. 20, 2020	Radiation (03CH13-HY)
Software	Audix	E3 6.2009-8-24c	RK-001124	N/A	N/A	Aug. 06, 2019~ Aug. 07, 2019	N/A	Radiation (03CH13-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.07
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.48
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.92
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	24.73	24.75	24.73
20	1	49		24.59	24.65	24.62
20	1	99		24.56	24.57	24.58
20	50	0		23.71	23.75	23.73
20	50	24		23.75	23.79	23.76
20	50	50		23.72	23.77	23.76
20	100	0		23.72	23.76	23.70
20	1	0	16-QAM	23.50	23.51	23.51
20	1	49		23.37	23.42	23.43
20	1	99		23.37	23.37	23.40
20	50	0		22.25	22.29	22.26
20	50	24		22.27	22.33	22.28
20	50	50		22.27	22.31	22.28
20	100	0		22.25	22.29	22.25
20	1	0	64-QAM	22.45	22.48	22.45
20	1	49		22.29	22.34	22.36
20	1	99		22.34	22.34	22.35
20	50	0		21.26	21.29	21.27
20	50	24		21.28	21.32	21.30
20	50	50		21.27	21.32	21.29
20	100	0		21.25	21.31	21.28
15	1	0	QPSK	24.57	24.74	24.70
15	1	37		24.61	24.64	24.64
15	1	74		24.58	24.63	24.63
15	36	0		23.70	23.76	23.73
15	36	20		23.76	23.82	23.78
15	36	39		23.72	23.81	23.77
15	75	0		23.72	23.79	23.76
15	1	0	16-QAM	23.36	23.50	23.49
15	1	37		23.36	23.45	23.43
15	1	74		23.37	23.40	23.39
15	36	0		22.25	22.29	22.24
15	36	20		22.28	22.36	22.31
15	36	39		22.25	22.33	22.29
15	75	0		22.25	22.34	22.27
15	1	0	64-QAM	22.32	22.47	22.43
15	1	37		22.27	22.41	22.25
15	1	74		22.34	22.37	22.25
15	36	0		21.26	21.32	21.23
15	36	20		21.31	21.37	21.26
15	36	39		21.26	21.32	21.25
15	75	0		21.25	21.32	21.23



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	24.41	24.45	24.38
10	1	25		24.32	24.41	24.36
10	1	49		24.33	24.40	24.35
10	25	0		23.45	23.53	23.49
10	25	12		23.46	23.55	23.50
10	25	25		23.46	23.54	23.49
10	50	0		23.45	23.55	23.51
10	1	0	16-QAM	23.13	23.21	23.15
10	1	25		23.09	23.17	23.14
10	1	49		23.09	23.12	23.09
10	25	0		21.98	22.06	22.02
10	25	12		21.99	22.07	22.01
10	25	25		21.98	22.07	22.03
10	50	0		21.97	22.05	22.03
10	1	0	64-QAM	22.11	22.21	22.12
10	1	25		22.01	22.14	22.11
10	1	49		22.02	22.12	22.06
10	25	0		20.99	21.07	21.02
10	25	12		20.98	21.08	21.03
10	25	25		20.97	21.07	21.05
10	50	0		21.00	21.07	21.05
5	1	0	QPSK	24.27	24.39	24.33
5	1	12		24.38	24.45	24.44
5	1	24		24.38	24.52	24.46
5	12	0		23.44	23.53	23.42
5	12	7		23.51	23.63	23.47
5	12	13		23.50	23.58	23.53
5	25	0		23.46	23.57	23.45
5	1	0	16-QAM	23.00	23.14	23.13
5	1	12		23.15	23.23	23.19
5	1	24		23.19	23.31	23.18
5	12	0		21.95	22.07	21.95
5	12	7		22.02	22.16	22.02
5	12	13		22.00	22.11	22.05
5	25	0		22.00	22.10	21.98
5	1	0	64-QAM	21.98	22.12	22.08
5	1	12		22.09	22.21	22.15
5	1	24		22.11	22.24	22.18
5	12	0		21.00	21.08	21.00
5	12	7		21.07	21.17	21.05
5	12	13		21.05	21.19	21.11
5	25	0		21.02	21.09	20.99



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	24.22	24.32	24.27
3	1	8		24.44	24.53	24.47
3	1	14		24.31	24.45	24.42
3	8	0		23.40	23.52	23.42
3	8	4		23.50	23.58	23.49
3	8	7		23.40	23.53	23.50
3	15	0		23.44	23.54	23.45
3	1	0	16-QAM	22.92	23.08	23.00
3	1	8		23.15	23.25	23.21
3	1	14		23.05	23.22	23.19
3	8	0		21.97	22.07	22.00
3	8	4		22.06	22.13	22.04
3	8	7		21.99	22.11	22.07
3	15	0		21.95	22.08	21.98
3	1	0	64-QAM	21.96	22.08	22.00
3	1	8		22.13	22.22	22.22
3	1	14		22.03	22.18	22.16
3	8	0		20.94	21.04	21.00
3	8	4		21.01	21.12	21.08
3	8	7		21.01	21.13	21.10
3	15	0		20.96	21.08	21.00
1.4	1	0	QPSK	24.28	24.44	24.36
1.4	1	3		24.40	24.49	24.49
1.4	1	5		24.32	24.43	24.44
1.4	3	0		24.32	24.44	24.43
1.4	3	1		24.37	24.50	24.47
1.4	3	3		24.35	24.45	24.44
1.4	6	0		23.45	23.54	23.51
1.4	1	0	16-QAM	23.07	23.14	23.11
1.4	1	3		23.18	23.28	23.24
1.4	1	5		23.13	23.19	23.16
1.4	3	0		22.88	22.95	22.96
1.4	3	1		22.93	23.01	23.02
1.4	3	3		22.89	22.98	22.98
1.4	6	0		22.01	22.10	22.09
1.4	1	0	64-QAM	22.01	22.09	22.10
1.4	1	3		22.11	22.24	22.23
1.4	1	5		22.08	22.15	22.15
1.4	3	0		22.04	22.11	22.11
1.4	3	1		22.09	22.17	22.17
1.4	3	3		22.07	22.16	22.15
1.4	6	0		20.99	21.09	21.01



LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK		24.26	
10	1	25			24.45	
10	1	49			24.42	
10	25	0			23.48	
10	25	12			23.59	
10	25	25			23.57	
10	50	0			23.59	
10	1	0	16-QAM	-	22.94	-
10	1	25			23.17	
10	1	49			23.21	
10	25	0			21.95	
10	25	12			22.05	
10	25	25			22.04	
10	50	0			22.05	
10	1	0	64-QAM		21.87	
10	1	25			22.10	
10	1	49			22.17	
10	25	0			20.94	
10	25	12			21.07	
10	25	25			21.07	
10	50	0			21.05	
5	1	0	QPSK	24.17	24.35	24.37
5	1	12		24.39	24.42	24.43
5	1	24		24.43	24.44	24.40
5	12	0		23.41	23.48	23.54
5	12	7		23.49	23.59	23.58
5	12	13		23.57	23.59	23.55
5	25	0		23.52	23.59	23.56
5	1	0	16-QAM	22.86	23.02	23.07
5	1	12		23.09	23.17	23.21
5	1	24		23.11	23.20	23.15
5	12	0		21.89	21.96	22.00
5	12	7		21.95	22.07	22.08
5	12	13		22.02	22.06	22.03
5	25	0		21.98	22.09	22.01
5	1	0	64-QAM	21.83	21.96	22.05
5	1	12		22.06	22.14	22.15
5	1	24		22.13	22.18	22.08
5	12	0		20.91	21.01	21.06
5	12	7		21.01	21.12	21.13
5	12	13		21.07	21.10	21.08
5	25	0		21.01	21.07	21.03



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.99	24.96	24.73
15	1	37		24.92	24.95	24.18
15	1	74		24.67	24.72	24.07
15	36	0		23.98	23.73	23.60
15	36	20		23.97	23.98	23.18
15	36	39		23.92	23.92	23.25
15	75	0		23.97	23.97	23.56
15	1	0	16-QAM	23.86	23.87	23.60
15	1	37		23.82	23.84	23.54
15	1	74		23.88	23.87	23.56
15	36	0		22.73	22.74	22.38
15	36	20		22.76	22.74	22.39
15	36	39		22.69	22.68	22.46
15	75	0		22.71	22.71	22.47
15	1	0	64-QAM	22.78	22.79	22.52
15	1	37		22.74	22.79	22.50
15	1	74		22.79	22.76	22.46
15	36	0		21.71	21.73	21.37
15	36	20		21.72	21.73	21.45
15	36	39		21.68	21.66	21.48
15	75	0		21.68	21.70	21.43
10	1	0	QPSK	24.95	24.62	24.24
10	1	25		24.83	24.84	24.01
10	1	49		24.83	24.75	23.67
10	25	0		23.91	23.78	23.08
10	25	12		23.95	23.95	23.20
10	25	25		23.91	23.90	23.30
10	50	0		23.96	23.94	23.35
10	1	0	16-QAM	23.81	23.76	23.47
10	1	25		23.76	23.76	23.40
10	1	49		23.80	23.69	23.16
10	25	0		22.59	22.59	22.21
10	25	12		22.62	22.61	22.32
10	25	25		22.59	22.58	22.32
10	50	0		22.58	22.60	22.33
10	1	0	64-QAM	22.80	22.71	22.46
10	1	25		22.74	22.75	22.35
10	1	49		22.78	22.67	22.23
10	25	0		21.60	21.60	21.26
10	25	12		21.62	21.63	21.34
10	25	25		21.62	21.61	21.36
10	50	0		21.60	21.62	21.34



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.77	24.70	24.02
5	1	12		24.83	24.82	24.34
5	1	24		24.89	24.79	23.37
5	12	0		23.87	23.84	23.40
5	12	7		23.97	23.90	23.50
5	12	13		23.94	23.94	23.16
5	25	0		23.91	23.84	23.21
5	1	0	16-QAM	23.54	23.51	23.25
5	1	12		23.79	23.77	23.55
5	1	24		23.76	23.74	22.90
5	12	0		22.57	22.54	22.32
5	12	7		22.62	22.56	22.39
5	12	13		22.61	22.62	22.39
5	25	0		22.59	22.53	22.32
5	1	0	64-QAM	22.63	22.67	22.36
5	1	12		22.76	22.72	22.53
5	1	24		22.73	22.70	22.05
5	12	0		21.62	21.59	21.35
5	12	7		21.71	21.65	21.47
5	12	13		21.69	21.66	21.41
5	25	0		21.59	21.52	21.34
3	1	0	QPSK	24.78	24.76	24.40
3	1	8		24.90	24.90	24.16
3	1	14		24.82	24.85	23.33
3	8	0		23.94	23.88	23.48
3	8	4		23.98	23.89	23.29
3	8	7		23.93	23.91	22.98
3	15	0		23.93	23.87	23.16
3	1	0	16-QAM	23.60	23.64	23.41
3	1	8		23.75	23.73	23.55
3	1	14		23.69	23.69	22.85
3	8	0		22.62	22.55	22.33
3	8	4		22.64	22.56	22.37
3	8	7		22.59	22.59	22.23
3	15	0		22.58	22.52	22.29
3	1	0	64-QAM	22.62	22.62	22.39
3	1	8		22.76	22.79	22.52
3	1	14		22.65	22.64	22.00
3	8	0		21.64	21.52	21.34
3	8	4		21.64	21.58	21.36
3	8	7		21.62	21.59	21.30
3	15	0		21.59	21.55	21.31



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.88	24.80	23.91
1.4	1	3		24.92	24.94	23.67
1.4	1	5		24.80	24.81	23.23
1.4	3	0		24.86	24.83	23.89
1.4	3	1		24.92	24.84	23.80
1.4	3	3		24.86	24.86	23.44
1.4	6	0		23.96	23.85	22.86
1.4	1	0	16-QAM	23.75	23.63	23.32
1.4	1	3		23.80	23.78	23.10
1.4	1	5		23.70	23.65	22.69
1.4	3	0		23.53	23.48	23.08
1.4	3	1		23.60	23.49	23.01
1.4	3	3		23.52	23.47	22.69
1.4	6	0		22.67	22.54	22.07
1.4	1	0	64-QAM	22.71	22.61	22.31
1.4	1	3		22.74	22.76	22.18
1.4	1	5		22.69	22.65	21.86
1.4	3	0		22.71	22.63	22.34
1.4	3	1		22.75	22.67	22.27
1.4	3	3		22.67	22.64	21.97
1.4	6	0		21.60	21.53	21.10



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	24.93	24.97	24.57
20	1	49		24.82	24.80	24.42
20	1	99		24.79	24.78	23.69
20	50	0		23.98	23.92	23.55
20	50	24		23.91	23.87	23.48
20	50	50		23.83	23.80	23.37
20	100	0		23.89	23.84	23.48
20	1	0	16-QAM	23.84	23.79	23.50
20	1	49		23.71	23.72	23.34
20	1	99		23.67	23.67	22.93
20	50	0		22.69	22.66	22.27
20	50	24		22.64	22.63	22.22
20	50	50		22.56	22.52	22.15
20	100	0		22.61	22.58	22.20
20	1	0	64-QAM	22.83	22.77	22.45
20	1	49		22.69	22.66	22.27
20	1	99		22.67	22.66	21.90
20	50	0		21.73	21.68	21.31
20	50	24		21.66	21.64	21.24
20	50	50		21.59	21.55	21.18
20	100	0		21.65	21.61	21.23
15	1	0	QPSK	24.96	24.95	24.58
15	1	37		24.83	24.83	24.47
15	1	74		24.80	24.77	23.55
15	36	0		23.96	23.94	23.57
15	36	20		23.91	23.89	23.49
15	36	39		23.87	23.84	23.26
15	75	0		23.93	23.90	23.50
15	1	0	16-QAM	23.87	23.88	23.44
15	1	37		23.66	23.70	23.33
15	1	74		23.69	23.65	22.97
15	36	0		22.68	22.66	22.30
15	36	20		22.61	22.58	22.22
15	36	39		22.57	22.53	22.15
15	75	0		22.63	22.60	22.22
15	1	0	64-QAM	22.73	22.74	22.40
15	1	37		22.61	22.58	22.24
15	1	74		22.60	22.57	21.88
15	36	0		21.68	21.63	21.28
15	36	20		21.63	21.59	21.20
15	36	39		21.57	21.51	21.14
15	75	0		21.58	21.57	21.18



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	24.80	24.76	24.42
10	1	25		24.76	24.72	24.35
10	1	49		24.74	24.69	23.82
10	25	0		23.96	23.88	23.53
10	25	12		23.95	23.88	23.51
10	25	25		23.89	23.81	23.20
10	50	0		23.93	23.86	23.42
10	1	0	16-QAM	23.57	23.54	23.18
10	1	25		23.53	23.53	23.16
10	1	49		23.52	23.51	23.08
10	25	0		22.46	22.42	22.06
10	25	12		22.45	22.39	22.05
10	25	25		22.39	22.34	21.97
10	50	0		22.44	22.38	22.01
10	1	0	64-QAM	22.56	22.48	22.17
10	1	25		22.51	22.47	22.12
10	1	49		22.49	22.47	22.10
10	25	0		21.48	21.42	21.06
10	25	12		21.48	21.41	21.04
10	25	25		21.42	21.35	20.97
10	50	0		21.47	21.39	21.03
5	1	0	QPSK	24.76	24.72	24.26
5	1	12		24.79	24.77	23.92
5	1	24		24.88	24.82	23.80
5	12	0		23.93	23.84	23.35
5	12	7		23.94	23.94	23.15
5	12	13		23.96	23.90	22.99
5	25	0		23.96	23.88	22.95
5	1	0	16-QAM	23.53	23.46	23.13
5	1	12		23.59	23.54	23.23
5	1	24		23.62	23.56	23.07
5	12	0		22.45	22.35	21.99
5	12	7		22.49	22.45	22.00
5	12	13		22.49	22.45	21.96
5	25	0		22.46	22.42	21.98
5	1	0	64-QAM	22.48	22.45	22.10
5	1	12		22.54	22.52	22.18
5	1	24		22.57	22.57	22.02
5	12	0		21.51	21.38	21.05
5	12	7		21.55	21.48	21.06
5	12	13		21.54	21.49	21.02
5	25	0		21.48	21.40	20.99



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	24.70	24.63	24.08
3	1	8		24.82	24.79	24.00
3	1	14		24.71	24.69	23.83
3	8	0		23.81	23.81	23.14
3	8	4		23.88	23.83	23.08
3	8	7		23.86	23.80	22.98
3	15	0		23.89	23.84	22.96
3	1	0	16-QAM	23.38	23.39	23.08
3	1	8		23.55	23.56	23.21
3	1	14		23.44	23.46	23.06
3	8	0		22.40	22.40	21.97
3	8	4		22.43	22.43	22.00
3	8	7		22.42	22.39	22.00
3	15	0		22.40	22.35	21.93
3	1	0	64-QAM	22.39	22.38	22.05
3	1	8		22.54	22.49	22.21
3	1	14		22.47	22.49	22.03
3	8	0		21.43	21.39	20.95
3	8	4		21.49	21.43	20.98
3	8	7		21.46	21.42	20.97
3	15	0		21.42	21.39	20.92
1.4	1	0	QPSK	24.72	24.66	23.91
1.4	1	3		24.84	24.81	23.93
1.4	1	5		24.78	24.75	23.82
1.4	3	0		24.82	24.72	23.88
1.4	3	1		24.87	24.80	23.95
1.4	3	3		24.83	24.74	23.85
1.4	6	0		23.93	23.86	22.94
1.4	1	0	16-QAM	23.45	23.44	23.15
1.4	1	3		23.59	23.56	23.17
1.4	1	5		23.50	23.47	23.07
1.4	3	0		23.31	23.29	22.91
1.4	3	1		23.36	23.34	22.95
1.4	3	3		23.34	23.30	22.86
1.4	6	0		22.47	22.41	21.96
1.4	1	0	64-QAM	22.44	22.42	22.06
1.4	1	3		22.56	22.53	22.08
1.4	1	5		22.45	22.46	21.99
1.4	3	0		22.49	22.45	22.08
1.4	3	1		22.54	22.48	22.09
1.4	3	3		22.49	22.46	22.04
1.4	6	0		21.42	21.36	20.91



LTE Band 13


Peak-to-Average Ratio

Mode	LTE Band 13 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.19	4.90	3.71	5.62	
Highest CH	-	-	-	-	
Mode	LTE Band 13 / 10MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	-	-	-	-	PASS
Middle CH	4.46	6.06	-	-	
Highest CH	-	-	-	-	




LTE Band 13 / 10MHz / QPSK

Middle Channel / 1RB



Date: 1.AUG.2019 08:12:08


Middle Channel / Full RB



Date: 1.AUG.2019 08:12:18


LTE Band 13 / 10MHz / 16QAM

Middle Channel / 1RB



Date: 1.AUG.2019 08:11:48


Middle Channel / Full RB



Date: 1.AUG.2019 08:11:58


LTE Band 13 / 10MHz / 64QAM

Middle Channel / 1RB



Date: 1.AUG.2019 08:11:28

Middle Channel / Full RB



Date: 1.AUG.2019 08:11:38




26dB Bandwidth

Mode	LTE Band 13 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.90	4.89	-	-	-	-	-	-
Middle CH	-	-	-	-	4.89	4.91	9.79	9.75	-	-	-	-
Highest CH	-	-	-	-	4.93	4.91	-	-	-	-	-	-
Mode	LTE Band 13 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.96	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.99	-	9.89	-	-	-	-	-
Highest CH	-	-	-	-	4.82	-	-	-	-	-	-	-




LTE Band 13

Lowest Channel / 5MHz / QPSK




Date: 1.AUG.2019 07:18:22

Lowest Channel / 5MHz / 16QAM




Date: 1.AUG.2019 07:18:10

Middle Channel / 5MHz / QPSK




Date: 1.AUG.2019 07:28:42

Middle Channel / 5MHz / 16QAM




Date: 1.AUG.2019 07:28:53

Highest Channel / 5MHz / QPSK



Date: 1.AUG.2019 07:30:02

Highest Channel / 5MHz / 16QAM




Date: 1.AUG.2019 07:29:51




LTE Band 13

Middle Channel / 10MHz / QPSK



Date: 1.AUG.2019 07:49:17

Middle Channel / 10MHz / 16QAM




Date: 1.AUG.2019 07:49:25




LTE Band 13

Lowest Channel / 5MHz / 64QAM




Date: 1.AUG.2019 07:38:49

Middle Channel / 5MHz / 64QAM




Date: 1.AUG.2019 07:44:04

Middle Channel / 10MHz / 64QAM



Date: 1.AUG.2019 08:01:41

Highest Channel / 5MHz / 64QAM



Date: 1.AUG.2019 07:44:39




Occupied Bandwidth

Mode	LTE Band 13 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.47	4.49	-	-	-	-	-	-
Middle CH	-	-	-	-	4.48	4.48	9.03	9.05	-	-	-	-
Highest CH	-	-	-	-	4.51	4.49	-	-	-	-	-	-
Mode	LTE Band 13 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.52	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.49	-	9.01	-	-	-	-	-
Highest CH	-	-	-	-	4.53	-	-	-	-	-	-	-




LTE Band 13

Lowest Channel / 5MHz / QPSK




Date: 1.AUG.2019 07:17:47

Lowest Channel / 5MHz / 16QAM




Date: 1.AUG.2019 07:17:59

Middle Channel / 5MHz / QPSK




Date: 1.AUG.2019 07:29:16

Middle Channel / 5MHz / 16QAM




Date: 1.AUG.2019 07:29:05

Highest Channel / 5MHz / QPSK



Date: 1.AUG.2019 07:29:28

Highest Channel / 5MHz / 16QAM




Date: 1.AUG.2019 07:29:39




LTE Band 13

Middle Channel / 10MHz / QPSK



Date: 1.AUG.2019 07:49:02

Middle Channel / 10MHz / 16QAM




Date: 1.AUG.2019 07:49:13




LTE Band 13

Lowest Channel / 5MHz / 64QAM




Date: 1.AUG.2019 07:38:17

Middle Channel / 5MHz / 64QAM




Date: 1.AUG.2019 07:44:15

Middle Channel / 10MHz / 64QAM



Date: 1.AUG.2019 08:01:29

Highest Channel / 5MHz / 64QAM




Date: 1.AUG.2019 07:44:27



Conducted Band Edge


LTE Band 13 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 1.AUG.2019 07:25:02

Highest Band Edge / 1 RB




Date: 1.AUG.2019 07:36:42

Lowest Band Edge / Full RB



Date: 1.AUG.2019 07:20:02

Highest Band Edge / Full RB




Date: 1.AUG.2019 07:31:42




LTE Band 13 / 5MHz / 16QAM


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 13 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Date: 1.AUG.2019 07:42:08

Highest Band Edge / 1 RB




Date: 1.AUG.2019 07:47:58

Lowest Band Edge / Full RB



Date: 1.AUG.2019 07:40:28

Highest Band Edge / Full RB





Date: 1.AUG.2019 07:46:19



LTE Band 13 / 10MHz / QPSK

Lowest Band Edge / 1 RB


Highest Band Edge / 1 RB



Date: 1.AUG.2019 07:56:14

Date: 1.AUG.2019 07:57:54

Band Edge / Full RB




Date: 1.AUG.2019 07:51:16




LTE Band 13 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 1.AUG.2019 07:54:35

Highest Band Edge / 1 RB



Date: 1.AUG.2019 07:59:33

Band Edge / Full RB




Date: 1.AUG.2019 07:52:55




LTE Band 13 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 1.AUG.2019 08:04:59

Highest Band Edge / 1 RB



Date: 1.AUG.2019 08:06:39


Band Edge / Full RB



Date: 1.AUG.2019 08:03:20




Conducted Spurious Emission






LTE Band 13 / 5MHz

Highest Channel / QPSK



Date: 1.AUG.2019 07:37:33


Highest Channel / 16QAM



Date: 1.AUG.2019 07:38:25


LTE Band 13 / 10MHz

Middle Channel / QPSK



Date: 1.AUG.2019 08:01:17

Middle Channel / 16QAM




Date: 1.AUG.2019 08:00:25



LTE Band 13 / 5MHz

Lowest Channel / 64QAM


Middle Channel / 64QAM



Date: 1.AUG.2019 07:43:00

Date: 1.AUG.2019 07:43:52

Highest Channel / 64QAM




Date: 1.AUG.2019 07:48:50



LTE Band 13 / 10MHz

Middle Channel / 64QAM





Frequency Stability

Test Conditions		LTE Band 13 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0033	PASS
40	Normal Voltage	0.0035	
30	Normal Voltage	0.0036	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0040	
0	Normal Voltage	0.0006	
-10	Normal Voltage	0.0046	
-20	Normal Voltage	0.0031	
-30	Normal Voltage	0.0037	
20	Maximum Voltage	0.0006	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0066	

Note:

1. Normal Voltage =3.85 V. ; Battery End Point (BEP) =3.65 V. ; Maximum Voltage =4.25 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.



LTE Band 25

Peak-to-Average Ratio

Mode	LTE Band 25 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.54	4.84	4.03	5.94	PASS
Middle CH	3.51	4.90	4.41	5.91	
Highest CH	3.57	4.75	4.26	5.83	
Mode	LTE Band 25 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	5.62	6.38	-	-	PASS
Middle CH	5.22	6.49	-	-	
Highest CH	5.22	6.38	-	-	