



Accredited Bluetooth™ Test Facility (BQTF)

Test report no.: 4_0703-01-02/02
FCC Part 15.247 / CANADA RSS-210
8502001
FCC ID : PY78502001

CETECOM – ICT Services GmbH
Untertürkheimerstr. 6-10
66117 Saarbrücken, Germany

Telephone: + 49 (0) 681 / 598-0
Fax: + 49 (0) 681 / 9075

Table of Contents

1 General information

1.1 Notes

1.2 Testing laboratory

1.3 Details of applicant

1.4 Application details

1.5 Test item

1.6 Test standards

2 Technical test

2.1 Summary of test results

2.2 Test report

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Telephone : + 49 681 598 - 9100

Telefax : + 49 681 598 - 9075

E-mail : Harro.Ames@ict.cetecom.de

Internet : www.cetecom.de

Accredited testing laboratory

DAR-registration number : TTI-P-G 166/98-30

Accredited Bluetooth™ Test Facility (BQTF)

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc. and licensed to CETECOM

1.3 Details of applicant

Name : SonyEricsson Mobile Communications AB
Street : Nya Vattentornet
City : SE-22188 Lund
Country : Sweden
Telephone : +46 46 193 242
Telefax : +46 46 193 295
Contact : Mr. Bo Johansson
Telephone : +46 46 193 242

1.4 Application details

Date of receipt of application : 2002-07-22
Date of receipt of test item : 2002-08-21
Date of test : 2002-08-22/28

1.5 Test item

Type of equipment : **Bluetooth™ CarKit**
Type designation : 8502001
Manufacturer : applicant
Street :
City :
Country :
Serial number : -.-
Hardware : EP2
Software : CAH109737 R1A

Additional informations: :

Frequency : 2400 – 2483.5 MHz
Type of modulation : 1M00FXD / 79M8FXD (FHSS)
Number of channels : 79
Antenna : integral antenna / print antenna
Power supply : 12V DC external (Car battery)
Output power : EIRP: 1.8 mW
Temperature range : -10°C to +50°C
FCC ID : PY78502001

1.6 Test standards: **FCC Part 15 §15.247**
CANADA RSS-210

2 Technical test

2.1 Summary of test results

The radiated measurements were performed vertical and horizontal over the whole frequency range. We start at 1 m high with vertical receiving antenna and rotate the dish continuously. During rotation we use the antenna lift system to vary the high from 1 to 4 m. So we find maximum radiation output. At this points we do manual remeasurements. After this we do the same measurements in horizontal position of the receiving antenna. This (horizontal and vertical) is made for all the three planes of the test sample. We use the maximum received results.

The detector function and selection of bandwidth are according ANSI C63.2-1996 item 8.2.1 and ANSI C63.4-1992 Item 4.2.

Antennas are conform with ANSI C63.2-1996 item 15.

150 kHz - 30 MHz: Quasi Peak measurement, 9kHz Bandwidth, passive loop antenna.

30 MHz - 200 MHz: Quasi Peak measurement, 120KHz Bandwidth, biconical antenna

200MHz - 1GHz: Quasi Peak measurement, 120KHz Bandwidth, log periodic antenna

1GHz: Average, RBW 1MHz, VBW 10 MHz, waveguide horn

The product fullfills also the requirements for CANACA RSS-210

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

Final verdict : PASS

Technical responsibility for area of testing :

2002-08-28 RSC 8411 Berg M.

Date Section Name

Signature




Technical responsibility for area of testing :

2002-08-28 RSC8412 Hausknecht D.

Date Section Name

Signature



2.2 Testreport

TEST REPORT

Testreport no. : 4_0703-01-02/02

TEST REPORT REFERENCE

LIST OF MEASUREMENTS

Paragraph	PARAMETER TO BE MEASURED	PAGE
	Transmitter parameters	
§ 15.204	Antenna gain	7
§ 15.247 (a)	Carrier frequency separation	8
§ 15.247 (a)	Number of hopping channels	9
§ 15.247 (a)	Time of occupancy (dwell time)	11
§ 15.247 (d)	Power spectral density (Inquiry/Page mode)	15
§ 15.247 (a)(1)	Spectrum bandwidth of a FHSS System	16
§ 15.247 (b)(2)	Maximum peak output power	20
§ 15.247 (b) (4)	RF Exposure calculation	20
§15.247	Band edge compliance	25
§ 15.247 (c)(1)	Emission limitations	33
	Receiver parameters	
§ 15.109	Spurious radiations - Radiated	56
	Test equipment listing	63
	Photographs of the equipment	65

Equipment under test : 8502001**Ambient temperature : 25.7°C****Relative humidity : 55%****Antenna Gain****SUBCLAUSE § 15.204**

The antenna gain of the complete system is calculated by the difference of conducted power of the module and the radiated power in EIRP.

	low channel	mid channel	high channel
Conducted power	0.37 dBm	-0.08 dBm	-0.85 dBm
Radiated power	2.56 dBm	2.29 dBm	1.36 dBm
Gain	2.19 dBi	2.37 dBi	2.21 dB

**The calculated antenna gain is between 2.19 and 2.37 dBi for the build-in antenna.
So we will calculate the Defacto EIRP with the middle value from: 2.26 dBi**

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED**(for reference numbers see test equipment listing)**

Page 8 (75)

Relative humidity : 55%

§15.247(a)



64

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 9 (75)

Equipment under test : 8502001

Ambient temperature : 25.7°C


Relative humidity : 55%

Number of hopping channels
Channel 1 - 40

§15.247(a)

The number of hopping channels is 79.


 Ref Lvl 24.3 dBm
 Marker 2 [T1] 2.44100000 GHz
 RBW 500 kHz
 RF Att 30 dB
 VBW 500 kHz
 SWT 5 ms
 Unit dBm



Date: 28.AUG.2002 09:24:29

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C


Relative humidity : 55%

Number of hopping channels

Channel 41 - 79

§15.247(a)


 Ref Lvl 24.3 dBm
 Marker 2 [T1] -1.28 dBm
 2.48000000 GHz
 RBW 500 kHz
 VBW 500 kHz
 SWT 5 ms
 RF Att 30 dB
 Unit dBm



Date: 28.AUG.2002 09:26:10

The number of hopping channels is 79.

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%


Time of occupancy (dwell time) for DH1

§15.247(a)

The system makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 79 channels. So you have each channel 10.13 times per second and for 30 seconds you have 303.9 times of appearance .

Each tx-time per appearance is 385.174 µs.

So we have $303.9 * 385.174 \mu s = 117.054 \text{ ms}$ per 31.6 seconds.



Date: 28.AUG.2002 09:34:34

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Time of occupancy (dwell time) for DH3


§15.247(a)

A DH3 Packets need 3 time slots for transmit and 1 for receiving, then the system makes worst case 400 hops per second with 79 channels. So you have each channel 5.1 times per second and for 30 seconds you have 153 times of appearance .

Each tx-time per appearance is 1.630 ms.

So we have $153 * 1.630 \text{ ms} = 249.39 \text{ ms}$ per 31.6 seconds.

	Delta 1 [T1]	RBW	3 MHz	RF Att	20 dB
Ref Lvl	-0.04 dB	VBW	3 MHz		
14.3 dBm	1.629659 ms	SWT	5 ms	Unit	dBm



Date: 28.AUG.2002 09:40:32

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 13 (75)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%


Time of occupancy (dwell time) for DH5

§15.247(a)

At DH5 Packets you need 5 time slots for transmit and 1 for receiving, so the system makes worst case 266,7 hops per second with 79 channels. So you have each channel 3.36 times per second and for 30 seconds you have 100,8 times of appearance .

Each tx-time per appearance is 2.872 ms.

So we have $100,8 * 2.872 \text{ ms} = 289.498 \text{ ms}$ per 31.6 seconds.



Date: 28.AUG.2002 09:39:18

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Time of occupancy (dwell time) for page mode /Inquiry mode (TX-on time) §15.247(a)

At paging mode the system makes first hopping with 16 channels. One sequence(called train A) lasts 10 ms. Every 1.28s frequencies change and a second train A starts with different frequencies. After max $7 \cdot 1.28$ s 16 new more distance frequencies (Train B) are used.

So we have in the worst case (same frequency is in every train) the following time scedule.


First: $7 \cdot 128 \cdot 10$ ms. For the next 7 seconds train B with other frequencies.

Then train A and B changes frequently.

⇒ so we have $7 \cdot 128 \cdot 148.697 \mu$ s, then 8.96 s other frequencies, then again $7 \cdot 128 \cdot 148.697 \mu$ s

⇒ together in 31.6 s maximal 2 sequences =>maximal 0.266 s per 31.6 second period.

Page mode (TX-on time) / Inquiry mode (TX-on time)



Date: 28.AUG.2002 09:46:11

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 15 (75)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

Power Spectral density (Hybrid system in Inquiry mode / Page scan)

§15.247(d)


 Marker 1 [T1 NOI] RBW 3 kHz RF Att 10 dB
 Ref Lvl -49.16 dBm/Hz VBW 3 kHz
 -6.8 dBm 2.44100752 GHz SWT 500 s Unit dBm



Date: 28.AUG.2002 09:17:37

Power density : -49.16 dBm/Hz = -14.36 dBm / 3 KHz

Correction factor from dBm/Hz to dBm/3KHz is +34,8 dB

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Spectrum Bandwidth of a FHSS System

§15.247(a)

20 dB bandwidth

TEST CONDITIONS		20 dB BANDWIDTH (kHz)		
Frequency (MHz)		2402	2441	2480
T _{nom} (25.6)°C	V _{nom} (13.2)V	913.828	955.912	931.864
Measurement uncertainty		±1kHz		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)

RBW: 10 kHz / VBW 10 kHz

LIMIT

SUBCLAUSE §15.247(a) (1)

The maximum 20dB bandwidth shall be at maximum 1000 KHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%


Spectrum Bandwidth of a FHSS System

§15.247(a)

20 dB bandwidth

Channel 1


 Delta 1 [T1] RBW 10 kHz RF Att 10 dB
 Ref Lvl -5.4 dBm -0.81 dB VBW 10 kHz
 913.82765531 kHz SWT 76 ms Unit dBm



Date: 28.AUG.2002 08:28:53

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%


Spectrum Bandwidth of a FHSS System

§15.247(a)

20 dB bandwidth

Channel 2


Delta 1 [T1] RBW 10 kHz RF Att 10 dB
 Ref Lvl -0.48 dB VBW 10 kHz
 -6.4 dBm 955.91182365 kHz SWT 76 ms Unit dBm



Date: 28.AUG.2002 08:30:30

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

Spectrum Bandwidth of a FHSS System
20 dB bandwidth

§15.247(a)

Channel 3:



Date: 28.AUG.2002 14:13:30

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

MAXIMUM PEAK OUTPUT POWER (conducted)

SUBCLAUSE § 15.247 (b) (1)

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (mW)			
Frequency (MHz)		2402		2442	2480
T _{nom} (25)°C	V _{nom} (2.4)V	PK	1.09	0.98	0.82
		AV	0.84	0.76	0.64
De facto EIRP (Peak) (Antenna gain 2.26 dBi)		1.83 (+2.63 dBm)		1.65 (+2.18 dBm)	1.38 (+1.41 dBm)
Measurement uncertainty		±3dB			

RBW / VBW : 3 MHz

Peak / Average value : -1.12 dB

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 21 (75)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

MAXIMUM PEAK OUTPUT POWER

SUBCLAUSE § 15.247 (b) (1)

(conducted)

Channel 1



Marker 1 [T1]

RBW 3 MHz RF Att 30 dB

Ref Lvl

0.37 dBm

VBW 3 MHz


10 dBm

2.40180461 GHz

SWT 5 ms

Unit

dBm



Date: 28.AUG.2002 07:48:56

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 22 (75)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

MAXIMUM PEAK OUTPUT POWER

SUBCLAUSE § 15.247 (b) (1)

(conducted)

Channel 2



Marker 1 [T1]

RBW 3 MHz RF Att 30 dB

Ref Lvl

-0.08 dBm

VBW 3 MHz


10 dBm

2.44078457 GHz

SWT 5 ms

Unit

dBm



Date: 28.AUG.2002 07:47:18

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

MAXIMUM PEAK OUTPUT POWER

SUBCLAUSE § 15.247 (b) (1)

(conducted)

Channel 3



Marker 1 [T1]

RBW 3 MHz RF Att 30 dB

Ref Lvl -0.85 dBm

VBW 3 MHz

10 dBm


2.47978457 GHz

SWT

5 ms

Unit

dBm



Date: 28.AUG.2002 07:48:14

LIMIT

SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

**MAXIMUM PEAK OUTPUT POWER
(RADIATED)****SUBCLAUSE § 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (mW) EIRP		
Frequency (MHz)		2402	2441	2480
T _{nom} (25.7)°C	V _{nom} (13.2)V	1.80	1.69	1.37
Maximum deviation from output power under extreme test conditions (dBc)		not applicable	not applicable	not applicable
Measurement uncertainty		±3dB		

RBW/VBW : 3 MHz**Measured at a distance of 3m****LIMIT****SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

RF EXPOSURE CALCULATION**SUBCLAUSE § 15.247 (B) (4)****The maximal power density at 20cm distance is calculated as: $P_d = (P_{out} * G)/(4\pi * r^2)$**

$1.8\text{mW} / 4\pi 400\text{cm}^2 = 0.000358 \text{ mW/cm}^2$

The Limit for general population/uncontrolled exposures according §1.1307(b) is 1mW/cm²**REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)**

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 25 (75)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

Band-edge compliance of conducted emissions

§15.247 (c)

Low frequency section (hopping off)



Date: 28.AUG.2002 08:25:22

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C


Relative humidity : 55%

Band-edge compliance of conducted emissions

§15.247 (c)

Low frequency section (hopping on)

 Marker 1 [T1] RBW 100 kHz RF Att 10 dB
 Ref Lvl 56.84 dBμV VBW 100 kHz
 110 dBμV 2.39996994 GHz SWT 28 ms Unit dBμV



Date: 28.AUG.2002 08:24:38

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

Band-edge compliance of conducted emissions

§15.247 (c)

high frequency section (hopping off)




Date: 28.AUG.2002 08:03:52

Page 28 (75)

Relative humidity : 55%

§15.247 (c)

	Ref Lvl	Delta 1 [T1]	RBW	100 kHz	RF Att	10 dB
	110 dBμV	54.66 dB	VBW	100 kHz		
		-3.80661323 MHz	SWT	62 ms	Unit	dBμV



Date: 28.AUG.2002 08:12:02


17 - 24

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Band-edge compliance radiated



Date: 28.AUG.2002 15:13:54

Limit Line 54 dBμV/m


REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Band-edge compliance radiated



Date: 28.AUG.2002 15:12:31

This measurement was made to show that the behavior of the system is conform to

FCC 15.205 (restricted bands)


REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Band-edge compliance radiated



Date: 28.AUG.2002 14:43:07

This measurement was made to show that the behavior of the system is conform to

FCC 15.205 (restricted bands)


REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

Band-edge compliance radiated



Date: 28.AUG.2002 14:43:07

This measurement was made to show that the behavior of the system is conform to FCC 15.205 (restricted bands)

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

EMISSION LIMITATIONS					
f (MHz)		amplitude of emission (dBm)	limit max. allowed emmission power	actual attenuation below frequency of operation (dB)	results
2402		+0.37	30 dBm	-	Operating frequency
1201		-50.52	-20 dBc	-50.89	complies
2441		-0.08	30 dBm	-	Operating frequency
1220.5		-51.35	-20 dBc	-51.27	complies
					complies
2480		-0.85	30 dBm		Operating frequency
1240		-50.27	-20 dBc	-49.42	complies
3720		-56.26	-20 dBc	-55.41	complies
Measurement uncertainty		± 3dB			

RBW : 100 kHz VBW: 1 MHz

For emissions that fall into restricted bands you find the radiated emissions later in the report.

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 34 (75)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

Channel 1: - 25 GHz



Date: 28.AUG.2002 07:51:05

RBW:100 kHz / VBW: 1MHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

Channel 2:- 25 GHz



Date: 28.AUG.2002 07:55:46

RBW:100 kHz / VBW: 1MHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS- Conducted (Transmitter)

§ 15.247 (c) (1)

Channel 3: 30 MHz – 25 GHz



Date: 28.AUG.2002 07:58:16

RBW:100 kHz / VBW: 1MHz

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 38 (75)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

**EMISSION LIMITATIONS (Transmitter)
< 1 GHz****SUBCLAUSE § 15.247 (c) (1)****2402 MHz**

Data File : /40703_05.DOC

22 Aug 1902 11:28:27

No	EMISSION	SPEC	MEASUREMENTS			POL	SITE		CORR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE		HGT	AZM		
			dBuV/m	dB			cm	deg	dB	
1	141.5	33.0	21.5	-11.5	PK	V	101	360	N/T	
2	170.7	33.0	20.6	-12.4	PK	H	302	0	N/T	
3	333.8	35.5	27.1	-8.5	PK	V	98	0	N/T	

2441 MHz

Data File : /40703_10.DOC

22 Aug 1902 13:52:17

No	EMISSION	SPEC	MEASUREMENTS			POL	SITE		CORR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE		HGT	AZM		
			dBuV/m	dB			cm	deg	dB	
1	141.5	33.0	21.6	-11.4	PK	V	98	360	N/T	
2	333.8	35.5	26.9	-8.7	PK	V	98	0	N/T	

2480 MHz

Data File : /40703_15.DOC

22 Aug 1902 14:33:06

No	EMISSION	SPEC	MEASUREMENTS			POL	SITE		CORR	COMMENTS
	FREQUENCY MHz		ABS	dLIM	MODE		HGT	AZM		
			dBuV/m	dB			cm	deg	dB	
1	141.5	33.0	22.4	-10.6	PK	V	98	0	N/T	
2	335.5	35.5	25.6	-9.9	PK	V	98	0	N/T	

N/T in CORR FACTOR column denotes a non-traceable signal.


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Frequency	Level QP (dB μ V/m)	Level AV (dB μ V/m)	Limit (dB μ V/m)
1201		33.5 (V)	54.0
1201		31.5 (H)	54.0

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz


 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 40.30 dBμV VBW 1 MHz
 96 dBμV 15.94388778 GHz SWT 34 ms Unit dBμV



Date: 27.AUG.2002 14:14:54

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02 Issue Date: 2002-08-28 Page 43 (75)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2402 MHz


 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 39.30 dBμV VBW 1 MHz
 96 dBμV 24.95791583 GHz SWT 40 ms Unit dBμV



Date: 27.AUG.2002 14:14:12
 f < 1 GHz : RBW/VBW: 100 kHz f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Frequency	Level QP (dB μ V/m)	Level AV (dB μ V/m)	Limit (dB μ V/m)
1220.5		32.4 (H)	54.0
1220,5		32.8(V)	54.0

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%


EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz



Ref Lvl
96 dBµV

RBW 1 MHz RF Att 0 dB
VBW 1 MHz
SWT 34 ms Unit dBµV



Date: 27.AUG.2002 14:12:21

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2441 MHz


 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 39.30 dBµV VBW 1 MHz
 96 dBµV 24.95791583 GHz SWT 40 ms Unit dBµV



Date: 27.AUG.2002 14:12:55

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Frequency	Level QP (dB μ V/m)	Level AV (dB μ V/m)	Limit (dB μ V/m)
1240.0		34.0 (V)	54.0
1240.0		29.8 (H)	54.0

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz


 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 39.47 dBµV VBW 1 MHz
 96 dBµV 15.47494990 GHz SWT 34 ms Unit dBµV



Date: 27.AUG.2002 14:15:58

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

2480 MHz

 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 38.66 dBµV VBW 1 MHz
 96 dBµV 18.37875752 GHz SWT 40 ms Unit dBµV



Date: 27.AUG.2002 14:16:14

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Test report nr.: 4_0703-01-02/02

Issue Date: 2002-08-28

Page 56 (75)

Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109

Radiated

Data File : /40703_20.DOC

22 Aug 1902 15:12:00

No	EMISSION	SPEC	MEASUREMENTS			SITE		CORR	COMMENTS
	FREQUENCY MHz	LIMIT dBuV/m	ABS	dLIM dB	MODE	POL	HGT cm	FACTOR dB	
							AZM deg		
1	141.5	33.0	21.8	-11.2	PK	V	98 360	N/T	

N/T in CORR FACTOR column denotes a non-traceable signal.

SPURIOUS EMISSIONS LEVEL (µV/m)								
CH 1 / 2 / 3								
f (MHz)	Detector	Level (µV/m)	f (MHz)	Detector	Level (µV/m)	f (MHz)	Detector	Level (µV/m)
>1000	no peak	found						
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Measurement distance see table

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

17 - 24


Equipment under test : 8502001

Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109



$f < 1 \text{ GHz}$: RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$: RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109


 Ref Lvl 96 dBμV
 Marker 1 [T1] 38.88 dBμV
 12.43286573 GHz
 RBW 1 MHz
 RF Att 0 dB
 VBW 1 MHz
 SWT 34 ms
 Unit dBμV



Date: 27.AUG.2002 14:17:15

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

Equipment under test : 8502001


Ambient temperature : 25.7°C

Relative humidity : 55%

RECEIVER SPURIOUS RADIATION

§ 15.109


 Marker 1 [T1] RBW 1 MHz RF Att 0 dB
 Ref Lvl 38.44 dBμV VBW 1 MHz
 96 dBμV 23.00801603 GHz SWT 40 ms Unit dBμV



Date: 27.AUG.2002 14:16:54

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits

SUBCLAUSE § 15.109

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED

(for reference numbers see test equipment listing)

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	8566 A	Hewlett-Packard	1925A00257
02	Analyzer Display	8566 A	Hewlett-Packard	1925A00860
03	Oscilloscope	7633	Tektronix	230054
04	Radio Analyzer	CMTA 54	Rohde & Schwarz	894 043/010
05	System Power Supply	6038 A	Hewlett-Packard	2848A07027
06	Signal Generator	8111 A	Hewlett-Packard	2215G00867
07	Signal Generator	8662 A	Hewlett-Packard	2224A01012
08	Funktionsgenerator	AFGU	Rohde & Schwarz	862 480/032
09	Regeltrenntrafo	MPL	Erfi	91350
10	Netznachbildung	NNLA 8120	Schwarzbeck	8120331
11	Relais-Matrix	PSU	Rohde & Schwarz	893 285/020
12	Power-Meter	436 A	Hewlett-Packard	2101A12378
13	Power-Sensor	8484 A	Hewlett-Packard	2237A10156
14	Power-Sensor	8482 A	Hewlett-Packard	2237A00616
15	Modulationsmeter	9008	Racal-Dana	2647
16	Frequenzzähler	5340 A	Hewlett-Packard	1532A03899
17	Absorber Schirmkabine	---	MWB	87400/002
18	Spectrum Analyzer	85660 B	Hewlett-Packard	2747A05306
19	Analyzer Display	85662 A	Hewlett-Packard	2816A16541
20	Quasi Peak Adapter	85650 A	Hewlett-Packard	2811A01131
21	RF-Preselector	85685 A	Hewlett-Packard	2833A00768
22	Biconical Antenne	3104	Emco	3758
23	Log. Per. Antenne	3146	Emco	2130
24	Double Ridge Horn	3115	Emco	3088
25	EMI-Testreceiver	ESAI	Rohde & Schwarz	863 180/013
26	EMI-Analyzer-Display	ESAI-D	Rohde & Schwarz	862 771/008
27	Biconical Antenne	HK 116	Rohde & Schwarz	888 945/013
28	Log. Per. Antenne	HL 223	Rohde & Schwarz	825 584/002
29	Relais-Switch-Unit	RSU	Rohde & Schwarz	375 339/002
30	Highpass	HM985955	FSY Microwave	001
31	Amplifier	P42-GA29	Tron-Tech	B 23602
32	Absorber Schirmkabine		Frankonia	
33	Steuerrechner	PSM 7	Rohde & Schwarz	834 621/004
34	EMI Test Reciever	ESMI	Rohde & Schwarz	827 063/010
35	EMI Test Receiver	Display	Rohde & Schwarz	829 808/010

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
36	Controler	HD 100	Deisel	100/322/93
37	Relais Matrix	PSN	Rohde & Schwarz	829 065/003
38	Control Unit	GB 016 A2	Rohde & Schwarz	344 122/008
39	Relais Switch Unit	RSU	Rohde & Schwarz	316 790/001
40	Power Supply	6032A	Hewlett Packard	2846A04063
41	Spektrum Monitor	EZM	Rohde & Schwarz	883 720/006
42	Meßempfänger	ESH 3	Rohde & Schwarz	890 174/002
43	Meßempfänger	ESVP	Rohde & Schwarz	891 752/005
44	Biconi Ant. 20-300MHz	HK 116	Rohde & Schwarz	833 162/011
45	Logper Ant. 0.3-1 GHz	HL 223	Rohde & Schwarz	832 914/010
46	Amplifier 0.1-4 GHz	AFS4	Miteq Inc.	206461
47	Logper Ant. 1-18 GHz	HL 024 A2	Rohde & Schwarz	342 662/002
48	Polarisationsnetzwerk	HL 024 Z1	Rohde & Schwarz	341 570/002
49	Double Ridge G Horn Antenne 1-26.5 GHz	3115	EMCO	9107-3696
50	Microw. Sys. Amplifier 0.5- 26.5 GHz	8317A	Hewlett Packard	3123A00105
51	Audio Analyzer	UPD	Rohde & Schwarz	1030.7500.04
52	Steuerrechner	PSM 7	Rohde & Schwarz	883 086/026
53	DC V-Netzwerk	ESH3-Z6	Rohde & Schwarz	861 406/005
54	DC V-Netzwerk	ESH3-Z6	Rohde & Schwarz	893 689/012
55	AC 2 Phasen V- Netzwerk	ESH3-Z5	Rohde & Schwarz	861 189/014
56	AC 2 Phasen V- Netzwerk	ESH3-Z5	Rohde & Schwarz	894 981/019
57	AC-3 Phasen V- Netzwerk	ESH2-Z5	Rohde & Schwarz	882 394/007
58	Stromversorgung	6032A	Rohde & Schwarz	2933A05441
59	HF-Test Empfänger	ESVP.52	Rohde & Schwarz	881 487/021
60	Spectrum Monitor	EZM	Rohde & Schwarz	883 086/026
61	HF-Test Empfänger	ESH3	Rohde & Schwarz	881 515/002
62	Relais Matrix	PSU	Rohde & Schwarz	882 943/029
63	Relais Matrix	PSU	Rohde & Schwarz	828 628/007
64	Spectrum Analyzer	FSIQ 26	Rohde & Schwarz	119.6001.27
65	Spectrum Analyzer	HP 8565E	Hewlett Packard	3473A00773
66				

Test site



Test site



Photographs of the equipment

Photograph no.: 1



Photographs of the equipment

Photograph no.: 2



Photographs of the equipment


Photograph no.: 3





Photographs of the equipment

Photograph no.: 5



Photographs of the equipment

Car speaker

Photograph no.: 6



Photographs of the equipment

Car speaker

Photograph no.: 7



Photographs of the equipment

Remote control

Photograph no.: 8



Photographs of the equipment

Microphone

Photograph no.: 9

