



Prepared (also subject responsible if other)

SEM/BGURDBB, Niklas Lövberg

Approved

SEM/BGURDBB (Niklas Lövberg)

Checked

Company Internal
MARKING DRAWING
No.

151 86-SVV 107 201/1 Uen

Date

2004-09-16

Rev

A

Reference

Approved according to 000 21-LXE 107 42/1

J200, KRH-label, Type: AAB-1021061-BV

1

General information

The format of the label is based on label SVF 930 2391.

If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.

All bar codes, when applicable, are according to Ericsson corporate standard 102 01-109 Uen. All bar codes shall fulfil minimum print quality C according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01-1003 Uen. No bar codes are allowed to be closer to a label edge than 2 mm! (quiet zone).

“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (portrait format), both in mm. When needed, the alignment is adjusted to fit the label.

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88-) for the KRH.

2

Printing information

	Content	Format
Line 1 (3,0/1,0)	Line 2a in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 2a (4,6/1,0)	Actual electronic serial number (IMEI) of the phone (KRH), “nnnnnnnn-nnnnnn-n”	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from the 3/151 86- document in the 1095- for the SVV. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 2b (4,6/15,3)	ROA and R-state identification field, “GHY ₁ Y ₂ Y ₃ ”	Text, height 1,2 mm. According to the 3/151 86- document in the 1095- for the SVV.



Prepared (also subject responsible if other)

SEM/BGURDBB, Niklas Lövberg

Approved

SEM/BGURDBB (Niklas Lövberg)

Checked

Company Internal
MARKING DRAWING
No.

151 86–SVV 107 201/1 Uen

Date

Rev

Reference

2004-09-16

A

Content		Format
Line 2c (4,6/21,4)	Production week. “yy’W’ww” (yy = year, ww = week)	Text, height 1,2 mm.
Line 3 (7,1/1,0)	Line 4a in bar code. As desired by supplier (e.g. only actual number, with data identifier).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbolology).
Line 4a (8,8/1,0)	Supplier’s identification for trace-ability of the included telephone, as desired by supplier, (e.g. “nnn....” for serial number).	Text, height 1,2 mm. Defined by supplier.
Line 4b (8,8/9,9)	Actual product number without R-state of the DPY kit in which the phone is packed, if applicable. Printed without “DPY 101”, “nnnn/nnn”	Text, height 1,2 mm.
Line 4c (8,8/16,4)	Marking of origin.	Text, height 1,2 mm. The line shall be printed as stated in the 1/151 86- document in the 1095- for the SVV, if any.
Line 5 (11,2/1,0)	Sony Ericsson stylized name.	Graphics, height 2,0 mm. According to 190 89–EN/LZT 108 5347.
Line 6 (12,8/1,0)	Type number of the phone (KRH), “Type: AAB-1021061-BV”.	Text, height 1,2 mm.
Line 7a (14,9/1,0)	“FCC ID: PY7A1021061	Text, height 1,2 mm.
Line 7b (14,9/16,1)	Actual location code of where the phone is flashed, if applicable, “XXX”	Text, height 1,2 mm. According to the 1050-LZT 108 6537 Uen.
Line 8 (17,1/1,0)	“IC: 4170B-A1021061”	Text, height 1,2 mm.
Line 9a (19,0/1,0)	Actual model name, “J200i”	Text, height 1,5 mm.
Line 9b (19,0/5,8)	Repair week, if applicable. “Ry’W’ww” (y = year, ww = week)	Text, height 1,2 mm.
Line 10a (24,7/1,0)	“CE” approval symbol.	Graphics, height 5 mm. According to SVF 930 52.
Line 10b (24,7/8,1)	“0682”	Text, height 2,0 mm.
Line 11 (31,5/*)	Additional field/lines.	The field shall be left blank unless otherwise stated in a separate 2/151 86– document in the 1095- of the actual SVV.

Prepared (also subject responsible if other)

SEM/BGURDBB, Niklas Lövberg

Approved

SEM/BGURDBB (Niklas Lövberg)

Checked

Company Internal
MARKING DRAWING

No.

151 86–SVV 107 201/1 Uen

Date

Rev

Reference


2004-09-16

A

3 Layout

The conceptual picture (for Zebra 90Xill printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



double underlined = changed since last revision.