

Prepared (also subject responsible if other)
SEM/BGLDC, (Yulin Cheng)
Approved
SEM/BGLDC, (Yulin Cheng)

Company Internal MARKING DRAWING

151 86–SVV 107 747/13 Uen

Date Rev Reference

2007-11-05 B

3

Approved according to 000 21-LXE 107 42/1

Checked

K530c, KRH-label, CN, Made in- in ZS

1 General information

The format of the label is based on a label SVF 930 2406 (40,4 x 31,4 mm). If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.

All bar codes, when applicable, are according to Ericsson corporate standard 102 01–109 Uen. All bar codes shall fulfil minimum print quality C according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen. No bar codes are allowed to be closer to a label edge than 2 mm! (quiet zone).

"(x/y)" under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88-) for the KRH.

2 Printing information

	Content	Format
Line 1 (1,0/29,0)	SIM-card logo	Graphics, height 7,3 mm. According to 1424-SVF 930 1418. Rotated 90° Clockwise.
Line 2 (13,2/28,9)	CCC-sticker with S&E.	Graphics, outside diameter: height 5,5 mm, width 7,1 mm. According to 1424-SVF 930 2413.
Line 3 (17,5/29,6)	GSM/GPRS 移动电话机	Text, height 1,5 mm.
Line 4a (20,5/1,0)	Sony Ericsson stylized name.	Graphics, height 2,0 mm. According to 190 89–EN/LZT 108 5347
Line 4b (20,5/17,0)	Product number of the DPY kit in which the phone is packed. Printed without R-state, "DPY 101 0000/000"	Text, height 1,2 mm.
Line 4c (20,0/29,5)	Marking of origin. The line shall be printed as stated in chapter 3 in this document	Text, height 1,2 mm.



Prepared (also subject responsible if other)

SEM/BGLDC, (Yulin Cheng)

SEM/BGLDC, (Yulin Cheng)

Company Internal MARKING DRAWING

151 86-SVV 107 747/13 Uen

te Rev Reference

2007-11-05 B

Checked

	Content	Format
Line 5a (22,7/1,0)	Type number of the phone (KRH), "Type: AAB-1022131-BV"	Text, height 1,2 mm.
Line 5b (22,7/16,6)	ROA and R-state identification field, "FG"	Text, height 1,2 mm. According to the 3/151 86- document in the 1095- for the SVV.
Line 5c (22,7/22,0)	Location code of where the phone is flashed, if applicable, "FFF"	Text, height 1,2 mm. According to 1050-LZT 108 6537.
Line 5d (22,7/24,0)	Production week (flash), "yy'W'ww" (yy = year, ww = week)	Text, height 1,2 mm.
Line 5e (22,7/30,6)	Repair week, if applicable. "Ry'W'ww" (y = year, ww = week)	Text, height 1,2 mm.
Line 6a (24,5/1,0)	Country approval mark 1 "FCC ID: PY7A1022131"	Text, height 1,2 mm.
Line 6b (24,5/14,0)	Country approval mark 2 "IC: 4170B-A1022131"	Text, height 1,2 mm.
Line 7a (25,6/38,4)	"CMII ID: 2007CJ3503"	Text, height 1,2 mm. Rotated 90°counter-clockwise.
Line 7b (25,6/38,1)	Frame around line 7a.	Graphics. Rotated 90°counter-clockwise.
Line 8 (26,7/2,0)	Line 9a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 9a (28,7/1,0)	Supplier's identification for trace- ability of the telephone, as desired by supplier (e.g. "S/N: nnn" for serial number).	Text, height 1,2 mm. Defined by supplier.
Line 9b (28,7/13,0)	Actual electronic serial number (IMEI) of the phone (KRH), "00000000-000000-0"	Text, height 2,0 mm. In the format TAC-SNR-CD. TAC and SNR derived from the 3/151 86- document in the 1095- for the SVV. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 9c (28,7/27,5)	CE approval symbol.	Graphics, height 5 mm. According to 1424-SVF 930 52.
Line 9d (28,7/34,5)	The Notified body number. "0682"	Text, height 2,0 mm.



Prepared (also subject responsible if other)

SEM/BGLDC, (Yulin Cheng)

SEM/BGLDC, (Yulin Cheng)

Company Internal MARKING DRAWING

151 86-SVV 107 747/13 Uen

te Rev Reference

2007-11-05 B

3

	Content	Format
Line 10	索尼爱立信移动通信产品(中国)有限公司	Text, height 2,0 mm.
(30,2/40,4)	系尼发立后移动地信广即(中国)有限公司	Rotated 90°counter-clockwise.
		Bar code, height 2,0 mm.
Line 11a	Line 9b in bar code (only actual	Code 128 symbology, code C subset. If
(30,7/2,0)	number, without data identifier).	uneven number of digits, code B subset
		shall be used for the last digit.
Line 11b	"Model" in Chinese Simplified;	Text, height 2,0 mm.
(30,7/27,8)	"型号:"	Text, fieight 2,0 min.
Line 11b	Model name "VE20e"	Toyt hoight 1.2 mm
(30,7/30,9)	Model name, "K530c"	Text, height 1,2 mm.

3 Marking of Origin

3.1 Content


Made in China in ZS: 中国制造

The text or graphics according to 1424-SVF 930 1350/1Uen.

4 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

4.1 Conceptual picture



<u>double underlined</u> = major changes since last revision.



Prepared (also subject responsible if other)

SEM/BGLDC, (Yulin Cheng)

SEM/BGLDC, (Yulin Cheng)

Company Internal MARKING DRAWING

151 86-SVV 107 747/13 Uen

ate Rev Reference

2007-11-05 B

3

4.2 Label placement

To find the label follow these steps:

Checked

- 1. Remove the cover on the rear side of the product.
- 2. Remove the battery.
- 3. The label is located behind the battery.

