

Confidential MARKING DRAWING 1(3)

Prepared		Date	Rev	Doc no.
RT/SEM/CA/KA Jeff Chlebowski		2003-11-18	Α	1/151 86-DPY 101 1431
Approved	Checked			File
CA/KA (Jeff Chlebowski)				

1/151 86-DPY 101 1431 Marking Drawing For T637

Type AAB-1031012-BV.

Label

The Label used for marking is defined in the Manufacturing Specification 1301-SVF 930 2239.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88 KRH 101 166) for the KRH.

Print Layout

Sony Ericsson		Model Number		
Type number	GHY ¹ fields			Sony Ericsson
Country appro	val mark 1 Country a	approval mark 2	2	Type AAB-1031012-BV
IMEI-numbers	as barcode	• •	※ 뭐	[FCC ID: PY7A1031012] IC:
IMEI-numbers	as characters		풀쥐	
Serial number	as barcode		PY nu larkino	00100300-099207-6
Serial number	as characters		numb ina of	
				CRECONTITO
	Prod / Repair wk as	s characters	er, R-s Oriain	0000
CE Marking	Prod wk as barcode	е	in (-s	€ 11682 m
			state	- 000F II
			ወ	



1637

03W45

*Note: representative sample, text in image may not match required information for this product defined in table below.

Definitions

Cany Friedon trademark	Cany Friedon tradomark shall be according to the
Sony Ericsson trademark	Sony Ericsson trademark shall be according to the
	corporate standard 190 89-EN/LZT 108 5347.
Model number	The model number is T637 and shall be printed
	"T637"
Type number	The type number is AAB-1031012-BV and shall be
"	printed "Type AAB-1031012-BV"
G-field	R-state identification of the CXC 112 2713-module
	according to the Marking data 1/151 86 for the KRH.
H-field	R-state identification of the KRH according to the
	Marking data 1/151 86 for the KRH.
Y ¹ -field	R-state identification of the ROA according to the
	Marking data 1/151 86 for the KRH.
Country approval mark 1	Consist of text: FCC ID: PY7A1031012
	Within a frame with height > 1,5 mm.



Confidential MARKING DRAWING 2(3)

				· ,
Prepared		Date	Rev	Doc no.
RT/SEM/CA/KA Jeff Chlebowski		2003-11-18	Α	1/151 86-DPY 101 1431
Approved	Checked			File
CA/KA (Jeff Chlebowski)				

IMEI number as barcode	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -).	
IMEI number as characters	See the 1/151 86-KRH 101 166 (latest revision). The IMEI number has format: 01AAAAAA-BBBBBB-C AAAAAA = TAC BBBBBB = assigned serial number C = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.	
Serial number as barcode	According to Ericsson corporate standard 102 01 - 109.	
Serial number as characters	According to Ericsson group standard 0012-101. Ericsson group factory number system according the Ericsson corporate standard 1120-101	
Production week (Prod wk)	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.	
Production week as barcode	According to Ericsson corporate standard 102 01 - 109.	
Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)	
Reduced DPY	The reduced product number of the DPY including the R-state: 1431/XX RXX	
Marking of origin	"Made in" statement should reflect the country of origin of the KRC (i.e. Made in China).	
CE Marking	1. According to 1424 - SVF 930 52	
	2. The notified body number from the type approval certificate, 0682. The print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.	

<u>Print regulations</u>
The printing shall be well readable and permanent.

Typeface Type size OCR-B min 1.1 mm Line spacing min 1.5 mm Trademark ` min 1.5 mm Approval Marks min 5.0 mm



Confidential MARKING DRAWING 3(3)

RT/SEM/CA/KA Jeff Chlebowski		Date 2003-11-18	Rev A	Doc no. 1/151 86-DPY 101 1431
Approved CA/KA (Jeff Chlebowski)	Checked			File

Product Listing

In the event that this marking drawing is to be used for the production of DPA units please use the following chart for crossreferencing the DPA number to the reduced DPY number that shall appear on the KRH label.

Product Number	Associated DPA	Customer
DPY 1431/11	TBD	Generic T637
DPY 1431/30	TBD	Cingular
DPY 1431/54	TBD	AWS

Revision History

Revision	Reason	Originator
PA1	Initial Release	Jeff Chlebowski
PA2	Corrected txt referring to G, H, Y	Jeff Chlebowski
	fields to read "KRH" versus "KRC."	
PA3	Referred to 1/151 86 KRH 101 166	Jeff Chlebowski
	for IMEI range.	
	Removed "T637" and "DPY" from	
	label.	
PA4	Replaced label graphic.	Jeff Chlebowski