

Prepared (also subject responsible if other)

SEM/BGLDB, Patrik Jonsson

SEM/BGLDB (Patrik Jonsson)

Company Internal MARKING DRAWING

1202-8703 Uen

Rev

Reference

2007-07-26 1

6

Approved according to 000 21-LXE 107 42/1

Checked

Mobile Phone label content, No mark of origin

1 General information

Core Unit label part no	1200-3698		
Bar code	Standard: according to Ericsson corporate standard 102 01–109 Uen		
	 Print quality: C, according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01– 1003 Uen 		
	Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!		
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.		
Coordinates	"(x/y)" under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.		

MLCI= Main Label Content Information-document.

2 Printing information

	Content	Format
Line 1a (2,2/12,0)	Sony Ericsson stylized name.	Graphics, height 1,5 mm. According to 1200-1925.
Line 1b (2,2/26,0)	Model Name "W908c"	Text, height 1,2 mm.
Line 2a (4,5/12,0)	Product number without revision of the Sales Item in which the phone is packed, if applicable. "SI XXXX-XXXX"	Text, height 1,2 mm.
Line 2b (4,5/26,0)	Repair week, if applicable. "Ry'W'ww" (y = year, ww = week)	Text, height 1,2 mm.
Line 2c (4,5/33,0)	Location code of where the phone is flashed, if applicable, "XXX"	Text, height 1,2 mm.
Line 3a (6,5/12,0)	"TYPE: AAC-1052051-BV"	Text, height 1,2 mm
Line 3b (6,5/30,0)	HW & SW identification field, if applicable; "FG"	Text, height 1,2 mm. According to Type-testing report in BOM pos 1C.
Line 3c (6,5/33,0)	Production week (flash), "yy'W'ww" (yy = year, ww = week)	Text, height 1,2 mm.
Line 4a (8,5/12,0)	"FCC ID: PY7A1052051"	Text, height 1,2 mm.
Line 4b (8,5/26,0)	"IC: 4170B-A1052051"	Text, height 1,2 mm.
Line 5a (9,0/5,0)	SIM-card logo	Graphics height 8,0mm According to 1200-3991 document
Line 6 (11,5/2,6)	Line 7a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 7a (13,0/1,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn" for serial number).	Text, height 1,2 mm. Defined by supplier.

6



Prepared (also subject responsible if other)

SEM/BGLDB, Patrik Jonsson

SEM/BGLDB (Patrik Jonsson)

Company Internal MARKING DRAWING

1202-8703 Uen

Checked

Date Rev Reference


2007-07-26 1

		_
	Content	Format
Line 7b (13,0/18,0)	Actual electronic serial number (IMEI) of the Mobile Phone, "00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 8 (16,5/2,6)	Line 7b in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 9a (34,0/29,0)	CE approval symbol	Graphics, height 5 mm. According to 1202-5482.
Line 9b (34 0/36 5)	The notified body number "0682"	Text, height 1,2 mm.

3 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



<u>double underlined</u> = major changes since last revision.



Prepared (also subject responsible if other)

SEM/BGLDB, Patrik Jonsson

SEM/BGLDB (Patrik Jonsson)

Company Internal MARKING DRAWING

1202-8703 Uen

Date Rev Reference

2007-07-26 1

3.1 Label placement

To find the label follow these steps:

Checked

- 1. Remove the cover on the rear side of the product.
- 2. Remove the battery.
- 3. The label is located under the battery.

