



## **Accredited testing-laboratory**

**DAR registration number: DAT-P-176/94-D1**

**Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97**

**Recognized by the Federal Communications Commission**

**Anechoic chamber registration no.: 90462 (FCC)**

**Anechoic chamber registration no.: 3463A-1 (IC)**

**Certification ID: DE 0001**

**Accreditation ID: DE 0002**

**Accredited Bluetooth® Test Facility (BQTF)**

*The Bluetooth word mark and logos are owned by the Bluetooth SIG,  
Inc. and any use of such marks by Cetecom ICT is under license*

**Test report no. : 2-4883-18-08/08-A**  
**Type identification : AAD-3132011-BV**  
**Applicant : Sony Ericsson Mobile Communications AB**  
**FCC ID : PY7A3132011**  
**IC Certification No : 4170B-A3132011**  
**Test standards : 47 CFR Part 27**

---

## Table of contents

<b>1</b>	<b>General information</b>	<b>3</b>
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of applicant	4
1.4	Application details	4
<b>2</b>	<b>Test standard/s:</b>	<b>5</b>
<b>3</b>	<b>Technical tests</b>	<b>5</b>
3.1	Details of manufacturer	5
3.1.1	Test item	5
3.2	Test Setup	6
<b>4</b>	<b>Statement of Compliance</b>	<b>7</b>
4.1	Summary of Measurement Results	7
4.1.1	UMTS FDD IV	7
<b>5</b>	<b>Measurements and results</b>	<b>8</b>
5.1	PART UMTS FDD IV	8
5.1.1	RF Output Power Conducted	8
5.1.2	RF Output Power Radiated	9
5.1.3	Frequency Stability	11
5.1.4	Radiated Emissions	14
5.1.5	Receiver Radiated Emissions	21
5.1.6	Conducted Spurious Emissions	27
5.1.7	Block Edge Compliance	31
5.1.8	Occupied Bandwidth	33
<b>6</b>	<b>Test equipment and ancillaries used for tests</b>	<b>37</b>

---

## 1 General information

### 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

**Test laboratory manager:**

2008-04-10

Jakob Reschke

Date

Name

Signature



**Technical responsibility for area of testing:**


2008-04-10

Michael Berg

Date

Name

Signature



## 1.2 Testing laboratory

CETECOM ICT Services GmbH  
Untertürkheimer Straße 6 - 10  
66117 Saarbrücken  
Germany  
Phone: + 49 681 5 98 - 0  
Fax: + 49 681 5 98 - 9075  
e-mail: info@ICT.cetecom.de  
Internet: http://www.cetecom-ict.de

State of accreditation: The test laboratory (area of testing) is accredited according to  
DIN EN ISO/IEC 17025  
DAR registration number: DAT-P-176/94-D1

Accredited by: Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97

Testing location, if different from CETECOM ICT Services GmbH:

Name :  
Street :  
Town :  
Country :  
Phone :  
Fax :

## 1.3 Details of applicant

<b>Name:</b>	<b>Sony Ericsson Mobile Communications AB</b>
<b>Street:</b>	<b>Nya Vattentornet</b>
<b>Town:</b>	<b>22188 Lund</b>
<b>Country:</b>	<b>Sweden</b>
<b>Telephone:</b>	<b>+46-46-19-3000</b>
<b>Fax:</b>	<b>+46-46-19-3295</b>
<b>Contact:</b>	<b>Peter Lindeborg</b>
<b>E-mail:</b>	<b>peter.lindeborg@sonyericsson.com</b>
<b>Telephone:</b>	<b>+46-46-212-6180</b>

## 1.4 Application details

<b>Date of receipt of order:</b>	<b>2008-03-17</b>
<b>Date of receipt of test item:</b>	<b>2008-03-24</b>
<b>Date of start test:</b>	<b>2008-03-24</b>
<b>Date of end test:</b>	<b>2008-04-10</b>
<b>Persons(s) who have been present during the test:</b>	<b>-/-</b>

**2 Test standard/s:**

47 CFR Part 27                                      2006-10                      Title 47 of the Code of Federal Regulations Part 27-  
Miscellaneous wireless communications services; subpart C/L

**3 Technical tests**

**3.1 Details of manufacturer**

Name:	Sony Ericsson Mobile Communications AB
Street:	Nya Vattentornet
Town:	22188 Lund
Country:	Sweden

**3.1.1 Test item**


Kind of test item	:	GSM 850/1800/1900/UMTS/HSDPA/BT/AGPS
Type identification	:	AAD-3132011-BV
Serial Number	:	Rad. BX90088J0Z Cond. BX90087AA8
Frequency Bands	:	1712.4 – 1752.6 MHz
Type of modulation	:	QPSK / 16QAM
Emission Designator	:	4M76F9W
Number of channels	:	201 (FDD IV)
Antenna Type	:	Integrated antenna
Power supply (normal)	:	DC by Li-Polymer Battery (CBA-0001003)
Output power UMTS FDD IV/WCDMA:		cond.: 26.19 dBm (Peak) EIRP: 26.41 dBm (Burst)
Transmitter Spurious (worst case)		Nothing found
Receiver Spurious (worst case)		Nothing found
FCC ID	:	PY7A3132011

**ATTESTATION:**

**DECLARATION OF COMPLIANCE:**

I declare that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned Industry Canada standard(s); and that the equipment identified in this application has been subjected to all the applicable test conditions specified in the Industry Canada standards and all of the requirements of the standard have been met.

**Laboratory Manager:**

2008-04-10	Jakob Reschke	
Date	Name	Signature

### 3.2 Test Setup

Hardware : A  
Software : -/-

Mobile; (cond. measurements): BX90087AA8  
Mobile; (rad. measurements) : BX90088J0Z

The radiated measurements were performed with standard world wide charger.

## 4 Statement of Compliance

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

### 4.1 Summary of Measurement Results

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

#### 4.1.1 UMTS FDD IV

Section in This Report	Test Name	Verdict
5.1.1	RF Power Output Conducted	pass
5.1.2	RF Power Output Radiated	pass
5.1.3	Frequency Stability	pass
5.1.4	Radiated Emissions	pass
5.1.5	Receiver Radiated Emissions	pass
5.1.6	Conducted Spurious Emissions	pass
5.1.7	Block Edge Compliance	pass
5.1.8	Occupied Bandwidth	pass

## 5 Measurements and results

### 5.1 PART UMTS FDD IV

#### 5.1.1 RF Output Power Conducted

##### Reference

FCC:	CFR Part 27.1101, 2.1046
------	--------------------------

##### Summary:

This paragraph contains both average and peak output power measurements for the EUT. In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

##### Method of Measurements:

The EUT was set up for the max. output power with pseudo random data modulation. The power was measured with R&S Signal Analyzer FSIQ 26 (peak and average) These measurements were done at 3 frequencies, 1712.4 MHz, 1732.4 MHz and 1752.6 MHz (bottom, middle and top of operational frequency range).

##### Limits:

Nominal Peak Output Power (dBm)
+30

##### Test Results: Output Power (conducted) UMTS Mode

Frequency (MHz)	Peak Output Power (dBm)	Average Output Power (dBm)
1712.4	26.06	23.51
1732.4	26.04	23.43
1752.6	26.19	23.59
Measurement uncertainty	±0.5 dB	



### 5.1.2 RF Output Power Radiated

#### Reference

FCC:	CFR Part 27.1101, 2.1046
------	--------------------------

#### Summary:

In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

#### Method of Measurements:

The power was measured with R&S Signal Analyzer FSIQ 26 (peak)

These measurements were done at 3 frequencies, 1712.4 MHz, 1732.4 MHz and 1752.6 MHz (bottom, middle and top of operational frequency range).

#### ERP Measurements

Description: This is the test for the maximum radiated power from the phone.

Rule Part 22.913 specifies that "Mobile/portable stations are limited to 7 watts ERP.

Measuring the EIRP of Spurious/Harmonic Emissions using Substitution Method

(a) The measurements were performed with full rf output power and modulation.

(b) Test was performed at listed 3m test site (listed with FCC, IC).

(c) The transmitter under test was placed at the specified height on a non-conducting turntable (80 cm height)

(d) The BICONILOG antenna (20 MHz to 1 GHz) or HORN antenna (1 GHz to 18 GHz) was used for measuring.

(e) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor

$E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

(f) Set the EMI Receiver and #2 as follows:

Center Frequency: test frequency

Resolution BW: 100 kHz

Video BW: same

Detector Mode: positive

Average: off

Span: 3 x the signal bandwidth

(g) The test antenna was lowered or raised from 1 to 4 meters until the maximum signal level was detected.

(h) The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.

(i) The test antenna was lowered or raised again from 1 to 4 meters until a maximum was obtained. This level was recorded.

(j) The recorded reading was corrected to the true field strength level by adding the antenna factor, cable loss and subtracting the pre-amplifier gain.

(k) The above steps were repeated with both transmitters' antenna and test receiving antenna placed in vertical and horizontal polarization. Both readings with the antennas placed in vertical and horizontal polarization shall be recorded.

(l) Repeat for all different test signal frequencies

**Measuring the ERP of Spurious/Harmonic Emissions using Substitution Method**

(a) Set the EMI Receiver (for measuring E-Field) and Receiver #2 (for measuring ERP) as follows:

- Center Frequency : equal to the signal source
- Resolution BW : 10 kHz
- Video BW : same
- Detector Mode : positive
- Average : off
- Span : 3 x the signal bandwidth

(b) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor

$E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

(c) Select the frequency and E-field levels for ERP/EIRP measurements.

(d) Substitute the EUT by a signal generator and one of the following transmitting antennas (substitution antenna): .DIPOLE antenna for frequency from 30-1000 MHz or .HORN antenna for frequency above 1 GHz }.

(e) Mount the transmitting antenna at 1.5 meter high from the ground plane.

(f) Use one of the following antenna as a receiving antenna: .DIPOLE antenna for frequency from 30-1000 MHz or .HORN antenna for frequency above 1 GHz }.

(g) If the DIPOLE antenna is used, tune its elements to the frequency as specified in the calibration manual.

(h) Adjust both transmitting and receiving antenna in a VERTICAL polarization.

(i) Tune the EMI Receivers to the test frequency.

(j) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.

(k) The transmitter was rotated through 360 o about a vertical axis until a higher maximum signal was received.

(l) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.

(m) Adjust input signal to the substitution antenna until an equal or a known related level to that detected from the transmitter was obtained in the test receiver.

(n) Record the power level read from the Average Power Meter and calculate the ERP/EIRP as follows:

$$P = P1 - L1 = (P2 + L2) - L1 = P3 + A + L2 - L1$$

$$\text{EIRP} = P + G1 = P3 + L2 - L1 + A + G1$$

$$\text{ERP} = \text{EIRP} - 2.15 \text{ dB}$$

Total Correction factor in EMI Receiver # 2 =  $L2 - L1 + G1$

Where: P: Actual RF Power fed into the substitution antenna port after corrected.

P1: Power output from the signal generator

P2: Power measured at attenuator A input

P3: Power reading on the Average Power Meter

EIRP: EIRP after correction

ERP: ERP after correction

(o) Adjust both transmitting and receiving antenna in a HORIZONTAL polarization, then repeat step (k) to (o)

(p) Repeat step (d) to (o) for different test frequency

(q) Repeat steps (c) to (j) with the substitution antenna oriented in horizontal polarization.

(r) Actual gain of the EUT's antenna is the difference of the measured EIRP and measured RF power at the RF port. Correct the antenna gain if necessary.

**Limits:**

Nominal Peak Output Power (dBm)
+30

**Test Results: Output Power (radiated) GMSK Mode**

Frequency (MHz)	Burst Peak EIRP (dBm)
1712.4	26.41
1732.4	26.30
1752.6	26.22
Measurement uncertainty	±1.5 dB

---

### 5.1.3 Frequency Stability

#### Reference

FCC:	CFR Part 27.54, 2.1055
------	------------------------

#### Method of Measurement:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a "call mode". This is accomplished with the use of a R&S CMU 200 DIGITAL RADIOCOMMUNICATION TESTER..



1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with 3.7 Volts, connected to the CMU 200 and in a simulated call on channel 661 (centre channel), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10 C increments from -30 C to +60 C. Allow at least 1 1/2 hours at each temperature, un-powered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal 3.7 Volts. Vary supply voltage from minimum 3.3 Volts to maximum 4.4 Volts, in 13 steps re-measuring carrier frequency at each voltage. Pause at 3.7 V ac Volts for 1 1/2 hours un-powered, to allow any self heating to stabilize, before continuing.
6. Subject the mobile station to overnight soak at +60 C.
7. With the mobile station, powered with 3.7 Volts, connected to the CMU 200 and in a simulated call on channel 661(center channel), measure the carrier frequency. These measurements should be made within 2 minutes of powering up the mobile station, to prevent significant self warming.
8. Repeat the above measurements at 10 C increments from +60 C to -30 C. Allow at least 1 1/2 hours at each temperature, un-powered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5 C during the measurement procedure.

**Test Results: AFC FREQ ERROR vs. VOLTAGE**

Voltage (V)	Frequency Error (Hz)	Frequency Error (%)	Frequency Error (ppm)
3.3	-16	-0,00000085	-0,0085
3.4	-21	-0,00000112	-0,0112
3.5	-15	-0,00000080	-0,0080
3.6	-21	-0,00000112	-0,0112
3.7	-10	-0,00000053	-0,0053
3.8	-24	-0,00000128	-0,0128
3.9	-33	-0,00000176	-0,0176
4.0	-22	-0,00000117	-0,0117
4.1	-20	-0,00000106	-0,0106
4.2	-21	-0,00000112	-0,0112
4.3	-14	-0,00000074	-0,0074
4.4	-22	-0,00000117	-0,0117

**Test Results: AFC FREQ ERROR vs. TEMPERATURE**

TEMPERATURE (°C)	Frequency Error (Hz)	Frequency Error (%)	Frequency Error (ppm)
-30	-33	-0,00000176	-0,0176
-20	-53	-0,00000282	-0,0282
-10	-50	-0,00000266	-0,0266
±0.0	-54	-0,00000287	-0,0287
+10	-49	-0,00000261	-0,0261
+20	-38	-0,00000202	-0,0202
+30	-59	-0,00000314	-0,0314
+40	-63	-0,00000335	-0,0335
+50	-46	-0,00000245	-0,0245
+60	-31	-0,00000165	-0,0165



#### 5.1.4 Radiated Emissions

##### Reference

FCC:	CFR Part 27.53(g), 2.1053
------	---------------------------

##### Measurement Procedure:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2003 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1752.6 MHz. This was rounded up to 12 GHz. The resolution bandwidth is set as outlined in Part 27.54. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the UMTS band.

The final open field emission ( here 10m semi-anechoic chamber listed by FCC) test procedure is as follows:

- a) The test item was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna.
- b) The antenna output was terminated in a 50 ohm load.
- c) A double ridged wave guide antenna was placed on an adjustable height antenna mast 3 meters from the test item for emission measurements.
- d) Detected emissions were maximized at each frequency by rotating the test item and adjusting the receive antenna height and polarization. The maximum meter reading was recorded. The radiated emission measurements of the harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1 MHz bandwidth. If the harmonic could not be detected above the noise floor, the ambient level was recorded. The equivalent power into a dipole antenna was calculated from the field intensity levels measured at 3 meters using the equation shown below:
- e) Now each detected emissions were substituted by the Substitution method, in accordance with the TIA/EIA 603 .

##### Measurement Limit:

Sec. 27.54 Emission Limits.

(g) On any frequency outside a licensee' s frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

**Measurement Results:**

Radiated emissions measurements were made only at the upper, center, and lower carrier frequencies of the UMTS band (1712.4 MHz, 1732.4 MHz and 1752.6 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the UMTS band into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

The final open field radiated levels are presented on the next pages.

All measurements were done in horizontal and vertical polarization, the plots shows the worst case.

As can be seen from this data, the emissions from the test item were within the specification limit.

Harmonic	Tx ch.-1312 Freq. (MHz)	Level (dBm)	Tx ch.-1412 Freq. (MHz)	Level (dBm)	Tx ch.-1513 Freq. (MHz)	Level (dBm)
2	3424.8	-	3464.8	-	3505.2	-
3	5137.2	-	5197.2	-	5257.8	-
4	6849.6	-	6929.6	-	7010.4	-
5	8562.0	-	8662.0	-	8763.0	-
6	10274.4	-	10394.4	-	10515.6	-
7	11986.8	-	12126.8	-	12268.2	-
8	13699.2	-	13859.2	-	14020.8	-
9	15411.6	-	15591.6	-	15773.4	-


**Sample calculation:**

Freq	SA Reading	SG Setting	Ant. gain	Dipol gain	Cable loss	ERP	Substitution Antenna
MHz	dB $\mu$ V	dBm	dBi	dBi	dB	dBm	
1712.4	128.9	18.5	8.4	0.0	3.3	23.6	UHAP Schwarzbeck S/N 460

$ERP = SG \text{ (dBm)} - \text{Cable Loss (dB)} + \text{Ant. gain (dB)}$


\*ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.1\text{dBi}$

Traffic Mode (9 kHz - 30 MHz)





**Channel 1312 (30 MHz - 4 GHz)**




$f < 1 \text{ GHz}$ : RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$ : RBW / VBW 1 MHz


Carrier suppressed with a rejection filter

**Channel 1312 (4 GHz – 12.5 GHz)**




RBW / VBW 1 MHz

Channel 1312 (12 GHz - 25 GHz) valid for all 3 channels and all modes



RBW / VBW 1 MHz

**Channel 1412 (30 MHz - 4 GHz)**




$f < 1 \text{ GHz}$ : RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$ : RBW / VBW 1 MHz


Carrier suppressed with a rejection filter

**Channel 1412 (4 GHz – 12.5 GHz)**



RBW / VBW 1 MHz

**Channel 1513 (30 MHz - 4 GHz)**




$f < 1 \text{ GHz}$ : RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$ : RBW / VBW 1 MHz

Carrier suppressed with a rejection filter

**Channel 1513 (4 GHz – 12.5 GHz)**



RBW / VBW 1 MHz

### 5.1.5 Receiver Radiated Emissions

#### Reference

FCC:	CFR Part 15B
------	--------------

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 20 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber.

The receiving antennas are conform with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test set-ups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received.

The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.4-2003 clause 4.2.

Antennas are conform with ANSI C63.2-1996 item 15.

150 kHz - 30 MHz: Quasi Peak measurement, 9kHz Bandwidth, passive loop antenna.

30 MHz - 200 MHz: Quasi Peak measurement, 120KHz Bandwidth, biconical antenna

200MHz - 1GHz: Quasi Peak measurement, 120KHz Bandwidth, log periodic antenna

>1GHz: Average, RBW 1MHz, VBW 10 Hz, wave guide horn

All measurement settings are according to FCC 15.109 and 15.107

SPURIOUS EMISSIONS LEVEL ( $\mu\text{V/m}$ )								
Idle Mode								
f (MHz)	Detector	Level ( $\mu\text{V/m}$ )	f (MHz)	Detector	Level ( $\mu\text{V/m}$ )	f (MHz)	Detector	Level ( $\mu\text{V/m}$ )
No critical peaks found			-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
Measurement uncertainty			±3 dB					

$f < 1 \text{ GHz}$  : RBW/VBW: 100 kHz

$f \geq 1 \text{ GHz}$  : RBW/VBW: 1 MHz

H = Horizontal; V= Vertical

Measurement distance see table

#### Limits: § 15.109

Frequency (MHz)	Field strength (dB $\mu\text{V/m}$ )	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3

**Idle-Mode (30 MHz - 1 GHz)**

**Information**


EUT: AAD-3132011-BV + charger  
 Serial Number: IMEI: 004401071405540  
 Test Description: FCC Part 15.B  
 Operating Conditions: Idle Mode  
 Operator Name: Kraus  
 Comment: AC: 115V / 60 Hz

**Scan Setup: STAN\_Fin [EMI radiated]**


Hardware Setup: EMI radiated\Electric Field (NOS)  
 Level Unit: dB $\mu$ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30MHz - 1GHz	QuasiPeak	120kHz	15s	Receiver

**FCC\_1GHz**




**Idle-Mode (1 GHz – 4 GHz)**




RBW / VBW 1 MHz

**Idle-Mode (4 GHz – 12 GHz)**



RBW / VBW 1 MHz

Idle-Mode (12 GHz – 25 GHz)




RBW / VBW 1 MHz




**AC-Line conducted emissions**

**Idle-Mode (150 KHz – 30 MHz)**

Plot 1:




Plot 2:




Traffic-Mode (150 KHz – 30 MHz)

Plot 1:



Plot 2:



### 5.1.6 Conducted Spurious Emissions

#### Reference

FCC:	CFR Part 27.53(g), 2.1051
------	---------------------------

#### Measurement Procedure:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 19.1 GHz, data taken from 10 MHz to 20 GHz.

2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

UMTS Transmitter Channel Frequency

1312 1712.4 MHz

1412 1732.4 MHz

1513 1752.6 MHz


#### Measurement Limit:

(a) On any frequency outside frequency band of the UMTS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\text{Log}(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

#### Measurement Results


Harmonic	Tx ch.-1312 Freq. (MHz)	Level (dBm)	Tx ch.-1412 Freq. (MHz)	Level (dBm)	Tx ch.-1513 Freq. (MHz)	Level (dBm)
2	1712.4	-	1732.4	-	1752.6	-
3	3424.8	-	3464.8	-	3505.2	-
4	5137.2	-	5197.2	-	5257.8	-
5	6849.6	-	6929.6	-	7010.4	-
6	8562.0	-	8662.0	-	8763.0	-
7	10274.4	-	10394.4	-	10515.6	-
8	11986.8	-	12126.8	-	12268.2	-
9	13699.2	-	13859.2	-	14020.8	-
10	15411.6	-	15591.6	-	15773.4	-

**Channel 1312 (30 MHz – 1 GHz)**




The peak at the beginning of the Plot is the LO from the measuring spectrum Analyzer and not from the EUT.

**Channel 1312 (1 GHz – 25 GHz)**




Channel 1412: (30 MHz – 1 GHz)




The peak at the beginning of the Plot is the LO from the measuring spectrum Analyzer and not from the EUT.

Channel 1412: (1 GHz – 25 GHz)




Channel 1513: (30 MHz – 1 GHz)



The peak at the beginning of the Plot is the LO from the measuring spectrum Analyzer and not from the EUT.

Channel 1513: (1 GHz – 25 GHz)



### 5.1.7 Block Edge Compliance

#### Reference


FCC:	CFR Part 27.53(g), 2.1051
------	---------------------------

#### Measurement Limit:


Sec. 27.53(g) Emission Limits.

(a) On any frequency outside frequency band of the UMTS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\log(P)$  dB. For all power levels +33 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

#### Channel 1312



Channel 1513





### 5.1.8 Occupied Bandwidth

#### Reference

FCC:	CFR Part 27.53(g)(1), 2.1049
------	------------------------------

#### Occupied Bandwidth Results:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the UMTS frequency band. Table below lists the measured 99% power and -26dBC occupied bandwidths. Spectrum analyzer plots are included on the following pages.


Normal mode

Frequency	99% Occupied Bandwidth (kHz)	-26 dBc Bandwidth (kHz)
1712.4 MHz	4761	4905
1732.4 MHz	4737	4893
1752.6 MHz	4725	4905

Part 27 requires a measurement bandwidth of at least 1% of the occupied bandwidth. For ca. 5 MHz, this equates to a resolution bandwidth of at least 50 kHz. For this testing, a resolution bandwidth 100 kHz was used.


Channel 1312

99% (-20 dB) Occupied Bandwidth




Channel 1312

-26 dBc Bandwidth




**Channel 1412**

**99% (-20 dB) Occupied Bandwidth**




**Channel 1412**

**-26 dBc Bandwidth**




## Channel 1513

### 99% (-20 dB) Occupied Bandwidth



## Channel 1513

### -26 dBc Bandwidth



## 6 Test equipment and ancillaries used for tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

### *Anechoic chamber C:*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Anechoic chamber	MWB	87400/02	300000996	Monthly verification		
2	System-Rack 85900	HP I.V.	*	300000222	n.a.		
3	Measurement System 1						
4	Spektrum Analyzer 8566B	HP	2747A05306	300001000	05.10.2006	24	05.10.2008
5	Spektrum Analyzer Display 85662A	HP	2816A16541	300002297	05.10.2006	24	05.10.2008
6	Quasi-Peak-Adapter 85650A	HP	2811A01131	300000999	05.10.2006	24	05.10.2008
7	RF-Preselector 85685A	HP	2837A00779	300000218	08.11.2006	24	08.11.2008
8	PC Vectra VL	HP		300001688	n.a.		
9	Software EMI	HP		300000983	n.a.		
10	Measurement System 2						
11	FSP 30	R&S	100623	ICT 300003464	26.10.2006	12	26.10.2007
12	PC	F+W			n.a.		
13	TILE	TILE			n.a.		
14	Biconical antenna	EMCO	S/N: 860 942/003		Monthly verification (System cal.)		
15	Log. Period. Antenna 3146	EMCO	2130	300001603	Monthly verification (System cal.)		
16	Double Ridged Antenna HP 3115P	EMCO	3088	300001032	Monthly verification (System cal.)		
17	Active Loop Antenna 6502	EMCO	2210	300001015	Monthly verification (System cal.)		
18	Power Supply 6032A	HP	2818A03450	300001040	12.05.2007	36	12.05.2010
19	Busisolator	Kontron		300001056	n.a.		
20	Leitungsteiler 11850C	HP		300000997	Monthly verification (System cal.)		
21	Power attenuator 8325	Byrd	1530	300001595	Monthly verification (System cal.)		
22	Band reject filter WRCG1855/1910	Wainwright	7	300003350	Monthly verification (System cal.)		
23	Band reject filter WRCG2400/2483	Wainwright	11	300003351	Monthly verification (System cal.)		

### *Signaling Units:*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	CBT	R&S	100313	300003516	24.10.2006	24	24.10.2008
2	CBT	R&S	100185	300003416	21.02.2006	24	21.02.2008
3	CMU-200	R&S	103992	300003231	27.04.2007	12	27.04.2008
4	CMU-200	R&S	106240	300003321	02.05.2006	24	02.05.2008

**SRD Laboratory Room 002:**

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller PSM 12	R&S	835259/007	3000002681-00xx	n.a.		
2	Memory Extension PSM-K10	R&S	To 1	3000002681	n.a.		
3	Operating Software PSM-B2	R&S	To 1	3000002681	n.a.		
4	19" Monitor		22759020-ED	3000002681	n.a.		
5	Mouse		LZE 0095/6639	3000002681	n.a.		
6	Keyboard		G00013834L 461	3000002681	n.a.		
7	Spectrum Analyser FSIQ 26	R&S	835540/018	3000002681-0005	01.08.2006	24	01.08.2008
8	Tracking Generator FSIQ-B10	R&S	835107/015	3000002681	s.No.7		
10	RF-Generator SMIQ03 (B1 Signal)	R&S	835541/056	3000002681-0002	01.08.2006	36	01.08.2009
11	Modulation Coder SMIQ-B20	R&S	To 10	3000002681	s.No.10		
12	Data Generator SMIQ-B11	R&S	To 10	3000002681	s.No.10		
13	RF Rear Connection SMIQ-B19	R&S	To 10	3000002681	s.No.10		
14	Fast CPU SM-B50	R&S	To 10	3000002681	s.No.10		
15	FM Modulator SM-B5	R&S	835676/033	3000002681	s.No.10		
16	RF-Generator SMIQ03 (B2 Signal)	R&S	835541/055	3000002681-0001	01.08.2006	36	01.08.2009
17	Modulation Coder SMIQ-B20	R&S	To 16	3000002681	s.No.16		
18	Data Generator SMIQ-B11	R&S	To 16	3000002681	s.No.16		
19	RF Rear Connection SMIQ-B19	R&S	To 16	3000002681	s.No.16		
20	Fast CPU SM-B50	R&S	To 16	3000002681	s.No.16		
21	FM Modulator SM-B5	R&S	836061/022	3000002681	s.No.16		
22	RF-Generator SMP03 (B3 Signal)	R&S	835133/011	3000002681-0003	01.08.2006	36	01.08.2009
23	Attenuator SMP-B15	R&S	835136/014	3000002681	S.No.22		
24	RF Rear Connection SMP-B19	R&S	834745/007	3000002681	S.No.22		
25	Power Meter NRVD	R&S	835430/044	3000002681-0004	01.08.2006	24	01.08.2008
26	Power Sensor NRVD-Z1	R&S	833894/012	3000002681-0013	01.08.2006	24	01.08.2008
27	Power Sensor NRVD-Z1	R&S	833894/011	3000002681-0010	01.08.2006	24	01.08.2008
28	Rubidium Standard RUB	R&S		3000002681-0009	01.08.2006	24	01.08.2008
29	Switching and Signal Conditioning Unit SSCU	R&S	338864/003	3000002681-0006	01.08.2006	24	01.08.2008
30	Laser Printer HP Deskjet 2100	HP	N/A	3000002681-0011	n.a.		
31	19" Rack	R&S	11138363000 004	3000002681	n.a.		
32	RF-cable set	R&S	N/A	3000002681	n.a.		
33	IEEE-cables	R&S	N/A	3000002681	n.a.		
34	Sampling System FSIQ-B70	R&S	835355/009	3000002681	s.No.7		

35	RSP programmable attenuator	R&S	834500/010	3000002681-0007	01.08.2006	24	01.08.2008
36	Signalling Unit	R&S	838312/011	3000002681	n.a.		
37	NGPE programmable Power Supply for EUT	R&S	192.033.41	3000002681			
38	Climatic box VT 4002	Heraeus Vötsch	58566046820 010	300003019	11.05.2007	24	11.05.2009
39	Signaling Unit CMU200	R&S	832221/0055	300002862	12.01.2006	24	12.01.2008
40	Power Splitter 6005-3	Inmet Corp.	none	300002841	23.12.2006	24	23.12.2008
41	SMA Cables SPS-1151-985-SPS	Insulated Wire	different	different	n.a.		
42	CBT32 with EDR Signaling Unit	R&S					
43	Coupling unit	Narda	N/A	--	n.a.		
44	2xSwitch Matrix PSU	R&S	872584/021	300001329	n.a.		
45	RF-cable set	R&S	N/A	different	n.a.		
46	IEEE-cables	R&S	N/A	--	n.a.		

Anmerkung: 3000002681-00xx als Systeme inventarisiert

**Anechoic chamber F:**

No.	Instrument/Ancillary	Manufacturer	Type	Serial-No.	Internal identification
<b>Radiated emission in chamber F</b>					
F-1	Control Computer	F+W		FW0502032	300003303
F-2	Bilog antenna	Chase	CBL 6112A	2110	300000573
F-3a	Amplifier	Veritech Microwave Inc.	0518C-138	- / -	- / -
F-4b	Switch	HP	3488A	- / -	300000368
F-5	EMI Test receiver	R&S	ESCI	100083	300003312
F-6	Turntable Controller	EMCO	1061 3M	1218	300000661
F-7	Tower Controller	EMCO	1051 Controller	1262	300000625
F-8	Tower	EMCO	1051 Tower	1262	300000625
F-9	Ultra Notch-Filter Rejected band Ch. 62	WRCD		9	
<b>Radiated immunity in chamber F</b>					
F-10	Control Computer	F+W		FW0502032	300003303
F-11	Signal Generator	R&S	SML 03	102519	300003407
F-12	RF-Amplifier	ar	50W1000	12932	300001438
F-13	Directional Coupler	ar	DC 3010	12708	300001428
F-14	Logger Antenna	R&S	HL023A1	323704/016	300001476
F-15	RF-Amplifier	ar	60S1G3	313649	300003410
F-16	Directional Coupler	ar	DC7144A	312786	300003411
F-17	Horn Antenna	ar	AT 4002	19739	300000633
F-18	Power Meter	R&S	NRV	860327/024	F033
F-19	Power sensor	R&S	URV5-Z2	839080/005	300002844.02
F-20	Power sensor	R&S	URV5-Z2	830755/057	F032
<b>Harmonics and flicker in front of chamber F</b>					
F-21	Flicker and Harmonics Test System	Spitzenberger & Spies	PHE4500/B I PHE4500/B II	B5983 B5984	300000210
F-22	Control Unit	Spitzenberger & Spies	STE	B5980	300000210
F-23	Power Amplifier	Spitzenberger & Spies	EP 4500/B	B5976	300000210
F-24	Conect Panel	Spitzenberger & Spies	Conect panel	B5982	300000210
F-25	Power Supply	Spitzenberger & Spies	NT-EP 4500	B3977	300000210
F-26	Additional transformer	Spitzenberger & Spies	UT-EP 4500	B5978	300000210
F-27	Analyzer Reference System	Spitzenberger & Spies	ARS 16/1	A3509 07/0 0205	300003314
F-26	Power Supply	Hewlett Packard	6032 A	2920 A 04466	300000580