







TEST REPORT Test Report No.: 1-1954-02-02/10



Testing Laboratory

CETECOM ICT Services GmbH Untertürkheimer Straße 6-10 66117 Saarbrücken/Germany Phone: + 49 681 5 98 - 0 + 49 681 5 98 - 9075 Fax: Internet: http://www.cetecom-ict.de info@ict.cetecom.de e-mail:

Accredited Test Laboratory:

The test laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025

DAR registration number: DGA-PL-176/94-D1

Applicant

Sony Ericsson Mobile Communications AB Nya Vattentornet 22188 Lund/Sweden

Phone:	+46-46-19-3000
Fax:	+46-10-800-2441

Contact: Peter Lindeborg peter.lindeborg@sonyericsson.com e-mail: +46-10-802-43 68 Phone:

Manufacturer

Sony Ericsson Mobile Communications AB Nya Vattentornet 22188 Lund/Sweden

Test Standard/s

Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate IEEE 1528-2003 (SAR)in the Human Head from Wireless Communications Devices: Measurement Techniques Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency **OET Bulletin 65** Supplement C **Electromagnetic Fields** Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency RSS-102 Issue 2 Bands)

For further applied test standards please refer to section 3 of this test report.

	Test Item
Kind of test item:	Mobile Phone
Device type:	portable device
Model name:	AAD-3880080-BV
S/N serial number:	BX9017228C
FCC-ID:	PY7A3880080
IC:	4170B-A3880080
IMEI-Number:	00440107993360-8
HW hardware status:	AP1.1
SW software status:	R7BA037
Frequency:	see technical details
Antenna:	integrated antenna
Battery option:	BST-43 Li-Polymer 3.7V / 1000mAh
Accessories:	stereo headset
Test sample status:	production unit
Exposure category:	general population / uncontrolled environment



Test performed:

Oleksandr Hnatovskiy

Test Report authorised:

Thomas Voy

2010-01-29

Thomas Vogler

2010-01-29

2010-01-29

Test report no.: 1-1954-02-02/10



1 Table of contents

1	Table of co	ontents	2
2	General in	formation	4
	2.1 Note	95	4
	2.2 App	lication details	4
	2.3 Stat	ement of compliance	4
	2.4 Tecl	nnical details	5
3	Test stand	ard/s:	6
	3.1 RF e	exposure limits	6
4	Summary	of Measurement Results	7
5	Test Envir	onment	7
6	Test Set-u	ο	8
-	6.1 Mea	surement system	8
	6.1.1	System Description	8
	6.1.2	Test environment	9
	6.1.3	Probe description	9
	6.1.4	Phantom description	
	6.1.5	Device holder description	10
	6.1.6	Scanning procedure	11
	6.1.7	Spatial Peak SAR Evaluation	12
	6.1.8	Data Storage and Evaluation	13
	6.1.9	Tissue simulating liquids: dielectric properties	15
	6.1.10	Tissue simulating liquids: parameters	16
	6.1.11	Measurement uncertainty evaluation for SAR test	17
	6.1.12	Measurement uncertainty evaluation for system validation	
	6.1.13	System validation	
	6.1.14	Validation procedure	20
7	Detailed To	est Results	21
	7.1 Con	ducted power measurements	21
	7.1.1	Conducted power measurements GSM 850 MHz	21
	7.1.2	Conducted power measurements GSM 1900 MHz	22
	7.1.3	Justification of SAR measurements in GSM mode	22
	7.1.4	Multiple Transmitter Information	23
	7.2 SAR	test results	
	7.2.1	Results overview	
_	7.2.2	General description of test procedures	
8	Test equip	ment and ancillaries used for tests	27
9	Observatio	ons	27
An	nex A: Sy	stem performance verification	28
An	nex B: D/	ASY4 measurement results	32
	Annex B.1	: GSM 850 MHz head	
	Annex B.2	: GSM 850 MHz body	
	Annex B.3	: GSM 1900 MHz head	63
	Annex B.4	: GSM 1900 MHz body	87

Test report no.: 1-1954-02-02/10



Annex E	3.5: Z-axis scan	94
Annex C:	Photo documentation	96
Annex C	C.6: Liquid depth	111
Annex D:	RF Technical Brief Cover Sheet acc. to RSS-102	113
Annex D	0.7: Declaration of RF Exposure Compliance	113
Annex E:	Calibration parameters	114
Annex F:	Document History	114
Annex G:	Further Information	114



2 General information

2.1 Notes

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

2.2 Application details

Date of receipt of order:2010-01-18Date of receipt of test item:2010-01-19Start of test:2010-01-19End of test:2010-01-28Person(s) present during the test:

2.3 Statement of compliance

The SAR values found for the AAD-3880080-BV Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1 g tissue according to the FCC rule §2.1093, the ANSI/IEEE C 95.1:1999, the NCRP Report Number 86 for uncontrolled environment, according to the Health Canada's Safety Code 6 and the Industry Canada Radio Standards Specification RSS-102 for General Population/Uncontrolled exposure.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and that positions the handset a minimum of 15 mm from the body. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.



2.4 Technical details

Band tested for this SAR test report	Technology	Frequency band	Lowest transmit frequency/MHz	Highest transmit frequency/MHz	Lowest receive Frequency/MHz	Highest receive Frequency/MHz	Kind of modulation	Power Class	Tested power control level	GPRS/EGPRS mobile station class	GPRS/EGPRS multislot class	(E)GPRS voice mode or DTM	Test channel low	Test channel middle	Test channel high	Maximum output power/dBm)*
	GSM	GSM	880.2	914.8	925.2	959.8	GMSK 8-PSK	4 E2	5	В	10	no	975	37	124	
	GSM	DCS	1710.2	1784.8	1805.2	1879.8	GMSK 8-PSK	1 E2	0	В	10	no	512	698	885	
	GSM	cellular	824.2	848.8	869.2	893.8	GMSK 8-PSK	4 E2	5	В	10	no	128	190	251	32.6
	GSM	PCS	1850.2	1909.8	1930.2	1989.8	GMSK 8-PSK	1 E2	0	В	10	no	512	661	810	30.7
	UMTS	FDD I	1922.4	1977.6	2112.4	2167.6	QPSK	3	max				9612	9750	9888	
	UMTS	FDD VIII	882.4	912.6	927.4	957.6	QPSK	3	max				2712	2787	2863	
	BT	ISM	2412	2462	2412	2462	GFSK	3	max				0	39	78	8

)*: slotted peak power for GSM, averaged max. RMS power for UMTS, WLAN and BT.



3 Test standard/s:

Test Standard	Version	Test Standard Description
IEEE 1528-2003	2003-04	Recommended Practice for Determining the Peak Spatial- Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
OET Bulletin 65 Supplement C	1997-01 2001-01	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
RSS-102 Issue 2	2005-11	Radio Frequency Exposure Compliance of Radiocommuni- cation Apparatus (All Frequency Bands)
Canada's Safety Code No. 6	99-EHD-237	Limits of Human Exposure to Radiofrequency Electromag- netic Fields in the Frequency Range from 3 kHz to 300 GHz
IEEE Std. C95-3	1991	Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave
IEEE Std. C95-1	1999	Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields

3.1 RF exposure limits

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR* (Brain)	1.60 mW/g	8.00 mW/g
Spatial Average SAR** (Whole Body)	0.08 mW/g	0.40 mW/g
Spatial Peak SAR*** (Hands/Feet/Ankle/Wrist)	4.00 mW/g	20.00 mW/g

Table 1: RF exposure limits

The limit applied in this test report is shown in bold letters

Notes:

- The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time
- ** The Spatial Average value of the SAR averaged over the whole body.
- *** The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).



4 Summary of Measurement Results

\boxtimes	No deviations from the technical specifications ascertained
	Deviations from the technical specifications ascertained

5 Test Environment

Ambient temperature:	20 – 24 ℃
Tissue Simulating liquid:	20 – 24 ℃

Relative humidity content:	40 – 50 %
Air pressure:	not relevant for this kind of testing
Power supply:	230 V / 50 Hz

Exact temperature values for each test are shown in the table(s) under 2.5. and/or on the measurement plots.



6 Test Set-up

6.1 Measurement system

6.1.1 System Description



- The DASY4 system for performing compliance tests consists of the following items:
- A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, ADconversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- A unit to operate the optical surface detector which is connected to the EOC.
- The <u>Electro-Optical Coupler (EOC)</u> performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY4 measurement server.
- The DASY4 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2000
- DASY4 software and SEMCAD data evaluation software.
- Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- The generic twin phantom enabling the testing of left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- System validation dipoles allowing to validate the proper functioning of the system.



6.1.2 Test environment

The DASY4 measurement system is placed at the head end of a room with dimensions:

 $5 \times 2.5 \times 3 \text{ m}^3$, the SAM phantom is placed in a distance of 75 cm from the side walls and 1.1m from the rear wall. Above the test system a 1.5 x 1.5 m² array of pyramid absorbers is installed to reduce reflections from the ceiling.

Picture 1 of the photo documentation shows a complete view of the test environment. The system allows the measurement of SAP values larger than 0.005 mW/g.

The system allows the measurement of SAR values larger than 0.005 mW/g.

6.1.3 Probe description

Isotropic E-Field Probe ET3DV6 for Dosimetric Measurements

Technical data according to manufacturer information				
Construction	Symmetrical design with triangular core			
	Built-in optical fiber for surface detection system			
	Built-in shielding against static charges			
	PEEK enclosure material (resistant to organic solvents,			
	e.g., glycolether)			
Calibration	In air from 10 MHz to 2.5 GHz			
	In head tissue simulating liquid (HSL) at 900 (800-1000)			
	MHz and 1.8 GHz (1700-1910 MHz) (accuracy ± 9.5%;			
	k=2) Calibration for other liquids and frequencies upon			
	request			
Frequency	10 MHz to 3 GHz (dosimetry); Linearity: ± 0.2 dB (30 MH			
	to 3 GHz)			
Directivity	± 0.2 dB in HSL (rotation around probe axis)			
	± 0.4 dB in HSL (rotation normal to probe axis)			
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB			
Optical Surface Detection	± 0.2 mm repeatability in air and clear liquids over diffuse			
	reflecting surfaces (ET3DV6 only)			
Dimensions	Overall length: 330 mm			
	Tip length: 16 mm			
	Body diameter: 12 mm			
	Tip diameter: 6.8 mm			
	Distance from probe tip to dipole centers: 2.7 mm			
Application	General dosimetry up to 3 GHz			
	Compliance tests of mobile phones			
	Fast automatic scanning in arbitrary phantoms (ET3DV6)			



6.1.4 Phantom description

The used SAM Phantom meets the requirements specified in Edition 01-01 of Supplement C to OET Bulletin 65 for Specific Absorption Rate (SAR) measurements.

The phantom consists of a fibreglass shell integrated in a wooden table. It allows left-hand and right-hand head as well as body-worn measurements with a maximum liquid depth of 18 cm in head position and 22 cm in planar position (body measurements). The thickness of the Phantom shell is 2 mm +/- 0.1 mm.



6.1.5 Device holder description

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used.



Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values.

Therefore those devices are normally only tested at the flat part of the SAM.



6.1.6 Scanning procedure

- The DASY4 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.
- The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT's output power and should vary max. +/- 5 %.
- The "surface check" measurement tests the optical surface detection system of the DASY4 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1mm). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within ± 30°.)
- The "area scan" measures the SAR above the DUT or verification dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The robot performs a stepped movement along one grid axis while the local electrical field strenth is measured by the probe. The probe is touching the surface of the SAM during acquisition of measurement values. The standard scan uses large grid spacing for faster measurement. Standard grid spacing for head measurements is 15 mm in x- and y- dimension. If a finer resolution is needed, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result. For special applications where the standard scan method does not find the peak SAR within the grid, e.g. mobile phones with flip cover, the grid can be adapted in orientation. Results of this coarse scan are shown in annex 2.
- A "7x7x7 zoom scan" measures the field in a volume around the 2D peak SAR value acquired in the previous "coarse" scan. This is a fine 7x7 grid where the robot additionally moves the probe in 7 steps along the z-axis away from the bottom of the Phantom. Grid spacing for the cube measurement is 5 mm in x and y-direction and 5 mm in z-direction. DASY4 is also able to perform repeated zoom scans if more than 1 peak is found during area scan. In this document, the evaluated peak 1g and 10g averaged SAR values are shown in the 2D-graphics in annex 2. Test results relevant for the specified standard (see section 3) are shown in table form in section 7.
- A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x7 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 2mm steps. This measurement shows the continuity of the liquid and can depending in the field strength also show the liquid depth. A z-axis scan of the measurement with maximum SAR value is shown in annex 2.



6.1.7 Spatial Peak SAR Evaluation

The spatial peak SAR - value for 1 and 10 g is evaluated after the Cube measurements have been done. The basis of the evaluation are the SAR values measured at the points of the fine cube grid consisting of 7 x 7 x 7 points. The algorithm that finds the maximal averaged volume is separated into three different stages.

- The data between the dipole center of the probe and the surface of the phantom are extrapolated. This data cannot be measured since the center of the dipole is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is about 1 mm (see probe calibration sheet). The extrapolated data from a cube measurement can be visualized by selecting 'Graph Evaluated'.
- The maximum interpolated value is searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10 g) are computed using the 3d-spline interpolation algorithm. If the volume cannot be evaluated (i.e., if a part of the grid was cut off by the boundary of the measurement area) the evaluation will be started on the corners of the bottom plane of the cube.
- All neighboring volumes are evaluated until no neighboring volume with a higher average value is found.

Extrapolation

The extrapolation is based on a least square algorithm [W. Gander, Computermathematik, p.168-180]. Through the points in the first 3 cm along the z-axis, polynomials of order four are calculated. These polynomials are then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1 mm from each other.

Interpolation

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot"-condition [W. Gander, Computermathematik, p.141-150] (x, y and z -direction) [Numerical Recipes in C, Second Edition, p.123ff].

Volume Averaging

At First the size of the cube is calculated. Then the volume is integrated with the trapezoidal algorithm. 8000 points (20x20x20) are interpolated to calculate the average.

Advanced Extrapolation

DASY4 uses the advanced extrapolation option which is able to compansate boundary effects on E-field probes.



6.1.8 Data Storage and Evaluation

Data Storage

The DASY4 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	 Sensitivity Conversion factor 	Norm _i , a _{i0} , a _{i1} , a _{i2} ConvF _i
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY4 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.



If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf/dcp_i$$

with	Vi	= compensated signal of channel i	(i = x, y, z)
	Ui	= input signal of channel i	(i = x, y, z)
	cf	= crest factor of exciting field	(DASY parameter)
	dcpi	= diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field	probes:	$E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$	
H-field	probes:	$H_{i} = (V_{i})^{1/2} \cdot (a_{i0} + a_{i1}f + a_{i2}f^{2})/2$	/f
with	V _i Norm _i	 compensated signal of channel i sensor sensitivity of channel i ImV/(V/m)²1 for E-field Probes 	(i = x, y, z) (i = x, y, z)
	ConvF	= sensitivity enhancement in solution	
	a _{ij}	= sensor sensitivity factors for H-field probes	
	f	= carrier frequency [GHz]	
	Ei	= electric field strength of channel i in V/m	
	Hi	= magnetic field strength of channel i in A/m	

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \sigma) / (\rho \cdot 1000)$$

withSAR
 E_{tot} = local specific absorption rate in mW/g
= total field strength in V/m σ = conductivity in [mho/m] or [Siemens/m]
= equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^{2}/3770$$
 or $P_{pwe} = H_{tot}^{2} \cdot 37.7$

with

 P_{pwe} = equivalent power density of a plane wave in mW/cm²

 E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m



6.1.9 Tissue simulating liquids: dielectric properties

The following materials are used for producing the tissue-equivalent materials.

(Liquids used for tests described in section 7. are marked with \boxtimes) :

Ingredients (% of weight)	Frequency (MHz)							
frequency band	450	🛛 835	900	1800	🛛 1900	2450		
Tissue Type	Head	Head	Head	Head	Head	Head		
Water	38.56	41.45	40.92	52.64	54.9	62.7		
Salt (NaCl)	3.95	1.45	1.48	0.36	0.18	0.5		
Sugar	56.32	56.0	56.5	0.0	0.0	0.0		
HEC	0.98	1.0	1.0	0.0	0.0	0.0		
Bactericide	0.19	0.1	0.1	0.0	0.0	0.0		
Triton X-100	0.0	0.0	0.0	0.0	0.0	36.8		
DGBE	0.0	0.0	0.0	47.0	44.92	0.0		

Table 2: Head tissue dielectric properties

Ingredients (% of weight)	Frequency (MHz)								
frequency band	450	🛛 835	900	1800	🖂 1900	2450			
Tissue Type	Body	Body	Body	Body	Body	Body			
Water	51.16	52.4	56.0	69.91	69.91	73.2			
Salt (NaCl)	1.49	1.40	0.76	0.13	0.13	0.04			
Sugar	46.78	45.0	41.76	0.0	0.0	0.0			
HEC	0.52	1.0	1.21	0.0	0.0	0.0			
Bactericide	0.05	0.1	0.27	0.0	0.0	0.0			
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0			
DGBE	0.0	0.0	0.0	29.96	29.96	26.7			

Table 3: Body tissue dielectric properties

Salt: 99+% Pure Sodium Chloride Sugar: 98+% Pure Sucrose Water: De-ionized, 16MΩ+ resistivity HEC: Hydroxyethyl Cellulose DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol] Triton X-100(ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

Note: Due to their availability body tissue simulating liquids as defined by FCC OET Bulletin 65 Supplement C are generally used for body worn SAR testing according to European standards.



6.1.10 Tissue simulating liquids: parameters

Used Target	Target		Meas	sured	Measured Date
Frequency	Head	Tissue	Head	Tissue	Medsared Bate
[MHz]	Permittivity	Conductivity [S/m]	Permittivity	Conductivity [S/m]	
835	41.5	0.90	42.7	0.91	2010-01-25
900	41.5	0.97	41.9	0.97	2010-01-25
1900	40.0	1.40	40.5	1.40	2010-01-21

Table 4: Parameter of the head tissue simulating liquid

Used Target	Target		Meas	sured	Measured Date
Frequency	Body	Tissue	Body	Tissue	
[MHz]	Permittivity	Conductivity	Permittivity	Conductivity	
		[S/m]		[S/m]	
835	55.2	0.97	54.5	0.97	2010-01-20
900	55.0	1.05	53.8	1.04	2010-01-20
1900	53.3	1.52	53.2	1.53	2010-01-28

Table 5: Parameter of the body tissue simulating liquid

Note: The dielectric properties have been measured using the contact probe method at 22 °C.



6.1.11 Measurement uncertainty evaluation for SAR test

The overall combined measurement uncertainty of the measurement system is \pm 10.3% (K=1). The expanded uncertainty (k=2) is assessed to be \pm 20.6%

This measurement uncertainty budget is suggested by IEEE 1528-2003 and determined by Schmid & Partner Engineering AG. The breakdown of the individual uncertainties is as follows:

Error Sources	Uncertainty	Probability	Divi-	C _i	Ci	Standard	Standard	V _i ²
	Value	Distribution	sor	1g	10g	Uncertainty	Uncertainty	or
						1g	10g	V _{eff}
Measurement System								
Probe calibration	± 4.8%	Normal	1	1	1	± 4.8%	± 4.8%	∞
Axial isotropy	± 4.7%	Rectangular	√3	0.7	0.7	± 1.9%	± 1.9%	∞
Hemispherical isotropy	± 9.6%	Rectangular	√3	0.7	0.7	± 3.9%	± 3.9%	∞
Spatial resolution	± 0.0%	Rectangular	√3	1	1	± 0.0%	± 0.0%	∞
Boundary effects	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	∞
Probe linearity	± 4.7%	Rectangular	√3	1	1	± 2.7%	± 2.7%	∞
System detection limits	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Readout electronics	± 1.0%	Normal	1	1	1	± 1.0%	± 1.0%	8
Response time	± 0.8%	Rectangular	√3	1	1	± 0.5%	± 0.5%	8
Integration time	± 2.6%	Rectangular	√3	1	1	± 1.5%	± 1.5%	8
RF ambient conditions	± 3.0%	Rectangular	√3	1	1	± 1.7%	± 1.7%	8
Probe positioner	± 0.4%	Rectangular	√3	1	1	± 0.2%	± 0.2%	8
Probe positioning	± 2.9%	Rectangular	√3	1	1	± 1.7%	± 1.7%	8
Max. SAR evaluation	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Test Sample Related								
Device positioning	± 2.9%	Normal	1	1	1	± 2.9%	± 2.9%	145
Device holder uncertainty	± 3.6%	Normal	1	1	1	± 3.6%	± 3.6%	5
Power drift	± 5.0%	Rectangular	√3	1	1	± 2.9%	± 2.9%	8
Phantom and Set-up								
Phantom uncertainty	± 4.0%	Rectangular	√3	1	1	± 2.3%	± 2.3%	8
Liquid conductivity (target)	± 5.0%	Rectangular	√3	0.64	0.43	± 1.8%	± 1.2%	8
Liquid conductivity	± 2.5%	Normal	1	0.64	0.43	± 1.6%	± 1.1%	8
(meas.)								
Liquid permittivity (target)	± 5.0%	Rectangular	√3	0.6	0.49	± 1.7%	± 1.4%	∞
Liquid permittivity (meas.)	± 2.5%	Normal	1	0.6	0.49	± 1.5%	± 1.2%	∞
Combined Uncertainty						± 10.3%	± 10.0%	330
Expanded Std.						± 20.6%	± 20.1%	
Uncertainty								

Table 6: Measurement uncertainties



6.1.12 Measurement uncertainty evaluation for system validation

The overall combined measurement uncertainty of the measurement system is \pm 8.4% (K=1). The expanded uncertainty (k=2) is assessed to be \pm 16.8%

This measurement uncertainty budget is suggested by IEEE 1528-2003 and determined by Schmid & Partner Engineering AG. The breakdown of the individual uncertainties is as follows:

Error Sources	Uncertainty	Probability	Divi-	Ci	Ci	Standard	Standard	V_i^2
	Value	Distribution	sor	1g	10g	Uncertainty	Uncertainty	or
						1g	10g	v_{eff}
Maggurgmont System								
Neasurement System	1. 1. 00/	N La sea al	4		-	1. 1. 00/	1. 4.00/	
Probe calibration	± 4.8%	Normal	1	1	1	± 4.8%	± 4.8%	∞
Axial isotropy	± 4.7%	Rectangular	√3	0.7	0.7	± 1.9%	± 1.9%	∞
Hemispherical isotropy	± 0.0%	Rectangular	√3	0.7	0.7	± 0.0%	± 3.9%	8
Boundary effects	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Probe linearity	± 4.7%	Rectangular	√3	1	1	± 2.7%	± 2.7%	∞
System detection limits	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Readout electronics	± 1.0%	Normal	1	1	1	± 1.0%	± 1.0%	8
Response time	± 0.0%	Rectangular	√3	1	1	± 0.0%	± 0.0%	8
Integration time	± 0.0%	Rectangular	√3	1	1	± 0.0%	± 0.0%	8
RF ambient conditions	± 3.0%	Rectangular	√3	1	1	± 1.7%	± 1.7%	8
Probe positioner	± 0.4%	Rectangular	√3	1	1	± 0.2%	± 0.2%	8
Probe positioning	± 2.9%	Rectangular	√3	1	1	± 1.7%	± 1.7%	8
Max. SAR evaluation	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Test Sample Related								
Dipole axis to liquid	± 2.0%	Normal	1	1	1	± 1.2%	± 1.2%	8
distance			1-					
Power drift	± 4.7%	Rectangular	√3	1	1	± 2.7%	± 2.7%	∞
Phantom and Set-up								
Phantom uncertainty	± 4.0%	Rectangular	√3	1	1	± 2.3%	± 2.3%	8
Liquid conductivity (target)	± 5.0%	Rectangular	√3	0.64	0.43	± 1.8%	± 1.2%	∞
Liquid conductivity (meas.)	± 2.5%	Normal	1	0.64	0.43	± 1.6%	± 1.1%	∞
Liquid permittivity (target)	± 5.0%	Rectangular	√3	0.6	0.49	± 1.7%	± 1.4%	∞
Liquid permittivity (meas.)	± 2.5%	Normal	1	0.6	0.49	± 1.5%	± 1.2%	∞
Combined Uncertainty						± 8.4%	± 8.1%	
Expanded Std.						± 16.8%	± 16.2%	
Uncertainty								

Table 7: Measurement uncertainties



6.1.13 System validation

The system validation is performed for verifying the accuracy of the complete measurement system and performance of the software. The system validation is performed with tissue equivalent material according to IEEE 1528. The following table shows validation results for all frequency bands and tissue liquids used during the tests (plot(s) see annex A).

Validation Kit	Frequency	Target Peak SAR (1000 mW) (+/- 10%)	Target SAR _{1g} (1000 mW) (+/- 10%)	Measured Peak SAR (1000 mW)	Measured SAR _{1g} (1000 mW)	Measured date
D900V2 S/N: 102	900 MHz head	16.7 mW/g	11.3 mW/g	16.4 mW/g	10.8 mW/g	2010-01-25
D900V2 S/N: 102	900 MHz body	16.8 mW/g	11.3 mW/g	16.5 mW/g	11.2 mW/g	2010-01-20
D1900V2 S/N: 5d009	1900 MHz head	72.4 mW/g	39.7 mW/g	68.4 mW/g	38.6 mW/g	2010-01-21
D1900V2 S/N: 5d009	1900 MHz body	68.1 mW/g	40.1 mW/g	63.4 mW/g	37.2 mW/g	2010-01-28

Table 8: Results system validation

Note : 900 MHz probe/dipole calibration is valid +/-100 MHz and fully covers the 850 MHz band.



6.1.14 Validation procedure

The validation is performed by using a validation dipole which is positioned parallel to the planar part of the SAM phantom at the reference point. The distance of the dipole to the SAM phantom is determined by a plexiglass spacer. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 1000 mW. To adjust this power a power meter is used. The power sensor is connected to the cable before the validation to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the validation to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

Validation results have to be equal or near the values determined during dipole calibration (target SAR in table above) with the relevant liquids and test system.







7 Detailed Test Results

7.1 Conducted power measurements

For the measurements a Rohde & Schwarz Radio Communication Tester CMU 200 was used. The output power was measured using an integrated RF connector and attached RF cable. The conducted output power was also checked before and after each SAR measurement. The resulting power values were within a 0.2 dB tolerance of the values shown below.

Note: CMU200 measures GSM peak and average output power for active timeslots. For SAR the timebased average power is relevant. The difference inbetween depends on the duty cycle of the TDMA signal :

No. of timeslots	1	2	3	4
Duty Cycle	1:8	1:4	1 : 2.66	1:2
timebased avg. power compared to slotted avg. power	- 9 dB	- 6 dB	- 4.25 dB	- 3 dB

The signalling modes differ as follows :

mode	coding scheme	modulation
GPRS	CS1 to CS4	GMSK
EGPRS (EDGE)	MCS1 to MCS4	GMSK
EGPRS (EDGE)	MCS5 to MCS9	8PSK

Apart from modulation change (GMSK/8PSK) coding schemes differ in code rate without influence on the RF signal. Therefore one coding scheme per mode was selected for conducted power measurements.

7.1.1 Conducted power measurements GSM 850 MHz

Channel / frequency	modulation	timeslots	slotted avg. power	timebased avg. power (calculated)
128 / 824.2 MHz	GMSK	1	32.6dBm	23.6dBm
190 / 836.6 MHz	GMSK	1	32.6dBm	23.6dBm
251 / 848.0 MHz	GMSK	1	32.5dBm	23.5dBm
128 / 824.2 MHz	GMSK	2	29.7dBm	23.7 dBm
190 / 836.6 MHz	GMSK	2	29.8dBm	23.8 dBm
251 / 848.0 MHz	GMSK	2	29.6dBm	23.6 dBm
128 / 824.2 MHz	8PSK	2	27.8dBm	21.8dBm
190 / 836.6 MHz	8PSK	2	27.8dBm	21.8dBm
251 / 848.0 MHz	8PSK	2	27.6dBm	21.6dBm

Table 9: Test results conducted power measurement GSM 850 MHz



Channel / frequency	modulation	timeslots	slotted avg. power	timebased avg. power (calculated)
512 / 1850.2 MHz	GMSK	1	30.2dBm	21.2dBm
661 / 1880.0 MHz	GMSK	1	30.5dBm	21.5dBm
810 / 1909.8 MHz	GMSK	1	30.7dBm	21.7dBm
512 / 1850.2 MHz	GMSK	2	27.4dBm	21.4 dBm
661 / 1880.0 MHz	GMSK	2	27.7dBm	21.7 dBm
810 / 1909.8 MHz	GMSK	2	27.7dBm	21.7 dBm
512 / 1850.2 MHz	8PSK	2	27.0dBm	21.0dBm
661 / 1880.0 MHz	8PSK	2	27.1dBm	21.1dBm
810 / 1909.8 MHz	8PSK	2	27.2dBm	21.2dBm

7.1.2 Conducted power measurements GSM 1900 MHz

Table 10: Test results conducted power measurement GSM 1900 MHz

7.1.3 Justification of SAR measurements in GSM mode

SAR measurements were performed in GPRS mode with 2 active timeslots because highest timebased averaged output power was calculated for that configuration.

For comparison an additional delta measurement was performed with 1 timeslot in speech mode. In EDGE mode no delta measurement was performed.



7.1.4 Multiple Transmitter Information

The following tables list information which is relevant for the decision if a simultaneous transmit evaluation is necessary according to KDB 648474.

important abbreviations :

SPLSR : Antenna pair SAR to Peak Location Separation Ratio $(SAR_x + SAR_y)/d_{xy}$ P_{ref} : 12 mW at 2.4 GHz

a) head position

Tx No.	Communcation system and frequency band	P _{avg} (mW)	single SAR (W/kg) (see ch. 2.6)	remarks
1a	GSM 850 MHz	250	0.924	routine evaluation
1b	GSM 1900 MHz	125	0.567	routine evaluation
2	Bluetooth 2450 MHz	6.3	:=0	P ₂ < P _{ref}
Sum	of all 1g-SAR values		n/a	

Table 11: Communication systems and SAR values in head position

antenna pair (x,y)	antenna distance d _{xy} (cm)	L _{xy} (cm)	SPLSR _{xy}	sim Tx SAR	remarks
(1a,2)	5.8	n/a	0.172	Ν	SPLSR _{xy} < 0.3
(1b,2)	5.8	n/a	0.098	Ν	SPLSR _{xy} < 0.3

Table 12: Antenna distances and SPLSR evaluation in head position



b) body position

Tx No.	Communcation system and frequency band	P _{avg} (mW)	single SAR (W/kg) (see ch. 2.6)	remarks
1a	GSM 850 MHz	500	0.766	routine evaluation
1b	GSM 1900 MHz	250	0.429	routine evaluation
2	Bluetooth 2450 MHz	6.3	:=0	$P_2 < P_{ref}$
Sum	of all 1g-SAR values		n/a	

Table 13: Communication systems and SAR values in body position

antenna pair (x,y)	antenna distance d _{xy} (cm)	L _{xy} (cm)	SPLSR _{xy}	sim Tx SAR	remarks
(1a,2)	5.8	n/a	0.132	Ν	$SPLSR_{xy} < 0.3$
(1b,2)	5.8	n/a	0.074	Ν	$SPLSR_{xy} < 0.3$

Table 14: Antenna distances and SPLSR evaluation in body position

In simple words :

The distance of the GSM/UMTS antenna at the bottom end of the DUT to the Bluetooth antenna at the top end of the DUT is > 5 cm and the sum of the SAR values is < 1.6 W/kg : No simultaneous transmission SAR evaluation is necessary with GSM.

The Bluetooth output power is below P_{ref}. So standalone SAR for BT is not necessary.



7.2 SAR test results

7.2.1 Results overview

Head SAR GSM 850 MHz (averaged over 1g tissue volume)								
Channel / frequency	Position	Left hand test result	Right hand test result	Limit	Liquid tem left	perature right		
128 / 824.2 MHz	cheek	0.762 W/kg	0.639 W/kg	1.6 W/kg	21.7 ℃	21.4 ℃		
190 / 836.6 MHz	cheek	0.924 W/kg	0.790 W/kg	1.6 W/kg	21.7 ℃	21.4 °C		
251 / 848.8 MHz	cheek	0.922 W/kg	0.786 W/kg	1.6 W/kg	21.7 ℃	21.4 °C		
128 / 824.2 MHz	tilted 15°	0.423 W/kg	0.442 W/kg	1.6 W/kg	21.7 ℃	21.4 °C		
190 / 836.6 MHz	tilted 15°	0.538 W/kg	0.570 W/kg	1.6 W/kg	21.7 ℃	21.4 °C		
251 / 848.8 MHz	tilted 15°	0.551 W/kg	0.584 W/kg	1.6 W/kg	21.7 ℃	21.4 °C		
		Slide	e opened					
128 / 824.2 MHz	cheek	0.617 W/kg	0.530 W/kg	1.6 W/kg	21.7 ℃	21.3 ℃		
190 / 836.6 MHz	cheek	0.739 W/kg	0.604 W/kg	1.6 W/kg	21.7 ℃	21.3 °C		
251 / 848.8 MHz	cheek	0.824 W/kg	0.678 W/kg	1.6 W/kg	21.7 ℃	21.3 °C		
128 / 824.2 MHz	tilted 15°	0.242 W/kg	0.282 W/kg	1.6 W/kg	21.7 ℃	21.3 ℃		
190 / 836.6 MHz	tilted 15°	0.279 W/kg	0.354 W/kg	1.6 W/kg	21.7 ℃	21.3 ℃		
251 / 848.8 MHz	tilted 15°	0.311 W/kg	0.389 W/kg	1.6 W/kg	21.7 ℃	21.3 ℃		

Table 15: Test results head SAR GSM 850 MHz

Body SAR GSM 850 MHz (averaged over 1g tissue volume)								
Channel / frequency	Position	test condition	Body worn test result	Limit	Liquid temperature			
128 / 824.2 MHz	front	2 time slots	0.375 W/kg	1.6 W/kg	21.2 ℃			
190 / 836.6 MHz	front	2 time slots	0.449 W/kg	1.6 W/kg	21.2 ℃			
251 / 848.8 MHz	front	2 time slots	0.522 W/kg	1.6 W/kg	21.2 ℃			
128 / 824.2 MHz	rear	2 time slots	0.520 W/kg	1.6 W/kg	21.2 ℃			
190 / 836.6 MHz	rear	2 time slots	0.684 W/kg	1.6 W/kg	21.2 ℃			
251 / 848.8 MHz	rear	2 time slots	0.766 W/kg	1.6 W/kg	21.2 ℃			
251 / 848.8 MHz	rear	1 time slot	0.592 W/kg	1.6 W/kg	21.2 ℃			

Table 16: Test results body SAR GSM 850 MHz



Hea	Head SAR GSM 1900 MHz (averaged over 1g tissue volume)								
Channel / frequency	Position	Left hand test result	Right hand test result	Limit	Liquid tem left	perature right			
512 / 1850.2 MHz	cheek	0.468 W/kg	0.567 W/kg	1.6 W/kg	21.4 ℃	21.3 °C			
661 / 1880.0 MHz	cheek	0.470 W/kg	0.537 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
810 / 1909.8 MHz	cheek	0.499 W/kg	0.561 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
512 / 1850.2 MHz	tilted 15°	0.288 W/kg	0.286 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
661 / 1880.0 MHz	tilted 15°	0.259 W/kg	0.270 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
810 / 1909.8 MHz	tilted 15°	0.255 W/kg	0.284 W/kg	1.6 W/kg	21.4 ℃	21.3 °C			
		Slide	e opened						
512 / 1850.2 MHz	cheek	0.489 W/kg	0.377 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
661 / 1880.0 MHz	cheek	0.414 W/kg	0.326 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
810 / 1909.8 MHz	cheek	0.377 W/kg	0.312 W/kg	1.6 W/kg	21.4 ℃	21.3 °C			
512 / 1850.2 MHz	tilted 15°	0.205 W/kg	0.274 W/kg	1.6 W/kg	21.4 ℃	21.3 ℃			
661 / 1880.0 MHz	tilted 15°	0.186 W/kg	0.250 W/kg	1.6 W/kg	21.4 ℃	21.3 °C			
810 / 1909.8 MHz	tilted 15°	0.185 W/kg	0.236 W/kg	1.6 W/kg	21.4 °C	21.3 ℃			

Table 17: Test results head SAR GSM 1900 MHz

Body SAR GSM 1900 MHz (averaged over 1g tissue volume)								
Channel / frequency	Position	test condition	Body worn test result	Limit	Liquid temperature			
512 / 1850.2 MHz	front	2 time slots	0.200 W/kg	1.6 W/kg	21.3 ℃			
661 / 1880.0 MHz	front	2 time slots	0.176 W/kg	1.6 W/kg	21.3 ℃			
810 / 1909.8 MHz	front	2 time slots	0.156 W/kg	1.6 W/kg	21.3 ℃			
512 / 1850.2 MHz	rear	2 time slots	0.429 W/kg	1.6 W/kg	21.3 ℃			
661 / 1880.0 MHz	rear	2 time slots	0.393 W/kg	1.6 W/kg	21.3 ℃			
810 / 1909.8 MHz	rear	2 time slots	0.383 W/kg	1.6 W/kg	21.3 ℃			
512 / 1850.2 MHz	rear	1 time slot	0.411 W/kg	1.6 W/kg	21.3 ℃			

Table 18: Test results body SAR GSM 1900 MHz

Note:

The SAR test shall be performed at the high, middle and low frequency channels of each operating mode. If the SAR measured at mid-band channel for each test configuration is at least 3.0 dB lower than the SAR limit (< 0.8 W/kg), testing at the high and low channels is optional.

Tests in body position were performed with 15 mm air gap between DUT and SAM to simulate the use of a non-metallic belt-clip or holster.

The additional GSM body test was performed at worst case with 1 time slot in uplink in accordance with Sony Ericsson requirements.

7.2.2 General description of test procedures

The DUT is tested using a CMU 200 communications tester as controller unit to set test channels and maximum output power to the DUT, as well as for measuring the conducted peak power.

Test positions as described in the tables above are in accordance with the specified test standard.

Tests in body position were performed in that configuration, which generates the highest time based averaged output power (see conducted power results).

Tests in head position with GSM were performed in voice mode with 1 timeslot unless GPRS/EGPRS/DTM function allows parallel voice and data traffic on 2 or more timeslots (see section 2.3 for details).



8 Test equipment and ancillaries used for tests

To simplify the identification of the test equipment and/or ancillaries which were used, the reporting of the relevant test cases only refer to the test item number as specified in the table below.

No	used	Equipment	Туре	Manufacturer	Serial No.	Last Calibration	Frequency (months)
1	\boxtimes	Dosimetric E-Field Probe	ET3DV6	Schmid & Partner Engineering AG	1558	August 21, 2009	12
2		Dosimetric E-Field Probe	ET3DV6	Schmid & Partner Engineering AG	1559	January 14, 2009	12
3	\boxtimes	900 MHz System Validation Dipole	D900V2	Schmid & Partner Engineering AG	102	August 17, 2009	12
4		1800 MHz System Validation Dipole	D1800V2	Schmid & Partner Engineering AG	287	August 18, 2009	12
5	\boxtimes	1900 MHz System Validation Dipole	D1900V2	Schmid & Partner Engineering AG	531	August 18, 2009	12
6		2450 MHz System Validation Dipole	D2450V2	Schmid & Partner Engineering AG	710	August 17, 2009	12
7		Data acquisition electronics	DAE3V1	Schmid & Partner Engineering AG	413	January 8, 2009	12
8	\square	Data acquisition electronics	DAE3V1	Schmid & Partner Engineering AG	477	May 14, 2009	12
9	\boxtimes	Software	DASY 4 V4.5	Schmid & Partner Engineering AG		N/A	
10	\boxtimes	Phantom	SAM	Schmid & Partner Engineering AG		N/A	
11	\boxtimes	Universal Radio Communication Tester	CMU 200	Rohde & Schwarz	106826	January 12, 2010	12
12	\boxtimes	Network Analyser 300 kHz to 6 GHz	8753C	Hewlett Packard)*	2937U00269	January 8, 2010	12
13	\boxtimes	Network Analyser 300 kHz to 6 GHz	85047A	Hewlett Packard)*	2936A00872	January 8, 2010	12
14	\boxtimes	Dielectric Probe Kit	85070C	Hewlett Packard	US99360146	N/A	12
15	\boxtimes	Signal Generator	8665A	Hewlett Packard	2833A00112	January 8, 2010	12
16		Amplifier	25S1G4 (25 Watt)	Amplifier Reasearch	20452	N/A	
17	\square	Power Meter	NRP	Rohde & Schwarz	101367	January 8, 2010	12
18	\boxtimes	Power Meter Sensor	NRP Z22	Rohde & Schwarz	100227	January 8, 2010	12
19	\square	Power Meter Sensor	NRP Z22	Rohde & Schwarz	100234	January 8, 2010	12

)* : Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

9 **Observations**

No observations exceeding those reported with the single test cases have been made.



Annex A: System performance verification

Date/Time: 2010-01-25 14:21:30Date/Time: 2010-01-25 14:25:31

SystemPerformanceCheck-D900-850 head 2010-01-25

DUT: Dipole 900 MHz; Type: D900V2; Serial: 102

Communication System: CW; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: HSL850 Medium parameters used: f = 900 MHz; σ = 0.97 mho/m; ϵ_r = 41.9; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.84, 5.84, 5.84); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

d=15mm, Pin=1000mW/Area Scan (51x51x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 11.4 mW/g

d=15mm, Pin=1000mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 114.2 V/m; Power Drift = -0.019 dB Peak SAR (extrapolated) = 16.4 W/kg SAR(1 g) = 10.8 mW/g; SAR(10 g) = 6.87 mW/g Maximum value of SAR (measured) = 11.7 mW/g



 $0 \, dB = 11.7 mW/g$

Additional information:



Date/Time: 2010-01-20 13:37:57Date/Time: 2010-01-20 13:41:35 SystemPerformanceCheck-D900-850 body 2010-01-20

DUT: Dipole 900 MHz; Type: D900V2; Serial: 102

Communication System: CW; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: M850 Medium parameters used: f = 900 MHz; σ = 1.04 mho/m; ϵ_r = 53.8; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.63, 5.63, 5.63); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

d=15mm, Pin=1000mW/Area Scan (51x51x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 12.0 mW/g

d=15mm, Pin=1000mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 113.1 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 16.5 W/kg SAR(1 g) = 11.2 mW/g; SAR(10 g) = 7.27 mW/g Maximum value of SAR (measured) = 12.2 mW/g



 $0 \, dB = 12.2 mW/g$

Additional information:



Date/Time: 2010-01-21 12:56:30Date/Time: 2010-01-21 13:00:48 SystemPerformanceCheck-D1900 head 2010-01-21

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d009

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL1900 Medium parameters used (interpolated): f = 1900 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

d=10mm, Pin=1000mW/Area Scan (51x51x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 52.4 mW/g

d=10mm, Pin=1000mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 186.9 V/m; Power Drift = -0.024 dB Peak SAR (extrapolated) = 68.4 W/kg SAR(1 g) = 38.6 mW/g; SAR(10 g) = 20.2 mW/g Maximum value of SAR (measured) = 43.8 mW/g



0 dB = 43.8 mW/g

Additional information:



Date/Time: 2010-01-28 08:40:33Date/Time: 2010-01-28 09:00:47 SystemPerformanceCheck-D1900 body 2010-01-28

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d009

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: M1900 Medium parameters used (interpolated): f = 1900 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

d=10mm, Pin=1000mW/Area Scan (51x51x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 52.6 mW/g

d=10mm, Pin=1000mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 183.7 V/m; Power Drift = -0.00 dB Peak SAR (extrapolated) = 63.4 W/kg SAR(1 g) = 37.2 mW/g; SAR(10 g) = 20.2 mW/g Maximum value of SAB (measured) = 42.9 mW/g





 $0 \, dB = 42.9 \, mW/g$

Additional information:



Annex B: DASY4 measurement results

Annex B.1: GSM 850 MHz head

Date/Time: 2010-01-25 08:55:11Date/Time: 2010-01-25 09:01:09

IEEE1528_OET65-LeftHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn477; Calibrated: 2009-05-14

- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.815 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 30.8 V/m; Power Drift = -0.023 dB Peak SAR (extrapolated) = 0.996 W/kg SAR(1 g) = 0.762 mW/g; SAR(10 g) = 0.546 mW/g Maximum value of SAR (measured) = 0.808 mW/g



Additional information:



Date/Time: 2010-01-25 08:34:07Date/Time: 2010-01-25 08:40:03

IEEE1528_OET65-LeftHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.987 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 33.9 V/m; Power Drift = -0.061 dB Peak SAR (extrapolated) = 1.20 W/kg SAR(1 g) = 0.924 mW/g; SAR(10 g) = 0.663 mW/g Maximum value of SAR (measured) = 0.982 mW/g



Additional information:



Date/Time: 2010-01-25 09:16:24Date/Time: 2010-01-25 09:22:26

IEEE1528_OET65-LeftHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.992 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 34.0 V/m; Power Drift = -0.055 dB Peak SAR (extrapolated) = 1.25 W/kg SAR(1 g) = 0.922 mW/g; SAR(10 g) = 0.655 mW/g Maximum value of SAR (measured) = 0.980 mW/g



0 dB = 0.980 mW/g

Additional information:



Date/Time: 2010-01-25 10:50:59Date/Time: 2010-01-25 10:57:12Date/Time: 2010-01-25 11:08:59 IEEE1528 OET65-LeftHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.430 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.0 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.511 W/kg

SAR(1 g) = 0.423 mW/g; SAR(10 g) = 0.319 mW/g

Maximum value of SAR (measured) = 0.440 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 22.0 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.924 W/kg

SAR(1 g) = 0.335 mW/g; SAR(10 g) = 0.212 mW/g Maximum value of SAR (measured) = 0.369 mW/g



 $0 \, dB = 0.369 \, mW/g$

Additional information:



Date/Time: 2010-01-25 10:13:36Date/Time: 2010-01-25 10:19:43Date/Time: 2010-01-25 10:31:31 IEEE1528_OET65-LeftHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn477; Calibrated: 2009-05-14

- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.545 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.7 V/m; Power Drift = 0.039 dBPeak SAR (extrapolated) = 0.653 W/kg

SAR(1 g) = 0.538 mW/g; SAR(10 g) = 0.403 mW/g Maximum value of SAR (measured) = 0.562 mW/g

 T_{1} and T_{2} and T_{2} and T_{2} and T_{2} and T_{2} and T_{2}

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 24.7 V/m; Power Drift = 0.039 dB Peak SAR (extrapolated) = 1.23 W/kg SAR(1 g) = 0.429 mW/g; SAR(10 g) = 0.269 mW/g

Maximum value of SAR (measured) = 0.466 mW/g



0 dB = 0.466 mW/g




Date/Time: 2010-01-25 09:37:26Date/Time: 2010-01-25 09:44:17Date/Time: 2010-01-25 09:57:28 IEEE1528_OET65-LeftHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn477; Calibrated: 2009-05-14

- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.567 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.3 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.667 W/kg

SAR(1 g) = 0.551 mW/g; SAR(10 g) = 0.414 mW/g

Maximum value of SAR (measured) = 0.578 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 25.3 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 1.24 W/kg SAR(1 g) = 0.435 mW/g; SAR(10 g) = 0.275 mW/g Maximum value of SAR (measured) = 0.470 mW/g



0 dB = 0.470 mW/g

Additional information:



Date/Time: 2010-01-25 13:11:12Date/Time: 2010-01-25 13:17:53

IEEE1528_OET65-LeftHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.627 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 27.2 V/m; Power Drift = 0.015 dB Peak SAR (extrapolated) = 1.00 W/kg SAR(1 g) = 0.617 mW/g; SAR(10 g) = 0.436 mW/g Maximum value of SAR (measured) = 0.664 mW/g



0 dB = 0.664 mW/g

Additional information:



Date/Time: 2010-01-25 13:33:10Date/Time: 2010-01-25 13:39:53

IEEE1528_OET65-LeftHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.756 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 29.6 V/m; Power Drift = -0.036 dB Peak SAR (extrapolated) = 1.24 W/kg SAR(1 g) = 0.739 mW/g; SAR(10 g) = 0.513 mW/g Maximum value of SAR (measured) = 0.787 mW/g



0 dB = 0.787 mW/g

Additional information:



Date/Time: 2010-01-25 13:55:42Date/Time: 2010-01-25 14:02:45

IEEE1528_OET65-LeftHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.842 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 31.2 V/m; Power Drift = -0.014 dB Peak SAR (extrapolated) = 1.40 W/kg SAR(1 g) = 0.824 mW/g; SAR(10 g) = 0.565 mW/g Maximum value of SAR (measured) = 0.905 mW/g



0 dB = 0.905 mW/g

Additional information:



Date/Time: 2010-01-25 12:38:28Date/Time: 2010-01-25 12:45:29Date/Time: 2010-01-25 12:57:11 IEEE1528 OET65-LeftHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.248 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.9 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.289 W/kg

SAR(1 g) = 0.242 mW/g; SAR(10 g) = 0.184 mW/g

Maximum value of SAR (measured) = 0.252 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 16.9 V/m; Power Drift = 0.021 dB Peak SAR (extrapolated) = 0.542 W/kg

SAR(1 g) = 0.215 mW/g; SAR(10 g) = 0.153 mW/g

Maximum value of SAR (measured) = 0.239 mW/g



Additional information:



Date/Time: 2010-01-25 11:32:14Date/Time: 2010-01-25 11:40:09Date/Time: 2010-01-25 11:52:37 IEEE1528_OET65-LeftHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8 Medium: HSL850 Medium parameters used: f = 836.6 MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 42.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section $PAOV4 O a s f = 0.91 \text{ mno/m}; \epsilon_r = 42.7; \rho = 1000 \text{ kg/m}$

DASY4 Configuration:

- Probe: ET3DV6 - SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn477; Calibrated: 2009-05-14

- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.290 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.3 V/m; Power Drift = -0.016 dB Peak SAR (extrapolated) = 0.335 W/kg

SAR(1 g) = 0.279 mW/g; SAR(10 g) = 0.213 mW/g Maximum value of SAR (measured) = 0.289 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.3 V/m; Power Drift = -0.016 dB Peak SAR (extrapolated) = 0.619 W/kg SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.174 mW/g Maximum value of SAR (measured) = 0.275 mW/g



Additional information:



Date/Time: 2010-01-25 12:06:06Date/Time: 2010-01-25 12:13:08Date/Time: 2010-01-25 12:24:25 IEEE1528 OET65-LeftHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.327 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.3 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.696 W/kg

SAR(1 g) = 0.279 mW/g; SAR(10 g) = 0.198 mW/g

Maximum value of SAR (measured) = 0.313 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 19.3 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.374 W/kg

SAR(1 g) = 0.311 mW/g; SAR(10 g) = 0.236 mW/g

Maximum value of SAR (measured) = 0.326 mW/g



Additional information:



Date/Time: 2010-01-25 15:04:12Date/Time: 2010-01-25 15:10:06

IEEE1528_OET65-RightHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.686 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 28.4 V/m; Power Drift = 0.016 dB Peak SAR (extrapolated) = 0.939 W/kg SAR(1 g) = 0.639 mW/g; SAR(10 g) = 0.468 mW/g Maximum value of SAR (measured) = 0.675 mW/g



0 dB = 0.675 mW/g

Additional information:



Date/Time: 2010-01-25 14:42:51Date/Time: 2010-01-25 14:48:46

IEEE1528_OET65-RightHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.870 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 32.0 V/m; Power Drift = -0.038 dB Peak SAR (extrapolated) = 1.11 W/kg SAR(1 g) = 0.790 mW/g; SAR(10 g) = 0.578 mW/g Maximum value of SAR (measured) = 0.838 mW/g



0 dB = 0.838 mW/g

Additional information:



Date/Time: 2010-01-25 15:25:07Date/Time: 2010-01-25 15:31:03

IEEE1528_OET65-RightHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.851 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 31.3 V/m; Power Drift = -0.00 dB Peak SAR (extrapolated) = 1.11 W/kg SAR(1 g) = 0.786 mW/g; SAR(10 g) = 0.570 mW/g Maximum value of SAR (measured) = 0.844 mW/g



 $0 \, dB = 0.844 \, mW/g$

Additional information:



Date/Time: 2010-01-25 16:54:32Date/Time: 2010-01-25 17:00:41Date/Time: 2010-01-25 17:12:01 IEEE1528 OET65-RightHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.457 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 23.1 V/m; Power Drift = -0.052 dB Peak SAR (extrapolated) = 0.549 W/kg SAR(1 g) = 0.442 mW/g; SAR(10 g) = 0.332 mW/g Maximum value of SAR (measured) = 0.466 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 23.1 V/m; Power Drift = -0.052 dB Peak SAR (extrapolated) = 1.14 W/kg SAR(1 g) = 0.379 mW/g; SAR(10 g) = 0.239 mW/g Maximum value of SAR (measured) = 0.403 mW/g



Additional information:



Date/Time: 2010-01-25 16:17:25Date/Time: 2010-01-25 16:23:34Date/Time: 2010-01-25 16:35:24 IEEE1528 OET65-RightHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.591 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

 $\label{eq:source} \begin{array}{l} dx{=}5mm, \, dy{=}5mm, \, dz{=}5mm \\ \text{Reference Value} = 26.2 \ \text{V/m}; \ \text{Power Drift} = 0.020 \ \text{dB} \\ \text{Peak SAR (extrapolated)} = 0.715 \ \text{W/kg} \\ \textbf{SAR(1 g)} = \textbf{0.570 mW/g}; \ \textbf{SAR(10 g)} = \textbf{0.424 mW/g} \\ \text{Maximum value of SAR (measured)} = 0.601 \ \text{mW/g} \end{array}$

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 26.2 V/m; Power Drift = 0.020 dB Peak SAR (extrapolated) = 1.43 W/kg SAR(1 g) = 0.483 mW/g; SAR(10 g) = 0.310 mW/g Maximum value of SAR (measured) = 0.506 mW/g



Additional information:



Date/Time: 2010-01-25 15:46:15Date/Time: 2010-01-25 15:52:20Date/Time: 2010-01-25 16:03:39 IEEE1528 OET65-RightHandSide-GSM850

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.613 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 26.7 V/m; Power Drift = -0.012 dB Peak SAR (extrapolated) = 0.746 W/kg SAR(1 g) = 0.584 mW/g; SAR(10 g) = 0.434 mW/g Maximum value of SAR (measured) = 0.613 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 26.7 V/m; Power Drift = -0.012 dB Peak SAR (extrapolated) = 1.54 W/kg SAR(1 g) = 0.506 mW/g; SAR(10 g) = 0.319 mW/g Maximum value of SAR (measured) = 0.540 mW/g



Additional information:



Date/Time: 2010-01-25 17:30:24Date/Time: 2010-01-25 17:38:33Date/Time: 2010-01-25 17:50:25 IEEE1528_OET65-RightHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.556 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

ax=5mm, dy=5mm, dz=5mm Reference Value = 25.5 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 0.736 W/kg

SAR(1 g) = 0.530 mW/g; SAR(10 g) = 0.385 mW/g

Maximum value of SAR (measured) = 0.565 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.5 V/m; Power Drift = -0.060 dB Peak SAR (extrapolated) = 0.866 W/kg

SAR(1 g) = 0.506 mW/g; SAR(10 g) = 0.346 mW/g

Maximum value of SAR (measured) = 0.545 mW/g



 $0 \, dB = 0.545 mW/g$

Additional information:



Date/Time: 2010-01-25 18:05:13Date/Time: 2010-01-25 18:11:45Date/Time: 2010-01-25 18:23:34 IEEE1528 OET65-RightHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.659 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.8 V/m; Power Drift = -0.060 dB Peak SAR (extrapolated) = 0.805 W/kg SAR(1 g) = 0.604 mW/g; SAR(10 g) = 0.440 mW/g Maximum value of SAR (measured) = 0.648 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.8 V/m; Power Drift = -0.060 dB Peak SAR (extrapolated) = 0.961 W/kg SAR(1 g) = 0.581 mW/g; SAR(10 g) = 0.387 mW/g



 $0 \, dB = 0.635 mW/g$

Additional information:



Date/Time: 2010-01-25 18:38:30Date/Time: 2010-01-25 18:45:06Date/Time: 2010-01-25 18:56:59 IEEE1528_OET65-RightHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.718 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 28.9 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 1.01 W/kg SAR(1 g) = 0.678 mW/g; SAR(10 g) = 0.485 mW/g Maximum value of SAR (measured) = 0.724 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 28.9 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 1.23 W/kg SAR(1 g) = 0.675 mW/g; SAR(10 g) = 0.434 mW/g Maximum value of SAR (measured) = 0.716 mW/g



Additional information:



Date/Time: 2010-01-25 19:12:59Date/Time: 2010-01-25 19:19:56Date/Time: 2010-01-25 19:31:16 IEEE1528_OET65-RightHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 824.2 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 824.2 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.316 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

 $\label{eq:source} \begin{array}{l} dy{=}5mm, \, dz{=}5mm \\ \text{Reference Value} = 18.5 \ \text{V/m}; \ \text{Power Drift} = 0.051 \ \text{dB} \\ \text{Peak SAR (extrapolated)} = 0.767 \ \text{W/kg} \\ \textbf{SAR(1 g)} = \textbf{0.254 mW/g}; \ \textbf{SAR(10 g)} = \textbf{0.153 mW/g} \\ \text{Maximum value of SAR (measured)} = 0.270 \ \text{mW/g} \end{array}$

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 18.5 V/m; Power Drift = 0.051 dB Peak SAR (extrapolated) = 0.355 W/kg SAR(1 g) = 0.282 mW/g; SAR(10 g) = 0.215 mW/g Maximum value of SAR (measured) = 0.295 mW/g



Additional information:



Date/Time: 2010-01-25 19:48:18Date/Time: 2010-01-25 19:55:17Date/Time: 2010-01-25 20:07:06 IEEE1528 OET65-RightHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 836.6 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.367 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 20.7 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.446 W/kg

SAR(1 g) = 0.354 mW/g; SAR(10 g) = 0.267 mW/g

Maximum value of SAR (measured) = 0.372 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.7 V/m; Power Drift = -0.00 dB Peak SAR (extrapolated) = 0.968 W/kg

SAR(1 g) = 0.303 mW/g; SAR(10 g) = 0.192 mW/g

Maximum value of SAR (measured) = 0.317 mW/g



Additional information:



Date/Time: 2010-01-25 20:21:20Date/Time: 2010-01-25 20:29:36Date/Time: 2010-01-25 20:42:28 IEEE1528 OET65-RightHandSide-GSM850open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: HSL850 Medium parameters used: f = 848.8 MHz; σ = 0.91 mho/m; ϵ_r = 42.7; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(6.02, 6.02, 6.02); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.404 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

 $\label{eq:source} \begin{array}{l} dy{=}5mm, \, dz{=}5mm \\ \text{Reference Value} = 21.6 \ \text{V/m}; \ \text{Power Drift} = 0.00 \ \text{dB} \\ \text{Peak SAR (extrapolated)} = 0.499 \ \text{W/kg} \\ \textbf{SAR(1 g)} = \textbf{0.389 mW/g}; \ \textbf{SAR(10 g)} = \textbf{0.292 mW/g} \\ \text{Maximum value of SAR (measured)} = 0.413 \ \text{mW/g} \end{array}$

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 21.6 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 1.03 W/kg SAR(1 g) = 0.332 mW/g; SAR(10 g) = 0.211 mW/g Maximum value of SAR (measured) = 0.353 mW/g



Additional information:



Annex B.2: GSM 850 MHz body

Date/Time: 2010-01-20 14:02:32Date/Time: 2010-01-20 14:13:18

IEEE1528 OET65-Body-GSM850 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850 GPRS 2TS; Frequency: 824.2 MHz; Duty Cycle: 1.4

Medium: M850 Medium parameters used: f = 824.2 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Front position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.403 mW/g

Front position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mmReference Value = 21.2 V/m; Power Drift = -0.115 dB Peak SAR (extrapolated) = 0.479 W/kg SAR(1 g) = 0.375 mW/g; SAR(10 g) = 0.280 mW/gMaximum value of SAR (measured) = 0.396 mW/g



 $0 \, dB = 0.396 \, mW/g$

Additional information:



Date/Time: 2010-01-20 14:36:45Date/Time: 2010-01-20 14:51:51

IEEE1528_OET65-Body-GSM850 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850 GPRS 2TS; Frequency: 836.6 MHz; Duty Cycle: 1:4 Medium: M850 Medium parameters used: f = 836.6 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Front position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.485 mW/g

Front position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 23.0 V/m; Power Drift = -0.078 dB Peak SAR (extrapolated) = 0.585 W/kg SAR(1 g) = 0.449 mW/g; SAR(10 g) = 0.334 mW/g Maximum value of SAR (measured) = 0.475 mW/g



0 dB = 0.475 mW/g

Additional information:



Date/Time: 2010-01-20 15:05:53Date/Time: 2010-01-20 15:12:41

IEEE1528_OET65-Body-GSM850 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850 GPRS 2TS; Frequency: 848.8 MHz; Duty Cycle: 1:4 Medium: M850 Medium parameters used: f = 848.8 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Front position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.553 mW/g

Front position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 24.7 V/m; Power Drift = 0.028 dB Peak SAR (extrapolated) = 0.667 W/kg SAR(1 g) = 0.522 mW/g; SAR(10 g) = 0.387 mW/g Maximum value of SAR (measured) = 0.550 mW/g



 $0 \, dB = 0.550 \, mW/g$

Additional information: position or distance of DUT to SAM: 15 mm ambient temperature: 22.8 °C; liquid temperature: 21.2 °C



Date/Time: 2010-01-20 15:29:19Date/Time: 2010-01-20 15:35:12

IEEE1528_OET65-Body-GSM850 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850 GPRS 2TS; Frequency: 824.2 MHz; Duty Cycle: 1:4 Medium: M850 Medium parameters used: f = 824.2 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.561 mW/g

Rear position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 24.6 V/m; Power Drift = 0.059 dB Peak SAR (extrapolated) = 0.745 W/kg SAR(1 g) = 0.520 mW/g; SAR(10 g) = 0.360 mW/g Maximum value of SAR (measured) = 0.556 mW/g



Additional information:



Date/Time: 2010-01-20 15:57:24Date/Time: 2010-01-20 16:09:26Date/Time: 2010-01-20 16:21:10 IEEE1528_OET65-Body-GSM850 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850 GPRS 2TS; Frequency: 836.6 MHz; Duty Cycle: 1:4 Medium: M850 Medium parameters used: f = 836.6 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.739 mW/g

Rear position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 28.1 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 0.961 W/kg

SAR(1 g) = 0.684 mW/g; SAR(10 g) = 0.474 mW/g

Maximum value of SAR (measured) = 0.728 mW/g

Rear position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 28.1 V/m; Power Drift = -0.042 dBPeak SAR (extrapolated) = 0.986 W/kgSAR(1 g) = 0.667 mW/g; SAR(10 g) = 0.432 mW/g



 $0 \, dB = 0.728 mW/g$





Date/Time: 2010-01-20 16:37:02Date/Time: 2010-01-20 16:43:00

IEEE1528_OET65-Body-GSM850 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 850 GPRS 2TS; Frequency: 848.8 MHz; Duty Cycle: 1:4 Medium: M850 Medium parameters used: f = 848.8 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position -High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.812 mW/g

Rear position -High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 30.0 V/m; Power Drift = -0.027 dB Peak SAR (extrapolated) = 1.09 W/kg SAR(1 g) = 0.766 mW/g; SAR(10 g) = 0.527 mW/g Maximum value of SAR (measured) = 0.811 mW/g



Additional information:



Date/Time: 2010-01-20 17:01:02Date/Time: 2010-01-20 17:08:04Date/Time: 2010-01-20 17:19:47 IEEE1528_OET65-Body-GSM850 GPRS 1TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: PCS 850; Frequency: 848.8 MHz; Duty Cycle: 1:8

Medium: M850 Medium parameters used: f = 848.8 MHz; σ = 0.97 mho/m; ϵ_r = 54.5; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(5.78, 5.78, 5.78); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position -High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.626 mW/g

Rear position -High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 26.1 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.849 W/kg

SAR(1 g) = 0.592 mW/g; SAR(10 g) = 0.409 mW/g

Maximum value of SAR (measured) = 0.638 mW/g

Rear position -High/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.1 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 0.874 W/kg

SAR(1 g) = 0.583 mW/g; SAR(10 g) = 0.374 mW/g

Maximum value of SAR (measured) = 0.633 mW/g



Additional information:

Test report no.: 1-1954-02-02/10



Annex B.3: GSM 1900 MHz head

Date/Time: 2010-01-21 08:29:53Date/Time: 2010-01-21 08:49:26Date/Time: 2010-01-21 09:03:00 IEEE1528 OET65-LeftHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.481 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.8 V/m; Power Drift = 0.00 dBPeak SAR (extrapolated) = 0.718 W/kg

SAR(1 g) = 0.468 mW/g; SAR(10 g) = 0.279 mW/g Maximum value of SAR (measured) = 0.511 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 18.8 V/m; Power Drift = 0.00 dBPeak SAR (extrapolated) = 0.595 W/kgSAR(1 g) = 0.405 mW/g; SAR(10 g) = 0.251 mW/g

Maximum value of SAR (measured) = 0.428 mW/g



0 dB = 0.428 mW/g

Additional information:



Date/Time: 2010-01-21 07:54:38Date/Time: 2010-01-21 08:00:36Date/Time: 2010-01-21 08:12:47 IEEE1528 OET65-LeftHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.483 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.0 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.698 W/kg

SAR(1 g) = 0.470 mW/g; SAR(10 g) = 0.278 mW/g

Maximum value of SAR (measured) = 0.516 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.0 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 0.578 W/kg

SAR(1 g) = 0.403 mW/g; SAR(10 g) = 0.254 mW/g

Maximum value of SAR (measured) = 0.413 mW/g



 $0 \, dB = 0.413 mW/g$

Additional information:



Date/Time: 2010-01-21 09:18:31Date/Time: 2010-01-21 09:24:36

IEEE1528_OET65-LeftHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.509 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 19.5 V/m; Power Drift = 0.048 dB Peak SAR (extrapolated) = 0.753 W/kg SAR(1 g) = 0.499 mW/g; SAR(10 g) = 0.294 mW/g Maximum value of SAR (measured) = 0.548 mW/g



0 dB = 0.548 mW/g

Additional information:



Date/Time: 2010-01-21 10:22:44Date/Time: 2010-01-21 10:29:22

IEEE1528_OET65-LeftHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.304 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 15.5 V/m; Power Drift = 0.089 dB Peak SAR (extrapolated) = 0.449 W/kg SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.174 mW/g Maximum value of SAR (measured) = 0.320 mW/g



0 dB = 0.320 mW/g

Additional information:



Date/Time: 2010-01-21 10:03:12Date/Time: 2010-01-21 10:09:21

IEEE1528_OET65-LeftHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.274 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 14.7 V/m; Power Drift = 0.011 dB Peak SAR (extrapolated) = 0.413 W/kg SAR(1 g) = 0.259 mW/g; SAR(10 g) = 0.154 mW/g Maximum value of SAR (measured) = 0.287 mW/g



0 dB = 0.287 mW/g

Additional information:



Date/Time: 2010-01-21 09:43:39Date/Time: 2010-01-21 09:49:50

IEEE1528_OET65-LeftHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.273 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 14.7 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 0.407 W/kg SAR(1 g) = 0.255 mW/g; SAR(10 g) = 0.152 mW/g Maximum value of SAR (measured) = 0.281 mW/g



 $0 \, dB = 0.281 \, mW/g$

Additional information:



Date/Time: 2010-01-21 12:30:37Date/Time: 2010-01-21 12:37:28

IEEE1528_OET65-LeftHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.483 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 18.4 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.814 W/kg SAR(1 g) = 0.489 mW/g; SAR(10 g) = 0.281 mW/g Maximum value of SAR (measured) = 0.542 mW/g



 $0 \, dB = 0.542 mW/g$

Additional information:



Date/Time: 2010-01-21 12:08:04Date/Time: 2010-01-21 12:14:46

IEEE1528_OET65-LeftHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.413 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 16.9 V/m; Power Drift = -0.00 dB Peak SAR (extrapolated) = 0.698 W/kg SAR(1 g) = 0.414 mW/g; SAR(10 g) = 0.236 mW/g Maximum value of SAR (measured) = 0.451 mW/g



0 dB = 0.451 mW/g

Additional information:



Date/Time: 2010-01-21 11:45:09Date/Time: 2010-01-21 11:51:50

IEEE1528_OET65-LeftHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.368 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 16.1 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.658 W/kg SAR(1 g) = 0.377 mW/g; SAR(10 g) = 0.212 mW/g Maximum value of SAR (measured) = 0.411 mW/g



 $0 \, dB = 0.411 mW/g$

Additional information:



Date/Time: 2010-01-21 10:43:53Date/Time: 2010-01-21 10:50:50

IEEE1528_OET65-LeftHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.253 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 13.3 V/m; Power Drift = -0.011 dB Peak SAR (extrapolated) = 0.326 W/kg SAR(1 g) = 0.205 mW/g; SAR(10 g) = 0.129 mW/g Maximum value of SAR (measured) = 0.222 mW/g



 $0 \, dB = 0.222 mW/g$

Additional information:


Date/Time: 2010-01-21 11:04:07Date/Time: 2010-01-21 11:11:03

IEEE1528_OET65-LeftHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.227 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 12.7 V/m; Power Drift = -0.037 dB Peak SAR (extrapolated) = 0.301 W/kg SAR(1 g) = 0.186 mW/g; SAR(10 g) = 0.114 mW/g Maximum value of SAR (measured) = 0.200 mW/g



0 dB = 0.200 mW/g

Additional information:



Date/Time: 2010-01-21 11:24:22Date/Time: 2010-01-21 11:31:26

IEEE1528_OET65-LeftHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.224 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 12.7 V/m; Power Drift = 0.022 dB Peak SAR (extrapolated) = 0.304 W/kg SAR(1 g) = 0.185 mW/g; SAR(10 g) = 0.110 mW/g Maximum value of SAR (measured) = 0.205 mW/g



0 dB = 0.205 mW/g

Additional information:



Date/Time: 2010-01-21 13:42:28Date/Time: 2010-01-21 13:49:28

IEEE1528_OET65-RightHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.645 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 20.7 V/m; Power Drift = -0.013 dB Peak SAR (extrapolated) = 0.899 W/kg SAR(1 g) = 0.567 mW/g; SAR(10 g) = 0.315 mW/g Maximum value of SAR (measured) = 0.628 mW/g



0 dB = 0.628 mW/g

Additional information:



Date/Time: 2010-01-21 13:18:02Date/Time: 2010-01-21 13:25:32

IEEE1528_OET65-RightHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.603 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 20.4 V/m; Power Drift = -0.00 dB Peak SAR (extrapolated) = 0.872 W/kg SAR(1 g) = 0.537 mW/g; SAR(10 g) = 0.297 mW/g Maximum value of SAR (measured) = 0.600 mW/g



0 dB = 0.600 mW/g

Additional information:



Date/Time: 2010-01-21 14:07:50Date/Time: 2010-01-21 14:13:44

IEEE1528_OET65-RightHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.630 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 20.8 V/m; Power Drift = 0.050 dB Peak SAR (extrapolated) = 0.910 W/kg SAR(1 g) = 0.561 mW/g; SAR(10 g) = 0.312 mW/g Maximum value of SAR (measured) = 0.614 mW/g



 $0 \, dB = 0.614 mW/g$

Additional information:



Date/Time: 2010-01-21 15:09:19Date/Time: 2010-01-21 15:15:20

IEEE1528_OET65-RightHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.324 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 14.5 V/m; Power Drift = -0.042 dB Peak SAR (extrapolated) = 0.504 W/kg SAR(1 g) = 0.286 mW/g; SAR(10 g) = 0.171 mW/g Maximum value of SAR (measured) = 0.310 mW/g



 $0 \, dB = 0.310 mW/g$

Additional information:



Date/Time: 2010-01-21 14:49:23Date/Time: 2010-01-21 14:55:23

IEEE1528_OET65-RightHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.314 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 14.3 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 0.479 W/kg SAR(1 g) = 0.270 mW/g; SAR(10 g) = 0.160 mW/g Maximum value of SAR (measured) = 0.292 mW/g



0 dB = 0.292 mW/g

Additional information:



Date/Time: 2010-01-21 14:29:32Date/Time: 2010-01-21 14:35:31

IEEE1528_OET65-RightHandSide-GSM1900

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.327 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 14.6 V/m; Power Drift = 0.060 dB Peak SAR (extrapolated) = 0.510 W/kg SAR(1 g) = 0.284 mW/g; SAR(10 g) = 0.164 mW/g Maximum value of SAR (measured) = 0.312 mW/g



0 dB = 0.312 mW/g

Additional information:



Date/Time: 2010-01-21 17:20:00Date/Time: 2010-01-21 17:26:37

IEEE1528_OET65-RightHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.421 mW/g

Touch position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 17.7 V/m; Power Drift = 0.041 dB Peak SAR (extrapolated) = 0.557 W/kg SAR(1 g) = 0.377 mW/g; SAR(10 g) = 0.236 mW/g Maximum value of SAR (measured) = 0.405 mW/g



Additional information:



Date/Time: 2010-01-21 16:36:04Date/Time: 2010-01-21 16:42:47

IEEE1528_OET65-RightHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.377 mW/g

Touch position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 16.6 V/m; Power Drift = -0.018 dB Peak SAR (extrapolated) = 0.479 W/kg SAR(1 g) = 0.326 mW/g; SAR(10 g) = 0.202 mW/g Maximum value of SAR (measured) = 0.355 mW/g



0 dB = 0.355 mW/g

Additional information:



Date/Time: 2010-01-21 16:57:39Date/Time: 2010-01-21 17:04:14

IEEE1528_OET65-RightHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Touch position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.347 mW/g

Touch position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 16.4 V/m; Power Drift = -0.031 dB Peak SAR (extrapolated) = 0.476 W/kg SAR(1 g) = 0.312 mW/g; SAR(10 g) = 0.191 mW/g Maximum value of SAR (measured) = 0.339 mW/g



 $0 \, dB = 0.339 mW/g$

Additional information:



Date/Time: 2010-01-21 15:30:03Date/Time: 2010-01-21 15:38:23

IEEE1528_OET65-RightHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1850.2 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Low/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.319 mW/g

Tilt position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 14.4 V/m; Power Drift = -0.070 dB Peak SAR (extrapolated) = 0.430 W/kg SAR(1 g) = 0.274 mW/g; SAR(10 g) = 0.161 mW/g Maximum value of SAR (measured) = 0.300 mW/g



0 dB = 0.300 mW/g

Additional information:



Date/Time: 2010-01-21 15:52:06Date/Time: 2010-01-21 15:58:53

IEEE1528_OET65-RightHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1880 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - Middle/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.297 mW/g

Tilt position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 13.7 V/m; Power Drift = 0.016 dB Peak SAR (extrapolated) = 0.417 W/kg SAR(1 g) = 0.250 mW/g; SAR(10 g) = 0.145 mW/g Maximum value of SAR (measured) = 0.274 mW/g



0 dB = 0.274 mW/g

Additional information:



Date/Time: 2010-01-21 16:12:25Date/Time: 2010-01-21 16:19:10

IEEE1528_OET65-RightHandSide-GSM1900open

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8

Medium: HSL1900 Medium parameters used: f = 1909.8 MHz; σ = 1.4 mho/m; ϵ_r = 40.5; ρ = 1000 kg/m³ Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.75, 4.75, 4.75); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilt position - High/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.276 mW/g

Tilt position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 13.3 V/m; Power Drift = 0.058 dB Peak SAR (extrapolated) = 0.409 W/kg SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.134 mW/g Maximum value of SAR (measured) = 0.260 mW/g



0 dB = 0.260 mW/g

Additional information:



Annex B.4: GSM 1900 MHz body

Date/Time: 2010-01-28 09:31:46Date/Time: 2010-01-28 09:47:18

IEEE1528_OET65-Body-GSM1900 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900 GPRS 2TS; Frequency: 1850.2 MHz; Duty Cycle: 1:4 Medium: M1900 Medium parameters used: f = 1850.2 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Front position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.226 mW/g

Front position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 13.0 V/m; Power Drift = -0.111 dB Peak SAR (extrapolated) = 0.267 W/kg SAR(1 g) = 0.200 mW/g; SAR(10 g) = 0.134 mW/g

Maximum value of SAR (measured) = 0.214 mW/g



 $0 \, dB = 0.214 mW/g$

Additional information:



Date/Time: 2010-01-28 10:07:44Date/Time: 2010-01-28 10:14:26

IEEE1528_OET65-Body-GSM1900 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900 GPRS 2TS; Frequency: 1880 MHz; Duty Cycle: 1:4 Medium: M1900 Medium parameters used: f = 1880 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Front position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.193 mW/g

Front position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 12.0 V/m; Power Drift = -0.027 dB Peak SAR (extrapolated) = 0.237 W/kg SAR(1 g) = 0.176 mW/g; SAR(10 g) = 0.117 mW/g Maximum value of SAR (measured) = 0.189 mW/g



 $0 \, dB = 0.189 mW/g$

Additional information:



Date/Time: 2010-01-28 10:30:04Date/Time: 2010-01-28 10:36:01

IEEE1528_OET65-Body-GSM1900 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900 GPRS 2TS; Frequency: 1909.8 MHz; Duty Cycle: 1:4 Medium: M1900 Medium parameters used: f = 1909.8 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Front position - High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.173 mW/g

Front position - High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 11.2 V/m; Power Drift = 0.047 dB Peak SAR (extrapolated) = 0.214 W/kg SAR(1 g) = 0.156 mW/g; SAR(10 g) = 0.103 mW/g Maximum value of SAR (measured) = 0.169 mW/g



0 dB = 0.169 mW/g

Additional information: position or distance of DUT to SAM: 15 mm ambient temperature: 22.4 °C; liquid temperature: 21.3 °C



Date/Time: 2010-01-28 11:35:19Date/Time: 2010-01-28 11:41:15

IEEE1528_OET65-Body-GSM1900 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900 GPRS 2TS; Frequency: 1850.2 MHz; Duty Cycle: 1:4 Medium: M1900 Medium parameters used: f = 1850.2 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.477 mW/g

Rear position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 18.6 V/m; Power Drift = -0.015 dB Peak SAR (extrapolated) = 0.636 W/kg SAR(1 g) = 0.429 mW/g; SAR(10 g) = 0.264 mW/g Maximum value of SAR (measured) = 0.471 mW/g



Additional information:



Date/Time: 2010-01-28 11:14:24Date/Time: 2010-01-28 11:20:21

IEEE1528_OET65-Body-GSM1900 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900 GPRS 2TS; Frequency: 1880 MHz; Duty Cycle: 1:4 Medium: M1900 Medium parameters used: f = 1880 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position - Middle/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.444 mW/g

Rear position - Middle/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 17.8 V/m; Power Drift = 0.014 dB Peak SAR (extrapolated) = 0.590 W/kg SAR(1 g) = 0.393 mW/g; SAR(10 g) = 0.240 mW/g Maximum value of SAR (measured) = 0.425 mW/g



 $0 \, dB = 0.425 mW/g$

Additional information:



Date/Time: 2010-01-28 10:53:24Date/Time: 2010-01-28 10:59:20

IEEE1528_OET65-Body-GSM1900 GPRS 2TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: GSM 1900 GPRS 2TS; Frequency: 1909.8 MHz; Duty Cycle: 1:4 Medium: M1900 Medium parameters used: f = 1909.8 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position -High/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.423 mW/g

Rear position -High/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 17.7 V/m; Power Drift = 0.032 dB Peak SAR (extrapolated) = 0.580 W/kg SAR(1 g) = 0.383 mW/g; SAR(10 g) = 0.234 mW/g Maximum value of SAR (measured) = 0.418 mW/g



 $0 \, dB = 0.418 \, mW/g$

Additional information:



Date/Time: 2010-01-28 11:57:12Date/Time: 2010-01-28 12:07:48

IEEE1528_OET65-Body-GSM1900 GPRS 1TS

DUT: Sony Ericsson; Type: AAD-3880080-BV; Serial: BX9017228C

Communication System: PCS 1900 GPRS 1TS; Frequency: 1850.2 MHz; Duty Cycle: 1:8 Medium: M1900 Medium parameters used: f = 1850.2 MHz; σ = 1.53 mho/m; ϵ_r = 53.2; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 SN1558; ConvF(4.31, 4.31, 4.31); Calibrated: 2009-08-21
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn477; Calibrated: 2009-05-14
- Phantom: SAM 12; Type: SAM; Serial: 1043
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Rear position - Low/Area Scan (51x81x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.458 mW/g

Rear position - Low/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:

dx=5mm, dy=5mm, dz=5mm Reference Value = 17.8 V/m; Power Drift = 0.071 dB Peak SAR (extrapolated) = 0.603 W/kg SAR(1 g) = 0.411 mW/g; SAR(10 g) = 0.254 mW/g Maximum value of SAR (measured) = 0.446 mW/g



 $0 \, dB = 0.446 mW/g$

Additional information:



Annex B.5: Z-axis scan









SAR(x,y,z,f0) SAR; Z Scan:Value Along Z, X=0, Y=0 0,30 0,25 0,20 5 MAE 0,15 0,10 0,05 0,00 F.F IT + + 0,00 0,01 0,02 0,03 0,04 0,05 0,06 0,07 0,08 0,09 0,10 m 1900 body



Annex C: Photo documentation



Photo 1: Measurement System DASY 4

Photo 2: DUT - front view





Photo 3: DUT - front view (slide opened)



Photo 4: DUT - side view





Photo 5: DUT - rear view



Photo 6: DUT - rear view (open)







Photo 7: DUT - rear view (open) without battery

Photo 8: DUT - rear view (label)





Photo 9: Battery



Photo 10: Test position left hand touched





Photo 11: Test position left hand touched



Photo 12: Test position left hand touched







Photo 13: Test position left hand tilted 15°



Photo 14: Test position left hand tilted 15°







Photo 15: Test position left hand touched (slide open)

Photo 16: Test position left hand touched (slide open)







Photo 17: Test position left hand tilted 15° (slide open)









Photo 19: Test position right hand touched

Photo 20: Test position right hand touched







Photo 21: Test position right hand touched

Photo 22: Test position right hand tilted 15°





Photo 23: Test position right hand tilted 15°



Photo 24: Test position right hand touched (slide open)







Photo 25: Test position right hand touched (slide open)

Photo 26: Test position right hand tilted 15° (slide open)






Photo 27: Test position right hand tilted 15° (slide open)

Photo 28: Test position body worn front side (15 mm distance)







Photo 29: Test position body worn rear side (15 mm distance)



Annex C.6: Liquid depth



Photo 2: Liquid depth 850 MHz body simulating liquid







Photo 3: Liquid depth 1900MHz head simulating liquid

Photo 4: Liquid depth 1900 MHz body simulating liquid





Annex D: RF Technical Brief Cover Sheet acc. to RSS-102

- 1. COMPANY NUMBER: 4170B
- 2. MODEL NUMBER: A3880080
- 3. MANUFACTURER: Sony Ericsson Mobile Communications AB
- 4. TYPE OF EVALUATION:

(a) SAR Evaluation: Device used in the Vicinity of the Human Head

- Multiple transmitters: Yes \Box No \boxtimes
- Evaluated against exposure limits: General Public Use \square Controlled Use \square
- Duty cycle used in evaluation: 12.5 %
- Standard used for evaluation: RSS-102 Issue 2 (2005-11)
- SAR value: 0.924 W/kg. Measured ⊠ Computed □ Calculated □

(b) SAR Evaluation: Body-worn Device

- Multiple transmitters: Yes □ No ⊠
- Evaluated against exposure limits: General Public Use $oxed{e}$ Controlled Use $oxed{e}$
- Duty cycle used in evaluation: 25 %
- Standard used for evaluation: RSS-102 Issue 2 (2005-11)
- SAR value: 0.766 W/kg. Measured ⊠ Computed □ Calculated □

Annex D.7: Declaration of RF Exposure Compliance

ATTESTATION: I attest that the information provided in Annex D: is correct; that a Technical Brief was prepared and the information it contains is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed and that the device meets the SAR and/or RF exposure limits of RSS-102.

Signature:

homes log Da

Date: 2010-01-29

NAME : Thomas Vogler

TITLE : Dipl.-Ing. (FH)

COMPANY : CETECOM ICT Services GmbH



Annex E: Calibration parameters

Calibration parameters are described in the additional document :

Appendix to test report no. 1-1954-02-02/10 Calibration data, Phantom certificate and detail information of the DASY4 System

Annex F: Document History

Version	Applied Changes	Date of Release
	Initial Release	2010-01-29

Annex G: Further Information

Glossary

DUT	-	Device under Test
EUT	-	Equipment under Test
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	not applicable
SAR	-	Specific Absorption Rate
S/N	-	Serial Number
SW	-	Software









CETECOM ICT Services consulting - testing - certification >>>

TEST REPORT



Test Report No.: 1-1954-02-02/10

Testing Laboratory

CETECOM ICT Services GmbH Untertürkheimer Straße 6 – 10 66117 Saarbrücken/Germany Phone: + 49 681 5 98 - 0 Fax: + 49 681 5 98 - 9075 Internet: <u>http://www.cetecom-ict.de</u> e-mail: info@ict.cetecom.de

Accredited Test Laboratory:

The test laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025

DAR registration number: DAT-P-176/94-D1

Appendix with Calibration data, Phantom certificate and system validation information



1 Table of contents

1	Tabl	e of contents	2
2	Calil	bration report "Probe ET3DV6"	3
3	Calil	bration report "900 MHz System validation dipole"	12
4	Calil	bration report "1900 MHz System validation dipole"	21
5	Calil	bration certificate of Data Acquisition Unit (DAE)	31
6	Cert	ificate of "SAM Twin Phantom V4.0/V4.0C"	32
7	App	lication Note System Performance Check	33
	7.1	Purpose of system performance check	
	7.2	System Performance check procedure	
	7.3	Uncertainty Budget	34
	7.4	Power set-up for validation	
	7.5	Laboratory reflection	
	7.6	Additional system checks	
		-	



2 Calibration report "Probe ET3DV6"

eughausstrasse 43, 8004 Zurio	ch, Switzerland	HAC MIRA	S Schweizerischer Kalibrierdienst C Service sulsse d'étalonnage S Servizio svizzero di taratura S Swiss Calibration Service
accredited by the Swiss Accredit The Swiss Accreditation Servic fulfilateral Agreement for the r	ation Service (SAS) te is one of the signator recognition of calibratio	Accreditat les to the EA in certificates	ion No.: SCS 108
lient Cetecom		Certificate	No: ET3-1558_Aug09
CALIBRATION	CERTIFICAT	ſΕ	
Object	ET3DV6 - SN:1	558	
Calibration procedure(s)	QA CAL-01.v6, Calibration proc	QA CAL-23.v3 and QA CAL-25. edure for dosimetric E-field prob	v2 Jes
Celibration dete:	August 21, 200	9	
Condition of the calibrated item	In Tolerance		
Calibration Equipment used (M&	TE critical for calibration)		
Calibration Equipment used (M&	TE critical for calibration)	Cal Date (Certificate No.)	Scheduled Calibration
Calibration Equipment used (M& Primary Standards Power mater E4419B	TE critical for calibration)	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030)	Scheduled Calibration Apr-10
Calibration Equipment used (M& Primary Standards Power matar E4419B Power sensor E4412A	TE critical for calibration) ID # G341283874 MY41495277	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030)	Scheduled Celibration Apr-10 Apr-10
Calibration Equipment used (M& Primary Standards Power matar E4419B Power sensor E4412A Power sensor E4412A	TE critical for calibration) ID # GB41293874 MY41495277 MY41496087	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030)	Scheduled Celibration Apr-10 Apr-10 Apr-10
Calibration Equipment used (M& Primary Standards Power matar E4419B Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator	TE critical for calibration) ID # G541293874 MY41495277 MY41496057 SN: S5054 (3c)	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01028)	Scheduled Celibration Apr-10 Apr-10 Apr-10 Mar-10
Calibration Equipment used (M& Primary Standards Power sensor E4419B Power sensor E4412A Power sensor E4412A Reference 30 dB Attenuator Reference 20 dB Attenuator	TE critical for calibration) ID # G541293874 MY41495277 MY41496057 SN: S5054 (3c) SN: S5086 (205) CN: S5086 (205)	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01026) 31-Mar-09 (No. 217-01028) 24 More 09 (No. 217-01028)	Scheduled Calibration Apr-10 Apr-10 Apr-10 Mar-10 Mar-10
Calibration Equipment used (M& Primary Standards Power retar E4419B Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator Reference 30 dB Attenuator Reference 30 dB Attenuator Reference 30 dB Attenuator	TE critical for calibration) ID # GB41283874 MY41495277 MY41496087 SN: S5054 (3c) SN: S5056 (20c) SN: S5129 (30c) SN: S5129 (30c)	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 31-Mar-09 (No. 217-01027)	Scheduled Calibration Apr-10 Apr-10 Apr-10 Mar-10 Mar-10 Mar-10
Calibration Equipment used (M& Primary Standards Power mater E4419B Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2 DAE4	TE critical for calibration) ID # G341283874 MY41495277 MY41496087 SN: S5054 (3c) SN: S5054 (2c) SN: S5129 (30b) SN: 3013 SN: 660	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 2-Jan-09 (No. ES3-3013_Jan09) 9-Sep-08 (No. DAE4-680_Sep08)	Scheduled Calibration Apr-10 Apr-10 Mar-10 Mar-10 Mar-10 Jan-10 Jan-10 Sep-09
Calibration Equipment used (M& Primary Standards Power matar E4419B Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator Reference 30 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards	TE critical for calibration) ID # G341283874 MY41495277 MY41496087 SN: S5054 (3c) SN: S5056 (20b) SN: S5129 (30b) SN: 3013 SN: 660 ID #	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 2-Jan-09 (No. 233-013_Jan09) 9-Sep-08 (No. DAE4-660_Sep08) Check Date (in house)	Scheduled Calibration Apr-10 Apr-10 Mar-10 Mar-13 Mar-10 Jan-10 Sep-09 Scheduled Check
Calibration Equipment used (M& Primary Standards Power matar E4419B Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator Reference 30 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2 DAE4 Recondary Standards RE generator HP 8648C	TE critical for calibration) ID # G341283874 MY41495277 MY41496037 SN: S5054 (3c) SN: S5056 (20c) SN: S5129 (30c) SN: S5129 (30c) SN: S603 ID # US3642U01700	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01026) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 2-Jan-09 (No. 23-3013_Jan09) 9-Sep-08 (No. DAE4-660_Sep08) Check Date (in house) 4-Aug-99 (in house check Oct-07)	Scheduled Calibration Apr-10 Apr-10 Mar-10 Mar-10 Jan-10 Jan-10 Sep-09 Scheduled Check In house check Oct-09
Calibration Equipment used (M& Primary Standards Power sensor E4419B Power sensor E4412A Power sensor E4412A Reference 30 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator Reference 90 dB Attenuator Reference Probe ES3DV2 DAE4 Recordary Standards RF generator HP 8648C setwork Analyzer HP 8753E	ID # GB41283874 MY41495277 MY41496097 SN: S5054 (30) SN: S5056 (200) SN: S5129 (30b) SN: 3013 SN: 660 ID # US3642U01700 US37390565	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01030) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 2-Jan-09 (No. ES3-3013_Jan09) 9-Sep-08 (No. DAE4-680_Sep08) Check Date (in house) 4-Aug-99 (in house check Oct-07) 18-Oct-01 (in house check Oct-08)	Scheduled Calibration Apr-10 Apr-10 Mar-10 Mar-10 Jan-10 Jan-10 Sep-09 Scheduled Check In house check: Oct-09 In house check: Oct-09
Calibration Equipment used (M& Primary Standards Power mater E44195 Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator Reference 9 robe ES3DV2 DAE4 Secondary Standards RF generator HP 8649C Network Analyzer HP 8753E	TE critical for calibration) ID # G341283874 MY41495277 MY41496087 SN: S5054 (3c) SN: S5056 (205) SN: S5129 (30b) SN: S5129 (30b) SN: 3013 SN: 660 ID # US3642U01700 US37390585 Name	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01026) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. ES3-3013_Jan09) 9-Sep-08 (No. DAE4-660_Sep08) Check Date (in house) 4-Aug-09 (in house check Oct-07) 18-Oct-01 (in house check Oct-08) Function	Scheduled Calibration Apr-10 Apr-10 Mar-10 Mar-10 Jan-10 Jan-10 Sep-09 Scheduled Check In house check: Oct-09 In house check: Oct-09 Signature
Calibration Equipment used (M& Primary Standards Power rentar E4419B Power sensor E4412A Power sensor E4412A Reference 30 dB Attenuator Reference 20 dB Attenuator Reference 30 dB Attenuator Reference Probe ES3DV2 DAE4 Secondary Standards Reference HP 8649C Network Analyzer HP 8753E Calibrated by:	ID # GB41283874 MY41495277 MY41495277 MY41495277 MY41496087 SN: S5054 (3c) SN: S5086 (20o) SN: S5129 (30b) SN: 3013 SN: 663 ID # US3042U01700 US37390585 Name Katja Pokovic	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 2-Jan-09 (No. 217-01027) 2-Jan-09 (No. 217-01027) 2-Jan-09 (No. 217-01027) 2-Jan-09 (No. 217-01027) 2-Jan-09 (No. 217-01027) 2-Jan-09 (No. 217-01028) 31-Mar-09 (No. 217-01027) 2-Jan-09 (No. 217-01027) 2-Jan-09 (No. 217-01028) 31-Mar-09 (No. 217-01028) 31-M	Scheduled Calibration Apr-10 Apr-10 Apr-10 Mar-13 Mar-13 Mar-10 Jan-10 Sep-09 Scheduled Check In house check: Oct-09 In house check: Oct-09 Signature
Calibration Equipment used (M& Primary Standards Power matar E4419B Power sensor E4412A Power sensor E4412A Reference 3 dB Attenuator Reference 30 dB Attenuator Reference 30 dB Attenuator Reference 30 dB Attenuator Reference 90 dB Attenuator Reference 90 dB Attenuator Reference 91 dB Attenu	ID # G341283874 MY41495277 MY41496087 SN: S5054 (3c) SN: S5056 (2c) SN: S5086 (2c) SN: S5129 (30b) SN: 3013 SN: 660 ID # US3042U01700 US37390585 Name Katja Pokovic Niels Kuster	Cal Date (Certificate No.) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 1-Apr-09 (No. 217-01030) 31-Mar-09 (No. 217-01026) 31-Mar-09 (No. 217-01028) 31-Mar-09 (No. ES3-3013_Jan09) 9-Sep-08 (No. DAE4-660_Sep08) Check Date (in house) 4-Aug-09 (in house check Oct-07) 18-Oct-01 (in house check Oct-08) Function Technical Manager	Scheduled Calibration Apr-10 Apr-10 Mar-10 Mar-13 Mar-10 Jan-10 Sep-09 Scheduled Check In house check: Oct-09 In house check: Oct-09 Signature

Certificate No: ET3-1558_Aug09

Page 1 of 9



Calibration Laboratory of Schmid & Partner Engineering AG Zeughsuestrasse 43, 8004 Zurich, Switzerland



S

C

s

Schweizerischer Kalibrierdianst

Service suisse d'étalonnage

Servizio svizzero di taratura

Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary: TSL

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
Polarization ϕ	φ rotation around probe axis
Polarization 9	9 rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $9 = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORMx,y,z: Assessed for E-field polarization 9 = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not effect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)x,y,z = NORMx,y,z * frequency_response (see Frequency Response Chart). This
 linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of
 the frequency response is included in the stated uncertainty of ConvF.
- DCPx, y, z: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Certificate No: ET3-1558_Aug09



ET3DV6 SN:1558

August 21, 2009

Probe ET3DV6

SN:1558

Manufactured: Last calibrated: Recalibrated:

September 16, 2003 August 15, 2008 August 21, 2009

Calibrated for DASY Systems (Note: non-compatible with DASY2 system!)

Certificate No: ET3-1558_Aug09

Page 3 of 9



ET3DV6 SN:1558

August 21, 2009

DASY - Parameters of Probe: ET3DV6 SN:1558

Sensitivity in Free Space^A

Diode Compression^B

NormX	1.97 ± 10.1%	$\mu V/(V/m)^2$	DCP X	93 mV
NormY	1.94 ± 10.1%	μV/(V/m) ²	DCP Y	94 mV
NormZ	1.73 ± 10.1%	$\mu V/(V/m)^2$	DCP Z	95 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL

900 MHz Typical SAR gradient: 5 % per mm

Sensor Cente	r to Phantom Surface Distance	3.7 mm	4.7 mm
SAR _{be} [%]	Without Correction Algorithm	10.1	5.8
SAR _{be} [%]	With Correction Algorithm	0.9	0.7

TSL

1750 MHz Typical SAR gradient: 10 % per mm

Sensor Cente	er to Phantom Surface Distance	3.7 mm	4.7 mm
SAR _{be} [%]	Without Correction Algorithm	9.7	5.8
SAR _{be} [%]	With Correction Algorithm	0.8	0.6

Sensor Offset

Probe Tip to Sensor Center

2.7 mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y.Z do not affect the E²-field uncertainty inside TSL (see Page 8).

⁶ Numerical inearization parameter: uncertainty not required.

Certificate No: ET3-1558_Aug09

Page 4 of 9



ET3DV6 SN:1558

August 21, 2009

Frequency Response of E-Field





25

Certificate No: ET3-1558_Aug09

Page 5 of 9



ET3DV6 SN:1558

August 21, 2009



Receiving Pattern (ϕ), $\vartheta = 0^{\circ}$



Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Certificate No: ET3-1558_Aug09

Page 6 of 9

Dynamic Range f(SAR_{head})



ET3DV6 SN:1558

August 21, 2009



Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: ET3-1558_Aug09

Page 7 of 9



ET3DV6 SN:1558

August 21, 2009



Conversion Factor Assessment

f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
835	±50/±100	Head	41.5 ± 5%	0.90 ± 5%	0.59	1.94	6.02 ± 11.0% (k=2)
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.55	1.96	5.84 ± 11.0% (k=2)
1750	± 50 / ± 100	Head	40.1 ± 5%	1.37 ± 5%	0.52	2.56	5.00 ± 11.0% (k=2)
1900	\pm 50 / \pm 100	Head	40.0 ± 5%	$1.40 \pm 5\%$	0.70	2.12	4.75 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.99	1.64	4.16 ± 11.0% (k=2)
835	± 50 / ± 100	Body	55.2 ± 5%	0.97 ± 5%	0.38	2.51	5.78 ± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.33	2.80	5.63 ± 11.0% (k=2)
1750	± 50 / ± 100	Body	53.4 ± 5%	1.49 ± 5%	0.62	3.28	4.53 ± 11.0% (k=2)
1900	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.84	2.63	4.31 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.99	1.80	3.96 ± 11.0% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Certificate No: ET3-1558_Aug09

Page 8 of 9



ET3DV6 SN:1558

August 21, 2009

Deviation from Isotropy in HSL

Error (¢, ୬), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

Certificate No: ET3-1558_Aug09

Page 9 of 9



3 Calibration report "900 MHz System validation dipole"

Calibration Laboratory of	
Schmid & Partner	
Engineering AG	
Zeughausstrasse 43, 8004 Zurich, Switzerland	1



S Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service Is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates Accreditation No.: SCS 108

Object	D900V2 - SN: 10)2	
Calibration procedure(s)	QA CAL-05.v7		
	Calibration proce	dure for dipole validation kits	
Calibration date:	August 17, 2009		
Condition of the calibrated item	In Tolerance		
This calibration certificate docum	ents the traceability to nat	ional standards, which realize the physical ur	its of measurements (SI)
he measurements and the unce	stainties with confidence p	robability are given on the following pages ar	nd are part of the certificate.
Al cal brations have been conducted	ted in the closed laborato	ry facility: environment temperature (22 \pm 3)°	C and humidity < 70%.
Calibration Equipment used (M&	FE critical for calibration)		
Calibration Equipment used (M&)	FE critical for calibration)	Cal Date (Certificate No.)	Scheduled Calibration
Selibration Equipment used (M& <u>'rimary Standards</u> 'ower meter EPM-442A	FE critical for calibration)	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898)	Scheduled Calibration
alibration Equipment used (M& rimary Standards ower meter EPM-442A ower sensor HP 8481A	FE critical for calibration) ID # GB37450704 US37292783	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898)	Scheduled Calibration Oct-09 Oct-09
Collibration Equipment used (M& rimary Standards rower meter EPM-442A ower sarsor HP 8481A eference 20 cB Attenuator	FE critical for calibration) ID # GB37460704 US37292793 SN: 5036 (20g)	Cal Data (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025)	Scheduled Calibration Oct-09 Mar-10
alibration Equipment used (M& <u>rimary Standards</u> ower meter EPM-442A ower sensor HP 8461A eference 20 cB Attenuator ype-N mismatch combination	FE critical for calibration) ID # GB37450704 US37292783 SN: 5036 (20g) SN: 5047.2 / 06327	Cal Data (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217 01029)	Scheduled Calibration Oct-09 Mar-10 Mar-10
alibration Equipment used (M& rimary Standards ower meter EPM-442A ower sensor HP 8481A eference 20 cB Attonuator ype-N mismatch combination eterence Probe ES3DV3	E critical for calibration) ID # GB37480704 US37292783 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3205	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. E33-3205, Jun09)	Scheduled Calibration Oct-08 Oct-09 Mar-10 Mar-10 Jun-10
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sansor HP 8481A Reference 20 dB Attonuator Pype-N mismatch combination Reference Probe ES3DV3 PAE4	FE critical for calibration) ID # GB37460704 US37292783 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601	Cal Data (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. ES3-3205_Jun09) 07-Mar-09 (No. D/\E4-601_Mar09)	Scheduled Calibration Oct-09 Mar-10 Mar-10 Jun-10 Mar-10
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Spo-N mismatch combination Reference Probe ES3DV3 DAE4 Secondary Stancards	FE critical for calibration) ID # GB37460704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601 ID #	Cal Data (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. ES3-3205_Jun-09) 07-Mar-09 (No. D/\E4-601_Mar08) Check Date (in house)	Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Jun-10 Mar-10 Scheduled Check
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attonuator Spo-N mismatch combination Reference Probe ES3DV3 AAE4 Pecondary Stancards Power sensor HP 8481A	FE critical for calibration) ID # GB37460704 US37292793 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601 ID # M ⁴ 41092317	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. E33-3205_Jun-09) 07-Mar-09 (No. DAE4-601_Mar09) Check Date (in house) 18-Oct-02 (in house check Oct-07)	Scheduled Calibration Oct-09 Oct-09 Mar-10 Jun-10 Jun-10 Mar-10 Scheduled Check In house check: Oct-09
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 cB Attenuator Pype-N mismatch combination Reference Probe ES3DV3 PAE4 Recondary Stancards Power sensor HP 8481A RF generator R&S SVIT-06	FE critical for calibration) ID # GB37460704 US37292793 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3206 SN: 601 ID # M ⁴ 41092317 100005	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 26-Jun-09 (No. DAE4-601_Mar09) O7-Mar-09 (No. DAE4-601_Mar09) Check Date (in house) 18-Oct-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07)	Scheduled Calibration Oct-09 Mar-10 Mar-10 Jun-10 Jun-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 cB Attonuator Type-N mismatch combination Reference Probe ES3DV3 DAE4 Secondary Stancards Power sensor HP 8481A RE generator R&S SMT-06 Network Analyzer HP 8753E	FE critical for calibration) ID # GB37460704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601 ID # MM41092317 100005 US3/390585 S4206	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. DAE4-601_Mar02) O7-Mar-09 (No. DAE4-601_Mar02) Check Date (in house) 18-Oct-02 (in house check Oct-07) 4-Aug-93 (in house check Oct-07) 18-Oct-01 (in house check Oct-08)	Scheduled Calibration Oct-08 Oct-09 Mar-10 Mar-10 Jun-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 In house check: Oct-09
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 cB Attenuator Type-N mismatch combination Reference Probe ES3DV3 DAE4 Secondary Stancards Power sensor HP 8481A RF generator R&S SVIT-C6 Network Analyzer HP 8753E	FE critical for calibration) ID # GB37460704 US37292783 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601 ID # MM41092317 100005 US3/390585 S4206 Name	Cal Data (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 07-Mar-09 (No. 217-0	Scheduled Calibration Oct-09 Mar-10 Mar-10 Jun-10 Mar-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 Signature
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Nower sensor HP 8481A Reference 20 cB Attenuator Type-N mismatch combination Reference Probe ES3DV3 NE4 Secondary Stancards Nover sensor HP 8481A Regenerator R&S SVIT-06 Retwork Analyzer HP 8753E Salibrated by:	FE critical for calibration) ID # GB37460704 US37292793 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3206 SN: 601 ID # M*41092317 100005 US3/390585 S4206 Name Jeton Kastrafi	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 07-Mar-09 (No. 217-0	Scheduled Calibration Oct-09 Mar-10 Mar-10 Jun-10 Jun-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 Signature
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 cB Attonuator Type-N mismatch combination Reference Probe ES3DV3 DAE4 Secondary Stancards Power sensor HP 8481A RF generator R&S SMT-06 Network Analyzer HP 8753E Calibrated by:	FE critical for calibration) ID # GB37460704 US37292793 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601 ID # MM41092317 100005 US3/390585 S4206 Name Joton Kastrati	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. E33-3205_Jun09) 07-Mar-09 (No. DAE4-601_Mar09) Check Date (in house) 18-Oct-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07) 18-Oct-01 (in house check Oct-08) Function Laboratory Technician	Scheduled Calibration Oct-08 Oct-09 Mar-10 Jun-10 Jun-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 Signature
Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 cB Attenuator Rype-N mismatch combination Reference Probe ES3DV3 DAE4 Secondary Stancards Power sensor HP 8481A RF generator R&S SVIT-06 Vetwork Analyzer HP 8753E Calibrated by:	FE critical for calibration) ID # GB37460704 US37292783 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3205 SN: 601 ID # MM41092317 100005 US37390585 S4206 Name Joton Kastrati Katja Pokovic	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. 217 01029) 26-Jun-09 (No. ES3-3205_Jun09) 07-Mar-09 (No. DAE4-601_Mar09) Check Date (in house) 18-Oot-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07) 18-Oot-01 (in house check Oct-08) Function Laboratory Technician Technica: Manager	Scheduled Calibration Oct-09 Mar-10 Mar-10 Jun-10 Mar-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 Signature
Calibration Equipment used (M& 2nimary Standards 2nover meter EPM-442A 2nover sensor HP 8481A Reference 20 dB Attonuator Sype-N mismatch combination Reterence Probe ES3DV3 20Xe1 Secondary Stancards 2nover sensor HP 8481A Regenerator R&S SVIT-06 Retwork Analyzer HP 8753E Calibrated by: approved by:	FE critical for calibration) ID # GB37460704 US37292793 SN: 5036 (20g) SN: 5047.2 / 06327 SN: 3206 SN: 601 ID # M*41092317 100005 US3/390585 S4206 Name Jeton Kastrafi Katja Pokovic	Cal Date (Certificate No.) 08 Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 26-Jun-09 (No. 217-01029) 07-Mar-09 (No. 217-01029) 18-Oct-01 (In house check Oct-07) 4-Aug-99 (In house check Oct-07) 18-Oct-01 (In house check Oct-07) 18-Oct-01 (In house check Oct-08) Function Laboratory Technician Technica: Manager	Scheduled Calibration Oct-09 Mar-10 Mar-10 Jun-10 Jun-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 Signature

Certificate No: D900V2-102_Aug09

Page 1 of 9



Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland



SWISC

BOI

S

C

s

Schweizerischer Kalibrierdienst Service sulsse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole
 positioned under the liquid filled phantom. The impedance stated is transformed from the
 measurement at the SMA connector to the feed point. The Return Loss ensures low
 reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

Certificate No: D900V2-102_Aug09

Page 2 of 9



Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V5.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V4.9	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	900 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.97 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.4 ± 6 %	0.96 mho/m ± 6 %
Head TSL temperature during test	(22.0 ± 0.2) °C		

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.81 mW / g
SAR normalized	normalized to 1W	11.2 mW / g
SAR for nominal Head TSL parameters 1	normalized to 1W	11.3 mW /g ± 17.0 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.80 mW / g
SAD pormelized		
SAR normalized	normalized to 1W	7.20 mW / g

¹ Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Certificate No: D900V2-102_Aug09

Page 3 of 9



Body TSL parameters The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.0	1.05 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.7 ± 6 %	1.06 mho/m ± 6 %
Body TSL temperature during test	(22.0 ± 0.2) °C		

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.88 mW / g
SAR normalized	normalized to 1W	11.5 mW / g
SAR for nominal Body TSL parameters 2	normalized to 1W	11.3 mW / g ± 17.0 % (k=2)

SAN averaged over to chi (to g) of Body tal	contaition		
SAR measured	250 mW input power	1.85 mW / g	1
SAR normalized	normalized to 1W	7.40 mW / g	
SAR for nominal Body TSL parameters ²	normalized to 1W	7.32 mW / g ± 16.5 % (k=2)	

² Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Certificate No: D900V2-102_Aug09

Page 4 of 9



Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.8 Ω - 4.2 jΩ	
Return Loss	- 27.5 dB	

Antenna Parameters with Body TSL

Impedance, transformed to feed point	45.9 Ω - 5.6 jΩ	
Return Loss	- 22.8 dB	

General Antenna Parameters and Design

Electrical Delay (one direction)	1.408 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cablo. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	January 24, 2001

Certificate No: D900V2-102_Aug09

Page 5 of 9



DASY5 Validation Report for Head TSL

Date/Time: 10.08.2009 12:21:29

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 900 MHz; Type: D900V2; Serial: D900V2 - SN:102

Communication System: CW-900; Frequency: 900 MHz; Duty Cycle: 1:1 Medium: 11SL 900 MHz Medium parameters used: f - 900 MHz; $\sigma = 0.96$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV3 SN3205; ConvF(5.88, 5.88, 5.88); Calibrated: 26.06.2009
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.03.2009
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA: Serial: 1001
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45

Pin=250mW; dip=15mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz-5mm

Reference Value = 59.9 V/m; Power Drift = 0.038 dB Peak SAR (extrapolated) = 4.28 W/kg SAR(1 g) = 2.81 mW/g; SAR(10 g) = 1.8 mW/g Maximum value of SAR (measured) = 3.27 mW/g



Certificate No: D900V2-102_Aug09

Page 6 of 9





Impedance Measurement Plot for Head TSL

Certificate No: D900V2-102_Aug09

Page 7 of 9



DASY5 Validation Report for Body

Date/Time: 17.08.2009 10:47:05

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 900 MHz; Type: D900V2; Serial: D900V2 - SN:102

Communication System: CW-900; Frequency: 900 MHz; Duty Cycle: 1:1 Medium: MSL900 Medium parameters used: f = 900 MHz; σ = 1.06 mho/m; ϵ_r = 52.7; ρ = 1000 kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV3 SN3205; ConvF(5.81, 5.81, 5.81); Calibrated: 26.06.2009
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.03.2009
- Phantom: Flat Phantom 4.9L: Type: QD000P49AA; Serial: 1001
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45

Pin=250mW; dip=15mm; dist=3.0mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mmReference Value = 58.3 V/m; Power Drift = 0.00443 dB Peak SAR (extrapolated) = 4.3 W/kg SAR(1 g) = 2.88 mW/g; SAR(10 g) = 1.85 mW/g

SAR(1 g) = 2.38 mw/g; SAR(10 g) = 1.85 mw/g Maximum value of SAR (measured) = 3.37 mW/g



Certificate No: D900V2-102_Aug09

Page 8 of 9



Impedance Measurement Plot for Body TSL



Certificate No: D900V2-102_Aug09

Page 9 of 9



4 Calibration report "1900 MHz System validation dipole"

	ch, Switzerland	RUNCH S	Servizio svizzero di taratura Swiss Calibration Service
Accredited by the Swiss Accre The Swiss Accreditation Servic Nultilateral Agreement for the r	ditation Service (SAS) to is one of the signatorie recognition of calibration	Accreditation f es to the EA I certificates	No.: SCS 10B
Client Cetecom		Certificate No:	D1900V2-531-May09
CALIBRATION	CERTIFICATI		
Object	D1900V2 - SN: 5	531	
Calibration procedure(s)	QA CAL-05.v7 Calibration proce	edure for dipole validation kits	
Calibration date:	May 20, 2009		
Condition of the calibrated item	In Tolerance		
This calibration certificate docum The measurements and the unce All calibrations have been conduc	ents the traceability to nati stainties with confidence p cted in the closed laborator	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3) °C a	of measurements (SI). are part of the certificate. and humidity < 70%.
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M&	ents the traceability to nati reainties with confidence p cted in the closed laborato TE critical for calibration)	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature $(22 \pm 3)^{\circ}$ C a	of measurements (SI). are part of the certificate. and humidity < 70%.
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards	ents the traceability to nati enteinties with confidence p cted in the closed laborato TE critical for calibration) ID #	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a Cal Date (Calibrated by, Certificate No.)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A	ents the traceability to nati enteinties with confidence p cted in the closed laborato TE critical for calibration) ID # GB37480704	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A	ents the traceability to nati entainties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator	ents the traceability to nati entainties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g)	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination	ents the traceability to nati enternties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAEA	ents the traceability to nati enternties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. ES3-3025_Apr09)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheculed Calibration Oct-09 Oct-09 Mar-10 Mar-10 Apr-10 Mar-10
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4	ents the traceability to nati entainties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025 SN: 601	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Mar-10 Mar-10
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards	ents the traceability to nati exteinties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025 SN: 601 ID #	ional standards, which realize the physical units robability are given on the following pages and a ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 03-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) Check Date (in house)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Mar-10 Mar-10 Scheduled Check
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor HP 8481A	ents the traceability to nati exteinties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 5047.2 / 06327 SN: 3025 SN: 601 ID # MY41092317	ional standards, which realize the physical units robability are given on the following pages and a ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 03-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) <u>Check Date (in house)</u> 18-Oct-02 (in house check Oct-07)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Mar-10 Mar-10 Scheduled Check In house check: Oct-09
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor HP 8481A RF generator R&S SMT-06	ents the traceability to nati exteinties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 5025 SN: 601 ID # MY41092317 100005	ional standards, which realize the physical units robability are given on the following pages and a ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 03-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) <u>Check Date (in house)</u> 18-Oct-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Mar-10 Mar-10 Scheduled Check In house check: Oct-09 In house check: Oct-09
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor HP 8481A RF generator R&S SMT-06 Network Analyzer HP 8753E	ents the traceability to nati enternities with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025 SN: 601 ID # MY41092317 100005 US37390585 S4206	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 03-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 30-Apr-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) <u>Check Date (in house)</u> 18-Oct-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07) 18-Oct-01 (in house check Oct-08)	of measurements (SI). are part of the certificate. and humidity < 70%. Scheculed Calibration Oct-09 Oct-09 Mar-10 Mar-10 Apr-10 Mar-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor HP 8481A RF generator R&S SMT-06 Network Analyzer HP 8753E	ents the traceability to nati entainties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025 SN: 601 ID # MY41092317 100005 US37390585 S4206 Name	ional standards, which realize the physical units robability are given on the following pages and a ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 30-Apr-09 (No. 217-01029) 30-Apr-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) <u>Check Date (in house)</u> 18-Oct-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07) 18-Oct-01 (in house check Oct-08) Function	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Apr-10 Mar-10 Scheduled Cheox In house check: Oct-09 In house check: Oct-09 In house check: Oct-09 Signature 1
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor HP 8481A RF generator R&S SMT-06 Network Analyzer HP 8753E	ents the traceability to nati entrainties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025 SN: 601 ID # MY41092317 100005 US37390585 S4206 Name Claudio Leubler	ional standards, which realize the physical units robability are given on the following pages and ry facility: environment temperature (22 ± 3)°C a <u>Cal Date (Calibrated by, Certificate No.)</u> 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-00898) 08-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 30-Apr-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) <u>Check Date (in house check Oct-07)</u> 4-Aug-99 (in house check Oct-07) 18-Oct-01 (in house check Oct-07) 18-Oct-01 (in house check Oct-08) <u>Function</u> Laboratory Technician	of measurements (SI). are part of the certificate. and humidity < 70%. Scheduled Calibration Oct-09 Oct-09 Mar-10 Mar-10 Apr-10 Mar-10 Scheduled Check In house check: Oct-09 In house check: Oct-09 In house check: Oct-09
This calibration certificate docum The measurements and the unce All calibrations have been conduc Calibration Equipment used (M& Primary Standards Power meter EPM-442A Power sensor HP 8481A Reference 20 dB Attenuator Type-N mismatch combination Reference Probe ES3DV2 DAE4 Secondary Standards Power sensor HP 8481A RF generator R&S SMT-06 Network Analyzer HP 8753E Calibrated by:	ents the traceability to nati exteinties with confidence p cted in the closed laborator TE critical for calibration) ID # GB37480704 US37292783 SN: 5086 (20g) SN: 5047.2 / 06327 SN: 3025 SN: 601 ID # MY41092317 100005 US37390585 S4206 Name Claudio Leubler Katja Pokovic	Cal Date (Calibrated by, Certificate No.) Cal Date (Calibrated by, Certificate No.) 08-Oct-08 (No. 217-00898) 03-Oct-08 (No. 217-00898) 03-Oct-08 (No. 217-01025) 31-Mar-09 (No. 217-01025) 31-Mar-09 (No. 217-01029) 30-Apr-09 (No. ES3-3025_Apr09) 07-Mar-09 (No. DAE4-601_Mar09) Check Date (in house) 18-Oct-02 (in house check Oct-07) 4-Aug-99 (in house check Oct-07) 18-Oct-01 (in house check Oct-07) 18-Oct-01 (in house check Oct-08) Function Laboratory Technician	of measurements (SI). are part of the certificate. and humidity < 70%. Scheculed Calibration Oct-09 Oct-09 Mar-10 Mar-10 Mar-10 Scheduled Cheox In house check: Oct-09 In house check: Oct-09 In house check: Oct-09

Certificate No: D1900V2-531_May09

Page 1 of 9



Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland



NIS

Schweizerischer Kalibrierdienst S Service suisse d'étalonnage C Servizio svizzero di taratura s

Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

d) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

Certificate No: D1900V2-531_May09

Page 2 of 9



Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V5.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

Head TSL parameters The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	41.3 ± 6 %	1.43 mho/m ± 6 %
Head TSL temperature during test	(21.6 ± 0.2) °C		

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	condition	
SAR measured	250 mW input power	10.3 mW/g
SAR normalized	normalized to 1W	41.2 mW/g
SAR for nominal Head TSL parameters ¹	normalized to 1W	41.0 mW / g ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	5.38 mW / g
SAR normalized	normalized to 1W	21.5 mW / g
SAR for nominal Head TSL parameters 1	normalized to 1W	21.5 mW / g ± 16.5 % (k=2)

1 Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Certificate No: D1900V2-531_May09

Page 3 of 9



Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V5.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

Head TSL parameters The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	41.3 ± 6 %	1.43 mho/m ± 6 %
Head TSL temperature during test	(21.6 ± 0.2) °C		

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	condition	
SAR measured	250 mW input power	10.3 mW/g
SAR normalized	normalized to 1W	41.2 mW / g
SAR for nominal Head TSL parameters ¹	normalized to 1W	41.0 mW / g ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	5.38 mW / g
SAR normalized	normalized to 1W	21.5 mW / g
SAR for nominal Head TSL parameters 1	normalized to 1W	21.5 mW / g ± 16.5 % (k=2)

1 Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Certificate No: D1900V2-531_May09

Page 3 of 9



Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	53.7 ± 6 %	1.56 mha/m ± 6 %
Body TSL temperature during test	(22.0 ± 0.2) °C		

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.6 mW / g
SAR normalized	normalized to 1W	42.4 mW / g
SAR for nominal Body TSL parameters 2	normalized to 1W	41.8 mW / g ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.60 mW / g
SAR normalized	normalized to 1W	22.4 mW / g
SAR for nominal Body TSL parameters ²	normalized to 1W	22.3 mW / g ± 16.5 % (k=2)

² Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

Certificate No: D1900V2-531_May09

Page 4 of 9



Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.4 Ω + 6.4 jΩ	
Return Loss	- 23.5 dB	

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.1 <u>\$2</u> + 6.9 j <u>\$2</u>
Return Loss	- 22.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.200 ns

After long torm use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG	
Manufactured on	January 24, 2001	

Certificate No: D1900V2-531_May09

Page 5 of 9



DASY5 Validation Report for Head TSL

Date/Time: 13.05.2009 13:01:14

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:531

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1 Medium: HSL U11 BB Medium parameters used: f = 1900 MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV2 SN3025; ConvF(4.88, 4.88, 4.88); Calibrated: 30.04.2009
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.03.2009
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45

Pin = 250 mW; dip = 10 mm, scan at 3.0 mm/Zoom Scan (dist=3.0 mm, probe 0deg) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 96.5 V/m; Power Drift = 0.049 dB Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 10.3 mW/g; SAR(10 g) = 5.38 mW/g Maximum value of SAR (measured) = 12.5 mW/g



0 dB = 12.5 mW/g

Certificate No: D1900V2-531_May09

Page 6 of 9



Impedance Measurement Plot for Head TSL



Certificate No: D1900V2-531_May09

Page 7 of 9



DASY5 Validation Report for Body TSL

Date/Time: 20.05.2009 12:38:49

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:531

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1 Medium: MSL U10 BB Medium parameters used: f = 1900 MHz; $\sigma = 1.56$ mho/m; $\varepsilon_r = 53.7$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV2 SN3025; ConvF(4.46, 4.46, 4.46); Calibrated: 30.04.2009
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.03.2009
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45

Pin = 250 mW; dip = 10 mm, scan at 3.0mm/Zoom Scan (dist=3.0mm, probe 0deg) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 96.3 V/m; Power Drift = 0.00816 dB Peak SAR (extrapolated) = 18.6 W/kg SAR(1 g) = 10.6 mW/g; SAR(10 g) = 5.6 mW/g Maximum value of SAR (measured) = 13.4 mW/g



0 dB = 13.4 mW/g

Certificate No: D1900V2-531_May09

Page 8 of 9



Impedance Measurement Plot for Body TSL



Certificate No: D1900V2-531_May09

Page 9 of 9


5 Calibration certificate of Data Acquisition Unit (DAE)

eughausstrasse 43, 8004 Zurich,	, Switzerland	RIGRATO	Servizio svizzero di taratura S Swiss Calibration Service
Accredited by the Swiss Accreditation The Swiss Accreditation Service Multilateral Agreement for the rec	on Service (SAS) is one of the signatories cognition of calibration of	Accredite to the EA sertificates	tation No.: SCS 108
Client Cetecom		Certifica	ate No: DAE3-477_May09
CALIBRATION C	ERTIFICATE		
Object	DAE3 - SD 000 D	03 AA - SN: 477	
Calibration procedura(s)	QA CAL-06.v12 Calibration proceed	lure for the data acquisition	electronics (DAE)
Calibration date:	May 14, 2009		
Condition of the calibrated item	In Tolerance		
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducte	nts the traceability to natio sinties with confidence pro ed in the closed laboratory	nal standards, which realize the physio obability are given on the following pag r facility: environment temperature (22	cal units of measurements (SI). ges and are part of the certificate. ± 3)°C and humidity < 70%.
This calibration certificate occumer The measurements and the uncert All calibrations have been conducto Calibration Equipment used (M&TE Primary Standards	nts lhe traceability to natio sinties with confidence pro ed in the closed laboratory contical for calibration)	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 Cal Data (Certificate No.)	cal units of measurements (SI). ges and are part of the certificate. ± 3)°C and humidity < 70%. Scheduled Calibration
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducto Calibration Equipment used (M&TE Primary Standards Fluke Process Calibrator Type 702 Keithley Multimeter Type 2001	hts The traceability to natio sinties with confidence pro- ed in the closed faboratory contical for calibration) ID # SN: 6295803 SN: 0810278	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 <u>Cal Date (Certificate No.)</u> 30-Sep-08 (No: 7673) 30-Sep-08 (No: 7670)	cal units of measurements (SI). ges and are part of the certificate. ± 3)°C and humidity < 70%. <u>Scheduled Calibration</u> Sep-09 Sep-09
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducte Calibration Equipment used (M&TE Primary Standards Fluke Process Calibrator Type 702 Keithley Multimeter Type 2001 Secondary Standards	nts line traceability to natio sinties with confidence pro- ed in the closed laboratory E critical for calibration) ID # SN: 6295803 SN: 0810278	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 <u>Cal Data (Certificata No.)</u> 30-Sep-08 (No: 7673) 30-Sep-08 (No: 7670) Check Date (in house)	cal units of measurements (SI), ges and are part of the certificate. (± ± 3)°C and humidity < 70%. Scheduled Calibration Sep-09 Sep-09 Scheduled Check
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducte Calibration Equipment used (M&TE Primary Standards Fluke Process Calibrator Type 702 Keithley Multimeter Type 2001 Secondary Standards Calibrator Box V1.1	hts life traceability to natio sinties with confidence pro- ed in the closed laboratory E critical for calibration) ID # SN: 6295803 SN: 0810278 ID # SE UMS 006 AB 1004	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 <u>Cal Date (Certificate No.)</u> 30-Sep-08 (No: 7673) 30-Sep-08 (No: 7670) <u>Check Date (in house)</u> 06-Jun-08 (in house check)	cal units of measurements (SI), ges and are part of the certificate. (± ± 3)*C and humidity < 70%. Scheduled Calibration Sep-09 Sep-09 Sep-09 Scheduled Check In house check: Jun-09
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducte Calibration Equipment used (M&TE Primary Standards Fluke Process Calibrator Type 702 Keithley Multimeter Type 2001 Secondary Standards Calibrator Box V1.1	hts line traceability to natio ainties with confidence pro- ed in the closed laboratory E critical for calibration) ID # SN: 6295803 SN: 0810278 ID # SE UMS 006 AB 1004	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 <u>Cal Date (Certificate No.)</u> 30-Sep-08 (No: 7673) 30-Sep-08 (No: 7670) <u>Check Date (in house)</u> 06-Jun-08 (in house check)	cal units of measurements (SI), ges and are part of the certificate. et ± 3)°C and humidity < 70%. <u>Scheduled Calibration</u> Sep-09 Sep-09 <u>Scheduled Check</u> In house check: Jun-09 Signature
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducte Calibration Equipment used (M&TE <u>Primary Standards</u> Fluke Process Calibrator Type 702 Keithley Multimeter Type 2001 <u>Secondary Standards</u> Calibrator Box V1.1	hts lhe traceability to natio sinties with confidence pro- ed in the closed laboratory critical for calibration) ID # SN: 6295803 SN: 0810278 ID # SE UMS 006 AB 1004	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 <u>Cal Date (Certificate No.)</u> 30-Sep-08 (No: 7673) 30-Sep-08 (No: 7670) <u>Check Date (in house)</u> 06-Jun-08 (in house check) Function Technician	cal units of measurements (SI), ges and are part of the certificate. (± ± 3)*C and humidity < 70%. Scheduled Calibration Sep-09 Sep-09 Scheduled Check In house check: Jun-09 Signature
This calibration certificate cocumer The measurements and the uncert All calibrations have been conducts Calibration Equipment used (M&TE Primary Standards Fluke Process Calibrator Type 702 Keithley Multimeter Type 2001 Secondary Standards Calibrator Box V1.1 Calibrated by: Approvec by:	hts lhe traceability to natio sinties with confidence pro- ed in the closed laboratory critical for calibration) ID # SN: 6295803 SN: 0810278 ID # SE UMS 006 AB 1004 SE UMS 006 AB 1004 Name Eric Hainfeid	nal standards, which realize the physio obability are given on the following page facility: environment temperature (22 <u>Cal Date (Certificate No.)</u> 30-Sep-08 (No: 7673) 30-Sep-08 (No: 7670) <u>Check Date (in house)</u> 06-Jun-08 (in house check) Function Technician R&D Director	cal units of measurements (SI), ges and are part of the certificate. (± ± 3) °C and humidity < 70%. Scheduled Calibration Sep-09 Sep-09 Scheduled Check In house check: Jun-09 Signature



Certificate of "SAM Twin Phantom V4.0/V4.0C" 6

Schmid & Partner Engineering AG

Zeugheusstresse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fex +41 1 245 97 79

Certificate of conformity / First Article Inspection

ltem	SAM Twin Phantom V4.0	
Type No	QD 000 P40 BA	
Series No	TP-1002 and higher	
Manufacturer / Origin	Untersee Composites Hauptstr. 69 CH-8559 Fruthwiten Switzerland	

Tests

The series production process used allows the limitation to test of first articles. Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 8A, Serial No. TP-1006. Certain parameters have been retested using further series units (called samples).

Test	Requirement	Details	Units tested
Shape	Compliance with the geometry according to the CAD model.	IT'IS CAD File (*)	First article, Samples
Material thickness	Compliant with the requirements according to the standards	2mm +/- 0.2mm in specific areas	First article. Samples
Material parameters	Dielectric parameters for required frequencies	. 200 MHz – 3 GHz i Relative permittivity < 5 Loss tangent < 0.05.	Material sample TP 104-5
Material resistivity	The material has been tested to be compatible with the liquids defined in the standards	Liquid type HSL 1800 and others according to the standard.	Pre-series, First article

Standards

- [1] CENELEC EN 50361
 [2] IEEE P1526-200× draft 6.5
- [3] IEC PT 62209 draft 0.9
- The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of (\cdot) [1] and [3].

Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standard [1] and draft standards [2] and [3].

Date	18.11.2001		
Signature / Stamp	Schmid & Partner Engineering AG	For Brutelt	<u></u>
	Zeughsusstrase 63, CH-8004 Zurich Tel. 441 1 245 97 00, F6x 441 1 245 42	79	
		Page	1(1)

Doc No 881 - QD 000 P40 BA - B

1 (1)



7 Application Note System Performance Check

7.1 Purpose of system performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check is performed prior to any usage of the system in order to guarantee reproducible results.

The measurement of the Specific Absorption Rate (SAR) is a complicated task and the result depends on the proper functioning of many components and the correct settings of many parameters. Faulty results due to drift, failures or incorrect parameters might not be recognized, since they often look similar in distribution to the correct ones. The Dosimetric Assessment System DASY4 incorporates a system performance check procedure to test the proper functioning of the system. The system performance check uses normal SAR measurements in a simplified setup (the flat section of the SAM Twin Phantom) with a well characterized source (a matched dipole at a specified distance). This setup was selected to give a high sensitivity to all parameters that might fail or vary over time (e.g., probe, liquid parameters, and software settings) and a low sensitivity to external effects inherent in the system (e.g., positioning uncertainty of the device holder). The system performance check does not replace the calibration of the components. The accuracy of the system performance check is not sufficient for calibration purposes. It is possible to calculate the field quite accurately in this simple setup; however, due to the open field situation some factors (e.g., laboratory reflections) cannot be accounted for. Calibrations in the flat phantom are possible with transfer calibration methods, using either temperature probes or calibrated E-field probes. The system performance check also does not test the system performance for arbitrary field situations encountered during real measurements of mobile phones. These checks are performed at SPEAG by testing the components under various conditions (e.g., spherical isotropy measurements in liquid, linearity measurements, temperature variations, etc.), the results of which are used for an error estimation of the system. The system performance check will indicate situations where the system uncertainty is exceeded due to drift or failure.

7.2 System Performance check procedure

Preparation

The conductivity should be measured before the validation and the measured liquid parameters must be entered in the software. If the measured values differ from targeted values in the dipole document, the liquid composition should be adjusted. If the validation is performed with slightly different (measured) liquid parameters, the expected SAR will also be different. See the application note about SAR sensitivities for an estimate of possible SAR deviations. Note that the liquid parameters are temperature dependent with approximately - 0.5% decrease in permittivity and + 1% increase in conductivity for a temperature decrease of 1° C. The dipole must be placed beneath the flat phantom section of the Generic Twin Phantom with the correct distance holder in place. The distance holder should touch the phantom surface with a light pressure at the reference marking (little hole) and be oriented parallel to the long side of the phantom. Accurate positioning is not necessary, since the system will search for the peak SAR location, except that the dipole arms should be parallel to the surface. The device holder for mobile phones can be left in place but should be rotated away from the dipole. The forward power into the dipole at the dipole SMA connector should be determined as accurately as possible. See section 4 for a description of the recommended setup to measure the dipole input power. The actual dipole input power level can be between 20mW and several watts. The result can later be normalized to any power level. It is strongly recommended to note the actually used power level in the "comment"-window of the measurement file; otherwise you loose this crucial information for later reference.

Test report no.: 1-1954-02-02/10



System Performance Check

The DASY4 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks, so you must save the finished validation under a different name. The validation document requires the Generic Twin Phantom, so this phantom must be properly installed in your system. (You can create your own measurement procedures by opening a new document or editing an existing document file). Before you start the validation, you just have to tell the system with which components (probe, medium, and device) you are performing the validation; the system will take care of all parameters. After the validation, which will take about 20 minutes, the results of each task are displayed in the document window. Selecting all measured tasks and opening the predefined "validation" graphic format displays all necessary information for validation. A description of the different measurement tasks in the predefined document is given below, together with the information that can be deduced from their results:

- The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the amplifier output power. If it is too high (above ± 0.1dB) the validation should be repeated; some amplifiers have very high drift during warm-up. A stable amplifier gives drift results in the DASY4 system below ± 0.02 dB.
- The "surface check" measurement tests the optical surface detection system of the DASY4 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1mm). In that case it is better to abort the validation and stir the liquid. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within ± 30°.) However, varying breaking indices of different liquid compositions might also influence the distance. If the indicated difference varies from the actual setting, the probe parameter "optical surface distance" should be changed in the probe settings (see manual). For more information see the application note about SAR evaluation.
- The "area scan" measures the SAR above the dipole on a parallel plane to the surface. It is used to locate the approximate location of the peak SAR with 2D spline interpolation. The proposed scan uses large grid spacing for faster measurement; due to the symmetric field the peak detection is reliable. If a finer graphic is desired, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result.
- The zoom scan job measures the field in a volume around the peak SAR value assessed in the previous "area" scan (for more information see the application note on SAR evaluation).

If the validation measurements give reasonable results, the peak 1g and 10g spatial SAR values averaged between the two cubes and normalized to 1W dipole input power give the reference data for comparisons. The next section analyzes the expected uncertainties of these values. Section 6 describes some additional checks for further information or troubleshooting.

7.3 Uncertainty Budget

Please note that in the following Tables, the tolerance of the following uncertainty components depends on the actual equipment and setup at the user location and need to be either assessed or verified on-site by the end user of the DASY4 system:

- RF ambient conditions
- Dipole Axis to Liquid Distance
- Input power and SAR drift measurement
- Liquid permittivity measurement uncertainty
- Liquid conductivity measurement uncertainty

Note: All errors are given in percent of SAR, so 0.1 dB corresponds to 2.3%. The field error would be half of that. The liquid parameter assessment give the targeted values from the dipole document. All errors are given in percent of SAR, so 0.1dB corresponds to 2.3%. The field error would be half of that.



System validation

In the table below, the system validation uncertainty with respect to the analytically assessed SAR value of a dipole source as given in the P1528 standard is given. This uncertainty is smaller than the expected uncertainty for mobile phone measurements due to the simplified setup and the symmetric field distribution.

Error Sources	Uncertainty	Probability	Divi-	Ci	Ci	Standard	Standard	V _i ²
	Value	Distribution	sor	1g	10g	Uncertainty	Uncertainty	or
						1g	10g	V _{eff}
Measurement System								
Probe calibration	± 4.8%	Normal	1	1	1	± 4.8%	± 4.8%	8
Axial isotropy	± 4.7%	Rectangular	√3	0.7	0.7	± 1.9%	± 1.9%	8
Hemispherical isotropy	± 0.0%	Rectangular	√3	0.7	0.7	± 0.0%	± 3.9%	∞
Boundary effects	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Probe linearity	± 4.7%	Rectangular	√3	1	1	± 2.7%	± 2.7%	8
System detection limits	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Readout electronics	± 1.0%	Normal	1	1	1	± 1.0%	± 1.0%	8
Response time	± 0.0%	Rectangular	√3	1	1	± 0.0%	± 0.0%	8
Integration time	± 0.0%	Rectangular	√3	1	1	± 0.0%	± 0.0%	8
RF ambient conditions	± 3.0%	Rectangular	√3	1	1	± 1.7%	± 1.7%	8
Probe positioner	± 0.4%	Rectangular	√3	1	1	± 0.2%	± 0.2%	8
Probe positioning	± 2.9%	Rectangular	√3	1	1	± 1.7%	± 1.7%	8
Max. SAR evaluation	± 1.0%	Rectangular	√3	1	1	± 0.6%	± 0.6%	8
Test Sample Related								
Dipole axis to liquid distance	± 2.0%	Normal	1	1	1	± 1.2%	± 1.2%	8
Power drift	± 4.7%	Rectangular	√3	1	1	± 2.7%	± 2.7%	8
Phantom and Set-up								
Phantom uncertainty	± 4.0%	Rectangular	√3	1	1	± 2.3%	± 2.3%	8
Liquid conductivity (target)	± 5.0%	Rectangular	√3	0.64	0.43	± 1.8%	± 1.2%	8
Liquid conductivity (meas.)	± 2.5%	Normal	1	0.64	0.43	± 1.6%	± 1.1%	8
Liquid permittivity (target)	± 5.0%	Rectangular	√3	0.6	0.49	± 1.7%	± 1.4%	8
Liquid permittivity (meas.)	± 2.5%	Normal	1	0.6	0.49	± 1.5%	± 1.2%	8
Combined Uncertainty						± 8.4%	± 8.1%	
Expanded Std.						± 16.8%	± 16.2%	
Uncertainty								



Performance check repeatability

The repeatability check of the validation is insensitive to external effects and gives an indication of the variations in the DASY4 measurement system, provided that the same power reading setup is used for all validations. The repeatability estimate is given in the following table:

Error Sources	Uncertainty Value	Probability Distribution	Divi- sor	c _i 1g	c _i 10g	Standard Uncertainty	Standard Uncertainty 10g	V _i ² Or V _{off}
						.9		·en
Measurement System								
Probe calibration	± 4.8%	Normal	1	1	1	0	0	8
Axial isotropy	± 4.7%	Rectangular	√3	0.7	0.7	0	0	8
Hemispherical isotropy	± 0.0%	Rectangular	√3	0.7	0.7	0	0	∞
Boundary effects	± 1.0%	Rectangular	√3	1	1	0	0	8
Probe linearity	± 4.7%	Rectangular	√3	1	1	0	0	8
System detection limits	± 1.0%	Rectangular	√3	1	1	0	0	8
Readout electronics	± 1.0%	Normal	1	1	1	0	0	8
Response time	± 0.0%	Rectangular	√3	1	1	0	0	8
Integration time	± 0.0%	Rectangular	√3	1	1	0	0	8
RF ambient conditions	± 3.0%	Rectangular	√3	1	1	0	0	8
Probe positioner	± 0.4%	Rectangular	√3	1	1	0	0	8
Probe positioning	± 2.9%	Rectangular	√3	1	1	0	0	8
Max. SAR evaluation	± 1.0%	Rectangular	√3	1	1	0	0	8
Test Sample Related								
Dipole axis to liquid	± 2.0%	Normal	1	1	1	± 1.2%	± 1.2%	8
distance								
Power drift	± 4.7%	Rectangular	√3	1	1	± 2.7%	± 2.7%	∞
Phantom and Set-up								
Phantom uncertainty	± 4.0%	Rectangular	√3	1	1	± 2.3%	± 2.3%	∞
Liquid conductivity (target)	± 5.0%	Rectangular	√3	0.64	0.43	± 1.8%	± 1.2%	∞
Liquid conductivity (meas.)	± 2.5%	Normal	1	0.64	0.43	± 1.6%	± 1.1%	∞
Liquid permittivity (target)	± 5.0%	Rectangular	√3	0.6	0.49	± 1.7%	± 1.4%	∞
Liquid permittivity (meas.)	± 2.5%	Normal	1	0.6	0.49	± 1.5%	± 1.2%	∞
Combined Uncertainty						± 5.3%	± 4.9%	
Expanded Std. Uncertainty						± 10.6%	± 9.7%	

The expected repeatability deviation is low. Excessive drift (e.g., drift in liquid parameters), partial system failures or incorrect parameter settings (e.g., wrong probe or device settings) will lead to unexpectedly high repeatability deviations. The repeatability gives an indication that the system operates within its initial specifications. Excessive drift, system failure and operator errors are easily detected.



7.4 Power set-up for validation

The uncertainty of the dipole input power is a significant contribution to the absolute uncertainty and the expected deviation in interlaboratory comparisons. The values in Section 2 for a typical and a sophisticated setup are just average values. Refer to the manual of the power meter and the detector head for the evaluation of the uncertainty in your system. The uncertainty also depends on the source matching and the general setup. Below follows the description of a recommended setup and procedures to increase the accuracy of the power reading:



The figure shows the recommended setup. The PM1 (incl. Att1) measures the forward power at the location of the validation dipole connector. The signal generator is adjusted for the desired forward power at the dipole connector and the power meter PM2 is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow a setting in 0.01dB steps, the remaining difference at PM2 must be noted and considered in the normalization of the validation results. The requirements for the components are:

- The signal generator and amplifier should be stable (after warm-up). The forward power to the dipole should be above 10mW to avoid the influence of measurement noise. If the signal generator can deliver 15dBm or more, an amplifier is not necessary. Some high power amplifiers should not be operated at a level far below their maximum output power level (e.g. a 100W power amplifier operated at 250mW output can be quite noisy). An attenuator between the signal generator and amplifier is recommended to protect the amplifier input.
- The low pass filter after the amplifier reduces the effect of harmonics and noise from the amplifier. For most amplifiers in normal operation the filter is not necessary.
- The attenuator after the amplifier improves the source matching and the accuracy of the power head. (See power meter manual.) It can also be used also to make the amplifier operate at its optimal output level for noise and stability. In a setup without directional coupler, this attenuator should be at least 10dB.
- The directional coupler (recommended ³ 20dB) is used to monitor the forward power and adjust the signal generator output for constant forward power. A medium quality coupler is sufficient because the loads (dipole and power head) are well matched. (If the setup is used for reflective loads, a high quality coupler with respect to directivity and output matching is necessary to avoid additional errors.)
- The power meter PM2 should have a low drift and a resolution of 0.01dBm, but otherwise its accuracy has no impact on the power setting. Calibration is not required.
- The cable between the coupler and dipole must be of high quality, without large attenuation and phase changes when it is moved. Otherwise, the power meter head PM1 should be brought to the location of the dipole for measuring.
- The power meter PM1 and attenuator Att1 must be high quality components. They should be calibrated, preferably together. The attenuator (³10dB) improves the accuracy of the power reading. (Some higher power heads come with a built-in calibrated attenuator.) The exact attenuation of the attenuator at the frequency used must be known; many attenuators are up to 0.2dB off from the specified value.



- Use the same power level for the power setup with power meter PM1 as for the actual measurement to avoid linearity and range switching errors in the power meter PM2. If the validation is performed at various power levels, do the power setting procedure at each level.
- The dipole must be connected directly to the cable at location "X". If the power meter has a different connector system, use high quality couplers. Preferably, use the couplers at the attenuator Att1 and calibrate the attenuator with the coupler.
- Always remember: We are measuring power, so 1% is equivalent to 0.04dB.

7.5 Laboratory reflection

In near-field situations, the absorption is predominantly caused by induction effects from the magnetic nearfield. The absorption from reflected fields in the laboratory is negligible. On the other hand, the magnetic field around the dipole depends on the currents and therefore on the feed point impedance. The feed point impedance of the dipole is mainly determined from the proximity of the absorbing phantom, but reflections in the laboratory can change the impedance slightly. A 1% increase in the real part of the feed point impedance will produce approximately a 1% decrease in the SAR for the same forward power. The possible influence of laboratory reflections should be investigated during installation. The validation setup is suitable for this check, since the validation is sensitive to laboratory reflections. The same tests can be performed with a mobile phone, but most phones are less sensitive to reflections due to the shorter distance to the phantom. The fastest way to check for reflection effects is to position the probe in the phantom above the feed point and start a continuous field measurement in the DASY4 multi-meter window. Placing absorbers in front of possible reflectors (e.g. on the ground near the dipole or in front of a metallic robot socket) will reveal their influence immediately. A 10dB absorber (e.g. ferrite tiles or flat absorber mats) is probably sufficient, as the influence of the reflections is small anyway. If you place the absorber too near the dipole, the absorber itself will interact with the reactive near-field. Instead of measuring the SAR, it is also possible to monitor the dipole impedance with a network analyzer for reflection effects. The network analyzer must be calibrated at the SMA connector and the electrical delay (two times the forward delay in the dipole document) must be set in the NWA for comparisons with the reflection data in the dipole document. If the absorber has a significant influence on the results, the absorber should be left in place for validation or measurements. The reference data in the dipole document are produced in a low reflection environment.

7.6 Additional system checks

While the validation gives a good check of the DASY4 system components, it does not include all parameters necessary for real phone measurements (e.g. device modulation or device positioning). For system validation (repeatability) or comparisons between laboratories a reference device can be useful. This can be any mobile phone with a stable output power (preferably a device whose output power can be set through the keyboard). For comparisons, the same device should be sent around, since the SAR variations between samples can be large. Several measurement possibilities in the DASY software allow additional tests of the performance of the DASY system and components. These tests can be useful to localize component failures:

- The validation can be performed at different power levels to check the noise level or the correct compensation of the diode compression in the probe.
- If a pulsed signal with high peak power levels is fed to the dipole, the performance of the diode compression compensation can be tested. The correct crest factor parameter in the DASY software must be set (see manual). The system should give the same SAR output for the same averaged input power.
- The probe isotropy can be checked with a 1D-probe rotation scan above the feed point. The automatic probe alignment procedure must be passed through for accurate probe rotation movements (optional DASY4 feature with a robot-mounted light beam unit). Otherwise the probe tip might move on a small circle during rotation, producing some additional isotropy errors in gradient fields.