

Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

SEM/CVVGP, Leif Hedin

Company Internal MARKING DRAWING

1249-8240 Uen

2011-06-14

Rev

1

Reference

ST17i, Mobile Phone label, ROW, made in...

General information 1

Checked

Mobile Phone label part no	• 1241-3099	
Mobile Phone label content part no	• 1249-8239	
Bar code	Print quality: according to COSMETIC GUIDELINE – Bar code labels document 1222-6072 Uen	
	Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!	
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.	
Coordinates	"(x/y)" under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.	

MLCI= Main Label Content Information Document

2 **Printing information**

Content **Format** Line 1a Graphics, height 1,5 mm. Sony Ericsson stylized name. (4,0/2,0)According to 1200-1925 Line 1b Model Name Text, height 1,2 mm. (4,0/20,0)According to Chapter 1 in MLCI "ST17i" Line 2a Product number of the Sales Item in which the (6,2/2,0)phone is packed, if applicable. "SI XXXX-XXXX" Text, height 1,2 mm. Line 2b Location code of where the phone is flashed, if (6,2/20,0) Text, height 1,2 mm. applicable, "XXX" Line 3a Text, height 1,2 mm. "TYPE: AAD-3880121-BV" (8,5/2,0)According to Chapter 1 in MLCI. Line 3b Text, height 1,2 mm. (8,5/20,0) HW & SW identification field, if applicable; According to Type-testing report under Product Model "FFGG" **Specifying Documents** Line 4 Graphics height 7,0mm SIM-card logo (9,0/27,0) according to 1001-6195 Line 5a Text, height 1,2 mm. "FCC ID: PY7A3880121" (11,5/2,0)According to Chapter 1 in MLCI. Line 5b Production week (flash), "yyWww" Text, height 1,2 mm. (11,5/20,0) (yy = year, ww = week) Line 6a Text, height 1,2 mm. "IC: 4170B-A3880121" (14,5/2,0)According to Chapter 1 in MLCI. Repair week, if applicable. Line 6b "RyyWww" Text, height 1,2 mm. (14,5/20,0)(yy = year, ww = week)



Prepared (also subject responsible if other)

SEM/CVVGP, Leif Hedin

SEM/CVVGP, Leif Hedin

Company Internal MARKING DRAWING

Checked

1249-8240 Uen

Reference

2011-06-14 1

Line 7 (18,0/2,0)	Line 7 in bar code, according to line 8a. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 8a (20,0/2,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn" for serial number).	Text, height 1,5 mm. Defined by supplier.
Line 8b (20,0/17,0)	Actual electronic serial number (IMEI) of the mobile phone, "00000000-000000-0"	Text, height 1,5mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 9 (23,0/2,0)	Line 9 in bar code, according to line 8b As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 10a (29,3/2,0)	CE approval symbol, the NB-"0682" and "Alert Symbol" in one artwork	Graphics, height 5 mm. According to 1242-7470
Line 10b (29,3/32,0)	WEEE trashcan without bar symbol	Graphics, min. height 5mm, according to 1202-5537.
Line 11 (32,2/2,0)	Marking of origin; "Made in Xxx" "Xxx" = actual country of production of the included telephone, in English	Text, height 1,2 mm.

Layout 3

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



<u>double underlined</u> = major changes since last revision.